KRINI CRUDE • LUBECON

INDUSTRIAL CHEMICALS • CONSTRUCTION CHEMICALS DIVISION

Nikri 30 Shuttering Oil

Road Project Shuttering Oil. Cost Effective MS, Plywood & Road Projects Shuttering Oil.

KEY FEATURES & BENEFITS

- Easy mold release
- No stains on concrete after demolding
- Used for MS, plywood

APPLICATIONS & USES

- MS (mild steel) formwork
- Plywood formwork
- Road projects

TYPICAL TECHNICAL SPECIFICATIONS

Test Parameter	Typical Value / Result	Test Method / Note
Appearance	Uniform release fluid / grease	Visual
Coverage Rate	20–25 m²/L	Site trial rate
Formwork Compatibility	Mivan aluminium, MS, plywood, FRP	All moulds
Flash Point	> 140 °C	Safety standard
Demoulding Performance	Smooth concrete finish, clean strip	Field tested

APPLICATION & HANDLING GUIDELINES

- Ensure contact surfaces or machines are clean and free of heavy contaminants.
- Apply as supplied without unauthorized dilution or contamination.
- Conduct a preliminary trial under site conditions to calibrate optimum consumption.

Packaging: Standard industrial packaging: 20 L pails, 200 L / 210 L steel drums. • **Storage:** Store in original tightly sealed containers in a cool, dry and well-ventilated area away from direct sunlight. • **Shelf Life:** 12 months from date of manufacture when stored in unopened containers as recommended.

Technical values are typical and represent current production data. Suitability should be confirmed by site trials. For industrial use only.