NIKRI AL

SHUTTERING OIL

Emulsion-based concrete formwork release agent

EASY DEMOULDING | CLEANER FINISH

RECOMMENDED FOR

MIVAN ALUMINIUM

MS • PLYWOOD • FRP

AND COMPATIBLE FORMWORK

PERFORMANCE

NIKRI AL is an emulsion-based shuttering oil that forms a uniform release film between concrete and formwork, supporting cleaner stripping and a smoother concrete finish.

KEY BENEFITS

- Promotes easy demoulding and reduces concrete adhesion.
- Helps minimise pinholes on concrete surfaces.
- Supports smoother, cleaner concrete finishes.
- Recommended for Mivan aluminium, MS, plywood and FRP formwork.

TYPICAL CHARACTERISTICS

PROPERTY	TYPICAL VALUE
Density at 15 °C	0.90 g/ml
Viscosity, B4 cup	100 seconds
Flash point	Not applicable
Appearance	Ivory, non-transparent

Typical values based on MTC batch KN/AL/09, September 2026.
Values are indicative and not a sales specification.

APPLICATION

- **Prepare:** Clean and dry the formwork; remove concrete, dust, rust flakes and excess oil.
- **Mix:** Stir the emulsion thoroughly before use.
- **Apply:** Spray, roll, brush or wipe on a thin, continuous, uniform film.
- **Best result:** Remove pools and runs; use only the minimum quantity required for complete coverage.

STORAGE & SAFETY

Store tightly closed in a cool, dry and well-ventilated place. Protect from freezing and excessive heat. Use suitable gloves and eye protection. Avoid prolonged skin contact and inhalation of mist. Trial application is recommended before full-scale use.