KRINI CRUDE • VIBRANT

INDUSTRIAL CHEMICALS • AEROSOLS DIVISION

Relese Anti-Spatter Spray

RELESE ANTI-SPATTER SPRAY is a premium industrial aerosol welding anti-spatter agent. Specially formulated without silicone, it forms a thin, protective barrier on workpieces, welding nozzles, contact tips, and jigs to prevent welding spatter from adhering. It eliminates laborious post-weld chiselling and grinding, and allows direct subsequent painting, powder coating, or galvanizing without fish-eye defects.

KEY FEATURES & BENEFITS

- Non-flammable carrier formulation with uniform spray mist
- 100% silicone-free for flawless post-weld surface treatment and painting
- Prolongs the service life of expensive welding torch consumables
- Economical 550 ml can size for maximum coverage per aerosol unit
- Ozone friendly with safe, modern propellants

APPLICATIONS & USES

- Anti-Spatter Effect: Prevents hot metal droplets and welding spatter from adhering to steelwork
- Silicone-Free Formulation: Allows direct subsequent painting, galvanizing, or plating without adhesion issues
- Lasts Longer: Enduring heat-resistant film provides lasting protection through extended welding cycles
- Protects Torch & Nozzles: Extends the working life of MIG/MAG contact tips, gas shrouds, and diffusers
- Saves Post-Weld Labor: Eliminates costly manual grinding, chipping, and mechanical surface cleaning

TYPICAL TECHNICAL SPECIFICATIONS

Test Parameter	Typical Value / Result	Test Method / Note
Product Type	Industrial Welding Anti-Spatter Aerosol	—
Net Volume	550 ml	—
Silicone Content	100% Silicone-Free	—
Film Characteristic	Non-greasy, heat-resistant barrier film	—
Post-Weld Finish	Paintable, Powder-Coatable, Galvanizable	—
Welding Types	MIG / MAG, Robotic, Spot & Arc Welding	—

APPLICATION & HANDLING GUIDELINES

- Shake can well before use.
- Spray a light, uniform coat on areas adjacent to the weld seam before beginning welding.
- Spray inside the torch shroud / gas nozzle to prevent spatter buildup.
- Proceed with welding as normal.

Packaging: Standard packing: 550 ml aerosol spray cans (Cartons of 12 / 24 cans) • **Storage:** Store in a cool, dry area below 50 °C away from open flames and direct heat. • **Shelf Life:** 24 months from date of manufacture

Technical values are typical and represent current production data. Suitability should be confirmed by site trials. For industrial use only.