KRINI CRUDE • LUBECON

INDUSTRIAL CHEMICALS • CONSTRUCTION CHEMICALS DIVISION

Repel Shuttering Oil

Premium Shuttering Oil Suitable for Aluminium & All Formworks. Applied to formwork (shuttering) before the concrete is poured, shuttering oil leaves a release film so the formwork strips cleanly without concrete sticking to it, which protects the concrete surface and helps the formwork last for more pours.

KEY FEATURES & BENEFITS

- Premium industrial grade formulation manufactured in Chennai
- Consistent batch-to-batch quality and high thermal stability
- Engineered for optimal operational efficiency and equipment protection

APPLICATIONS & USES

- Industrial manufacturing and engineering applications
- Heavy-duty machinery, tooling and fabrication environments
- Compatible with standard industrial metal and construction surfaces

TYPICAL TECHNICAL SPECIFICATIONS

Test Parameter	Typical Value / Result	Test Method / Note
Appearance	Uniform release fluid / grease	Visual
Coverage Rate	30–40 m²/L	Site trial rate
Formwork Compatibility	Mivan aluminium, MS, plywood, FRP	All moulds
Flash Point	> 140 °C	Safety standard
Demoulding Performance	Smooth concrete finish, clean strip	Field tested

APPLICATION & HANDLING GUIDELINES

- Ensure contact surfaces or machines are clean and free of heavy contaminants.
- Apply as supplied without unauthorized dilution or contamination.
- Conduct a preliminary trial under site conditions to calibrate optimum consumption.

Packaging: Standard industrial packaging: 20 L pails, 200 L / 210 L steel drums. • **Storage:** Store in original tightly sealed containers in a cool, dry and well-ventilated area away from direct sunlight. • **Shelf Life:** 12 months from date of manufacture when stored in unopened containers as recommended.

Technical values are typical and represent current production data. Suitability should be confirmed by site trials. For industrial use only.