KRINI CRUDE • 1-COOL

INDUSTRIAL CHEMICALS • LUBRICANTS DIVISION

Rust Preventive Oil

Rust preventive oils leave a protective film on metal parts between operations, in storage and in transit. Dewatering types first displace water from freshly washed or machined parts.

KEY FEATURES & BENEFITS

- Available in: Dewatering RP oil, Oil based RP oil

APPLICATIONS & USES

- Protecting machined components between operations
- Storage and shipment of steel parts
- Parts that come out of washing or water-based coolant

TYPICAL TECHNICAL SPECIFICATIONS

Test Parameter	Typical Value / Result	Test Method / Note
Appearance	Clear amber / yellow fluid	Visual
Kinematic Viscosity @ 40°C	Typical: 32 - 68 cSt	ASTM D445
Density @ 29.5°C	0.850 - 0.890 g/cm³	ASTM D1298
Flash Point (COC)	> 200 °C	ASTM D92
Copper Strip Corrosion	1a (Passes)	ASTM D130

APPLICATION & HANDLING GUIDELINES

- Ensure contact surfaces or machines are clean and free of heavy contaminants.
- Apply as supplied without unauthorized dilution or contamination.
- Conduct a preliminary trial under site conditions to calibrate optimum consumption.

Packaging: Standard industrial packaging (pails, drums, barrels) • **Storage:** Store in original tightly closed container in a cool, dry place. • **Shelf Life:** 12 months from date of manufacture when stored properly.

Technical values are typical and represent current production data. Suitability should be confirmed by site trials. For industrial use only.