KRINI CRUDE

SPECIALITY CONSTRUCTION CHEMICALS

SILEASE 360

PRECAST SHUTTERING OIL / MOULD RELEASE AGENT

SILEASE 360 is a ready-to-use mould release oil developed for precast concrete production. It forms a uniform release film on the formwork, supports clean demoulding and helps reduce surface pinholes and honeycombing when applied correctly.

AVERAGE COVERAGE

40 m²/L

Actual coverage may vary with formwork porosity, surface condition and application method.

KEY BENEFITS

- Helps minimise pinholes and improves the appearance of precast concrete surfaces
- Provides clean and easy demoulding with reduced concrete adhesion to formwork
- Promotes a uniform surface finish without adversely affecting concrete colour
- Suitable for vertical and horizontal precast moulding applications
- Ready to use and economical due to high spreading coverage

TYPICAL PROPERTIES

Appearance	Milky / Ivory Emulsion
Viscosity, B4 cup	Typical: 100 seconds (specification: 30-200 seconds)
Density at 15°C	Approx. 0.90 g/mL (specification: >0.866 g/mL)
Suitable formwork	Mild steel, plywood and FRP
Coverage	Average 40 m²/L

APPLICATION METHOD

- Clean the formwork and remove concrete residue, rust, dust, water and excess oil.
- Apply a very thin, uniform film by fine spray, lint-free cloth, roller or suitable applicator.
- Avoid puddles and over-application; wipe off excess oil before placing reinforcement or concrete.
- For new or highly absorbent plywood, conduct a small site trial and adjust the application rate.

STORAGE, HANDLING & PACKING

Store in the original closed container in a cool, dry, well-ventilated area away from heat and direct sunlight.
Use appropriate gloves and eye protection. Avoid prolonged skin contact. Refer to the Safety Data Sheet before use.
Shelf life: 6 months from date of manufacture when stored as recommended. Standard packing: 200 L barrel.

Typical values are not guaranteed specifications. Suitability and coverage should be confirmed by a site trial under actual conditions.