Conplast WL Xtra

FOSROC

constructive solutions

IS:2645

Integral waterproofing liquid admixture for concrete, plaster and mortars

Uses

To minimise permeability and increase the waterproofing properties of concrete, plaster and cement sand mortars for critical applications like roof slabs,screeds, basements, external plastering, bathroom floors, water tanks, sumps, drains etc.

Feature and Benefits:

- **Advanced Technology** : New generation molecule yields high performance concrete. Suitable for any grade of concrete including higher grades.
- **High Strength :** Due to better dispersion of cement particles and helps in the better degree of hydration yielding high strength compared to control.
- **Cohesive Mix** : Improves workablity and cohesiveness of the concrete.
- **Durability** : Improves durability due to reduction in permeability of concrete and corrosion resistance of steel
- Compatible with all types of sand.

Standards compliance

Conplast WL Xtra conforms to IS:2645-2003.

Description

Conplast WL Xtra is a light coloured liquid based on cement dispersion polymers which mixes readily with water and therefore disperses evenly.

Conplast WL Xtra waterproofs by reducing the permeability in the concrete, mortar. It reduces the water demand for required workability and minimises segregation and bleeding. Thus it is more efficient compared to traditional powder and conventional integral waterproofing compounds.

Technical support

Fosroc provides a technical advisory service for onsite assistance and advice on admixture selection, evaluation trials and dispensing equipment. Technical data and guidance can be provided for admixtures and other products for use with fresh and hardened concrete.

Properties

Chloride content	As per IS:2645-2003.
Compatibility	Can be used with all types of cements, including pozzolanic slag but not HighAlumina Cement.
Permeability to water	Confirms to IS 2645
Setting Time	No significant effect on setting time of concrete or mortar.
Compressive Strength	Maintains compressive strength equal to control concrete or mortar and can even improve on strength property if full advantage of water reduction potential is utilised.
Workability	Improves workability at reduced water cement ratio

Application Instructions

- Add cement & aggregates to concrete mixer as per the mix design, mix in dry state for 1 minutes.
- Start addition of 75–80% mixing water & mix for 2-3 minutes.
- Fosroc Conplast WL Xtra is added as per the recommended dosage into the remaining mixing / gauging water, then add to concrete mixer & mix for another 2 minutes.
- Place the concrete or apply plaster, as needed.
- Cure the applied mortar or concrete as per good construction practices or use Fosroc Concure curing compounds.

Dosage : The Optimum dosage is 200ml for 50kg of cement..

Site trials shall be carried out to validate the optimum dosage.

Note: Mix using Conplast WL Xtra will require much less water than normal mix for the same workability. Water reduction may be as much as 10% or more. If the moisture content of the sand or aggregate changes i.e., it becomes wetter or dryer, then the amount of water used must be reduced or increased to give the original workability.

Conplast WL Xtra

DO's and DOnt's :

- Do not add Fosroc Conplast WL Xtra directly to dry cement & aggregate mix.
- Maintain water-cement ratio as low as possible.
- Do not increase the dosage of Conplast WL Xtra than the recommendation.

Estimating

Packaging

Conplast WL Xtra is supplied in 200ml, 1, 5, 10, 20, 50, and 200 litre containers.

Storage

Conplast WL Xtra has a minimum shelf life of 24 months, if kept in a dry store in unopened containers,temperature below 50°C.

Precautions

Health and safety instructions

Conplast WL Xtra is non-toxic. Any splashes on skin should be washed well with water. If contact with eyes occurs, it shall be washed well with plenty of water and medical advice sought immediately.

Fire

Conplast WL Xtra is non-flammable.

Additional information

FOSguard is registered brand owned by FOSROC for building care products. With our commitment to our valued customers for providing a complete solutions for the buildings we have host of products including waterproofing, repairs, grouts, anchors protective coatings , sealants , mould release agents and curing compounds.

Separate datasheets are available on these products.

Fosroc Chemicals (India) Pvt. Ltd.
Head Office
Embassy Point, No. 150,
2nd Floor, Infantry Road,
Bangalore 560 001,
Karnataka

Important note :
Fosroc products are guaranteed against defective materials and manufacture and are sold subject to its standard terms and conditions of sale, copies of which may be obtained on request. Whilst Fosroc endeavours to ensure that any advice, recommendation, specification or information it may give is accurate and correct, it cannot, because it has no direct or continuous control over where or how its products are applied, accept any liability either directly or indirectly arising from the use of its products whether or not in accordance with any advice, specification, recommendation or information given by it.

telephone	fax	e-mail
+91 80-42521900	+91 80-22281510	enquiry.india@fosroc.com

Regional Offices

Chennai
Hills Centre,Old No 5,
New No 9, 3rd Cross Street,
Jeth Nagar, Raja Annamalaipuram,
Chennai 600 028.
Ph: 9500064795

Mumbai
MBC Park, 12th floor, Office No.12B,
'D' Block, Near G Corp/Hyper City
Kasarwadawali, Ghodbunder Road,
Thane (West) 400 615
Ph: +91 22 6229 6800

Noida
Unit No. 601, Highway Tower-II
A-13/2, 6th Floor, Sector– 62
Gautam Buddha Nagar,
Noida 201 309, Uttar Pradesh
Ph: +91 120 6121900
Fax: 0120-4270622

Kolkata
Shrachi Tower,Wing A,3rd
floor, Anandapur Em Bypass
Anandapur, Kolkata
West Bengal 700 107
Ph:+91 33-65343188
Fax: 033-24990278

www.fosroc.com

INDIA/2025/0156/A