

[MS-WCFESAN]:

WCF-Based Encrypted Server Administration and Notification Protocol

Intellectual Property Rights Notice for Open Specifications Documentation

- **Technical Documentation.** Microsoft publishes Open Specifications documentation ("this documentation") for protocols, file formats, data portability, computer languages, and standards support. Additionally, overview documents cover inter-protocol relationships and interactions.
- **Copyrights.** This documentation is covered by Microsoft copyrights. Regardless of any other terms that are contained in the terms of use for the Microsoft website that hosts this documentation, you can make copies of it in order to develop implementations of the technologies that are described in this documentation and can distribute portions of it in your implementations that use these technologies or in your documentation as necessary to properly document the implementation. You can also distribute in your implementation, with or without modification, any schemas, IDLs, or code samples that are included in the documentation. This permission also applies to any documents that are referenced in the Open Specifications documentation.
- **No Trade Secrets.** Microsoft does not claim any trade secret rights in this documentation.
- **Patents.** Microsoft has patents that might cover your implementations of the technologies described in the Open Specifications documentation. Neither this notice nor Microsoft's delivery of this documentation grants any licenses under those patents or any other Microsoft patents. However, a given Open Specifications document might be covered by the Microsoft [Open Specifications Promise](#) or the [Microsoft Community Promise](#). If you would prefer a written license, or if the technologies described in this documentation are not covered by the Open Specifications Promise or Community Promise, as applicable, patent licenses are available by contacting iplg@microsoft.com.
- **License Programs.** To see all of the protocols in scope under a specific license program and the associated patents, visit the [Patent Map](#).
- **Trademarks.** The names of companies and products contained in this documentation might be covered by trademarks or similar intellectual property rights. This notice does not grant any licenses under those rights. For a list of Microsoft trademarks, visit www.microsoft.com/trademarks.
- **Fictitious Names.** The example companies, organizations, products, domain names, email addresses, logos, people, places, and events that are depicted in this documentation are fictitious. No association with any real company, organization, product, domain name, email address, logo, person, place, or event is intended or should be inferred.

Reservation of Rights. All other rights are reserved, and this notice does not grant any rights other than as specifically described above, whether by implication, estoppel, or otherwise.

Tools. The Open Specifications documentation does not require the use of Microsoft programming tools or programming environments in order for you to develop an implementation. If you have access to Microsoft programming tools and environments, you are free to take advantage of them. Certain Open Specifications documents are intended for use in conjunction with publicly available standards specifications and network programming art and, as such, assume that the reader either is familiar with the aforementioned material or has immediate access to it.

Support. For questions and support, please contact dochelp@microsoft.com.

Revision Summary

Date	Revision History	Revision Class	Comments
7/12/2012	1.0	New	Released new document.
10/25/2012	2.0	Major	Significantly changed the technical content.
1/31/2013	3.0	Major	Significantly changed the technical content.
8/8/2013	4.0	Major	Significantly changed the technical content.
11/14/2013	5.0	Major	Significantly changed the technical content.
2/13/2014	5.0	None	No change to the meaning, language, or formatting of the technical content.
5/15/2014	5.0	None	No change to the meaning, language, or formatting of the technical content.
6/30/2015	6.0	Major	Significantly changed the technical content.
10/16/2015	6.0	None	No changes to the meaning, language, or formatting of the technical content.
7/14/2016	7.0	Major	Significantly changed the technical content.
6/1/2017	8.0	Major	Significantly changed the technical content.
9/15/2017	9.0	Major	Significantly changed the technical content.
12/1/2017	9.0	None	No changes to the meaning, language, or formatting of the technical content.
9/12/2018	10.0	Major	Significantly changed the technical content.
4/7/2021	11.0	Major	Significantly changed the technical content.

Table of Contents

1 Introduction	30
1.1 Glossary	30
1.2 References	31
1.2.1 Normative References	31
1.2.2 Informative References	32
1.3 Overview	32
1.4 Relationship to Other Protocols	33
1.5 Prerequisites/Preconditions	33
1.6 Applicability Statement	33
1.7 Versioning and Capability Negotiation	33
1.8 Vendor-Extensible Fields	34
1.9 Standards Assignments.....	34
2 Messages.....	35
2.1 Transport	35
2.2 Message Syntax	35
2.2.1 Namespaces	35
2.2.2 Messages.....	36
2.2.2.1 Common SOAP Fault	36
2.2.2.2 Keepalive.....	36
2.2.3 Elements	36
2.2.4 Complex Types.....	37
2.2.4.1 Client File Backup Provider	39
2.2.4.1.1 ClientFileBackupException	39
2.2.4.1.2 ConfigurationSet	39
2.2.4.2 Client Backup Provider.....	40
2.2.4.2.1 AutoExclusionSizesInfo	40
2.2.4.2.2 PCBackupClientFault	40
2.2.4.2.3 PCBackupConfiguration	41
2.2.4.2.4 PCBackupServerFault	41
2.2.4.2.5 PCBackupStatus	42
2.2.4.2.6 BadFileInfo	42
2.2.4.2.7 ClientConfig	43
2.2.4.2.8 ClientConfigurationInfo	43
2.2.4.2.9 ClientJobInfo	44
2.2.4.2.10 ClientRepairStatus	44
2.2.4.2.11 ClientVolumeInfo	45
2.2.4.2.12 ConfigureBackupFault	46
2.2.4.2.13 ExcludedFolderInfo	46
2.2.4.2.14 FolderInfo.....	46
2.2.4.2.15 FolderInfoGroup	47
2.2.4.2.16 FolderRequest.....	47
2.2.4.2.17 OperationStatusResponse.....	47
2.2.4.2.18 ServiceStatusResponse	48
2.2.4.2.19 VolumeJobInfo	48
2.2.4.2.20 WaitingOperation	49
2.2.4.2.21 RepairResult	50
2.2.4.3 Health Provider.....	50
2.2.4.3.1 AlertListChunk	50
2.2.4.3.2 AlertInfo.....	50
2.2.4.3.3 UserContextTask	52
2.2.4.3.4 ClearCommand	52
2.2.4.3.5 RaiseCommand	52
2.2.4.3.6 SuppressCommand.....	52
2.2.4.3.7 PlugInInfo	53

2.2.4.4	Machine Identity Provider.....	53
2.2.4.4.1	ReturnClass Type	53
2.2.4.4.2	GetMachineStatusType.....	54
2.2.4.5	User Identity Provider.....	54
2.2.4.5.1	PersonalInfo	54
2.2.4.5.2	UserInfo	54
2.2.4.5.3	UserFault.....	55
2.2.4.5.4	UserExceptionFault	55
2.2.4.5.5	ReturnClass	56
2.2.4.6	Provider Registry Service	56
2.2.4.6.1	ProviderEndpointBehaviorAttribute	56
2.2.4.6.2	ProviderInfo.....	56
2.2.4.6.3	RequiredImpersonationLevelAttribute	57
2.2.4.6.4	QuerySpecification.....	57
2.2.4.7	Addin Management	57
2.2.4.7.1	PackageInfo.....	57
2.2.4.7.2	ClientInstallFilter	58
2.2.4.7.3	Package	59
2.2.4.7.4	BinaryReference	60
2.2.4.7.5	Filter.....	60
2.2.4.7.6	OtherBinariesMap	60
2.2.4.7.7	Preinstall	61
2.2.4.7.8	UninstallConfirm.....	61
2.2.4.8	Network Service	61
2.2.4.8.1	VPNSetting	61
2.2.4.8.2	VirtualNetworkSettings.....	62
2.2.4.8.3	AddressPrefix.....	62
2.2.4.8.4	IPAddress.....	63
2.2.4.9	Domain Infrastructure Service	63
2.2.4.9.1	DomainProviderCredentials	63
2.2.4.9.2	DomainManagerFault	63
2.2.4.9.3	DnsRecord	64
2.2.4.9.4	SrvRecord	64
2.2.4.9.5	ARecord	64
2.2.4.9.6	MXRecord	65
2.2.4.9.7	TxtRecord.....	65
2.2.4.9.8	CNameRecord	65
2.2.4.9.9	DomainState.....	66
2.2.4.9.10	CertificateState	66
2.2.4.9.11	DomainNameConfiguration	66
2.2.4.9.12	Offering.....	67
2.2.4.9.13	DynamicDNSInfo	68
2.2.4.9.14	DomainProviderManagerSettings	68
2.2.4.10	Office 365 Integration Service	69
2.2.4.10.1	O365ConfigurationException	69
2.2.4.11	Client Notification Service	69
2.2.4.11.1	NotificationResult	69
2.2.4.11.2	NotificationResults.....	69
2.2.4.11.3	Exception	69
2.2.5	Simple Types	70
2.2.5.1	Client File Backup Provider	72
2.2.5.1.1	SourceLibrary	72
2.2.5.1.2	ManagedStatus	72
2.2.5.2	Client Backup Provider.....	73
2.2.5.2.1	AbortReason	73
2.2.5.2.2	PCBackupClientFaultReason	74
2.2.5.2.3	PCBackupProviderState	74
2.2.5.2.4	PCBackupStatusOperation	75

2.2.5.2.5	PCBackupVolumePhase	75
2.2.5.2.6	CleanupStatus.....	76
2.2.5.2.7	PCClientDataStatus.....	76
2.2.5.2.8	ClientHealth.....	77
2.2.5.2.9	ClientJobStatus	77
2.2.5.2.10	ConfigureBackupFaultReason	78
2.2.5.2.11	DatabaseState	78
2.2.5.2.12	ExclusionReason.....	79
2.2.5.2.13	FailureReason	79
2.2.5.2.14	MountPhase	80
2.2.5.2.15	PCBackupRepairState.....	81
2.2.5.2.16	RetentionState	81
2.2.5.2.17	StopReason	82
2.2.5.2.18	VolumeJobStatus.....	82
2.2.5.2.19	VolumeLocation.....	83
2.2.5.2.20	VolumeStatus	83
2.2.5.2.21	PCBackupServerFaultReason.....	84
2.2.5.3	Health Provider.....	84
2.2.5.3.1	TaskType.....	84
2.2.5.3.2	HealthStatus.....	85
2.2.5.3.3	StreamBody.....	85
2.2.5.4	Machine Identity Provider.....	85
2.2.5.4.1	ErrorCatalogType	85
2.2.5.4.2	MachineStatus	86
2.2.5.5	User Identity Provider.....	87
2.2.5.5.1	WSSServerGroupType.....	87
2.2.5.5.2	UserCustomExceptionCode	87
2.2.5.5.3	RemoteAccessType	88
2.2.5.5.4	AccessLevelType	88
2.2.5.5.5	UserStatus	89
2.2.5.6	Provider Registry Service	89
2.2.5.6.1	CredentialType.....	89
2.2.5.6.2	ConnectionSetting	90
2.2.5.6.3	ImpersonationLevel	90
2.2.5.7	Addin Management	91
2.2.5.7.1	UpdateClassification.....	91
2.2.5.7.2	OSEditions.....	91
2.2.5.7.3	AddInError	92
2.2.5.8	Network Service	93
2.2.5.8.1	AddressFamily.....	93
2.2.5.9	Domain Infrastructure Service	98
2.2.5.9.1	FailureReason	98
2.2.5.9.2	DomainStatus	99
2.2.5.9.3	CertificateStatus.....	100
2.2.5.9.4	DomainType	101
2.2.5.9.5	DomainProviderEnvironment.....	101
2.2.5.10	AzureAD and HostedEmail Integration Service	102
2.2.5.10.1	PasswordChangeType	102
2.2.5.10.2	PasswordChangeStatus	102
3	Protocol Details.....	104
3.1	Client File Backup Provider Service Contract Details	104
3.1.1	Abstract Data Model.....	104
3.1.2	Timers	104
3.1.3	Initialization.....	104
3.1.4	Higher-Layer Triggered Events	104
3.1.5	Message Processing Events and Sequencing Rules	104
3.1.5.1	IUserConfigProvider.GetUserSettingAsync	104

3.1.5.1.1	Messages	104
3.1.5.1.1.1	IUserConfigProvider_GetUserSettingAsync_InputMessage	104
3.1.5.1.2	Elements	105
3.1.5.1.2.1	GetUserSettingAsync	105
3.1.5.2	IUserConfigProvider.GetClientManagedSettingAsync	105
3.1.5.2.1	Messages	105
3.1.5.2.1.1	IUserConfigProvider_GetClientManagedSettingAsync_InputMessage	105
3.1.5.2.2	Elements	106
3.1.5.2.2.1	GetClientManagedSettingAsync	106
3.1.5.3	IUserConfigProviderCallback.GetUserSettingCompleted	106
3.1.5.3.1	Messages	106
3.1.5.3.1.1	IUserConfigProvider_GetUserSettingCompleted_OutputCallbackMessage	106
3.1.5.3.2	Elements	106
3.1.5.3.2.1	GetUserSettingCompleted	106
3.1.5.4	IUserConfigProvider.GetClientManagedCompleted	107
3.1.5.4.1	Messages	107
3.1.5.4.1.1	IUserConfigProvider_GetClientManagedCompleted_OutputCallbackMess age	107
3.1.5.4.2	Elements	107
3.1.5.4.2.1	GetClientManagedCompleted	107
3.1.5.5	GetUserManagedSettingAsync	108
3.1.5.5.1	Messages	108
3.1.5.5.1.1	IUserConfigProvider_GetUserManagedSettingAsync_InputMessage	108
3.1.5.5.2	Elements	108
3.1.5.5.2.1	GetUserManagedSettingAsync	108
3.1.6	Timer Events	109
3.1.7	Other Local Events	109
3.2	Client Backup Provider Service Contract Details	109
3.2.1	Abstract Data Model	109
3.2.1.1	Backup Server	109
3.2.1.1.1	List of Backup Client Configurations	109
3.2.1.1.2	List of Backup Status	109
3.2.1.1.3	List of Backup Volume Configurations for Each Client	109
3.2.1.1.4	List of Backup Jobs	110
3.2.1.1.5	Backup Window and Retention Policy	110
3.2.1.1.6	Retention Policy	110
3.2.1.2	Backup Client	110
3.2.2	Timers	110
3.2.3	Initialization	110
3.2.4	Higher-Layer Triggered Events	110
3.2.5	Message Processing Events and Sequencing Rules	110
3.2.5.1	IPCBACKUPSERVERREGISTER.RegisterBackupClient	112
3.2.5.1.1	Messages	113
3.2.5.1.1.1	IPCBACKUPSERVERREGISTER_RegisterBackupClient_InputMessage	113
3.2.5.1.1.2	IPCBACKUPSERVERREGISTER_RegisterBackupClient_OutputMessage	113
3.2.5.1.2	Elements	113
3.2.5.1.2.1	RegisterBackupClient	113
3.2.5.1.2.2	RegisterBackupClientResponse	114
3.2.5.2	IPCBACKUPSERVERREGISTER.KeepAlive	114
3.2.5.2.1	Messages	114
3.2.5.2.1.1	IPCBACKUPSERVERREGISTER_KeepAlive_InputMessage	114
3.2.5.2.1.2	IPCBACKUPSERVERREGISTER_KeepAlive_OutputMessage	115
3.2.5.2.2	Elements	115
3.2.5.2.2.1	KeepAlive	115
3.2.5.2.2.2	KeepAliveResponse	115
3.2.5.3	IPCBACKUPSERVERREGISTER.VolumeCalculatorProgress	115

3.2.5.3.1	Messages	115
3.2.5.3.1.1	IPCBACKUPSERVERREGISTER_VOLUMECALCULATORPROGRESS_InputMessage	115
3.2.5.3.2	Elements	116
3.2.5.3.2.1	VolumeCalculatorProgress.....	116
3.2.5.4	IPCBACKUPSERVERREGISTER.GetClientPriority	116
3.2.5.4.1	Messages	117
3.2.5.4.1.1	IPCBACKUPSERVERREGISTER_GetClientPriority_OutputCallbackMessage	117
3.2.5.4.1.2	IPCBACKUPSERVERREGISTER_GetClientPriority_InputCallbackMessage	117
3.2.5.4.2	Elements	117
3.2.5.4.2.1	GetClientPriority	117
3.2.5.4.2.2	GetClientPriorityResponse	117
3.2.5.5	IPCBACKUPSERVERREGISTER.OnBatteryPower	118
3.2.5.5.1	Messages	118
3.2.5.5.1.1	IPCBACKUPSERVERREGISTER_OnBatteryPower_OutputCallbackMessage	118
3.2.5.5.1.2	IPCBACKUPSERVERREGISTER_OnBatteryPower_InputCallbackMessage	118
3.2.5.5.2	Elements	119
3.2.5.5.2.1	OnBatteryPower.....	119
3.2.5.5.2.2	OnBatteryPowerResponse	119
3.2.5.6	IPCBACKUPSERVERREGISTER.StartBackup.....	119
3.2.5.6.1	Messages	119
3.2.5.6.1.1	IPCBACKUPSERVERREGISTER_StartBackup_OutputCallbackMessage	120
3.2.5.6.1.2	IPCBACKUPSERVERREGISTER_StartBackup_InputCallbackMessage	120
3.2.5.6.2	Elements	120
3.2.5.6.2.1	StartBackup	120
3.2.5.6.2.2	StartBackupResponse	120
3.2.5.7	IPCBACKUPSERVERREGISTER.CancelBackup	121
3.2.5.7.1	Messages	121
3.2.5.7.1.1	IPCBACKUPSERVERREGISTER_CancelBackup_OutputCallbackMessage	121
3.2.5.7.1.2	IPCBACKUPSERVERREGISTER_CancelBackup_InputCallbackMessage	121
3.2.5.7.2	Elements	122
3.2.5.7.2.1	CancelBackup	122
3.2.5.7.2.2	CancelBackupResponse	122
3.2.5.8	IPCBACKUPSERVERREGISTER.UpdateBackupConfiguration	122
3.2.5.8.1	Messages	122
3.2.5.8.1.1	IPCBACKUPSERVERREGISTER_UpdateBackupConfiguration_OutputCallback Message	122
3.2.5.8.2	Elements	123
3.2.5.8.2.1	UpdateBackupConfiguration	123
3.2.5.9	IPCBACKUPSERVERREGISTER.SendBackupProgress	123
3.2.5.9.1	Messages	123
3.2.5.9.1.1	IPCBACKUPSERVERREGISTER_SendBackupProgress_OutputCallbackMessag e	123
3.2.5.9.2	Elements	124
3.2.5.9.2.1	SendBackupProgress	124
3.2.5.10	IPCBACKUPSERVERREGISTER.GetFolderChildren.....	124
3.2.5.10.1	Messages	124
3.2.5.10.1.1	IPCBACKUPSERVERREGISTER_GetFolderChildren_OutputCallbackMessage	124
3.2.5.10.1.2	IPCBACKUPSERVERREGISTER_GetFolderChildren_InputCallbackMessage	125
3.2.5.10.2	Elements	125
3.2.5.10.2.1	GetFolderChildren	125
3.2.5.10.2.2	GetFolderChildrenResponse	125
3.2.5.11	IPCBACKUPSERVERREGISTER.CalculateVolumeAsync	126
3.2.5.11.1	Messages	126

3.2.5.11.1.1	IPCBBackupServerRegister_CalculateVolumeAsync_OutputCallbackMessage.....	126
3.2.5.11.1.2	IPCBBackupServerRegister_CalculateVolumeAsync_InputCallbackMessage	126
3.2.5.11.2	Elements.....	127
3.2.5.11.2.1	CalculateVolumeAsync.....	127
3.2.5.11.2.2	CalculateVolumeAsyncResponse	127
3.2.5.12	IPCBBackupServerRegister.CleanFolderSizeCalculation	127
3.2.5.12.1	Messages	128
3.2.5.12.1.1	IPCBBackupServerRegister_CleanFolderSizeCalculation_OutputCallbackMessage	128
3.2.5.12.2	Elements.....	128
3.2.5.12.2.1	CleanFolderSizeCalculation.....	128
3.2.5.13	IPCBBackupServerRegister.GetConnectedVolumes	128
3.2.5.13.1	Messages	128
3.2.5.13.1.1	IPCBBackupServerRegister_GetConnectedVolumes_OutputCallbackMessage.....	129
3.2.5.13.1.2	IPCBBackupServerRegister_GetConnectedVolumes_InputCallbackMessage	129
3.2.5.13.2	Elements.....	129
3.2.5.13.2.1	GetConnectedVolumes.....	129
3.2.5.13.2.2	GetConnectedVolumesResponse	129
3.2.5.14	IPCBBackupClientManagement.RescanVolumesAsync	130
3.2.5.14.1	Messages	130
3.2.5.14.1.1	IPCBBackupServerRegister_RescanVolumesAsync_OutputCallbackMessage	130
3.2.5.14.2	Elements.....	130
3.2.5.14.2.1	RescanVolumesAsync	130
3.2.5.15	IPCBBackupServerProvider.Register	131
3.2.5.15.1	Messages	131
3.2.5.15.1.1	IPCBBackupServerProvider_Register_InputMessage	131
3.2.5.15.1.2	IPCBBackupServerProvider_Register_OutputMessage	131
3.2.5.15.2	Elements.....	131
3.2.5.15.2.1	Register.....	132
3.2.5.15.2.2	RegisterResponse	132
3.2.5.16	IPCBBackupServerProvider.GetClients	132
3.2.5.16.1	Messages	132
3.2.5.16.1.1	IPCBBackupServerProvider_GetClients_InputMessage	132
3.2.5.16.1.2	IPCBBackupServerProvider_GetClients_OutputMessage	133
3.2.5.16.2	Elements.....	133
3.2.5.16.2.1	GetClients	133
3.2.5.16.2.2	GetClientsResponse.....	133
3.2.5.17	IPCBBackupServerProvider.GetClient.....	133
3.2.5.17.1	Messages	134
3.2.5.17.1.1	IPCBBackupServerProvider_GetClient_InputMessage	134
3.2.5.17.1.2	IPCBBackupServerProvider_GetClient_OutputMessage.....	134
3.2.5.17.2	Elements.....	134
3.2.5.17.2.1	GetClient	134
3.2.5.17.2.2	GetClientResponse	135
3.2.5.18	IPCBBackupServerProvider.GetClientJobs.....	135
3.2.5.18.1	Messages	135
3.2.5.18.1.1	IPCBBackupServerProvider_GetClientJobs_InputMessage.....	135

3.2.5.18.1.2	IPCBACKUPSERVERPROVIDER_GetClientJobs_OutputMessage	136
3.2.5.18.2	Elements	136
3.2.5.18.2.1	GetClientJobs	136
3.2.5.18.2.2	GetClientJobsResponse	136
3.2.5.19	IPCBACKUPSERVERPROVIDER.GetVolumeJobs	137
3.2.5.19.1	Messages	137
3.2.5.19.1.1	IPCBACKUPSERVERPROVIDER_GetVolumeJobs_InputMessage	137
3.2.5.19.1.2	IPCBACKUPSERVERPROVIDER_GetVolumeJobs_OutputMessage	137
3.2.5.19.2	Elements	138
3.2.5.19.2.1	GetVolumeJobs	138
3.2.5.19.2.2	GetVolumeJobsResponse	138
3.2.5.20	IPCBACKUPSERVERPROVIDER.GetClientVolumes	138
3.2.5.20.1	Messages	139
3.2.5.20.1.1	IPCBACKUPSERVERPROVIDER_GetClientVolumes_InputMessage	139
3.2.5.20.1.2	IPCBACKUPSERVERPROVIDER_GetClientVolumes_OutputMessage	139
3.2.5.20.2	Elements	139
3.2.5.20.2.1	GetClientVolumes	139
3.2.5.20.2.2	GetClientVolumesResponse	140
3.2.5.21	IPCBACKUPSERVERPROVIDER.SetClientJobDescription	140
3.2.5.21.1	Messages	140
3.2.5.21.1.1	IPCBACKUPSERVERPROVIDER_SetClientJobDescription_InputMessage	140
3.2.5.21.1.2	IPCBACKUPSERVERPROVIDER_SetClientJobDescription_OutputMessage	141
3.2.5.21.2	Elements	141
3.2.5.21.2.1	SetClientJobDescription	141
3.2.5.21.2.2	SetClientJobDescriptionResponse	141
3.2.5.22	IPCBACKUPSERVERPROVIDER.SetClientJobRetentionState	142
3.2.5.22.1	Messages	142
3.2.5.22.1.1	IPCBACKUPSERVERPROVIDER_SetClientJobRetentionState_InputMessage	142
3.2.5.22.1.2	IPCBACKUPSERVERPROVIDER_SetClientJobRetentionState_OutputMessage	142
3.2.5.22.2	Elements	143
3.2.5.22.2.1	SetClientJobRetentionState	143
3.2.5.22.2.2	SetClientJobRetentionStateResponse	143
3.2.5.23	IPCBACKUPSERVERPROVIDER.SetClientVolumeStatus	143
3.2.5.23.1	Messages	144
3.2.5.23.1.1	IPCBACKUPSERVERPROVIDER_SetClientVolumeStatus_InputMessage	144
3.2.5.23.1.2	IPCBACKUPSERVERPROVIDER_SetClientVolumeStatus_OutputMessage	144
3.2.5.23.2	Elements	144
3.2.5.23.2.1	SetClientVolumeStatus	144
3.2.5.23.2.2	SetClientVolumeStatusResponse	145
3.2.5.24	IPCBACKUPSERVERPROVIDER.SetExcludedFolders	145
3.2.5.24.1	Messages	146
3.2.5.24.1.1	IPCBACKUPSERVERPROVIDER_SetExcludedFolders_InputMessage	146
3.2.5.24.1.2	IPCBACKUPSERVERPROVIDER_SetExcludedFolders_OutputMessage	146
3.2.5.24.2	Elements	146
3.2.5.24.2.1	SetExcludedFolders	146
3.2.5.24.2.2	SetExcludedFoldersResponse	146
3.2.5.25	IPCBACKUPSERVERPROVIDER.EnableBackups	147
3.2.5.25.1	Messages	147
3.2.5.25.1.1	IPCBACKUPSERVERPROVIDER_EnableBackups_InputMessage	147
3.2.5.25.1.2	IPCBACKUPSERVERPROVIDER_EnableBackups_OutputMessage	147
3.2.5.25.2	Elements	148
3.2.5.25.2.1	EnableBackups	148
3.2.5.25.2.2	EnableBackupsResponse	148
3.2.5.26	IPCBACKUPSERVERPROVIDER.DisableBackups	148
3.2.5.26.1	Messages	149
3.2.5.26.1.1	IPCBACKUPSERVERPROVIDER_DisableBackups_InputMessage	149

3.2.5.26.1.2	IPCBACKUPSERVERPROVIDER_DisableBackups_OutputMessage.....	149
3.2.5.26.2	Elements.....	149
3.2.5.26.2.1	DisableBackups	149
3.2.5.26.2.2	DisableBackupsResponse	149
3.2.5.27	IPCBACKUPSERVERPROVIDER.GetBackupConfiguration.....	150
3.2.5.27.1	Messages	150
3.2.5.27.1.1	IPCBACKUPSERVERPROVIDER_GetBackupConfiguration_InputMessage ..	150
3.2.5.27.1.2	IPCBACKUPSERVERPROVIDER_GetBackupConfiguration_OutputMessage	150
3.2.5.27.2	Elements.....	151
3.2.5.27.2.1	GetBackupConfiguration	151
3.2.5.27.2.2	GetBackupConfigurationResponse	151
3.2.5.28	IPCBACKUPSERVERPROVIDER.GetDefaultBackupConfiguration.....	151
3.2.5.28.1	Messages	152
3.2.5.28.1.1	IPCBACKUPSERVERPROVIDER_GetDefaultBackupConfiguration_InputMessag e	152
3.2.5.28.1.2	IPCBACKUPSERVERPROVIDER_GetDefaultBackupConfiguration_OutputMessag e.....	152
3.2.5.28.2	Elements.....	152
3.2.5.28.2.1	GetDefaultBackupConfiguration	152
3.2.5.28.2.2	GetDefaultBackupConfigurationResponse	153
3.2.5.29	IPCBACKUPSERVERPROVIDER.GetBackupOperationStatus.....	153
3.2.5.29.1	Messages	153
3.2.5.29.1.1	IPCBACKUPSERVERPROVIDER_GetBackupOperationStatus_InputMessage	153
3.2.5.29.1.2	IPCBACKUPSERVERPROVIDER_GetBackupOperationStatus_OutputMessage	154
3.2.5.29.2	Elements.....	154
3.2.5.29.2.1	GetBackupOperationStatus	154
3.2.5.29.2.2	GetBackupOperationStatusResponse	154
3.2.5.30	IPCBACKUPSERVERPROVIDER.GetServiceStatus	155
3.2.5.30.1	Messages	155
3.2.5.30.1.1	IPCBACKUPSERVERPROVIDER_GetServiceStatus_InputMessage ..	155
3.2.5.30.1.2	IPCBACKUPSERVERPROVIDER_GetServiceStatus_OutputMessage ..	155
3.2.5.30.2	Elements.....	156
3.2.5.30.2.1	GetServiceStatus	156
3.2.5.30.2.2	GetServiceStatusResponse	156
3.2.5.31	IPCBACKUPSERVERPROVIDER.GetWaitingOperations	156
3.2.5.31.1	Messages	157
3.2.5.31.1.1	IPCBACKUPSERVERPROVIDER_GetWaitingOperations_InputMessage ..	157
3.2.5.31.1.2	IPCBACKUPSERVERPROVIDER_GetWaitingOperations_OutputMessage ..	157
3.2.5.31.2	Elements.....	157
3.2.5.31.2.1	GetWaitingOperations.....	157
3.2.5.31.2.2	GetWaitingOperationsResponse	157
3.2.5.32	IPCBACKUPSERVERPROVIDER.SetBackupConfiguration	158
3.2.5.32.1	Messages	158
3.2.5.32.1.1	IPCBACKUPSERVERPROVIDER_SetBackupConfiguration_InputMessage ..	158
3.2.5.32.1.2	IPCBACKUPSERVERPROVIDER_SetBackupConfiguration_OutputMessage	158
3.2.5.32.2	Elements.....	159
3.2.5.32.2.1	SetBackupConfiguration.....	159
3.2.5.32.2.2	SetBackupConfigurationResponse	159
3.2.5.33	IPCBACKUPSERVERPROVIDER.GetUsedBytes	159
3.2.5.33.1	Messages	160
3.2.5.33.1.1	IPCBACKUPSERVERPROVIDER_GetUsedBytes_InputMessage ..	160
3.2.5.33.1.2	IPCBACKUPSERVERPROVIDER_GetUsedBytes_OutputMessage ..	160
3.2.5.33.2	Elements.....	160
3.2.5.33.2.1	GetUsedBytes.....	160

3.2.5.33.2.2	GetUsedBytesResponse	160
3.2.5.34	IPCBackupServerProvider.StartCleanup	161
3.2.5.34.1	Messages	161
3.2.5.34.1.1	IPCBackupServerProvider_StartCleanup_InputMessage	161
3.2.5.34.1.2	IPCBackupServerProvider_StartCleanup_OutputMessage	161
3.2.5.34.2	Elements	162
3.2.5.34.2.1	StartCleanup	162
3.2.5.34.2.2	StartCleanupResponse	162
3.2.5.35	IPCBackupServerProvider.CancelCleanup	162
3.2.5.35.1	Messages	163
3.2.5.35.1.1	IPCBackupServerProvider_CancelCleanup_InputMessage	163
3.2.5.35.1.2	IPCBackupServerProvider_CancelCleanup_OutputMessage	163
3.2.5.35.2	Elements	163
3.2.5.35.2.1	CancelCleanup	163
3.2.5.35.2.2	CancelCleanupResponse	163
3.2.5.36	IPCBackupServerProvider.StartRepair	164
3.2.5.36.1	Messages	164
3.2.5.36.1.1	IPCBackupServerProvider_StartRepair_InputMessage	164
3.2.5.36.1.2	IPCBackupServerProvider_StartRepair_OutputMessage	164
3.2.5.36.2	Elements	165
3.2.5.36.2.1	StartRepair	165
3.2.5.36.2.2	StartRepairResponse	165
3.2.5.37	IPCBackupServerProvider.CancelRepair	165
3.2.5.37.1	Messages	165
3.2.5.37.1.1	IPCBackupServerProvider_CancelRepair_InputMessage	165
3.2.5.37.1.2	IPCBackupServerProvider_CancelRepair_OutputMessage	166
3.2.5.37.2	Elements	166
3.2.5.37.2.1	CancelRepair	166
3.2.5.37.2.2	CancelRepairResponse	166
3.2.5.38	IPCBackupServerProvider.GetLastRepairResult	166
3.2.5.38.1	Messages	167
3.2.5.38.1.1	IPCBackupServerProvider_GetLastRepairResult_InputMessage	167
3.2.5.38.1.2	IPCBackupServerProvider_GetLastRepairResult_OutputMessage	167
3.2.5.38.2	Elements	167
3.2.5.38.2.1	GetLastRepairResult	168
3.2.5.38.2.2	GetLastRepairResultResponse	168
3.2.5.39	IPCBackupServerProvider.StartConsistencyChecker	168
3.2.5.39.1	Messages	168
3.2.5.39.1.1	IPCBackupServerProvider_StartConsistencyChecker_InputMessage	169
3.2.5.39.1.2	IPCBackupServerProvider_StartConsistencyChecker_OutputMessage	169
3.2.5.39.2	Elements	169
3.2.5.39.2.1	StartConsistencyChecker	169
3.2.5.39.2.2	StartConsistencyCheckerResponse	169
3.2.5.40	IPCBackupServerProvider.CancelConsistencyChecker	170
3.2.5.40.1	Messages	170
3.2.5.40.1.1	IPCBackupServerProvider_CancelConsistencyChecker_InputMessage	170
3.2.5.40.1.2	IPCBackupServerProvider_CancelConsistencyChecker_OutputMessage	170
3.2.5.40.2	Elements	171
3.2.5.40.2.1	CancelConsistencyChecker	171
3.2.5.40.2.2	CancelConsistencyCheckerResponse	171
3.2.5.41	IPCBackupServerProvider.Remove	171
3.2.5.41.1	Messages	171
3.2.5.41.1.1	IPCBackupServerProvider_Remove_InputMessage	172
3.2.5.41.1.2	IPCBackupServerProvider_Remove_OutputMessage	172
3.2.5.41.2	Elements	172
3.2.5.41.2.1	Remove	172
3.2.5.41.2.2	RemoveResponse	172

3.2.5.42	IPCBACKUPSERVERPROVIDER.CalculateVolumeAsync	173
3.2.5.42.1	Messages	173
3.2.5.42.1.1	IPCBACKUPSERVERPROVIDER_CalculateVolumeAsync_InputMessage	173
3.2.5.42.1.2	IPCBACKUPSERVERPROVIDER_CalculateVolumeAsync_OutputMessage	173
3.2.5.42.2	Elements	174
3.2.5.42.2.1	CalculateVolumeAsync	174
3.2.5.42.2.2	CalculateVolumeAsyncResponse	174
3.2.5.43	IPCBACKUPSERVERPROVIDER.GetFolderChildren	174
3.2.5.43.1	Messages	175
3.2.5.43.1.1	IPCBACKUPSERVERPROVIDER_GetFolderChildren_InputMessage	175
3.2.5.43.1.2	IPCBACKUPSERVERPROVIDER_GetFolderChildren_OutputMessage	175
3.2.5.43.2	Elements	175
3.2.5.43.2.1	GetFolderChildren	175
3.2.5.43.2.2	GetFolderChildrenResponse	176
3.2.5.44	IPCBACKUPSERVERPROVIDER.GetConnectedVolumes	176
3.2.5.44.1	Messages	176
3.2.5.44.1.1	IPCBACKUPSERVERPROVIDER_GetConnectedVolumes_InputMessage	177
3.2.5.44.1.2	IPCBACKUPSERVERPROVIDER_GetConnectedVolumes_OutputMessage	177
3.2.5.44.2	Elements	177
3.2.5.44.2.1	GetConnectedVolumes	177
3.2.5.44.2.2	GetConnectedVolumesResponse	177
3.2.5.45	IPCBACKUPSERVERPROVIDER.CleanFolderSizeCalculation	178
3.2.5.45.1	Messages	178
3.2.5.45.1.1	IPCBACKUPSERVERPROVIDER_CleanFolderSizeCalculation_InputMessage	178
3.2.5.45.2	Elements	178
3.2.5.45.2.1	CleanFolderSizeCalculation	178
3.2.5.46	IPCBACKUPSERVERPROVIDER.StartBackup	179
3.2.5.46.1	Messages	179
3.2.5.46.1.1	IPCBACKUPSERVERPROVIDER_StartBackup_InputMessage	179
3.2.5.46.1.2	IPCBACKUPSERVERPROVIDER_StartBackup_OutputMessage	179
3.2.5.46.2	Elements	180
3.2.5.46.2.1	StartBackup	180
3.2.5.46.2.2	StartBackupResponse	180
3.2.5.47	IPCBACKUPSERVERPROVIDER.CancelBackup	180
3.2.5.47.1	Messages	180
3.2.5.47.1.1	IPCBACKUPSERVERPROVIDER_CancelBackup_InputMessage	180
3.2.5.47.1.2	IPCBACKUPSERVERPROVIDER_CancelBackup_OutputMessage	181
3.2.5.47.2	Elements	181
3.2.5.47.2.1	CancelBackup	181
3.2.5.47.2.2	CancelBackupResponse	181
3.2.5.48	IPCBACKUPSERVERPROVIDER.StartBackupService	182
3.2.5.48.1	Messages	182
3.2.5.48.1.1	IPCBACKUPSERVERPROVIDER_StartBackupService_InputMessage	182
3.2.5.48.1.2	IPCBACKUPSERVERPROVIDER_StartBackupService_OutputMessage	182
3.2.5.48.2	Elements	183
3.2.5.48.2.1	StartBackupService	183
3.2.5.48.2.2	StartBackupServiceResponse	183
3.2.5.49	IPCBACKUPSERVERPROVIDER.StopBackupService	183
3.2.5.49.1	Messages	183
3.2.5.49.1.1	IPCBACKUPSERVERPROVIDER_StopBackupService_InputMessage	183
3.2.5.49.1.2	IPCBACKUPSERVERPROVIDER_StopBackupService_OutputMessage	184
3.2.5.49.2	Elements	184
3.2.5.49.2.1	StopBackupService	184
3.2.5.49.2.2	StopBackupServiceResponse	184
3.2.5.50	IPCBACKUPSERVERPROVIDER.NotifyBackupOperationStatusChange	185
3.2.5.50.1	Messages	185

3.2.5.50.1.1	IPCBackupServerProvider_NotifyBackupOperationStatusChange_OutputCallbackMessage.....	185
3.2.5.50.2	Elements.....	185
3.2.5.50.2.1	NotifyBackupOperationStatusChange.....	185
3.2.5.51	IPCBackupServerProvider.VolumeCalculatorProgress	186
3.2.5.51.1	Messages	186
3.2.5.51.1.1	IPCBackupServerProvider_VolumeCalculatorProgress_OutputCallbackMessage	186
3.2.5.51.2	Elements.....	186
3.2.5.51.2.1	VolumeCalculatorProgress.....	186
3.2.5.52	IPCBackupServerProvider.NotifyServiceStatusChange.....	187
3.2.5.52.1	Messages	187
3.2.5.52.1.1	IPCBackupServerProvider_NotifyServiceStatusChange_OutputCallbackMessage	187
3.2.5.52.2	Elements.....	187
3.2.5.52.2.1	NotifyServiceStatusChange	187
3.2.6	Timer Events.....	188
3.2.7	Other Local Events.....	188
3.3	Health Provider Service Contract Details	188
3.3.1	Abstract Data Model.....	188
3.3.1.1	ADM_ArrayOfKeyValueOfstringArrayOfAlertInfo	188
3.3.1.1.1	Data Model	188
3.3.1.1.1.1	AlertInfo	188
3.3.2	Timers	189
3.3.3	Initialization.....	189
3.3.4	Higher-Layer Triggered Events	189
3.3.5	Message Processing Events and Sequencing Rules	189
3.3.5.1	IAlertProviderCallback.RaiseAlertCompleted	190
3.3.5.1.1	Messages	191
3.3.5.1.1.1	IAlertProviderCallback_RaiseAlertCompleted_OutputCallbackMessage	191
3.3.5.1.2	Elements.....	191
3.3.5.1.2.1	RaiseAlertCompleted	191
3.3.5.2	IAlertProviderCallback.ClearAlertCompleted.....	191
3.3.5.2.1	Messages	191
3.3.5.2.1.1	IAlertProviderCallback_ClearAlertCompleted_OutputCallbackMessage	192
3.3.5.2.2	Elements.....	192
3.3.5.2.2.1	ClearAlertCompleted	192
3.3.5.3	IAlertProviderCallback.SuppressAlertCompleted	192
3.3.5.3.1	Messages	192
3.3.5.3.1.1	IAlertProviderCallback_SuppressAlertCompleted_OutputCallbackMessage	192
3.3.5.3.2	Elements.....	193
3.3.5.3.2.1	SuppressAlertCompleted.....	193
3.3.5.4	IAlertProviderCallback.RepairAlertCompleted	193
3.3.5.4.1	Messages	193
3.3.5.4.1.1	IAlertProviderCallback_RepairAlertCompleted_OutputCallbackMessage	193
3.3.5.4.2	Elements.....	193
3.3.5.4.2.1	RepairAlertCompleted.....	194
3.3.5.5	IAlertProviderCallback.EvaluateAlertsCompleted	194
3.3.5.5.1	Messages	194

3.3.5.5.1.1	IAlertProviderCallback_EvaluateAlertsCompleted_OutputCallbackMessage	194
3.3.5.5.2	Elements	194
3.3.5.5.2.1	EvaluateAlertsCompleted	194
3.3.5.6	IAlertProviderCallback.RaisedAlerts	195
3.3.5.6.1	Messages	195
3.3.5.6.1.1	IAlertProviderCallback_RaisedAlerts_OutputCallbackMessage	195
3.3.5.6.2	Elements	195
3.3.5.6.2.1	RaisedAlerts	195
3.3.5.7	IAlertProviderCallback.ClearedAlerts	196
3.3.5.7.1	Messages	196
3.3.5.7.1.1	IAlertProviderCallback_ClearedAlerts_OutputCallbackMessage	196
3.3.5.7.2	Elements	196
3.3.5.7.2.1	ClearedAlerts	196
3.3.5.8	IAlertSynchCallback.AlertChanged	197
3.3.5.8.1	Messages	197
3.3.5.8.1.1	IAlertSynchCallback_AlertChanged_OutputCallbackMessage	197
3.3.5.8.2	Elements	197
3.3.5.8.2.1	AlertChanged	197
3.3.5.9	IAlertManagementProviderService.GetAllNetworkAlerts	197
3.3.5.9.1	Messages	198
3.3.5.9.1.1	IAlertManagementProviderService_GetAllNetworkAlerts_InputMessage	198
3.3.5.9.1.2	IAlertManagementProviderService_GetAllNetworkAlerts_OutputMessage	198
3.3.5.9.2	Elements	199
3.3.5.9.2.1	GetAllNetworkAlerts	199
3.3.5.9.2.2	GetAllNetworkAlertsResponse	199
3.3.5.10	IAlertManagementProviderService.ClearAlertOneWay	199
3.3.5.10.1	Messages	199
3.3.5.10.1.1	IAlertManagementProviderService_ClearAlertOneWay_InputMessage	199
3.3.5.10.2	Elements	200
3.3.5.10.2.1	ClearAlertOneWay	200
3.3.5.11	IAlertManagementProviderService.ClearAlert	200
3.3.5.11.1	Messages	200
3.3.5.11.1.1	IAlertManagementProviderService_ClearAlert_InputMessage	200
3.3.5.11.1.2	IAlertManagementProviderService_ClearAlert_OutputMessage	201
3.3.5.11.2	Elements	201
3.3.5.11.2.1	ClearAlert	201
3.3.5.11.2.2	ClearAlertResponse	201
3.3.5.12	IAlertManagementProviderService.SuppressAlertOneWay	202
3.3.5.12.1	Messages	202
3.3.5.12.1.1	IAlertManagementProviderService_SuppressAlertOneWay_InputMessage	202
3.3.5.12.2	Elements	202
3.3.5.12.2.1	SuppressAlertOneWay	202
3.3.5.13	IAlertManagementProviderService.SuppressAlert	203
3.3.5.13.1	Messages	203
3.3.5.13.1.1	IAlertManagementProviderService_SuppressAlert_InputMessage	203
3.3.5.13.1.2	IAlertManagementProviderService_SuppressAlert_OutputMessage	203
3.3.5.13.2	Elements	204
3.3.5.13.2.1	SuppressAlert	204
3.3.5.13.2.2	SuppressAlertResponse	204
3.3.5.14	IAlertManagementProviderService.RaiseAlertOneWay	204
3.3.5.14.1	Messages	204

3.3.5.14.1.1	IAlertManagementProviderService_RaiseAlertOneWay_InputMessage	204
3.3.5.14.2	Elements	205
3.3.5.14.2.1	RaiseAlertOneWay	205
3.3.5.15	IAlertManagementProviderService.RaiseAlert	205
3.3.5.15.1	Messages	205
3.3.5.15.1.1	IAlertManagementProviderService_RaiseAlert_InputMessage	206
3.3.5.15.1.2	IAlertManagementProviderService_RaiseAlert_OutputMessage	206
3.3.5.15.2	Elements	206
3.3.5.15.2.1	RaiseAlert	206
3.3.5.15.2.2	RaiseAlertResponse	206
3.3.5.16	IAlertManagementProviderService.IsAuthorized	207
3.3.5.16.1	Messages	207
3.3.5.16.1.1	IAlertManagementProviderService_IsAuthorized_InputMessage	207
3.3.5.16.1.2	IAlertManagementProviderService_IsAuthorized_OutputMessage	207
3.3.5.16.2	Elements	208
3.3.5.16.2.1	IsAuthorized	208
3.3.5.16.2.2	IsAuthorizedResponse	208
3.3.5.17	IAlertSynchProviderService.RegisterClientAgent	208
3.3.5.17.1	Messages	208
3.3.5.17.1.1	IAlertSynchProviderService_RegisterClientAgent_InputMessage	209
3.3.5.17.1.2	IAlertSynchProviderService_RegisterClientAgent_OutputMessage	209
3.3.5.17.2	Elements	209
3.3.5.17.2.1	RegisterClientAgent	209
3.3.5.17.2.2	RegisterClientAgentResponse	209
3.3.5.18	IAlertSynchProviderService.SynchronizeAlerts	210
3.3.5.18.1	Messages	210
3.3.5.18.1.1	IAlertSynchProviderService_SynchronizeAlerts_InputMessage	210
3.3.5.18.2	Elements	210
3.3.5.18.2.1	SynchronizeAlerts	210
3.3.5.19	IAlertSynchProviderService.ClearCallbackCommandQueue	211
3.3.5.19.1	Messages	211
3.3.5.19.1.1	IAlertSynchProviderService_ClearCallbackCommandQueue_InputMessage	211
3.3.5.19.1.2	IAlertSynchProviderService_ClearCallbackCommandQueue_OutputMessage	211
3.3.5.19.2	Elements	212
3.3.5.19.2.1	ClearCallbackCommandQueue	212
3.3.5.19.2.2	ClearCallbackCommandQueueResponse	212
3.3.5.20	IAlertSynchProviderService.GetPlugInInformation	212
3.3.5.20.1	Messages	212
3.3.5.20.1.1	IAlertSynchProviderService_GetPlugInInformation_InputMessage	212
3.3.5.20.1.2	IAlertSynchProviderService_GetPlugInInformation_OutputMessage	213
3.3.5.20.2	Elements	213
3.3.5.20.2.1	GetPlugInInformation	213
3.3.5.20.2.2	GetPlugInInformationResponse	213
3.3.5.21	IAlertSynchProviderService.DownloadDefinition	214
3.3.5.21.1	Messages	214
3.3.5.21.1.1	IAlertSynchProviderService_DownloadDefinition_InputMessage	214
3.3.5.21.1.2	IAlertSynchProviderService_DownloadDefinition_OutputMessage	214
3.3.5.21.2	Elements	214
3.3.5.21.2.1	DownloadDefinition	214
3.3.5.21.2.2	DownloadDefinitionResponse	215
3.3.5.22	IAlertSynchProviderService.DownloadConfiguration	215
3.3.5.22.1	Messages	215
3.3.5.22.1.1	IAlertSynchProviderService_DownloadConfiguration_InputMessage	215

3.3.5.22.1.2	IAlertSynchProviderService_DownloadConfiguration_OutputMessage	216
3.3.5.22.2	Elements	216
3.3.5.22.2.1	DownloadConfiguration	216
3.3.5.22.2.2	DownloadConfigurationResponse	216
3.3.6	Timer Events	216
3.3.7	Other Local Events	217
3.4	Machine Identity Provider Service Contract Details	217
3.4.1	Abstract Data Model	217
3.4.1.1	Machine Identity	217
3.4.1.2	Machine RDP Permission	217
3.4.2	Timers	217
3.4.3	Initialization	217
3.4.4	Higher-Layer Triggered Events	217
3.4.5	Message Processing Events and Sequencing Rules	217
3.4.5.1	IMachineIdentityProvider.ReturnNewCertResponse	218
3.4.5.1.1	Messages	218
3.4.5.1.1.1	IMachineIdentityProvider_ReturnNewCertResponse_OutputCallbackMessage	218
3.4.5.1.2	Elements	219
3.4.5.1.2.1	ReturnNewCertResponse	219
3.4.5.2	IMachineIdentityProvider.ReturnRenewCert	219
3.4.5.2.1	Messages	219
3.4.5.2.1.1	IMachineIdentityProvider_ReturnRenewCert_OutputCallbackMessage	219
3.4.5.2.2	Elements	219
3.4.5.2.2.1	ReturnRenewCert	220
3.4.5.3	IMachineIdentityProvider.ReturnSid	220
3.4.5.3.1	Messages	220
3.4.5.3.1.1	IMachineIdentityProvider_ReturnSid_OutputCallbackMessage	220
3.4.5.3.2	Elements	220
3.4.5.3.2.1	ReturnSid	220
3.4.5.4	IMachineIdentityProvider.ReturnRevokeCert	221
3.4.5.4.1	Messages	221
3.4.5.4.1.1	IMachineIdentityProvider_ReturnRevokeCert_OutputCallbackMessage	221
3.4.5.4.2	Elements	221
3.4.5.4.2.1	ReturnRevokeCert	221
3.4.5.5	IMachineIdentityProvider.ReturnRemoveMachine	222
3.4.5.5.1	Messages	222
3.4.5.5.1.1	IMachineIdentityProvider_ReturnRemoveMachine_OutputCallbackMessage	222
3.4.5.5.2	Elements	222
3.4.5.5.2.1	ReturnRemoveMachine	222
3.4.5.6	IMachineIdentityProvider.ReturnGetMachineStatus	222
3.4.5.6.1	Messages	223
3.4.5.6.1.1	IMachineIdentityProvider_ReturnGetMachineStatus_OutputCallbackMessage	223
3.4.5.6.2	Elements	223
3.4.5.6.2.1	ReturnGetMachineStatus	223
3.4.5.7	IMachineIdentityProvider.ReturnMakeUserRemoteDesktopMapping	223
3.4.5.7.1	Messages	224
3.4.5.7.1.1	IMachineIdentityProvider_ReturnMakeUserRemoteDesktopMapping_OutputCallbackMessage	224
3.4.5.7.2	Elements	224

3.4.5.7.2.1	ReturnMakeUserRemoteDesktopMapping	224
3.4.5.8	IMachineIdentityProvider.RemoveMachine.....	224
3.4.5.8.1	Messages	224
3.4.5.8.1.1	IMachineIdentityProvider_RemoveMachine_InputMessage.....	224
3.4.5.8.2	Elements	225
3.4.5.8.2.1	RemoveMachine.....	225
3.4.5.9	IMachineIdentityProvider.RenewCert	225
3.4.5.9.1	Messages	225
3.4.5.9.1.1	IMachineIdentityProvider_RenewCert_InputMessage	225
3.4.5.9.2	Elements	226
3.4.5.9.2.1	RenewCert	226
3.4.5.10	IMachineIdentityProvider.RevokeCert	226
3.4.5.10.1	Messages	226
3.4.5.10.1.1	IMachineIdentityProvider_RevokeCert_InputMessage	226
3.4.5.10.2	Elements	226
3.4.5.10.2.1	RevokeCert	227
3.4.5.11	IMachineIdentityProvider.GenerateCertResponse	227
3.4.5.11.1	Messages	227
3.4.5.11.1.1	IMachineIdentityProvider_GenerateCertResponse_InputMessage	227
3.4.5.11.2	Elements	227
3.4.5.11.2.1	GenerateCertResponse	227
3.4.5.12	IMachineIdentityProvider.GenerateSid	228
3.4.5.12.1	Messages	228
3.4.5.12.1.1	IMachineIdentityProvider_GenerateSid_InputMessage	228
3.4.5.12.2	Elements	228
3.4.5.12.2.1	GenerateSid	228
3.4.5.13	IMachineIdentityProvider.GetMachineStatus	229
3.4.5.13.1	Messages	229
3.4.5.13.1.1	IMachineIdentityProvider_GetMachineStatus_InputMessage	229
3.4.5.13.2	Elements	229
3.4.5.13.2.1	GetMachineStatus	229
3.4.5.14	IMachineIdentityProvider.MakeUserRemoteDesktopMapping	230
3.4.5.14.1	Messages	230
3.4.5.14.1.1	IMachineIdentityProvider_MakeUserRemoteDesktopMapping_InputMessage	230
3.4.5.14.2	Elements	230
3.4.5.14.2.1	MakeUserRemoteDesktopMapping	230
3.4.6	Timer Events.....	230
3.4.7	Other Local Events.....	231
3.5	User Identity Provider Service Contract Details	231
3.5.1	Abstract Data Model.....	231
3.5.1.1	ADM_KeyValueOfUser	231
3.5.1.1.1	Data Model	231
3.5.1.1.1.1	UserInfo	231
3.5.1.1.1.1.1	PersonalInfo	231
3.5.2	Timers	232
3.5.3	Initialization.....	232
3.5.4	Higher-Layer Triggered Events	232
3.5.5	Message Processing Events and Sequencing Rules	232
3.5.5.1	IUserLogonProvider.LogonUser	232
3.5.5.1.1	Messages	233
3.5.5.1.1.1	IUserLogonProvider_LogonUser_InputMessage	233
3.5.5.1.1.2	IUserLogonProvider_LogonUser_OutputMessage	233
3.5.5.1.2	Elements	233
3.5.5.1.2.1	LogonUser	233
3.5.5.1.2.2	LogonUserResponse	234
3.5.5.2	IUserChangePasswordProvider.ChangePassword	234

3.5.5.2.1	Messages	235
3.5.5.2.1.1	IUserChangePasswordProvider_ChangePassword_InputMessage	235
3.5.5.2.1.2	IUserChangePasswordProvider_ChangePassword_OutputMessage	235
3.5.5.2.2	Elements	235
3.5.5.2.2.1	ChangePassword	235
3.5.5.2.2.2	ChangePasswordResponse	236
3.5.5.3	IUserInfoProvider.ReturnGroups	236
3.5.5.3.1	Messages	236
3.5.5.3.1.1	IUserInfoProvider_ReturnGroups_OutputCallbackMessage	236
3.5.5.3.2	Elements	237
3.5.5.3.2.1	ReturnGroups	237
3.5.5.4	IUserInfoProvider.ReturnWSServerGroups	237
3.5.5.4.1	Messages	237
3.5.5.4.1.1	IUserInfoProvider_ReturnWSServerGroups_OutputCallbackMessage	237
3.5.5.4.2	Elements	238
3.5.5.4.2.1	ReturnWSServerGroups	238
3.5.5.5	IUserInfoProvider.ReturnIsPartOfServerUsers	238
3.5.5.5.1	Messages	238
3.5.5.5.1.1	IUserInfoProvider_ReturnIsPartOfServerUsers_OutputCallbackMessage	238
3.5.5.5.2	Elements	239
3.5.5.5.2.1	ReturnIsPartOfServerUsers	239
3.5.5.6	IUserInfoProvider.GetGroups	239
3.5.5.6.1	Messages	239
3.5.5.6.1.1	IUserInfoProvider_GetGroups_InputMessage	239
3.5.5.6.2	Elements	240
3.5.5.6.2.1	GetGroups	240
3.5.5.7	IUserInfoProvider.GetWSServerGroups	240
3.5.5.7.1	Messages	240
3.5.5.7.1.1	IUserInfoProvider_GetWSServerGroups_InputMessage	240
3.5.5.7.2	Elements	240
3.5.5.7.2.1	GetWSServerGroups	240
3.5.5.8	IUserInfoProvider.IsPartOfServerUsers	241
3.5.5.8.1	Messages	241
3.5.5.8.1.1	IUserInfoProvider_IsPartOfServerUsers_InputMessage	241
3.5.5.8.2	Elements	241
3.5.5.8.2.1	IsPartOfServerUsers	241
3.5.6	Timer Events	242
3.5.7	Other Local Events	242
3.6	Provider Registry Service Contract Details	242
3.6.1	Abstract Data Model	242
3.6.2	Timers	242
3.6.3	Initialization	242
3.6.4	Higher-Layer Triggered Events	242
3.6.5	Message Processing Events and Sequencing Rules	242
3.6.5.1	IPrviderRegistry.Disconnect	243
3.6.5.1.1	Messages	243
3.6.5.1.1.1	IPrviderRegistry_Disconnect_InputMessage	243
3.6.5.1.2	Elements	243
3.6.5.1.2.1	Disconnect	243
3.6.5.2	IPrviderRegistry.Query	243
3.6.5.2.1	Messages	244
3.6.5.2.1.1	IPrviderRegistry_Query_InputMessage	244
3.6.5.2.1.2	IPrviderRegistry_Query_OutputMessage	244
3.6.5.2.2	Elements	244
3.6.5.2.2.1	Query	244
3.6.5.2.2.2	QueryResponse	245

3.6.5.3	IProviderRegistry.QueryAll	245
3.6.5.3.1	Messages	245
3.6.5.3.1.1	IProviderRegistry_QueryAll_InputMessage	245
3.6.5.3.1.2	IProviderRegistry_QueryAll_OutputMessage	246
3.6.5.3.2	Elements	246
3.6.5.3.2.1	QueryAll	246
3.6.5.3.2.2	QueryAllResponse	246
3.6.5.4	IProviderRegistry.RequestProviderInfoUpdate	246
3.6.5.4.1	Messages	247
3.6.5.4.1.1	IProviderRegistry_RequestProviderInfoUpdate_InputMessage	247
3.6.5.4.1.2	IProviderRegistry_RequestProviderInfoUpdate_OutputMessage	247
3.6.5.4.2	Elements	247
3.6.5.4.2.1	RequestProviderInfoUpdate	247
3.6.5.4.2.2	RequestProviderInfoUpdateResponse	248
3.6.5.5	IProviderRegistry.GetVersion	248
3.6.5.5.1	Messages	248
3.6.5.5.1.1	IProviderRegistry_GetVersion_InputMessage	248
3.6.5.5.1.2	IProviderRegistry_GetVersion_OutputMessage	248
3.6.5.5.2	Elements	249
3.6.5.5.2.1	GetVersion	249
3.6.5.5.2.2	GetVersionResponse	249
3.6.5.6	IProviderRegistry.InformOfProviderUpdate	249
3.6.5.6.1	Messages	249
3.6.5.6.1.1	IProviderRegistry_InformOfProviderUpdate_OutputCallbackMessage	249
3.6.5.6.2	Elements	250
3.6.5.6.2.1	InformOfProviderUpdate	250
3.6.5.7	INotificationProviderServiceAdminOnly.Connect	250
3.6.5.7.1	Messages	250
3.6.5.7.1.1	INotificationProviderServiceAdminOnly_Connect_InputMessage	250
3.6.5.7.2	Elements	251
3.6.5.7.2.1	Connect	251
3.6.5.8	INotificationProviderServiceAdminOnly.RaiseNotifications	251
3.6.5.8.1	Messages	251
3.6.5.8.1.1	INotificationProviderServiceAdminOnly_RaiseNotifications_InputMessage	251
3.6.5.8.2	Elements	252
3.6.5.8.2.1	RaiseNotifications	252
3.6.5.9	INotificationProviderServiceAdminOnly.ClearNotifications	252
3.6.5.9.1	Messages	252
3.6.5.9.1.1	INotificationProviderServiceAdminOnly_ClearNotifications_InputMessage	252
3.6.5.9.2	Elements	253
3.6.5.9.2.1	ClearNotifications	253
3.6.5.10	INotificationProviderServiceAdminOnly.RequestNotificationChange	253
3.6.5.10.1	Messages	253
3.6.5.10.1.1	INotificationProviderServiceAdminOnly_RequestNotificationChange_InputMessage	253
3.6.5.10.2	Elements	254
3.6.5.10.2.1	RequestNotificationChange	254
3.6.5.11	INotificationProviderServiceAdminOnly.FireEvent	254
3.6.5.11.1	Messages	254
3.6.5.11.1.1	INotificationProviderServiceAdminOnly_FireEvent_InputMessage	254
3.6.5.11.2	Elements	255
3.6.5.11.2.1	FireEvent	255
3.6.5.12	INotificationProviderServiceAdminOnly.AddCategoryFilters	255
3.6.5.12.1	Messages	255

3.6.5.12.1.1	INotificationProviderServiceAdminOnly_AddCategoryFilters_InputMessage.....	255
3.6.5.12.2	Elements	256
3.6.5.12.2.1	AddCategoryFilters.....	256
3.6.5.13	INotificationProviderServiceAdminOnly.RemoveCategoryFilters	256
3.6.5.13.1	Messages	256
3.6.5.13.1.1	INotificationProviderServiceAdminOnly_RemoveCategoryFilters_InputMessage	256
3.6.5.13.2	Elements.....	257
3.6.5.13.2.1	RemoveCategoryFilters	257
3.6.5.14	INotificationProviderServiceAdminOnly.Disconnect	257
3.6.5.14.1	Messages	257
3.6.5.14.1.1	INotificationProviderServiceAdminOnly_Disconnect_InputMessage	257
3.6.5.14.2	Elements	258
3.6.5.14.2.1	Disconnect	258
3.6.6	Timer Events.....	258
3.6.7	Other Local Events.....	258
3.7	Addin Management Service Contract Details	258
3.7.1	Abstract Data Model.....	258
3.7.2	Timers	258
3.7.3	Initialization.....	258
3.7.4	Higher-Layer Triggered Events	258
3.7.5	Message Processing Events and Sequencing Rules	259
3.7.5.1	IAddInMetadata.GetPackagePath	259
3.7.5.1.1	Messages	260
3.7.5.1.1.1	IAddInMetadata_GetPackagePath_InputMessage	260
3.7.5.1.1.2	IAddInMetadata_GetPackagePath_OutputMessage	260
3.7.5.1.2	Elements	260
3.7.5.1.2.1	GetPackagePath.....	260
3.7.5.1.2.2	GetPackagePathResponse	261
3.7.5.2	IAddInMetadata.GetAddInIds	261
3.7.5.2.1	Messages	261
3.7.5.2.1.1	IAddInMetadata_GetAddInIds_InputMessage	261
3.7.5.2.1.2	IAddInMetadata_GetAddInIds_OutputMessage	261
3.7.5.2.2	Elements	262
3.7.5.2.2.1	GetAddInIds	262
3.7.5.2.2.2	GetAddInIdsResponse	262
3.7.5.3	IAddInMetadata.GetAddInInformation	262
3.7.5.3.1	Messages	263
3.7.5.3.1.1	IAddInMetadata_GetAddInInformation_InputMessage	263
3.7.5.3.1.2	IAddInMetadata_GetAddInInformation_OutputMessage	263
3.7.5.3.2	Elements	263
3.7.5.3.2.1	GetAddInInformation.....	263
3.7.5.3.2.2	GetAddInInformationResponse	263
3.7.5.4	IAddInMetadata.RegisterForChanges	264
3.7.5.4.1	Messages	264
3.7.5.4.1.1	IAddInMetadata_RegisterForChanges_InputMessage	264
3.7.5.4.1.2	IAddInMetadata_RegisterForChanges_OutputMessage	264
3.7.5.4.2	Elements	265
3.7.5.4.2.1	RegisterForChanges	265
3.7.5.4.2.2	RegisterForChangesResponse	265
3.7.5.5	IAddInMetadata.OperationInProgress	265
3.7.5.5.1	Messages	265
3.7.5.5.1.1	IAddInMetadata_OperationInProgress_InputMessage	266
3.7.5.5.1.2	IAddInMetadata_OperationInProgress_OutputMessage	266
3.7.5.5.2	Elements	266

3.7.5.5.2.1	OperationInProgress.....	266
3.7.5.5.2.2	OperationInProgressResponse	266
3.7.5.6	IAddInMetadata.ChangeOccured	267
3.7.5.6.1	Messages	267
3.7.5.6.1.1	IAddInMetadata_ChangeOccured_OutputCallbackMessage	267
3.7.5.6.2	Elements	267
3.7.5.6.2.1	ChangeOccured	267
3.7.5.7	IAddInMetadataInstall.CheckCredentials	267
3.7.5.7.1	Messages	268
3.7.5.7.1.1	IAddInMetadataInstall_CheckCredentials_InputMessage	268
3.7.5.7.1.2	IAddInMetadataInstall_CheckCredentials_OutputMessage	268
3.7.5.7.2	Elements	268
3.7.5.7.2.1	CheckCredentials	268
3.7.5.7.2.2	CheckCredentialsResponse	268
3.7.5.8	IAddInMetadataInstall.InstallAddIn	269
3.7.5.8.1	Messages	269
3.7.5.8.1.1	IAddInMetadataInstall_InstallAddIn_InputMessage	269
3.7.5.8.2	Elements	269
3.7.5.8.2.1	InstallAddIn	269
3.7.5.9	IAddInMetadataInstall.DownloadInstallAddIn.....	270
3.7.5.9.1	Messages	270
3.7.5.9.1.1	IAddInMetadataInstall_DownloadInstallAddIn_InputMessage	270
3.7.5.9.2	Elements	270
3.7.5.9.2.1	DownloadInstallAddIn.....	270
3.7.5.10	IAddInMetadataInstall.UninstallAddIn	271
3.7.5.10.1	Messages	271
3.7.5.10.1.1	IAddInMetadataInstall_UninstallAddIn_InputMessage	271
3.7.5.10.2	Elements	271
3.7.5.10.2.1	UninstallAddIn	271
3.7.5.11	IAddInMetadataInstall.CancelOperation	272
3.7.5.11.1	Messages	272
3.7.5.11.1.1	IAddInMetadataInstall_CancelOperation_InputMessage	272
3.7.5.11.2	Elements	272
3.7.5.11.2.1	CancelOperation	272
3.7.5.12	IAddInMetadataInstall.StartUploadAddinFile	272
3.7.5.12.1	Messages	273
3.7.5.12.1.1	IAddInMetadataInstall_StartUploadAddinFile_InputMessage	273
3.7.5.12.1.2	IAddInMetadataInstall_StartUploadAddinFile_OutputMessage	273
3.7.5.12.2	Elements	273
3.7.5.12.2.1	StartUploadAddinFile	273
3.7.5.12.2.2	StartUploadAddinFileResponse.....	274
3.7.5.13	IAddInMetadataInstall.UploadAddinFile	274
3.7.5.13.1	Messages	274
3.7.5.13.1.1	IAddInMetadataInstall_UploadAddinFile_InputMessage	274
3.7.5.13.1.2	IAddInMetadataInstall_UploadAddinFile_OutputMessage	275
3.7.5.13.2	Elements	275
3.7.5.13.2.1	UploadAddinFile	275
3.7.5.13.2.2	UploadAddinFileResponse.....	275
3.7.5.14	IAddInMetadataInstall.EndUploadAddinFile	275
3.7.5.14.1	Messages	276
3.7.5.14.1.1	IAddInMetadataInstall_EndUploadAddinFile_InputMessage	276
3.7.5.14.1.2	IAddInMetadataInstall_EndUploadAddinFile_OutputMessage	276
3.7.5.14.2	Elements	276
3.7.5.14.2.1	EndUploadAddinFile	276
3.7.5.14.2.2	EndUploadAddinFileResponse	277
3.7.5.15	IAddInMetadataInstall.ProgressChanged	277
3.7.5.15.1	Messages	277
3.7.5.15.1.1	IAddInMetadataInstall_ProgressChanged_OutputCallbackMessage ..	277

3.7.5.15.2 Elements	277
3.7.5.15.2.1 ProgressChanged	277
3.7.5.16 IAddInMetadataInstall.ErrorOccured	278
3.7.5.16.1 Messages	278
3.7.5.16.1.1 IAddInMetadataInstall_ErrorOccured_OutputCallbackMessage	278
3.7.5.16.2 Elements	278
3.7.5.16.2.1 ErrorOccured	278
3.7.5.17 IAddInMetadataInstall.RebootRequired	279
3.7.5.17.1 Messages	279
3.7.5.17.1.1 IAddInMetadataInstall_RebootRequired_OutputCallbackMessage	279
3.7.5.17.2 Elements	279
3.7.5.17.2.1 RebootRequired	279
3.7.5.18 IAddInMetadataInstall.RestartDashboardRequired	279
3.7.5.18.1 Messages	279
3.7.5.18.1.1 IAddInMetadataInstall_RestartDashboardRequired_OutputCallbackMessage	280
3.7.5.18.2 Elements	280
3.7.5.18.2.1 RestartDashboardRequired	280
3.7.6 Timer Events	280
3.7.7 Other Local Events	280
3.8 Network Service Contract Details	280
3.8.1 Abstract Data Model	280
3.8.2 Timers	280
3.8.3 Initialization	280
3.8.4 Higher-Layer Triggered Events	281
3.8.5 Message Processing Events and Sequencing Rules	281
3.8.5.1 INetworkingService.UpdateClientAddress	281
3.8.5.1.1 Messages	281
3.8.5.1.1.1 INetworkingService_UpdateClientAddress_InputMessage	281
3.8.5.1.1.2 INetworkingService_UpdateClientAddress_OutputMessage	282
3.8.5.1.2 Elements	282
3.8.5.1.2.1 UpdateClientAddress	282
3.8.5.1.2.2 UpdateClientAddressResponse	282
3.8.5.2 INetworkingService.RemoveClient	282
3.8.5.2.1 Messages	283
3.8.5.2.1.1 INetworkingService_RemoveClient_InputMessage	283
3.8.5.2.1.2 INetworkingService_RemoveClient_OutputMessage	283
3.8.5.2.2 Elements	283
3.8.5.2.2.1 RemoveClient	283
3.8.5.2.2.2 RemoveClientResponse	284
3.8.5.3 INetworkingService.Ping	284
3.8.5.3.1 Messages	284
3.8.5.3.1.1 INetworkingService_Ping_InputMessage	284
3.8.5.3.1.2 INetworkingService_Ping_OutputMessage	284
3.8.5.3.2 Elements	285
3.8.5.3.2.1 Ping	285
3.8.5.3.2.2 PingResponse	285
3.8.5.4 INetworkingService.GetVPNServerSetting	285
3.8.5.4.1 Messages	285
3.8.5.4.1.1 INetworkingService_GetVPNServerSetting_InputMessage	285
3.8.5.4.1.2 INetworkingService_GetVPNServerSetting_OutputMessage	286
3.8.5.4.2 Elements	286
3.8.5.4.2.1 GetVPNServerSetting	286
3.8.5.4.2.2 GetVPNServerSettingResponse	286
3.8.5.5 INetworkService.GetVirtualNetworkSettings	286
3.8.5.5.1 Messages	287
3.8.5.5.1.1 INetworkService_GetVirtualNetworkSettings_InputMessage	287

3.8.5.5.1.2	INetworkService_GetVirtualNetworkSettings_OutputMessage	287
3.8.5.5.2	Elements	287
3.8.5.5.2.1	GetVirtualNetworkSettings	287
3.8.5.5.2.2	GetVirtualNetworkSettingsResponse	288
3.8.6	Timer Events	288
3.8.7	Other Local Events	288
3.9	Domain Infrastructure Service Contract Details	288
3.9.1	Abstract Data Model	288
3.9.2	Timers	288
3.9.3	Initialization	288
3.9.4	Higher-Layer Triggered Events	288
3.9.5	Message Processing Events and Sequencing Rules	288
3.9.5.1	IDomainMaintenanceManager.SetCredentials	289
3.9.5.1.1	Messages	290
3.9.5.1.1.1	IDomainMaintenanceManager_SetCredentials_InputMessage	290
3.9.5.1.1.2	IDomainMaintenanceManager_SetCredentials_OutputMessage	290
3.9.5.1.2	Elements	290
3.9.5.1.2.1	SetCredentials	290
3.9.5.1.2.2	SetCredentialsResponse	290
3.9.5.2	IDomainMaintenanceManager.ValidateCredentials	291
3.9.5.2.1	Messages	291
3.9.5.2.1.1	IDomainMaintenanceManager_ValidateCredentials_InputMessage	291
3.9.5.2.1.2	IDomainMaintenanceManager_ValidateCredentials_OutputMessage	291
3.9.5.2.2	Elements	292
3.9.5.2.2.1	ValidateCredentials	292
3.9.5.2.2.2	ValidateCredentialsResponse	292
3.9.5.3	IDomainMaintenanceManager.UpdateDnsRecords	292
3.9.5.3.1	Messages	293
3.9.5.3.1.1	IDomainMaintenanceManager_UpdateDnsRecords_InputMessage	293
3.9.5.3.1.2	IDomainMaintenanceManager_UpdateDnsRecords_OutputMessage	293
3.9.5.3.2	Elements	293
3.9.5.3.2.1	UpdateDnsRecords	293
3.9.5.3.2.2	UpdateDnsRecordsResponse	294
3.9.5.4	IDomainMaintenanceManager.QueryAddressFromDNS	294
3.9.5.4.1	Messages	294
3.9.5.4.1.1	IDomainMaintenanceManager_QueryAddressFromDNS_InputMessage	294
3.9.5.4.1.2	IDomainMaintenanceManager_QueryAddressFromDNS_OutputMessage	295
3.9.5.4.2	Elements	295
3.9.5.4.2.1	QueryAddressFromDNS	295
3.9.5.4.2.2	QueryAddressFromDNSResponse	295
3.9.5.5	IDomainMaintenanceManager.QueryAddressFromProvider	295
3.9.5.5.1	Messages	296
3.9.5.5.1.1	IDomainMaintenanceManager_QueryAddressFromProvider_InputMessage	296
3.9.5.5.1.2	IDomainMaintenanceManager_QueryAddressFromProvider_OutputMessage	296
3.9.5.5.2	Elements	296
3.9.5.5.2.1	QueryAddressFromProvider	296
3.9.5.5.2.2	QueryAddressFromProviderResponse	297
3.9.5.6	IDomainMaintenanceManager.TestConnection	297
3.9.5.6.1	Messages	297
3.9.5.6.1.1	IDomainMaintenanceManager_TestConnection_InputMessage	297
3.9.5.6.1.2	IDomainMaintenanceManager_TestConnection_OutputMessage	298
3.9.5.6.2	Elements	298

3.9.5.6.2.1	TestConnection.....	298
3.9.5.6.2.2	TestConnectionResponse	298
3.9.5.7	IDomainMaintenanceManager.GetDomainState.....	298
3.9.5.7.1	Messages	299
3.9.5.7.1.1	IDomainMaintenanceManager_GetDomainState_InputMessage.....	299
3.9.5.7.1.2	IDomainMaintenanceManager_GetDomainState_OutputMessage.....	299
3.9.5.7.2	Elements.....	299
3.9.5.7.2.1	GetDomainState	299
3.9.5.7.2.2	GetDomainStateResponse	300
3.9.5.8	IDomainMaintenanceManager.GetCertificateState	300
3.9.5.8.1	Messages	300
3.9.5.8.1.1	IDomainMaintenanceManager_GetCertificateState_InputMessage ..	300
3.9.5.8.1.2	IDomainMaintenanceManager_GetCertificateState_OutputMessage ..	301
3.9.5.8.2	Elements.....	301
3.9.5.8.2.1	GetCertificateState.....	301
3.9.5.8.2.2	GetCertificateStateResponse	301
3.9.5.9	IDomainMaintenanceManager.GetDomainNameConfiguration	301
3.9.5.9.1	Messages	302
3.9.5.9.1.1	IDomainMaintenanceManager_GetDomainNameConfiguration_InputMes sage.....	302
3.9.5.9.1.2	IDomainMaintenanceManager_GetDomainNameConfiguration_OutputMe ssage	302
3.9.5.9.2	Elements.....	302
3.9.5.9.2.1	GetDomainNameConfiguration.....	302
3.9.5.9.2.2	GetDomainNameConfigurationResponse	303
3.9.5.10	IDomainMaintenanceManager.GetDynamicDNSInfo	303
3.9.5.10.1	Messages	303
3.9.5.10.1.1	IDomainMaintenanceManager_GetDynamicDNSInfo_InputMessage ..	303
3.9.5.10.1.2	IDomainMaintenanceManager_GetDynamicDNSInfo_OutputMessage ..	304
3.9.5.10.2	Elements.....	304
3.9.5.10.2.1	GetDynamicDNSInfo	304
3.9.5.10.2.2	GetDynamicDNSInfoResponse	304
3.9.5.11	IDomainMaintenanceManager.GetSettings	304
3.9.5.11.1	Messages	305
3.9.5.11.1.1	IDomainMaintenanceManager_GetSettings_InputMessage	305
3.9.5.11.1.2	IDomainMaintenanceManager_GetSettings_OutputMessage	305
3.9.5.11.2	Elements.....	305
3.9.5.11.2.1	GetSettings.....	305
3.9.5.11.2.2	GetSettingsResponse.....	306
3.9.6	Timer Events.....	306
3.9.7	Other Local Events.....	306
3.10	AzureAD and HostedEmail Integration Service Contract Details.....	306
3.10.1	Abstract Data Model.....	306
3.10.2	Timers	306
3.10.3	Initialization.....	306
3.10.4	Higher-Layer Triggered Events	306
3.10.5	Message Processing Events and Sequencing Rules	306
3.10.5.1	IPasswordSyncClientProvider.Disconnect.....	307
3.10.5.1.1	Messages	307
3.10.5.1.1.1	IPasswordSyncClientProvider_Disconnect_InputMessage	307
3.10.5.1.2	Elements.....	307
3.10.5.1.2.1	Disconnect	307
3.10.5.2	IPasswordSyncClientProvider.RaiseOperationInvokeEvent	307
3.10.5.2.1	Messages	308

3.10.5.2.1.1	IO365ClientProvider_RaiseOperationInvokeEvent_OutputCallbackMessage.....	308
3.10.5.2.2	Elements	308
3.10.5.2.2.1	RaiseOperationInvokeEvent.....	308
3.10.5.3	IO365ClientProvider.GetSharePointAddress	308
3.10.5.3.1	Messages	309
3.10.5.3.1.1	IO365ClientProvider_GetSharePointAddress_InputMessage	309
3.10.5.3.1.2	IO365ClientProvider_GetSharePointAddress_OutputMessage	309
3.10.5.3.2	Elements	309
3.10.5.3.2.1	GetSharePointAddress	309
3.10.5.3.2.2	GetSharePointAddressResponse	310
3.10.5.4	IO365ClientProvider.IsActive.....	310
3.10.5.4.1	Messages	310
3.10.5.4.1.1	IO365ClientProvider_IsActivated_InputMessage	310
3.10.5.4.1.2	IO365ClientProvider_IsActivated_OutputMessage	311
3.10.5.4.2	Elements	311
3.10.5.4.2.1	IsActive.....	311
3.10.5.4.2.2	IsActiveResponse	311
3.10.5.5	IPasswordSyncClientProvider.GetPasswordChangeStatus	311
3.10.5.5.1	Messages	312
3.10.5.5.1.1	IPasswordSyncClientProvider_GetPasswordChangeStatus_InputMessage	312
3.10.5.5.1.2	IPasswordSyncClientProvider_GetPasswordChangeStatus_OutputMessage.....	312
3.10.5.5.2	Elements	312
3.10.5.5.2.1	GetPasswordChangeStatus.....	312
3.10.5.5.2.2	GetPasswordChangeStatusResponse	313
3.10.5.6	IPasswordSyncClientProvider.MarkUserPasswordChangeFixed.....	313
3.10.5.6.1	Messages	313
3.10.5.6.1.1	IPasswordSyncClientProvider_MarkUserPasswordChangeFixed_InputMessage.....	313
3.10.5.6.1.2	IPasswordSyncClientProvider_MarkUserPasswordChangeFixed_OutputMessage	314
3.10.5.6.2	Elements	314
3.10.5.6.2.1	MarkUserPasswordChangeFixed	314
3.10.5.6.2.2	MarkUserPasswordChangeFixedResponse	314
3.10.5.7	IO365ClientProvider.GetEmailAddress	315
3.10.5.7.1	Messages	315
3.10.5.7.1.1	IO365ClientProvider_GetEmailAddress_InputMessage	315
3.10.5.7.1.2	IO365ClientProvider_GetEmailAddress_OutputMessage	315
3.10.5.7.2	Elements	315
3.10.5.7.2.1	GetEmailAddress	315
3.10.5.7.2.2	GetEmailAddressResponse	316
3.10.6	Timer Events.....	316
3.10.7	Other Local Events.....	316
3.11	Client Notification Service Contract Details	316
3.11.1	Abstract Data Model.....	316
3.11.2	Timers	316
3.11.3	Initialization	316
3.11.4	Higher-Layer Triggered Events	316
3.11.5	Message Processing Events and Sequencing Rules	317
3.11.5.1	IClientRegistrationService.RegisterClient	317
3.11.5.1.1	Messages	317
3.11.5.1.1.1	IClientRegistrationService_RegisterClient_InputMessage.....	317

3.11.5.1.2	Elements	317
3.11.5.1.2.1	RegisterClient	317
3.11.5.2	IClientNotificationCallback.NotificationReceived	318
3.11.5.2.1	Messages	318
3.11.5.2.1.1	IClientNotificationCallback_NotificationReceived_OutputCallbackMessage	318
3.11.5.2.1.2	IClientNotificationCallback_NotificationReceived_InputCallbackMessage	318
3.11.5.2.2	Elements	318
3.11.5.2.2.1	NotificationReceived	318
3.11.5.2.2.2	NotificationReceivedResponse	319
3.11.5.3	IClientNotificationProvider.NotifyClientByName	319
3.11.5.3.1	Messages	319
3.11.5.3.1.1	IClientNotificationProvider_NotifyClientByName_InputMessage	319
3.11.5.3.1.2	IClientNotificationProvider_NotifyClientByName_OutputMessage	320
3.11.5.3.2	Elements	320
3.11.5.3.2.1	NotifyClientByName	320
3.11.5.3.2.2	NotifyClientByNameResponse	320
3.11.5.4	IClientNotificationProvider.NotifyClientById	320
3.11.5.4.1	Messages	321
3.11.5.4.1.1	IClientNotificationProvider_NotifyClientById_InputMessage	321
3.11.5.4.1.2	IClientNotificationProvider_NotifyClientById_OutputMessage	321
3.11.5.4.2	Elements	321
3.11.5.4.2.1	NotifyClientById	321
3.11.5.4.2.2	NotifyClientByIdResponse	322
3.11.5.5	IClientNotificationProvider.NotifyAllClients	322
3.11.5.5.1	Messages	322
3.11.5.5.1.1	IClientNotificationProvider_NotifyAllClients_InputMessage	322
3.11.5.5.1.2	IClientNotificationProvider_NotifyAllClients_OutputMessage	322
3.11.5.5.2	Elements	323
3.11.5.5.2.1	NotifyAllClients	323
3.11.5.5.2.2	NotifyAllClientsResponse	323
4	Protocol Examples	324
4.1	Get the Computer Backup Service Status	324
5	Security	325
5.1	Security Considerations for Implementers	325
5.1.1	User Identity	325
5.1.2	Machine Identity	325
5.2	Index of Security Parameters	325
6	Appendix A: Full WSDL	326
6.1	Client File Backup Provider Service WSDL	326
6.1.1	wsdl	326
6.1.2	http://tempuri.org/	328
6.1.3	http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.DataProtection.FileBackup	329
6.1.4	http://schemas.microsoft.com/2003/10/Serialization/	329
6.1.5	http://schemas.datacontract.org/2004/07/System	330
6.2	Client Backup Provider Service WSDL	331
6.2.1	IPCBBackupServerRegister	331
6.2.1.1	wsdl	331
6.2.1.2	http://tempuri.org	337
6.2.1.3	http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.DataProtection.PCBackup.BackupUtil.WcfContracts	340

6.2.1.4	http://schemas.microsoft.com/2003/10/Serialization/Arrays	342
6.2.1.5	http://schemas.microsoft.com/2003/10/Serialization	342
6.2.1.6	http://schemas.datacontract.org/2004/07/System	343
6.2.2	IPCBBackupServiceProvider	344
6.2.2.1	wsdl	344
6.2.2.2	http://tempuri.org	373
6.2.2.3		
	http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.D ataProtection.PCBackup.BackupUtil.WcfContracts.....	381
6.2.2.4	http://schemas.microsoft.com/2003/10/Serialization/Arrays	388
6.2.2.5	http://schemas.microsoft.com/2003/10/Serialization	389
6.2.2.6	http://schemas.datacontract.org/2004/07/System.ServiceModel.Security ..	389
6.2.2.7	http://schemas.datacontract.org/2004/07/System.ServiceModel	390
6.2.2.8	http://schemas.datacontract.org/2004/07/System	390
6.3	Health Provider Service WSDL	390
6.3.1	wsdl.....	390
6.3.2	http://tempuri.org	401
6.3.3		
	http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.Netwo rkHealth.AlertFramework.Commands	405
6.3.4	http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.Netwo rkHealth.AlertFramework.Service.....	406
6.3.5		
	http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.Netwo rkHealth.AlertFramework	406
6.3.6		
	http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.Netwo rkHealth.Engine.....	407
6.3.7	http://schemas.microsoft.com/2003/10/Serialization/Arrays	408
6.3.8	http://schemas.microsoft.com/2003/10/Serialization	408
6.3.9	http://schemas.microsoft.com/Message	409
6.3.10	http://schemas.datacontract.org/2004/07/System.ServiceModel.Security ..	409
6.3.11	http://schemas.datacontract.org/2004/07/System.ServiceModel	409
6.3.12	http://schemas.datacontract.org/2004/07/System	410
6.4	Machine Identity Provider Service WSDL	410
6.4.1	wsdl.....	410
6.4.2	http://tempuri.org	414
6.4.3		
	http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.Devic es.Identity	416
6.4.4	http://schemas.microsoft.com/2003/10/Serialization	417
6.5	User Identity Provider Service WSDL	417
6.5.1	IUserLogonProvider.....	417
6.5.1.1	wsdl1	417
6.5.1.2	wsdl2	419
6.5.1.3		
	http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.U ser	420
6.5.1.4	http://schemas.microsoft.com/2003/10/Serialization/Arrays	422
6.5.1.5	http://schemas.microsoft.com/2003/10/Serialization	422
6.5.1.6	http://schemas.datacontract.org/2004/07/System.....	423
6.5.1.7		
	http://www.microsoft.com/WindowsServerSolutions/ProviderFramework/Notific ations/3/2010	423
6.5.2	IUserChangePasswordProvider	424
6.5.2.1	wsdl	424
6.5.2.2	wsdl2	425

6.5.2.3	http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.Users	427
6.5.2.4	http://schemas.microsoft.com/2003/10/Serialization	427
6.5.2.5	http://schemas.datacontract.org/2004/07/System	428
6.5.2.6	http://www.microsoft.com/WindowsServerSolutions/ProviderFramework/Notifications/3/2010	429
6.5.3	IUserInfoProvider	429
6.5.3.1	wsdl	429
6.5.3.2	wsdl2	431
6.5.3.3	http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.Users	432
6.5.3.4	http://schemas.microsoft.com/2003/10/Serialization/Arrays	433
6.5.3.5	http://schemas.microsoft.com/2003/10/Serialization	433
6.5.3.6	http://www.microsoft.com/WindowsServerSolutions/ProviderFramework/Notifications/3/2010	434
6.6	Provider Registry Service WSDL	435
6.6.1	IProviderRegistry	435
6.6.1.1	wsdl	435
6.6.1.2	http://tempuri.org	439
6.6.1.3	http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.Common.ProviderFramework	441
6.6.1.4	http://schemas.microsoft.com/2003/10/Serialization	442
6.6.1.5	http://schemas.datacontract.org/2004/07/System	443
6.6.1.6	http://www.microsoft.com/2010/06/Microsoft.WindowsServerSolutions.Common.ProviderFramework	443
6.6.2	INotificationProviderServiceAdminOnly	444
6.6.2.1	wsdl	444
6.6.2.2	wsdl2	447
6.6.2.3	http://schemas.microsoft.com/2003/10/Serialization/Arrays	449
6.6.2.4	http://schemas.microsoft.com/2003/10/Serialization	449
6.6.2.5	http://www.microsoft.com/WindowsServerSolutions/ProviderFramework/Notifications/3/2010	450
6.7	Addin Management Service WSDL	451
6.7.1	wsdl	451
6.7.2	http://tempuri.org	460
6.7.3	http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.Addin.Infrastructure	463
6.7.4	http://schemas.microsoft.com/2003/10/Serialization/Arrays	465
6.7.5	http://schemas.microsoft.com/2003/10/Serialization	465
6.7.6	http://schemas.microsoft.com/WindowsServerSolutions/2010/03/Addins	466
6.7.7	http://schemas.datacontract.org/2004/07/System.Collections.ObjectModel	468
6.7.8	http://schemas.datacontract.org/2004/07/System	469
6.8	Network Service WSDL	469
6.8.1	wsdl	469
6.8.2	http://tempuri.org	472
6.8.3	http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.Networking	472

6.8.4	http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.RemoteAccess.....	473
6.8.5	http://schemas.microsoft.com/2003/10/Serialization/Arrays.....	473
6.8.6	http://schemas.microsoft.com/2003/10/Serialization	474
6.8.7	http://schemas.datacontract.org/2004/07/System.Net.Sockets.....	474
6.8.8	http://schemas.datacontract.org/2004/07/System.Net.....	478
6.9	Domain Infrastructure Service WSDL.....	479
6.9.1	wsdl.....	479
6.9.2	http://tempuri.org	486
6.9.3	http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.RemoteAccess.Domains.....	489
6.9.4	http://schemas.microsoft.com/2003/10/Serialization/Arrays.....	494
6.9.5	http://schemas.microsoft.com/2003/10/Serialization	494
6.9.6	http://schemas.datacontract.org/2004/07/System.Collections.ObjectModel	495
6.9.7	http://schemas.datacontract.org/2004/07/System.Net.Sockets.....	495
6.9.8	http://schemas.datacontract.org/2004/07/System.Net.....	499
6.9.9	http://schemas.datacontract.org/2004/07/System	500
6.10	AzureAD and HostedEmail Integration Service WSDL.....	500
6.10.1	IPasswordSyncClientProvider	500
6.10.1.1	wsdl	500
6.10.1.2	http://tempuri.org	504
6.10.1.3	http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.PasswordSync	505
6.10.1.4	http://schemas.microsoft.com/2003/10/Serialization	506
6.10.1.5	http://schemas.datacontract.org/2004/07/System	507
6.10.2	IO365ClientProvider.....	507
6.10.2.1	wsdl	507
6.10.2.2	http://tempuri.org	530
6.10.2.3	http://schemas.microsoft.com/2003/10/Serialization	541
6.10.2.4	http://schemas.datacontract.org/2004/07/System.Collections.ObjectModel	542
6.10.2.5	http://schemas.datacontract.org/2004/07/System.Net.Sockets	546
6.10.2.6	http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.O365Integration	549
6.10.2.7	http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.RemoteAccess.Domains.....	565
6.10.2.8	http://schemas.microsoft.com/2003/10/Serialization/Arrays	566
6.10.2.9	http://schemas.datacontract.org/2004/07/System.Net	567
6.10.2.10	http://schemas.datacontract.org/2004/07/System.ServiceModel.Security	567
6.10.2.11	http://schemas.datacontract.org/2004/07/System.ServiceModel	568
6.10.2.12	http://schemas.datacontract.org/2004/07/System	568
6.11	Client Notification Service WSDL	569
6.11.1	wsdl.....	569
6.11.2	http://tempuri.org	571
6.11.3	http://schemas.microsoft.com/2003/10/Serialization	572
6.11.4	http://schemas.datacontract.org/2004/07/System	573
7	Appendix B: Product Behavior	575
8	Change Tracking.....	577
9	Index.....	578

1 Introduction

The WCF-Based Encrypted Server Administration and Notification Protocol (Provider Framework) enables the protocol client to monitor and manage the protocol server in the same network.

This protocol is an extension to the .NET Message Framing TCP Binding Protocol [\[MS-NMFTB\]](#).

Sections 1.5, 1.8, 1.9, 2, and 3 of this specification are normative. All other sections and examples in this specification are informative.

1.1 Glossary

This document uses the following terms:

Active Directory: The Windows implementation of a general-purpose directory service, which uses LDAP as its primary access protocol. **Active Directory** stores information about a variety of objects in the network such as user accounts, computer accounts, groups, and all related credential information used by Kerberos [\[MS-KILE\]](#). **Active Directory** is either deployed as Active Directory Domain Services (AD DS) or Active Directory Lightweight Directory Services (AD LDS), which are both described in [\[MS-ADOD\]](#): Active Directory Protocols Overview.

Coordinated Universal Time (UTC): A high-precision atomic time standard that approximately tracks Universal Time (UT). It is the basis for legal, civil time all over the Earth. Time zones around the world are expressed as positive and negative offsets from UTC. In this role, it is also referred to as Zulu time (Z) and Greenwich Mean Time (GMT). In these specifications, all references to UTC refer to the time at UTC-0 (or GMT).

Domain Name System (DNS): A hierarchical, distributed database that contains mappings of domain names to various types of data, such as IP addresses. DNS enables the location of computers and services by user-friendly names, and it also enables the discovery of other information stored in the database.

fully qualified domain name (FQDN): An unambiguous domain name that gives an absolute location in the **Domain Name System's (DNS)** hierarchy tree, as defined in [\[RFC1035\]](#) section 3.1 and [\[RFC2181\]](#) section 11.

globally unique identifier (GUID): A term used interchangeably with universally unique identifier (UUID) in Microsoft protocol technical documents (TDs). Interchanging the usage of these terms does not imply or require a specific algorithm or mechanism to generate the value. Specifically, the use of this term does not imply or require that the algorithms described in [\[RFC4122\]](#) or [\[C706\]](#) must be used for generating the **GUID**. See also universally unique identifier (UUID).

security identifier (SID): An identifier for security principals that is used to identify an account or a group. Conceptually, the **SID** is composed of an account authority portion (typically a domain) and a smaller integer representing an identity relative to the account authority, termed the relative identifier (RID). The **SID** format is specified in [\[MS-DTYP\]](#) section 2.4.2; a string representation of **SIDs** is specified in [\[MS-DTYP\]](#) section 2.4.2 and [\[MS-AZOD\]](#) section 1.1.1.2.

service (SRV) resource record: A **Domain Name System (DNS)** resource record used to identify computers that host specific services, as specified in [\[RFC2782\]](#). SRV resource records are used to locate domain controllers (DCs) for **Active Directory**.

SOAP: A lightweight protocol for exchanging structured information in a decentralized, distributed environment. **SOAP** uses XML technologies to define an extensible messaging framework, which provides a message construct that can be exchanged over a variety of underlying protocols. The framework has been designed to be independent of any particular programming model and

other implementation-specific semantics. SOAP 1.2 supersedes SOAP 1.1. See [\[SOAP1.2-1/2003\]](#).

SOAP message: An XML document consisting of a mandatory SOAP envelope, an optional SOAP header, and a mandatory SOAP body. See [\[SOAP1.2-1/2007\]](#) section 5 for more information.

Transmission Control Protocol (TCP): A protocol used with the Internet Protocol (IP) to send data in the form of message units between computers over the Internet. TCP handles keeping track of the individual units of data (called packets) that a message is divided into for efficient routing through the Internet.

Uniform Resource Identifier (URI): A string that identifies a resource. The URI is an addressing mechanism defined in Internet Engineering Task Force (IETF) Uniform Resource Identifier (URI): Generic Syntax [\[RFC3986\]](#).

XML namespace: A collection of names that is used to identify elements, types, and attributes in XML documents identified in a URI reference [\[RFC3986\]](#). A combination of XML namespace and local name allows XML documents to use elements, types, and attributes that have the same names but come from different sources. For more information, see [\[XMLNS-2ED\]](#).

MAY, SHOULD, MUST, SHOULD NOT, MUST NOT: These terms (in all caps) are used as defined in [\[RFC2119\]](#). All statements of optional behavior use either MAY, SHOULD, or SHOULD NOT.

1.2 References

Links to a document in the Microsoft Open Specifications library point to the correct section in the most recently published version of the referenced document. However, because individual documents in the library are not updated at the same time, the section numbers in the documents may not match. You can confirm the correct section numbering by checking the [Errata](#).

1.2.1 Normative References

We conduct frequent surveys of the normative references to assure their continued availability. If you have any issue with finding a normative reference, please contact dochelp@microsoft.com. We will assist you in finding the relevant information.

[IANAPORT] IANA, "Service Name and Transport Protocol Port Number Registry",
<http://www.iana.org/assignments/service-names-port-numbers/service-names-port-numbers.xhtml>

[MS-KILE] Microsoft Corporation, "[Kerberos Protocol Extensions](#)".

[MS-NMFTB] Microsoft Corporation, "[.NET Message Framing TCP Binding Protocol](#)".

[MS-WSPOL] Microsoft Corporation, "[Web Services: Policy Assertions and WSDL Extensions](#)".

[RFC1518] Rekhter, Y., Watson, T.J., and Li, T., "An Architecture for IP Address Allocation with CIDR", RFC 1518, September 1993, <http://www.ietf.org/rfc/rfc1518.txt>

[RFC1519] Fuller, V., Li, T., Yu, J., and Varadhan, K., "Classless Inter-Domain Routing (CIDR): an Address Assignment and Aggregation Strategy", RFC 1519, September 1993,
<https://www.ietf.org/rfc/rfc1519.txt>

[RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", BCP 14, RFC 2119, March 1997, <https://www.rfc-editor.org/rfc/rfc2119.html>

[RFC2246] Dierks, T., and Allen, C., "The TLS Protocol Version 1.0", RFC 2246, January 1999,
<https://www.rfc-editor.org/info/rfc2246>

[RFC4120] Neuman, C., Yu, T., Hartman, S., and Raeburn, K., "The Kerberos Network Authentication Service (V5)", RFC 4120, July 2005, <https://www.rfc-editor.org/rfc/rfc4120>

[SOAP1.2-1/2007] Gudgin, M., Hadley, M., Mendelsohn, N., et al., "SOAP Version 1.2 Part 1: Messaging Framework (Second Edition)", W3C Recommendation, April 2007, <http://www.w3.org/TR/2007/REC-soap12-part1-20070427/>

[SOAP1.2-2/2007] Gudgin, M., Hadley, M., Mendelsohn, N., et al., "SOAP Version 1.2 Part 2: Adjuncts (Second Edition)", W3C Recommendation, April 2007, <http://www.w3.org/TR/2007/REC-soap12-part2-20070427/>

[WSADDSoapBind1.0] Gudgin, M., Hadley, M., and Rogers, T., Eds., "Web Services Addressing 1.0 - SOAP Binding", W3C Recommendation, May 2006, <http://www.w3.org/TR/2006/REC-ws-addr-soap-20060509/ws-addr-soap.pdf>

[WSDL] Christensen, E., Curbera, F., Meredith, G., and Weerawarana, S., "Web Services Description Language (WSDL) 1.1", W3C Note, March 2001, <https://www.w3.org/TR/2001/NOTE-wsdl-20010315>

[XMLNS-2ED] Bray, T., Hollander, D., Layman, A., and Tobin, R., Eds., "Namespaces in XML 1.0 (Second Edition)", W3C Recommendation, August 2006, <http://www.w3.org/TR/2006/REC-xml-names-20060816/>

[XMLSCHEMA1] Thompson, H., Beech, D., Maloney, M., and Mendelsohn, N., Eds., "XML Schema Part 1: Structures", W3C Recommendation, May 2001, <https://www.w3.org/TR/2001/REC-xmlschema-1-20010502/>

[XMLSCHEMA2] Biron, P.V., Ed. and Malhotra, A., Ed., "XML Schema Part 2: Datatypes", W3C Recommendation, May 2001, <https://www.w3.org/TR/2001/REC-xmlschema-2-20010502/>

1.2.2 Informative References

[MSDN-GetLocMachCert] Microsoft Corporation, "MachineIdentityManager.GetLocalMachineCert method", <http://msdn.microsoft.com/library/microsoft.windowsserversolutions.devices.identity.machineidentitymanager.getlocalmachinecert.aspx>

[MSDN-NETTcpBE] Microsoft Corporation, "TcpTransportBindingElement Class", <http://msdn.microsoft.com/en-us/library/system.servicemodel.channels.tcptransportbindingelement.aspx>

[MSDN-ProviderException] Microsoft Corporation, "ProviderException Class", <http://msdn.microsoft.com/library/microsoft.windowsserversolutions.common.providerframework.providerexception>

[MSDN-WSSSDK] Microsoft Corporation, "Windows Server Solutions SDK", <http://msdn.microsoft.com/library/gg513877.aspx>

[MSKB-2975719] Microsoft Corporation, "August 2014 update rollup for Windows RT 8.1, Windows 8.1, and Windows Server 2012 R2", <http://support.microsoft.com/kb/2975719>

1.3 Overview

The WCF-Based Encrypted Server Administration and Notification Protocol (Provider Framework) defines a series of WCF services that provide basic monitoring and manageability functionalities of the protocol server. Network administrators can use the protocol to monitor and manage the protocol server. It is a classic duplex mode client-server protocol.

The WCF services defined by Provider Framework are described in section [3](#). The data contracts used by these services are described in section [2.2](#).

1.4 Relationship to Other Protocols

The Provider Framework protocol uses **SOAP messages** to format the requests and responses as specified in [\[SOAP1.2-1/2007\]](#) and [\[SOAP1.2-2/2007\]](#). These SOAP messages are encrypted by the TcpTransportBindingElement Class described in [\[MSDN-NETTcpBE\]](#) and sent over the .NET Message Framing TCP Binding Protocol [\[MS-NMFTB\]](#), which is built on top of the TCP/IP protocol.




Figure 1: Protocol stack diagram

1.5 Prerequisites/Preconditions

This protocol operates against a protocol server that exposes a set of WCF service methods that are known by protocol clients.

Provider Framework services needs to be deployed on the protocol server for this protocol to work correctly.

The protocol also assumes that the authentication has been performed by the underlying protocols.

1.6 Applicability Statement

This protocol is intended for use by protocol clients and protocol servers that are connected by high-bandwidth, low-latency network connections.

1.7 Versioning and Capability Negotiation

This document covers versioning issues in the following areas:

- Supported transports:** This protocol can be implemented on top of **TCP** as discussed in section [2.1](#).
- Protocol versions:** This protocol is not versioned.
- Capability negotiation:** This protocol does not support version negotiation.

1.8 Vendor-Extensible Fields

Vendor-extensible fields can extend the Provider Framework by writing their own WCF services. This is done by using the Provider Framework API, which is included in the Windows Server Solutions SDK [\[MSDN-WSSSDK\]](#), to create a provider.

1.9 Standards Assignments

The Provider Framework protocol uses the following assignment:

Parameter	TCP Port	Reference
wsscomfrmwk	6602(0x19CA)	[IANAPORT]

2 Messages

2.1 Transport

This protocol transports messages using a TCP stream and specifies a framing for messages over a TCP stream. The protocol does not define a mechanism to establish the TCP connection; rather, an established TCP connection is a precondition for this protocol.

This protocol does not define any means for activating a protocol server or protocol client. The protocol server MUST be configured and begin listening in an implementation-specific way. Additionally, the protocol client MUST know the format and transport that is used by the protocol server, for example, the SOAP format over a TCP transport.

The protocol server MUST support formatting of **SOAP** over TCP/IP as specified in [\[MS-NMFTB\]](#).

All protocol messages MUST be transported by using **TCP** bindings at the transport level.

All protocol messages MUST be formatted as specified in [\[SOAP1.2-1/2007\]](#) or [\[SOAP1.2-2/2007\]](#).

The protocol MUST use Message Framing Security Provider WindowsTransportSecurity as specified in [\[MS-WSPOL\]](#) section 2.2.3.8 with the ProtectionLevel being EncryptAndSign.

2.2 Message Syntax

This section contains common definitions used by this protocol. The syntax of the definitions uses XML schema (XSD) as defined in [\[XMLSCHEMA1\]](#) and [\[XMLSCHEMA2\]](#), and Web Services Description Language as defined in [\[WSDL\]](#).

In the following sections, the schema definition might be less restrictive than the processing rules imposed by the protocol. The WSDL in this specification provides a base description of the schema. The text that introduces the WSDL specifies additional restrictions that reflect protocol behavior. For example, the schema definition might allow for an element to be empty, null, or not present, but the behavior of the protocol as specified restricts the same elements to being non-empty, present, and not null.

2.2.1 Namespaces

This specification defines and references various **XML namespaces** using the mechanisms specified in [\[XMLNS-2ED\]](#). Although this specification associates a specific XML namespace prefix for each XML namespace that is used, the choice of any particular XML namespace prefix is implementation-specific and not significant for interoperability.

Prefix	Namespace URI	Reference
None	http://www.microsoft.com/WindowsServerSolutions/ProviderFramework/Notifications/3/2010	
xsd	http://www.w3.org/2001/XMLSchema	[XMLSCHEMA1] [XMLSCHEMA2]
soap	http://schemas.xmlsoap.org/wsdl/soap/	[SOAP1.2-1/2007] [SOAP1.2-2/2007]
s	http://www.w3.org/2003/05/soap-envelope	[SOAP1.2-1/2007]
a	http://www.w3.org/2005/08/addressing	[WSADDSoapBind1]

Prefix	Namespace URI	Reference
		.01

2.2.2 Messages

Message	Description
Common Soap Fault	The structure of the common SOAP fault that is returned by the protocol server to the protocol client when there is an error processing the request.
Keepalive	The structure of the Keepalive message sent by the management client to the management server to detect loss of the underlying transport connection.

2.2.2.1 Common SOAP Fault

The SOAP fault message is defined in [\[SOAP1.2-1/2007\]](#). The following is the specific format used by this protocol.

```
<s:Envelope xmlns:s="http://www.w3.org/2003/05/soap-envelope">
  <s:Body>
    <s:Fault>
      <s:Code>
        <s:Value>s:Sender</s:Value>
      </s:Code>
      <s:Reason>
        <s:Text xml:lang="en-US">The creator of this fault did not specify a Reason.</s:Text>
      </s:Reason>
      <s:Detail>
        [ProviderException]
      </s:Detail>
    </s:Fault>
  </s:Body>
</s:Envelope>
```

The [ProviderException] element is the part of the message that provides more information about the fault itself. This will be of type

Microsoft.WindowsServerSolutions.Common.ProviderFramework.ProviderException [\[MSDN-ProviderException\]](#) or the types that extend the same.

2.2.2.2 Keepalive

Following is the **Keepalive** message that is transmitted by the protocol client in a period of inactivity and ignored by the server. This helps to detect the drop of the TCP session because of inactivity.

```
<s:Envelope xmlns:s="http://www.w3.org/2003/05/soap-envelope"
  xmlns:a="http://www.w3.org/2005/08/addressing">
  <s:Header>
    <a:Action
      s:mustUnderstand="1">Microsoft.WindowsServerSolutions.Common.ProviderFramework.Keepalive</a:Action>
  </s:Header>
  <s:Body/>
</s:Envelope>
```

2.2.3 Elements

This specification does not define any common XML schema element definitions.

2.2.4 Complex Types

The following table summarizes the set of common XML schema complex type definitions defined by this specification. XML Schema complex type definitions that are specific to a particular operation are described with the operation.

Complex Type	Description
ClientFileBackupException (section 2.2.4.1.1)	The errors in a client file backup provider.
ConfigurationSet (section 2.2.4.1.2)	The configuration settings for client file backups.
AutoExclusionSizesInfo (section 2.2.4.2.1)	Information about sizes of data automatically excluded from a backup.
PCBackupClientFault (section 2.2.4.2.2)	Information about an error occurring in the computer backup provider service.
PCBackupConfiguration (section 2.2.4.2.3)	The entire computer backup configuration as seen from management UI.
PCBackupServerFault (section 2.2.4.2.4)	Information about an error occurring in the computer backup server provider service.
PCBackupStatus (section 2.2.4.2.5)	The state of the current backup set operation.
BadFileInfo (section 2.2.4.2.6)	One file in the backup that contains a bad block.
ClientConfig (section 2.2.4.2.7)	All of the client configuration of a backup.
ClientConfigurationInfo (section 2.2.4.2.8)	The type of client configuration of a backup.
PCClientDataStatus	The status of backups for each client after repair.
ClientJobInfo (section 2.2.4.2.9)	Information about one machine-wide backup job.
ClientRepairStatus (section 2.2.4.2.10)	The status of backups for each client after repair.
ClientVolumeInfo (section 2.2.4.2.11)	Information for a one-client volume.
ConfigureBackupFault (section 2.2.4.2.12)	Information about an error occurring when configure backup for a client fails due to another configure backup being in progress.
ExcludedFolderInfo (section 2.2.4.2.13)	Information about one excluded folder.
FolderInfo (section 2.2.4.2.14)	Information about one folder.
FolderInfoGroup (section 2.2.4.2.15)	Information about a group of folders.
FolderRequest (section 2.2.4.2.16)	Data needed for Get Folder Children.
OperationStatusResponse (section 2.2.4.2.17)	The response of a Get Operation Status request.
ServiceStatusResponse (section 2.2.4.2.18)	The response of service status request.
VolumeJobInfo (section 2.2.4.2.19)	Information about a volume job.
WaitingOperation (section 2.2.4.2.20)	Information about a waiting operation.

Complex Type	Description
RepairResult (section 2.2.4.2.21)	Information about the result of a repair job.
AlertListChunk (section 2.2.4.3.1)	A portion of a list of alerts.
AlertInfo (section 2.2.4.3.2)	Information about a Network Health Alert.
UserContextTask (section 2.2.4.3.3)	Defines a task that is expected to be launched from a user context.
ClearCommand (section 2.2.4.3.4)	Clears an alert.
RaiseCommand (section 2.2.4.3.5)	Raises an alert.
SuppressCommand (section 2.2.4.3.6)	Suppresses an alert.
ReturnClass Type (section 2.2.4.4.1)	Describes the return class for the machine identity provider.
GetMachineStatusType (section 2.2.4.4.2)	The return of the get security identifier (SID) request.
PersonalInfo (section 2.2.4.5.1)	User personal information.
UserInfo (section 2.2.4.5.2)	Present information about a user.
UserFault (section 2.2.4.5.3)	Failure information for custom exceptions generated by a user identity provider call.
UserExceptionFault (section 2.2.4.5.4)	Failure information for errors generated by a user identity provider call.
ReturnClass (section 2.2.4.5.5)	Represents return codes for a user identity provider call
ProviderEndpointBehaviorAttribute (section 2.2.4.6.1)	An attribute used to decorate Provider contracts to specify their behavior.
ProviderInfo (section 2.2.4.6.2)	The information necessary to connect to a provider.
RequiredImpersonationLevelAttribute (section 2.2.4.6.3)	An attribute used to decorate Provider contracts to specify Impersonation Level.
PackageInfo (section 2.2.4.7.1)	The information about an add-in that is not contained in the normal metadata file.
ClientInstallFilter (section 2.2.4.7.2)	In which clients (if any) an add-in is installed.
Package (section 2.2.4.7.3)	Information used to describe and install an add-in package.
BinaryReference (section 2.2.4.7.4)	The information needed to install an MSI on a machine.
Filter (section 2.2.4.7.5)	Limits which computers a client add-in MSI will be installed to.
OtherBinariesMap (section 2.2.4.7.6)	The list of binaries for other client platforms.<1>
Preinstall (section 2.2.4.7.7)	The details of preinstall.
UninstallConfirm (section 2.2.4.7.8)	The details of UninstallCommand.
VPNSetting (section 2.2.4.8.1)	The information about an add-in that is not contained in the normal metadata file.
VirtualNetworkSettings (section 2.2.4.8.2)	The information about Azure Virtual Network settings
AddressPrefix (section 2.2.4.8.3)	An IP address range in Classless Inter-Domain Routing (CIDR) notion

Complex Type	Description
DomainProviderCredentials (section 2.2.4.9.1)	The credentials for a domain provider.
DomainManagerFault (section 2.2.4.9.2)	The fault generated by a domain manager.
DnsRecord (section 2.2.4.9.3)	A DNS record.
SrvRecord (section 2.2.4.9.4)	An SRV record in DNS.
ARecord (section 2.2.4.9.5)	An A record in DNS.
MXRecord (section 2.2.4.9.6)	A mail service (MX) record in DNS.
TxtRecord (section 2.2.4.9.7)	A text record in DNS.
CNameRecord (section 2.2.4.9.8)	A canonical name record in DNS.
DomainState (section 2.2.4.9.9)	The status of the domain.
CertificateState (section 2.2.4.9.10)	The status of the certificate.
DomainNameConfiguration (section 2.2.4.9.11)	The currently active domain name configuration.
Offering (section 2.2.4.9.12)	The domain name offering.
DynamicDNSInfo (section 2.2.4.9.13)	The information of dynamic DNS.
DomainProviderManagerSettings (section 2.2.4.9.14)	The settings for Domain Manager operation.
O365ConfigurationException (section 2.2.4.10.1)	An error in Microsoft Office 365 integration configurations.
NotificationResult (section 2.2.4.11.1)	The client notification result.
NotificationResults (section 2.2.4.11.2)	The client notification results.

2.2.4.1 Client File Backup Provider

2.2.4.1.1 ClientFileBackupException

The **ClientFileBackupException** type describes errors in client file backup provider.

```
<xs:complexType name="ClientFileBackupException">
  <xs:complexContent mixed="false">
    <xs:extension xmlns:q1="http://schemas.datacontract.org/2004/07/System"
      base="q1:Exception" />
  </xs:complexContent>
</xs:complexType>
```

2.2.4.1.2 ConfigurationSet

The **ConfigurationSet** type describes the global file backup configuration settings.

```
<xs:complexType name="ConfigurationSet">
  <xs:sequence>
```

```

<xs:element minOccurs="0" name="FrequencyInMinutes" type="xs:unsignedInt" />
<xs:element minOccurs="0" name="IsEnabled" type="xs:boolean" />
<xs:element minOccurs="0" name="RetentionInMonths" type="xs:unsignedInt" />
<xs:element minOccurs="0" name="SourceLibraries" type="tns:SourceLibrary" />
<xs:element minOccurs="0" name="TargetPath" nillable="true" type="xs:string" />
<xs:element minOccurs="0" name="UnmanagedClients" nillable="true" type="xs:string"
/>
</xs:sequence>
</xs:complexType>

```

FrequencyInMinutes: The backup frequency in minutes.

.IsEnabled: TRUE if the client file backup is enabled; otherwise, FALSE.

RetentionInMonths: The backup retention age in months.

SourceLibraries: The source libraries to back up.

TargetPath: The target folder's UNC path for the caller.

UnmanagedClients: The list of machine names of unmanaged clients, separated by the pipe (|) character.

2.2.4.2 Client Backup Provider

2.2.4.2.1 AutoExclusionSizesInfo

The **AutoExclusionSizesInfo** type describes information about sizes of data that are automatically excluded from a backup.

```

<xs:complexType name="AutoExclusionSizesInfo">
  <xs:sequence>
    <xs:element minOccurs="1" maxOccurs="1" name="ClientSideCache" type="xs:long" />
    <xs:element minOccurs="1" maxOccurs="1" name="TemporaryFiles" type="xs:long" />
    <xs:element minOccurs="1" maxOccurs="1" name="DigitalVideoRecorder" type="xs:long" />
    <xs:element minOccurs="1" maxOccurs="1" name="PageFile" type="xs:long" />
    <xs:element minOccurs="1" maxOccurs="1" name="RecycleBin" type="xs:long" />
    <xs:element minOccurs="1" maxOccurs="1" name="HibernationFile" type="xs:long" />
    <xs:element minOccurs="1" maxOccurs="1" name="MemoryDump" type="xs:long" />
    <xs:element minOccurs="1" maxOccurs="1" name="ShadowVolumes" type="xs:long" />
    <xs:element minOccurs="1" maxOccurs="1" name="Other" type="xs:long" />
  </xs:sequence>
</xs:complexType>

```

ClientSideCache: The size allocated for client side cache folders.

TemporaryFiles: The size allocated for user temporary files.

DigitalVideoRecorder: The size allocated for media center temporary files.

PageFile: The size allocated for the system page file.

RecycleBin: The size allocated for the recycle bin folder.

HibernationFile: The size allocated for the hibernation file.

MemoryDump: The size allocated for the memory dump file.

ShadowVolumes: The size allocated for shadow volume implementation folders.

Other: The size allocated for other automatic exclusions.

2.2.4.2.2 PCBackupClientFault

The **PCBackupClientFault** type contains information about an error that occurred in the computer backup client provider service.

```
<xs:complexType name="PCBackupClientFault">
  <xs:sequence>
    <xs:element minOccurs="1" maxOccurs="1" name="Reason" type="PCBackupClientFaultReason"
  />
    <xs:element minOccurs="0" maxOccurs="1" name="Description" type="xs:string" />
    <xs:element minOccurs="0" maxOccurs="1" name="Other" type="xs:string" />
  </xs:sequence>
</xs:complexType>
```

Reason: The fault reason.

Description: The fault description.

Other: Any other information.

2.2.4.2.3 PCBackupConfiguration

The **PCBackupConfiguration** type contains all the computer backup configurations as seen from management UI.

```
<xs:complexType name="PCBackupConfiguration">
  <xs:sequence>
    <xs:element minOccurs="1" maxOccurs="1" name="windowStartTime" type="TimeSpan" />
    <xs:element minOccurs="1" maxOccurs="1" name="windowEndTime" type="TimeSpan" />
    <xs:element minOccurs="1" maxOccurs="1" name="dailyRetainCount" type="xs:unsignedInt"
  />
    <xs:element minOccurs="1" maxOccurs="1" name="weeklyRetainCount" type="xs:unsignedInt"
  />
    <xs:element minOccurs="1" maxOccurs="1" name="monthlyRetainCount" type="xs:unsignedInt"
  />
    <xs:element minOccurs="1" maxOccurs="1" name="yearlyRetainCount" type="xs:unsignedInt"
  />
    <xs:element minOccurs="1" maxOccurs="1" name="alertDiskBytes" type="xs:long" />
  </xs:sequence>
</xs:complexType>
```

windowStartTime: The backup window start time.

windowEndTime: The backup window end time.

dailyRetainCount: The daily backup retain count.

weeklyRetainCount: The weekly backup retain count.

monthlyRetainCount: The monthly backup retain count.

yearlyRetainCount: The yearly backup retain count.

alertDiskBytes: The alert disk bytes.

2.2.4.2.4 PCBackupServerFault

The **PCBackupServerFault** type contains information about an error that occurred in the computer backup server provider service.

```

<xs:complexType name="PCBackupServerFault">
  <xs:sequence>
    <xs:element minOccurs="1" maxOccurs="1" name="Reason" type="PCBackupServerFaultReason"
    />
    <xs:element minOccurs="0" maxOccurs="1" name="Description" type="xs:string" />
    <xs:element minOccurs="0" maxOccurs="1" name="Other" type="xs:string" />
  </xs:sequence>
</xs:complexType>

```

Reason: The fault reason.

Description: The fault description.

Other: Any other information.

2.2.4.2.5 PCBackupStatus

The **PCBackupStatus** type describes the state of the current backup set operation.

```

<xs:complexType name="PCBackupStatus">
  <xs:sequence>
    <xs:element minOccurs="1" maxOccurs="1" name="clientJobStatus"
      type="ClientJobStatus" />
    <xs:element minOccurs="1" maxOccurs="1" name="progress" type="xs:int" />
    <xs:element minOccurs="1" maxOccurs="1" name="failureReason"
      type="AbortReason" />
    <xs:element minOccurs="1" maxOccurs="1" name="lastBackupTime"
      type="xs:dateTime" />
    <xs:element minOccurs="0" maxOccurs="1" name="IncompleteVolumeMountPoints"
      type="ArrayOfString" />
    <xs:element minOccurs="0" maxOccurs="1" name="IncompleteVolumeLabels"
      type="ArrayOfString" />
  </xs:sequence>
</xs:complexType>

```

clientJobStatus: The current job status.

progress: How far the backup has progressed in the current phase, 0 <= progress <= 100.

failureReason: The reason for the most recent failure. Set only if backup status is Failed.

lastBackupTime: The last backup time.

IncompleteVolumeMountPoints: The mount points of volumes that are yet to be backed up in current backup, as well as volumes that were not backed up if the last backup failed or was incomplete.

IncompleteVolumeLabels: The labels of volumes that are yet to be backed up in the current backup, as well as volumes that were not backed up if the last backup failed or was incomplete.

2.2.4.2.6 BadFileInfo

The **BadFileInfo** type describes one file in the backup that contains a bad block.

```

<xs:complexType name="BadFileInfo">
  <xs:sequence>
    <xs:element minOccurs="0" maxOccurs="1" name="Name" type="xs:string" />
    <xs:element minOccurs="1" maxOccurs="1" name="Size" type="xs:long" />
  </xs:sequence>
</xs:complexType>

```

Name: The name of the file.

Size: The size of the file.

2.2.4.2.7 ClientConfig

The **ClientConfig** type contains all the client configuration of a backup.

```
<xs:complexType name="ClientConfig">
  <xs:sequence>
    <xs:element minOccurs="1" maxOccurs="1" name="IsConfigured" type="xs:boolean" />
    <xs:element minOccurs="1" maxOccurs="1" name="AnyVolumesIncluded" type="xs:boolean" />
    <xs:element minOccurs="1" maxOccurs="1" name="WindowStart" type="xs:int" />
    <xs:element minOccurs="1" maxOccurs="1" name="WindowEnd" type="xs:int" />
  </xs:sequence>
</xs:complexType>
```

IsConfigured: TRUE if the backup is enabled; otherwise, FALSE.

AnyVolumesIncluded: TRUE if any volumes eligible for backup are included; otherwise FALSE. If backup is not enabled or not configured, then the value of this variable is irrelevant.

WindowStart: The backup window start time, in number of minutes from midnight.

WindowEnd: The backup window end time, in number of minutes from midnight.

2.2.4.2.8 ClientConfigurationInfo

The **ClientConfigurationInfo** type describes the type of client configuration of a backup.

```
<xs:complexType name="ClientConfigurationInfo">
  <xs:sequence>
    <xs:element minOccurs="0" maxOccurs="1" name="Sid" type="xs:string" />
    <xs:element minOccurs="0" maxOccurs="1" name="Name" type="xs:string" />
    <xs:element minOccurs="1" maxOccurs="1" name="IsOnline" type="xs:boolean" />
    <xs:element minOccurs="1" maxOccurs="1" name="IsConfigured" type="xs:boolean" />
    <xs:element minOccurs="1" maxOccurs="1" name="AllVolumesConfigured" type="xs:boolean" />
    <xs:element minOccurs="1" maxOccurs="1" name="AnyVolumesIncluded" type="xs:boolean" />
    <xs:element minOccurs="1" maxOccurs="1" name="JobsExist" type="xs:boolean" />
    <xs:element minOccurs="1" maxOccurs="1" name="LastGoodBackupTime" type="xs:dateTime" />
    <xs:element minOccurs="1" maxOccurs="1" name="LastBackupEnabledTime" type="xs:dateTime" />
    <xs:element minOccurs="1" maxOccurs="1" name="LastStatus" type="ClientJobStatus" />
  </xs:sequence>
</xs:complexType>
```

The following members SHOULD be used only for reading the property. Each is marked as writable only so that it can support the infrastructure.

Sid: The client machine SID, used to uniquely identify the client.

Name: The client machine name.

IsOnline: TRUE if the machine is online; otherwise FALSE.

IsConfigured: TRUE if client is configured for backup; otherwise FALSE.

AllVolumesConfigured: TRUE if all volumes are configured for backup; otherwise FALSE.

AnyVolumesIncluded: TRUE if at least one volume is included for backup; otherwise FALSE.

JobsExist: TRUE if a backup exists for the client; otherwise false.

LastGoodBackupTime: The time of the last successfully completed backup.

LastBackupEnabledTime: When the client was last enabled for backups.

LastStatus: The last backup status.

2.2.4.2.9 ClientJobInfo

The **ClientJobInfo** type describes one machine-wide backup job.

```
<xs:complexType name="ClientJobInfo">
  <xs:sequence>
    <xs:element minOccurs="1" maxOccurs="1" name="Index" type="xs:int" />
    <xs:element minOccurs="1" maxOccurs="1" name="StartTime" type="xs:dateTime" />
    <xs:element minOccurs="1" maxOccurs="1" name="Duration" type="TimeSpan" />
    <xs:element minOccurs="1" maxOccurs="1" name="BytesUsed" type="xs:long" />
    <xs:element minOccurs="1" maxOccurs="1" name="IsAutomatic" type="xs:boolean" />
    <xs:element minOccurs="0" maxOccurs="1" name="Description" type="xs:string" />
    <xs:element minOccurs="1" maxOccurs="1" name="Status" type="ClientJobStatus" />
    <xs:element minOccurs="1" maxOccurs="1" name="retentionState" type="RetentionState" />
    <xs:element minOccurs="1" maxOccurs="1" name="failureReason" type="AbortReason" />
    <xs:element minOccurs="0" maxOccurs="1" name="FailureDetails" type="ArrayOfString" />
  </xs:sequence>
</xs:complexType>
```

The following members SHOULD be used only for reading the property. Each is marked as writable only so that it can support the infrastructure.

Index: The backup job index.

StartTime: The backup start time.

Duration: The duration for which the backup ran.

BytesUsed: The bytes used on disk on the server for this backup.

IsAutomatic: TRUE if a scheduled backup; FALSE if manual.

Description: The backup job description.

Status: The backup job status.

retentionState: The retention state for the job, such as "marked for deletion", following the normal retention policy, or locked status.

failureReason: The failure reason for the job, or "none" if the job succeeded.

FailureDetails: The failure details for the job. Empty array or null if successful.

2.2.4.2.10 ClientRepairStatus

The **ClientRepairStatus** type describes the status of backups for each client after repair.

```
<xs:complexType name="ClientRepairStatus">
  <xs:sequence>
    <xs:element minOccurs="0" maxOccurs="1" name="Sid" type="xs:string" />
```

```

<xs:element minOccurs="1" maxOccurs="1" name="DataStatus" type="PCClientDataStatus" />
<xs:element minOccurs="0" maxOccurs="1" name="Name" type="xs:string" />
</xs:sequence>
</xs:complexType>

```

The following members SHOULD be used only for reading the property. Each is marked as writable only so that it can support the infrastructure.

Sid: The client SID, used to uniquely identify the client.

DataStatus: The status of backup for this client.

Name: The client name, used to identify a client to the user.

2.2.4.2.11 ClientVolumeInfo

The **ClientVolumeInfo** type describes a one-client volume.

```

<?xml version="1.0" encoding="utf-8"?>
<xs:complexType name="ClientVolumeInfo">
<xs:sequence>
<xs:element minOccurs="1" maxOccurs="1" name="guid"
  xmlns:q1="http://microsoft.com/wsdl/types/" type="q1:guid" />
<xs:element minOccurs="0" maxOccurs="1" name="uniqueIdBytes"
  type="ArrayOfUnsignedByte" />
<xs:element minOccurs="0" maxOccurs="1" name="MountPoint" type="xs:string" />
<xs:element minOccurs="0" maxOccurs="1" name="VolumeName" type="xs:string" />
<xs:element minOccurs="1" maxOccurs="1" name="Capacity" type="xs:long" />
<xs:element minOccurs="1" maxOccurs="1" name="BytesUsed" type="xs:long" />
<xs:element minOccurs="0" maxOccurs="1" name="FileSystem" type="xs:string" />
<xs:element minOccurs="1" maxOccurs="1" name="BytesPerSector" type="xs:int"
  />
<xs:element minOccurs="1" maxOccurs="1" name="BytesPerCluster" type="xs:int"
  />
<xs:element minOccurs="1" maxOccurs="1" name="Location" type="VolumeLocation"
  />
<xs:element minOccurs="1" maxOccurs="1" name="BackupBytes" type="xs:long" />
<xs:element minOccurs="1" maxOccurs="1" name="Status" type="VolumeStatus" />
<xs:element minOccurs="1" maxOccurs="1" name="IsEligibleForBackup"
  type="xs:boolean" />
<xs:element minOccurs="1" maxOccurs="1" name="JobsExist" type="xs:boolean" />
<xs:element minOccurs="0" maxOccurs="1" name="ExcludedFolders"
  type="ArrayOfString" />
</xs:sequence>
</xs:complexType>

```

The following members SHOULD be used only for reading the property. Each is marked as writable only so that it can support the infrastructure.

guid: The volume **GUID**.

uniqueIdBytes: The unique ID of the volume.

MountPoint: The volume mount point.

VolumeName: The name of the volume.

Capacity: The total capacity of the volume in bytes.

BytesUsed: The total number of bytes used on the volume.

FileSystem: The file system type of the volume.

BytesPerSector: The bytes per sector for the volume.

BytesPerCluster: The bytes per cluster for the volume.

Location: The volume location details, such as internal, external, and so on.

BackupBytes: The total number of bytes for backup on the volume.

Status: The volume status.

IsEligibleForBackup: TRUE if volume is eligible for backup; otherwise FALSE.

JobsExist: TRUE if any volume jobs exist for the volume; otherwise FALSE.

ExcludedFolders: A list of excluded folders.

2.2.4.2.12 ConfigureBackupFault

The **ConfigureBackupFault** type contains information about an error that occurred when configure backup for a client failed due to another configure backup being in progress.

```
<xs:complexType name="ConfigureBackupFault">
  <xs:sequence>
    <xs:element minOccurs="1" maxOccurs="1" name="Reason"
      type="ConfigureBackupFaultReason" />
    <xs:element minOccurs="0" maxOccurs="1" name="Description" type="xs:string"
      />
    <xs:element minOccurs="0" maxOccurs="1" name="Other" type="xs:string" />
  </xs:sequence>
</xs:complexType>
```

Reason: The fault reason.

Description: The fault description.

Other: Any other information, such as Exception Stack trace if needed for logging.

2.2.4.2.13 ExcludedFolderInfo

The **ExcludedFolderInfo** type describes one excluded folder.

```
<xs:complexType name="ExcludedFolderInfo">
  <xs:sequence>
    <xs:element minOccurs="0" maxOccurs="1" name="Name" type="xs:string" />
    <xs:element minOccurs="1" maxOccurs="1" name="Size" type="xs:long" />
    <xs:element minOccurs="1" maxOccurs="1" name="IsAutomatic" type="xs:boolean"
      />
  </xs:sequence>
</xs:complexType>
```

Name: The folder name.

Size: The folder size, excluding automatically excluded content.

IsAutomatic: TRUE, if and only if the folder is automatically excluded; otherwise FALSE.

2.2.4.2.14 FolderInfo

The **FolderInfo** type describes one folder.

```

<xs:complexType name="FolderInfo">
  <xs:sequence>
    <xs:element minOccurs="0" maxOccurs="1" name="Name" type="xs:string" />
    <xs:element minOccurs="1" maxOccurs="1" name="FileRecordIndex" type="xs:long" />
    <xs:element minOccurs="1" maxOccurs="1" name="UsedBytes" type="xs:long" />
    <xs:element minOccurs="1" maxOccurs="1" name="ExclusionReason" type="ExclusionReason"
  />
  <xs:element minOccurs="1" maxOccurs="1" name="IsFolder" type="xs:boolean" />
  <xs:element minOccurs="1" maxOccurs="1" name="HasChildren" type="xs:boolean" />
</xs:sequence>
</xs:complexType>

```

Name: The folder name.

FileRecordIndex: The file record index.

UsedBytes: The bytes used by this folder, including subfolders.

ExclusionReason: The exclusion reason.

IsFolder: TRUE only if the entry is a folder; otherwise FALSE.

HasChildren: TRUE, if this folder has children; otherwise, FALSE.

2.2.4.2.15 FolderInfoGroup

The **FolderInfoGroup** type describes a group of folders.

```

<xs:complexType name="FolderInfoGroup">
  <xs:sequence>
    <xs:element minOccurs="0" maxOccurs="1" name="FolderInfoList" type="ArrayOfFolderInfo"
  />
    <xs:element minOccurs="1" maxOccurs="1" name="TotalNumChildren" type="xs:int" />
  </xs:sequence>
</xs:complexType>

```

FolderInfoList: The list of folder information objects in the group.

TotalNumChildren: The total number of children in the group.

2.2.4.2.16 FolderRequest

The **FolderRequest** type describes the data needed for Get Folder Children.

```

<xs:complexType name="FolderRequest">
  <xs:sequence>
    <xs:element minOccurs="1" maxOccurs="1" name="volumeGuid"
      xmlns:q1="http://microsoft.com/wsdl/types/" type="q1:guid" />
    <xs:element minOccurs="1" maxOccurs="1" name="fileRecordIndex" type="xs:long" />
  </xs:sequence>
</xs:complexType>

```

volumeGuid: The GUID of the volume.

fileRecordIndex: The index of the file record.

2.2.4.2.17 OperationStatusResponse

The **OperationStatusResponse** type contains the response of a Get Operation Status request.

```

<xs:complexType name="OperationStatusResponse">
    <xs:sequence>
        <xs:element minOccurs="1" maxOccurs="1" name="Operation" type="PCBackupStatusOperation"
    />
        <xs:element minOccurs="0" maxOccurs="1" name="ClientSid" type="xs:string" />
        <xs:element minOccurs="0" maxOccurs="1" name="Machine" type="xs:string" />
        <xs:element minOccurs="1" maxOccurs="1" name="PercentDone" type="xs:int" />
        <xs:element minOccurs="1" maxOccurs="1" name="Phase" type="PCBackupVolumePhase" />
        <xs:element minOccurs="1" maxOccurs="1" name="RepairState" type="PCBackupRepairState"
    />
    </xs:sequence>
</xs:complexType>

```

Operation: The type of operation in progress.

ClientSid: The GUID of the client backing up or restoring, or Guid.Empty if none.

Machine: The name of the client backing up or restoring, or null if none.

PercentDone: The progress indicator of the current operation, from 0 to 100 percent.

Phase: The phase of the operation.

RepairState: The repair state of the operation.

2.2.4.2.18 ServiceStatusResponse

The **ServiceStatusResponse** type contains the response of a service status request.

```

<xs:complexType name="ServiceStatusResponse">
    <xs:sequence>
        <xs:element minOccurs="1" maxOccurs="1" name="Ready" type="xs:boolean" />
    </xs:sequence>
</xs:complexType>

```

Ready: TRUE only if the service is ready for requests; otherwise FALSE.

2.2.4.2.19 VolumeJobInfo

The **VolumeJobInfo** type contains information about a volume job.

```

<xs:complexType name="VolumeJobInfo">
    <xs:sequence>
        <xs:element minOccurs="0" maxOccurs="1" name="volumeInfo" type="ClientVolumeInfo" />
        <xs:element minOccurs="0" maxOccurs="1" name="uniqueIdBytes" type="xs:base64Binary" />
        <xs:element minOccurs="0" maxOccurs="1" name="MountPoint" type="xs:string" />
        <xs:element minOccurs="0" maxOccurs="1" name="VolumeName" type="xs:string" />
        <xs:element minOccurs="0" maxOccurs="1" name="FileSystem" type="xs:string" />
        <xs:element minOccurs="1" maxOccurs="1" name="BytesPerSector" type="xs:int" />
        <xs:element minOccurs="1" maxOccurs="1" name="BytesPerCluster" type="xs:int" />
        <xs:element minOccurs="1" maxOccurs="1" name="StartTimeUtc" type="xs:dateTime" />
        <xs:element minOccurs="1" maxOccurs="1" name="Duration" type="TimeSpan" />
        <xs:element minOccurs="1" maxOccurs="1" name="InitialCapacity" type="xs:long" />
        <xs:element minOccurs="1" maxOccurs="1" name="MinimumCapacity" type="xs:long" />
        <xs:element minOccurs="1" maxOccurs="1" name="BytesUsed" type="xs:long" />
        <xs:element minOccurs="1" maxOccurs="1" name="Status" type="VolumeJobStatus" />
        <xs:element minOccurs="0" maxOccurs="1" name="autoExclusionSizes"
            type="AutoExclusionSizesInfo" />
            <xs:element minOccurs="0" maxOccurs="1" name="ExcludedFolders"
            type="ArrayOfExcludedFolderInfo" />
                <xs:element minOccurs="0" maxOccurs="1" name="BadFiles" type="ArrayOfBadFileInfo" />
                    <xs:element minOccurs="1" maxOccurs="1" name="failureReason" type="AbortReason" />

```

```

<xs:element minOccurs="0" maxOccurs="1" name="FailureDetails" type="ArrayOfString" />
</xs:sequence>
</xs:complexType>

```

The following members SHOULD be used only for reading the property. Each is marked as writable so as to support the infrastructure.

volumeInfo: The volume details.

uniqueIdBytes: The unique ID of the volume at the time of backup.

MountPoint: The volume mount point at time of backup.

VolumeName: The volume name at time of backup.

FileSystem: The file system time at the time of backup.

BytesPerSector: The bytes per sector for the volume at the time of backup.

BytesPerCluster: The bytes per cluster for the volume at the time of backup.

StartTimeUtc: The **Coordinated Universal Time (UTC)** start time for the volume job.

Duration: The volume job duration.

InitialCapacity: The initial capacity of the volume during backup, in bytes.

MinimumCapacity: The minimum capacity of the volume required for restoring this volume backup.

BytesUsed: The bytes used for this volume job.

Status: The volume job status for the volume job.

autoExclusionSizes: The size of all auto-excluded folders.

ExcludedFolders: List of excluded folders.

BadFiles: Information about the file that contains a list of bad blocks on the volume.

failureReason: The failure reason for the volume job. If the job succeeded, this element SHOULD be set to "None".

FailureDetails: The failure details for the volume job. If the job succeeded, this element SHOULD be set to Null or an empty array.

2.2.4.2.20 WaitingOperation

The **WaitingOperation** type contains information about a waiting operation.

```

<xs:complexType name="WaitingOperation">
  <xs:sequence>
    <xs:element minOccurs="1" maxOccurs="1" name="Operation" type="PCBackupStatusOperation"
  />
    <xs:element minOccurs="0" maxOccurs="1" name="MachineSID" type="xs:string" />
    <xs:element minOccurs="0" maxOccurs="1" name="MachineName" type="xs:string" />
    <xs:element minOccurs="1" maxOccurs="1" name="PercentComplete" type="xs:int" />
  </xs:sequence>
</xs:complexType>

```

Operation: An indicator that the backup operation is queued.

MachineSID: The SID of the machine for which backup/restore is queued.

MachineName: The name of the machine for which backup/restore is queued.

PercentComplete: The progress indicator of the current operation, from 0 to 100 percent

2.2.4.2.21 RepairResult

The **RepairResult** type contains information about the result of a repair job.

```
<xs:complexType name="RepairResult">
  <xs:sequence>
    <xs:element minOccurs="0" name="ClientStatus" nillable="true"
      type="tns:ArrayOfClientRepairStatus" />
    <xs:element minOccurs="0" name="RepairStartTime" type="xs:dateTime" />
    <xs:element minOccurs="0" name="RepairState" type="tns:PCBackupRepairState" />
  </xs:sequence>
</xs:complexType>
```

ClientStatus: A list of client repair status values.

RepairStartTime: The start time of the repair job.

RepairState: The state of the repair job.

2.2.4.3 Health Provider

2.2.4.3.1 AlertListChunk

The **AlertListChunk** type describes a portion of a list of alerts.

```
<xs:complexType name="AlertListChunk">
  <xs:sequence>
    <xs:element minOccurs="0" name="Alerts" nillable="true"
      xmlns:q1="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.NetworkHea
      lth.AlertFramework" type="q1:ArrayOfAlertInfo" />
    <xs:element minOccurs="0" name="HasMore" type="xs:boolean" />
  </xs:sequence>
</xs:complexType>
```

Alerts: The alerts in this chunk.

HasMore: TRUE, if there are more alerts to be sent in another chunk; otherwise FALSE.

2.2.4.3.2 AlertInfo

The **AlertInfo** type contains informational data about a Network Health Alert.

```
<xs:complexType name="AlertInfo">
  <xs:sequence>
    <xs:element minOccurs="1" maxOccurs="1" name="InstanceId" type="Guid" />
    <xs:element minOccurs="1" maxOccurs="1" name="MachineName" type="xs:string" />
    <xs:element minOccurs="1" maxOccurs="1" name="MachineId" type="xs:string" />
    <xs:element minOccurs="1" maxOccurs="1" name="FeatureName" type="xs:string" />
    <xs:element minOccurs="1" maxOccurs="1" name="HealthDefinitionName" type="xs:string" />
    <xs:element minOccurs="1" maxOccurs="1" name="FeatureTitle" type="xs:string" />
    <xs:element minOccurs="1" maxOccurs="1" name="HealthDefinitionTitle" type="xs:string" />
  />
  <xs:element minOccurs="1" maxOccurs="1" name="Description" type="xs:string" />
  <xs:element minOccurs="1" maxOccurs="1" name="Severity" type="HealthStatus" />
```

```

<xs:element minOccurs="1" maxOccurs="1" name="ActionPerformed" type="xs:string" />
<xs:element minOccurs="1" maxOccurs="1" name="IsRepairDefined" type="xs:boolean" />
<xs:element minOccurs="1" maxOccurs="1" name="RepairActionPerformed" type="xs:string"
/>
<xs:element minOccurs="1" maxOccurs="1" name="DateAndTime" type="xs:dateTime" />
<xs:element minOccurs="1" maxOccurs="1" name="IsSystem" type="xs:boolean" />
<xs:element minOccurs="1" maxOccurs="1" name="TroubleshootSteps" type="xs:string" />
<xs:element minOccurs="1" maxOccurs="1" name="SupportLink" type="xs:string" />
<xs:element minOccurs="1" maxOccurs="1" name="Troubleshooter" type="UserContextTask" />
<xs:element minOccurs="1" maxOccurs="1" name="IsNew" type="xs:boolean" />
<xs:element minOccurs="1" maxOccurs="1" name="IsSuppressed" type="xs:boolean" />
<xs:element minOccurs="1" maxOccurs="1" name="LastSuppressedDateTime"
type="xs:dateTime" />
<xs:element minOccurs="1" maxOccurs="1" name="AdditionalInfo"
type="IEnumerable<string>" />
<xs:element minOccurs="1" maxOccurs="1" name="Escalate" type="xs:boolean" />
</xs:sequence>
</xs:complexType>

```

InstanceId: The instance ID of the alert.

MachineName: The name of the machine on which the alert is raised.

MachineId: Typically the SID of the client computer.

FeatureName: The name of the feature definition to which the health definition belongs.

HealthDefinitionName: The name of the feature definition for which the alert is raised.

FeatureTitle: The title of the health definition for which the alert is raised.

HealthDefinitionTitle: The title of the feature definition to which the health definition belongs.

Description: A description of the alert.

Severity: The health status.

ActionPerformed: The health definition alert action performed when the alert is detected.

IsRepairDefined: TRUE, if the alert is repairable; otherwise, FALSE.

RepairActionPerformed: The information about the health definition repair action performed when the alert is repaired.

DateAndTime: The date and time when the alert was raised.

IsSystem: TRUE, if the alert is a system alert; otherwise, FALSE.

TroubleshootSteps: The troubleshooting steps of the alert.

SupportLink: The support link of the alert.

Troubleshooter: Allows the user to launch the task from the Alert Viewer.

IsNew: TRUE, if the alert being raised is not already present; otherwise, FALSE.

IsSuppressed: TRUE, if the alert is suppressed; otherwise, FALSE.

LastSuppressedDateTime: The last time the alert was suppressed.

AdditionalInfo: A store of additional information bound to the alert.

Escalate: TRUE, if the alert will be escalated to the administrator through email; otherwise, FALSE.

2.2.4.3.3 UserContextTask

The **UserContextTask** type defines a task that is expected to be launched from a user context.

```
<xs:complexType name="UserContextTask">
  <xs:sequence>
    <xs:element minOccurs="0" name="Arguments" nillable="true" type="xs:string" />
    <xs:element minOccurs="0" name="Program" nillable="true" type="xs:string" />
    <xs:element minOccurs="0" name="Title" nillable="true" type="xs:string" />
  </xs:sequence>
</xs:complexType>
```

Arguments: The command line arguments to the program. These arguments can contain references to environment variables.

Program: The program path of the task. This path can contain references to environment variables.

Title: The title of the task.

2.2.4.3.4 ClearCommand

The **ClearCommand** type describes the command to clear an alert.

```
<xs:complexType name="ClearCommand">
  <xs:sequence>
    <xs:element minOccurs="1" maxOccurs="1" name="AlertInstanceId" type="Guid" />
    <xs:element minOccurs="1" maxOccurs="1" name="MachineId" type="xs:string"/>
    <xs:element minOccurs="1" maxOccurs="1" name="AlertDateAndTime" type="xs:dateTime" />
  </xs:sequence>
</xs:complexType>
```

AlertInstanceId: The instance SID of the alert.

MachineId: The SID of the target machine.

AlertDateAndTime: The alert date and time.

2.2.4.3.5 RaiseCommand

The **RaiseCommand** type describes the command to raise an alert.

```
<xs:complexType name="RaiseCommand">
  <xs:sequence>
    <xs:element minOccurs="1" maxOccurs="1" name="RaisedAlert" type="AlertInfo" />
  </xs:sequence>
</xs:complexType>
```

RaisedAlert: The alert that needs to be raised.

2.2.4.3.6 SuppressCommand

The **SuppressCommand** type describes the command to suppress an alert.

```
<xs:complexType name=" SecurityUpdateDetailProperty">
  <xs:sequence>
    <xs:element minOccurs="1" maxOccurs="1" name="AlertInstanceId" type="Guid" />
    <xs:element minOccurs="1" maxOccurs="1" name="MachineId" type="xs:string" />
    <xs:element minOccurs="1" maxOccurs="1" name="AlertDateAndTime" type="xs:dateTime" />
  </xs:sequence>
</xs:complexType>
```

```

<xs:element minOccurs="1" maxOccurs="1" name="Suppress" type="xs:boolean" />
<xs:element minOccurs="1" maxOccurs="1" name="SuppressTime" type="xs:dateTime" />
</xs:sequence>
</xs:complexType>

```

AlertInstanceId: The instance SID of the alert.

MachineId: The SID of the target machine.

AlertDateAndTime: The alert date and time.

Suppress: TRUE, if the user wants to suppress an alert; otherwise, FALSE.

SuppressTime: The date and time when the alert was suppressed.

2.2.4.3.7 PlugInInfo

The **PlugInInfo** type describes the data structure that is used to get the summary of the installed plug-in.

```

<xs:complexType name="PlugInInfo">
  <xs:sequence>
    <xs:element name="x003C_ConfigHashCode_x003E_k__BackingField" nillable="true"
      type="xs:base64Binary" />
    <xs:element name="x003C_DefinitionHashCode_x003E_k__BackingField" nillable="true"
      type="xs:base64Binary" />
    <xs:element name="_x003C_FeatureName_x003E_k__BackingField" nillable="true"
      type="xs:string" />
    <xs:element name="x003C_RelativePath_x003E_k__BackingField" nillable="true"
      type="xs:string" />
  </xs:sequence>
</xs:complexType>

```

_x003C_ConfigHashCode_x003E_k__BackingField: A BASE64 binary that contains the hash of the definition configuration file.

_x003C_DefinitionHashCode_x003E_k__BackingField: A BASE64 binary that contains the hash of the definition file.

_x003C_FeatureName_x003E_k__BackingField: A string that contains the name of the feature.

_x003C_RelativePath_x003E_k__BackingField: A string that contains the relative installed folder name under the feature definitions folder.

2.2.4.4 Machine Identity Provider

2.2.4.4.1 ReturnClass Type

The **ReturnClass** type describes the return class for the Machine Identity Provider.

```

<xs:complexType name="ReturnClass">
  <xs:sequence>
    <xs:element minOccurs="0" name="ErrorCatalog" type="tns:ErrorCatalogType" />
    <xs:element minOccurs="0" name="NativeError" type="xs:int" />
  </xs:sequence>
</xs:complexType>

```

ErrorCatalog: The ErrorCatalogType value of an error, if one occurred.

NativeError: The native error code if an error happened.

2.2.4.4.2 GetMachineStatusType

The **GetMachineStatusType** type contains the result of GetMachineStatus request.

```
<xs:complexType name="GetMachineStatusType">
  <xs:sequence>
    <xs:element minOccurs="1" maxOccurs="1" name="MaxClientComputer" type="xs:int" />
    <xs:element minOccurs="1" maxOccurs="1" name="CurrentClientComputer" type="xs:int" />
    <xs:element minOccurs="1" maxOccurs="1" name="MachineStatus" type="MachineStatus" />
  </xs:sequence>
</xs:complexType>
```

MaxClientComputer: The maximum number of clients allowed.

CurrentClientComputer: The current number of clients.

MachineStatus: The return status for the specified client machine.

2.2.4.5 User Identity Provider

2.2.4.5.1 PersonalInfo

The **PersonalInfo** type describes user personal information.

```
<xs:complexType name="PersonalInfo">
  <xs:sequence>
    <xs:element minOccurs="1" maxOccurs="1" name="IsLocalUser" type="xs:boolean" />
    <xs:element minOccurs="0" maxOccurs="1" name="UserFolder" type="xs:string" />
    <xs:element minOccurs="0" maxOccurs="1" name="FirstName" type="xs:string" />
    <xs:element minOccurs="0" maxOccurs="1" name="LastName" type="xs:string" />
    <xs:element minOccurs="1" maxOccurs="1" name="RemoteAccess" type="RemoteAccessType" />
    <xs:element minOccurs="1" maxOccurs="1" name="VpnAccess" type="RemoteAccessType" />
    <xs:element minOccurs="1" maxOccurs="1" name="AccessLevel" type="AccessLevelType" />
    <xs:element minOccurs="1" maxOccurs="1" name="IsBuiltIn" type="xs:boolean" />
    <xs:element minOccurs="1" maxOccurs="1" name="IsShowInUI" type="xs:boolean" />
  </xs:sequence>
</xs:complexType>
```

IsLocalUser: TRUE, if this is the local user; otherwise, FALSE.

UserFolder: The path of the shared folder belonging to this user.

FirstName: The first name of the user.

LastName: The last name of the user.

RemoteAccess: The remote access status of the user.

VpnAccess: The VPN access status of the user.

AccessLevel: The access level of the user.

IsBuiltIn: TRUE, if the user is built-in; otherwise, FALSE.

IsShowInUI: TRUE, if user will be shown in the UI; otherwise, FALSE.

2.2.4.5.2 UserInfo

The **UserInfo** type presents the information of a user.

```
<xs:complexType name="UserInfo">
  <xs:sequence>
    <xs:element minOccurs="0" maxOccurs="1" name="UserName" type="xs:string" />
    <xs:element minOccurs="0" maxOccurs="1" name="PersonalInfo" type="PersonalInfo" />
    <xs:element minOccurs="1" maxOccurs="1" name="UserStatus" type="UserStatus" />
    <xs:element minOccurs="1" maxOccurs="1" name="Warning" type="UserCustomExceptionCode" />
    <xs:element minOccurs="0" maxOccurs="1" name="WindowsSID" type="xs:string" />
    <xs:element minOccurs="0" maxOccurs="1" name="WindowsAccount" type="xs:string" />
    <xs:element minOccurs="0" maxOccurs="1" name="FullUserName" type="xs:string" />
  </xs:sequence>
</xs:complexType>
```

UserName: The name of the user.

PersonalInfo: The detailed personal information of the given user.

UserStatus: The status of the user.

Warning: The last error of import/update/add user.

WindowsSID: The SID of this user.[<2>](#)

WindowsAccount: The account of this user.[<3>](#)

FullUserName: The domain/server name of the user.

2.2.4.5.3 UserFault

The **UserFault** type contains failure information from a custom user identity provider call.

```
<xs:complexType name="UserFault">
  <xs:sequence>
    <xs:element minOccurs="0" name="ExceptionCode" type="xs:int" />
    <xs:element minOccurs="0" name="Message" nillable="true" type="xs:string" />
    <xs:element minOccurs="0" name="UserCode" type="tns:UserCustomExceptionCode" />
  </xs:sequence>
</xs:complexType>
```

ExceptionCode: The custom exception code.

Message: The custom error message.

UserCode: The user custom exception code.

2.2.4.5.4 UserExceptionFault

The **UserExceptionFault** type contains information about exceptions raised by a custom user identity provider call.

```
<xs:complexType name="UserExceptionFault">
  <xs:sequence>
    <xs:element minOccurs="0" name="ErrorCode" type="xs:int" />
    <xs:element minOccurs="0" name="Message" nillable="true" type="xs:string" />
    <xs:element minOccurs="0" name="UserErrorCode" type="tns:UserCustomExceptionCode" />
  </xs:sequence>
</xs:complexType>
```

ErrorCode: The custom error code.

Message: The custom error message.

UserErrorCode: The user custom exception code.

2.2.4.5.5 ReturnClass

The **ReturnClass** type represents return codes for a custom user identity provider call.

```
<xs:complexType name="ReturnClass">
  <xs:sequence>
    <xs:element minOccurs="0" name="NativeError" type="xs:int" />
    <xs:element minOccurs="0" name="UserCode" type="tns:UserCustomExceptionCode" />
  </xs:sequence>
</xs:complexType>
```

NativeError: The native error code.

UserCode: The user custom exception code.

2.2.4.6 Provider Registry Service

2.2.4.6.1 ProviderEndpointBehaviorAttribute

The **ProviderEndpointBehaviorAttribute** type describes the attribute to use to decorate Provider contracts to specify their behavior.

```
<xs:complexType name="ProviderEndpointBehaviorAttribute">
  <xs:sequence>
    <xs:element minOccurs="1" maxOccurs="1" name="EndpointCredentialType"
      type="CredentialType" />
    <xs:element minOccurs="0" maxOccurs="1" name="AllowedConnectionType"
      type="ConnectionSetting" />
  </xs:sequence>
</xs:complexType>
```

EndpointCredentialType: The credential type expected by a provider.

AllowedConnectionType: The connection setting used or expected by a provider.

2.2.4.6.2 ProviderInfo

The **ProviderInfo** type represents the information necessary to connect to a provider.

```
<xs:complexType name="ProviderInfo">
  <xs:sequence>
    <xs:element minOccurs="0" name="Address" nillable="true" type="xs:anyURI" />
    <xs:element minOccurs="0" name="Binding" nillable="true" type="xs:string" />
    <xs:element minOccurs="0" name="Connected" type="xs:boolean" />
    <xs:element minOccurs="0" name="Contract" nillable="true" type="xs:string" />
    <xs:element minOccurs="0" name="Host" nillable="true" type="xs:string" />
    <xs:element minOccurs="0" name="Identifier" nillable="true" type="xs:string" />
    <xs:element minOccurs="0" name="IsInProc" type="xs:boolean" />
    <xs:element minOccurs="0" name="ProviderEndpointBehavior" nillable="true"
      xmlns:q1="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.Common.ProviderFramework"
      type="q1:ProviderEndpointBehaviorAttribute" />
    <xs:element minOccurs="0" name="RequiredImpersonationLevel" nillable="true"
      xmlns:q2="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.Common.ProviderFramework"
      type="q2:RequiredImpersonationLevelAttribute" />
  </xs:sequence>
</xs:complexType>
```

```
</xs:sequence>
</xs:complexType>
```

Address: The **URI** of the provider.

Binding: The binding type to use for the provider.

Connected: TRUE, if the provider is currently connected; otherwise, FALSE.

Contract: The name of the contract of the provider, as a string.

Host: The host of this provider.

Identifier: The identifier of the provider. The identifier is used to differentiate between multiple providers that expose the same contract.

IsInProc: True if the provider is in-process loadable; otherwise, false.

ProviderEndpointBehavior: The endpoint behavior of the provider.

RequiredImpersonationLevel: The required client's impersonation level needed by the provider.

2.2.4.6.3 RequiredImpersonationLevelAttribute

The **RequiredImpersonationLevelAttribute** type describes the attribute to use to decorate provider contracts to specify the Impersonation Level.

```
<xs:complexType name="RequiredImpersonationLevelAttribute">
  <xs:sequence>
    <xs:element minOccurs="1" maxOccurs="1" name="Level" type="ImpersonationLevel" />
  </xs:sequence>
</xs:complexType>
```

Level: The impersonation level expected by the provider.

2.2.4.6.4 QuerySpecification

The **QuerySpecification** type describes the details of providers to query for.

```
<xs:complexType name="QuerySpecification">
  <xs:sequence>
    <xs:element minOccurs="0" name="Contract" nillable="true" type="xs:string" />
    <xs:element minOccurs="0" name="ProviderId" nillable="true" type="xs:string" />
    <xs:element minOccurs="0" name="Server" type="xs:boolean" />
  </xs:sequence>
</xs:complexType>
```

Contract: A string that contains the contract to query.

ProviderId: A string that contains the ID of the provider.

Server: A Boolean where TRUE indicates that the provider is for a server; otherwise, this value is FALSE.

2.2.4.7 Addin Management

2.2.4.7.1 PackageInfo

The **PackageInfo** type describes the information about an add-in that is not contained in the typical metadata file.

```
<xs:complexType name="PackageInfo">
  <xs:sequence>
    <xs:element minOccurs="0" name="Company" nillable="true" type="xs:string" />
    <xs:element minOccurs="0" name="ExpirationDateUtc" type="xs:dateTime" />
    <xs:element minOccurs="0" name="Filter" nillable="true"
      type="tns:ClientInstallFilter" />
    <xs:element minOccurs="0" name="Install" type="xs:boolean" />
    <xs:element minOccurs="0" name="InstallDateUtc" type="xs:dateTime" />
    <xs:element minOccurs="0" name="LastRedeployDate" type="xs:dateTime" />
    <xs:element minOccurs="0" name="Package" nillable="true" type="tns:Package" />
    <xs:element minOccurs="0" name="RenewalUri" nillable="true" type="xs:anyURI" />
    <xs:element minOccurs="0" name="UpdateType" type="tns:UpdateClassification" />
    <xs:element minOccurs="0" name="UpdateUri" nillable="true" type="xs:anyURI" />
    <xs:element minOccurs="0" name="UpdateVersion" nillable="true" type="xs:string" />
    <xs:element minOccurs="0" name="VersionOnServer" nillable="true" type="xs:string" />
  </xs:sequence>
</xs:complexType>
```

Company: The company that the add-in package is for. This is set only for add-ins that have a verified digital signature.

ExpirationDateUtc: The date on which the add-in package subscription will expire.
DateTime.MinValue means that there is no expiration date.

Filter: Determines which clients (if any) to install the add-in to.

Install: TRUE, if the add-in is meant to be installed; otherwise, FALSE.

InstallDateUtc: The time the add-in was first installed.

LastRedeployDate: The date of the last redeployment or of the initial install if there was not a redeploy.

Package: The actual add-in metadata.

RenewalUri: The address to show for renewing the add-in.

UpdateType: The type of update.

UpdateUri: The Uri of the latest update.

UpdateVersion: The version of the latest update.

VersionOnServer: The version of the package that is currently installed on the server. Used to prevent clients from installing/upgrading before the server has installed the package.

2.2.4.7.2 ClientInstallFilter

The **ClientInstallFilter** type indicates in which clients (if any) an add-in is installed.

```
<xs:complexType name="ClientInstallFilter">
  <xs:sequence>
    <xs:element minOccurs="0" name="clientSidList" nillable="true"
      xmlns:q3="http://schemas.microsoft.com/2003/10/Serialization/Arrays" type="q3:ArrayOfstring" />
    <xs:element minOccurs="0" name="listIsMachinesToInclude" type="xs:boolean" />
  </xs:sequence>
```

```
</xs:complexType>
```

clientSidList: The list of client machine SIDs, will always be sorted.

listIsMachinesToInclude: TRUE, if the list is of machines to be included; otherwise, FALSE.

2.2.4.7.3 Package

The **Package** type contains information used to describe and install an add-in package.

```
<xs:complexType name="Package">
  <xs:sequence>
    <xs:element name="Id" type="ser:guid" />
    <xs:element name="Version" nillable="true" type="xs:string" />
    <xs:element name="Name" nillable="true" type="xs:string" />
    <xs:element minOccurs="0" name="Allow32BitOn64BitClients" type="xs:boolean" />
    <xs:element minOccurs="0" name="ServerBinary" nillable="true"
      type="tns:BinaryCollection" />
      <xs:element minOccurs="0" name="ClientBinary32" nillable="true"
        type="tns:BinaryCollection" />
          <xs:element minOccurs="0" name="ClientBinary64" nillable="true"
            type="tns:BinaryCollection" />
              <xs:element minOccurs="0" name="SupportedSkus" nillable="true"
                type="tns:SkuCollection" />
                  <xs:element minOccurs="0" name="SupportUrl" nillable="true" type="xs:anyURI" />
                    <xs:element minOccurs="0" name="Location" nillable="true" type="xs:string" />
                      <xs:element minOccurs="0" name="PrivacyStatement" nillable="true" type="xs:anyURI" />
                        <xs:element minOccurs="0" name="OtherBinaries" nillable="true"
                          type="tns:OtherBinariesMap" />
                            <xs:element minOccurs="0" name="Preinstall" nillable="true" type="tns:Preinstall" />
                              <xs:element minOccurs="0" name="UninstallConfirm" nillable="true"
                                type="tns:UninstallConfirm" />
      </xs:sequence>
  </xs:complexType>
```

Id: The ID for the package.

Version: The version of the add-in package.

Name: The name of the package.

Allow32BitOn64BitClients: TRUE, if 64-bit clients fall back to the 32-bit binaries when no 64-bit binaries can be found; otherwise, FALSE.

ServerBinary: The binaries to install on the server.

ClientBinary32: The binary to install on 32-bit clients.

ClientBinary64: The binary to install on 64-bit clients.

SupportedSkus: A list of operating systems that are supported by this package.

SupportUrl: The support URL for add-in.

Location: Indicates whether the add-in integrates with an online service or mainly has functionality local to the server.

PrivacyStatement: A link to the privacy statement for the add-in.

OtherBinaries: Other client binaries.[<4>](#)

Preinstall: The specified preinstall command.

UninstallConfirm: The specified uninstall command to override the default action.

2.2.4.7.4 BinaryReference

The **BinaryReference** type encapsulates the information needed to install an MSI on a machine.

```
<xs:complexType name="BinaryReference">
  <xs:sequence>
    <xs:element name="ProductCode" type="ser:guid" />
    <xs:element name="Version" nillable="true" type="xs:string" />
    <xs:element name="Name" nillable="true" type="xs:string" />
    <xs:element minOccurs="0" name="Arguments" nillable="true" type="xs:string" />
    <xs:element minOccurs="0" name="Filter" nillable="true" type="tns:Filter" />
  </xs:sequence>
</xs:complexType>
```

ProductCode: The product code for the MSI to be installed.

Version: The version of the MSI to be installed.

Name: The name of the file to be installed.

Arguments: Any parameters that will be used to install the MSI.

Filter: The filter used to determine whether the binary applies to a given computer.

2.2.4.7.5 Filter

The Filter type limits which client computers the add-in MSI can be installed on.

```
<xs:complexType name="Filter">
  <xs:sequence>
    <xs:element minOccurs="0" name="MinOSVersion" nillable="true" type="xs:string" />
    <xs:element minOccurs="0" name="MaxOSVersion" nillable="true" type="xs:string" />
    <xs:element minOccurs="0" name="OSEdition"
      xmlns:q1="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.AddinInfrastructure"
      type="q1:OSEditions" />
    <xs:element minOccurs="0" name="Language" nillable="true" type="xs:string" />
    <xs:element minOccurs="0" name="IsLanguageFallback" type="xs:boolean" />
  </xs:sequence>
</xs:complexType>
```

MinOSVersion: The minimum OS version supported (inclusive).

MaxOSVersion: The maximum OS version supported (inclusive).

OSEdition: The supported OS editions.

Language: The supported OS languages.

IsLanguageFallback: TRUE, if this binary is to be used as the language fallback when the client OS language is not used as the language fallback; otherwise, false.

2.2.4.7.6 OtherBinariesMap

The **OtherBinariesMap** type describes the list of binaries for other client platforms.[<5>](#)

```
<xs:complexType name="OtherBinariesMap">
  <xs:annotation>
    <xs:appinfo>
```

```

<IsDictionary
  xmlns="http://schemas.microsoft.com/2003/10/Serialization/">true</IsDictionary>
  </xs:appinfo>
</xs:annotation>
<xs:sequence>
  <xs:element minOccurs="0" maxOccurs="unbounded" name="Item">
    <xs:complexType>
      <xs:sequence>
        <xs:element name="Target" nillable="true" type="xs:string" />
        <xs:element name="FileName" nillable="true" type="xs:string" />
      </xs:sequence>
    </xs:complexType>
  </xs:element>
</xs:sequence>
</xs:complexType>

```

Target: The key of the map.

FileName: The value of the map.

2.2.4.7.7 Preinstall

The **Preinstall** type describes the details of preinstall.

```

<xs:complexType name="Preinstall">
  <xs:sequence>
    <xs:element name="Executable" nillable="true" type="xs:string" />
    <xs:element minOccurs="0" name="NormalArgs" nillable="true" type="xs:string" />
    <xs:element minOccurs="0" name="SilentArgs" nillable="true" type="xs:string" />
    <xs:element minOccurs="0" name="IgnoreExitCode" type="xs:boolean" />
  </xs:sequence>
</xs:complexType>

```

Executable: The file name of executable; the path is relative inside the package.

NormalArgs: An argument for normal option.

SilentArgs: An argument for silent option.

IgnoreExitCode: Whether to ignore the exit code.

2.2.4.7.8 UninstallConfirm

The **UninstallConfirm** type describes the details of UninstallCommand.

```

<xs:complexType name="UninstallConfirm">
  <xs:sequence>
    <xs:element name="Executable" nillable="true" type="xs:string" />
    <xs:element minOccurs="0" name="Arguments" nillable="true" type="xs:string" />
  </xs:sequence>
</xs:complexType>

```

Executable: The file name of the executable.

Arguments: The arguments of the executable.

2.2.4.8 Network Service

2.2.4.8.1 VPNSetting

The **VPNSetting** type describes the information about an add-in that is not contained in the normal metadata file.

```
<xs:complexType name="VPNSetting">
  <xs:sequence>
    <xs:element minOccurs="0" name="ConnectionName" nillable="true" type="xs:string" />
    <xs:element minOccurs="0" name="InternetAddress" nillable="true" type="xs:string" />
    <xs:element minOccurs="0" name="IntranetDnsSuffix" nillable="true" type="xs:string" />
  </xs:sequence>
</xs:complexType>
```

ConnectionName: The name for the VPN connection (that is, both the phone-book entry name and the PPP adapter name).

InternetAddress: The connect-to address for the VPN connection. It can be either a public IP address or a **fully qualified domain name (FQDN)** that can be resolved on the Internet. VPN clients use this address to dial-up the VPN server.

IntranetDnsSuffix: The common suffix of the FQDNs of the computers on the private network, which will be set as the connection-specific DNS suffix of the PPP adapter on VPN clients. With these settings, nondomain-joined clients are able to resolve FQDNs of the computers on the private network.

2.2.4.8.2 VirtualNetworkSettings

The **VirtualNetworkSettings** type SHOULD [<6>](#) describe the Azure Virtual Network settings .

```
<xs:complexType name="VirtualNetworkSettings">
  <xs:sequence>
    <xs:element minOccurs="1" maxOccurs="1" name="Enabled" type="xs:boolean" />
    <xs:element minOccurs="0" maxOccurs="1" name="VpnDeviceName" nillable="true"
      type="xs:string" />
    <xs:element minOccurs="0" maxOccurs="1" name="VirtualNetworkAddressPrefixes"
      nillable="true"
      xmlns:q1="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.Networking
      " type="q1:ArrayOfAddressPrefix" />
  </xs:sequence>
</xs:complexType>
```

Enabled: TRUE if the Azure Virtual Network integration is enabled; otherwise, FALSE.

VpnDeviceName: The name of the local VPN device.

VirtualNetworkAddressPrefixes: The IP address ranges assigned to the Azure Virtual Network resources in Classless Inter-Domain Routing (CIDR) notation.

2.2.4.8.3 AddressPrefix

The **AddressPrefix** type SHOULD [<7>](#) describe an IP address range in Classless Inter-Domain Routing (CIDR) notation. For more information about Classless Inter-Domain Routing (CIDR), see [\[RFC1518\]](#) and [\[RFC1519\]](#).

```
<xs:complexType name="AddressPrefix">
  <xs:sequence>
    <xs:element minOccurs="0" maxOccurs="1" name="Address" nillable="true"
      xmlns:q2="http://schemas.datacontract.org/2004/07/System.Net" type="q2:IPAddress"/>
    <xs:element minOccurs="1" maxOccurs="1" name="PrefixLength" type="xs:int" />
  </xs:sequence>
</xs:complexType>
```

Address: The IP address of the Classless Inter-Domain Routing (CIDR) block.

PrefixLength: The prefix length of the Classless Inter-Domain Routing (CIDR) block.

2.2.4.8.4 IPAddress

The **IPAddress** type specifies an IP address independent of the address family.

```
<xs:complexType name="IPAddress">
  <xs:sequence>
    <xs:element name="m_Address" type="xs:long" />
    <xs:element
      xmlns:q1="http://schemas.datacontract.org/2004/07/System.Net.Sockets" name="m_Family"
      type="q1:AddressFamily" />
    <xs:element name="m_HashCode" type="xs:int" />
    <xs:element
      xmlns:q2="http://schemas.microsoft.com/2003/10/Serialization/Arrays"
      name="m_Numbers" nillable="true" type="q2:ArrayOfunsignedShort" />
    <xs:element name="m_ScopeId" type="xs:long" />
  </xs:sequence>
</xs:complexType>
```

m_Address: A long integer that represents an IPv4 address if the address family is InterNetwork; otherwise, it is 0.

m_Family: An **AddressFamily** (section [2.2.5.8.1](#)) simple type containing the address family of the address. The supported values for this are InterNetwork and InterNetworkV6.

m_HashCode: This is a reserved element and MUST be ignored.

m_Numbers: An array of unsigned short integers that represent the bytes of the IP address.

m_ScopeId: A long integer that represents the scope identifier of the address, if the address family is InterNetworkV6; otherwise, it MUST be ignored.

2.2.4.9 Domain Infrastructure Service

2.2.4.9.1 DomainProviderCredentials

The **DomainProviderCredentials** type carries credentials for the domain provider.

```
<xs:complexType name="DomainProviderCredentials">
  <xs:sequence>
    <xs:element minOccurs="0" name="Password" nillable="true" type="xs:string" />
    <xs:element minOccurs="0" name="UserName" nillable="true" type="xs:string" />
  </xs:sequence>
</xs:complexType>
```

Password: The password for the credential.

UserName: The user name for the credential.

2.2.4.9.2 DomainManagerFault

The **DomainManagerFault** type describes the fault generated by the domain manager.

```
<xs:complexType name="DomainManagerFault">
  <xs:sequence>
    <xs:element minOccurs="0" name="Detail" nillable="true" type="xs:string" />
    <xs:element minOccurs="0" name="Message" nillable="true" type="xs:string" />
  </xs:sequence>
</xs:complexType>
```

```

<xs:element minOccurs="0" name="Reason" type="tns:FailureReason" />
</xs:sequence>
</xs:complexType>

```

Detail: The details about this fault.

Message: A message about this fault.

Reason: The reason for this fault.

2.2.4.9.3 DnsRecord

The **DnsRecord** type describes a DNS record.

```

<xs:complexType name="DnsRecord">
  <xs:sequence>
    <xs:element minOccurs="0" name="Label" nillable="true" type="xs:string" />
    <xs:element minOccurs="0" name="TimeToLive" type="ser:duration" />
  </xs:sequence>
</xs:complexType>

```

Label: The label of the record.

TimeToLive: The time span within which the record is effective.

2.2.4.9.4 SrvRecord

The **SrvRecord** type describes a **service (SRV) resource record** in **DNS**.

```

<xs:complexType name="SrvRecord">
  <xs:complexContent mixed="false">
    <xs:extension base="tns:DnsRecord">
      <xs:sequence>
        <xs:element minOccurs="0" name="Port" type="xs:int" />
        <xs:element minOccurs="0" name="Priority" type="xs:int" />
        <xs:element minOccurs="0" name="Protocol" nillable="true" type="xs:string" />
        <xs:element minOccurs="0" name="Service" nillable="true" type="xs:string" />
        <xs:element minOccurs="0" name="Target" nillable="true" type="xs:string" />
        <xs:element minOccurs="0" name="Weight" type="xs:int" />
      </xs:sequence>
    </xs:extension>
  </xs:complexContent>
</xs:complexType>

```

Port: The port number of the service.

Priority: The priority of the target host. Lower values indicate greater priority.

Protocol: The transport protocol.

Service: The symbolic name of the desired service.

Target: The canonical name of the host providing the service.

Weight: A weighting factor for records with the same priority value.

2.2.4.9.5 ARecord

The **ARecord** type describes an A record in **DNS**.

```

<xs:complexType name="ARecord">
  <xs:complexContent mixed="false">
    <xs:extension base="tns:DnsRecord">
      <xs:sequence>
        <xs:element minOccurs="0" name="Address" nillable="true"
        xmlns:q1="http://schemas.datacontract.org/2004/07/System.Net" type="q1:IPAddress" />
      </xs:sequence>
    </xs:extension>
  </xs:complexContent>
</xs:complexType>

```

Address: The address of the DNS record.

2.2.4.9.6 MXRecord

The **MXRecord** type describes a mail service (MX) record in **DNS**.

```

<xs:complexType name="MXRecord">
  <xs:complexContent mixed="false">
    <xs:extension base="tns:DnsRecord">
      <xs:sequence>
        <xs:element minOccurs="0" name="MailExchange" nillable="true" type="xs:string" />
        <xs:element minOccurs="0" name="MailExchangePreference" type="xs:int" />
      </xs:sequence>
    </xs:extension>
  </xs:complexContent>
</xs:complexType>

```

MailExchange: The name or address of the mail Exchange server.

MailExchangePreference: The preference for mail Exchange server.

2.2.4.9.7 TxtRecord

The **TxtRecord** type describes a text record in **DNS**.

```

<xs:complexType name="TxtRecord">
  <xs:complexContent mixed="false">
    <xs:extension base="tns:DnsRecord">
      <xs:sequence>
        <xs:element minOccurs="0" name="Text" nillable="true" type="xs:string" />
      </xs:sequence>
    </xs:extension>
  </xs:complexContent>
</xs:complexType>

```

Text: The text for the record.

2.2.4.9.8 CNameRecord

The **CNameRecord** type describes a canonical name record in **DNS**.

```

<xs:complexType name="CNameRecord">
  <xs:complexContent mixed="false">
    <xs:extension base="tns:DnsRecord">
      <xs:sequence>
        <xs:element minOccurs="0" name="CanonicalName" nillable="true" type="xs:string" />
      </xs:sequence>
    </xs:extension>
  </xs:complexContent>
</xs:complexType>

```

```
</xs:complexType>
```

CanonicalName: The canonical name for the record.

2.2.4.9.9 DomainState

The **DomainState** type describes the status of the domain.

```
<xs:complexType name="DomainState">
  <xs:sequence>
    <xs:element minOccurs="0" name="ExpirationDate" type="xs:dateTime" />
    <xs:element minOccurs="0" name="Status" type="tns:DomainStatus" />
    <xs:element minOccurs="0" name="StatusDescription" nillable="true" type="xs:string" />
  </xs:sequence>
</xs:complexType>
```

ExpirationDate: The expiration date.

Status: The domain status.

StatusDescription: The description for domain status.

2.2.4.9.10 CertificateState

The **CertificateState** type describes the status of the certificate.

```
<xs:complexType name="CertificateState">
  <xs:sequence>
    <xs:element minOccurs="0" name="Status" type="tns:CertificateStatus" />
    <xs:element minOccurs="0" name="StatusDescription" nillable="true" type="xs:string" />
  </xs:sequence>
</xs:complexType>
```

Status: The certificate status.

StatusDescription: The description of the certificate status.

2.2.4.9.11 DomainNameConfiguration

The **DomainNameConfiguration** type represents the currently active domain name configuration.

```
<xs:complexType name="DomainNameConfiguration">
  <xs:sequence>
    <xs:element minOccurs="0" name="AccountName" nillable="true" type="xs:string" />
    <xs:element minOccurs="0" name="CertificateRenewInProgress" type="xs:boolean" />
    <xs:element minOccurs="0" name="CertificateRenewStatus" type="tns:CertificateStatus" />
    <xs:element minOccurs="0" name="CertificateStatus" type="tns:CertificateStatus" />
    <xs:element minOccurs="0" name="CertificateStatusDescription" nillable="true"
      type="xs:string" />
    <xs:element minOccurs="0" name="AutoConfiguredAnywhereAccessHostName" type="tns:Idn" />
    <xs:element minOccurs="0" name="AutoConfiguredInternetDomainFullName" type="tns:Idn" />
    <xs:element minOccurs="0" name="DomainPrefix" type="tns:Idn" />
    <xs:element minOccurs="0" name="DomainStatus" type="tns:DomainStatus" />
    <xs:element minOccurs="0" name="DomainStatusDescription" nillable="true" type="xs:string" />
  />
  <xs:element minOccurs="0" name="ExpirationDate" type="xs:dateTime" />
  <xs:element minOccurs="0" name="ManualModeEnabled" type="xs:boolean" />
  <xs:element minOccurs="0" name="Offering" nillable="true" type="tns:Offering" />
  <xs:element minOccurs="0" name="ProviderID" type="ser:guid" />
```

```
</xs:sequence>
</xs:complexType>
```

AccountName: The account name used by the user to configure this offering.

CertificateRenewInProgress: TRUE, if a certificate renew is in progress; otherwise, FALSE.

CertificateRenewStatus: The status of the certificate renew task.

CertificateStatus: The certificate status.

CertificateStatusDescription: The description of the certificate status.

AutoConfiguredAnywhereAccessHostName: If the domain was automatically configured, this element contains the relative domain name of a host address, which can then be used to access the server from other network locations.

AutoConfiguredInternetDomainFullName: If the domain was automatically configured, this element contains the absolute domain name of the forward-lookup domain zone on the Internet.

DomainPrefix: The domain name prefix.

DomainStatus: The domain status.

DomainStatusDescription: The description for the domain status.

ExpirationDate: The expiration date.

ManualModeEnabled: TRUE, if manual mode is enabled; otherwise, FALSE.

Offering: The domain offering.

ProviderID: The provider ID.

2.2.4.9.12 Offering

The **Offering** type describes the domain name offering.

```
<xs:complexType name="Offering">
  <xs:sequence>
    <xs:element minOccurs="0" name="AccountManagementUrl" nillable="true" type="xs:anyURI" />
    <xs:element minOccurs="0" name="AdditionalSites" nillable="true"
      xmlns:q2="http://schemas.datacontract.org/2004/07/System.Collections.ObjectModel"
      type="q2:ReadOnlyCollectionOfanyURI" />
    <xs:element minOccurs="0" name="Description" nillable="true" type="xs:string" />
    <xs:element minOccurs="0" name="EulaUrl" nillable="true" type="xs:anyURI" />
    <xs:element minOccurs="0" name="Icon" nillable="true" type="xs:base64Binary" />
    <xs:element minOccurs="0" name="MembershipServiceName" nillable="true" type="xs:string" />
    <xs:element minOccurs="0" name="MembershipServiceSignupUrl" nillable="true"
      type="xs:anyURI" />
    <xs:element minOccurs="0" name="MoreInfoUrl" nillable="true" type="xs:anyURI" />
    <xs:element minOccurs="0" name="Name" nillable="true" type="xs:string" />
    <xs:element minOccurs="0" name="ProviderID" type="ser:guid" />
    <xs:element minOccurs="0" name="SupportedDomainType" type="tns:DomainType" />
    <xs:element minOccurs="0" name="TroubleshootingUrl" nillable="true" type="xs:anyURI" />
  </xs:sequence>
</xs:complexType>
```

AccountManagementUrl: The account management URL.

AdditionalSites: A collection of additional sites.

Description: The description of the offering.

EulaUrl: The URL pointing to the EULA of the offering.

Icon: The icon of the offering.

MembershipServiceName: The membership service name.

MembershipServiceSignupUrl: The membership service signup URL.

MoreInfoUrl: The URL pointing to more information for the offering.

Name: The name of the offering.

ProviderID: The provider ID.

SupportedDomainType: A description of the supported domain type.

TroubleshootingUrl: A URL pointing to a troubleshooting webpage.

2.2.4.9.13 DynamicDNSInfo

The **DynamicDNSInfo** type describes the information of dynamic DNS.

```
<xs:complexType name="DynamicDNSInfo">
  <xs:sequence>
    <xs:element minOccurs="0" name="FailedDNSUpdateAttempts" type="xs:int" />
    <xs:element minOccurs="0" name="LastSuccessfulDNSUpdate" type="xs:dateTime" />
    <xs:element minOccurs="0" name="LastUpdatedIPAddress" nillable="true"
      xmlns:q3="http://schemas.datacontract.org/2004/07/System.Net" type="q3:IPAddress" />
  </xs:sequence>
</xs:complexType>
```

FailedDNSUpdateAttempts: Retrieves the number of unsuccessful DNS update attempts since the last successful update.

LastSuccessfulDNSUpdate: The time of the most recent successful DNS update.

LastUpdatedIPAddress: The most recently updated IP address by the dynamic DNS.

2.2.4.9.14 DomainProviderManagerSettings

The **DomainProviderManagerSettings** type describes settings for Domain Manager operation. At run-time, these settings are read-only. Administrators and/or tools can change these settings in the registry if needed.

```
<xs:complexType name="DomainProviderManagerSettings">
  <xs:sequence>
    <xs:element minOccurs="0" name="BypassProxyForLocalAddresses" type="xs:boolean" />
    <xs:element minOccurs="0" name="DNSUpdateInterval" type="ser:duration" />
    <xs:element minOccurs="0" name="DomainStatusQueryInterval" type="ser:duration" />
    <xs:element minOccurs="0" name="Environment" type="tns:DomainProviderEnvironment" />
    <xs:element minOccurs="0" name="Proxy" nillable="true" type="xs:string" />
  </xs:sequence>
</xs:complexType>
```

BypassProxyForLocalAddresses: TRUE, if the proxy for local addresses is bypassed; otherwise, FALSE.

DNSUpdateInterval: The DNS update interval.

DomainStatusQueryInterval: The domain status query interval.

Environment: The environment in which the provider is running.

Proxy: The proxy setting.

2.2.4.10 Office 365 Integration Service

2.2.4.10.1 O365ConfigurationException

The **O365ConfigurationException** type describes errors in Office 365 integration configurations.

```
<xs:complexType name="O365ConfigureException">
  <xs:complexContent mixed="false">
    <xs:extension xmlns:q1="http://schemas.datacontract.org/2004/07/System"
      base="q1:Exception" />
  </xs:complexContent>
</xs:complexType>
```

2.2.4.11 Client Notification Service

2.2.4.11.1 NotificationResult

The **NotificationResult** type describes the notification result in the client notification service.

```
<xs:complexType name="NotificationResult">
  <xs:sequence>
    <xs:element minOccurs="0" name="clientName" nillable="true" type="xs:string" />
    <xs:element minOccurs="0" name="result" type="xs:boolean" />
  </xs:sequence>
</xs:complexType>
```

clientName: A string that contains the name of the client.

result: A Boolean where TRUE indicates the notification is successfully sent to the client; otherwise, the value is FALSE.

2.2.4.11.2 NotificationResults

The **NotificationResults** type describes notification results in the client notification service.

```
<xs:complexType name="NotificationResults">
  <xs:sequence>
    <xs:list minOccurs="0" name="result" type="NotificationResult" />
  </xs:sequence>
</xs:complexType>
```

result: A list of **NotificationResults** (section [2.2.4.11.1](#)) that contains the results of the notifications.

2.2.4.11.3 Exception

The **Exception** type is an error complex type that contains information about a protocol server-side error. This complex type MUST only be included as part of a SOAP fault, as specified in section [2.2.4](#).

```

<xs:complexType name="Exception">
  <xs:sequence>
    <xs:any minOccurs="0" maxOccurs="unbounded" namespace="##local"
processContents="skip" />
  </xs:sequence>
  <xs:attribute ref="ser:FactoryType" />
</xs:complexType>

```

FactoryType: Specifies a factory class that can deserialize the type.

2.2.5 Simple Types

The following table summarizes the set of common XML Schema simple type definitions defined by this specification. XML Schema simple type definitions that are specific to a particular operation are described with the operation.

Simple Type	Description
SourceLibrary (section 2.2.5.1.1)	The SourceLibrary type contains the options governing which source libraries the client file backup provider will back up.
ManagedStatus (section 2.2.5.1.2)	The ManagedStatus type describes the computer managed status.
AbortReason (section 2.2.5.2.1)	The AbortReason type describes why a client backup job is aborted.
PCBackupClientFaultReason (section 2.2.5.2.2)	The PCBackupClientFaultReason type describes the type of fault that occurred in the client backup provider.
PCBackupProviderState (section 2.2.5.2.3)	The PCBackupProviderState type describes the state of the current backup set operation.
PCBackupStatusOperation (section 2.2.5.2.4)	The PCBackupStatusOperation type describes the operation status of the backup service.
PCBackupVolumePhase (section 2.2.5.2.5)	The PCBackupVolumePhase type describes the state of the current backup volume operation.
CleanupStatus (section 2.2.5.2.6)	The CleanupStatus type describes the status of the cleanup job.
PCClientDataStatus (section 2.2.5.2.7)	The PCClientDataStatus type describes the status of backups for each client after repair.
ClientHealth (section 2.2.5.2.8)	The ClientHealth type describes the client backup health status.
ClientJobStatus (section 2.2.5.2.9)	The ClientJobStatus type describes the status of client backup job.
ConfigureBackupFaultReason (section 2.2.5.2.10)	The ConfigureBackupFaultReason type contains the reason for an error that occurred when configuring the computer backup.
DatabaseState (section 2.2.5.2.11)	The DatabaseState type describes the state of the computer backup database.
ExclusionReason (section 2.2.5.2.12)	The ExclusionReason type describes why a file is excluded.
FailureReason (section 2.2.5.2.13)	The FailureReason type describes the reason for a backup failure.
MountPhase (section 2.2.5.2.14)	The MountPhase type describes the different phases of mounting a backup.

Simple Type	Description
PCBackupRepairState (section 2.2.5.2.15)	The PCBackupRepairState type describes the state of a backup repair operation.
RetentionState (section 2.2.5.2.16)	The RetentionState type describes backup jobs retention state.
StopReason (section 2.2.5.2.17)	The StopReason type describes why the computer backup service is stopped.
VolumeJobStatus (section 2.2.5.2.18)	The VolumeJobStatus type describes the configuration status of a volume.
VolumeLocation (section 2.2.5.2.19)	The VolumeLocation type indicates the location of a volume.
VolumeStatus (section 2.2.5.2.20)	The VolumeStatus type describes the configuration status of a volume.
PCBackupServerFaultReason (section 2.2.5.2.21)	The PCBackupServerFaultReason type indicates the type of fault that occurred in the client backup provider on the backup server.
TaskType (section 2.2.5.3.1)	The TaskType type represents type of tasks that the health provider processes.
HealthStatus (section 2.2.5.3.2)	The HealthStatus type represents the status of a health alert.
ErrorCatalogType (section 2.2.5.4.1)	The ErrorCatalogType describes the error catalog of the Machine provider call. It is used as error code.
MachineStatus (section 2.2.5.4.2)	The MachineStatus type describes the current status of a machine.
WSSServerGroupType (section 2.2.5.5.1)	The WSSServerGroupType type describes the type of group to which the user belongs.
UserCustomExceptionCode (section 2.2.5.5.2)	The UserCustomExceptionCode type describes the definition of the error code for the user operation in the user provider.
RemoteAccessType (section 2.2.5.5.3)	The RemoteAccessType type describes the type of remote access.
AccessLevelType (section 2.2.5.5.4)	The AccessLevelType type describes the type of access level.
UserStatus (section 2.2.5.5.5)	The UserStatus type describes the user status.
CredentialType (section 2.2.5.6.1)	The CredentialType type describes the type of credentials that will be used for client authentication on the provider.
ConnectionSetting (section 2.2.5.6.2)	The ConnectionSetting type describes the connection setting to decide what type of sources are allowed to access the provider.
ImpersonationLevel (section 2.2.5.6.3)	The ImpersonationLevel type defines security impersonation levels. Security impersonation levels govern the degree to which a server process can act on behalf of a client process.
UpdateClassification (section 2.2.5.7.1)	The UpdateClassification type represents the different types of updates that an add-in can have.
OSEditions (section 2.2.5.7.2)	The OSEditions type describes information about the operating system that is used to limit which clients a file is installed to.
AddInError (section 2.2.5.7.3)	The AddInError type represents the error ID strings that can be reported back from the download provider.

Simple Type	Description
FailureReason (section 2.2.5.9.1)	The FailureReason type represents the reason a failure occurred in the domain infrastructure service.
DomainStatus (section 2.2.5.9.2)	The DomainStatus type represents domain status from the point of view of the domain provider.
CertificateStatus (section 2.2.5.9.3)	The CertificateStatus type represents certificate status from the point of view of the domain provider.
DomainType (section 2.2.5.9.4)	The DomainType type describes the type of the domain supported.
DomainProviderEnvironment (section 2.2.5.9.5)	The DomainProviderEnvironment type describes the environment that the domain provider is running.
PasswordChangeStatus (section 2.2.5.10.2)	The PasswordChangeStatus type describes the status of a password change operation.

2.2.5.1 Client File Backup Provider

2.2.5.1.1 SourceLibrary

The **SourceLibrary** type contains the options governing which source libraries the client file backup provider will back up.

```
<xs:simpleType name="SourceLibrary">
  <xs:restriction base="xs:string">
    <xs:enumeration value="DocumentsAndDesktop" />
    <xs:enumeration value="NoMediaLibraries" />
    <xs:enumeration value="All" />
  </xs:restriction>
</xs:simpleType>
```

The following table describes the values for this type.

Value	Description
DocumentsAndDesktop	The provider will back up the client's documents library and desktop items.
NoMediaLibraries	The provider will back up all files except media libraries (picture, video, music).
All	The provider will back up all files supported by the file history.

2.2.5.1.2 ManagedStatus

The **ManagedStatus** type describes the computer managed status.

```
<xs:simpleType name="ManagedStatus">
  <xs:restriction base="xs:string">
    <xs:enumeration value="Managed" />
    <xs:enumeration value="NotManaged" />
    <xs:enumeration value="Unknown" />
  </xs:restriction>
</xs:simpleType>
```

The following table describes the values for this type.

Value	Description
Managed	The file backup feature on the client is managed by the server.
NotManaged	The file backup feature on the client is not managed by the server.
Unknown	The managed status is unknown.

2.2.5.2 Client Backup Provider

2.2.5.2.1 AbortReason

- The **AbortReason** type describes why a client backup job is aborted.

```

<xs:simpleType name="AbortReason">
    <xs:restriction base="xs:string">
        <xs:enumeration value="None" />
        <xs:enumeration value="Authentication" />
        <xs:enumeration value="VersionMismatch" />
        <xs:enumeration value="Cancel" />
        <xs:enumeration value="ServerUnreachable" />
        <xs:enumeration value="ClientVssProblem" />
        <xs:enumeration value="ClientVssInsufficientSpace" />
        <xs:enumeration value="ClientIoError" />
        <xs:enumeration value="ClientException" />
        <xs:enumeration value="DBErrors" />
        <xs:enumeration value="ConnectionLost" />
        <xs:enumeration value="NotConfigured" />
        <xs:enumeration value="ServerFailure" />
        <xs:enumeration value="Unknown" />
        <xs:enumeration value="VolumeMissing" />
        <xs:enumeration value="CantOpenVolume" />
        <xs:enumeration value="BadFileSystem" />
        <xs:enumeration value="DBIsOffline" />
        <xs:enumeration value="EspCaptureFailed" />
    </xs:restriction>
</xs:simpleType>

```

The following table describes the values for this type.

Value	Description
None	No abort occurred; never send this.
Authentication	Authentication problem.
VersionMismatch	Mismatch between server side and client side protocol versions.
Cancel	Operation canceled by user.
ServerUnreachable	Server could not be contacted.
ClientVssProblem	VSS problem on client.
ClientVssInsufficientSpace	Insufficient space on client for a VSS snapshot.
ClientIoError	Disk I/O error on client.
ClientException	Unexpected exception on client.
DBErrors	Server database is corrupt.

Value	Description
ConnectionLost	Connection was lost after backup was started.
NotConfigured	Either the client or the volume is not configured for backup.
ServerFailure	Unexpected exception on server.
Unknown	Failed due to unknown reason.
VolumeMissing	Volume is currently missing.
CantOpenVolume	Volume could not be opened.
BadFileSystem	Volume's file system is not supported.
DBIsOffline	Backup database is currently offline.
EspCaptureFailed	Backup engine failed to capture ESP.

2.2.5.2.2 PCBackupClientFaultReason

The **PCBackupClientFaultReason** type describes the type of fault that occurred in the client backup provider.

```
<xs:simpleType name="PCBackupClientFaultReason">
  <xs:restriction base="xs:string">
    <xs:enumeration value="ServerNotReachable" />
    <xs:enumeration value="ClientNotConfigured" />
    <xs:enumeration value="Unknown" />
  </xs:restriction>
</xs:simpleType>
```

The following table describes the values for this type.

Value	Description
ServerNotReachable	ServerProvider is not reachable.
ClientNotConfigured	Client is not configured.
Unknown	Unknown error.

2.2.5.2.3 PCBackupProviderState

The **PCBackupProviderState** type describes the state of the current backup set operation.

```
<xs:simpleType name="PCBackupProviderState">
  <xs:restriction base="xs:string">
    <xs:enumeration value="Disconnected" />
    <xs:enumeration value="NotConfigured" />
    <xs:enumeration value="Connected" />
  </xs:restriction>
</xs:simpleType>
```

The following table describes the values for this type.

Value	Description
Disconnected	Server is not available.
NotConfigured	Client is not configured for backup.
Connected	Server is connected.

2.2.5.2.4 PCBackupStatusOperation

The **PCBackupStatusOperation** type describes the operation status of the backup service.

```
<xs:simpleType name="PCBackupStatusOperation">
  <xs:restriction base="xs:string">
    <xs:enumeration value="None" />
    <xs:enumeration value="DeleteBackup" />
    <xs:enumeration value="Cleanup" />
    <xs:enumeration value="Backup" />
    <xs:enumeration value="PrepareRestore" />
    <xs:enumeration value="BasicChecker" />
    <xs:enumeration value="ComprehensiveChecker" />
    <xs:enumeration value="Suspend" />
    <xs:enumeration value="Repair" />
    <xs:enumeration value="Unknown" />
  </xs:restriction>
</xs:simpleType>
```

The following table describes the values for this type.

Value	Description
None	Backup server is idle.
DeleteBackup	Delete backups of a volume OR remove machine.
Cleanup	Database cleanup is in progress.
Backup	Backup operation is in progress.
PrepareRestore	Preparation phase of restore is in progress
BasicChecker	Basic consistency checker (BCC).
ComprehensiveChecker	Comprehensive consistency checker (CCC).
Suspend	A suspend operation (external).
Repair	Backup repair is in progress.
Unknown	Backup service is not reachable.

2.2.5.2.5 PCBackupVolumePhase

The **PCBackupVolumePhase** type describes the state of the current backup volume operation.

```
<xs:simpleType name="PCBackupVolumePhase">
  <xs:restriction base="xs:string">
    <xs:enumeration value="Idle" />
    <xs:enumeration value="ScanFileRecords" />
    <xs:enumeration value="ScanClusters" />
    <xs:enumeration value="Reorganize1" />
```

```

<xs:enumeration value="SendClusters" />
<xs:enumeration value="Reorganize2" />
<xs:enumeration value="Complete" />
</xs:restriction>
</xs:simpleType>

```

The following table describes the values for this type.

Value	Description
Idle	No volume operation in progress.
ScanFileRecords	Phase 1: Determining which file records have changed.
ScanClusters	Phase 2: Determining which clusters have changed.
Reorganize1	Phase 3: Reorganizing data on the server.
SendClusters	Phase 4: Sending data to the server.
Reorganize2	Phase 5: Reorganizing data on the server.
Complete	Volume completed.

2.2.5.2.6 CleanupStatus

The **CleanupStatus** type describes the status of the cleanup job.

```

<xs:simpleType name="CleanupStatus">
  <xs:restriction base="xs:string">
    <xs:enumeration value="None" />
    <xs:enumeration value="Running" />
    <xs:enumeration value="CancelRequested" />
    <xs:enumeration value="Completed" />
    <xs:enumeration value="Cancelled" />
    <xs:enumeration value="CleanupStatusPendingRestore" />
    <xs:enumeration value="CleanupStatusDBErrors" />
  </xs:restriction>
</xs:simpleType>

```

The following table describes the values for this type.

Value	Description
None	No cleanup attempted since the last server start.
Running	Cleanup is currently running.
CancelRequested	Cleanup is running; cancel has been requested.
Completed	Most recent cleanup completed successfully.
Cancelled	Most recent cleanup was canceled.
CleanupStatusPendingRestore	Cleanup could not run due to pending restores.
CleanupStatusDBErrors	Cleanup could not run due to database errors.

2.2.5.2.7 PCClientDataStatus

The **PCClientDataStatus** type describes the status of backups for each client after repair.

```
<xs:simpleType name="PCClientDataStatus">
  <xs:restriction base="xs:string">
    <xs:enumeration value="NoLoss" />
    <xs:enumeration value="PartialLoss" />
    <xs:enumeration value="FullLoss" />
  </xs:restriction>
</xs:simpleType>
```

The following table describes the values for this type.

Value	Description
NoLoss	All backups were preserved after repair.
PartialLoss	Some backups were lost after repair.
FullLoss	All backups were lost for this machine.

2.2.5.2.8 ClientHealth

The **ClientHealth** type describes the client backup health status.

```
<xs:simpleType name="ClientHealth">
  <xs:restriction base="xs:string">
    <xs:enumeration value="Unknown" />
    <xs:enumeration value="Normal" />
    <xs:enumeration value="Warning" />
    <xs:enumeration value="Error" />
  </xs:restriction>
</xs:simpleType>
```

The following table describes the values for this type.

Value	Description
Unknown	No information.
Normal	Backups on schedule.
Warning	Missed a few backups.
Error	Missed several backups.

2.2.5.2.9 ClientJobStatus

The **ClientJobStatus** type describes the status of client backup job.

```
<xs:simpleType name="ClientJobStatus">
  <xs:restriction base="xs:string">
    <xs:enumeration value="Complete" />
    <xs:enumeration value="Incomplete" />
    <xs:enumeration value="Failed" />
    <xs:enumeration value="InProgress" />
    <xs:enumeration value="InQueue" />
  </xs:restriction>
</xs:simpleType>
```

The following table describes the values for this type.

Value	Description
Complete	Job completed successfully. All configured volumes were backed up successfully.
Incomplete	Backup of at least one configured volume failed or skipped because volume was not available or broken because of data loss after backup.
Failed	Backup of every volume failed or every volume was skipped.
InProgress	Backup job is in progress. Backup of at least one volume is in progress or not started.
InQueue	Backup job is queued/waiting.

2.2.5.2.10 ConfigureBackupFaultReason

The **ConfigureBackupFaultReason** type contains the reason for an error that occurred when configuring the computer backup.

```
<xs:simpleType name="ConfigureBackupFaultReason">
  <xs:restriction base="xs:string">
    <xs:enumeration value="ConfigurationInProgress" />
  </xs:restriction>
</xs:simpleType>
```

The following table describes the values for this type.

Value	Description
ConfigurationInProgress	Another configuration is in progress.

2.2.5.2.11 DatabaseState

The **DatabaseState** type describes the state of the computer backup database.

```
<xs:simpleType name="DatabaseState">
  <xs:restriction base="xs:string">
    <xs:enumeration value="Unknown" />
    <xs:enumeration value="Healthy" />
    <xs:enumeration value="DBHasErrors" />
    <xs:enumeration value="DBIsNew" />
    <xs:enumeration value="DBIsOld" />
  </xs:restriction>
</xs:simpleType>
```

The following table describes the values for this type.

Value	Description
Unknown	Database state is unknown.
Healthy	Database is online without any errors.
DBHasErrors	Database is online with errors.
DBIsNew	Database is offline because it is newer than code.
DBIsOld	Database is offline because it is older than code.

2.2.5.2.12 ExclusionReason

The **ExclusionReason** type describes why a file is excluded.

```
<xs:simpleType name="ExclusionReason">
  <xs:restriction base="xs:string">
    <xs:enumeration value="NotExcluded" />
    <xs:enumeration value="ClientSideCache" />
    <xs:enumeration value="TemporaryFiles" />
    <xs:enumeration value="DigitalVideoRecorder" />
    <xs:enumeration value="PageFile" />
    <xs:enumeration value="RecycleBin" />
    <xs:enumeration value="HibernationFile" />
    <xs:enumeration value="MemoryDump" />
    <xs:enumeration value="ShadowVolumes" />
    <xs:enumeration value="Other" />
    <xs:enumeration value="Count" />
  </xs:restriction>
</xs:simpleType>
```

The following table describes the values for this type.

Value	Description
NotExcluded	File is not excluded.
ClientSideCache	File is excluded because it is a client-side cache file.
TemporaryFiles	File is excluded because it is a temporary file.
DigitalVideoRecorder	File is excluded because it is a digital video recorder file.
PageFile	File is excluded because it is a page file.
RecycleBin	File is excluded because it is in the recycle bin.
HibernationFile	File is excluded because it is a hibernation file.
MemoryDump	File is excluded because it is a memory dump.
ShadowVolumes	File is excluded because it is a shadow volume file.
Other	File is excluded because of some other reason.
Count	Count of items in this enumeration.

2.2.5.2.13 FailureReason

The **FailureReason** type describes the reason for a backup failure.

```
<xs:simpleType name="FailureReason">
  <xs:restriction base="xs:string">
    <xs:enumeration value="Unknown" />
    <xs:enumeration value="NotAuthed" />
    <xs:enumeration value="InvalidSID" />
    <xs:enumeration value="ServerBusy" />
    <xs:enumeration value="MaxRestoreSessions" />
    <xs:enumeration value="DBErrors" />
    <xs:enumeration value="VolumeMissing" />
    <xs:enumeration value="BackupSetMissing" />
    <xs:enumeration value="BackupFailed" />
    <xs:enumeration value="RestoreVerifierFailed" />
    <xs:enumeration value="DBIsOffline" />
```

```

</xs:restriction>
</xs:simpleType>

```

The following table describes the values for this type.

Value	Description
Unknown	Unknown failure reason.
NotAuthed	User is not authorized to perform this operation.
InvalidSID	Invalid client SID.
ServerBusy	Server is busy.
MaxRestoreSessions	Reached maximum number of simultaneous restore sessions.
DBErrors	Backup database has errors.
VolumeMissing	Requested volume GUID not in the volume configuration file.
BackupSetMissing	Requested backup set not in backup set file.
BackupFailed	Requested backup is marked as failed backup.
RestoreVerifierFailed	Restore verifier detected an error during preparation.
DBIsOffline	Backup database is currently offline.

2.2.5.2.14 MountPhase

The **MountPhase** type describes the different phases of mounting a backup.

```

<xs:simpleType name="MountPhase">
  <xs:restriction base="xs:string">
    <xs:enumeration value="MountConnect" />
    <xs:enumeration value="MountAuthenticate" />
    <xs:enumeration value="MountLocateComputer" />
    <xs:enumeration value="MountLocateBackup" />
    <xs:enumeration value="MountLocateVolume" />
    <xs:enumeration value="MountMountVolume" />
    <xs:enumeration value="MountExploreVolume" />
  </xs:restriction>
</xs:simpleType>

```

The following table describes the values for this type.

Value	Description
MountConnect	Connect to the server.
MountAuthenticate	Authenticate the connection.
MountLocateComputer	Locate source computer.
MountLocateBackup	Locate source backup set.
MountLocateVolume	Locate source volume.

Value	Description
MountMountVolume	Actually mount the volume.
MountExploreVolume	Allow exploring the mounted volume.

2.2.5.2.15 PCBackupRepairState

The **PCBackupRepairState** type describes the state of a backup repair operation.

```
<xs:simpleType name="PCBackupRepairState">
  <xs:restriction base="xs:string">
    <xs:enumeration value="NotStarted" />
    <xs:enumeration value="RepairNoErrors" />
    <xs:enumeration value="RepairDBIsNew" />
    <xs:enumeration value="RepairDBIsOld" />
    <xs:enumeration value="RepairInProgress" />
    <xs:enumeration value="RepairSucceeded" />
    <xs:enumeration value="RepairFailed" />
    <xs:enumeration value="RepairCanceled" />
    <xs:enumeration value="Unknown" />
  </xs:restriction>
</xs:simpleType>
```

The following table describes the values for this type.

Value	Description
NotStarted	Repair is starting. Not started yet.
RepairNoErrors	No database errors. Repair did not run.
RepairDBIsNew	Database is new. Repair did not run.
RepairDBIsOld	Database is old. Repair did not run.
RepairInProgress	Repair is running.
RepairSucceeded	Repair succeeded, for example, fixed all errors.
RepairFailed	Repair failed, for example, could not fix all errors.
RepairCanceled	Repair was canceled by user.
Unknown	Repair state is unknown.

2.2.5.2.16 RetentionState

The **RetentionState** type describes backup jobs retention state.

```
<xs:simpleType name="RetentionState">
  <xs:restriction base="xs:string">
    <xs:enumeration value="Delete" />
    <xs:enumeration value="Normal" />
    <xs:enumeration value="Locked" />
  </xs:restriction>
</xs:simpleType>
```

The following table describes the values for this type.

Value	Description
Delete	Delete this job at next cleanup.
Normal	Delete this job when it is outside of retention policy.
Locked	Do not automatically delete this job.

2.2.5.2.17 StopReason

The **StopReason** type describes why the computer backup service is stopped.

```
<xs:simpleType name="StopReason">
  <xs:restriction base="xs:string">
    <xs:enumeration value="None" />
    <xs:enumeration value="DatabaseRestore" />
    <xs:enumeration value="DatabaseRepair" />
    <xs:enumeration value="DatabaseLocationChanged" />
  </xs:restriction>
</xs:simpleType>
```

The following table describes the values for this type.

Value	Description
None	This is not used.
DatabaseRestore	Service is stopped because the database is being restored.
DatabaseRepair	Service is stopped because the database is being repaired.
DatabaseLocationChanged	Service is stopped because the database location has changed.

2.2.5.2.18 VolumeJobStatus

The **VolumeJobStatus** type describes the configuration status of a volume.

```
<xs:simpleType name="VolumeJobStatus">
  <xs:restriction base="xs:string">
    <xs:enumeration value="Complete" />
    <xs:enumeration value="Broken" />
    <xs:enumeration value="Failed" />
    <xs:enumeration value="Cancelled" />
    <xs:enumeration value="Skipped" />
    <xs:enumeration value="CheckPoint" />
    <xs:enumeration value="NotStarted" />
    <xs:enumeration value="InProgress" />
  </xs:restriction>
</xs:simpleType>
```

The following table describes the values for this type.

Value	Description
Complete	Volume backup completed successfully. Volume can be used for restoration successfully.
Broken	Volume backup is broken due to data loss. Volume can be used for restoration but restore might fail.

Value	Description
Failed	Volume backup failed. Volume backup cannot be used for restoration.
Cancelled	Volume backup canceled. Volume backup cannot be used for restoration.
Skipped	Volume backup skipped. Volume backup cannot be used for restoration.
CheckPoint	Volume backup was completed but marked as a checkpoint. Volume backup cannot be used for restoration.
NotStarted	Volume backup has not started yet. Volume backup cannot be used for restoration.
InProgress	Volume backup is in progress.

2.2.5.2.19 VolumeLocation

The **VolumeLocation** type indicates the location of a volume.

```
<xs:simpleType name="VolumeLocation">
  <xs:restriction base="xs:string">
    <xs:enumeration value="Missing" />
    <xs:enumeration value="Internal" />
    <xs:enumeration value="External" />
  </xs:restriction>
</xs:simpleType>
```

The following table describes the values for this type.

Value	Description
Missing	Volume is not attached to the client.
Internal	Volume is attached and not removable.
External	Volume is attached but removable.

2.2.5.2.20 VolumeStatus

The **VolumeStatus** type describes the configuration status of a volume.

```
<xs:simpleType name="VolumeStatus">
  <xs:restriction base="xs:string">
    <xs:enumeration value="NotConfigured" />
    <xs:enumeration value="Exclude" />
    <xs:enumeration value="Include" />
  </xs:restriction>
</xs:simpleType>
```

The following table describes the values for this type.

Value	Description
NotConfigured	User has not indicated whether to back up this volume.
Exclude	Exclude this volume from backups.
Include	Include this volume in backups.

2.2.5.2.21 PCBackupServerFaultReason

The **PCBackupServerFaultReason** type indicates the type of fault that occurred in the client backup provider on the backup server.

```
<xs:simpleType name="PCBackupServerFaultReason">
  <xs:restriction base="xs:string">
    <xs:enumeration value="ClientNotReachable" />
    <xs:enumeration value="ClientNotConfigured" />
    <xs:enumeration value="ServiceBusy" />
    <xs:enumeration value="ServiceNotReachable" />
    <xs:enumeration value="ClientNotFound" />
    <xs:enumeration value="ClientJobNotFound" />
    <xs:enumeration value="ClientVolumeNotFound" />
    <xs:enumeration value="RepairRunning" />
    <xs:enumeration value="DBHasErrors" />
    <xs:enumeration value="DBIsOffline" />
    <xs:enumeration value="ArgumentOutOfRange" />
    <xs:enumeration value="UnexpectedError" />
  </xs:restriction>
</xs:simpleType>
```

The following table describes the values for this type.

Value	Description
ClientNotReachable	Client cannot be reached.
ClientNotConfigured	Client is not configured for backup.
ServiceBusy	Backup service is busy.
ServiceNotReachable	Backup service cannot be reached.
ClientNotFound	Client was not found.
ClientJobNotFound	Client job was not found.
ClientVolumeNotFound	Client volume was not found.
RepairRunning	Repair operation is running.
DBHasErrors	Error occurred in the backup database.
DBIsOffline	Backup database is offline.
ArgumentOutOfRange	Invalid argument.
UnexpectedError	Unexpected error occurred.

2.2.5.3 Health Provider

2.2.5.3.1 TaskType

The **TaskType** type represents type of tasks that the health provider processes.

```
<xs:simpleType name="TaskType">
  <xs:restriction base="xs:string">
    <xs:enumeration value="Raise" />
    <xs:enumeration value="Evaluate" />
    <xs:enumeration value="Clear" />
    <xs:enumeration value="Update" />
```

```

</xs:restriction>
</xs:simpleType>

```

The following table describes the values for this type.

Value	Description
Raise	Represents raising an alert via an API call.
Evaluate	Represents evaluating local alerts.
Clear	Clearing an alert via an API call.
Update	Updates an alert via an API call.

2.2.5.3.2 HealthStatus

The **HealthStatus** type represents the status of a health alert.

```

<xs:simpleType name="HealthStatus">
  <xs:restriction base="xs:string">
    <xs:enumeration value="OK" />
    <xs:enumeration value="Information" />
    <xs:enumeration value="Warning" />
    <xs:enumeration value="Critical" />
    <xs:enumeration value="Report" />
  </xs:restriction>
</xs:simpleType>

```

The following table describes the values for this type.

Value	Description
OK	The alert is not active.
Information	The alert is an information alert.
Warning	The alert is a warning alert.
Critical	The alert is a critical alert.
Report	The alert is a report containing additional information.

2.2.5.3.3 StreamBody

The **StreamBody** type represents a BASE64 encoded stream of data.

```

<xs:simpleType name="StreamBody">
  <xs:restriction base="xs:base64Binary" />
</xs:simpleType>

```

2.2.5.4 Machine Identity Provider

2.2.5.4.1 ErrorCatalogType

The **ErrorCatalogType** describes the error catalog of the Machine provider call. It is used as error code.

```

<xs:simpleType name="ErrorCatalogType">
  <xs:restriction base="xs:string">
    <xs:enumeration value="Succeeded" />
    <xs:enumeration value="MachineExists" />
    <xs:enumeration value="NetworkError" />
    <xs:enumeration value="CAError" />
    <xs:enumeration value="InvalidUser" />
    <xs:enumeration value="InvalidOwnerOfMachine" />
    <xs:enumeration value="InvalidCert" />
    <xs:enumeration value="ProviderNotAvailable" />
    <xs:enumeration value="AccessDenied" />
    <xs:enumeration value="TooManyComputers" />
    <xs:enumeration value="OtherError" />
  </xs:restriction>
</xs:simpleType>

```

The following table describes the values for this type.

Value	Description
Succeeded	The call succeeded.
MachineExists	Found the same Certificate in the Server, and the Enroll is not a forced enrollment.
NetworkError	An HTTPS error occurred.
CAError	Any error reported back from the certificate authority.
InvalidUser	The user credentials are incorrect. The detailed error code will be a native error code.
InvalidOwnerOfMachine	The machine object is not owned by the user.
InvalidCert	The certificate has expired.
ProviderNotAvailable	The dependent provider is not available.
AccessDenied	The current user does not have the required permissions.
TooManyComputers	Too many computers.
OtherError	All other errors.

2.2.5.4.2 MachineStatus

The **MachineStatus** type describes the current status of a machine.

```

<xs:simpleType name="MachineStatus">
  <xs:restriction base="xs:string">
    <xs:enumeration value="Active" />
    <xs:enumeration value="Deactive" />
    <xs:enumeration value="ActiveWithCert" />
    <xs:enumeration value="DeactiveWithCert" />
    <xs:enumeration value="NotExists" />
  </xs:restriction>
</xs:simpleType>

```

The following table describes the values for this type.

Value	Description
Active	The machine is active.

Value	Description
Deactive	The machine is disabled or inactive.
ActiveWithCert	The machine is active with a certificate.
DeactiveWithCert	The machine is disabled or inactive with a certificate.
NotExists	The machine does not exist.

2.2.5.5 User Identity Provider

2.2.5.5.1 WSServerGroupType

The **WSServerGroupType** type describes the type of group to which the user belongs.

```
<xs:simpleType name="WSServerGroupType">
  <xs:restriction base="xs:string">
    <xs:enumeration value="InvalidAccess" />
    <xs:enumeration value="RemoteAccess" />
    <xs:enumeration value="ShareAccess" />
    <xs:enumeration value="ComputerAccess" />
    <xs:enumeration value="MediaAccess" />
    <xs:enumeration value="AddInAccess" />
    <xs:enumeration value="DashboardAccess" />
    <xs:enumeration value="HomePageLinks" />
    <xs:enumeration value="NetworkAlertAccess" />
    <xs:enumeration value="VpnAccess" />
  </xs:restriction>
</xs:simpleType>
```

The following table describes the values for this type.

Value	Description
InvalidAccess	InvalidAccess Group.
RemoteAccess	Global group that defines whether the user can log into the Remote Web Access (RWA).
ShareAccess	A user in this group can see the same shares they would if the user were internal on the network.
ComputerAccess	A user in this group can connect to the computers the user could if they were internal on the network.
MediaAccess	A user in this group has access to media components of the RWA as well as WMP RME Vail.
AddInAccess	A user in this group can see web-enabled add-ins.
DashboardAccess	A user in this group gets a link to the server dashboard in their RWA.
HomePageLinks	A user in this group can see the administrator-defined links on the home page.
NetworkAlertAccess	Network Alert Administrators. The user in this group is the alert administrator.
VpnAccess	A user in this group can access via VPN.

2.2.5.5.2 UserCustomExceptionCode

The **UserCustomExceptionCode** type describes the definition of the error code for the user operation in the user provider.

```

<xs:simpleType name="UserCustomExceptionCode">
  <xs:restriction base="xs:string">
    <xs:enumeration value="Succeeded" />
    <xs:enumeration value="WinLogonFailed" />
    <xs:enumeration value="UserExists" />
    <xs:enumeration value="UserNotExist" />
    <xs:enumeration value="ProviderNotAvailable" />
    <xs:enumeration value="AccessDenied" />
    <xs:enumeration value="TooManyUsers" />
    <xs:enumeration value="CreateUserSharedFolderFailed" />
    <xs:enumeration value="Failed" />
  </xs:restriction>
</xs:simpleType>

```

The following table describes the values for this type.

Value	Description
Succeeded	The user operation succeeded.
WinLogonFailed	Account does not exist, or the password of the account is wrong.
UserExists	User already exists.
UserNotExist	User does not exist.
ProviderNotAvailable	Dependent provider not available.
AccessDenied	Caller does not have the access required for this operation.
TooManyUsers	User number limit exceeds the policy per the Eula.
CreateUserSharedFolderFailed	Cannot create user folder.
Failed	General failure for any other reason.

2.2.5.5.3 RemoteAccessType

The **RemoteAccessType** type describes the type of remote access.

```

<xs:simpleType name="RemoteAccessType">
  <xs:restriction base="xs:string">
    <xs:enumeration value="Unknown" />
    <xs:enumeration value="Allowed" />
    <xs:enumeration value="NotAllowed" />
  </xs:restriction>
</xs:simpleType>

```

The following table describes the values for this type.

Value	Description
Unknown	Remote access type is unknown.
Allowed	Remote access is allowed.
NotAllowed	Remote access is not allowed.

2.2.5.5.4 AccessLevelType

The **AccessLevelType** type describes the type of access level.

```
<xs:simpleType name="AccessLevelType">
  <xs:restriction base="xs:string">
    <xs:enumeration value="Unknown" />
    <xs:enumeration value="Guest" />
    <xs:enumeration value="User" />
    <xs:enumeration value="Administrator" />
  </xs:restriction>
</xs:simpleType>
```

The following table describes the values for this type.

Value	Description
Unknown	Access level type is unknown.
Guest	Guest account.
User	Standard user account.
Administrator	Administrator account.

2.2.5.5.5 UserStatus

The **UserStatus** type describes the user status.

```
<xs:simpleType name="UserStatus">
  <xs:restriction base="xs:string">
    <xs:enumeration value="Disabled" />
    <xs:enumeration value="Enabled" />
    <xs:enumeration value="Error" />
  </xs:restriction>
</xs:simpleType>
```

The following table describes the values for this type.

Value	Description
Disabled	It is disabled.
Enabled	It is enabled.
Error	User creation encountered an error.

2.2.5.6 Provider Registry Service

2.2.5.6.1 CredentialType

The **CredentialType** type describes the type of credentials that will be used for client authentication on the provider.

```
<xs:simpleType name="CredentialType">
  <xs:restriction base="xs:string">
    <xs:enumeration value="User" />
    <xs:enumeration value="Machine" />
    <xs:enumeration value="None" />
  </xs:restriction>
</xs:simpleType>
```

```
</xs:simpleType>
```

The following table describes the values for this type.

Value	Description
User	Client credential type will be tied to the user. <8>
Machine	Client credential type will be tied to the machine. <9>
None	No client credential will be used.

2.2.5.6.2 ConnectionSetting

The **ConnectionSetting** type describes the connection setting to decide what type of sources are allowed to access the provider.

```
<xs:simpleType name="ConnectionSetting">
  <xs:restriction base="xs:string">
    <xs:enumeration value="AllowLocalAccessOnly" />
    <xs:enumeration value="AllowRemoteAccess" />
  </xs:restriction>
</xs:simpleType>
```

The following table describes the values for this type.

Value	Description
AllowLocalAccessOnly	Allows the provider to accept incoming connections based on whether they are from the local host computer or the remote connection.
AllowRemoteAccess	Allows the provider to accept incoming connections from the local host and to have remote access to the host computer.

2.2.5.6.3 ImpersonationLevel

The **ImpersonationLevel** type defines security impersonation levels. Security impersonation levels govern the degree to which a server process can act on behalf of a client process.

```
<xs:simpleType name="ImpersonationLevel">
  <xs:restriction base="xs:string">
    <xs:enumeration value="Identification" />
    <xs:enumeration value="Impersonation" />
  </xs:restriction>
</xs:simpleType>
```

The following table describes the values for this type.

Value	Description
Identification	The server process can obtain information about the client, such as security identifiers and privileges, but it cannot impersonate the client. This is useful for servers that export their own objects, such as database products that export tables and views. Using the retrieved client-security information, the server can make access-validation decisions without being able to use other services that are using the client's security context.

Value	Description
Impersonation	The server process can impersonate the client's security context on its local system, but not on remote systems.

2.2.5.7 Addin Management

2.2.5.7.1 UpdateClassification

The **UpdateClassification** type represents the different types of updates that an add-in can have.

```
<xs:simpleType name="UpdateClassification">
  <xs:restriction base="xs:string">
    <xs:enumeration value="Unknown" />
    <xs:enumeration value="CriticalUpdate" />
    <xs:enumeration value="ImportantUpdate" />
    <xs:enumeration value="Update" />
  </xs:restriction>
</xs:simpleType>
```

The following table describes the values for this type.

Value	Description
Unknown	Unknown is not a valid value to set using AddInManager.NewAddInVersionAvailable.
CriticalUpdate	The update is critical. Note the idiosyncratic spelling of the value string.
ImportantUpdate	The update is important.
Update	The update is less important.

2.2.5.7.2 OSEditions

The **OSEditions** type describes information about the operating system that is used to limit which clients a file is installed to.

```
<xs:simpleType name="OSEditions">
  <xs:list>
    <xs:simpleType>
      <xs:restriction base="xs:string">
        <xs:enumeration value="None">
          <xs:annotation>
            <xs:appinfo>
              <EnumerationValue
                xmlns="http://schemas.microsoft.com/2003/10/Serialization/">0</EnumerationValue>
            </xs:appinfo>
          </xs:annotation>
        </xs:enumeration>
        <xs:enumeration value="NotSet">
          <xs:annotation>
            <xs:appinfo>
              <EnumerationValue
                xmlns="http://schemas.microsoft.com/2003/10/Serialization/">0</EnumerationValue>
            </xs:appinfo>
          </xs:annotation>
        </xs:enumeration>
        <xs:enumeration value="Home">
          <xs:annotation>
            <xs:appinfo>
```

```

<EnumerationValue
  xmlns="http://schemas.microsoft.com/2003/10/Serialization/">1</EnumerationValue>
  </xs:appinfo>
</xs:annotation>
</xs:enumeration>
<xs:enumeration value="Pro">
  <xs:annotation>
    <xs:appinfo>
      <EnumerationValue
        xmlns="http://schemas.microsoft.com/2003/10/Serialization/">2</EnumerationValue>
        </xs:appinfo>
      </xs:annotation>
    </xs:enumeration>
    <xs:enumeration value="Starter">
      <xs:annotation>
        <xs:appinfo>
          <EnumerationValue
            xmlns="http://schemas.microsoft.com/2003/10/Serialization/">4</EnumerationValue>
            </xs:appinfo>
          </xs:annotation>
        </xs:enumeration>
        <xs:enumeration value="MediaCenter">
          <xs:annotation>
            <xs:appinfo>
              <EnumerationValue
                xmlns="http://schemas.microsoft.com/2003/10/Serialization/">8</EnumerationValue>
                </xs:appinfo>
              </xs:annotation>
            </xs:enumeration>
            </xs:restriction>
          </xs:simpleType>
        </xs:list>
      </xs:simpleType>

```

The following table describes the values for this type.

Value	Description
None	The filter is not based on an operating system (OS) edition.
NotSet	Compatible with published SDK.
Home	Home OS SKUs.
Pro	Pro OS SKUs.
Starter	Starter OS SKUs.
MediaCenter	OS editions that contain Media Center.

2.2.5.7.3 AddInError

The **AddInError** type represents the error ID strings that can be reported back from the download provider.

```

<xs:simpleType name="AddInError">
  <xs:restriction base="xs:string">
    <xs:enumeration value="None" />
    <xs:enumeration value="OperationCancelled" />
    <xs:enumeration value="UnknownException" />
    <xs:enumeration value="FileNotFoundException" />
    <xs:enumeration value="InvalidSignature" />
    <xs:enumeration value="DownloadError" />
    <xs:enumeration value="PackageExtraction" />

```

```

<xs:enumeration value="InstallError" />
<xs:enumeration value="UpgradeError" />
<xs:enumeration value="UnableToQueryServer" />
<xs:enumeration value="InvalidDownloadRequest" />
<xs:enumeration value="UninstallError" />
<xs:enumeration value="AuthorizationError" />
<xs:enumeration value="ProviderConnectionError" />
<xs:enumeration value="PackageFileCopyError" />
<xs:enumeration value="SettingsProviderError" />
<xs:enumeration value="InvalidData" />
<xs:enumeration value="UnknownAddIn" />
<xs:enumeration value="OperationInProgress" />
</xs:restriction>
</xs:simpleType>

```

The following table describes the values for this type.

Value	Description
None	No error.
OperationCancelled	The asynchronous operation was successfully canceled.
UnknownException	An unknown error has occurred.
FileNotFoundException	The add-in package does not include an expected file.
InvalidSignature	The add-in package either does not have a signature when it is needed, or the signature is invalid.
DownloadError	An error occurred while downloading a file.
PackageExtraction	An error occurred while extracting files from the add-in package.
InstallError	An error occurred while installing an MSI.
UpgradeError	An error occurred while upgrading an MSI.
UnableToQueryServer	Unable to query server.
InvalidDownloadRequest	The download request was invalid (for example, an attempt to download using neither HTTP nor a signed package).
UninstallError	An error occurred while uninstalling an MSI.
AuthorizationError	Access denied.
ProviderConnectionError	An error occurred while connecting to the provider.
PackageFileCopyError	Could not copy add-in package.
SettingsProviderError	An error occurred while contacting the settings provider; changes will not be persisted.
InvalidData	The provided data is invalid; no changes have been made.
UnknownAddIn	The given add-in ID is not known; no action was taken.
OperationInProgress	An install/uninstall operation is already in progress.

2.2.5.8 Network Service

2.2.5.8.1 AddressFamily

The **Network Service** type is an enumeration that defines the various address family types. This protocol supports only the InterNetwork and InterNetworkV6 address family types. The other values MUST NOT be used. The InterNetwork address family specifies the IPv4 address family, and the InterNetworkV6 address family specifies the IPv6 address family.

```
<xs:simpleType name="AddressFamily">
  <xs:restriction base="xs:string">
    <xs:enumeration value="Unknown">
      <xs:annotation>
        <xs:appinfo>
          <EnumerationValue
            xmlns="http://schemas.microsoft.com/2003/10/Serialization/">-1</EnumerationValue>
        </xs:appinfo>
      </xs:annotation>
    </xs:enumeration>
    <xs:enumeration value="Unspecified">
      <xs:annotation>
        <xs:appinfo>
          <EnumerationValue
            xmlns="http://schemas.microsoft.com/2003/10/Serialization/">0</EnumerationValue>
        </xs:appinfo>
      </xs:annotation>
    </xs:enumeration>
    <xs:enumeration value="Unix">
      <xs:annotation>
        <xs:appinfo>
          <EnumerationValue
            xmlns="http://schemas.microsoft.com/2003/10/Serialization/">1</EnumerationValue>
        </xs:appinfo>
      </xs:annotation>
    </xs:enumeration>
    <xs:enumeration value="InterNetwork">
      <xs:annotation>
        <xs:appinfo>
          <EnumerationValue
            xmlns="http://schemas.microsoft.com/2003/10/Serialization/">2</EnumerationValue>
        </xs:appinfo>
      </xs:annotation>
    </xs:enumeration>
    <xs:enumeration value="ImpLink">
      <xs:annotation>
        <xs:appinfo>
          <EnumerationValue
            xmlns="http://schemas.microsoft.com/2003/10/Serialization/">3</EnumerationValue>
        </xs:appinfo>
      </xs:annotation>
    </xs:enumeration>
    <xs:enumeration value="Pup">
      <xs:annotation>
        <xs:appinfo>
          <EnumerationValue
            xmlns="http://schemas.microsoft.com/2003/10/Serialization/">4</EnumerationValue>
        </xs:appinfo>
      </xs:annotation>
    </xs:enumeration>
    <xs:enumeration value="Chaos">
      <xs:annotation>
        <xs:appinfo>
          <EnumerationValue
            xmlns="http://schemas.microsoft.com/2003/10/Serialization/">5</EnumerationValue>
        </xs:appinfo>
      </xs:annotation>
    </xs:enumeration>
    <xs:enumeration value="NS">
      <xs:annotation>
        <xs:appinfo>
          <EnumerationValue
            xmlns="http://schemas.microsoft.com/2003/10/Serialization/">6</EnumerationValue>
        </xs:appinfo>
      </xs:annotation>
    </xs:enumeration>
  </xs:restriction>
</xs:simpleType>
```

```

        </xs:appinfo>
    </xs:annotation>
</xs:enumeration>
<xs:enumeration value="Ipx">
    <xs:annotation>
        <xs:appinfo>
            <EnumerationValue
xmlns="http://schemas.microsoft.com/2003/10/Serialization/">6</EnumerationValue>
        </xs:appinfo>
    </xs:annotation>
</xs:enumeration>
<xs:enumeration value="Iso">
    <xs:annotation>
        <xs:appinfo>
            <EnumerationValue
xmlns="http://schemas.microsoft.com/2003/10/Serialization/">7</EnumerationValue>
        </xs:appinfo>
    </xs:annotation>
</xs:enumeration>
<xs:enumeration value="Osi">
    <xs:annotation>
        <xs:appinfo>
            <EnumerationValue
xmlns="http://schemas.microsoft.com/2003/10/Serialization/">7</EnumerationValue>
        </xs:appinfo>
    </xs:annotation>
</xs:enumeration>
<xs:enumeration value="Ecma">
    <xs:annotation>
        <xs:appinfo>
            <EnumerationValue
xmlns="http://schemas.microsoft.com/2003/10/Serialization/">8</EnumerationValue>
        </xs:appinfo>
    </xs:annotation>
</xs:enumeration>
<xs:enumeration value="DataKit">
    <xs:annotation>
        <xs:appinfo>
            <EnumerationValue
xmlns="http://schemas.microsoft.com/2003/10/Serialization/">9</EnumerationValue>
        </xs:appinfo>
    </xs:annotation>
</xs:enumeration>
<xs:enumeration value="Ccitt">
    <xs:annotation>
        <xs:appinfo>
            <EnumerationValue
xmlns="http://schemas.microsoft.com/2003/10/Serialization/">10</EnumerationValue>
        </xs:appinfo>
    </xs:annotation>
</xs:enumeration>
<xs:enumeration value="Sna">
    <xs:annotation>
        <xs:appinfo>
            <EnumerationValue
xmlns="http://schemas.microsoft.com/2003/10/Serialization/">11</EnumerationValue>
        </xs:appinfo>
    </xs:annotation>
</xs:enumeration>
<xs:enumeration value="DecNet">
    <xs:annotation>
        <xs:appinfo>
            <EnumerationValue
xmlns="http://schemas.microsoft.com/2003/10/Serialization/">12</EnumerationValue>
        </xs:appinfo>
    </xs:annotation>
</xs:enumeration>
<xs:enumeration value="DataLink">
    <xs:annotation>

```

```

        <xs:appinfo>
            <EnumerationValue
        xmlns="http://schemas.microsoft.com/2003/10/Serialization/">13</EnumerationValue>
            </xs:appinfo>
        </xs:annotation>
    </xs:enumeration>
    <xs:enumeration value="Lat">
        <xs:annotation>
            <xs:appinfo>
                <EnumerationValue
        xmlns="http://schemas.microsoft.com/2003/10/Serialization/">14</EnumerationValue>
            </xs:appinfo>
        </xs:annotation>
    </xs:enumeration>
    <xs:enumeration value="HyperChannel">
        <xs:annotation>
            <xs:appinfo>
                <EnumerationValue
        xmlns="http://schemas.microsoft.com/2003/10/Serialization/">15</EnumerationValue>
            </xs:appinfo>
        </xs:annotation>
    </xs:enumeration>
    <xs:enumeration value="AppleTalk">
        <xs:annotation>
            <xs:appinfo>
                <EnumerationValue
        xmlns="http://schemas.microsoft.com/2003/10/Serialization/">16</EnumerationValue>
            </xs:appinfo>
        </xs:annotation>
    </xs:enumeration>
    <xs:enumeration value="NetBios">
        <xs:annotation>
            <xs:appinfo>
                <EnumerationValue
        xmlns="http://schemas.microsoft.com/2003/10/Serialization/">17</EnumerationValue>
            </xs:appinfo>
        </xs:annotation>
    </xs:enumeration>
    <xs:enumeration value="VoiceView">
        <xs:annotation>
            <xs:appinfo>
                <EnumerationValue
        xmlns="http://schemas.microsoft.com/2003/10/Serialization/">18</EnumerationValue>
            </xs:appinfo>
        </xs:annotation>
    </xs:enumeration>
    <xs:enumeration value="FireFox">
        <xs:annotation>
            <xs:appinfo>
                <EnumerationValue
        xmlns="http://schemas.microsoft.com/2003/10/Serialization/">19</EnumerationValue>
            </xs:appinfo>
        </xs:annotation>
    </xs:enumeration>
    <xs:enumeration value="Banyan">
        <xs:annotation>
            <xs:appinfo>
                <EnumerationValue
        xmlns="http://schemas.microsoft.com/2003/10/Serialization/">21</EnumerationValue>
            </xs:appinfo>
        </xs:annotation>
    </xs:enumeration>
    <xs:enumeration value="Atm">
        <xs:annotation>
            <xs:appinfo>
                <EnumerationValue
        xmlns="http://schemas.microsoft.com/2003/10/Serialization/">22</EnumerationValue>
            </xs:appinfo>
        </xs:annotation>

```

```

        </xs:enumeration>
    <xs:enumeration value="InterNetworkV6">
        <xs:annotation>
            <xs:appinfo>
                <EnumerationValue
                    xmlns="http://schemas.microsoft.com/2003/10/Serialization/">23</EnumerationValue>
                </xs:appinfo>
            </xs:annotation>
        </xs:enumeration>
    <xs:enumeration value="Cluster">
        <xs:annotation>
            <xs:appinfo>
                <EnumerationValue
                    xmlns="http://schemas.microsoft.com/2003/10/Serialization/">24</EnumerationValue>
                </xs:appinfo>
            </xs:annotation>
        </xs:enumeration>
    <xs:enumeration value="Ieee12844">
        <xs:annotation>
            <xs:appinfo>
                <EnumerationValue
                    xmlns="http://schemas.microsoft.com/2003/10/Serialization/">25</EnumerationValue>
            </xs:appinfo>
        </xs:annotation>
    </xs:enumeration>
    <xs:enumeration value="Irda">
        <xs:annotation>
            <xs:appinfo>
                <EnumerationValue
                    xmlns="http://schemas.microsoft.com/2003/10/Serialization/">26</EnumerationValue>
            </xs:appinfo>
        </xs:annotation>
    </xs:enumeration>
    <xs:enumeration value="NetworkDesigners">
        <xs:annotation>
            <xs:appinfo>
                <EnumerationValue
                    xmlns="http://schemas.microsoft.com/2003/10/Serialization/">28</EnumerationValue>
            </xs:appinfo>
        </xs:annotation>
    </xs:enumeration>
    <xs:enumeration value="Max">
        <xs:annotation>
            <xs:appinfo>
                <EnumerationValue
                    xmlns="http://schemas.microsoft.com/2003/10/Serialization/">29</EnumerationValue>
            </xs:appinfo>
        </xs:annotation>
    </xs:enumeration>
</xs:restriction>
</xs:simpleType>

```

The following table describes the values for this type.

Value	Description
InterNetwork	Specifies the IPv4 address family.
InterNetworkV6	Specifies the IPv6 address family.

2.2.5.9 Domain Infrastructure Service

2.2.5.9.1 FailureReason

The **FailureReason** type represents the reason a failure occurred in the domain infrastructure service.

```
<xs:simpleType name="FailureReason">
  <xs:restriction base="xs:string">
    <xs:enumeration value="Unknown" />
    <xs:enumeration value="InvalidCredentials" />
    <xs:enumeration value="InvalidDomainName" />
    <xs:enumeration value="QuotaExceeded" />
    <xs:enumeration value="PurchaseNotStarted" />
    <xs:enumeration value="PurchaseFailed" />
    <xs:enumeration value="PendingCustomerInterventionRequired" />
    <xs:enumeration value="InRenewalCustomerInterventionRequired" />
    <xs:enumeration value="RenewalFailed" />
    <xs:enumeration value="RemoteProviderFailure" />
    <xs:enumeration value="CommunicationFailure" />
    <xs:enumeration value="LocalProviderFailure" />
    <xs:enumeration value="CertificateInstallFailure" />
    <xs:enumeration value="CertificateFileBroken" />
    <xs:enumeration value="CertificateNotTrusted" />
    <xs:enumeration value="CertificateBeforeValidPeriod" />
    <xs:enumeration value="CertificateNoPrivateKey" />
    <xs:enumeration value="CertificateFileBrokenOrPasswordWrong" />
  </xs:restriction>
</xs:simpleType>
```

The following table describes the values for this type.

Value	Description
Unknown	Unknown failure.
InvalidCredentials	User credentials are incorrect.
InvalidDomainName	Domain name is not valid.
QuotaExceeded	Domain names under a user account exceeded the quota.
PurchaseNotStarted	User has not correctly initiated the purchase process.
PurchaseFailed	An error occurred when purchasing the domain name.
PendingCustomerInterventionRequired	Domain setup in progress; customer intervention needed.
InRenewalCustomerInterventionRequired	Domain renewal in progress; customer intervention needed.
RenewalFailed	Domain renewal failed.
RemoteProviderFailure	Remote provider failure.
CommunicationFailure	Communication failure.
LocalProviderFailure	Local provider failure.
CertificateInstallFailure	An error occurred when installing the certificate.
CertificateFileBroken	Certificate file is broken.
CertificateNotTrusted	Certificate is not trusted.

Value	Description
CertificateBeforeValidPeriod	The current time precedes the valid certificate period.
CertificateNoPrivateKey	Certificate has no private key.
CertificateFileBrokenOrPasswordWrong	Certificate file is broken or the provider password is wrong.

2.2.5.9.2 DomainStatus

The **DomainStatus** type represents domain status from the point of view of the domain provider.

```

<xs:simpleType name="DomainStatus">
  <xs:restriction base="xs:string">
    <xs:enumeration value="Unknown" />
    <xs:enumeration value="NotConfigured">
      <xs:annotation>
        <xs:appinfo>
          <EnumerationValue
            xmlns="http://schemas.microsoft.com/2003/10/Serialization/">0</EnumerationValue>
        </xs:appinfo>
      </xs:annotation>
    </xs:enumeration>
    <xs:enumeration value="Ready">
      <xs:annotation>
        <xs:appinfo>
          <EnumerationValue
            xmlns="http://schemas.microsoft.com/2003/10/Serialization/">1</EnumerationValue>
        </xs:appinfo>
      </xs:annotation>
    </xs:enumeration>
    <xs:enumeration value="Pending">
      <xs:annotation>
        <xs:appinfo>
          <EnumerationValue
            xmlns="http://schemas.microsoft.com/2003/10/Serialization/">2</EnumerationValue>
        </xs:appinfo>
      </xs:annotation>
    </xs:enumeration>
    <xs:enumeration value="PendingCustomerInterventionRequired">
      <xs:annotation>
        <xs:appinfo>
          <EnumerationValue
            xmlns="http://schemas.microsoft.com/2003/10/Serialization/">3</EnumerationValue>
        </xs:appinfo>
      </xs:annotation>
    </xs:enumeration>
    <xs:enumeration value="Failed">
      <xs:annotation>
        <xs:appinfo>
          <EnumerationValue
            xmlns="http://schemas.microsoft.com/2003/10/Serialization/">4</EnumerationValue>
        </xs:appinfo>
      </xs:annotation>
    </xs:enumeration>
    <xs:enumeration value="PurchaseFailed">
      <xs:annotation>
        <xs:appinfo>
          <EnumerationValue
            xmlns="http://schemas.microsoft.com/2003/10/Serialization/">5</EnumerationValue>
        </xs:appinfo>
      </xs:annotation>
    </xs:enumeration>
    <xs:enumeration value="DomainNotFound">
      <xs:annotation>
        <xs:appinfo>

```

```

<EnumerationValue
  xmlns="http://schemas.microsoft.com/2003/10/Serialization/">6</EnumerationValue>
</xs:appinfo>
</xs:annotation>
</xs:enumeration>
<xs:enumeration value="InRenewal">
  <xs:annotation>
    <xs:appinfo>
      <EnumerationValue
        xmlns="http://schemas.microsoft.com/2003/10/Serialization/">7</EnumerationValue>
      </xs:appinfo>
    </xs:annotation>
  </xs:enumeration>
<xs:enumeration value="InRenewalCustomerInterventionRequired">
  <xs:annotation>
    <xs:appinfo>
      <EnumerationValue
        xmlns="http://schemas.microsoft.com/2003/10/Serialization/">8</EnumerationValue>
      </xs:appinfo>
    </xs:annotation>
  </xs:enumeration>
<xs:enumeration value="RenewalFailed">
  <xs:annotation>
    <xs:appinfo>
      <EnumerationValue
        xmlns="http://schemas.microsoft.com/2003/10/Serialization/">9</EnumerationValue>
      </xs:appinfo>
    </xs:annotation>
  </xs:enumeration>
</xs:restriction>
</xs:simpleType>

```

The following table describes the values for this type.

Value	Description
Unknown	Domain status is unknown.
NotConfigured	Domain is not configured
Ready	Domain name is ready. DNS data might still be propagating.
Pending	Domain setup in progress; no customer intervention needed.
PendingCustomerInterventionRequired	Domain setup in progress; customer intervention needed.
Failed	Domain setup failed without a specific reason.
PurchaseFailed	Purchase of domain failed.
DomainNotFound	Domain is not found for this credential. This usually means that the purchase has not started.
InRenewal	Domain renewal in progress; no customer intervention needed.
InRenewalCustomerInterventionRequired	Domain renewal in progress; customer intervention needed.
RenewalFailed	Domain renewal failed.

2.2.5.9.3 CertificateStatus

The **CertificateStatus** type represents certificate status from the point of view of the domain provider.

```
<xs:simpleType name="CertificateStatus">
  <xs:restriction base="xs:string">
    <xs:enumeration value="Unknown" />
    <xs:enumeration value="Ready" />
    <xs:enumeration value="Failed" />
    <xs:enumeration value="CertificateRequestNotSubmitted" />
    <xs:enumeration value="Pending" />
    <xs:enumeration value="PendingCustomerInterventionRequired" />
  </xs:restriction>
</xs:simpleType>
```

The following table describes the values for this type.

Value	Description
Unknown	Certificate status is unknown.
Ready	Certificate has been successfully provisioned or renewed and is ready for downloading.
Failed	Certificate request failed.
CertificateRequestNotSubmitted	Certificate request has not been submitted.
Pending	Trusted certificate issuance pending; no customer intervention needed.
PendingCustomerInterventionRequired	Trusted certificate issuance pending; customer intervention needed.

2.2.5.9.4 DomainType

The **DomainType** type describes the type of the domain supported.

```
<xs:simpleType name="DomainType">
  <xs:restriction base="xs:string">
    <xs:enumeration value="None" />
    <xs:enumeration value="Home" />
    <xs:enumeration value="Business" />
    <xs:enumeration value="All" />
  </xs:restriction>
</xs:simpleType>
```

The following table describes the values for this type.

Value	Description
None	Domain is not supported.
Home	Domain is for a home network.
Business	Domain is for a business network.
All	Domain is for any network.

2.2.5.9.5 DomainProviderEnvironment

The **DomainProviderEnvironment** type describes the environment that the domain provider is running.

```

<xs:simpleType name="DomainProviderEnvironment">
  <xs:restriction base="xs:string">
    <xs:enumeration value="Testing" />
    <xs:enumeration value="Production" />
  </xs:restriction>
</xs:simpleType>

```

The following table describes the values for this type.

Value	Description
Testing	Domain provider is running in a testing environment.
Production	Domain provider is running in a production environment.

2.2.5.10 AzureAD and HostedEmail Integration Service

AzureAD and HostedEmail integration service SHOULD [<10>](#) be implemented.

2.2.5.10.1 PasswordChangeType

The PasswordChangeType type describes the type of a password change operation.

```

<xs:simpleType name="PasswordChangeType">
  <xs:restriction base="xs:string">
    <xs:enumeration value="AzureAD" />
    <xs:enumeration value="HostedEmail" />
  </xs:restriction>
</xs:simpleType>

```

The following table describes the values for this type.

Value	Description
AzureAD	The password change is for AzureAD.
HostedEmail	The password change is for HostedEmail.

2.2.5.10.2 PasswordChangeStatus

The PasswordChangeStatus type describes the status of a password change operation.

```

<xs:simpleType name="PasswordChangeStatus">
  <xs:restriction base="xs:string">
    <xs:enumeration value="Unknown" />
    <xs:enumeration value="Required" />
    <xs:enumeration value="UnSubmitted" />
    <xs:enumeration value="New" />
    <xs:enumeration value="InProcess" />
    <xs:enumeration value="Success" />
    <xs:enumeration value="WaitForRetry" />
    <xs:enumeration value="Failed" />
    <xs:enumeration value="Fixed" />
    <xs:enumeration value="InvalidPassword" />
  </xs:restriction>
</xs:simpleType>

```

The following table describes the values for this type.

Value	Description
Unknown	Password change status is unknown.
Required	User is required to change the password, but it is not changed yet.
UnSubmitted	Password has not been submitted to the password sync receiver.
New	Password has been submitted to the password sync manager as a new event.
InProcess	Password change event needs to process.
Success	Succeeded in syncing with online.
WaitForRetry	Process failed within retry time, pending next retry.
Failed	Retry exceeded retry time.
Fixed	Marked fixed by end-users for failed data.
InvalidPassword	The password is invalid for Azure Active Directory. <11>

3 Protocol Details

3.1 Client File Backup Provider Service Contract Details

3.1.1 Abstract Data Model

None.

3.1.2 Timers

None.

3.1.3 Initialization

None.

3.1.4 Higher-Layer Triggered Events

None.

3.1.5 Message Processing Events and Sequencing Rules

OperationContract	Description
IUserConfigProvider.GetUserSettingAsync	An asynchronous operation to obtain user settings.
IUserConfigProvider.GetClientManagedSettingAsync	An asynchronous operation to determine whether a client is managed.
IUserConfigProvider.GetUserSettingCompleted	The callback for the IUserConfigProvider.GetUserSettingAsync operation contract.
IUserConfigProvider.GetClientManagedCompleted	The callback for the IUserConfigProvider.GetClientManagedSettingAsync operation contract.

3.1.5.1 IUserConfigProvider.GetUserSettingAsync

This operation submits an asynchronous request to obtain user settings.

```
<wsdl:operation name=" GetUserSettingAsync">
  <wsdl:input wsam:Action="http://tempuri.org/IUserConfigProvider/ GetUserSettingAsync"
  message="tns:IUserConfigProvider_GetUserSettingAsync_InputMessage" />
</wsdl:operation>
```

Upon receiving the **IUserConfigProvider_GetUserSettingAsync_InputMessage** request message, the protocol server retrieves the specified user settings and returns them through the **IUserConfigProvider.GetUserSettingCompleted** callback.

3.1.5.1.1 Messages

3.1.5.1.1.1 IUserConfigProvider_GetUserSettingAsync_InputMessage

This is the request for the **GetUserSettingAsync** operation.

```
<wsdl:message name="IUserConfigProvider.GetUserSettingAsync_InputMessage">
  <wsdl:part name="parameters" element="tns:GetUserSettingAsync" />
</wsdl:message>
```

This message MUST be sent with the following SOAP action.

```
http://tempuri.org/IUserConfigProvider/ GetUserSettingAsyncResponse
```

The body of the SOAP message MUST contain the **GetUserSettingAsync** element.

3.1.5.1.2 Elements

3.1.5.1.2.1 GetUserSettingAsync

This element specifies input values for the **GetUserSettingAsync** operation. This element has no parameters.

```
<xs:element name=" GetUserSettingAsync">
  <xs:complexType>
    <xs:sequence />
  </xs:complexType>
</xs:element>
```

3.1.5.2 IUserConfigProvider.GetClientManagedSettingAsync

This operation determines whether the client is managed.

```
<wsdl:operation name="GetClientManagedSettingAsync">
  <wsdl:input
    wsam:Action="http://tempuri.org/IUserConfigProvider/GetClientManagedSettingAsync"
    message="tns:IUserConfigProvider_GetClientManagedSettingAsync_InputMessage" />
</wsdl:operation>
```

Upon receiving the **IUserConfigProvider_GetClientManagedSettingAsync_InputMessage** request message, the protocol server retrieves the specified user settings and returns them through the **IUserConfigProvider.GetClientManagedCompleted** callback.

3.1.5.2.1 Messages

3.1.5.2.1.1 IUserConfigProvider_GetClientManagedSettingAsync_InputMessage

This is the request for the **GetClientManagedSettingAsync** operation.

```
<wsdl:message name="IUserConfigProvider.GetClientManagedSettingAsync_InputMessage">
  <wsdl:part name="parameters" element="tns: GetClientManagedSettingAsync" />
</wsdl:message>
```

This message MUST be sent with the following SOAP action.

```
http://tempuri.org/IUserConfigProvider/GetClientManagedSettingAsync
```

The body of the SOAP message MUST contain the **GetClientManagedSettingAsync** element.

3.1.5.2.2 Elements

3.1.5.2.2.1 GetClientManagedSettingAsync

This element specifies input values for the **GetClientManagedSettingAsync** operation.

```
<xs:element name="GetClientManagedSettingAsync">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" name="machineName" nillable="true" type="xs:string"
        />
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

machineName: A string that contains the name of the machine from which the client managed setting is retrieved.

3.1.5.3 IUserConfigProviderCallback.GetUserSettingCompleted

This operation is the callback associated with the **IUserConfigProvider.GetUserSettingAsync** operation.

```
<wsdl:operation name=" GetUserSettingCompleted">
  <wsdl:output wsam:Action="http://tempuri.org/IUserConfigProvider/ GetUserSettingCompleted"
    message="tns:IUserConfigProvider GetUserSettingCompleted OutputCallbackMessage"
  />
</wsdl:operation>
```

3.1.5.3.1 Messages

3.1.5.3.1.1 IUserConfigProvider_GetUserSettingCompleted_OutputCallbackMessage

This is the request for the **GetUserSettingCompleted** operation.

```
<wsdl:message name="IUserConfigProviderCallback_GetUserSettingCompleted_InputMessage">
  <wsdl:part name="parameters" element="tns: GetUserSettingCompleted" />
</wsdl:message>
```

This message MUST be sent with the following SOAP action.

<http://tempuri.org/IUserConfigProviderCallback/ GetUserSettingCompleted>

The body of the SOAP message MUST contain the **GetUserSettingCompleted** element.

3.1.5.3.2 Elements

3.1.5.3.2.1 GetUserSettingCompleted

This element specifies input values for the **GetUserSettingCompleted** operation.

```
<xs:element name=" GetUserSettingCompleted">
```

```

<xs:complexType>
  <xs:sequence>
    <xs:element minOccurs="0" name="exception" nillable="true"
      type="ClientFileBackupException" />
    <xs:element minOccurs="0" name="configSet" type="ConfigurationSet" />
  </xs:sequence>
</xs:complexType>
</xs:element>

```

exception: A **ClientFileBackupException** (section [2.2.4.1.1](#)) complex type that contains the exception thrown when getting user setting, if there is any; otherwise, the value is null.

configset: A **ConfigurationSet** (section [2.2.4.1.2](#)) complex type that contains the user configuration setting returned.

3.1.5.4 IUserConfigProvider.GetClientManagedCompleted

This operation is the callback associated with the **IUserConfigProvider.GetClientManagedSettingAsync** operation.

```

<wsdl:operation name="GetClientManagedCompleted">
  <wsdl:output wsam:Action="http://tempuri.org/IUserConfigProvider/GetClientManagedCompleted"
    message="tns:IUserConfigProvider_GetClientManagedCompleted_OutputCallbackMessage" />
</wsdl:operation>

```

3.1.5.4.1 Messages

3.1.5.4.1.1 IUserConfigProvider_GetClientManagedCompleted_OutputCallbackMessage

This operation is the request for the **GetClientManagedCompleted** operation.

```

<wsdl:message name="IUserConfigProvider_GetClientManagedCompleted_OutputCallbackMessage">
  <wsdl:part name="parameters" element="tns:GetClientManagedCompleted" />
</wsdl:message>

```

This message MUST be sent with the following SOAP action.

<http://tempuri.org/IUserConfigProvider/GetClientManagedCompleted>

The body of the SOAP message MUST contain the **GetClientManagedCompleted** element.

3.1.5.4.2 Elements

3.1.5.4.2.1 GetClientManagedCompleted

This element specifies input values for the **GetClientManagedCompleted** operation.

```

<xs:element name="GetClientManagedCompleted">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" name="exception" nillable="true"
        xmlns:q3="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.DataProtection.FileBackup" type="q3:ClientFileBackupException" />

```

```

<xs:element minOccurs="0" name="isManaged"
  xmlns:q4="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.DataProtection.FileBackup" type="q4:ManagedStatus" />
  </xs:sequence>
</xs:complexType>
</xs:element>

```

exception: A **ClientFileBackupException** (section [2.2.4.1.1](#)) complex type that contains the exception thrown when calling **GetClientManagedAsync**, if there is any; otherwise, the value is null.

isManaged: A **ManagedStatus** (section [2.2.5.1.2](#)) string that indicates the management status of the client.

3.1.5.5 GetUserManagedSettingAsync

This operation submits an asynchronous request to obtain user managed settings.

```

<wsdl:operation name=" GetUserManagedSettingAsync">
  <wsdl:input
    wsaw:Action="http://tempuri.org/IUserConfigProvider/ GetUserManagedSettingAsync"
    message="tns:IUserConfigProvider_ GetUserManagedSettingAsync_InputMessage" />
</wsdl:operation>

```

Upon receiving the **IUserConfigProvider_GetUserManagedSettingAsync_InputMessage** request message, the protocol server retrieves the specified user settings and returns them through **IUserConfigProviderCallback.GetUserSettingCompleted** (section [3.1.5.3](#)).

3.1.5.5.1 Messages

3.1.5.5.1.1 IUserConfigProvider_GetUserManagedSettingAsync_InputMessage

This operation is the request for the **GetUserManagedCompleted** operation.

```

<wsdl:operation name=" GetUserManagedSettingAsync">
  <wsdl:input
    wsaw:Action="http://tempuri.org/IUserConfigProvider/ GetUserManagedSettingAsync"
    message="tns:IUserConfigProvider_ GetUserManagedSettingAsync_InputMessage" />
</wsdl:operation>

```

This message MUST be sent with the following SOAP action.

```
http://tempuri.org/IUserConfigProvider/ GetUserManagedSettingAsync
```

The body of the SOAP message MUST contain the **GetUserManagedSettingAsync** element.

3.1.5.5.2 Elements

3.1.5.5.2.1 GetUserManagedSettingAsync

This element specifies input values for the **GetUserManagedSettingAsync** operation.

```

<xs:element name=" GetUserManagedSettingAsync">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" name="userName" nillable="true" type="xs:string" />

```

```

</xs:sequence>
</xs:complexType>
</xs:element>

```

userName: A string that contains the name of the user from which the user managed setting is retrieved.

3.1.6 Timer Events

None.

3.1.7 Other Local Events

None.

3.2 Client Backup Provider Service Contract Details

3.2.1 Abstract Data Model

This section describes a conceptual service contract that an implementation maintains to participate in this protocol. The described operations of the service contract are provided to facilitate the explanation of how the protocol behaves. This document does not mandate that implementations adhere to this service contract as long as their external behavior is consistent with how it is described in this document.

3.2.1.1 Backup Server

The backup server maintains the following data elements.

3.2.1.1.1 List of Backup Client Configurations

The server maintains a list of backup configurations for each client.

3.2.1.1.2 List of Backup Status

The server maintains a list of backup statuses for each client. The protocol allows the backup client to request to change the status.

The following state machine diagram illustrates the relationship between backup status and series of backup requests.




Figure 2: Backup status machine diagram

3.2.1.1.3 List of Backup Volume Configurations for Each Client

The server maintains a list of backup configurations for each volume of each client.

3.2.1.1.4 List of Backup Jobs

The server maintains a list of backup jobs, including jobs that are complete but not cleaned up, the job that is currently running, and jobs that are scheduled in the job queue.

3.2.1.1.5 Backup Window and Retention Policy

Specifies the start time and the end time of the backup window in which automatic backups are scheduled.

3.2.1.1.6 Retention Policy

Specifies the retention policy for old backups.

3.2.1.2 Backup Client

The backup clients maintain the following data elements:

- Priority: The priority of backup jobs for the client. This protocol only gets this value over the wire. This value can only be changed locally on the client by adding or changing a registry.
- Automatic backup schedule: The backup schedule of automatic backup jobs for the client. This is calculated from the backup window on the server. Each client has a different backup schedule; this prevents two clients from starting the automatic backup process at the same time. The schedule can be saved in the task scheduler.[<12>](#)

3.2.2 Timers

None.

3.2.3 Initialization

None.

3.2.4 Higher-Layer Triggered Events

None.

3.2.5 Message Processing Events and Sequencing Rules

OperationContract	Description
IPCBBackupServerRegister.RegisterBackupClient	Registers the client's callback interface. Also returns client configuration from the server when called for the first time. For example, before the client sends any volume configuration information.
IPCBBackupServerRegister.KeepAlive	Keeps the channel alive.
IPCBBackupServerRegister.VolumeCalculatorProgress	Notifies the server of changes in progress on the volume tree calculation.
IPCBBackupServerRegister.GetClientPriority	Returns the priority of the client.
IPCBBackupServerRegister.OnBatteryPower	Returns whether the client is running on battery

OperationContract	Description
	power.
IPCBBackupServerRegister.StartBackup	Throws a fault of type invalid operation if the backup job is not in a stopped or started state. If the backup is already started, the operation has no effect and returns without any faults.
IPCBBackupServerRegister.CancelBackup	Cancels the backup job without regard for its state. Does nothing if it is already idle.
IPCBBackupServerRegister.UpdateBackupConfiguration	Updates the backup configuration on the client whenever it changes.
IPCBBackupServerRegister.SendBackupProgress	Updates the progress percentage of a running backup operation.
IPCBBackupServerRegister.GetFolderChildren	Gets folder children. Called after CalculateVolume finishes.
IPCBBackupServerRegister.CalculateVolumeAsync	Calculates the folder tree for the volume.
IPCBBackupServerRegister.CleanFolderSizeCalculation	Called by the server to clean the folder size calculation. Also called internally when the connection with the server breaks.
IPCBBackupServerRegister.GetConnectedVolumes	Called by the server to get the list of volumes that are connected to the client. Some could be configured while others are not.
IPCBBackupServerRegister.RescanVolumesAsync	Forces the client to send the volume configuration to the server.
IPCBBackupServerProvider.Register	Registers the caller with the PC backup server provider.
IPCBBackupServerProvider.GetClients	Operation to get list of all clients.
IPCBBackupServerProvider.GetClient	Operation to get a specific client.
IPCBBackupServerProvider.GetClientJobs	Returns the list of up to 100 client jobs from index.
IPCBBackupServerProvider.GetVolumeJobs	Operation to get list of all volume jobs.
IPCBBackupServerProvider.GetClientVolumes	Operation to get list of all client volumes.
IPCBBackupServerProvider.SetClientJobDescription	Operation to set client job description.
IPCBBackupServerProvider.SetClientJobRetentionState	Operation to set client job retention state.
IPCBBackupServerProvider.SetClientVolumeStatus	Operation to set client volume status.
IPCBBackupServerProvider.SetExcludedFolders	Operation to set excluded folders.
IPCBBackupServerProvider.EnableBackups	Operation to enable backups on a client.
IPCBBackupServerProvider.DisableBackups	Operation to disable backups on a client.
IPCBBackupServerProvider.GetBackupConfiguration	Operation to get system wide backup configuration: backup windows, cleanup schedule etc.
IPCBBackupServerProvider.GetDefaultBackupConfiguration	Operation to get default backup configuration:

OperationContract	Description
	backup windows, cleanup schedule etc.
IPCBBackupServerProvider.GetBackupOperationStatus	Operation to get backup operation status.
IPCBBackupServerProvider.GetServiceStatus	Operation to get backup service status.
IPCBBackupServerProvider.GetWaitingOperations	Operation to get waiting operations.
IPCBBackupServerProvider.SetBackupConfiguration	Operation to set system wide backup configurations.
IPCBBackupServerProvider.GetUsedBytes	Get total number of used bytes for all backups.
IPCBBackupServerProvider.StartCleanup	Operation to start cleanup operation.
IPCBBackupServerProvider.CancelCleanup	Operation to cancel cleanup operation.
IPCBBackupServerProvider.StartRepair	Operation to start repair operation.
IPCBBackupServerProvider.CancelRepair	Operation to cancel repair operation.
IPCBBackupServerProvider.GetLastRepairResult	Get last repair result.
IPCBBackupServerProvider.StartConsistencyChecker	Operation to start consistency checker operation.
IPCBBackupServerProvider.CancelConsistencyChecker	Operation to cancel consistency checker operation.
IPCBBackupServerProvider.Remove	Operation to remove specific client.
IPCBBackupServerProvider.CalculateVolumeAsync	Starts to calculate the specific volume.
IPCBBackupServerProvider.GetFolderChildren	Get children of the specified folder.
IPCBBackupServerProvider.GetConnectedVolumes	Get connected volumes of the specified client.
IPCBBackupServerProvider.CleanFolderSizeCalculation	Cleanup folder size calculation.
IPCBBackupServerProvider.StartBackup	Operation to start backup on a particular client.
IPCBBackupServerProvider.CancelBackup	Operation to cancel backup on a particular client.
IPCBBackupServerProvider.StartBackupService	Operation to start backup service.
IPCBBackupServerProvider.StopBackupService	Operation to stop backup service.
IPCBBackupServerProvider.NotifyBackupOperationStatusChange	Callback operation to notify caller of backup operation status change.
IPCBBackupServerProvider.VolumeCalculatorProgress	Callback operation to notify caller of volume calculator progress change.
IPCBBackupServerProvider.NotifyServiceStatusChange	Callback operation to notify caller of service status change.

3.2.5.1 IPCBackupServerRegister.RegisterBackupClient

Registers the client's callback interface. Also returns client configuration from the server when called for the first time. For example, before the client sends any volume configuration information.

```

<wsdl:operation name="RegisterBackupClient">
  <wsdl:input wsam:Action="http://tempuri.org/IPCBackupServerRegister/RegisterBackupClient"
  message="tns:IPCBackupServerRegister_RegisterBackupClient_InputMessage" />
  <wsdl:output
  wsam:Action="http://tempuri.org/IPCBackupServerRegister/RegisterBackupClientResponse"
  message="tns:IPCBackupServerRegister RegisterBackupClient OutputMessage" />
  <wsdl:fault
  wsam:Action="http://tempuri.org/IPCBackupServerRegister/RegisterBackupClientInvalidOperationExceptionFault"
  name="InvalidOperationExceptionFault"
  message="tns:IPCBackupServerRegister_RegisterBackupClient_InvalidOperationExceptionFault_FaultMessage" />
</wsdl:operation>

```

Upon receiving the **IPCBackupServerRegister_RegisterBackupClient_InputMessage** request message, the protocol server registers the callback interface. Upon successful completion of the action, the server MUST respond with**IPCBackupServerRegister_RegisterBackupClient_OutputMessage**. In the event of a failure, the appropriate SOAP fault MUST be sent to the client, as specified in section [2.2.2.1](#).

3.2.5.1.1 Messages

3.2.5.1.1.1 IPCBackupServerRegister_RegisterBackupClient_InputMessage

This is the request for the **RegisterBackupClient** operation.

```

<wsdl:message name="IPCBackupServerRegister_RegisterBackupClient_InputMessage">
  <wsdl:part name="parameters" element="tns:RegisterBackupClient" />
</wsdl:message>

```

This message MUST be sent with the following SOAP action.

<http://tempuri.org/IPCBackupServerRegister/RegisterBackupClient>

The body of the SOAP message MUST contain the **RegisterBackupClient** element.

3.2.5.1.1.2 IPCBackupServerRegister_RegisterBackupClient_OutputMessage

This is the response for the **RegisterBackupClient** operation.

```

<wsdl:message name="IPCBackupServerRegister_RegisterBackupClient_OutputMessage">
  <wsdl:part name="parameters" element="tns:RegisterBackupClientResponse" />
</wsdl:message>

```

This message MUST be sent with the following SOAP action.

<http://tempuri.org/IPCBackupServerRegister/RegisterBackupClientResponse>

The body of the SOAP message MUST contain the **RegisterBackupClientResponse** element.

3.2.5.1.2 Elements

3.2.5.1.2.1 RegisterBackupClient

This element specifies input values for the **RegisterBackupClient** operation. This element has no parameters.

```
<xs:element name="RegisterBackupClient">
  <xs:complexType>
    <xs:sequence />
  </xs:complexType>
</xs:element>
```

3.2.5.1.2.2 RegisterBackupClientResponse

This element specifies output values for the **RegisterBackupClient** operation.

```
<xs:element name="RegisterBackupClientResponse">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" name="RegisterBackupClientResult" nillable="true"
        xmlns:q1="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.DataProtocols.PCBackup.BackupUtil.WcfContracts" type="q1:ClientConfig" />
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

RegisterBackupClientResult: A **ClientConfig** (section [2.2.4.2.7](#)) complex type that contains the result of the attempt to register the backup client.

3.2.5.2 IPCBackupServerRegister.KeepAlive

This operation only keeps the channel alive.

```
<wsdl:operation name="KeepAlive">
  <wsdl:input wsam:Action="http://tempuri.org/IPCBackupServerRegister/KeepAlive"
    message="tns:IPCBackupServerRegister_KeepAlive_InputMessage" />
  <wsdl:output wsam:Action="http://tempuri.org/IPCBackupServerRegister/KeepAliveResponse"
    message="tns:IPCBackupServerRegister_KeepAlive_OutputMessage" />
</wsdl:operation>
```

Upon receiving **IPCBackupServerRegister_KeepAlive_InputMessage** request message, the protocol server gets the priority of the client. Upon successful completion of the action, the server MUST respond with **IPCBackupServerRegister_KeepAlive_OutputMessage**. In the event of a failure, the appropriate SOAP fault MUST be sent to the client as specified in section [2.2.2.1](#).

3.2.5.2.1 Messages

3.2.5.2.1.1 IPCBackupServerRegister_KeepAlive_InputMessage

This is the request for the **KeepAlive** operation.

```
<wsdl:message name="IPCBackupServerRegister KeepAlive InputMessage">
  <wsdl:part name="parameters" element="tns:KeepAlive" />
</wsdl:message>
```

This message MUST be sent with the following SOAP action.

<http://tempuri.org/IPCBackupServerRegister/KeepAlive>

The body of the SOAP message MUST contain the **KeepAlive** element.

3.2.5.2.1.2 IPCBackupServerRegister_KeepAlive_OutputMessage

This is the response for the **KeepAlive** operation.

```
<wsdl:message name="IPCB backupServerRegister KeepAlive OutputMessage">
  <wsdl:part name="parameters" element="tns:KeepAliveResponse" />
</wsdl:message>
```

This message MUST be sent with the following SOAP action.

```
http://tempuri.org/IPCB backupServerRegister/KeepAliveResponse
```

The body of the SOAP message MUST contain the **KeepAliveResponse** element.

3.2.5.2.2 Elements

3.2.5.2.2.1 KeepAlive

This element specifies input values for the **KeepAlive** operation. This element has no parameters.

```
<xs:element name="KeepAlive">
  <xs:complexType>
    <xs:sequence />
  </xs:complexType>
</xs:element>
```

3.2.5.2.2.2 KeepAliveResponse

This element specifies output values for the **KeepAlive** operation. This element has no parameters.

```
<xs:element name="KeepAliveResponse">
  <xs:complexType>
    <xs:sequence />
  </xs:complexType>
</xs:element>
```

3.2.5.3 IPCBackupServerRegister.VolumeCalculatorProgress

Notifies the server of progress on a volume tree calculation.

```
<wsdl:operation name="VolumeCalculatorProgress">
  <wsdl:input
    wsam:Action="http://tempuri.org/IPCB backupServerRegister/VolumeCalculatorProgress"
    message="tns:IPCB backupServerRegister_VolumeCalculatorProgress_InputMessage" />
</wsdl:operation>
```

Upon receiving the **IPCB backupServerRegister_VolumeCalculatorProgress_InputMessage** request message, the protocol server is notified of the changes in progress on the volume tree calculation.

3.2.5.3.1 Messages

3.2.5.3.1.1 IPCBackupServerRegister_VolumeCalculatorProgress_InputMessage

This is the request for the **VolumeCalculatorProgress** operation.

```
<wsdl:message name="IPCB backupServerRegister_VolumeCalculatorProgress_InputMessage">
  <wsdl:part name="parameters" element="tns:VolumeCalculatorProgress" />
</wsdl:message>
```

This message MUST be sent with the following SOAP action.

```
http://tempuri.org/IPCB backupServerRegister/VolumeCalculatorProgress
```

The body of the SOAP message MUST contain the **VolumeCalculatorProgress** element.

3.2.5.3.2 Elements

3.2.5.3.2.1 VolumeCalculatorProgress

This element specifies input values for the **VolumeCalculatorProgress** operation.

```
<xs:element name="VolumeCalculatorProgress">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" name="guid"
        xmlns:q2="http://schemas.microsoft.com/2003/10/Serialization/" type="q2:guid" />
      <xs:element minOccurs="0" name="percentDone" type="xs:int" />
      <xs:element minOccurs="0" name="folders" nillable="true"
        xmlns:q3="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.DataProtection.PCBackup.BackupUtil.WcfContracts" type="q3:ArrayOfFolderInfo" />
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

guid: The GUID of the volume.

percentDone: An integer that contains the progress of the current operation; valid values range from 0 to 100 percent.

Folders: An array of **FolderInfo** (section [2.2.4.2.14](#)) complex types that contains folders that have already been calculated.

3.2.5.4 IPCBackupServerRegister.GetClientPriority

This callback operation returns the priority of the client.

```
<wsdl:operation name="GetClientPriority">
  <wsdl:output wsam:Action="http://tempuri.org/IPCB backupServerRegister/GetClientPriority"
    message="tns:IPCB backupServerRegister_GetClientPriority_OutputCallbackMessage" />
  <wsdl:input
    wsam:Action="http://tempuri.org/IPCB backupServerRegister/GetClientPriorityResponse"
    message="tns:IPCB backupServerRegister GetClientPriority InputCallbackMessage" />
</wsdl:operation>
```

Upon receiving the **IPCB backupServerRegister_GetClientPriority_OutputCallbackMessage** request message, the protocol client MUST return its priority with

IPCB backup Server Register _GetClientPriority _InputCallbackMessage. In the event of a failure, the appropriate **SOAP** fault MUST be sent to the server as specified in section [2.2.2.1](#).

3.2.5.4.1 Messages

3.2.5.4.1.1 IPCBackupServerRegister_GetClientPriority_OutputCallbackMessage

This is the request for the **GetClientPriority** operation.

```
<wsdl:message name="IPCB backup Server Register _GetClientPriority _OutputCallbackMessage">
  <wsdl:part name="parameters" element="tns: GetClientPriority" />
</wsdl:message>
```

This message MUST be sent with the following SOAP action.

```
http://tempuri.org/IPCB backup Server Register/GetClientPriority
```

The body of the SOAP message MUST contain the **GetClientPriority** element.

3.2.5.4.1.2 IPCBackupServerRegister_GetClientPriority_InputCallbackMessage

This is the response for the **GetClientPriority** operation.

```
<wsdl:message name="IPCB backup Server Register _GetClientPriority _InputCallbackMessage">
  <wsdl:part name="parameters" element="tns: GetClientPriorityResponse" />
</wsdl:message>
```

This message MUST be sent with the following SOAP action.

```
http://tempuri.org/IPCB backup Server Register/GetClientPriorityResponse
```

The body of the SOAP message MUST contain the **GetClientPriorityResponse** element.

3.2.5.4.2 Elements

3.2.5.4.2.1 GetClientPriority

This element specifies input values for the **GetClientPriority** operation. This element has no parameters.

```
<xs:element name="GetClientPriority">
  <xs:complexType>
    <xs:sequence />
  </xs:complexType>
</xs:element>
```

3.2.5.4.2.2 GetClientPriorityResponse

This element specifies output values for the **GetClientPriority** operation.

```
<xs:element name="GetClientPriorityResponse">
  <xs:complexType>
    <xs:sequence>
```

```

<xs:element minOccurs="0" name="GetClientPriorityResult" type="xs:int" />
</xs:sequence>
</xs:complexType>
</xs:element>

```

GetClientPriorityResult: An integer that contains the priority of the client for the on-demand backup job. The lowest priority value is Int.MaxValue; the smaller the value, the higher the priority.

3.2.5.5 IPCBackupServerRegister.OnBatteryPower

This callback operation returns a value indicating whether the client is running on battery power.

```

<wsdl:operation name="OnBatteryPower">
  <wsdl:output wsam:Action="http://tempuri.org/IPCBackupServerRegister/OnBatteryPower"
    message="tns:IPCBackupServerRegister_OnBatteryPower_OutputCallbackMessage" />
  <wsdl:input wsam:Action="http://tempuri.org/IPCBackupServerRegister/OnBatteryPowerResponse"
    message="tns:IPCBackupServerRegister_OnBatteryPower_InputCallbackMessage" />
</wsdl:operation>

```

Upon receiving the **IPCBackupServerRegister_OnBatteryPower_OutputCallbackMessage** request message, the protocol client checks whether it is running on battery. On successful completion of the action, the client MUST respond with **IPCBackupServerRegister_OnBatteryPower_InputCallbackMessage**. In the event of a failure, the appropriate SOAP fault MUST be sent to the server as specified in section [2.2.2.1](#).

3.2.5.5.1 Messages

3.2.5.5.1.1 IPCBackupServerRegister_OnBatteryPower_OutputCallbackMessage

This is the request for the **OnBatteryPower** operation.

```

<wsdl:message name="IPCBackupServerRegister_OnBatteryPower_OutputCallbackMessage">
  <wsdl:part name="parameters" element="tns:OnBatteryPower" />
</wsdl:message>

```

This message MUST be sent with the following SOAP action.

<http://tempuri.org/IPCBackupServerRegister/OnBatteryPower>

The body of the SOAP message MUST contain the **OnBatteryPower** element.

3.2.5.5.1.2 IPCBackupServerRegister_OnBatteryPower_InputCallbackMessage

This is the response for the **OnBatteryPower** operation.

```

<wsdl:message name="IPCBackupServerRegister_OnBatteryPower_InputCallbackMessage">
  <wsdl:part name="parameters" element="tns:OnBatteryPowerResponse" />
</wsdl:message>

```

This message MUST be sent with the following SOAP action.

<http://tempuri.org/IPCBackupServerRegister/OnBatteryPowerResponse>

The body of the SOAP message MUST contain the **OnBatteryPowerResponse** element.

3.2.5.5.2 Elements

3.2.5.5.2.1 OnBatteryPower

This element specifies input values for the **OnBatteryPower** operation. This element has no parameters.

```
<xs:element name="OnBatteryPower">
  <xs:complexType>
    <xs:sequence />
  </xs:complexType>
</xs:element>
```

3.2.5.5.2.2 OnBatteryPowerResponse

This element specifies output values for the **OnBatteryPower** operation.

```
<xs:element name="OnBatteryPowerResponse">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" name="OnBatteryPowerResult" type="xs:boolean" />
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

OnBatteryPowerResult: A Boolean where TRUE indicates that the client is currently on battery; otherwise, the value is FALSE.

3.2.5.6 IPCBackupServerRegister.StartBackup

This callback operation throws an invalid operation fault if the backup job is not in the stopped or started state. Has no effect if the backup job is already started.

```
<wsdl:operation name="StartBackup">
  <wsdl:output wsam:Action="http://tempuri.org/IPCBackupServerRegister/StartBackup"
  message="tns:IPCBackupServerRegister_StartBackup_OutputCallbackMessage" />
  <wsdl:input wsam:Action="http://tempuri.org/IPCBackupServerRegister/StartBackupResponse"
  message="tns:IPCBackupServerRegister_StartBackup_InputCallbackMessage" />
  <wsdl:fault
  wsam:Action="http://tempuri.org/IPCBackupServerRegister/StartBackupPCBackupClientFaultFault"
  name="PCBackupClientFaultFault"
  message="tns:IPCBackupServerRegister_StartBackup_PCBBackupClientFaultFault_FaultMessage" />
</wsdl:operation>
```

Upon receiving the **IPCBackupServerRegister_StartBackup_OutputCallbackMessage** request message, the protocol client starts a backup. Upon successful completion of a start backup operation, or if one is already in progress, the client MUST respond with

IPCBackupServerRegister_StartBackup_InputCallbackMessage. In the event of a failure, or if backup is not in a stopped or started state, the appropriate SOAP fault MUST be sent to the server as specified in section [2.2.1](#).

If backup is automatic, **allowPostpone** specifies whether a queued backup can be postponed if the automatic backup window is finished. The **allowPostpone** option is ignored if backups are configured to be started manually.

3.2.5.6.1 Messages

3.2.5.6.1.1 IPCBackupServerRegister_StartBackup_OutputCallbackMessage

This is the request for the **StartBackup** operation.

```
<wsdl:message name="IPCB backupServerRegister_StartBackup_OutputCallbackMessage">
  <wsdl:part name="parameters" element="tns:StartBackup" />
</wsdl:message>
```

This message MUST be sent with the following SOAP action.

<http://tempuri.org/IPCB backupServerRegister/StartBackup>

The body of the SOAP message MUST contain the **StartBackup** element.

3.2.5.6.1.2 IPCBackupServerRegister_StartBackup_InputCallbackMessage

This is the response for the **StartBackup** operation.

```
<wsdl:message name="IPCB backupServerRegister StartBackup InputCallbackMessage">
  <wsdl:part name="parameters" element="tns:StartBackupResponse" />
</wsdl:message>
```

This message MUST be sent with the following SOAP action.

<http://tempuri.org/IPCB backupServerRegister/StartBackupResponse>

The body of the SOAP message MUST contain the **StartBackupResponse** element.

3.2.5.6.2 Elements

3.2.5.6.2.1 StartBackup

This element specifies input values for the **StartBackup** operation.

```
<x s:element name="StartBackup">
  <x s:complexType>
    <x s:sequence>
      <x s:element minOccurs="0" name="automatic" type="x s:boolean" />
      <x s:element minOccurs="0" name="description" nillable="true" type="x s:string" />
      <x s:element minOccurs="0" name="allowPostpone" type="x s:boolean" />
    </x s:sequence>
  </x s:complexType>
</x s:element>
```

automatic: A Boolean where TRUE indicates the backup is automatic; otherwise, the value is FALSE.

description: The description of the backup.

allowPostpone: A Boolean where TRUE indicates that postponing the backup is allowed; otherwise, the value is FALSE.

3.2.5.6.2.2 StartBackupResponse

This element specifies output values for the **StartBackup** operation. This element has no parameters.

```
<xs:element name="StartBackupResponse">
  <xs:complexType>
    <xs:sequence />
  </xs:complexType>
</xs:element>
```

3.2.5.7 IPCBackupServerRegister.CancelBackup

This callback operation cancels the backup job, regardless of the job's current state.

```
<wsdl:operation name="CancelBackup">
  <wsdl:output wsam:Action="http://tempuri.org/IPCBackupServerRegister/CancelBackup"
  message="tns:IPCBackupServerRegister_CancelBackup_OutputCallbackMessage" />
  <wsdl:input wsam:Action="http://tempuri.org/IPCBackupServerRegister/CancelBackupResponse"
  message="tns:IPCBackupServerRegister_CancelBackup_InputCallbackMessage" />
  <wsdl:fault
  wsam:Action="http://tempuri.org/IPCBackupServerRegister/CancelBackupPCBackupClientFaultFault"
  name="PCBackupClientFaultFault"
  messages="tns:IPCBackupServerRegister_CancelBackup_PCBackupClientFaultFault_FaultMessage" />
</wsdl:operation>
```

Upon receiving the **IPCBackupServerRegister_CancelBackup_OutputCallbackMessage** request message, the protocol client cancels the backup job without regard for its state. If it is already idle, then it does nothing. On successful completion of the action, the client MUST respond with **IPCBackupServerRegister_CancelBackup_InputCallbackMessage**. In the event of a failure, the appropriate SOAP fault MUST be sent to the server as specified in section [2.2.2.1](#).

3.2.5.7.1 Messages

3.2.5.7.1.1 IPCBackupServerRegister_CancelBackup_OutputCallbackMessage

This is the request for the **CancelBackup** operation.

```
<wsdl:message name="IPCBackupServerRegister_CancelBackup_OutputCallbackMessage">
  <wsdl:part name="parameters" element="tns:CancelBackup" />
</wsdl:message>
```

This message MUST be sent with the following SOAP action.

<http://tempuri.org/IPCBackupServerRegister/CancelBackup>

The body of the SOAP message MUST contain the **CancelBackup** element.

3.2.5.7.1.2 IPCBackupServerRegister_CancelBackup_InputCallbackMessage

This is the response for the **CancelBackup** operation.

```
<wsdl:message name="IPCBackupServerRegister_CancelBackup_InputCallbackMessage">
  <wsdl:part name="parameters" element="tns:CancelBackupResponse" />
</wsdl:message>
```

This message MUST be sent with the following SOAP action.

```
http://tempuri.org/IPCBackupServerRegister/CancelBackupResponse
```

The body of the SOAP message MUST contain the **CancelBackupResponse** element.

3.2.5.7.2 Elements

3.2.5.7.2.1 CancelBackup

This element specifies input values for the **CancelBackup** operation. This element has no parameters.

```
<xs:element name="CancelBackup">
  <xs:complexType>
    <xs:sequence />
  </xs:complexType>
</xs:element>
```

3.2.5.7.2.2 CancelBackupResponse

This element specifies output values for the **CancelBackup** operation. This element has no parameters.

```
<xs:element name="CancelBackupResponse">
  <xs:complexType>
    <xs:sequence />
  </xs:complexType>
</xs:element>
```

3.2.5.8 IPCBackupServerRegister.UpdateBackupConfiguration

This callback operation sets the protocol server to update the backup configuration on the client whenever it changes.

```
<wsdl:operation name="UpdateBackupConfiguration">
  <wsdl:output
    wsam:Action="http://tempuri.org/IPCBackupServerRegister/UpdateBackupConfiguration"
    message="tns:IPCBackupServerRegister_UpdateBackupConfiguration_OutputCallbackMessage" />
</wsdl:operation>
```

Upon receiving the

IPCBackupServerRegister_UpdateBackupConfiguration_OutputCallbackMessage request message, the protocol client updates the backup configuration on the server whenever it changes. In the event of a failure, the appropriate SOAP fault MUST be sent to the server as specified in section [2.2.2.1](#).

3.2.5.8.1 Messages

3.2.5.8.1.1 IPCBackupServerRegister_UpdateBackupConfiguration_OutputCallbackMessage

This is the request for the **UpdateBackupConfiguration** operation.

```
<wsdl:message name="IPCB backupServerRegister_UpdateBackupConfiguration_OutputCallbackMessage">
  <wsdl:part name="parameters" element="tns:UpdateBackupConfiguration" />
</wsdl:message>
```

This message MUST be sent with the following SOAP action.

<http://tempuri.org/IPCB backupServerRegister/UpdateBackupConfiguration>

The body of the SOAP message MUST contain the **UpdateBackupConfiguration** element.

3.2.5.8.2 Elements

3.2.5.8.2.1 UpdateBackupConfiguration

This element specifies input values for the **UpdateBackupConfiguration** operation.

```
<xs:element name="UpdateBackupConfiguration">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" name="backupConfig" nillable="true"
        xmlns:q4="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.DataProtec
        tion.PCBackup.BackupUtil.WcfContracts" type="q4:ClientConfig" />
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

backupConfig: A **ClientConfig** (section [2.2.4.2.7](#)) complex type that indicates the type of backup configuration.

3.2.5.9 IPCBackupServerRegister.SendBackupProgress

This callback operation updates the percent complete of a running backup operation.

```
<wsdl:operation name="SendBackupProgress">
  <wsdl:output wsam:Action="http://tempuri.org/IPCB backupServerRegister/SendBackupProgress"
    message="tns:IPCB backupServerRegister_SendBackupProgress_OutputCallbackMessage" />
</wsdl:operation>
```

Upon receiving the **IPCB backupServerRegister_SendBackupProgress_OutputCallbackMessage** request message, the protocol client updates the progress percentage of a running backup operation. In the event of a failure, the appropriate SOAP fault MUST be sent to the server as specified in section [2.2.2.1](#).

3.2.5.9.1 Messages

3.2.5.9.1.1 IPCBackupServerRegister_SendBackupProgress_OutputCallbackMessage

This is the request for the **SendBackupProgress** operation.

```
<wsdl:message name="IPCB backupServerRegister_SendBackupProgress_OutputCallbackMessage">
  <wsdl:part name="parameters" element="tns:SendBackupProgress" />
</wsdl:message>
```

This message MUST be sent with the following SOAP action.

<http://tempuri.org/IPCBackupServerRegister/SendBackupProgress>

The body of the SOAP message MUST contain the **SendBackupProgress** element.

3.2.5.9.2 Elements

3.2.5.9.2.1 SendBackupProgress

This element specifies input values for the **SendBackupProgress** operation.

```
<xs:element name="SendBackupProgress">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" name="progress" type="xs:int" />
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

progress: An integer that contains the progress of the backup; valid values range from 0 to 100 percent.

3.2.5.10 IPCBackupServerRegister.GetFolderChildren

This callback operation returns the children of a specific folder.

```
<wsdl:operation name="GetFolderChildren">
  <wsdl:output wsam:Action="http://tempuri.org/IPCBackupServerRegister/GetFolderChildren"
  message="tns:IPCBackupServerRegister_GetFolderChildren_OutputCallbackMessage" />
  <wsdl:input
  wsam:Action="http://tempuri.org/IPCBackupServerRegister/GetFolderChildrenResponse"
  message="tns:IPCBackupServerRegister_GetFolderChildren_InputCallbackMessage" />
  <wsdl:fault
  wsam:Action="http://tempuri.org/IPCBackupServerRegister/GetFolderChildrenPCBackupClientFaultF
  ault" name="PCBackupClientFaultFault"
  message="tns:IPCBackupServerRegister_GetFolderChildren_PCBackupClientFaultFault_FaultMessage"
  />
</wsdl:operation>
```

Upon receiving the **IPCBackupServerRegister_GetFolderChildren_OutputCallbackMessage** request message, the protocol client returns the children of the specific folder. It is called after **CalculateVolume** has finished. On successful completion of the action, the client MUST respond with **IPCBackupServerRegister_GetFolderChildren_InputCallbackMessage**. In the event of a failure, the appropriate SOAP fault MUST be sent to the server as specified in section [2.2.2.1](#).

3.2.5.10.1 Messages

3.2.5.10.1.1 IPCBackupServerRegister_GetFolderChildren_OutputCallbackMessage

This is the request for the **GetFolderChildren** operation.

```
<wsdl:message name="IPCBackupServerRegister_GetFolderChildren_OutputCallbackMessage">
  <wsdl:part name="parameters" element="tns:GetFolderChildren" />
</wsdl:message>
```

This message MUST be sent with the following SOAP action.

<http://tempuri.org/IPCBackupServerRegister/GetFolderChildren>

The body of the SOAP message MUST contain the **GetFolderChildren** element.

3.2.5.10.1.2 IPCBackupServerRegister_GetFolderChildren_InputCallbackMessage

This is the response for the **GetFolderChildren** operation.

```
<wsdl:message name="IPCBackupServerRegister_GetFolderChildren_InputCallbackMessage">
  <wsdl:part name="parameters" element="tns:GetFolderChildrenResponse" />
</wsdl:message>
```

This message MUST be sent with the following SOAP action.

<http://tempuri.org/IPCBackupServerRegister/GetFolderChildrenResponse>

The body of the SOAP message MUST contain the **GetFolderChildrenResponse** element.

3.2.5.10.2 Elements

3.2.5.10.2.1 GetFolderChildren

This element specifies input values for the **GetFolderChildren** operation.

```
<xs:element name="GetFolderChildren">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" name="folderRequest" nillable="true"
        xmlns:q5="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.DataProtection.PCBackup.BackupUtil.WcfContracts" type="q5:FolderRequest" />
      <xs:element minOccurs="0" name="index" type="xs:int" />
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

folderRequest: A **FolderRequest** (section [2.2.4.2.16](#)) complex type that contains the data needed for getting folder children.

index: An integer that contains the index of the request.

3.2.5.10.2.2 GetFolderChildrenResponse

This element specifies output values for the **GetFolderChildren** operation.

```
<xs:element name="GetFolderChildrenResponse">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" name="GetFolderChildrenResult" nillable="true"
        xmlns:q6="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.DataProtection.PCBackup.BackupUtil.WcfContracts" type="q6:FolderInfoGroup" />
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

GetFolderChildrenResult: A **FolderInfoGroup** (section [2.2.4.2.15](#)) complex type that contains the result of the attempt to get information about folder children.

3.2.5.11 IPCBackupServerRegister.CalculateVolumeAsync

This callback operation calculates the folder tree for a given volume.

```
<wsdl:operation name="CalculateVolumeAsync">
  <wsdl:output wsam:Action="http://tempuri.org/IPCBackupServerRegister/CalculateVolumeAsync"
    message="tns:IPCBackupServerRegister_CalculateVolumeAsync_OutputCallbackMessage" />
  <wsdl:input
    wsam:Action="http://tempuri.org/IPCBackupServerRegister/CalculateVolumeAsyncResponse"
    message="tns:IPCBackupServerRegister_CalculateVolumeAsync_InputCallbackMessage" />
  <wsdl:fault
    wsam:Action="http://tempuri.org/IPCBackupServerRegister/CalculateVolumeAsyncPCBackupClientFault"
    name="PCBackupClientFaultFault"
    message="tns:IPCBackupServerRegister_CalculateVolumeAsync_PCBackupClientFaultFault_FaultMessage" />
</wsdl:operation>
```

Upon receiving the **IPCBackupServerRegister_CalculateVolumeAsync_OutputCallbackMessage** request message, the protocol client calculates the folder tree for the volume. On successful completion of the action, the client MUST respond with **IPCBackupServerRegister_CalculateVolumeAsync_InputCallbackMessage**. In the event of a failure, the appropriate SOAP fault MUST be sent to the server as specified in section [2.2.2.1](#).

3.2.5.11.1 Messages

3.2.5.11.1.1 IPCBackupServerRegister_CalculateVolumeAsync_OutputCallbackMessage

This is the request for the **CalculateVolumeAsync** operation.

```
<wsdl:message name="IPCBackupServerRegister_CalculateVolumeAsync_OutputCallbackMessage">
  <wsdl:part name="parameters" element="tns:CalculateVolumeAsync" />
</wsdl:message>
```

This message MUST be sent with the following SOAP action.

`http://tempuri.org/IPCBackupServerRegister/CalculateVolumeAsync`

The body of the SOAP message MUST contain the **CalculateVolumeAsync** element.

3.2.5.11.1.2 IPCBackupServerRegister_CalculateVolumeAsync_InputCallbackMessage

This is the response for the **CalculateVolumeAsync** operation.

```
<wsdl:message name="IPCBackupServerRegister_CalculateVolumeAsync_InputCallbackMessage">
  <wsdl:part name="parameters" element="tns:CalculateVolumeAsyncResponse" />
</wsdl:message>
```

This message MUST be sent with the following SOAP action.

<http://tempuri.org/IPCBackupServerRegister/CalculateVolumeAsyncResponse>

The body of the SOAP message MUST contain the **CalculateVolumeAsyncResponse** element.

3.2.5.11.2 Elements

3.2.5.11.2.1 CalculateVolumeAsync

This element specifies input values for the **CalculateVolumeAsync** operation.

```
<xs:element name="CalculateVolumeAsync">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" name="volumeGuid"
        xmlns:q7="http://schemas.microsoft.com/2003/10/Serialization/" type="q7:guid" />
      <xs:element minOccurs="0" name="excludedFolders" nillable="true"
        xmlns:q8="http://schemas.microsoft.com/2003/10/Serialization/Arrays" type="q8:ArrayOfstring"
      />
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

volumeGuid: The GUID of the volume.

excludedFolders: An array of string values that contains the folders that should be excluded.

3.2.5.11.2.2 CalculateVolumeAsyncResponse

This element specifies output values for the **CalculateVolumeAsync** operation.

```
<xs:element name="CalculateVolumeAsyncResponse">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" name="CalculateVolumeAsyncResult" type="xs:boolean" />
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

CalculateVolumeAsyncResult: A Boolean where TRUE indicates that the calculation was successfully started; otherwise, the value is FALSE.

3.2.5.12 IPCBackupServerRegister.CleanFolderSizeCalculation

This callback operation resets the protocol client's folder size calculation.

```
<wsdl:operation name="CleanFolderSizeCalculation">
  <wsdl:output
    wsam:Action="http://tempuri.org/IPCBackupServerRegister/CleanFolderSizeCalculation"
    message="tns:IPCBackupServerRegister_CleanFolderSizeCalculation_OutputCallbackMessage" />
</wsdl:operation>
```

Upon receiving the **IPCBackupServerRegister_CleanFolderSizeCalculation_OutputCallbackMessage** request message, the protocol client resets the folder size calculation. In the event of a failure, an appropriate SOAP fault MUST be sent to the server as specified in section [2.2.2.1](#).

3.2.5.12.1 Messages

3.2.5.12.1.1 IPCBackupServerRegister_CleanFolderSizeCalculation_OutputCallbackMessage

This is the request for the **CleanFolderSizeCalculation** operation.

```
<wsdl:message  
name="IPCB backupServerRegister CleanFolderSizeCalculation OutputCallbackMessage">  
  <wsdl:part name="parameters" element="tns:CleanFolderSizeCalculation" />  
</wsdl:message>
```

This message MUST be sent with the following SOAP action.

```
http://tempuri.org/IPCB backupServerRegister/CleanFolderSizeCalculation
```

The body of the SOAP message MUST contain the **CleanFolderSizeCalculation** element.

3.2.5.12.2 Elements

3.2.5.12.2.1 CleanFolderSizeCalculation

This element specifies input values for the **CleanFolderSizeCalculation** operation. This element has no parameters.

```
<xs:element name="CleanFolderSizeCalculation">  
  <xs:complexType>  
    <xs:sequence />  
  </xs:complexType>  
</xs:element>
```

3.2.5.13 IPCBackupServerRegister.GetConnectedVolumes

This callback operation is called by the server to obtain the list of volumes connected to the client.

```
<wsdl:operation name="GetConnectedVolumes">  
  <wsdl:output wsam:Action="http://tempuri.org/IPCB backupServerRegister/GetConnectedVolumes"  
  message="tns:IPCB backupServerRegister_GetConnectedVolumes_OutputCallbackMessage" />  
  <wsdl:input  
  wsam:Action="http://tempuri.org/IPCB backupServerRegister/GetConnectedVolumesResponse"  
  message="tns:IPCB backupServerRegister_GetConnectedVolumes_InputCallbackMessage" />  
  <wsdl:fault  
  wsam:Action="http://tempuri.org/IPCB backupServerRegister/GetConnectedVolumesPCBackupClientFault"  
  tFault" name="PCBackupClientFaultFault"  
  message="tns:IPCB backupServerRegister_GetConnectedVolumes_PCBackupClientFaultFault_FaultMessage" />  
</wsdl:operation>
```

Upon receiving the **IPCB backupServerRegister_GetConnectedVolumes_OutputCallbackMessage** request message, the protocol client returns the list of configured and unconfigured volumes connected to the client. On successful completion of the action, the client MUST respond with **IPCB backupServerRegister_GetConnectedVolumes_InputCallbackMessage**. In the event of a failure, the appropriate SOAP fault MUST be sent to the server as specified in section [2.2.2.1](#).

3.2.5.13.1 Messages

3.2.5.13.1.1 IPCBackupServerRegister_GetConnectedVolumes_OutputCallbackMessage

This is the request for the **GetConnectedVolumes** operation.

```
<wsdl:message name="IPCB backupServerRegister_GetConnectedVolumes_OutputCallbackMessage">
  <wsdl:part name="parameters" element="tns: GetConnectedVolumes" />
</wsdl:message>
```

This message MUST be sent with the following SOAP action.

```
http://tempuri.org/IPCB backupServerRegister/GetConnectedVolumes
```

The body of the SOAP message MUST contain the **GetConnectedVolumes** element.

3.2.5.13.1.2 IPCBackupServerRegister_GetConnectedVolumes_InputCallbackMessage

This is the response for the **GetConnectedVolumes** operation.

```
<wsdl:message name="IPCB backupServerRegister_GetConnectedVolumes_InputCallbackMessage">
  <wsdl:part name="parameters" element="tns: GetConnectedVolumesResponse" />
</wsdl:message>
```

This message MUST be sent with the following SOAP action.

```
http://tempuri.org/IPCB backupServerRegister/GetConnectedVolumesResponse
```

The body of the SOAP message MUST contain the **GetConnectedVolumesResponse** element.

3.2.5.13.2 Elements

3.2.5.13.2.1 GetConnectedVolumes

This element specifies input values for the **GetConnectedVolumes** operation. This element has no parameters.

```
<xs:element name="GetConnectedVolumes">
  <xs:complexType>
    <xs:sequence />
  </xs:complexType>
</xs:element>
```

3.2.5.13.2.2 GetConnectedVolumesResponse

This element specifies output values for the **GetConnectedVolumes** operation.

```
<xs:element name="GetConnectedVolumesResponse">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" name="GetConnectedVolumesResult" nillable="true"
        xmlns:q9="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.DataProtection.PCBackup.BackupUtil.WcfContracts" type="q9:ArrayOfClientVolumeInfo" />
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

```
</xs:complexType>
</xs:element>
```

GetConnectedVolumesResult: An array of **ClientVolumeInfo** (section [2.2.4.2.11](#)) complex types that contains the result of the attempt to get information about the connected volumes of the specified client.

3.2.5.14 IPCBackupClientManagement.RescanVolumesAsync

This callback operation is called by the server to force a client to send the volume configuration to the server.

```
<wsdl:operation name="RescanVolumesAsync">
  <wsdl:output wsam:Action="http://tempuri.org/IPCBackupServerRegister/RescanVolumesAsync"
    message="tns:IPCBackupServerRegister RescanVolumesAsync OutputCallbackMessage" />
</wsdl:operation>
```

Upon receiving the **IPCBackupServerRegister_RescanVolumesAsync_OutputCallbackMessage** request message, the protocol client starts to send the volume configuration to the protocol server. In the event of a failure, the appropriate **SOAP** fault MUST be sent to the server as specified in section [2.2.2.1](#).

3.2.5.14.1 Messages

3.2.5.14.1.1 IPCBackupServerRegister_RescanVolumesAsync_OutputCallbackMessage

This is the request for the **RescanVolumesAsync** operation.

```
<wsdl:message name="IPCBackupServerRegister RescanVolumesAsync OutputCallbackMessage">
  <wsdl:part name="parameters" element="tns:RescanVolumesAsync" />
</wsdl:message>
```

This message MUST be sent with the following SOAP action.

<http://tempuri.org/IPCBackupServerRegister/RescanVolumesAsync>

The body of the SOAP message MUST contain the **RescanVolumesAsync** element.

3.2.5.14.2 Elements

3.2.5.14.2.1 RescanVolumesAsync

This element specifies input values for the **RescanVolumesAsync** operation. This element has no parameters.

```
<xs:element name="RescanVolumesAsync">
  <xs:complexType>
    <xs:sequence />
  </xs:complexType>
</xs:element>
```

3.2.5.15 IPCBackupServerProvider.Register

This operation registers the caller with the PC backup server provider.

```
<wsdl:operation name="Register">
  <wsdl:input wsam:Action="http://tempuri.org/IPCBackupServerProvider/Register"
  message="tns:IPCBackupServerProvider Register InputMessage" />
  <wsdl:output wsam:Action="http://tempuri.org/IPCBackupServerProvider/RegisterResponse"
  message="tns:IPCBackupServerProvider_Register_OutputMessage" />
  <wsdl:fault
  wsam:Action="http://tempuri.org/IPCBackupServerProvider/RegisterSecurityAccessDeniedException
  Fault" name="SecurityAccessDeniedExceptionFault"
  message="tns:IPCBackupServerProvider Register SecurityAccessDeniedExceptionFault FaultMessage
  " />
</wsdl:operation>
```

Upon receiving the **IPCBackupServerProvider_Register_InputMessage** request message, the protocol server registers the caller with the PC backup server provider. Upon successful completion of the action, the server MUST respond with **IPCBackupServerProvider_Register_OutputMessage**. In the event of a failure, the appropriate SOAP fault MUST be sent to the client as specified in section [2.2.2.1](#).

3.2.5.15.1 Messages

3.2.5.15.1.1 IPCBackupServerProvider_Register_InputMessage

This is the request for the **Register** operation.

```
<wsdl:message name="IPCBackupServerProvider_Register_InputMessage">
  <wsdl:part name="parameters" element="tns:Register" />
</wsdl:message>
```

This message MUST be sent with the following SOAP action.

<http://tempuri.org/IPCBackupServerProvider/Register>

The body of the SOAP message MUST contain the **Register** element.

3.2.5.15.1.2 IPCBackupServerProvider_Register_OutputMessage

This is the response for the **Register** operation.

```
<wsdl:message name="IPCBackupServerProvider Register OutputMessage">
  <wsdl:part name="parameters" element="tns:RegisterResponse" />
</wsdl:message>
```

This message MUST be sent with the following SOAP action.

<http://tempuri.org/IPCBackupServerProvider/RegisterResponse>

The body of the SOAP message MUST contain the **RegisterResponse** element.

3.2.5.15.2 Elements

3.2.5.15.2.1 Register

This element specifies input values for the **RegisterResponse** operation. This element has no parameters.

```
<xs:element name="Register">
  <xs:complexType>
    <xs:sequence />
  </xs:complexType>
</xs:element>
```

3.2.5.15.2.2 RegisterResponse

This element specifies output values for the **RegisterResponse** operation. This element has no parameters.

```
<xs:element name="RegisterResponse">
  <xs:complexType>
    <xs:sequence />
  </xs:complexType>
</xs:element>
```

3.2.5.16 IPCBackupServerProvider.GetClients

This operation returns the server's list of all clients.

```
<wsdl:operation name="GetClients">
  <wsdl:input wsam:Action="http://tempuri.org/IPCBackupServerProvider/GetClients"
  message="tns:IPCBackupServerProvider GetClients_InputMessage" />
  <wsdl:output wsam:Action="http://tempuri.org/IPCBackupServerProvider/GetClientsResponse"
  message="tns:IPCBackupServerProvider_GetClients_OutputMessage" />
  <wsdl:fault
  wsam:Action="http://tempuri.org/IPCBackupServerProvider/GetClientsSecurityAccessDeniedExceptionFault"
  name="SecurityAccessDeniedExceptionFault"
  message="tns:IPCBackupServerProvider GetClients SecurityAccessDeniedExceptionFault FaultMessage" />
  <wsdl:fault
  wsam:Action="http://tempuri.org/IPCBackupServerProvider/GetClientsPCBackupServerFaultFault"
  name="PCBackupServerFaultFault"
  message="tns:IPCBackupServerProvider GetClients PCBackupServerFaultFault FaultMessage" />
</wsdl:operation>
```

Upon receiving the **IPCBackupServerProvider_GetClients_InputMessage** request message, the protocol server generates list of all clients. Upon successful completion of the action, the server MUST respond with **IPCBackupServerProvider_GetClients_OutputMessage**. In the event of a failure, the appropriate SOAP fault MUST be sent to the client as specified in section [2.2.2.1](#).

3.2.5.16.1 Messages

3.2.5.16.1.1 IPCBackupServerProvider_GetClients_InputMessage

This is the request for the **GetClients** operation.

```
<wsdl:message name="IPCBackupServerProvider GetClients InputMessage">
  <wsdl:part name="parameters" element="tns:GetClients" />
</wsdl:message>
```

This message MUST be sent with the following SOAP action.

```
http://tempuri.org/IPCBackupServerProvider/GetClients
```

The body of the SOAP message MUST contain the **GetClients** element.

3.2.5.16.1.2 IPCBackupServerProvider_GetClients_OutputMessage

This is the response for the **GetClients** operation.

```
<wsdl:message name="IPCBackupServerProvider_GetClients_OutputMessage">
  <wsdl:part name="parameters" element="tns:GetClientsResponse" />
</wsdl:message>
```

This message MUST be sent with the following SOAP action.

```
http://tempuri.org/IPCBackupServerProvider/GetClientsResponse
```

The body of the SOAP message MUST contain the **GetClientsResponse** element.

3.2.5.16.2 Elements

3.2.5.16.2.1 GetClients

This element specifies input values for the **GetClients** operation. This element has no parameters.

```
<xs:element name="GetClients">
  <xs:complexType>
    <xs:sequence />
  </xs:complexType>
</xs:element>
```

3.2.5.16.2.2 GetClientsResponse

This element specifies output values for the **GetClients** operation.

```
<xs:element name="GetClientsResponse">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" name="GetClientsResult" nillable="true"
        xmlns:q1="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.DataProtection.PCBackup.BackupUtil.WcfContracts" type="q1:ArrayOfClientConfigurationInfo" />
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

GetClientsResult: An array of **ClientConfigurationInfo** (section [2.2.4.2.8](#)) complex types that contains the results of the attempt to get information about the specified clients.

3.2.5.17 IPCBackupServerProvider.GetClient

This operation returns the backup configuration information for a specific client.

```
<wsdl:operation name="GetClient">
```

```

<wsdl:input wsam:Action="http://tempuri.org/IPCBackupServerProvider/GetClient"
message="tns:IPCBackupServerProvider_GetClient_InputMessage" />
<wsdl:output wsam:Action="http://tempuri.org/IPCBackupServerProvider/GetClientResponse"
message="tns:IPCBackupServerProvider_GetClient_OutputMessage" />
<wsdl:fault
wsam:Action="http://tempuri.org/IPCBackupServerProvider/GetClientSecurityAccessDeniedExceptionFault"
name="SecurityAccessDeniedExceptionFault"
message="tns:IPCBackupServerProvider_GetClient_SecurityAccessDeniedExceptionFault_FaultMessage" />
<wsdl:fault
wsam:Action="http://tempuri.org/IPCBackupServerProvider/GetClientPCBackupServerFaultFault"
name="PCBackupServerFaultFault"
message="tns:IPCBackupServerProvider_GetClient_PCBackupServerFaultFault_FaultMessage" />
</wsdl:operation>

```

Upon receiving the **IPCBackupServerProvider_GetClient_InputMessage** request message, the protocol server gets the backup client information of the client. Upon successful completion of the action, the server MUST respond with **IPCBackupServerProvider_GetClient_OutputMessage**. In the event of a failure, the appropriate SOAP fault MUST be sent to the client as specified in section [2.2.2.1](#).

3.2.5.17.1 Messages

3.2.5.17.1.1 IPCBackupServerProvider_GetClient_InputMessage

This is the request for the **GetClient** operation.

```

<wsdl:message name="IPCBackupServerProvider_GetClient_InputMessage">
  <wsdl:part name="parameters" element="tns:GetClient" />
</wsdl:message>

```

This message MUST be sent with the following SOAP action.

<http://tempuri.org/IPCBackupServerProvider/GetClient>

The body of the SOAP message MUST contain the **GetClient** element.

3.2.5.17.1.2 IPCBackupServerProvider_GetClient_OutputMessage

This is the response for the **GetClient** operation.

```

<wsdl:message name="IPCBackupServerProvider_GetClient_OutputMessage">
  <wsdl:part name="parameters" element="tns:GetClientResponse" />
</wsdl:message>

```

This message MUST be sent with the following SOAP action.

<http://tempuri.org/IPCBackupServerProvider/GetClientResponse>

The body of the SOAP message MUST contain the **GetClientResponse** element.

3.2.5.17.2 Elements

3.2.5.17.2.1 GetClient

This element specifies input values for the **GetClient** operation.

```
<xs:element name="GetClient">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" name="clientSid" nillable="true" type="xs:string" />
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

clientSid: A string that contains the security identifier of the client.

3.2.5.17.2.2 GetClientResponse

This element specifies output values for the **GetClient** operation.

```
<xs:element name="GetClientResponse">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" name="GetClientResult" nillable="true"
        xmlns:q2="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.DataProtection.PCBackup.BackupUtil.WcfContracts" type="q2:ClientConfigurationInfo" />
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

GetClientResult: A **ClientConfigurationInfo** (section [2.2.4.2.8](#)) complex type that contains the result of the attempt to get information about the specified client.

3.2.5.18 IPCBackupServerProvider.GetClientJobs

This operation returns the list of up to 100 client jobs from the server's index.

```
<wsdl:operation name="GetClientJobs">
  <wsdl:input wsam:Action="http://tempuri.org/IPCBackupServerProvider/GetClientJobs"
    message="tns:IPCBackupServerProvider_GetClientJobs_InputMessage" />
  <wsdl:output wsam:Action="http://tempuri.org/IPCBackupServerProvider/GetClientJobsResponse"
    message="tns:IPCBackupServerProvider GetClientJobs OutputMessage" />
  <wsdl:fault
    wsam:Action="http://tempuri.org/IPCBackupServerProvider/GetClientJobsSecurityAccessDeniedExceptionFault"
    name="SecurityAccessDeniedExceptionFault"
    message="tns:IPCBackupServerProvider GetClientJobs SecurityAccessDeniedExceptionFault FaultMessage" />
  <wsdl:fault
    wsam:Action="http://tempuri.org/IPCBackupServerProvider/GetClientJobsPCBackupServerFaultFault"
    name="PCBackupServerFaultFault"
    message="tns:IPCBackupServerProvider_GetClientJobs_PCB backupServerFaultFault_FaultMessage" />
</wsdl:operation>
```

Upon receiving the **IPCBackupServerProvider_GetClientJobs_InputMessage** request message, the protocol server gets the list of the specified client jobs, or the first 100 if the list contains more than 100 jobs. Upon successful completion of the action, the server MUST respond with **IPCBackupServerProvider_GetClientJobs_OutputMessage**. In the event of a failure, the appropriate SOAP fault MUST be sent to the client as specified in section [2.2.2.1](#).

3.2.5.18.1 Messages

3.2.5.18.1.1 IPCBackupServerProvider_GetClientJobs_InputMessage

This is the request for the **GetClientJobs** operation.

```
<wsdl:message name="IPCBBackupServerProvider_GetClientJobs_InputMessage">
  <wsdl:part name="parameters" element="tns:GetClientJobs" />
</wsdl:message>
```

This message MUST be sent with the following SOAP action.

```
http://tempuri.org/IPCBBackupServerProvider/GetClientJobs
```

The body of the SOAP message MUST contain the **GetClientJobs** element.

3.2.5.18.1.2 IPCBackupServerProvider_GetClientJobs_OutputMessage

This is the response for the **GetClientJobs** operation.

```
<wsdl:message name="IPCBBackupServerProvider_GetClientJobs_OutputMessage">
  <wsdl:part name="parameters" element="tns:GetClientJobsResponse" />
</wsdl:message>
```

This message MUST be sent with the following SOAP action.

```
http://tempuri.org/IPCBBackupServerProvider/GetClientJobsResponse
```

The body of the SOAP message MUST contain the **GetClientJobsResponse** element.

3.2.5.18.2 Elements

3.2.5.18.2.1 GetClientJobs

This element specifies input values for the **GetClientJobs** operation.

```
<xs:element name="GetClientJobs">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" name="clientSid" nillable="true" type="xs:string" />
      <xs:element minOccurs="0" name="index" type="xs:int" />
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

clientSid: A string that contains the security identifier of the client.

index: An integer that contains the index of the client.

3.2.5.18.2.2 GetClientJobsResponse

This element specifies output values for the **GetClientJobs** operation.

```
<xs:element name="GetClientJobsResponse">
  <xs:complexType>
    <xs:sequence>
```

```

<xs:element minOccurs="0" name="GetClientJobsResult" nillable="true"
xmlns:q3="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.DataProtection.PCBackup.BackupUtil.WcfContracts" type="q3:ArrayOfClientJobInfo" />
  </xs:sequence>
</xs:complexType>
</xs:element>

```

GetClientJobsResult: An array of **ClientJobInfo** (section [2.2.4.2.9](#)) complex types that contains the results of the attempt to get information about the specified client jobs.

3.2.5.19 IPCBackupServerProvider.GetVolumeJobs

This operation gets the list of all volume jobs.

```

<wsdl:operation name="GetVolumeJobs">
  <wsdl:input wsam:Action="http://tempuri.org/IPCBackupServerProvider/GetVolumeJobs">
    message="tns:IPCBackupServerProvider GetVolumeJobs InputMessage" />
  <wsdl:output wsam:Action="http://tempuri.org/IPCBackupServerProvider/GetVolumeJobsResponse">
    message="tns:IPCBackupServerProvider_GetVolumeJobs_OutputMessage" />
  <wsdl:fault
    wsam:Action="http://tempuri.org/IPCBackupServerProvider/GetVolumeJobsPCBackupServerFaultFault
    " name="PCBackupServerFaultFault"
    message="tns:IPCBackupServerProvider GetVolumeJobs PCBackupServerFaultFault FaultMessage" />
  <wsdl:fault
    wsam:Action="http://tempuri.org/IPCBackupServerProvider/GetVolumeJobsSecurityAccessDeniedExceptionFault"
    name="SecurityAccessDeniedExceptionFault"
    message="tns:IPCBackupServerProvider GetVolumeJobs SecurityAccessDeniedExceptionFault FaultMessage" />
  </wsdl:operation>

```

Upon receiving the **IPCBackupServerProvider_GetVolumeJobs_InputMessage** request message, the protocol server generates the list of all volume jobs. Upon successful completion of the action, the server MUST respond with **IPCBackupServerProvider_GetVolumeJobs_OutputMessage**. In the event of a failure, the appropriate SOAP fault MUST be sent to the client as specified in section [2.2.2.1](#).

3.2.5.19.1 Messages

3.2.5.19.1.1 IPCBackupServerProvider_GetVolumeJobs_InputMessage

This is the request for the **GetVolumeJobs** operation.

```

<wsdl:message name="IPCBackupServerProvider GetVolumeJobs InputMessage">
  <wsdl:part name="parameters" element="tns:GetVolumeJobs" />
</wsdl:message>

```

This message MUST be sent with the following SOAP action.

<http://tempuri.org/IPCBackupServerProvider/GetVolumeJobs>

The body of the SOAP message MUST contain the **GetVolumeJobs** element.

3.2.5.19.1.2 IPCBackupServerProvider_GetVolumeJobs_OutputMessage

This is the response for the **GetVolumeJobs** operation.

```
<wsdl:message name="IPCBBackupServerProvider_GetVolumeJobs_OutputMessage">
  <wsdl:part name="parameters" element="tns:GetVolumeJobsResponse" />
</wsdl:message>
```

This message MUST be sent with the following SOAP action.

```
http://tempuri.org/IPCBBackupServerProvider/GetVolumeJobsResponse
```

The body of the SOAP message MUST contain the **GetVolumeJobsResponse** element.

3.2.5.19.2 Elements

3.2.5.19.2.1 GetVolumeJobs

This element specifies input values for the **GetVolumeJobs** operation.

```
<xs:element name="GetVolumeJobs">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" name="clientSid" nillable="true" type="xs:string" />
      <xs:element minOccurs="0" name="jobIndex" type="xs:int" />
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

clientSid: A string that contains the security identifier of the client.

jobIndex: An integer that contains the index of the job.

3.2.5.19.2.2 GetVolumeJobsResponse

This element specifies output values for the **GetVolumeJobs** operation.

```
<xs:element name="GetVolumeJobsResponse">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" name="GetVolumeJobsResult" nillable="true"
        xmlns:q4="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.DataProtec-
        tion.PCBackup.BackupUtil.WcfContracts" type="q4:ArrayOfVolumeJobInfo" />
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

GetVolumeJobsResult: An array of **VolumeJobInfo** (section [2.2.4.2.19](#)) complex types that contains the result of the attempt to get volume jobs.

3.2.5.20 IPCBackupServerProvider.GetClientVolumes

This operation gets the list of all client volumes.

```
<wsdl:operation name="GetClientVolumes">
  <wsdl:input wsam:Action="http://tempuri.org/IPCBBackupServerProvider/GetClientVolumes"
    message="tns:IPCBBackupServerProvider_GetClientVolumes_InputMessage" />
  <wsdl:output
    wsam:Action="http://tempuri.org/IPCBBackupServerProvider/GetClientVolumesResponse"
    message="tns:IPCBBackupServerProvider_GetClientVolumes_OutputMessage" />
```

```

<wsdl:fault
wsam:Action="http://tempuri.org/IPCBackupServerProvider/GetClientVolumesSecurityAccessDeniedE
xceptionFault" name="SecurityAccessDeniedExceptionFault"
message="tns:IPCBackupServerProvider_GetClientVolumes_SecurityAccessDeniedExceptionFault_Fau
tMessage" />
<wsdl:fault
wsam:Action="http://tempuri.org/IPCBackupServerProvider/GetClientVolumesPCBackupServerFaultFa
ult" name="PCBackupServerFaultFault"
message="tns:IPCBackupServerProvider_GetClientVolumes_PCBackupServerFaultFault_FaultMessage"
/>
</wsdl:operation>
```

Upon receiving the **IPCBackupServerProvider_GetClientVolumes_InputMessage** request message, the protocol server gets the list of all client volumes. Upon successful completion of the action, the server MUST respond with

IPCBackupServerProvider_GetClientVolumes_OutputMessage. In the event of a failure, the appropriate SOAP fault MUST be sent to the client as specified in section [2.2.2.1](#).

3.2.5.20.1 Messages

3.2.5.20.1.1 IPCBackupServerProvider_GetClientVolumes_InputMessage

This is the request for the **GetClientVolumes** operation.

```
<wsdl:message name="IPCBackupServerProvider_GetClientVolumes_InputMessage">
  <wsdl:part name="parameters" element="tns:GetClientVolumes" />
</wsdl:message>
```

This message MUST be sent with the following SOAP action.

<http://tempuri.org/IPCBackupServerProvider/GetClientVolumes>

The body of the SOAP message MUST contain the **GetClientVolumes** element.

3.2.5.20.1.2 IPCBackupServerProvider_GetClientVolumes_OutputMessage

This is the response for the **GetClientVolumes** operation.

```
<wsdl:message name="IPCBackupServerProvider_GetClientVolumes_OutputMessage">
  <wsdl:part name="parameters" element="tns:GetClientVolumesResponse" />
</wsdl:message>
```

This message MUST be sent with the following SOAP action.

<http://tempuri.org/IPCBackupServerProvider/GetClientVolumesResponse>

The body of the SOAP message MUST contain the **GetClientVolumesResponse** element.

3.2.5.20.2 Elements

3.2.5.20.2.1 GetClientVolumes

This element specifies input values for the **GetClientVolumes** operation.

```

<xs:element name="GetClientVolumes">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" name="clientSid" nillable="true" type="xs:string" />
    </xs:sequence>
  </xs:complexType>
</xs:element>

```

clientSid: A string that contains the security identifier of the client.

3.2.5.20.2.2 GetClientVolumesResponse

This element specifies output values for the **GetClientVolumes** operation.

```

<xs:element name="GetClientVolumesResponse">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" name="GetClientVolumesResult" nillable="true"
        xmlns:q5="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.DataProtec
        tion.PCBackup.BackupUtil.WcfContracts" type="q5:ArrayOfClientVolumeInfo" />
    </xs:sequence>
  </xs:complexType>
</xs:element>

```

GetClientVolumesResult: An array of **ClientVolumeInfo** (section [2.2.4.2.11](#)) complex types that contains the result of the attempt to get client volumes.

3.2.5.21 IPCBackupServerProvider.SetClientJobDescription

This operation sets a description for a client job.

```

<wsdl:operation name="SetClientJobDescription">
  <wsdl:input
    wsam:Action="http://tempuri.org/IPCBackupServerProvider/SetClientJobDescription"
    message="tns:IPCBackupServerProvider_SetClientJobDescription_InputMessage" />
  <wsdl:output
    wsam:Action="http://tempuri.org/IPCBackupServerProvider/SetClientJobDescriptionResponse"
    message="tns:IPCBackupServerProvider_SetClientJobDescription_OutputMessage" />
  <wsdl:fault
    wsam:Action="http://tempuri.org/IPCBackupServerProvider/SetClientJobDescriptionPCBackupServer
    FaultFault" name="PCBackupServerFaultFault"
    message="tns:IPCBackupServerProvider_SetClientJobDescription_PCB backupServerFaultFault_FaultMe
    ssage" />
  <wsdl:fault
    wsam:Action="http://tempuri.org/IPCBackupServerProvider/SetClientJobDescriptionSecurityAccess
    DeniedExceptionFault" name="SecurityAccessDeniedExceptionFault"
    message="tns:IPCBackupServerProvider_SetClientJobDescription_SecurityAccessDeniedExceptionFau
    lt_FaultMessage" />
</wsdl:operation>

```

Upon receiving the **IPCBackupServerProvider_SetClientJobDescription_InputMessage** request message, the protocol server sets the client job description. Upon successful completion of the action, the server MUST respond with

IPCBackupServerProvider_SetClientJobDescription_OutputMessage. In the event of a failure, the appropriate SOAP fault MUST be sent to the client as specified in section [2.2.2.1](#).

3.2.5.21.1 Messages

3.2.5.21.1.1 IPCBackupServerProvider_SetClientJobDescription_InputMessage

This is the request for the **SetClientJobDescription** operation.

```
<wsdl:message name="IPCBBackupServerProvider_SetClientJobDescription_InputMessage">
  <wsdl:part name="parameters" element="tns:SetClientJobDescription" />
</wsdl:message>
```

This message MUST be sent with the following SOAP action.

```
http://tempuri.org/IPCBBackupServerProvider/SetClientJobDescription
```

The body of the SOAP message MUST contain the **SetClientJobDescription** element.

3.2.5.21.1.2 IPCBackupServerProvider_SetClientJobDescription_OutputMessage

This is the response for the **SetClientJobDescription** operation.

```
<wsdl:message name="IPCBBackupServerProvider_SetClientJobDescription_OutputMessage">
  <wsdl:part name="parameters" element="tns:SetClientJobDescriptionResponse" />
</wsdl:message>
```

This message MUST be sent with the following SOAP action.

```
http://tempuri.org/IPCBBackupServerProvider/SetClientJobDescriptionResponse
```

The body of the SOAP message MUST contain the **SetClientJobDescriptionResponse** element.

3.2.5.21.2 Elements

3.2.5.21.2.1 SetClientJobDescription

This element specifies input values for the **SetClientJobDescription** operation.

```
<xs:element name="SetClientJobDescription">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" name="clientSid" nillable="true" type="xs:string" />
      <xs:element minOccurs="0" name="clientJobIndex" type="xs:int" />
      <xs:element minOccurs="0" name="Description" nillable="true" type="xs:string" />
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

clientSid: A string that contains the security identifier of the client.

clientJobIndex: An integer that contains the index of the client job.

Description: A string that contains the description of the client job.

3.2.5.21.2.2 SetClientJobDescriptionResponse

This element specifies output values for the **SetClientJobDescription** operation. This element has no parameters.

```
<xs:element name="SetClientJobDescriptionResponse">
```

```

<xs:complexType>
  <xs:sequence />
</xs:complexType>
</xs:element>

```

3.2.5.22 IPCBackupServerProvider.SetClientJobRetentionState

This operation sets the retention state for a client job.

```

<wsdl:operation name="SetClientJobRetentionState">
  <wsdl:input
    wsam:Action="http://tempuri.org/IPCBackupServerProvider/SetClientJobRetentionState"
    message="tns:IPCBackupServerProvider_SetClientJobRetentionState_InputMessage" />
  <wsdl:output
    wsam:Action="http://tempuri.org/IPCBackupServerProvider/SetClientJobRetentionStateResponse"
    message="tns:IPCBackupServerProvider_SetClientJobRetentionState_OutputMessage" />
  <wsdl:fault
    wsam:Action="http://tempuri.org/IPCBackupServerProvider/SetClientJobRetentionStateSecurityAcc
    essDeniedExceptionFault" name="SecurityAccessDeniedExceptionFault"
    message="tns:IPCBackupServerProvider_SetClientJobRetentionState_SecurityAccessDeniedException
    Fault_FaultMessage" />
  <wsdl:fault
    wsam:Action="http://tempuri.org/IPCBackupServerProvider/SetClientJobRetentionStatePCBackupSer
    verFaultFault" name="PCBackupServerFaultFault"
    message="tns:IPCBackupServerProvider_SetClientJobRetentionState_PCBackupServerFaultFault_Fau
    tMessage" />
</wsdl:operation>

```

Upon receiving the **IPCBackupServerProvider_SetClientJobRetentionState_InputMessage** request message, the protocol server gets the client job retention state. Upon successful completion of the action, the server MUST respond with **IPCBackupServerProvider_SetClientJobRetentionState_OutputMessage**. In the event of a failure, the appropriate SOAP fault MUST be sent to the client as specified in section [2.2.2.1](#).

3.2.5.22.1 Messages

3.2.5.22.1.1 IPCBackupServerProvider_SetClientJobRetentionState_InputMessage

This is the request for the **SetClientJobRetentionState** operation.

```

<wsdl:message name="IPCBackupServerProvider_SetClientJobRetentionState_InputMessage">
  <wsdl:part name="parameters" element="tns:SetClientJobRetentionState" />
</wsdl:message>

```

This message MUST be sent with the following SOAP action.

<http://tempuri.org/IPCBackupServerProvider/SetClientJobRetentionState>

The body of the SOAP message MUST contain the **SetClientJobRetentionState** element.

3.2.5.22.1.2 IPCBackupServerProvider_SetClientJobRetentionState_OutputMessage

This is the response for the **SetClientJobRetentionState** operation.

```

<wsdl:message name="IPCBackupServerProvider_SetClientJobRetentionState_OutputMessage">
  <wsdl:part name="parameters" element="tns:SetClientJobRetentionStateResponse" />

```

```
</wsdl:message>
```

This message MUST be sent with the following SOAP action.

```
http://tempuri.org/IPCBackupServerProvider/SetClientJobRetentionStateResponse
```

The body of the SOAP message MUST contain the **SetClientJobRetentionStateResponse** element.

3.2.5.22.2 Elements

3.2.5.22.2.1 SetClientJobRetentionState

This element specifies input values for the **SetClientJobRetentionState** operation.

```
<xs:element name="SetClientJobRetentionState">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" name="clientSid" nillable="true" type="xs:string" />
      <xs:element minOccurs="0" name="clientJobIndex" type="xs:int" />
      <xs:element minOccurs="0" name="retentionState"
        xmlns:q6="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.DataProtection.PCBackup.BackupUtil.WcfContracts" type="q6:RetentionState" />
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

clientSid: A string that contains the security identifier of the client.

clientJobIndex: An integer that contains the index of the client job.

retentionState: A **RetentionState** (section [2.2.5.2.16](#)) string that indicates the retention state of the client job.

3.2.5.22.2.2 SetClientJobRetentionStateResponse

This element specifies output values for the **SetClientJobRetentionState** operation. This element has no parameters.

```
<xs:element name="SetClientJobRetentionStateResponse">
  <xs:complexType>
    <xs:sequence />
  </xs:complexType>
</xs:element>
```

3.2.5.23 IPCBackupServerProvider.SetClientVolumeStatus

This operation sets the status of a client volume.

```
<wsdl:operation name="SetClientVolumeStatus">
  <wsdl:input wsam:Action="http://tempuri.org/IPCBackupServerProvider/SetClientVolumeStatus"
    message="tns:IPCBackupServerProvider_SetClientVolumeStatus_InputMessage" />
  <wsdl:output
    wsam:Action="http://tempuri.org/IPCBackupServerProvider/SetClientVolumeStatusResponse"
    message="tns:IPCBackupServerProvider_SetClientVolumeStatus_OutputMessage" />
  <wsdl:fault
    wsam:Action="http://tempuri.org/IPCBackupServerProvider/SetClientVolumeStatusPCBackupServerFa
```

```

        ultFault" name="PCBackupServerFaultFault"
        message="tns:IPCBackupServerProvider_SetClientVolumeStatus PCBackupServerFaultFault FaultMess
        age" />
        <wsdl:fault
        wsam:Action="http://tempuri.org/IPCBackupServerProvider/SetClientVolumeStatusSecurityAccessDe
        niedExceptionFault" name="SecurityAccessDeniedExceptionFault"
        message="tns:IPCBackupServerProvider_SetClientVolumeStatus_SecurityAccessDeniedExceptionFault
        FaultMessage" />
</wsdl:operation>
```

Upon receiving the **IPCBackupServerProvider_SetClientVolumeStatus_InputMessage** request message, the protocol server sets the client volume status. Upon successful completion of the action, the server MUST respond with **IPCBackupServerProvider_SetClientVolumeStatus_OutputMessage**. In the event of a failure, the appropriate SOAP fault MUST be sent to the client as specified in section [2.2.2.1](#).

3.2.5.23.1 Messages

3.2.5.23.1.1 IPCBackupServerProvider_SetClientVolumeStatus_InputMessage

This is the request for the **SetClientVolumeStatus** operation.

```

<wsdl:message name="IPCBackupServerProvider_SetClientVolumeStatus_InputMessage">
    <wsdl:part name="parameters" element="tns:SetClientVolumeStatus" />
</wsdl:message>
```

This message MUST be sent with the following SOAP action.

<http://tempuri.org/IPCBackupServerProvider/SetClientVolumeStatus>

The body of the SOAP message MUST contain the **SetClientVolumeStatus** element.

3.2.5.23.1.2 IPCBackupServerProvider_SetClientVolumeStatus_OutputMessage

This is the response for the **SetClientVolumeStatus** operation.

```

<wsdl:message name="IPCBackupServerProvider_SetClientVolumeStatus_OutputMessage">
    <wsdl:part name="parameters" element="tns:SetClientVolumeStatusResponse" />
</wsdl:message>
```

This message MUST be sent with the following SOAP action.

<http://tempuri.org/IPCBackupServerProvider/SetClientVolumeStatusResponse>

The body of the SOAP message MUST contain the **SetClientVolumeStatusResponse** element.

3.2.5.23.2 Elements

3.2.5.23.2.1 SetClientVolumeStatus

This element specifies input values for the **SetClientVolumeStatus** operation.

```

<xss:element name="SetClientVolumeStatus">
    <xss:complexType>
```

```

<xs:sequence>
    <xs:element minOccurs="0" name="clientSid" nillable="true" type="xs:string" />
    <xs:element minOccurs="0" name="volumeGuid"
    xmlns:q7="http://schemas.microsoft.com/2003/10/Serialization/" type="q7:guid" />
    <xs:element minOccurs="0" name="Status"
    xmlns:q8="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.DataProtection.PCBackup.BackupUtil.WcfContracts" type="q8:VolumeStatus" />
        <xs:element minOccurs="0" name="DeleteJobs" type="xs:boolean" />
    </xs:sequence>
</xs:complexType>
</xs:element>

```

clientSid: A string that contains the security identifier of the client.

volumeGuid: The GUID of the volume.

Status: A **VolumeStatus** (section [2.2.5.2.20](#)) value that contains the status of the volume.

DeleteJobs: A Boolean where TRUE indicates all volume jobs need to be deleted for the volume; otherwise, the value is FALSE.

3.2.5.23.2.2 SetClientVolumeStatusResponse

This element specifies output values for the **SetClientVolumeStatus** operation. This element has no parameters.

```

<xs:element name="SetClientVolumeStatusResponse">
    <xs:complexType>
        <xs:sequence />
    </xs:complexType>
</xs:element>

```

3.2.5.24 IPCBackupServerProvider.SetExcludedFolders

This operation sets excluded folders.

```

<wsdl:operation name="SetExcludedFolders">
    <wsdl:input wsam:Action="http://tempuri.org/IPCBackupServerProvider/SetExcludedFolders"
    message="tns:IPCBackupServerProvider_SetExcludedFolders_InputMessage" />
    <wsdl:output
    wsam:Action="http://tempuri.org/IPCBackupServerProvider/SetExcludedFoldersResponse"
    message="tns:IPCBackupServerProvider_SetExcludedFolders_OutputMessage" />
    <wsdl:fault
    wsam:Action="http://tempuri.org/IPCBackupServerProvider/SetExcludedFoldersPCBackupServerFault
    Fault" name="PCBackupServerFaultFault"
    message="tns:IPCBackupServerProvider_SetExcludedFolders_PCBackupServerFaultFault_FaultMessage
    " />
    <wsdl:fault
    wsam:Action="http://tempuri.org/IPCBackupServerProvider/SetExcludedFoldersSecurityAccessDenie
    dExceptionFault" name="SecurityAccessDeniedExceptionFault"
    message="tns:IPCBackupServerProvider_SetExcludedFolders_SecurityAccessDeniedExceptionFault_Fa
    ultMessage" />
</wsdl:operation>

```

Upon receiving the **IPCBackupServerProvider_SetExcludedFolders_InputMessage** request message, the protocol server sets the specified excluded folders. Upon successful completion of the action, the server MUST respond with

IPCBackupServerProvider_SetExcludedFolders_OutputMessage. In the event of a failure, the appropriate SOAP fault MUST be sent to the client as specified in section [2.2.2.1](#).

3.2.5.24.1 Messages

3.2.5.24.1.1 IPCBackupServerProvider_SetExcludedFolders_InputMessage

This is the request for the **SetExcludedFolders** operation.

```
<wsdl:message name="IPCB backupServerProvider_SetExcludedFolders_InputMessage">
    <wsdl:part name="parameters" element="tns:SetExcludedFolders" />
</wsdl:message>
```

This message MUST be sent with the following SOAP action.

<http://tempuri.org/IPCB backupServerProvider/SetExcludedFolders>

The body of the SOAP message MUST contain the **SetExcludedFolders** element.

3.2.5.24.1.2 IPCBackupServerProvider_SetExcludedFolders_OutputMessage

This is the response for the **SetExcludedFolders** operation.

```
<wsdl:message name="IPCB backupServerProvider_SetExcludedFolders_OutputMessage">
    <wsdl:part name="parameters" element="tns:SetExcludedFoldersResponse" />
</wsdl:message>
This message MUST be sent with the following SOAP action.
http://tempuri.org/IPCB backupServerProvider/SetExcludedFoldersResponse
The body of the SOAP message MUST contain the SetExcludedFoldersResponse element.
```

3.2.5.24.2 Elements

3.2.5.24.2.1 SetExcludedFolders

This element specifies input values for the **SetExcludedFolders** operation.

```
<xs:element name="SetExcludedFolders">
    <xs:complexType>
        <xs:sequence>
            <xs:element minOccurs="0" name="clientSid" nillable="true" type="xs:string" />
            <xs:element minOccurs="0" name="volumeGuid"
                xmlns:q9="http://schemas.microsoft.com/2003/10/Serialization/" type="q9:guid" />
            <xs:element minOccurs="0" name="excludedFolders" nillable="true"
                xmlns:q10="http://schemas.microsoft.com/2003/10/Serialization/Arrays"
                type="q10:ArrayOfstring" />
        </xs:sequence>
    </xs:complexType>
</xs:element>
```

clientSid: A string that contains the security identifier of the client.

volumeGuid: The GUID of the volume.

excludedFolders: An array of string values that indicates the folders that should be excluded.

3.2.5.24.2.2 SetExcludedFoldersResponse

This element specifies output values for the **SetExcludedFolders** operation. This element has no parameters.

```

<xs:element name="SetExcludedFoldersResponse">
  <xs:complexType>
    <xs:sequence />
  </xs:complexType>
</xs:element>

```

3.2.5.25 IPCBackupServerProvider.EnableBackups

This operation enables backups on a client.

```

<wsdl:operation name="EnableBackups">
  <wsdl:input wsam:Action="http://tempuri.org/IPCBackupServerProvider/EnableBackups"
  message="tns:IPCBackupServerProvider_EnableBackups_InputMessage" />
  <wsdl:output wsam:Action="http://tempuri.org/IPCBackupServerProvider/EnableBackupsResponse"
  message="tns:IPCBackupServerProvider_EnableBackups_OutputMessage" />
  <wsdl:fault
  wsam:Action="http://tempuri.org/IPCBackupServerProvider/EnableBackupsSecurityAccessDeniedExceptionFault"
  name="SecurityAccessDeniedExceptionFault"
  message="tns:IPCBackupServerProvider_EnableBackups_SecurityAccessDeniedExceptionFault_FaultMessage" />
  <wsdl:fault
  wsam:Action="http://tempuri.org/IPCBackupServerProvider/EnableBackupsPCBackupServerFaultFault"
  name="PCBackupServerFaultFault"
  message="tns:IPCBackupServerProvider_EnableBackups_PCBackupServerFaultFault_FaultMessage" />
</wsdl:operation>

```

Upon receiving the **IPCBackupServerProvider_EnableBackups_InputMessage** request message, the protocol server enables backups on a client. Upon successful completion of the action, the server MUST respond with **IPCBackupServerProvider_EnableBackups_OutputMessage**. In the event of a failure, the appropriate SOAP fault MUST be sent to the client as specified in section [2.2.2.1](#).

3.2.5.25.1 Messages

3.2.5.25.1.1 IPCBackupServerProvider_EnableBackups_InputMessage

This is the request for the **EnableBackups** operation.

```

<wsdl:message name="IPCBackupServerProvider_EnableBackups_InputMessage">
  <wsdl:part name="parameters" element="tns:EnableBackups" />
</wsdl:message>

```

This message MUST be sent with the following SOAP action.

```
http://tempuri.org/IPCBackupServerProvider/EnableBackups
```

The body of the SOAP message MUST contain the **EnableBackups** element.

3.2.5.25.1.2 IPCBackupServerProvider_EnableBackups_OutputMessage

This is the response for the **EnableBackups** operation.

```

<wsdl:message name="IPCBackupServerProvider_EnableBackups_OutputMessage">
  <wsdl:part name="parameters" element="tns:EnableBackupsResponse" />
</wsdl:message>

```

This message MUST be sent with the following SOAP action.

```
http://tempuri.org/IPCBackupServerProvider/EnableBackupsResponse
```

The body of the SOAP message MUST contain the **EnableBackupsResponse** element.

3.2.5.25.2 Elements

3.2.5.25.2.1 EnableBackups

This element specifies input values for the **EnableBackups** operation.

```
<xs:element name="EnableBackups">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" name="clientSid" nillable="true" type="xs:string" />
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

clientSid: A string that contains the security identifier of the client.

3.2.5.25.2.2 EnableBackupsResponse

This element specifies output values for the **EnableBackups** operation. This element has no parameters.

```
<xs:element name="EnableBackupsResponse">
  <xs:complexType>
    <xs:sequence />
  </xs:complexType>
</xs:element>
```

3.2.5.26 IPCBackupServerProvider.DisableBackups

This operation disables backups on a client.

```
<wsdl:operation name="DisableBackups">
  <wsdl:input wsam:Action="http://tempuri.org/IPCBackupServerProvider/DisableBackups"
  message="tns:IPCBackupServerProvider_DisableBackups_InputMessage" />
  <wsdl:output
  wsam:Action="http://tempuri.org/IPCBackupServerProvider/DisableBackupsResponse"
  message="tns:IPCBackupServerProvider_DisableBackups_OutputMessage" />
  <wsdl:fault
  wsam:Action="http://tempuri.org/IPCBackupServerProvider/DisableBackupsSecurityAccessDeniedExceptionFault"
  name="SecurityAccessDeniedExceptionFault"
  message="tns:IPCBackupServerProvider_DisableBackups_SecurityAccessDeniedExceptionFault_FaultMessage" />
  <wsdl:fault
  wsam:Action="http://tempuri.org/IPCBackupServerProvider/DisableBackupsPCBackupServerFaultFault"
  name="PCBackupServerFaultFault"
  message="tns:IPCBackupServerProvider_DisableBackups_PCBackupServerFaultFault_FaultMessage" />
</wsdl:operation>
```

Upon receiving the **IPCBackupServerProvider_DisableBackups_InputMessage** request message, the protocol server disables backups on a client. Upon successful completion of the action, the server

MUST respond with **IPCBBackupServerProvider_DisableBackups_OutputMessage**. In the event of a failure, the appropriate SOAP fault MUST be sent to the client as specified in section [2.2.2.1](#).

3.2.5.26.1 Messages

3.2.5.26.1.1 IPCBackupServerProvider_DisableBackups_InputMessage

This is the request for the **DisableBackups** operation.

```
<wsdl:message name="IPCBBackupServerProvider_DisableBackups_InputMessage">
  <wsdl:part name="parameters" element="tns:DisableBackups" />
</wsdl:message>
```

This message MUST be sent with the following SOAP action.

<http://tempuri.org/IPCBBackupServerProvider/DisableBackups>

The body of the SOAP message MUST contain the **DisableBackups** element.

3.2.5.26.1.2 IPCBackupServerProvider_DisableBackups_OutputMessage

This is the response for the **DisableBackups** operation.

```
<wsdl:message name="IPCBBackupServerProvider_DisableBackups_OutputMessage">
  <wsdl:part name="parameters" element="tns:DisableBackupsResponse" />
</wsdl:message>
```

This message MUST be sent with the following SOAP action.

<http://tempuri.org/IPCBBackupServerProvider/DisableBackupsResponse>

The body of the SOAP message MUST contain the **DisableBackupsResponse** element.

3.2.5.26.2 Elements

3.2.5.26.2.1 DisableBackups

This element specifies input values for the **DisableBackups** operation.

```
<xs:element name="DisableBackups">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" name="clientSid" nillable="true" type="xs:string" />
      <xs:element minOccurs="0" name="deleteAllJobs" type="xs:boolean" />
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

clientSid: A string that contains the security identifier of the client.

deleteAllJobs: A Boolean where TRUE indicates that all volume jobs for the identified client need to be deleted from the volume; otherwise, the value is FALSE.

3.2.5.26.2.2 DisableBackupsResponse

This element specifies output values for the **DisableBackups** operation. This element has no parameters.

```
<xs:element name="DisableBackupsResponse">
  <xs:complexType>
    <xs:sequence />
  </xs:complexType>
</xs:element>
```

3.2.5.27 IPCBackupServerProvider.GetBackupConfiguration

This operation returns a system-wide backup configuration, such as backup window and cleanup schedule.

```
<wsdl:operation name="GetBackupConfiguration">
  <wsdl:input wsam:Action="http://tempuri.org/IPCBackupServerProvider/GetBackupConfiguration"
  message="tns:IPCBackupServerProvider GetBackupConfiguration InputMessage" />
  <wsdl:output
  wsam:Action="http://tempuri.org/IPCBackupServerProvider/GetBackupConfigurationResponse"
  message="tns:IPCBackupServerProvider GetBackupConfiguration OutputMessage" />
  <wsdl:fault
  wsam:Action="http://tempuri.org/IPCBackupServerProvider/GetBackupConfigurationPCBackupServerFault"
  name="PCBackupServerFaultFault"
  message="tns:IPCBackupServerProvider_GetBackupConfiguration_PCB backupServerFaultFault_FaultMessage" />
  <wsdl:fault
  wsam:Action="http://tempuri.org/IPCBackupServerProvider/GetBackupConfigurationSecurityAccessDeniedExceptionFault"
  name="SecurityAccessDeniedExceptionFault"
  message="tns:IPCBackupServerProvider_GetBackupConfiguration_SecurityAccessDeniedExceptionFaultMessage" />
</wsdl:operation>
```

Upon receiving the **IPCBackupServerProvider_GetBackupConfiguration_InputMessage** request message, the protocol server gets the system wide backup configuration. Upon successful completion of the action, the server MUST respond with

IPCBackupServerProvider_GetBackupConfiguration_OutputMessage. In the event of a failure, the appropriate SOAP fault MUST be sent to the client as specified in section [2.2.2.1](#).

3.2.5.27.1 Messages

3.2.5.27.1.1 IPCBackupServerProvider_GetBackupConfiguration_InputMessage

This is the request for the **GetBackupConfiguration** operation.

```
<wsdl:message name="IPCBackupServerProvider_GetBackupConfiguration_InputMessage">
  <wsdl:part name="parameters" element="tns:GetBackupConfiguration" />
</wsdl:message>
```

This message MUST be sent with the following SOAP action.

<http://tempuri.org/IPCBackupServerProvider/GetBackupConfiguration>

The body of the SOAP message MUST contain the **GetBackupConfiguration** element.

3.2.5.27.1.2 IPCBackupServerProvider_GetBackupConfiguration_OutputMessage

This is the response for the **GetBackupConfiguration** operation.

```
<wsdl:message name="IPCBBackupServerProvider_GetBackupConfiguration_OutputMessage">
  <wsdl:part name="parameters" element="tns:GetBackupConfigurationResponse" />
</wsdl:message>
```

This message MUST be sent with the following SOAP action.

```
http://tempuri.org/IPCBBackupServerProvider/GetBackupConfigurationResponse
```

The body of the SOAP message MUST contain the **GetBackupConfigurationResponse** element.

3.2.5.27.2 Elements

3.2.5.27.2.1 GetBackupConfiguration

This element specifies input values for the **GetBackupConfiguration** operation. This element has no parameters.

```
<xs:element name="GetBackupConfiguration">
  <xs:complexType>
    <xs:sequence />
  </xs:complexType>
</xs:element>
```

3.2.5.27.2.2 GetBackupConfigurationResponse

This element specifies output values for the **GetBackupConfiguration** operation.

```
<xs:element name="GetBackupConfigurationResponse">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" name="GetBackupConfigurationResult" nillable="true"
        xmlns:q11="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.DataProtection.PCBackup.BackupUtil.WcfContracts" type="q11:PCBackupConfiguration" />
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

GetBackupConfigurationResult: A **PCBackupConfiguration** (section [2.2.4.2.3](#)) complex type that contains the result of the attempt to get the backup configuration.

3.2.5.28 IPCBackupServerProvider.GetDefaultBackupConfiguration

This operation returns the default backup configuration settings, such as for backup window and cleanup schedule.

```
<wsdl:operation name="GetDefaultBackupConfiguration">
  <wsdl:input
    wsam:Action="http://tempuri.org/IPCBBackupServerProvider/GetDefaultBackupConfiguration"
    message="tns:IPCBBackupServerProvider_GetDefaultBackupConfiguration_InputMessage" />
  <wsdl:output
    wsam:Action="http://tempuri.org/IPCBBackupServerProvider/GetDefaultBackupConfigurationResponse"
    message="tns:IPCBBackupServerProvider_GetDefaultBackupConfiguration_OutputMessage" />
  <wsdl:fault
    wsam:Action="http://tempuri.org/IPCBBackupServerProvider/GetDefaultBackupConfigurationSecurity"
```

```

AccessDeniedExceptionFault" name="SecurityAccessDeniedExceptionFault"
message="tns:IPCBackupServerProvider GetDefaultBackupConfiguration SecurityAccessDeniedExcept
ionFault FaultMessage" />
<wsdl:fault
wsam:Action="http://tempuri.org/IPCBackupServerProvider/GetDefaultBackupConfigurationPCBackup
ServerFaultFault" name="PCBackupServerFaultFault"
message="tns:IPCBackupServerProvider_GetDefaultBackupConfiguration_PCB backupServerFaultFault_F
aultMessage" />
</wsdl:operation>
```

Upon receiving the **IPCBackupServerProvider_GetDefaultBackupConfiguration_InputMessage** request message, the protocol server gets the default backup configuration. Upon successful completion of the action, the server MUST respond with **IPCBackupServerProvider_GetDefaultBackupConfiguration_OutputMessage**. In the event of a failure, the appropriate SOAP fault MUST be sent to the client as specified in section [2.2.2.1](#).

3.2.5.28.1 Messages

3.2.5.28.1.1 IPCBackupServerProvider_GetDefaultBackupConfiguration_InputMessage

This is the request for the **GetDefaultBackupConfiguration** operation.

```

<wsdl:message name="IPCBackupServerProvider_GetDefaultBackupConfiguration_InputMessage">
  <wsdl:part name="parameters" element="tns:GetDefaultBackupConfiguration" />
</wsdl:message>
```

This message MUST be sent with the following SOAP action.

<http://tempuri.org/IPCBackupServerProvider/GetDefaultBackupConfiguration>

The body of the SOAP message MUST contain the **GetDefaultBackupConfiguration** element.

3.2.5.28.1.2 IPCBackupServerProvider_GetDefaultBackupConfiguration_OutputMessage

This is the response for the **GetDefaultBackupConfiguration** operation.

```

<wsdl:message name="IPCBackupServerProvider_GetDefaultBackupConfiguration_OutputMessage">
  <wsdl:part name="parameters" element="tns:GetDefaultBackupConfigurationResponse" />
</wsdl:message>
```

This message MUST be sent with the following SOAP action.

<http://tempuri.org/IPCBackupServerProvider/GetDefaultBackupConfigurationResponse>

The body of the SOAP message MUST contain the **GetDefaultBackupConfigurationResponse** element.

3.2.5.28.2 Elements

3.2.5.28.2.1 GetDefaultBackupConfiguration

This element specifies input values for the **GetDefaultBackupConfiguration** operation. This element has no parameters.

```
<xs:element name="GetDefaultBackupConfiguration">
  <xs:complexType>
    <xs:sequence />
  </xs:complexType>
</xs:element>
```

3.2.5.28.2.2 GetDefaultBackupConfigurationResponse

This element specifies output values for the **GetDefaultBackupConfiguration** operation.

```
<xs:element name="GetDefaultBackupConfigurationResponse">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" name="GetDefaultBackupConfigurationResult" nillable="true"
        xmlns:q12="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.DataProtection.PCBackup.BackupUtil.WcfContracts" type="q12:PCBackupConfiguration" />
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

GetDefaultBackupConfigurationResult: A **PCBackupConfiguration** (section [2.2.4.2.3](#)) complex type that contains the result of the attempt to get the default backup configuration.

3.2.5.29 IPCBackupServerProvider.GetBackupOperationStatus

This operation gets the status of a backup operation.

```
<wsdl:operation name="GetBackupOperationStatus">
  <wsdl:input
    wsam:Action="http://tempuri.org/IPCBackupServerProvider/GetBackupOperationStatus"
    message="tns:IPCBackupServerProvider_GetBackupOperationStatus_InputMessage" />
  <wsdl:output
    wsam:Action="http://tempuri.org/IPCBackupServerProvider/GetBackupOperationStatusResponse"
    message="tns:IPCBackupServerProvider GetBackupOperationStatus OutputMessage" />
  <wsdl:fault
    wsam:Action="http://tempuri.org/IPCBackupServerProvider/GetBackupOperationStatusSecurityAccessDeniedExceptionFault"
    name="SecurityAccessDeniedExceptionFault"
    message="tns:IPCBackupServerProvider GetBackupOperationStatus SecurityAccessDeniedExceptionFaultMessage" />
  <wsdl:fault
    wsam:Action="http://tempuri.org/IPCBackupServerProvider/GetBackupOperationStatusPCBackupServerFaultFault"
    name="PCBackupServerFaultFault"
    message="tns:IPCBackupServerProvider_GetBackupOperationStatus_PCB backupServerFaultFault_FaultMessage" />
</wsdl:operation>
```

Upon receiving the **IPCBackupServerProvider_GetBackupOperationStatus_InputMessage** request message, the protocol server gets the backup operation status. Upon successful completion of the action, the server MUST respond with **IPCBackupServerProvider_GetBackupOperationStatus_OutputMessage**. In the event of a failure, the appropriate SOAP fault MUST be sent to the client as specified in section [2.2.2.1](#).

3.2.5.29.1 Messages

3.2.5.29.1.1 IPCBackupServerProvider_GetBackupOperationStatus_InputMessage

This is the request for the **GetBackupOperationStatus** operation.

```
<wsdl:message name="IPCB backupServerProvider _GetBackupOperationStatus _InputMessage">
  <wsdl:part name="parameters" element="tns: GetBackupOperationStatus" />
</wsdl:message>
```

This message MUST be sent with the following SOAP action.

```
http://tempuri.org/IPCB backupServerProvider/GetBackupOperationStatus
```

The body of the SOAP message MUST contain the **GetBackupOperationStatus** element.

3.2.5.29.1.2 IPCBackupServerProvider _GetBackupOperationStatus _OutputMessage

This is the response for the **GetBackupOperationStatus** operation.

```
<wsdl:message name="IPCB backupServerProvider _GetBackupOperationStatus _OutputMessage">
  <wsdl:part name="parameters" element="tns: GetBackupOperationStatusResponse" />
</wsdl:message>
```

This message MUST be sent with the following SOAP action.

```
http://tempuri.org/IPCB backupServerProvider/GetBackupOperationStatusResponse
```

The body of the SOAP message MUST contain the **GetBackupOperationStatusResponse** element.

3.2.5.29.2 Elements

3.2.5.29.2.1 GetBackupOperationStatus

This element specifies input values for the **GetBackupOperationStatus** operation. This element has no parameters.

```
<x s:element name="GetBackupOperationStatus">
  <x s:complexType>
    <x s:sequence />
  </x s:complexType>
</x s:element>
```

3.2.5.29.2.2 GetBackupOperationStatusResponse

This element specifies output values for the **GetBackupOperationStatus** operation.

```
<x s:element name="GetBackupOperationStatusResponse">
  <x s:complexType>
    <x s:sequence>
      <x s:element minOccurs="0" name="GetBackupOperationStatusResult" nillable="true"
        xmlns:q13="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.DataProtection.PCBackup.BackupUtil.WcfContracts" type="q13: OperationStatusResponse" />
    </x s:sequence>
  </x s:complexType>
</x s:element>
```

3.2.5.30 IPCBackupServerProvider.GetServiceStatus

This operation gets the status of the backup service.

```
<wsdl:operation name="GetServiceStatus">
  <wsdl:input wsam:Action="http://tempuri.org/IPCBackupServerProvider/GetServiceStatus"
  message="tns:IPCBackupServerProvider GetServiceStatus_InputMessage" />
  <wsdl:output
  wsam:Action="http://tempuri.org/IPCBackupServerProvider/GetServiceStatusResponse"
  message="tns:IPCBackupServerProvider_GetServiceStatus_OutputMessage" />
  <wsdl:fault
  wsam:Action="http://tempuri.org/IPCBackupServerProvider/GetServiceStatusSecurityAccessDeniedExceptionFault"
  name="SecurityAccessDeniedExceptionFault"
  message="tns:IPCBackupServerProvider_GetServiceStatus_SecurityAccessDeniedExceptionFault_FaultMessage" />
  <wsdl:fault
  wsam:Action="http://tempuri.org/IPCBackupServerProvider/GetServiceStatusPCBackupServerFaultFault"
  name="PCBackupServerFaultFault"
  message="tns:IPCBackupServerProvider_GetServiceStatus_PCBackupServerFaultFault_FaultMessage" />
</wsdl:operation>
```

Upon receiving the **IPCBackupServerProvider_GetServiceStatus_InputMessage** request message, the protocol server gets the backup service status. Upon successful completion of the action, the server MUST respond with **IPCBackupServerProvider_GetServiceStatus_OutputMessage**. In the event of a failure, the appropriate SOAP fault MUST be sent to the client as specified in section [2.2.2.1](#).

3.2.5.30.1 Messages

3.2.5.30.1.1 IPCBackupServerProvider_GetServiceStatus_InputMessage

This is the request for the **GetServiceStatus** operation.

```
<wsdl:message name="IPCBackupServerProvider_GetServiceStatus_InputMessage">
  <wsdl:part name="parameters" element="tns:GetServiceStatus" />
</wsdl:message>
```

This message MUST be sent with the following SOAP action.

<http://tempuri.org/IPCBackupServerProvider/GetServiceStatus>

The body of the SOAP message MUST contain the **GetServiceStatus** element.

3.2.5.30.1.2 IPCBackupServerProvider_GetServiceStatus_OutputMessage

This is the response for the **GetServiceStatus** operation.

```
<wsdl:message name="IPCBackupServerProvider_GetServiceStatus_OutputMessage">
  <wsdl:part name="parameters" element="tns:GetServiceStatusResponse" />
</wsdl:message>
```

This message MUST be sent with the following SOAP action.

<http://tempuri.org/IPCBackupServerProvider/GetServiceStatusResponse>

The body of the SOAP message MUST contain the **GetServiceStatusResponse** element.

3.2.5.30.2 Elements

3.2.5.30.2.1 GetServiceStatus

This element specifies input values for the **GetServiceStatus** operation. This element has no parameters.

```
<xs:element name="GetServiceStatus">
  <xs:complexType>
    <xs:sequence />
  </xs:complexType>
</xs:element>
```

3.2.5.30.2.2 GetServiceStatusResponse

This element specifies output values for the **GetServiceStatus** operation.

```
<xs:element name="GetServiceStatusResponse">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" name="GetServiceStatusResult" nillable="true"
        xmlns:q14="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.DataProtection.PCBackup.BackupUtil.WcfContracts" type="q14:ServiceStatusResponse" />
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

GetServiceStatusResult: A **ServiceStatusResponse** (section [2.2.4.2.18](#)) value that contains the result of getting the service status.

3.2.5.31 IPCBackupServerProvider.GetWaitingOperations

This operation returns a list of pending operations.

```
<wsdl:operation name="GetWaitingOperations">
  <wsdl:input wsam:Action="http://tempuri.org/IPCBackupServerProvider/GetWaitingOperations"
    message="tns:IPCBackupServerProvider_GetWaitingOperations_InputMessage" />
  <wsdl:output
    wsam:Action="http://tempuri.org/IPCBackupServerProvider/GetWaitingOperationsResponse"
    message="tns:IPCBackupServerProvider_GetWaitingOperations_OutputMessage" />
  <wsdl:fault
    wsam:Action="http://tempuri.org/IPCBackupServerProvider/GetWaitingOperationsSecurityAccessDeniedExceptionFault"
    name="SecurityAccessDeniedExceptionFault"
    message="tns:IPCBackupServerProvider_GetWaitingOperations_SecurityAccessDeniedExceptionFault_FaultMessage" />
  <wsdl:fault
    wsam:Action="http://tempuri.org/IPCBackupServerProvider/GetWaitingOperationsPCBackupServerFault"
    name="PCBackupServerFault"
    message="tns:IPCBackupServerProvider_GetWaitingOperations_PCBackupServerFault_FaultMessage" />
</wsdl:operation>
```

Upon receiving the **IPCBackupServerProvider_GetWaitingOperations_InputMessage** request message, the protocol server gets the list of pending operations. Upon successful completion of the action, the server MUST respond with

IPCBackupServerProvider_GetWaitingOperations_OutputMessage. In the event of a failure, the appropriate SOAP fault MUST be sent to the client as specified in section [2.2.2.1](#).

3.2.5.31.1 Messages

3.2.5.31.1.1 IPCBackupServerProvider_GetWaitingOperations_InputMessage

This is the request for the **GetWaitingOperations** operation.

```
<wsdl:message name="IPCB backupServerProvider_GetWaitingOperations_InputMessage">
  <wsdl:part name="parameters" element="tns: GetWaitingOperations" />
</wsdl:message>
```

This message MUST be sent with the following SOAP action.

<http://tempuri.org/IPCB backupServerProvider/GetWaitingOperations>

The body of the SOAP message MUST contain the **GetWaitingOperations** element.

3.2.5.31.1.2 IPCBackupServerProvider_GetWaitingOperations_OutputMessage

This is the response for the **GetWaitingOperations** operation.

```
<wsdl:message name="IPCB backupServerProvider GetWaitingOperations OutputMessage">
  <wsdl:part name="parameters" element="tns: GetWaitingOperationsResponse" />
</wsdl:message>
```

This message MUST be sent with the following SOAP action.

<http://tempuri.org/IPCB backupServerProvider/GetWaitingOperationsResponse>

The body of the SOAP message MUST contain the **GetWaitingOperationsResponse** element.

3.2.5.31.2 Elements

3.2.5.31.2.1 GetWaitingOperations

This element specifies input values for the **GetWaitingOperations** operation. This element has no parameters.

```
<xs:element name="GetWaitingOperations">
  <xs:complexType>
    <xs:sequence />
  </xs:complexType>
</xs:element>
```

3.2.5.31.2.2 GetWaitingOperationsResponse

This element specifies output values for the **GetWaitingOperations** operation.

```
<xs:element name="GetWaitingOperationsResponse">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" name="GetWaitingOperationsResult" nillable="true"
        xmlns:q15="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.DataProtection.PCBackup.BackupUtil.WcfContracts" type="q15:ArrayOfWaitingOperation" />
    </xs:sequence>
```

```
</xs:complexType>
</xs:element>
```

GetWaitingOperationsResult: An array of **WaitingOperation** (section [2.2.4.2.20](#)) complex types that contains the result of the waiting operation.

3.2.5.32 IPCBackupServerProvider.SetBackupConfiguration

This operation sets system-wide backup configurations.

```
<wsdl:operation name="SetBackupConfiguration">
  <wsdl:input wsam:Action="http://tempuri.org/IPCBackupServerProvider/SetBackupConfiguration"
    message="tns:IPCBackupServerProvider_SetBackupConfiguration_InputMessage" />
  <wsdl:output
    wsam:Action="http://tempuri.org/IPCBackupServerProvider/SetBackupConfigurationResponse"
    message="tns:IPCBackupServerProvider_SetBackupConfiguration_OutputMessage" />
  <wsdl:fault
    wsam:Action="http://tempuri.org/IPCBackupServerProvider/SetBackupConfigurationSecurityAccessD
    eniedExceptionFault" name="SecurityAccessDeniedExceptionFault"
    message="tns:IPCBackupServerProvider_SetBackupConfiguration_SecurityAccessDeniedExceptionFau
    lt_FaultMessage" />
  <wsdl:fault
    wsam:Action="http://tempuri.org/IPCBackupServerProvider/SetBackupConfigurationPCBackupServerF
    aultFault" name="PCBackupServerFaultFault"
    message="tns:IPCBackupServerProvider_SetBackupConfiguration_PCBackupServerFaultFault_FaultMes
    sage" />
</wsdl:operation>
```

Upon receiving the **IPCBackupServerProvider_SetBackupConfiguration_InputMessage** request message, the protocol server sets the system-wide backup configurations. Upon successful completion of the action, the server MUST respond with

IPCBackupServerProvider_SetBackupConfiguration_OutputMessage. In the event of a failure, the appropriate SOAP fault MUST be sent to the client as specified in section [2.2.2.1](#).

3.2.5.32.1 Messages

3.2.5.32.1.1 IPCBackupServerProvider_SetBackupConfiguration_InputMessage

This is the request for the **SetBackupConfiguration** operation.

```
<wsdl:message name="IPCBackupServerProvider_SetBackupConfiguration_InputMessage">
  <wsdl:part name="parameters" element="tns:SetBackupConfiguration" />
</wsdl:message>
```

This message MUST be sent with the following SOAP action.

```
http://tempuri.org/IPCBackupServerProvider/SetBackupConfiguration
```

The body of the SOAP message MUST contain the **SetBackupConfiguration** element.

3.2.5.32.1.2 IPCBackupServerProvider_SetBackupConfiguration_OutputMessage

This is the response for the **SetBackupConfiguration** operation.

```
<wsdl:message name="IPCBackupServerProvider_SetBackupConfiguration_OutputMessage">
  <wsdl:part name="parameters" element="tns:SetBackupConfigurationResponse" />
</wsdl:message>
```

```
</wsdl:message>
```

This message MUST be sent with the following SOAP action.

```
http://tempuri.org/IPCBackupServerProvider/SetBackupConfigurationResponse
```

The body of the SOAP message MUST contain the **SetBackupConfigurationResponse** element.

3.2.5.32.2 Elements

3.2.5.32.2.1 SetBackupConfiguration

This element specifies input values for the **SetBackupConfiguration** operation.

```
<xs:element name="SetBackupConfiguration">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" name="backupConfig" nillable="true"
        xmlns:q16="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.DataProtection.PCBackup.BackupUtil.WcfContracts" type="q16:PCBackupConfiguration" />
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

backupConfig: A **PCBackupConfiguration** (section [2.2.4.2.3](#)) complex type that contains the backup configuration details.

3.2.5.32.2.2 SetBackupConfigurationResponse

This element specifies output values for the **SetBackupConfiguration** operation. This element has no parameters.

```
<xs:element name="SetBackupConfigurationResponse">
  <xs:complexType>
    <xs:sequence />
  </xs:complexType>
</xs:element>
```

3.2.5.33 IPCBackupServerProvider.GetUsedBytes

This operation returns the total number of bytes used for all backups.

```
<wsdl:operation name="GetUsedBytes">
  <wsdl:input wsam:Action="http://tempuri.org/IPCBackupServerProvider/GetUsedBytes"
    message="tns:IPCBackupServerProvider_GetUsedBytes_InputMessage" />
  <wsdl:output wsam:Action="http://tempuri.org/IPCBackupServerProvider/GetUsedBytesResponse"
    message="tns:IPCBackupServerProvider_GetUsedBytes_OutputMessage" />
  <wsdl:fault
    wsam:Action="http://tempuri.org/IPCBackupServerProvider/GetUsedBytesPCBackupServerFaultFault"
    name="PCBackupServerFaultFault"
    message="tns:IPCBackupServerProvider_GetUsedBytes_PCBackupServerFaultFault_FaultMessage" />
  <wsdl:fault
    wsam:Action="http://tempuri.org/IPCBackupServerProvider/GetUsedBytesSecurityAccessDeniedExceptionFault"
    name="SecurityAccessDeniedExceptionFault"
    message="tns:IPCBackupServerProvider_GetUsedBytes_SecurityAccessDeniedExceptionFault_FaultMessage" />
```

```
</wsdl:operation>
```

Upon receiving the **IPCB backupServerProvider_GetUsedBytes_InputMessage** request message, the protocol server returns the total number of bytes used for all backups. Upon successful completion of the action, the server MUST respond with **IPCB backupServerProvider_GetUsedBytes_OutputMessage**. In the event of a failure, the appropriate SOAP fault MUST be sent to the client as specified in section [2.2.2.1](#).

3.2.5.33.1 Messages

3.2.5.33.1.1 IPCBackupServerProvider_GetUsedBytes_InputMessage

This is the request for the **GetUsedBytes** operation.

```
<wsdl:message name="IPCB backupServerProvider_GetUsedBytes_InputMessage">
  <wsdl:part name="parameters" element="tns:GetUsedBytes" />
</wsdl:message>
```

This message MUST be sent with the following SOAP action.

```
http://tempuri.org/IPCB backupServerProvider/GetUsedBytes
```

The body of the SOAP message MUST contain the **GetUsedBytes** element.

3.2.5.33.1.2 IPCBackupServerProvider_GetUsedBytes_OutputMessage

This is the response for the **GetUsedBytes** operation.

```
<wsdl:message name="IPCB backupServerProvider_GetUsedBytes_OutputMessage">
  <wsdl:part name="parameters" element="tns:GetUsedBytesResponse" />
</wsdl:message>
```

This message MUST be sent with the following SOAP action.

```
http://tempuri.org/IPCB backupServerProvider/GetUsedBytesResponse
```

The body of the SOAP message MUST contain the **GetUsedBytesResponse** element.

3.2.5.33.2 Elements

3.2.5.33.2.1 GetUsedBytes

This element specifies input values for the **GetUsedBytes** operation. This element has no parameters.

```
<xss:element name="GetUsedBytes">
  <xss:complexType>
    <xss:sequence />
  </xss:complexType>
</xss:element>
```

3.2.5.33.2.2 GetUsedBytesResponse

This element specifies output values for the **GetUsedBytes** operation.

```
<xs:element name="GetUsedBytesResponse">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" name="GetUsedBytesResult" type="xs:long" />
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

GetUsedBytesResult: A long integer that contains the number of bytes used by the backup.

3.2.5.34 IPCBackupServerProvider.StartCleanup

This operation starts the cleanup operation.

```
<wsdl:operation name="StartCleanup">
  <wsdl:input wsam:Action="http://tempuri.org/IPCBackupServerProvider/StartCleanup"
  message="tns:IPCBackupServerProvider_StartCleanup_InputMessage" />
  <wsdl:output wsam:Action="http://tempuri.org/IPCBackupServerProvider/StartCleanupResponse"
  message="tns:IPCBackupServerProvider_StartCleanup_OutputMessage" />
  <wsdl:fault
  wsam:Action="http://tempuri.org/IPCBackupServerProvider/StartCleanupPCBackupServerFaultFault"
  name="PCBackupServerFaultFault"
  message="tns:IPCBackupServerProvider_StartCleanup_PCBackupServerFaultFault_FaultMessage" />
  <wsdl:fault
  wsam:Action="http://tempuri.org/IPCBackupServerProvider/StartCleanupSecurityAccessDeniedExceptionFault"
  name="SecurityAccessDeniedExceptionFault"
  message="tns:IPCBackupServerProvider_StartCleanup_SecurityAccessDeniedExceptionFault_FaultMessage" />
</wsdl:operation>
```

Upon receiving the **IPCBackupServerProvider_StartCleanup_InputMessage** request message, the protocol server starts the cleanup operation. Upon successful completion of the action, the server MUST respond with **IPCBackupServerProvider_StartCleanup_OutputMessage**. In the event of a failure, the appropriate SOAP fault MUST be sent to the client as specified in section [2.2.2.1](#).

3.2.5.34.1 Messages

3.2.5.34.1.1 IPCBackupServerProvider_StartCleanup_InputMessage

This is the request for the **StartCleanup** operation.

```
<wsdl:message name="IPCBackupServerProvider_StartCleanup_InputMessage">
  <wsdl:part name="parameters" element="tns:StartCleanup" />
</wsdl:message>
```

This message MUST be sent with the following SOAP action.

`http://tempuri.org/IPCBackupServerProvider/StartCleanup`

The body of the SOAP message MUST contain the **StartCleanup** element.

3.2.5.34.1.2 IPCBackupServerProvider_StartCleanup_OutputMessage

This is the response for the **StartCleanup** operation.

```
<wsdl:message name="IPCB backupServerProvider_StartCleanup_OutputMessage">
  <wsdl:part name="parameters" element="tns:StartCleanupResponse" />
</wsdl:message>
```

This message MUST be sent with the following SOAP action.

```
http://tempuri.org/IPCB backupServerProvider/StartCleanupResponse
```

The body of the SOAP message MUST contain the StartCleanupResponse element.

3.2.5.34.2 Elements

3.2.5.34.2.1 StartCleanup

This element specifies input values for the **StartCleanup** operation. This element has no parameters.

```
<xs:element name="StartCleanup">
  <xs:complexType>
    <xs:sequence />
  </xs:complexType>
</xs:element>
```

3.2.5.34.2.2 StartCleanupResponse

This element specifies output values for the **StartCleanup** operation. This element has no parameters.

```
<xs:element name="StartCleanupResponse">
  <xs:complexType>
    <xs:sequence />
  </xs:complexType>
</xs:element>
```

3.2.5.35 IPCBackupServerProvider.CancelCleanup

This operation cancels the cleanup operation.

```
<wsdl:operation name="CancelCleanup">
  <wsdl:input wsam:Action="http://tempuri.org/IPCB backupServerProvider/CancelCleanup"
  message="tns:IPCB backupServerProvider_CancelCleanup_InputMessage" />
  <wsdl:output wsam:Action="http://tempuri.org/IPCB backupServerProvider/CancelCleanupResponse"
  message="tns:IPCB backupServerProvider_CancelCleanup_OutputMessage" />
  <wsdl:fault
  wsam:Action="http://tempuri.org/IPCB backupServerProvider/CancelCleanupPCBackupServerFaultFault
  " name="PCBackupServerFaultFault"
  message="tns:IPCB backupServerProvider_CancelCleanup_PCBackupServerFaultFault_FaultMessage" />
  <wsdl:fault
  wsam:Action="http://tempuri.org/IPCB backupServerProvider/CancelCleanupSecurityAccessDeniedExceptionFault"
  name="SecurityAccessDeniedExceptionFault"
  message="tns:IPCB backupServerProvider_CancelCleanup_SecurityAccessDeniedExceptionFault_FaultMessage" />
</wsdl:operation>
```

Upon receiving the **IPCB backupServerProvider_CancelCleanup_InputMessage** request message, the protocol server cancels the cleanup operation. Upon successful completion of the action, the server MUST respond with **IPCB backupServerProvider_CancelCleanup_OutputMessage**. In the

event of a failure, the appropriate SOAP fault MUST be sent to the client as specified in section [2.2.2.1](#).

3.2.5.35.1 Messages

3.2.5.35.1.1 IPCBackupServerProvider_CancelCleanup_InputMessage

This is the request for the **CancelCleanup** operation.

```
<wsdl:message name="IPCB backupServerProvider_CancelCleanup_InputMessage">
  <wsdl:part name="parameters" element="tns:CancelCleanup" />
</wsdl:message>
```

This message MUST be sent with the following SOAP action.

<http://tempuri.org/IPCB backupServerProvider/CancelCleanup>

The body of the SOAP message MUST contain the **CancelCleanup** element.

3.2.5.35.1.2 IPCBackupServerProvider_CancelCleanup_OutputMessage

This is the response for the **CancelCleanup** operation.

```
<wsdl:message name="IPCB backupServerProvider_CancelCleanup_OutputMessage">
  <wsdl:part name="parameters" element="tns:CancelCleanupResponse" />
</wsdl:message>
```

This message MUST be sent with the following SOAP action.

<http://tempuri.org/IPCB backupServerProvider/CancelCleanupResponse>

The body of the SOAP message MUST contain the **CancelCleanupResponse** element.

3.2.5.35.2 Elements

3.2.5.35.2.1 CancelCleanup

This element specifies input values for the **CancelCleanup** operation. This element has no parameters.

```
<xs:element name="CancelCleanup">
  <xs:complexType>
    <xs:sequence />
  </xs:complexType>
</xs:element>
```

3.2.5.35.2.2 CancelCleanupResponse

This element specifies output values for the **CancelCleanup** operation. This element has no parameters.

```
<xs:element name="CancelCleanupResponse">
  <xs:complexType>
```

```
<xs:sequence />
</xs:complexType>
</xs:element>
```

3.2.5.36 IPCBackupServerProvider.StartRepair

This operation starts the repair operation.

```
<wsdl:operation name="StartRepair">
  <wsdl:input wsam:Action="http://tempuri.org/IPCBackupServerProvider/StartRepair"
    message="tns:IPCBackupServerProvider_StartRepair_InputMessage" />
  <wsdl:output wsam:Action="http://tempuri.org/IPCBackupServerProvider/StartRepairResponse"
    message="tns:IPCBackupServerProvider_StartRepair_OutputMessage" />
  <wsdl:fault
    wsam:Action="http://tempuri.org/IPCBackupServerProvider/StartRepairPCBackupServerFaultFault"
    name="PCBackupServerFaultFault"
    message="tns:IPCBackupServerProvider_StartRepair_PCBackupServerFaultFault_FaultMessage" />
  <wsdl:fault
    wsam:Action="http://tempuri.org/IPCBackupServerProvider/StartRepairSecurityAccessDeniedExceptionFault"
    name="SecurityAccessDeniedExceptionFault"
    message="tns:IPCBackupServerProvider_StartRepair_SecurityAccessDeniedExceptionFault_FaultMessage" />
</wsdl:operation>
```

Upon receiving the **IPCBackupServerProvider_StartRepair_InputMessage** request message, the protocol server starts the repair operation. Upon successful completion of the action, the server MUST respond with the **IPCBackupServerProvider_StartRepair_OutputMessage**. In the event of a failure, the appropriate SOAP fault MUST be sent to the client as specified in section [2.2.2.1](#).

3.2.5.36.1 Messages

3.2.5.36.1.1 IPCBackupServerProvider_StartRepair_InputMessage

This is the request for the **StartRepair** operation.

```
<wsdl:message name="IPCBackupServerProvider_StartRepair_InputMessage">
  <wsdl:part name="parameters" element="tns:StartRepair" />
</wsdl:message>
```

This message MUST be sent with the following SOAP action.

```
http://tempuri.org/IPCBackupServerProvider/StartRepair
```

The body of the SOAP message MUST contain the **StartRepair** element.

3.2.5.36.1.2 IPCBackupServerProvider_StartRepair_OutputMessage

This is the response for the **StartRepair** operation.

```
<wsdl:message name="IPCBackupServerProvider_StartRepair_OutputMessage">
  <wsdl:part name="parameters" element="tns:StartRepairResponse" />
</wsdl:message>
```

This message MUST be sent with the following SOAP action.

<http://tempuri.org/IPCBackupServerProvider/StartRepairResponse>

The body of the SOAP message MUST contain the **StartRepairResponse** element.

3.2.5.36.2 Elements

3.2.5.36.2.1 StartRepair

This element specifies input values for the **StartRepair** operation. This element has no parameters.

```
<xs:element name="StartRepair">
  <xs:complexType>
    <xs:sequence />
  </xs:complexType>
</xs:element>
```

3.2.5.36.2.2 StartRepairResponse

This element specifies output values for the **StartRepair** operation. This element has no parameters.

```
<xs:element name="StartRepairResponse">
  <xs:complexType>
    <xs:sequence />
  </xs:complexType>
</xs:element>
```

3.2.5.37 IPCBackupServerProvider.CancelRepair

This operation cancels the repair operation.

```
<wsdl:operation name="CancelRepair">
  <wsdl:input wsam:Action="http://tempuri.org/IPCBackupServerProvider/CancelRepair"
  message="tns:IPCBackupServerProvider_CancelRepair_InputMessage" />
  <wsdl:output wsam:Action="http://tempuri.org/IPCBackupServerProvider/CancelRepairResponse"
  message="tns:IPCBackupServerProvider_CancelRepair_OutputMessage" />
  <wsdl:fault
  wsam:Action="http://tempuri.org/IPCBackupServerProvider/CancelRepairPCBackupServerFaultFault"
  name="PCBackupServerFaultFault"
  message="tns:IPCBackupServerProvider_CancelRepair_PCBackupServerFaultFault_FaultMessage" />
  <wsdl:fault
  wsam:Action="http://tempuri.org/IPCBackupServerProvider/CancelRepairSecurityAccessDeniedExceptionFault"
  name="SecurityAccessDeniedExceptionFault"
  message="tns:IPCBackupServerProvider_CancelRepair_SecurityAccessDeniedExceptionFault_FaultMessage" />
</wsdl:operation>
```

Upon receiving the **IPCBackupServerProvider_CancelRepair_InputMessage** request message, the protocol server cancels the repair operation. Upon successful completion of the action, the server MUST respond with **IPCBackupServerProvider_CancelRepair_OutputMessage**. In the event of a failure, the appropriate SOAP fault MUST be sent to the client as specified in section [2.2.2.1](#).

3.2.5.37.1 Messages

3.2.5.37.1.1 IPCBackupServerProvider_CancelRepair_InputMessage

This is the request for the **CancelRepair** operation.

```
<wsdl:message name="IPCBackupServerProvider_CancelRepair_InputMessage">
  <wsdl:part name="parameters" element="tns:CancelRepair" />
</wsdl:message>
```

This message MUST be sent with the following SOAP action.

```
http://tempuri.org/IPCBackupServerProvider/CancelRepair
```

The body of the SOAP message MUST contain the **CancelRepair** element.

3.2.5.37.1.2 IPCBackupServerProvider_CancelRepair_OutputMessage

This is the response for the **CancelRepair** operation.

```
<wsdl:message name="IPCBackupServerProvider_CancelRepair_OutputMessage">
  <wsdl:part name="parameters" element="tns:CancelRepairResponse" />
</wsdl:message>
```

This message MUST be sent with the following SOAP action.

```
http://tempuri.org/IPCBackupServerProvider/CancelRepairResponse
```

The body of the SOAP message MUST contain the **CancelRepairResponse** element.

3.2.5.37.2 Elements

3.2.5.37.2.1 CancelRepair

This element specifies input values for the **CancelRepair** operation. This element has no parameters.

```
<xs:element name="CancelRepair">
  <xs:complexType>
    <xs:sequence />
  </xs:complexType>
</xs:element>
```

3.2.5.37.2.2 CancelRepairResponse

This element specifies output values for the **CancelRepair** operation. This element has no parameters.

```
<xs:element name="CancelRepairResponse">
  <xs:complexType>
    <xs:sequence />
  </xs:complexType>
</xs:element>
```

3.2.5.38 IPCBackupServerProvider.GetLastRepairResult

This operation gets the most recent repair result.

```
<wsdl:operation name="GetLastRepairResult">
```

```

<wsdl:input wsam:Action="http://tempuri.org/IPCBackupServerProvider/GetLastRepairResult"
message="tns:IPCBackupServerProvider_GetLastRepairResult_InputMessage" />
<wsdl:output
wsam:Action="http://tempuri.org/IPCBackupServerProvider/GetLastRepairResultResponse"
message="tns:IPCBackupServerProvider_GetLastRepairResult_OutputMessage" />
<wsdl:fault
wsam:Action="http://tempuri.org/IPCBackupServerProvider/GetLastRepairResultSecurityAccessDeni
edExceptionFault" name="SecurityAccessDeniedExceptionFault"
message="tns:IPCBackupServerProvider_GetLastRepairResult_SecurityAccessDeniedExceptionFault_F
aultMessage" />
<wsdl:fault
wsam:Action="http://tempuri.org/IPCBackupServerProvider/GetLastRepairResultPCBackupServerFau
ltFault" name="PCBackupServerFaultFault"
message="tns:IPCBackupServerProvider_GetLastRepairResult_PCBackupServerFaultFault_FaultMessag
e" />
</wsdl:operation>

```

Upon receiving the **IPCBackupServerProvider_GetLastRepairResult_InputMessage** request message, the protocol server gets the most recent repair result. Upon successful completion of the action, the server MUST respond with **IPCBackupServerProvider_GetLastRepairResult_OutputMessage**. In the event of a failure, the appropriate SOAP fault MUST be sent to the client as specified in section [2.2.2.1](#).

3.2.5.38.1 Messages

3.2.5.38.1.1 IPCBackupServerProvider_GetLastRepairResult_InputMessage

This is the request for the **GetLastRepairResult** operation.

```

<wsdl:message name="IPCBackupServerProvider_GetLastRepairResult_InputMessage">
  <wsdl:part name="parameters" element="tns:GetLastRepairResult" />
</wsdl:message>

```

This message MUST be sent with the following SOAP action.

```
http://tempuri.org/IPCBackupServerProvider/GetLastRepairResult
```

The body of the SOAP message MUST contain the **GetLastRepairResult** element.

3.2.5.38.1.2 IPCBackupServerProvider_GetLastRepairResult_OutputMessage

This is the response for the **GetLastRepairResult** operation.

```

<wsdl:message name="IPCBackupServerProvider_GetLastRepairResult_OutputMessage">
  <wsdl:part name="parameters" element="tns:GetLastRepairResultResponse" />
</wsdl:message>

```

This message MUST be sent with the following SOAP action.

```
http://tempuri.org/IPCBackupServerProvider/GetLastRepairResultResponse
```

The body of the SOAP message MUST contain the **GetLastRepairResultResponse** element.

3.2.5.38.2 Elements

3.2.5.38.2.1 GetLastRepairResult

This element specifies input values for the **GetLastRepairResult** operation. This element has no parameters.

```
<xs:element name="GetLastRepairResult">
  <xs:complexType>
    <xs:sequence />
  </xs:complexType>
</xs:element>
```

3.2.5.38.2.2 GetLastRepairResultResponse

This element specifies output values for the **GetLastRepairResult** operation.

```
<xs:element name="GetLastRepairResultResponse">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" name="GetLastRepairResultResult" nillable="true"
        xmlns:q17="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.DataProtection.PCBackup.BackupUtil.WcfContracts" type="q17:RepairResult" />
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

GetLastRepairResultResult: A **RepairResult** (section [2.2.4.2.21](#)) complex type that contains the last repair result.

3.2.5.39 IPCBackupServerProvider.StartConsistencyChecker

This operation starts the consistency checking operation.

```
<wsdl:operation name="StartConsistencyChecker">
  <wsdl:input
    wsam:Action="http://tempuri.org/IPCBackupServerProvider/StartConsistencyChecker"
    message="tns:IPCBackupServerProvider_StartConsistencyChecker_InputMessage" />
  <wsdl:output
    wsam:Action="http://tempuri.org/IPCBackupServerProvider/StartConsistencyCheckerResponse"
    message="tns:IPCBackupServerProvider_StartConsistencyChecker_OutputMessage" />
  <wsdl:fault
    wsam:Action="http://tempuri.org/IPCBackupServerProvider/StartConsistencyCheckerPCBackupServerFaultFault"
    name="PCBackupServerFaultFault"
    message="tns:IPCBackupServerProvider_StartConsistencyChecker PCBackupServerFaultFault FaultMessage" />
  <wsdl:fault
    wsam:Action="http://tempuri.org/IPCBackupServerProvider/StartConsistencyCheckerSecurityAccessDeniedExceptionFault"
    name="SecurityAccessDeniedExceptionFault"
    message="tns:IPCBackupServerProvider_StartConsistencyChecker SecurityAccessDeniedExceptionFaultMessage" />
</wsdl:operation>
```

Upon receiving the **IPCBackupServerProvider_StartConsistencyChecker_InputMessage** request message, the protocol server starts the consistency checking operation. Upon successful completion of the action, the server MUST respond with **IPCBackupServerProvider_StartConsistencyChecker_OutputMessage**. In the event of a failure, the appropriate SOAP fault MUST be sent to the client as specified in section [2.2.2.1](#).

3.2.5.39.1 Messages

3.2.5.39.1.1 IPCBackupServerProvider_StartConsistencyChecker_InputMessage

This is the request for the **StartConsistencyChecker** operation.

```
<wsdl:message name="IPCB backupServerProvider_StartConsistencyChecker_InputMessage">
  <wsdl:part name="parameters" element="tns:StartConsistencyChecker" />
</wsdl:message>
```

This message MUST be sent with the following SOAP action.

<http://tempuri.org/IPCB backupServerProvider/StartConsistencyChecker>

The body of the SOAP message MUST contain the **StartConsistencyChecker** element.

3.2.5.39.1.2 IPCBackupServerProvider_StartConsistencyChecker_OutputMessage

This is the response for the **StartConsistencyChecker** operation.

```
<wsdl:message name="IPCB backupServerProvider_StartConsistencyChecker_OutputMessage">
  <wsdl:part name="parameters" element="tns:StartConsistencyCheckerResponse" />
</wsdl:message>
```

This message MUST be sent with the following SOAP action.

<http://tempuri.org/IPCB backupServerProvider/StartConsistencyCheckerResponse>

The body of the SOAP message MUST contain the **StartConsistencyCheckerResponse** element.

3.2.5.39.2 Elements

3.2.5.39.2.1 StartConsistencyChecker

This element specifies input values for the **StartConsistencyChecker** operation.

```
<x s:element name="StartConsistencyChecker">
  <x s:complexType>
    <x s:sequence>
      <x s:element minOccurs="0" name="fPreempt" type="x s:boolean" />
    </x s:sequence>
  </x s:complexType>
</x s:element>
```

fPreempt: A Boolean where TRUE indicates that the existing operation will be preempted; otherwise, the value is FALSE.

3.2.5.39.2.2 StartConsistencyCheckerResponse

This element specifies output values for the **StartConsistencyChecker** operation. This element has no parameters.

```
<x s:element name="StartConsistencyCheckerResponse">
  <x s:complexType>
    <x s:sequence />
  </x s:complexType>
```

```
</xs:element>
```

3.2.5.40 IPCBackupServerProvider.CancelConsistencyChecker

This operation cancels the consistency checking operation.

```
<wsdl:operation name="CancelConsistencyChecker">
  <wsdl:input
    wsam:Action="http://tempuri.org/IPCBackupServerProvider/CancelConsistencyChecker"
    message="tns:IPCBackupServerProvider_CancelConsistencyChecker_InputMessage" />
  <wsdl:output
    wsam:Action="http://tempuri.org/IPCBackupServerProvider/CancelConsistencyCheckerResponse"
    message="tns:IPCBackupServerProvider_CancelConsistencyChecker_OutputMessage" />
  <wsdl:fault
    wsam:Action="http://tempuri.org/IPCBackupServerProvider/CancelConsistencyCheckerSecurityAccessDeniedExceptionFault" name="SecurityAccessDeniedExceptionFault"
    message="tns:IPCBackupServerProvider_CancelConsistencyChecker_SecurityAccessDeniedExceptionFaultMessage" />
  <wsdl:fault
    wsam:Action="http://tempuri.org/IPCBackupServerProvider/CancelConsistencyCheckerPCBackupServerFaultFault" name="PCBackupServerFaultFault"
    message="tns:IPCBackupServerProvider_CancelConsistencyChecker_PCBackupServerFaultFault_FaultMessage" />
</wsdl:operation>
```

Upon receiving the **IPCBackupServerProvider_CancelConsistencyChecker_InputMessage** request message, the protocol server cancels the consistency checking operation. Upon successful completion of the action, the server MUST respond with

IPCBackupServerProvider_CancelConsistencyChecker_OutputMessage. In the event of a failure, the appropriate SOAP fault MUST be sent to the client as specified in section [2.2.1](#).

3.2.5.40.1 Messages

3.2.5.40.1.1 IPCBackupServerProvider_CancelConsistencyChecker_InputMessage

This is the request for the **CancelConsistencyChecker** operation.

```
<wsdl:message name="IPCBackupServerProvider_CancelConsistencyChecker_InputMessage">
  <wsdl:part name="parameters" element="tns:CancelConsistencyChecker" />
</wsdl:message>
```

This message MUST be sent with the following SOAP action.

```
http://tempuri.org/IPCBackupServerProvider/CancelConsistencyChecker
```

The body of the SOAP message MUST contain the **CancelConsistencyChecker** element.

3.2.5.40.1.2 IPCBackupServerProvider_CancelConsistencyChecker_OutputMessage

This is the response for the **CancelConsistencyChecker** operation.

```
<wsdl:message name="IPCBackupServerProvider_CancelConsistencyChecker_OutputMessage">
  <wsdl:part name="parameters" element="tns:CancelConsistencyCheckerResponse" />
</wsdl:message>
```

This message MUST be sent with the following SOAP action.

```
http://tempuri.org/IPCBackupServerProvider/CancelConsistencyCheckerResponse
```

The body of the SOAP message MUST contain the **CancelConsistencyCheckerResponse** element.

3.2.5.40.2 Elements

3.2.5.40.2.1 CancelConsistencyChecker

This element specifies input values for the **CancelConsistencyChecker** operation. This element has no parameters.

```
<xs:element name="CancelConsistencyChecker">
  <xs:complexType>
    <xs:sequence />
  </xs:complexType>
</xs:element>
```

3.2.5.40.2.2 CancelConsistencyCheckerResponse

This element specifies output values for the **CancelConsistencyChecker** operation. This element has no parameters.

```
<xs:element name="CancelConsistencyCheckerResponse">
  <xs:complexType>
    <xs:sequence />
  </xs:complexType>
</xs:element>
```

3.2.5.41 IPCBackupServerProvider.Remove

This operation removes a specific client.

```
<wsdl:operation name="Remove">
  <wsdl:input wsam:Action="http://tempuri.org/IPCBackupServerProvider/Remove"
  message="tns:IPCBackupServerProvider_Remove_InputMessage" />
  <wsdl:output wsam:Action="http://tempuri.org/IPCBackupServerProvider/RemoveResponse"
  message="tns:IPCBackupServerProvider_Remove_OutputMessage" />
  <wsdl:fault
  wsam:Action="http://tempuri.org/IPCBackupServerProvider/RemoveSecurityAccessDeniedExceptionFa
  ult" name="SecurityAccessDeniedExceptionFault"
  message="tns:IPCBackupServerProvider_Remove_SecurityAccessDeniedExceptionFault_FaultMessage" />
  <wsdl:fault
  wsam:Action="http://tempuri.org/IPCBackupServerProvider/RemovePCBackupServerFaultFault"
  name="PCBackupServerFaultFault"
  message="tns:IPCBackupServerProvider_Remove_PCBackupServerFaultFault_FaultMessage" />
</wsdl:operation>
```

Upon receiving the **IPCBackupServerProvider_Remove_InputMessage** request message, the protocol server removes the specified client. Upon successful completion of the action, the server MUST respond with **IPCBackupServerProvider_Remove_OutputMessage**. In the event of a failure, the appropriate SOAP fault MUST be sent to the client as specified in section [2.2.2.1](#).

3.2.5.41.1 Messages

3.2.5.41.1.1 IPCBackupServerProvider_Remove_InputMessage

This is the request for the **Remove** operation.

```
<wsdl:message name="IPCBackupServerProvider_Remove_InputMessage">
  <wsdl:part name="parameters" element="tns:Remove" />
</wsdl:message>
```

This message MUST be sent with the following SOAP action.

<http://tempuri.org/IPCBackupServerProvider/Remove>

The body of the SOAP message MUST contain the **Remove** element.

3.2.5.41.1.2 IPCBackupServerProvider_Remove_OutputMessage

This is the response for the **Remove** operation.

```
<wsdl:message name="IPCBackupServerProvider_Remove_OutputMessage">
  <wsdl:part name="parameters" element="tns:RemoveResponse" />
</wsdl:message>
```

This message MUST be sent with the following SOAP action.

<http://tempuri.org/IPCBackupServerProvider/RemoveResponse>

The body of the SOAP message MUST contain the **RemoveResponse** element.

3.2.5.41.2 Elements

3.2.5.41.2.1 Remove

This element specifies input values for the **Remove** operation.

```
<xs:element name="Remove">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" name="clientSid" nillable="true" type="xs:string" />
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

clientSid: A string that contains the security identifier of the client.

3.2.5.41.2.2 RemoveResponse

This element specifies output values for the **Remove** operation. This element has no parameters.

```
<xs:element name="RemoveResponse">
  <xs:complexType>
    <xs:sequence />
  </xs:complexType>
</xs:element>
```

3.2.5.42 IPCBackupServerProvider.CalculateVolumeAsync

This operation calculates the specific volume.

```
<wsdl:operation name="CalculateVolumeAsync">
  <wsdl:input wsam:Action="http://tempuri.org/IPCBackupServerProvider/CalculateVolumeAsync"
    message="tns:IPCBackupServerProvider_CalculateVolumeAsync_InputMessage" />
  <wsdl:output
    wsam:Action="http://tempuri.org/IPCBackupServerProvider/CalculateVolumeAsyncResponse"
    message="tns:IPCBackupServerProvider_CalculateVolumeAsync_OutputMessage" />
  <wsdl:fault
    wsam:Action="http://tempuri.org/IPCBackupServerProvider/CalculateVolumeAsyncSecurityAccessDeniedExceptionFault"
    name="SecurityAccessDeniedExceptionFault"
    message="tns:IPCBackupServerProvider_CalculateVolumeAsync_SecurityAccessDeniedExceptionFault_FaultMessage" />
  <wsdl:fault
    wsam:Action="http://tempuri.org/IPCBackupServerProvider/CalculateVolumeAsyncPCBackupServerFault"
    name="PCBackupServerFaultFault"
    message="tns:IPCBackupServerProvider_CalculateVolumeAsync_PCBackupServerFaultFault_FaultMessage" />
</wsdl:operation>
```

Upon receiving the **IPCBackupServerProvider_CalculateVolumeAsync_InputMessage** request message, the protocol server calculates the specific volume. Upon successful completion of the action, the server MUST respond with

IPCBackupServerProvider_CalculateVolumeAsync_OutputMessage. In the event of a failure, the appropriate SOAP fault MUST be sent to the client as specified in section [2.2.2.1](#).

3.2.5.42.1 Messages

3.2.5.42.1.1 IPCBackupServerProvider_CalculateVolumeAsync_InputMessage

This is the request for the **CalculateVolumeAsync** operation.

```
<wsdl:message name="IPCBackupServerProvider_CalculateVolumeAsync_InputMessage">
  <wsdl:part name="parameters" element="tns:CalculateVolumeAsync" />
</wsdl:message>
```

This message MUST be sent with the following SOAP action.

<http://tempuri.org/IPCBackupServerProvider/CalculateVolumeAsync>

The body of the SOAP message MUST contain the **CalculateVolumeAsync** element.

3.2.5.42.1.2 IPCBackupServerProvider_CalculateVolumeAsync_OutputMessage

This is the response for the **CalculateVolumeAsync** operation.

```
<wsdl:message name="IPCBackupServerProvider_CalculateVolumeAsync_OutputMessage">
  <wsdl:part name="parameters" element="tns:CalculateVolumeAsyncResponse" />
</wsdl:message>
```

This message MUST be sent with the following SOAP action.

<http://tempuri.org/IPCBackupServerProvider/CalculateVolumeAsyncResponse>

The body of the SOAP message MUST contain the **CalculateVolumeAsyncResponse** element.

3.2.5.42.2 Elements

3.2.5.42.2.1 CalculateVolumeAsync

This element specifies input values for the **CalculateVolumeAsync** operation.

```
<xs:element name="CalculateVolumeAsync">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" name="clientSid" nillable="true" type="xs:string" />
      <xs:element minOccurs="0" name="volumeGuid"
        xmlns:q18="http://schemas.microsoft.com/2003/10/Serialization/" type="q18:guid" />
      <xs:element minOccurs="0" name="excludedFolders" nillable="true"
        xmlns:q19="http://schemas.microsoft.com/2003/10/Serialization/Arrays"
        type="q19:ArrayOfstring" />
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

clientSid: A string that contains the security identifier of the client.

volumeGuid: The GUID of the volume.

excludedFolders: An array of string values that contains the folder that should be excluded.

3.2.5.42.2.2 CalculateVolumeAsyncResponse

This element specifies output values for the **CalculateVolumeAsync** operation.

```
<xs:element name="CalculateVolumeAsyncResponse">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" name="CalculateVolumeAsyncResult" type="xs:boolean" />
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

CalculateVolumeAsyncResult: A Boolean where TRUE indicates that the calculation has successfully started; otherwise, the value is FALSE.

3.2.5.43 IPCBackupServerProvider.GetFolderChildren

This operation gets the children of specified folder.

```
<wsdl:operation name="GetFolderChildren">
  <wsdl:input wsam:Action="http://tempuri.org/IPCBackupServerProvider/GetFolderChildren"
    message="tns:IPCBackupServerProvider_GetFolderChildren_InputMessage" />
  <wsdl:output
    wsam:Action="http://tempuri.org/IPCBackupServerProvider/GetFolderChildrenResponse"
    message="tns:IPCBackupServerProvider_GetFolderChildren_OutputMessage" />
  <wsdl:fault
    wsam:Action="http://tempuri.org/IPCBackupServerProvider/GetFolderChildrenSecurityAccessDenied
    ExceptionFault" name="SecurityAccessDeniedExceptionFault"
    message="tns:IPCBackupServerProvider GetFolderChildren SecurityAccessDeniedExceptionFault Fau
    ltMessage" />
  <wsdl:fault
    wsam:Action="http://tempuri.org/IPCBackupServerProvider/GetFolderChildrenPCBackupServerFaultF
    ault" name="PCBackupServerFaultFault"
```

```
message="tns:IPCBackupServerProvider_GetFolderChildren_PCTBackupServerFaultFault_FaultMessage"
/>
</wsdl:operation>
```

Upon receiving the **IPCBackupServerProvider_GetFolderChildren_InputMessage** request message, the protocol server gets the children of the specified folder. Upon successful completion of the action, the server MUST respond with **IPCBackupServerProvider_GetFolderChildren_OutputMessage**. In the event of a failure, the appropriate SOAP fault MUST be sent to the client as specified in section [2.2.2.1](#).

3.2.5.43.1 Messages

3.2.5.43.1.1 IPCBackupServerProvider_GetFolderChildren_InputMessage

This is the request for the **GetFolderChildren** operation.

```
<wsdl:message name="IPCBackupServerProvider_GetFolderChildren_InputMessage">
  <wsdl:part name="parameters" element="tns:GetFolderChildren" />
</wsdl:message>
```

This message MUST be sent with the following SOAP action.

<http://tempuri.org/IPCBackupServerProvider/GetFolderChildren>

The body of the SOAP message MUST contain the **GetFolderChildren** element.

3.2.5.43.1.2 IPCBackupServerProvider_GetFolderChildren_OutputMessage

This is the response for the **GetFolderChildren** operation.

```
<wsdl:message name="IPCBackupServerProvider_GetFolderChildren_OutputMessage">
  <wsdl:part name="parameters" element="tns:GetFolderChildrenResponse" />
</wsdl:message>
```

This message MUST be sent with the following SOAP action.

<http://tempuri.org/IPCBackupServerProvider/GetFolderChildrenResponse>

The body of the SOAP message MUST contain the **GetFolderChildrenResponse** element.

3.2.5.43.2 Elements

3.2.5.43.2.1 GetFolderChildren

This element specifies input values for the **GetFolderChildren** operation.

```
<xss:element name="GetFolderChildren">
  <xss:complexType>
    <xss:sequence>
      <xss:element minOccurs="0" name="clientSid" nillable="true" type="xss:string" />
      <xss:element minOccurs="0" name="folderRequest" nillable="true"
        xmlns:q20="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.DataProtection.PCBackup.BackupUtil.WcfContracts" type="q20:FolderRequest" />
      <xss:element minOccurs="0" name="index" type="xss:int" />
```

```

</xs:sequence>
</xs:complexType>
</xs:element>

```

clientSid: A string that contains the security identifier of the client.

folderRequest: A **FolderRequest** (section [2.2.4.2.16](#)) complex type that contains the data needed for getting folder children.

index: An integer that contains the index of the request.

3.2.5.43.2.2 GetFolderChildrenResponse

This element specifies output values for the **GetFolderChildren** operation.

```

<xs:element name="GetFolderChildrenResponse">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" name="GetFolderChildrenResult" nillable="true"
        xmlns:q21="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.DataProtection.PCBackup.BackupUtil.WcfContracts" type="q21:FolderInfoGroup" />
    </xs:sequence>
  </xs:complexType>
</xs:element>

```

GetFolderChildrenResult: A **FolderInfoGroup** (section [2.2.4.2.15](#)) complex type that contains the results of the attempt to get folder children.

3.2.5.44 IPCBackupServerProvider.GetConnectedVolumes

This operation gets the connected volumes of the specified client.

```

<wsdl:operation name="GetConnectedVolumes">
  <wsdl:input wsam:Action="http://tempuri.org/IPCBackupServerProvider/GetConnectedVolumes"
    message="tns:IPCBackupServerProvider_GetConnectedVolumes_InputMessage" />
  <wsdl:output
    wsam:Action="http://tempuri.org/IPCBackupServerProvider/GetConnectedVolumesResponse"
    message="tns:IPCBackupServerProvider_GetConnectedVolumes_OutputMessage" />
  <wsdl:fault
    wsam:Action="http://tempuri.org/IPCBackupServerProvider/GetConnectedVolumesPCBackupServerFault"
    name="PCBackupServerFaultFault"
    message="tns:IPCBackupServerProvider_GetConnectedVolumes_PCBackupServerFaultFault_FaultMessage" />
  <wsdl:fault
    wsam:Action="http://tempuri.org/IPCBackupServerProvider/GetConnectedVolumesSecurityAccessDeniedExceptionFault"
    name="SecurityAccessDeniedExceptionFault"
    message="tns:IPCBackupServerProvider_GetConnectedVolumes_SecurityAccessDeniedExceptionFault_FaultMessage" />
</wsdl:operation>

```

Upon receiving the **IPCBackupServerProvider_GetConnectedVolumes_InputMessage** request message, the protocol server gets the connected volumes of the client. Upon successful completion of the action, the server MUST respond with

IPCBackupServerProvider_GetConnectedVolumes_OutputMessage. In the event of a failure, the appropriate SOAP fault MUST be sent to the client as specified in section [2.2.2.1](#).

3.2.5.44.1 Messages

3.2.5.44.1.1 IPCBackupServerProvider_GetConnectedVolumes_InputMessage

This is the request for the **GetConnectedVolumes** operation.

```
<wsdl:message name="IPCBackupServerProvider_GetConnectedVolumes_InputMessage">
  <wsdl:part name="parameters" element="tns:GetConnectedVolumes" />
</wsdl:message>
```

This message MUST be sent with the following SOAP action.

```
http://tempuri.org/IPCBackupServerProvider/GetConnectedVolumes
```

The body of the SOAP message MUST contain the **GetConnectedVolumes** element.

3.2.5.44.1.2 IPCBackupServerProvider_GetConnectedVolumes_OutputMessage

This is the response for the **GetConnectedVolumes** operation.

```
<wsdl:message name="IPCBackupServerProvider_GetConnectedVolumes_OutputMessage">
  <wsdl:part name="parameters" element="tns:GetConnectedVolumesResponse" />
</wsdl:message>
```

This message MUST be sent with the following SOAP action.

```
http://tempuri.org/IPCBackupServerProvider/GetConnectedVolumesResponse
```

The body of the SOAP message MUST contain the **GetConnectedVolumesResponse** element.

3.2.5.44.2 Elements

3.2.5.44.2.1 GetConnectedVolumes

This element specifies input values for the **GetConnectedVolumes** operation.

```
<xs:element name="GetConnectedVolumes">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" name="clientSid" nillable="true" type="xs:string" />
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

clientSid: A string that contains the security identifier of the client.

3.2.5.44.2.2 GetConnectedVolumesResponse

This element specifies output values for the **GetConnectedVolumes** operation.

```
<xs:element name="GetConnectedVolumesResponse">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" name="GetConnectedVolumesResult" nillable="true"
        xmlns:q22="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.DataProtection.PCBackup.BackupUtil.WcfContracts" type="q22:ArrayOfClientVolumeInfo" />
```

```
</xs:sequence>
</xs:complexType>
</xs:element>
```

GetConnectedVolumesResult: An array of **ClientVolumeInfo** (section [2.2.4.2.11](#)) complex types that contains the result of the attempt to get connected volumes.

3.2.5.45 IPCBackupServerProvider.CleanFolderSizeCalculation

This operation resets the folder size calculation.

```
<wsdl:operation name="CleanFolderSizeCalculation">
  <wsdl:input
    wsam:Action="http://tempuri.org/IPCBackupServerProvider/CleanFolderSizeCalculation"
    message="tns:IPCBackupServerProvider CleanFolderSizeCalculation InputMessage" />
</wsdl:operation>
```

Upon receiving the **IPCBackupServerProvider_CleanFolderSizeCalculation_InputMessage** request message, the protocol server resets its folder size calculations. Upon successful completion of the action, the server MUST respond with **IPCBackupServerProvider_CleanFolderSizeCalculation_OutputMessage**. In the event of a failure, the appropriate SOAP fault MUST be sent to the client as specified in section [2.2.2.1](#).

3.2.5.45.1 Messages

3.2.5.45.1.1 IPCBackupServerProvider_CleanFolderSizeCalculation_InputMessage

This is the request for the **CleanFolderSizeCalculation** operation.

```
<wsdl:message name="IPCBackupServerProvider_CleanFolderSizeCalculation_InputMessage">
  <wsdl:part name="parameters" element="tns:CleanFolderSizeCalculation" />
</wsdl:message>
```

This message MUST be sent with the following SOAP action.

<http://tempuri.org/IPCBackupServerProvider/CleanFolderSizeCalculation>

The body of the SOAP message MUST contain the **CleanFolderSizeCalculation** element.

3.2.5.45.2 Elements

3.2.5.45.2.1 CleanFolderSizeCalculation

This element specifies input values for the **CleanFolderSizeCalculation** operation.

```
<xs:element name="CleanFolderSizeCalculation">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" name="clientSid" nillable="true" type="xs:string" />
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

clientSid: A string that contains the security identifier of the client.

3.2.5.46 IPCBackupServerProvider.StartBackup

This operation starts a backup operation on a particular client.

```
<wsdl:operation name="StartBackup">
  <wsdl:input wsam:Action="http://tempuri.org/IPCBackupServerProvider/StartBackup"
  message="tns:IPCBackupServerProvider_StartBackup_InputMessage" />
  <wsdl:output wsam:Action="http://tempuri.org/IPCBackupServerProvider/StartBackupResponse"
  message="tns:IPCBackupServerProvider_StartBackup_OutputMessage" />
  <wsdl:fault
  wsam:Action="http://tempuri.org/IPCBackupServerProvider/StartBackupPCBackupServerFaultFault"
  name="PCBackupServerFaultFault"
  message="tns:IPCBackupServerProvider_StartBackup_PCBBackupServerFaultFault_FaultMessage" />
  <wsdl:fault
  wsam:Action="http://tempuri.org/IPCBackupServerProvider/StartBackupSecurityAccessDeniedExceptionFault"
  name="SecurityAccessDeniedExceptionFault"
  message="tns:IPCBackupServerProvider_StartBackup_SecurityAccessDeniedExceptionFault_FaultMessage" />
</wsdl:operation>
```

Upon receiving the **IPCBackupServerProvider_StartBackup_InputMessage** request message, the protocol server starts a backup operation on the particular client. Upon successful completion of the action, the server MUST respond with **IPCBackupServerProvider_StartBackup_OutputMessage**. In the event of a failure, the appropriate SOAP fault MUST be sent to the client as specified in section [2.2.2.1](#).

3.2.5.46.1 Messages

3.2.5.46.1.1 IPCBackupServerProvider_StartBackup_InputMessage

This is the request for the **StartBackup** operation.

```
<wsdl:message name="IPCBackupServerProvider_StartBackup_InputMessage">
  <wsdl:part name="parameters" element="tns:StartBackup" />
</wsdl:message>
```

This message MUST be sent with the following SOAP action.

`http://tempuri.org/IPCBackupServerProvider/StartBackup`

The body of the SOAP message MUST contain the **StartBackup** element.

3.2.5.46.1.2 IPCBackupServerProvider_StartBackup_OutputMessage

This is the response for the **StartBackup** operation.

```
<wsdl:message name="IPCBackupServerProvider_StartBackup_OutputMessage">
  <wsdl:part name="parameters" element="tns:StartBackupResponse" />
</wsdl:message>
```

This message MUST be sent with the following SOAP action.

`http://tempuri.org/IPCBackupServerProvider/StartBackupResponse`

The body of the SOAP message MUST contain the **StartBackupResponse** element.

3.2.5.46.2 Elements

3.2.5.46.2.1 StartBackup

This element specifies input values for the **StartBackup** operation.

```
<xs:element name="StartBackup">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" name="clientSid" nillable="true" type="xs:string" />
      <xs:element minOccurs="0" name="description" nillable="true" type="xs:string" />
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

clientSid: A string that contains the security identifier of the client.

description: A string that contains the description of the backup.

3.2.5.46.2.2 StartBackupResponse

This element specifies output values for the **StartBackup** operation. This element has no parameters.

```
<xs:element name="StartBackupResponse">
  <xs:complexType>
    <xs:sequence />
  </xs:complexType>
</xs:element>
```

3.2.5.47 IPCBackupServerProvider.CancelBackup

This operation cancels a backup on a particular client.

```
<wsdl:operation name="CancelBackup">
  <wsdl:input wsam:Action="http://tempuri.org/IPCBackupServerProvider/CancelBackup"
  message="tns:IPCBackupServerProvider_CancelBackup_InputMessage" />
  <wsdl:output wsam:Action="http://tempuri.org/IPCBackupServerProvider/CancelBackupResponse"
  message="tns:IPCBackupServerProvider_CancelBackup_OutputMessage" />
  <wsdl:fault
  wsam:Action="http://tempuri.org/IPCBackupServerProvider/CancelBackupSecurityAccessDeniedExceptionFault"
  name="SecurityAccessDeniedExceptionFault"
  message="tns:IPCBackupServerProvider CancelBackup SecurityAccessDeniedExceptionFault FaultMessage" />
  <wsdl:fault
  wsam:Action="http://tempuri.org/IPCBackupServerProvider/CancelBackupPCBackupServerFaultFault"
  name="PCBackupServerFaultFault"
  message="tns:IPCBackupServerProvider CancelBackup PCBackupServerFaultFault FaultMessage" />
</wsdl:operation>
```

Upon receiving the **IPCBackupServerProvider_CancelBackup_InputMessage** request message, the protocol server cancels a backup on the particular client. Upon successful completion of the action, the server MUST respond with **IPCBackupServerProvider_CancelBackup_OutputMessage**. In the event of a failure, the appropriate SOAP fault MUST be sent to the client as specified in section [2.2.2.1](#).

3.2.5.47.1 Messages

3.2.5.47.1.1 IPCBackupServerProvider_CancelBackup_InputMessage

This is the request for the **CancelBackup** operation.

```
<wsdl:message name="IPCB backupServerProvider_CancelBackup_InputMessage">
  <wsdl:part name="parameters" element="tns:CancelBackup" />
</wsdl:message>
```

This message MUST be sent with the following SOAP action.

```
http://tempuri.org/IPCB backupServerProvider/CancelBackup
```

The body of the SOAP message MUST contain the **CancelBackup** element.

3.2.5.47.1.2 IPCBackupServerProvider_CancelBackup_OutputMessage

This is the response for the **CancelBackup** operation.

```
<wsdl:message name="IPCB backupServerProvider_CancelBackup_OutputMessage">
  <wsdl:part name="parameters" element="tns:CancelBackupResponse" />
</wsdl:message>
```

This message MUST be sent with the following SOAP action.

```
http://tempuri.org/IPCB backupServerProvider/CancelBackupResponse
```

The body of the SOAP message MUST contain the **CancelBackupResponse** element.

3.2.5.47.2 Elements

3.2.5.47.2.1 CancelBackup

This element specifies input values for the **CancelBackup** operation.

```
<xs:element name="CancelBackup">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" name="clientSid" nillable="true" type="xs:string" />
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

clientSid: A string that contains the security identifier of the client.

3.2.5.47.2.2 CancelBackupResponse

This element specifies output values for the **CancelBackup** operation. This element has no parameters.

```
<xs:element name="CancelBackupResponse">
  <xs:complexType>
    <xs:sequence />
  </xs:complexType>
</xs:element>
```

3.2.5.48 IPCBackupServerProvider.StartBackupService

This operation starts the backup service.

```
<wsdl:operation name="StartBackupService">
  <wsdl:input wsam:Action="http://tempuri.org/IPCBackupServerProvider/StartBackupService"
  message="tns:IPCBackupServerProvider_StartBackupService_InputMessage" />
  <wsdl:output
  wsam:Action="http://tempuri.org/IPCBackupServerProvider/StartBackupServiceResponse"
  message="tns:IPCBackupServerProvider_StartBackupService_OutputMessage" />
  <wsdl:fault
  wsam:Action="http://tempuri.org/IPCBackupServerProvider/StartBackupServicePCBackupServerFault
  Fault" name="PCBackupServerFaultFault"
  message="tns:IPCBackupServerProvider_StartBackupService_PCBackupServerFaultFault_FaultMessage"
  />
  <wsdl:fault
  wsam:Action="http://tempuri.org/IPCBackupServerProvider/StartBackupServiceSecurityAccessDenie
  dExceptionFault" name="SecurityAccessDeniedExceptionFault"
  message="tns:IPCBackupServerProvider_StartBackupService_SecurityAccessDeniedExceptionFault_Fa
  ultMessage" />
</wsdl:operation>
```

Upon receiving the **IPCBackupServerProvider_StartBackupService_InputMessage** request message, the protocol server starts the backup service. Upon successful completion of the action, the server MUST respond with **IPCBackupServerProvider_StartBackupService_OutputMessage**. In the event of a failure, the appropriate SOAP fault MUST be sent to the client as specified in section [2.2.2.1](#).

3.2.5.48.1 Messages

3.2.5.48.1.1 IPCBackupServerProvider_StartBackupService_InputMessage

This is the request for the **StartBackupService** operation.

```
<wsdl:message name="IPCBackupServerProvider_StartBackupService_InputMessage">
  <wsdl:part name="parameters" element="tns:StartBackupService" />
</wsdl:message>
```

This message MUST be sent with the following SOAP action.

<http://tempuri.org/IPCBackupServerProvider/StartBackupService>

The body of the SOAP message MUST contain the **StartBackupService** element.

3.2.5.48.1.2 IPCBackupServerProvider_StartBackupService_OutputMessage

This is the response for the **StartBackupService** operation.

```
<wsdl:message name="IPCBackupServerProvider_StartBackupService_OutputMessage">
  <wsdl:part name="parameters" element="tns:StartBackupServiceResponse" />
</wsdl:message>
```

This message MUST be sent with the following SOAP action.

<http://tempuri.org/IPCBackupServerProvider/StartBackupServiceResponse>

The body of the SOAP message MUST contain the **StartBackupServiceResponse** element.

3.2.5.48.2 Elements

3.2.5.48.2.1 StartBackupService

This element specifies input values for the **StartBackupService** operation. This element has no parameters.

```
<xs:element name="StartBackupService">
  <xs:complexType>
    <xs:sequence />
  </xs:complexType>
</xs:element>
```

3.2.5.48.2.2 StartBackupServiceResponse

This element specifies output values for the **StartBackupService** operation. This element has no parameters.

```
<xs:element name="StartBackupServiceResponse">
  <xs:complexType>
    <xs:sequence />
  </xs:complexType>
</xs:element>
```

3.2.5.49 IPCBackupServerProvider.StopBackupService

This operation stops the backup service.

```
<wsdl:operation name="StopBackupService">
  <wsdl:input wsam:Action="http://tempuri.org/IPCBackupServerProvider/StopBackupService"
  message="tns:IPCBackupServerProvider_StopBackupService_InputMessage" />
  <wsdl:output
  wsam:Action="http://tempuri.org/IPCBackupServerProvider/StopBackupServiceResponse"
  message="tns:IPCBackupServerProvider StopBackupService OutputMessage" />
  <wsdl:fault
  wsam:Action="http://tempuri.org/IPCBackupServerProvider/StopBackupServiceSecurityAccessDenied
  ExceptionFault" name="SecurityAccessDeniedExceptionFault"
  message="tns:IPCBackupServerProvider StopBackupService SecurityAccessDeniedExceptionFault Fau
  ltMessage" />
  <wsdl:fault
  wsam:Action="http://tempuri.org/IPCBackupServerProvider/StopBackupServicePCBackupServerFaultF
  ault" name="PCBackupServerFaultFault"
  message="tns:IPCBackupServerProvider_StopBackupService_PCBackupServerFaultFault_FaultMessage"
  />
</wsdl:operation>
```

Upon receiving the **IPCBackupServerProvider_StopBackupService_InputMessage** request message, the protocol server stops the backup service. Upon successful completion of the action, the server MUST respond with **IPCBackupServerProvider_StopBackupService_OutputMessage**. In the event of a failure, the appropriate SOAP fault MUST be sent to the client as specified in section [2.2.2.1](#).

3.2.5.49.1 Messages

3.2.5.49.1.1 IPCBackupServerProvider_StopBackupService_InputMessage

This is the request for the **StopBackupService** operation.

```
<wsdl:message name="IPCBBackupServerProvider_StopBackupService_InputMessage">
  <wsdl:part name="parameters" element="tns:StopBackupService" />
</wsdl:message>
```

This message MUST be sent with the following SOAP action.

```
http://tempuri.org/IPCBBackupServerProvider/StopBackupService
```

The body of the SOAP message MUST contain the **StopBackupService** element.

3.2.5.49.1.2 IPCBackupServerProvider_StopBackupService_OutputMessage

This is the response for the **StopBackupService** operation.

```
<wsdl:message name="IPCBBackupServerProvider_StopBackupService_OutputMessage">
  <wsdl:part name="parameters" element="tns:StopBackupServiceResponse" />
</wsdl:message>
```

This message MUST be sent with the following SOAP action.

```
http://tempuri.org/IPCBBackupServerProvider/StopBackupServiceResponse
```

The body of the SOAP message MUST contain the **StopBackupServiceResponse** element.

3.2.5.49.2 Elements

3.2.5.49.2.1 StopBackupService

This element specifies input values for the **StopBackupService** operation.

```
<xss:element name="StopBackupService">
  <xss:complexType>
    <xss:sequence>
      <xss:element minOccurs="0" name="reason"
        xmlns:q23="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.DataProtection.PCBackup.BackupUtil.WcfContracts" type="q23:StopReason" />
    </xss:sequence>
  </xss:complexType>
</xss:element>
```

reason: A **StopReason** (section [2.2.5.2.17](#)) string that contains the reason why the backup service should be stopped.

3.2.5.49.2.2 StopBackupServiceResponse

This element specifies output values for the **StopBackupService** operation. This element has no parameters.

```
<xss:element name="StopBackupServiceResponse">
  <xss:complexType>
    <xss:sequence />
  </xss:complexType>
```

```
</xs:element>
```

3.2.5.50 IPCBackupServerProvider.NotifyBackupOperationStatusChange

This callback operation notifies the caller of a change in the status of a backup operation.

```
<wsdl:operation name="NotifyBackupOperationStatusChange">
  <wsdl:output
    wsam:Action="http://tempuri.org/IPCBackupServerProvider/NotifyBackupOperationStatusChange"
    message="tns:IPCBackupServerProvider_NotifyBackupOperationStatusChange_OutputCallbackMessage"
  />
</wsdl:operation>
```

Upon receiving the

IPCBackupServerProvider_NotifyBackupOperationStatusChange_OutputCallbackMessage request message, the protocol client is notified of a change in the status of a backup operation.

3.2.5.50.1 Messages

3.2.5.50.1.1 IPCBackupServerProvider_NotifyBackupOperationStatusChange_OutputCallbackMessage

This is the request for the **NotifyBackupOperationStatusChange** operation.

```
<wsdl:message
  name="IPCBackupServerProvider_NotifyBackupOperationStatusChange_OutputCallbackMessage">
  <wsdl:part name="parameters" element="tns:NotifyBackupOperationStatusChange" />
</wsdl:message>
```

This message MUST be sent with the following SOAP action.

```
http://tempuri.org/IPCBackupServerProvider/NotifyBackupOperationStatusChange
```

The body of the SOAP message MUST contain the **NotifyBackupOperationStatusChange** element.

3.2.5.50.2 Elements

3.2.5.50.2.1 NotifyBackupOperationStatusChange

This element specifies input values for the **NotifyBackupOperationStatusChange** operation.

```
<xs:element name="NotifyBackupOperationStatusChange">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" name="backupOperationStatus" nillable="true"
        xmlns:q24="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.DataProtection.PCBackup.BackupUtil.WcfContracts" type="q24:OperationStatusResponse" />
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

backupOperationStatus: An **OperationStatusResponse** (section [2.2.4.2.17](#)) complex type that contains the status of the backup operation.

3.2.5.51 IPCBackupServerProvider.VolumeCalculatorProgress

This callback operation notifies the caller of the current progress of a volume calculation.

```
<wsdl:operation name="VolumeCalculatorProgress">
  <wsdl:output
    wsam:Action="http://tempuri.org/IPCBackupServerProvider/VolumeCalculatorProgress"
    message="tns:IPCBackupServerProvider_VolumeCalculatorProgress_OutputCallbackMessage" />
</wsdl:operation>
```

Upon receiving the

IPCBackupServerProvider_VolumeCalculatorProgress_OutputCallbackMessage request message, the protocol client is notified of the current progress of a volume calculation.

3.2.5.51.1 Messages

3.2.5.51.1.1 IPCBackupServerProvider_VolumeCalculatorProgress_OutputCallbackMessage

This is the request for the **VolumeCalculatorProgress** operation.

```
<wsdl:message name="IPCBackupServerProvider_VolumeCalculatorProgress_OutputCallbackMessage">
  <wsdl:part name="parameters" element="tns:VolumeCalculatorProgress" />
</wsdl:message>
```

This message MUST be sent with the following SOAP action.

<http://tempuri.org/IPCBackupServerProvider/VolumeCalculatorProgress>

The body of the SOAP message MUST contain the **VolumeCalculatorProgress** element.

3.2.5.51.2 Elements

3.2.5.51.2.1 VolumeCalculatorProgress

This element specifies input values for the **VolumeCalculatorProgress** operation.

```
<xss:element name="VolumeCalculatorProgress">
  <xss:complexType>
    <xss:sequence>
      <xss:element minOccurs="0" name="guid"
        xmlns:q25="http://schemas.microsoft.com/2003/10/Serialization/" type="q25:guid" />
      <xss:element minOccurs="0" name="percentDone" type="xs:int" />
      <xss:element minOccurs="0" name="folders" nillable="true"
        xmlns:q26="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.DataProtection.PCBackup.BackupUtil.WcfContracts" type="q26:ArrayOfFolderInfo" />
    </xss:sequence>
  </xss:complexType>
</xss:element>
```

guid: The GUID of the specified volume.

percentDone: An integer that indicates the progress of the current operation; valid values range from 0 to 100 percent.

Folders: An array of **FolderInfo** (section [2.2.4.2.14](#)) complex types that contains details about the folder that have already been calculated.

3.2.5.52 IPCBackupServerProvider.NotifyServiceStatusChange

This callback operation notifies the caller of a service status change.

```
<wsdl:operation name="NotifyServiceStatusChange">
  <wsdl:output
    wsam:Action="http://tempuri.org/IPCBackupServerProvider/NotifyServiceStatusChange"
    message="tns:IPCBackupServerProvider_NotifyServiceStatusChange_OutputCallbackMessage" />
</wsdl:operation>
```

Upon receiving the **IPCBackupServerProvider_NotifyServiceStatusChange_OutputCallbackMessage** request message, the protocol client is notified of service status change.

3.2.5.52.1 Messages

3.2.5.52.1.1 IPCBackupServerProvider_NotifyServiceStatusChange_OutputCallbackMessage

This is the request for the **NotifyServiceStatusChange** operation.

```
<wsdl:message name="IPCBackupServerProvider_NotifyServiceStatusChange_OutputCallbackMessage">
  <wsdl:part name="parameters" element="tns:NotifyServiceStatusChange" />
</wsdl:message>
```

This message MUST be sent with the following SOAP action.

`http://tempuri.org/IPCBackupServerProvider/NotifyServiceStatusChange`

The body of the SOAP message MUST contain the **NotifyServiceStatusChange** element.

3.2.5.52.2 Elements

3.2.5.52.2.1 NotifyServiceStatusChange

This element specifies input values for the **NotifyServiceStatusChange** operation.

```
<xs:element name="NotifyServiceStatusChange">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" name="serviceStatus" nillable="true"
        xmlns:q27="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.DataProtection.PCBackup.BackupUtil.WcfContracts" type="q27:ServiceStatusResponse" />
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

serviceStatus: A **ServiceStatusResponse** (section [2.2.4.2.18](#)) complex type that contains the service status details.

3.2.6 Timer Events

None.

3.2.7 Other Local Events

None.

3.3 Health Provider Service Contract Details

3.3.1 Abstract Data Model

This section describes a conceptual service contract that an implementation maintains to participate in this protocol. The described operations of the service contract are provided to facilitate the explanation of how the protocol behaves. This document does not mandate that implementations adhere to this service contract as long as their external behavior is consistent with how it is described in this document.

3.3.1.1 ADM_ArrayOfKeyValueOfstringArrayOfAlertInfo

This is an array of dictionaries of the alert information for all joined devices.

Key: The SID of the device.

Value: The alert information of the given alert.

3.3.1.1.1 Data Model

3.3.1.1.1.1 AlertInfo

Note that the AlertInfo data model also has a corresponding SOAP complex type defined in section [2.2.4.3.2](#).

ActionPerformed: The health definition alert action performed when the alert is detected.

AdditionalInfo: A store of additional information bound to the alert.

DateAndTime: The date and time when the alert was raised.

Description: The description of the alert.

Escalate: TRUE, if the alert will be escalated to admin through email; otherwise, FALSE.

FeatureName: The name of the feature definition to which the health definition belongs.

FeatureTitle: The title of the health definition for which the alert is raised.

HealthDefinitionName: The name of the feature definition for which the alert is raised.

HealthDefinitionTitle: The title of the feature definition to which the health definition belongs.

InstanceId: The instance ID of the alert.

IsNew: TRUE, if the alert being raised is not already present; otherwise, FALSE.

IsRepairDefined: TRUE, if the alert is repairable; otherwise, FALSE.

IsSuppressed: TRUE, if the alert is suppressed; otherwise, FALSE.

IsSystem: TRUE, if an alert is a system alert; otherwise, FALSE.

LastSuppressedDateTime: The last time the alert was suppressed.

MachineId: Typically the SID of the client computer.

MachineName: The name of the machine on which the alert is raised.

RepairActionPerformed: The information about the health definition repair action performed when the alert is repaired.

Severity: The health status:

- OK: There is no existing alert.
- Information: Informational alert.
- Warning: Warning alert.
- Critical: Critical alert.
- Report: An alert which collects information from the client.

SupportLink: The support link of the alert.

TroubleshootSteps: The troubleshooting steps of the alert.

Troubleshooter: Allow the user to launch the task from the Alert Viewer.

3.3.2 Timers

None.

3.3.3 Initialization

None.

3.3.4 Higher-Layer Triggered Events

None.

3.3.5 Message Processing Events and Sequencing Rules

OperationContract	Description
IAlertProviderCallback.RaiseAlertCompleted	Indicates the raise alert has completed.
IAlertProviderCallback.ClearAlertCompleted	Indicates the clear alert has completed.
IAlertProviderCallback.SuppressAlertCompleted	Indicates the suppress alert has completed.
IAlertProviderCallback.RepairAlertCompleted	Indicates the repair alert has completed.
IAlertProviderCallback.EvaluateAlertsCompleted	Indicates the health evaluation cycle has completed.
IAlertProviderCallback.RaisedAlerts	Provides the alerts raised on a client computer.
IAlertProviderCallback.ClearedAlerts	Provides the alerts cleared on a client computer.
IAlertSyncCallback.AlertChanged	Indicates a callback for alert changed event.

OperationContract	Description
IAlertManagementProviderService.GetAllNetworkAlerts	Gets the list of AlertInfo objects representing the alerts currently active in the entire network.
IAlertManagementProviderService.ClearAlertOneWay	Clears an alert that is currently active in the network, either on the primary server or on a client computer. This operation does not wait until the alert is cleared before returning.
IAlertManagementProviderService.ClearAlert	Clears an alert that is currently active in the network, either on the primary server or on a client computer. This operation waits until the alert is cleared before returning.
IAlertManagementProviderService.SuppressAlertOneWay	Changes the suppress flag on an alert that is currently active in the network, either on the primary server or on a client computer, to the value provided. This operation does not wait until the alert is suppressed before returning.
IAlertManagementProviderService.SuppressAlert	Changes the suppress flag on an alert that is currently active in the network, either on the primary server or on a client computer with the value provided. This operation waits until the alert is suppressed before returning.
IAlertManagementProviderService.RaiseAlertOneWay	Raises an alert for a health definition defined for a feature. This operation does not wait until the alert is raised before returning.
IAlertManagementProviderService.RaiseAlert	Raises an alert for a health definition defined for a feature. This operation waits until the alert is raised before returning.
IAlertManagementProviderService.IsAuthorized	Determines whether the connected user has network alert access. This is a provider service running on the primary server.
IAlertSynchProviderService.RegisterClientAgent	Registers a client computer for callback with IAlertSynchProviderService provider service running on the primary server.
IAlertSynchProviderService.SynchronizeAlerts	Synchronizes the list of AlertInfo objects representing alerts raised, cleared, updated, or evaluated on a particular machine in the network to the server.
IAlertSynchProviderService.ClearCallbackCommandQueue	Clears all the pending command queues for the machine. Used when a device cannot have an Agent running.
IAlertSynchProviderService.GetPlugInInformation	Get information about all the installed plugins.
IAlertSynchProviderService.DownloadDefinition	Get stream of definition file of a feature plug-in.
IAlertSynchProviderService.DownloadConfiguration	Get stream of definition configuration file of a feature plug-in.

3.3.5.1 IAlertProviderCallback.RaiseAlertCompleted

This operation is a callback indicating that the raise alert operation has completed.

```

<wsdl:operation name="RaiseAlertCompleted">
  <wsdl:output
    wsam:Action="http://tempuri.org/IAlertManagementProviderService/RaiseAlertCompleted"
    message="tns:IAlertManagementProviderService_RaiseAlertCompleted_OutputCallbackMessage" />
</wsdl:operation>

```

3.3.5.1.1 Messages

3.3.5.1.1.1 IAlertProviderCallback_RaiseAlertCompleted_OutputCallbackMessage

This is the request for the **RaiseAlertCompleted** operation.

```

<wsdl:message
  name="IAlertManagementProviderService_RaiseAlertCompleted_OutputCallbackMessage">
  <wsdl:part name="parameters" element="tns:RaiseAlertCompleted" />
</wsdl:message>

```

This message MUST be sent with the following SOAP action.

`http://tempuri.org/IAlertManagementProviderService/RaiseAlertCompleted`

The body of the SOAP message MUST contain the **RaiseAlertCompleted** element.

3.3.5.1.2 Elements

3.3.5.1.2.1 RaiseAlertCompleted

This element specifies input values for the **RaiseAlertCompleted** operation.

```

<xs:element name="RaiseAlertCompleted">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" name="alertInfo" nillable="true"
        xmlns:q5="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.NetworkHea
        lth.AlertFramework" type="q5:AlertInfo" />
      <xs:element minOccurs="0" name="errMessage" nillable="true" type="xs:string" />
    </xs:sequence>
  </xs:complexType>
</xs:element>

```

alertInfo: An **AlertInfo** (section [2.2.4.3.2](#)) complex type that contains the alert information.

errMessage: A string that contains any error received when raising an alert.

3.3.5.2 IAlertProviderCallback.ClearAlertCompleted

This operation is a callback indicating that the clear alert operation has completed.

```

<wsdl:operation name="ClearAlertCompleted">
  <wsdl:output
    wsam:Action="http://tempuri.org/IAlertManagementProviderService/ClearAlertCompleted"
    message="tns:IAlertManagementProviderService_ClearAlertCompleted_OutputCallbackMessage" />
</wsdl:operation>

```

3.3.5.2.1 Messages

3.3.5.2.1.1 IAlertProviderCallback_ClearAlertCompleted_OutputCallbackMessage

This is the request for the **ClearAlertCompleted** operation.

```
<wsdl:message name="IAlertProviderCallback_ClearAlertCompleted_OutputCallbackMessage">
  <wsdl:part name="parameters" element="tns:ClearAlertCompleted" />
</wsdl:message>
```

This message MUST be sent with the following SOAP action.

```
http://tempuri.org/IAlertManagementProviderService/ClearAlertCompleted
```

The body of the SOAP message MUST contain the **ClearAlertCompleted** element.

3.3.5.2.2 Elements

3.3.5.2.2.1 ClearAlertCompleted

This element specifies input values for the **ClearAlertCompleted** operation.

```
<xs:element name="ClearAlertCompleted">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" name="alertKey" nillable="true" type="xs:string" />
      <xs:element minOccurs="0" name="errMessage" nillable="true" type="xs:string" />
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

alertKey: A string that contains the key of the alert.

errMessage: A string that contains any error received when clearing an alert.

3.3.5.3 IAlertProviderCallback.SuppressAlertCompleted

This operation is a callback indicating that the suppress alert operation has completed.

```
<wsdl:operation name="SuppressAlertCompleted">
  <wsdl:output
    wsam:Action="http://tempuri.org/IAlertManagementProviderService/SuppressAlertCompleted"
    message="tns:IAlertManagementProviderService_SuppressAlertCompleted_OutputCallbackMessage" />
</wsdl:operation>
```

3.3.5.3.1 Messages

3.3.5.3.1.1 IAlertProviderCallback_SuppressAlertCompleted_OutputCallbackMessage

This is the request for the **SuppressAlertCompleted** operation.

```
<wsdl:message name="IAlertProviderCallback_SuppressAlertCompleted_OutputCallbackMessage">
  <wsdl:part name="parameters" element="tns:SuppressAlertCompleted" />
</wsdl:message>
```

This message MUST be sent with the following SOAP action.

```
http://tempuri.org/IAlertManagementProviderService/SuppressAlertCompleted
```

The body of the SOAP message MUST contain the **SuppressAlertCompleted** element.

3.3.5.3.2 Elements

3.3.5.3.2.1 SuppressAlertCompleted

This element specifies input values for the **SuppressAlertCompleted** operation.

```
<xss:element name="SuppressAlertCompleted">
  <xss:complexType>
    <xss:sequence>
      <xss:element minOccurs="0" name="alertKey" nillable="true" type="xs:string" />
      <xss:element minOccurs="0" name="errMessage" nillable="true" type="xs:string" />
    </xss:sequence>
  </xss:complexType>
</xss:element>
```

alertKey: A string that contains the key to the alert.

errMessage: A string that contains any error received when suppressing an alert.

3.3.5.4 IAlertProviderCallback.RepairAlertCompleted

This operation is a callback indicating that the repair alert operation has completed.

```
<wsdl:operation name="RepairAlertCompleted">
  <wsdl:output
    wsam:Action="http://tempuri.org/IAlertManagementProviderService/RepairAlertCompleted"
    message="tns:IAlertManagementProviderService_RepairAlertCompleted_OutputCallbackMessage" />
</wsdl:operation>
```

3.3.5.4.1 Messages

3.3.5.4.1.1 IAlertProviderCallback_RepairAlertCompleted_OutputCallbackMessage

This is the request for the **RepairAlertCompleted** operation.

```
<wsdl:message name="IAlertProviderCallback_RepairAlertCompleted_OutputCallbackMessage">
  <wsdl:part name="parameters" element="tns:RepairAlertCompleted" />
</wsdl:message>
```

This message MUST be sent with the following SOAP action.

```
http://tempuri.org/IAlertManagementProviderService/RepairAlertCompleted
```

The body of the SOAP message MUST contain the **RepairAlertCompleted** element.

3.3.5.4.2 Elements

3.3.5.4.2.1 RepairAlertCompleted

This element specifies input values for the **RepairAlertCompleted** operation.

```
<xs:element name="RepairAlertCompleted">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" name="alertKey" nillable="true" type="xs:string" />
      <xs:element minOccurs="0" name="errMessage" nillable="true" type="xs:string" />
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

alertKey: A string that contains the key to the alert.

errMessage: A string that contains any error received when repairing an alert.

3.3.5.5 IAlertProviderCallback.EvaluateAlertsCompleted

This operation is a callback indicating that the health evaluation process has completed.

```
<wsdl:operation name="EvaluateAlertsCompleted">
  <wsdl:output
    wsam:Action="http://tempuri.org/IAlertManagementProviderService/EvaluateAlertsCompleted"
    message="tns:IAlertManagementProviderService_EvaluateAlertsCompleted_OutputCallbackMessage"
  />
</wsdl:operation>
```

3.3.5.5.1 Messages

3.3.5.5.1.1 IAlertProviderCallback_EvaluateAlertsCompleted_OutputCallbackMessage

This is the request for the **EvaluateAlertsCompleted** operation.

```
<wsdl:message name="IAlertProviderCallback_EvaluateAlertsCompleted_OutputCallbackMessage">
  <wsdl:part name="parameters" element="tns:EvaluateAlertsCompleted" />
</wsdl:message>
```

This message MUST be sent with the following SOAP action.

<http://tempuri.org/IAlertManagementProviderService/EvaluateAlertsCompleted>

The body of the SOAP message MUST contain the **EvaluateAlertsCompleted** element.

3.3.5.5.2 Elements

3.3.5.5.2.1 EvaluateAlertsCompleted

This element specifies input values for the **EvaluateAlertsCompleted** operation.

```
<xs:element name="EvaluateAlertsCompleted">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" name="machineId" nillable="true" type="xs:string" />
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

```

<xs:element minOccurs="0" name="ignoreSchedule" nillable="true" type="xs:boolean" />
<xs:element minOccurs="0" name="errMessage" nillable="true" type="xs:string" />
</xs:sequence>
</xs:complexType>
</xs:element>

```

machineId: A string that contains the ID of the machine.

ignoreSchedule: A Boolean where TRUE indicates that the individual evaluation schedule of the health definition is ignored; otherwise, the value is FALSE.

errMessage: A string that contains any error received when evaluating an alert.

3.3.5.6 IAlertProviderCallback.RaisedAlerts

This operation is a callback that provides the alerts that have been raised on a client computer.

```

<wsdl:operation name="RaisedAlerts">
  <wsdl:output wsam:Action="http://tempuri.org/IAlertManagementProviderService/RaisedAlerts"
    message="tns:IAlertManagementProviderService_RaisedAlerts_OutputCallbackMessage" />
</wsdl:operation>

```

3.3.5.6.1 Messages

3.3.5.6.1.1 IAlertProviderCallback_RaisedAlerts_OutputCallbackMessage

This is the request for the **RaisedAlerts** operation.

```

<wsdl:message name="IAlertProviderCallback_RaisedAlerts_OutputCallbackMessage">
  <wsdl:part name="parameters" element="tns:RaisedAlerts" />
</wsdl:message>

```

This message MUST be sent with the following SOAP action.

```
http://tempuri.org/IAlertManagementProviderService/RaisedAlerts
```

The body of the SOAP message MUST contain the **RaisedAlerts** element.

3.3.5.6.2 Elements

3.3.5.6.2.1 RaisedAlerts

This element specifies input values for the **RaisedAlerts** operation.

```

<xs:element name="RaisedAlerts">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" name="alertInfoList" nillable="true"
        xmlns:q6="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.NetworkHea
        lth.AlertFramework" type="q6:ArrayOfAlertInfo" />
      <xs:element minOccurs="0" name="task"
        xmlns:q7="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.NetworkHea
        lth.AlertFramework" type="q7:TaskType" />
      <xs:element minOccurs="0" name="machineId" nillable="true" type="xs:string" />
    </xs:sequence>
  </xs:complexType>
</xs:element>

```

```
</xs:complexType>
</xs:element>
```

alertInfoList: An array of **AlertInfo** (section [2.2.4.3.2](#)) complex types that contains a list of the alerts raised.

task: A **TaskType** (section [2.2.5.3.1](#)) value that contains the type of task that raised the alerts.

machineId: A string that contains the ID of the machine.

3.3.5.7 IAlertProviderCallback.ClearedAlerts

This operation is a callback that provides the alerts that have been cleared on a client computer.

```
<wsdl:operation name="ClearedAlerts">
  <wsdl:output wsam:Action="http://tempuri.org/IAlertManagementProviderService/ClearedAlerts"
    message="tns:IAlertManagementProviderService ClearedAlerts OutputCallbackMessage" />
</wsdl:operation>
```

3.3.5.7.1 Messages

3.3.5.7.1.1 IAlertProviderCallback_ClearedAlerts_OutputCallbackMessage

This is the request for the **ClearedAlerts** operation.

```
<wsdl:message name="IAlertProviderCallback_ClearedAlerts_OutputCallbackMessage">
  <wsdl:part name="parameters" element="tns:ClearedAlerts" />
</wsdl:message>
```

This message MUST be sent with the following SOAP action.

<http://tempuri.org/IAlertManagementProviderService/ClearedAlerts>

The body of the SOAP message MUST contain the **ClearedAlerts** element.

3.3.5.7.2 Elements

3.3.5.7.2.1 ClearedAlerts

This element specifies input values for the **ClearedAlerts** operation.

```
<xs:element name="ClearedAlerts">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" name="alertInfoList" nillable="true"
        xmlns:q8="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.NetworkHea
        lth.AlertFramework" type="q8:ArrayOfAlertInfo" />
      <xs:element minOccurs="0" name="task"
        xmlns:q9="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.NetworkHea
        lth.AlertFramework" type="q9:TaskType" />
      <xs:element minOccurs="0" name="machineId" nillable="true" type="xs:string" />
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

alertInfoList: An array of **AlertInfo** (section [2.2.4.3.2](#)) complex types that contains a list of the alerts cleared.

task: A **TaskType** (section [2.2.5.3.1](#)) value that contains the type of task that cleared the alerts.

machineId: A string that contains the ID of the machine.

3.3.5.8 IAlertSynchCallback.AlertChanged

This operation is a callback for the alert changed event.

```
<wsdl:operation name="AlertChanged">
  <wsdl:output wsam:Action="http://tempuri.org/IAlertSynchProviderService/AlertChanged"
    message="tns:IAlertSynchProviderService_AlertChanged_OutputCallbackMessage" />
</wsdl:operation>
```

3.3.5.8.1 Messages

3.3.5.8.1.1 IAlertSynchCallback_AlertChanged_OutputCallbackMessage

This is the request for the **AlertChanged** operation.

```
<wsdl:message name="IAlertSynchCallback_AlertChanged_OutputCallbackMessage">
  <wsdl:part name="parameters" element="tns:AlertChanged" />
</wsdl:message>
```

This message MUST be sent with the following SOAP action.

```
http://tempuri.org/IAlertSynchProviderCallback/AlertChanged
```

The body of the SOAP message MUST contain the **AlertChanged** element.

3.3.5.8.2 Elements

3.3.5.8.2.1 AlertChanged

This element specifies input values for the **AlertChanged** operation.

```
<xs:element name="AlertChanged">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" name="commands" nillable="true"
        xmlns:q6="http://schemas.microsoft.com/2003/10/Serialization/Arrays" type="q6:ArrayOfanyType"
      />
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

commands: An array of values that contains the commands to process the alert.

3.3.5.9 IAlertManagementProviderService.GetAllNetworkAlerts

This operation returns the list of **AlertInfo** objects representing the alerts currently active in the entire network.

```

<wsdl:operation name="GetAllNetworkAlerts">
  <wsdl:input
    wsam:Action="http://tempuri.org/IAlertManagementProviderService/GetAllNetworkAlerts"
    message="tns:IAlertManagementProviderService_GetAllNetworkAlerts_InputMessage" />
  <wsdl:output
    wsam:Action="http://tempuri.org/IAlertManagementProviderService/GetAllNetworkAlertsResponse"
    message="tns:IAlertManagementProviderService_GetAllNetworkAlerts_OutputMessage" />
  <wsdl:fault
    wsam:Action="http://tempuri.org/IAlertManagementProviderService/GetAllNetworkAlertsSecurityAccessDeniedExceptionFault" name="SecurityAccessDeniedExceptionFault"
    message="tns:IAlertManagementProviderService_GetAllNetworkAlerts_SecurityAccessDeniedExceptionFault_FaultMessage" />
  <wsdl:fault
    wsam:Action="http://tempuri.org/IAlertManagementProviderService/GetAllNetworkAlertsStringFault" name="StringFault"
    message="tns:IAlertManagementProviderService_GetAllNetworkAlerts_StringFault_FaultMessage" />
</wsdl:operation>

```

Upon receiving the **IAlertManagementProviderService_GetAllNetworkAlerts_InputMessage** request message, the protocol server starts to query the alerts currently active in the entire network. Upon successful completion of the action, the server MUST respond with **IAlertManagementProviderService_GetAllNetworkAlerts_OutputMessage**, which includes the list of AlertInfo objects representing the results. In the event of a failure, an appropriate SOAP fault MUST be sent to the client as specified in section [2.2.2.1](#).

3.3.5.9.1 Messages

3.3.5.9.1.1 IAlertManagementProviderService_GetAllNetworkAlerts_InputMessage

This is the request for the **GetAllNetworkAlerts** operation.

```

<wsdl:message name="IAlertManagementProviderService_GetAllNetworkAlerts_InputMessage">
  <wsdl:part name="parameters" element="tns:GetAllNetworkAlerts" />
</wsdl:message>

```

This message MUST be sent with the following SOAP action.

<http://tempuri.org/IAlertManagementProviderService/GetAllNetworkAlerts>

The body of the SOAP message MUST contain the **GetAllNetworkAlerts** element.

3.3.5.9.1.2 IAlertManagementProviderService_GetAllNetworkAlerts_OutputMessage

This is the response for the **GetAllNetworkAlerts** operation.

```

<wsdl:message name="IAlertManagementProviderService_GetAllNetworkAlerts_OutputMessage">
  <wsdl:part name="parameters" element="tns:GetAllNetworkAlertsResponse" />
</wsdl:message>

```

This message MUST be sent with the following SOAP action.

<http://tempuri.org/IAlertManagementProviderService/GetAllNetworkAlertsResponse>

The body of the SOAP message MUST contain the **GetAllNetworkAlertsResponse** element.

3.3.5.9.2 Elements

3.3.5.9.2.1 GetAllNetworkAlerts

This element specifies input values for the **GetAllNetworkAlerts** operation. This element has no parameters.

```
<xs:element name="GetAllNetworkAlerts">
  <xs:complexType>
    <xs:sequence />
  </xs:complexType>
</xs:element>
```

3.3.5.9.2.2 GetAllNetworkAlertsResponse

This element specifies output values for the **GetAllNetworkAlerts** operation.

```
<xs:element name="GetAllNetworkAlertsResponse">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" name="GetAllNetworkAlertsResult" nillable="true"
        xmlns:q1="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.NetworkHea
        lth.AlertFramework.Service" type="q1:AlertListChunk" />
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

GetAllNetworkAlertsResult: An **AlertListChunk** (section [2.2.4.3.1](#)) complex type that contains the result of getting all network alerts.

3.3.5.10 IAlertManagementProviderService.ClearAlertOneWay

Clears an alert that is currently active in the network, either on the primary server or on a client computer. This operation does not wait for the alert to be cleared before returning.

```
<wsdl:operation name="ClearAlertOneWay">
  <wsdl:input
    wsam:Action="http://tempuri.org/IAlertManagementProviderService/ClearAlertOneWay"
    message="tns:IAlertManagementProviderService ClearAlertOneWay InputMessage" />
</wsdl:operation>
```

Upon receiving the **IAlertManagementProviderService_ClearAlertOneWay_InputMessage** request message, the protocol server is notified to clear the specific alert.

3.3.5.10.1 Messages

3.3.5.10.1.1 IAlertManagementProviderService_ClearAlertOneWay_InputMessage

This is the request for the **ClearAlertOneWay** operation.

```
<wsdl:message name="IAlertManagementProviderService_ClearAlertOneWay_InputMessage">
  <wsdl:part name="parameters" element="tns:ClearAlertOneWay" />
</wsdl:message>
```

This message MUST be sent with the following SOAP action.

<http://tempuri.org/IAlertManagementProviderService/ClearAlertOneWay>

The body of the SOAP message MUST contain the **ClearAlertOneWay** element.

3.3.5.10.2 Elements

3.3.5.10.2.1 ClearAlertOneWay

This element specifies input values for the **ClearAlertOneWay** operation.

```
<xs:element name="ClearAlertOneWay">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" name="alertKey" nillable="true" type="xs:string" />
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

alertKey: A string that contains the key to the alert.

3.3.5.11 IAlertManagementProviderService.ClearAlert

This operation clears an alert that is currently active in the network, either on the primary server or on a client computer. This operation waits until the alert is cleared before returning.

```
<wsdl:operation name="ClearAlert">
  <wsdl:input wsam:Action="http://tempuri.org/IAlertManagementProviderService/ClearAlert"
  message="tns:IAlertManagementProviderService_ClearAlert_InputMessage" />
  <wsdl:output
  wsam:Action="http://tempuri.org/IAlertManagementProviderService/ClearAlertResponse"
  message="tns:IAlertManagementProviderService_ClearAlert_OutputMessage" />
  <wsdl:fault
  wsam:Action="http://tempuri.org/IAlertManagementProviderService/ClearAlertStringFault"
  name="StringFault"
  message="tns:IAlertManagementProviderService_ClearAlert_StringFault_FaultMessage" />
  <wsdl:fault
  wsam:Action="http://tempuri.org/IAlertManagementProviderService/ClearAlertSecurityAccessDenie
  dExceptionFault" name="SecurityAccessDeniedExceptionFault"
  message="tns:IAlertManagementProviderService_ClearAlert_SecurityAccessDeniedExceptionFault_Fa
  ultMessage" />
</wsdl:operation>
```

Upon receiving the **IAlertManagementProviderService_ClearAlert_InputMessage** request message, the protocol server starts to clear the specific alert. Upon successful completion of the action, the server MUST respond with

IAlertManagementProviderService_ClearAlert_OutputMessage. In the event of a failure, an appropriate SOAP fault MUST be sent to the client as specified in section [2.2.2.1](#).

3.3.5.11.1 Messages

3.3.5.11.1.1 IAlertManagementProviderService_ClearAlert_InputMessage

This is the request for the **ClearAlert** operation.

```
<wsdl:message name="IAlertManagementProviderService_ClearAlert_InputMessage">
  <wsdl:part name="parameters" element="tns:ClearAlert" />
```

```
</wsdl:message>
```

This message MUST be sent with the following SOAP action.

```
http://tempuri.org/IAlertManagementProviderService/ClearAlert
```

The body of the SOAP message MUST contain the **ClearAlert** element.

3.3.5.11.1.2 IAlertManagementProviderService_ClearAlert_OutputMessage

This is the response for the **ClearAlert** operation.

```
<wsdl:message name="IAlertManagementProviderService_ClearAlert_OutputMessage">
  <wsdl:part name="parameters" element="tns:ClearAlertResponse" />
</wsdl:message>
```

This message MUST be sent with the following SOAP action.

```
http://tempuri.org/IAlertManagementProviderService/ClearAlertResponse
```

The body of the SOAP message MUST contain the **ClearAlertResponse** element.

3.3.5.11.2 Elements

3.3.5.11.2.1 ClearAlert

This element specifies input values for the **ClearAlert** operation.

```
<xs:element name="ClearAlert">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" name="alertKey" nillable="true"
        type="xs:string" />
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

alertKey: A string that contains the key to the alert.

3.3.5.11.2.2 ClearAlertResponse

This element specifies output values for the **ClearAlert** operation. This element has no parameters.

```
<xs:element name="ClearAlertResponse">
  <xs:complexType>
    <xs:sequence />
  </xs:complexType>
</xs:element>
```

3.3.5.12 IAlertManagementProviderService.SuppressAlertOneWay

This operation sets the suppress flag on an alert that is currently active in the network to the value provided. The alert can be either on the primary server or on a client computer. This operation does not wait until the alert is suppressed before returning.

```
<wsdl:operation name="SuppressAlertOneWay">
  <wsdl:input
    wsam:Action="http://tempuri.org/IAlertManagementProviderService/SuppressAlertOneWay"
    messages="tns:IAlertManagementProviderService_SuppressAlertOneWay_InputMessage" />
</wsdl:operation>
```

Upon receiving the **IAlertManagementProviderService_SuppressAlertOneWay_InputMessage** request message, the protocol server is notified to suppress the specific alert.

3.3.5.12.1 Messages

3.3.5.12.1.1 IAlertManagementProviderService_SuppressAlertOneWay_InputMessage

This is the request for the **SuppressAlertOneWay** operation.

```
<wsdl:message name="IAlertManagementProviderService_SuppressAlertOneWay_InputMessage">
  <wsdl:part name="parameters" element="tns:SuppressAlertOneWay" />
</wsdl:message>
```

This message MUST be sent with the following SOAP action.

<http://tempuri.org/IAlertManagementProviderService/SuppressAlertOneWay>

The body of the SOAP message MUST contain the **SuppressAlertOneWay** element.

3.3.5.12.2 Elements

3.3.5.12.2.1 SuppressAlertOneWay

This element specifies input values for the **SuppressAlertOneWay** operation.

```
<xss:element name="SuppressAlertOneWay">
  <xss:complexType>
    <xss:sequence>
      <xss:element minOccurs="0" name="alertKey" nillable="true" type="xs:string" />
      <xss:element minOccurs="0" name="value" type="xs:boolean" />
    </xss:sequence>
  </xss:complexType>
</xss:element>
```

alertKey: A string that contains the key to the alert.

value: A Boolean where TRUE indicates that the alert should be suppressed; otherwise, the value is FALSE.

3.3.5.13 IAlertManagementProviderService.SuppressAlert

This operation sets the suppress flag on an alert that is currently active in the network to the value provided. The alert can be either on the primary server or on a client computer. This operation waits until the alert is cleared before returning.

```
<wsdl:operation name="SuppressAlert">
  <wsdl:input wsam:Action="http://tempuri.org/IAlertManagementProviderService/SuppressAlert"
  message="tns:IAlertManagementProviderService_SuppressAlert_InputMessage" />
  <wsdl:output
  wsam:Action="http://tempuri.org/IAlertManagementProviderService/SuppressAlertResponse"
  message="tns:IAlertManagementProviderService SuppressAlert OutputMessage" />
  <wsdl:fault
  wsam:Action="http://tempuri.org/IAlertManagementProviderService/SuppressAlertStringFault"
  name="StringFault"
  message="tns:IAlertManagementProviderService_SuppressAlert_StringFault_FaultMessage" />
  <wsdl:fault
  wsam:Action="http://tempuri.org/IAlertManagementProviderService/SuppressAlertSecurityAccessDeniedExceptionFault"
  name="SecurityAccessDeniedExceptionFault"
  message="tns:IAlertManagementProviderService_SuppressAlert_SecurityAccessDeniedExceptionFault
  _FaultMessage" />
</wsdl:operation>
```

Upon receiving the **IAlertManagementProviderService_SuppressAlert_InputMessage** request message, the protocol server starts to suppress the specific alert. Upon successful completion of the action, the server MUST respond with

IAlertManagementProviderService_SuppressAlert_OutputMessage. In the event of a failure, an appropriate SOAP fault MUST be sent to the client as specified in section [2.2.2.1](#).

3.3.5.13.1 Messages

3.3.5.13.1.1 IAlertManagementProviderService_SuppressAlert_InputMessage

This is the request for the **SuppressAlert** operation.

```
<wsdl:message name="IAlertManagementProviderService SuppressAlert InputMessage">
  <wsdl:part name="parameters" element="tns:SuppressAlert" />
</wsdl:message>
```

This message MUST be sent with the following SOAP action.

<http://tempuri.org/IAlertManagementProviderService/SuppressAlert>

The body of the SOAP message MUST contain the **SuppressAlert** element.

3.3.5.13.1.2 IAlertManagementProviderService_SuppressAlert_OutputMessage

This is the response for the **SuppressAlert** operation.

```
<wsdl:message name="IAlertManagementProviderService_SuppressAlert_OutputMessage">
  <wsdl:part name="parameters" element="tns:SuppressAlertResponse" />
</wsdl:message>
```

This message MUST be sent with the following SOAP action.

<http://tempuri.org/IAlertManagementProviderService/SuppressAlertResponse>

The body of the SOAP message MUST contain the **SuppressAlertResponse** element.

3.3.5.13.2 Elements

3.3.5.13.2.1 SuppressAlert

This element specifies input values for the **SuppressAlert** operation.

```
<xs:element name="SuppressAlert">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" name="alertKey" nillable="true"
        type="xs:string" />
      <xs:element minOccurs="0" name="value" type="xs:boolean" />
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

alertKey: A string that contains the key to the alert.

value: A Boolean where TRUE indicates that the alert should be suppressed; otherwise, the value is FALSE.

3.3.5.13.2.2 SuppressAlertResponse

This element specifies input values for the **SuppressAlert** operation. This element has no parameters.

```
<xs:element name="SuppressAlertResponse">
  <xs:complexType>
    <xs:sequence />
  </xs:complexType>
</xs:element>
```

3.3.5.14 IAlertManagementProviderService.RaiseAlertOneWay

This operation raises an alert for a health definition for a feature. This operation does not wait until the alert is raised before returning.

```
<wsdl:operation name="RaiseAlertOneWay">
  <wsdl:input
    wsam:Action="http://tempuri.org/IAlertManagementProviderService/RaiseAlertOneWay"
    message="tns:IAlertManagementProviderService RaiseAlertOneWay InputMessage" />
</wsdl:operation>
```

Upon receiving the **IAlertManagementProviderService_RaiseAlertOneWay_InputMessage** request message, the protocol server is notified to raise the specific alert.

3.3.5.14.1 Messages

3.3.5.14.1.1 IAlertManagementProviderService_RaiseAlertOneWay_InputMessage

This is the request for the **RaiseAlertOneWay** operation.

```
<wsdl:message name="IAlertManagementProviderService_RaiseAlertOneWay_InputMessage">
  <wsdl:part name="parameters" element="tns:RaiseAlertOneWay" />
</wsdl:message>
```

This message MUST be sent with the following SOAP action.

```
http://tempuri.org/IAlertManagementProviderService/RaiseAlertOneWay
```

The body of the SOAP message MUST contain the **RaiseAlertOneWay** element.

3.3.5.14.2 Elements

3.3.5.14.2.1 RaiseAlertOneWay

This element specifies input values for the **RaiseAlertOneWay** operation.

```
<xs:element name="RaiseAlertOneWay">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" name="alertInfo" nillable="true"
        xmlns:q2="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.NetworkHea
        lth.AlertFramework" type="q2:AlertInfo" />
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

alertInfo: An **AlertInfo** (section [2.2.4.3.2](#)) complex type that contains the alert information.

3.3.5.15 IAlertManagementProviderService.RaiseAlert

This operation raises an alert for a health definition for a feature. This operation waits until the alert is cleared before returning.

```
<wsdl:operation name="RaiseAlert">
  <wsdl:input wsam:Action="http://tempuri.org/IAlertManagementProviderService/RaiseAlert"
    message="tns:IAlertManagementProviderService_RaiseAlert_InputMessage" />
  <wsdl:output
    wsam:Action="http://tempuri.org/IAlertManagementProviderService/RaiseAlertResponse"
    message="tns:IAlertManagementProviderService RaiseAlert OutputMessage" />
  <wsdl:fault
    wsam:Action="http://tempuri.org/IAlertManagementProviderService/RaiseAlertStringFault"
    name="StringFault"
    message="tns:IAlertManagementProviderService RaiseAlert StringFault FaultMessage" />
  <wsdl:fault
    wsam:Action="http://tempuri.org/IAlertManagementProviderService/RaiseAlertSecurityAccessDenie
    dExceptionFault" name="SecurityAccessDeniedExceptionFault"
    message="tns:IAlertManagementProviderService_RaiseAlert_SecurityAccessDeniedExceptionFault_Fa
    ultMessage" />
</wsdl:operation>
```

Upon receiving the **IAlertManagementProviderService_RaiseAlert_InputMessage** request message, the protocol server starts to raise the specific alert. Upon successful completion of the action, the server MUST respond with

IAlertManagementProviderService_RaiseAlert_OutputMessage. In the event of a failure, an appropriate SOAP fault MUST be sent to the client as specified in section [2.2.2.1](#).

3.3.5.15.1 Messages

3.3.5.15.1.1 IAlertManagementProviderService_RaiseAlert_InputMessage

This is the request for the **RaiseAlert** operation.

```
<wsdl:message name="IAlertManagementProviderService_RaiseAlert_InputMessage">
  <wsdl:part name="parameters" element="tns:RaiseAlert" />
</wsdl:message>
```

This message MUST be sent with the following SOAP action.

```
http://tempuri.org/IAlertManagementProviderService/RaiseAlert
```

The body of the SOAP message MUST contain the **RaiseAlert** element.

3.3.5.15.1.2 IAlertManagementProviderService_RaiseAlert_OutputMessage

This is the response for the **RaiseAlert** operation.

```
<wsdl:message name="IAlertManagementProviderService_RaiseAlert_OutputMessage">
  <wsdl:part name="parameters" element="tns:RaiseAlertResponse" />
</wsdl:message>
```

This message MUST be sent with the following SOAP action.

```
http://tempuri.org/IAlertManagementProviderService/RaiseAlertResponse
```

The body of the SOAP message MUST contain the **RaiseAlertResponse** element.

3.3.5.15.2 Elements

3.3.5.15.2.1 RaiseAlert

This element specifies input values for the **RaiseAlert** operation.

```
<xss:element name="RaiseAlert">
  <xss:complexType>
    <xss:sequence>
      <xss:element minOccurs="0" name="alertInfo" nillable="true"
        xmlns:q3="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.NetworkHea
        lth.AlertFramework" type="q3:AlertInfo" />
    </xss:sequence>
  </xss:complexType>
</xss:element>
```

alertInfo: An **AlertInfo** (section [2.2.4.3.2](#)) complex type that contains the alert information.

3.3.5.15.2.2 RaiseAlertResponse

This element specifies output values for the **RaiseAlert** operation.

```
<xss:element name="RaiseAlertResponse">
  <xss:complexType>
    <xss:sequence>
```

```

<xs:element minOccurs="0" name="RaiseAlertResult" nillable="true"
xmlns:q4="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.NetworkHea
lth.AlertFramework" type="q4:AlertInfo" />
  </xs:sequence>
</xs:complexType>
</xs:element>

```

RaiseAlertResult: An **AlertInfo** (section [2.2.4.3.2](#)) complex type that contains the result of raising an alert.

3.3.5.16 IAlertManagementProviderService.IsAuthorized

This operation determines whether the connected user has network alert access.

```

<wsdl:operation name="IsAuthorized">
  <wsdl:input wsam:Action="http://tempuri.org/IAlertManagementProviderService/IsAuthorized">
    message="tns:IAlertManagementProviderService_IsAuthorized_InputMessage" />
  <wsdl:output
  wsam:Action="http://tempuri.org/IAlertManagementProviderService/IsAuthorizedResponse">
    message="tns:IAlertManagementProviderService_IsAuthorized_OutputMessage" />
</wsdl:operation>

```

Upon receiving the **IAlertManagementProviderService_IsAuthorized_InputMessage** request message, the protocol server starts to check whether the connected user has network alert access. Upon successful completion of the action, the server MUST respond with **IAlertManagementProviderService_IsAuthorized_OutputMessage**. In the event of a failure, an appropriate SOAP fault MUST be sent to the client as specified in section [2.2.2.1](#).

3.3.5.16.1 Messages

3.3.5.16.1.1 IAlertManagementProviderService_IsAuthorized_InputMessage

This is the request for the **IsAuthorized** operation.

```

<wsdl:message name="IAlertManagementProviderService_IsAuthorized_InputMessage">
  <wsdl:part name="parameters" element="tns:IsAuthorized" />
</wsdl:message>

```

This message MUST be sent with the following SOAP action.

<http://tempuri.org/IAlertManagementProviderService/IsAuthorized>

The body of the SOAP message MUST contain the **IsAuthorized** element.

3.3.5.16.1.2 IAlertManagementProviderService_IsAuthorized_OutputMessage

This is the response for the **IsAuthorized** operation.

```

<wsdl:message name="IAlertManagementProviderService_IsAuthorized_OutputMessage">
  <wsdl:part name="parameters" element="tns:IsAuthorizedResponse" />
</wsdl:message>

```

This message MUST be sent with the following SOAP action.

<http://tempuri.org/IAlertManagementProviderService/IsAuthorizedResponse>

The body of the SOAP message MUST contain the **IsAuthorizedResponse** element.

3.3.5.16.2 Elements

3.3.5.16.2.1 IsAuthorized

This element specifies input values for the **IsAuthorized** operation. This element has no parameters.

```
<xs:element name="IsAuthorized">
  <xs:complexType>
    <xs:sequence />
  </xs:complexType>
</xs:element>
```

3.3.5.16.2.2 IsAuthorizedResponse

This element specifies output values for the **IsAuthorized** operation.

```
<xs:element name="IsAuthorizedResponse">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="1" name="returnValue" type="xs:boolean" />
    </xs:sequence>
  </xs:complexType>
```

returnValue: A Boolean where TRUE indicates that the service is authorized; otherwise, the value is FALSE.

3.3.5.17 IAlertSynchProviderService.RegisterClientAgent

This operation registers a client computer for callbacks with the **IAlertSynchProviderService** instance running on the primary server.

```
<wsdl:operation name="RegisterClientAgent">
  <wsdl:input wsam:Action="http://tempuri.org/IAlertSynchProviderService/RegisterClientAgent"
  message="tns:IAlertSynchProviderService_RegisterClientAgent_InputMessage" />
  <wsdl:output
  wsam:Action="http://tempuri.org/IAlertSynchProviderService/RegisterClientAgentResponse"
  message="tns:IAlertSynchProviderService RegisterClientAgent OutputMessage" />
  <wsdl:fault
  wsam:Action="http://tempuri.org/IAlertSynchProviderService/RegisterClientAgentArgumentNullExceptionFault"
  name="ArgumentNullExceptionFault"
  message="tns:IAlertSynchProviderService_RegisterClientAgent_ArgumentNullExceptionFaultMessage" />
</wsdl:operation>
```

Upon receiving the **IAlertSynchProviderService_RegisterClientAgent_InputMessage** request message, the protocol server starts to register the client computer. Upon successful completion of the action, the server MUST respond with

IAlertSynchProviderService_RegisterClientAgent_OutputMessage. In the event of a failure, an appropriate SOAP fault MUST be sent to the client as specified in section [2.2.2.1](#).

3.3.5.17.1 Messages

3.3.5.17.1.1 IAlertSynchProviderService_RegisterClientAgent_InputMessage

This is the request for the **RegisterClientAgent** operation.

```
<wsdl:message name="IAlertSynchProviderService_RegisterClientAgent_InputMessage">
  <wsdl:part name="parameters" element="tns:RegisterClientAgent" />
</wsdl:message>
```

This message MUST be sent with the following SOAP action.

```
http://tempuri.org/IAlertSynchProviderService/RegisterClientAgent
```

The body of the SOAP message MUST contain the **RegisterClientAgent** element.

3.3.5.17.1.2 IAlertSynchProviderService_RegisterClientAgent_OutputMessage

This is the response for the **RegisterClientAgent** operation.

```
<wsdl:message name="IAlertSynchProviderService_RegisterClientAgent_OutputMessage">
  <wsdl:part name="parameters" element="tns:RegisterClientAgentResponse" />
</wsdl:message>
```

This message MUST be sent with the following SOAP action.

```
http://tempuri.org/IAlertSynchProviderService/RegisterClientAgentResponse
```

The body of the SOAP message MUST contain the **RegisterClientAgentResponse** element.

3.3.5.17.2 Elements

3.3.5.17.2.1 RegisterClientAgent

This element specifies input values for the **RegisterClientAgent** operation.

```
<xss:element name="RegisterClientAgent">
  <xss:complexType>
    <xss:sequence>
      <xss:element minOccurs="0" name="networkMachineId" nillable="true" type="xss:string" />
    </xss:sequence>
  </xss:complexType>
</xss:element>
```

networkMachineId: A string that contains the ID of the network machine.

3.3.5.17.2.2 RegisterClientAgentResponse

This element specifies output values for the **RegisterClientAgent** operation. This element has no parameters.

```
<xss:element name="RegisterClientAgentResponse">
  <xss:complexType>
    <xss:sequence />
  </xss:complexType>
```

```
</xs:element>
```

3.3.5.18 IAlertSynchProviderService.SynchronizeAlerts

This operation synchronizes the list of **AlertInfo** objects representing alerts raised, cleared, updated, or evaluated on a particular machine in the network to the server.

```
<wsdl:operation name="SynchronizeAlerts">
  <wsdl:input wsam:Action="http://tempuri.org/IAlertSynchProviderService/SynchronizeAlerts"
  message="tns:IAlertSynchProviderService_SynchronizeAlerts_InputMessage" />
</wsdl:operation>
```

Upon receiving the **IAlertSynchProviderService_SynchronizeAlerts_InputMessage** request message, the protocol server starts to synchronize the list of AlertInfo objects.

3.3.5.18.1 Messages

3.3.5.18.1.1 IAlertSynchProviderService_SynchronizeAlerts_InputMessage

This is the request for the **SynchronizeAlerts** operation.

```
<wsdl:message name="IAlertSynchProviderService_SynchronizeAlerts_InputMessage">
  <wsdl:part name="parameters" element="tns:SynchronizeAlerts" />
</wsdl:message>
```

This message MUST be sent with the following SOAP action.

```
http://tempuri.org/IAlertSynchProviderService/SynchronizeAlerts
```

The body of the SOAP message MUST contain the **SynchronizeAlerts** element.

3.3.5.18.2 Elements

3.3.5.18.2.1 SynchronizeAlerts

This element specifies input values for the **SynchronizeAlerts** operation.

```
<xs:element name="SynchronizeAlerts">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" name="alerts" nillable="true"
      xmlns:q1="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.NetworkHea
      lth.AlertFramework" type="q1:ArrayOfAlertInfo" />
        <xs:element minOccurs="0" name="networkMachineId" nillable="true" type="xs:string" />
        <xs:element minOccurs="0" name="task"
      xmlns:q2="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.NetworkHea
      lth.AlertFramework" type="q2:TaskType" />
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

alerts: An array of **AlertInfo** (section [2.2.4.3.2](#)) complex types that contains a list of the objects of the alerts raised, cleared, updated, or evaluated between a particular machine in the network and the server.

networkMachineId: A string that contains the ID of the network machine.

Task: A **TaskType** (section [2.2.5.3.1](#)) value that indicates the type of task performed for which the alerts are being reported.

3.3.5.19 IAlertSynchProviderService.ClearCallbackCommandQueue

This operation clears all pending command queues for the machine.

```
<wsdl:operation name="ClearCallbackCommandQueue">
  <wsdl:input
    wsam:Action="http://tempuri.org/IAlertSynchProviderService/ClearCallbackCommandQueue"
    message="tns:IAlertSynchProviderService_ClearCallbackCommandQueue_InputMessage" />
  <wsdl:output
    wsam:Action="http://tempuri.org/IAlertSynchProviderService/ClearCallbackCommandQueueResponse"
    message="tns:IAlertSynchProviderService ClearCallbackCommandQueue OutputMessage" />
</wsdl:operation>
```

Upon receiving the **IAlertSynchProviderService_ClearCallbackCommandQueue_InputMessage** request message, the protocol server starts to clear all pending command queues for the machine. Upon successful completion of the action, the server MUST respond with **IAlertSynchProviderService_ClearCallbackCommandQueue_OutputMessage**. In the event of a failure, an appropriate SOAP fault MUST be sent to the client as specified in section [2.2.2.1](#).

3.3.5.19.1 Messages

3.3.5.19.1.1 IAlertSynchProviderService_ClearCallbackCommandQueue_InputMessage

This is the request for the **ClearCallbackCommandQueue** operation.

```
<wsdl:message name="IAlertSynchProviderService_ClearCallbackCommandQueue_InputMessage">
  <wsdl:part name="parameters" element="tns:ClearCallbackCommandQueue" />
</wsdl:message>
```

This message MUST be sent with the following SOAP action.

<http://tempuri.org/IAlertSynchProviderService/ClearCallbackCommandQueue>

The body of the SOAP message MUST contain the **ClearCallbackCommandQueue** element.

3.3.5.19.1.2 IAlertSynchProviderService_ClearCallbackCommandQueue_OutputMessage

This is the response for the **ClearCallbackCommandQueue** operation.

```
<wsdl:message name="IAlertSynchProviderService_ClearCallbackCommandQueue_OutputMessage">
  <wsdl:part name="parameters" element="tns:ClearCallbackCommandQueueResponse" />
</wsdl:message>
```

This message MUST be sent with the following SOAP action.

<http://tempuri.org/IAlertSynchProviderService/ClearCallbackCommandQueueResponse>

The body of the SOAP message MUST contain the **ClearCallbackCommandQueueResponse** element.

3.3.5.19.2 Elements

3.3.5.19.2.1 ClearCallbackCommandQueue

This element specifies input values for the **ClearCallbackCommandQueue** operation.

```
<xs:element name="ClearCallbackCommandQueue">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" name="networkMachineId" nillable="true" type="xs:string" />
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

networkMachineId: A string that contains the ID of the network machine.

3.3.5.19.2.2 ClearCallbackCommandQueueResponse

This element specifies output values for the **ClearCallbackCommandQueue** operation. This element has no parameters.

```
<xs:element name="ClearCallbackCommandQueueResponse">
  <xs:complexType>
    <xs:sequence />
  </xs:complexType>
</xs:element>
```

3.3.5.20 IAlertSynchProviderService.GetPlugInInformation

This operation gets information for all installed plugins.

```
<wsdl:operation name="GetPlugInInformation">
  <wsdl:input
    wsam:Action="http://tempuri.org/IAlertSynchProviderService/GetPlugInInformation"
    message="tns:IAlertSynchProviderService_GetPlugInInformation_InputMessage" />
  <wsdl:output
    wsam:Action="http://tempuri.org/IAlertSynchProviderService/GetPlugInInformationResponse"
    message="tns:IAlertSynchProviderService GetPlugInInformation OutputMessage" />
</wsdl:operation>
```

Upon receiving the **IAlertSynchProviderService_GetPlugInInformation_InputMessage** request message, the protocol server starts to get the plugin information. Upon successful completion of the action, the server MUST respond with

IAlertSynchProviderService_GetPlugInInformation_OutputMessage. In the event of a failure, an appropriate SOAP fault MUST be sent to the client as specified in section [2.2.2.1](#).

3.3.5.20.1 Messages

3.3.5.20.1.1 IAlertSynchProviderService_GetPlugInInformation_InputMessage

This is the request for the **GetPlugInInformation** operation.

```
<wsdl:message name="IAlertSynchProviderService_GetPlugInInformation_InputMessage">
```

```
<wsdl:part name="parameters" element="tns:GetPlugInInformation" />
</wsdl:message>
```

This message MUST be sent with the following SOAP action.

```
http://tempuri.org/IAlertSynchProviderService/GetPlugInInformation
```

The body of the SOAP message MUST contain the **GetPlugInInformation** element.

3.3.5.20.1.2 IAlertSynchProviderService_GetPlugInInformation_OutputMessage

This is the response for the **GetPlugInInformation** operation.

```
<wsdl:message name="IAlertSynchProviderService_GetPlugInInformation_OutputMessage">
  <wsdl:part name="parameters" element="tns:GetPlugInInformationResponse" />
</wsdl:message>
```

This message MUST be sent with the following SOAP action.

```
http://tempuri.org/IAlertSynchProviderService/GetPlugInInformationResponse
```

The body of the SOAP message MUST contain the GetPlugInInformationResponse element.

3.3.5.20.2 Elements

3.3.5.20.2.1 GetPlugInInformation

This element specifies input values for the **GetPlugInInformation** operation. This element has no parameters.

```
<xss:element name="GetPlugInInformation">
  <xss:complexType>
    <xss:sequence />
  </xss:complexType>
</xss:element>
```

3.3.5.20.2.2 GetPlugInInformationResponse

This element specifies output values for the **GetPlugInInformation** operation.

```
<xss:element name="GetPlugInInformationResponse">
  <xss:complexType>
    <xss:sequence>
      <xss:element minOccurs="0" name="GetPlugInInformationResult" nillable="true"
        xmlns:q3="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.NetworkHea
        lth.Engine" type="q3:ArrayOfPlugInInfo" />
    </xss:sequence>
  </xss:complexType>
</xss:element>
```

GetPlugInInformationResult: An array of **PlugInInfo** (section [2.2.4.3.7](#)) complex types that contains the result of getting plugin information.

3.3.5.21 IAlertSynchProviderService.DownloadDefinition

This operation obtains a stream containing the definition file for a feature plug-in.

```
<wsdl:operation name="DownloadDefinition">
  <wsdl:input wsam:Action="http://tempuri.org/IAlertSynchProviderService/DownloadDefinition"
  message="tns:IAlertSynchProviderService DownloadDefinition InputMessage" />
  <wsdl:output
  wsam:Action="http://tempuri.org/IAlertSynchProviderService/DownloadDefinitionResponse"
  message="tns:IAlertSynchProviderService_DownloadDefinition_OutputMessage" />
</wsdl:operation>
```

Upon receiving the **IAlertSynchProviderService_DownloadDefinition_InputMessage** request message, the protocol server generates a stream containing the definition file for the feature plug-in. Upon successful completion of the action, the server MUST respond with **IAlertSynchProviderService_DownloadDefinition_OutputMessage**. In the event of a failure, an appropriate SOAP fault MUST be sent to the client as specified in section [2.2.2.1](#).

3.3.5.21.1 Messages

3.3.5.21.1.1 IAlertSynchProviderService_DownloadDefinition_InputMessage

This is the request for the **DownloadDefinition** operation.

```
<wsdl:message name="IAlertSynchProviderService DownloadDefinition InputMessage">
  <wsdl:part name="parameters" element="tns:DownloadDefinition" />
</wsdl:message>
```

This message MUST be sent with the following SOAP action.

`http://tempuri.org/IAlertSynchProviderService/DownloadDefinition`

The body of the SOAP message MUST contain the **DownloadDefinition** element.

3.3.5.21.1.2 IAlertSynchProviderService_DownloadDefinition_OutputMessage

This is the response for the **DownloadDefinition** operation.

```
<wsdl:message name="IAlertSynchProviderService_DownloadDefinition_OutputMessage">
  <wsdl:part name="parameters" element="tns:DownloadDefinitionResponse" />
</wsdl:message>
```

This message MUST be sent with the following SOAP action.

`http://tempuri.org/IAlertSynchProviderService/DownloadDefinitionResponse`

The body of the SOAP message MUST contain the **DownloadDefinitionResponse** element.

3.3.5.21.2 Elements

3.3.5.21.2.1 DownloadDefinition

This element specifies input values for the **DownloadDefinition** operation.

```

<xs:element name="DownloadDefinition">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" name="featureName" nillable="true" type="xs:string" />
    </xs:sequence>
  </xs:complexType>
</xs:element>

```

featureName: A string that contains the feature name of the definition.

3.3.5.21.2.2 DownloadDefinitionResponse

This element specifies output values for the **DownloadDefinition** operation.

```

<xs:element name="DownloadDefinitionResponse">
  <xs:complexType>
    <xs:sequence>
      <xs:element name="DownloadDefinitionResult"
        xmlns:q4="http://schemas.microsoft.com/Message" type="q4:StreamBody" />
    </xs:sequence>
  </xs:complexType>
</xs:element>

```

DownloadDefinitionResult: A **StreamBody** (section [2.2.5.3.3](#)) simple type that contains the result of downloading the definition.

3.3.5.22 IAlertSynchProviderService.DownloadConfiguration

This operation obtains a stream containing the definition configuration file for a feature plug-in.

```

<wsdl:operation name="DownloadConfiguration">
  <wsdl:input
    wsam:Action="http://tempuri.org/IAlertSynchProviderService/DownloadConfiguration"
    message="tns:IAlertSynchProviderService_DownloadConfiguration_InputMessage" />
  <wsdl:output
    wsam:Action="http://tempuri.org/IAlertSynchProviderService/DownloadConfigurationResponse"
    message="tns:IAlertSynchProviderService_DownloadConfiguration_OutputMessage" />
</wsdl:operation>

```

Upon receiving the **IAlertSynchProviderService_DownloadConfiguration_InputMessage** request message, the protocol server generates a stream containing the definition configuration file for the feature plug-in. Upon successful completion of the action, the server MUST respond with **IAlertSynchProviderService_DownloadConfiguration_OutputMessage**. In the event of a failure, an appropriate SOAP fault MUST be sent to the client as specified in section [2.2.2.1](#).

3.3.5.22.1 Messages

3.3.5.22.1.1 IAlertSynchProviderService_DownloadConfiguration_InputMessage

This is the request for the **DownloadConfiguration** operation.

```

<wsdl:message name="IAlertSynchProviderService_DownloadConfiguration_InputMessage">
  <wsdl:part name="parameters" element="tns:DownloadConfiguration" />
</wsdl:message>

```

This message MUST be sent with the following SOAP action.

<http://tempuri.org/IAlertSyncProviderService/DownloadConfiguration>

The body of the SOAP message MUST contain the **DownloadConfiguration** element.

3.3.5.22.1.2 IAlertSyncProviderService_DownloadConfiguration_OutputMessage

This is the response for the **DownloadConfiguration** operation.

```
<wsdl:message name="IAlertSyncProviderService_DownloadConfiguration_OutputMessage">
  <wsdl:part name="parameters" element="tns:DownloadConfigurationResponse" />
</wsdl:message>
```

This message MUST be sent with the following SOAP action.

<http://tempuri.org/IAlertSyncProviderService/DownloadConfigurationResponse>

The body of the SOAP message MUST contain the **DownloadConfigurationResponse** element.

3.3.5.22.2 Elements

3.3.5.22.2.1 DownloadConfiguration

This element specifies input values for the **DownloadConfiguration** operation.

```
<xs:element name="DownloadConfiguration">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" name="featureName" nillable="true" type="xs:string" />
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

featureName: A string that contains the feature name of the configuration.

3.3.5.22.2.2 DownloadConfigurationResponse

This element specifies input values for the **DownloadConfiguration** operation.

```
<xs:element name="DownloadConfigurationResponse">
  <xs:complexType>
    <xs:sequence>
      <xs:element name="DownloadConfigurationResult" xmlns:q5="http://schemas.microsoft.com/Message" type="q5:StreamBody" />
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

DownloadConfigurationResult: A **StreamBody** (section [2.2.5.3.3](#)) simple type that contains the result of downloading the configuration.

3.3.6 Timer Events

None.

3.3.7 Other Local Events

None.

3.4 Machine Identity Provider Service Contract Details

3.4.1 Abstract Data Model

This section describes a conceptual service contract that an implementation maintains to participate in this protocol. The described operations of the service contract are provided to facilitate the explanation of how the protocol behaves. This document does not mandate that implementations adhere to this service contract as long as their external behavior is consistent with how it is described in this document.

3.4.1.1 Machine Identity

The protocol server saves certificates issued for each add machine request, and get machine identity status from the system certificates store.

3.4.1.2 Machine RDP Permission

The protocol server maintains the user-computer RDP permission allowance mapping that tells who has permission to connect to which machine using remote desktop. This can be achieved by creating one Active Directory security group for each machine and then joining the allowed users to the group.

3.4.2 Timers

None.

3.4.3 Initialization

None.

3.4.4 Higher-Layer Triggered Events

None.

3.4.5 Message Processing Events and Sequencing Rules

OperationContract	Description
IMachineIdentityProviderCallback.ReturnNewCertResponse	Callback for the New Certificate Response.
IMachineIdentityProviderCallback.ReturnRenewCert	Callback for the Renew New Certificate.
IMachineIdentityProviderCallback.ReturnSid	Callback for the machine SID. This happens only when a new machine is added to the Colorado system and the machine connects with the server. SID is the ID for this machine.
IMachineIdentityProviderCallback.ReturnRevokeCert	Callback for the Revoke Certificate.

OperationContract	Description
IMachineIdentityProviderCallback.ReturnRemoveMachine	Callback to remove a machine. This happens after the connection between the server and client terminates.
IMachineIdentityProviderCallback.ReturnGetMachineStatus	Get the machine status.
IMachineIdentityProviderCallback.ReturnMakeUserRemoteDesktopMapping	Callback for the MakeUserRemoteDesktopMapping operation.
IMachineIdentityProvider.RemoveMachine	Remove machine from the managed network. This is called from the server side.
IMachineIdentityProvider.RenewCert	Renew the caller's certificate.
IMachineIdentityProvider.RevokeCert	Revoke the caller's certificate.
IMachineIdentityProvider.GenerateCertResponse	This function is called by Enroll WebService. UserName/Password required to authenticate the user.
IMachineIdentityProvider.GenerateSid	Generate the SID for the machine. UserName/Password required to authenticate the user.
IMachineIdentityProvider.GetMachineStatus	Returns the status of machine named by the callback.
IMachineIdentityProvider.MakeUserRemoteDesktopMapping	Map a user to a particular remote desktop computer.

3.4.5.1 IMachineIdentityProvider.ReturnNewCertResponse

This operation is the callback for the **IMachineIdentityProvider.GenerateCertResponse** operation.

```
<wsdl:operation name="ReturnNewCertResponse">
  <wsdl:output
    wsam:Action="http://tempuri.org/IMachineIdentityProvider/ReturnNewCertResponse"
    message="tns:IMachineIdentityProvider_ReturnNewCertResponse_OutputCallbackMessage" />
</wsdl:operation>
```

3.4.5.1.1 Messages

3.4.5.1.1.1 IMachineIdentityProvider_ReturnNewCertResponse_OutputCallbackMessage

This is the request for the **ReturnNewCertResponse** operation.

```
<wsdl:message name="IMachineIdentityProviderCallback_ReturnNewCertResponse_OutputMessage">
  <wsdl:part name="parameters" element="tns:ReturnNewCertResponse" />
</wsdl:message>
```

This message MUST be sent with the following SOAP action.

<http://tempuri.org/IMachineIdentityProvider/ReturnNewCertResponse>

The body of the SOAP message MUST contain the **ReturnNewCertResponse** element.

3.4.5.1.2 Elements

3.4.5.1.2.1 ReturnNewCertResponse

This element specifies input values for the **ReturnNewCertResponse** operation. This operation MUST NOT be invoked by the management client and MUST be ignored by the server.

```
<xs:element name="ReturnNewCertResponse">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" name="newCert" nillable="true" type="xs:string" />
      <xs:element minOccurs="0" name="returnCode" nillable="true"
        xmlns:q1="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.Devices.Id
        entity" type="q1:ReturnClass" />
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

newCert: A string that contains the new certificate response.

returnCode: A **ReturnClass** (section [2.2.4.5.5](#)) complex type that contains the return code of the response.

3.4.5.2 IMachineIdentityProvider.ReturnRenewCert

This operation is the callback for the **IMachineIdentityProvider.RenewCert** operation. This operation MUST NOT be invoked by the management client and MUST be ignored by the server.

```
<wsdl:operation name="ReturnRenewCert">
  <wsdl:output wsam:Action="http://tempuri.org/IMachineIdentityProvider/ReturnRenewCert"
    messages="tns:IMachineIdentityProvider_ReturnRenewCert_OutputCallbackMessage" />
</wsdl:operation>
```

3.4.5.2.1 Messages

3.4.5.2.1.1 IMachineIdentityProvider_ReturnRenewCert_OutputCallbackMessage

This is the request for the **ReturnRenewCert** operation.

```
<wsdl:message name="IMachineIdentityProvider_ReturnRenewCert_OutputCallbackMessage">
  <wsdl:part name="parameters" element="tns:ReturnRenewCert" />
</wsdl:message>
```

This message MUST be sent with the following SOAP action.

<http://tempuri.org/IMachineIdentityProvider/ReturnRenewCert>

The body of the SOAP message MUST contain the **ReturnRenewCert** element.

3.4.5.2.2 Elements

3.4.5.2.2.1 ReturnRenewCert

This element specifies input values for the **ReturnRenewCert** operation.

```
<xs:element name="ReturnRenewCert">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" name="newCert" nillable="true" type="xs:string" />
      <xs:element minOccurs="0" name="returnCode" nillable="true"
        xmlns:q2="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.Devices.Id
        entity" type="q2:ReturnClass" />
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

newCert: A string that contains the response to the certificate renewal attempt.

returnCode: A **ReturnClass** (section [2.2.4.5.5](#)) complex type that contains the return code of the response.

3.4.5.3 IMachineIdentityProvider.ReturnSid

This operation is the callback for the **IMachineIdentityProvider.GenerateSid** operation.

```
<wsdl:operation name="ReturnSid">
  <wsdl:output wsam:Action="http://tempuri.org/IMachineIdentityProvider/ReturnSid"
    message="tns:IMachineIdentityProvider_ReturnSid_OutputCallbackMessage" />
</wsdl:operation>
```

3.4.5.3.1 Messages

3.4.5.3.1.1 IMachineIdentityProvider_ReturnSid_OutputCallbackMessage

This is the request for the **ReturnSid** operation.

```
<wsdl:message name="IMachineIdentityProvider_ReturnSid_OutputCallbackMessage">
  <wsdl:part name="parameters" element="tns:ReturnSid" />
</wsdl:message>
```

This message MUST be sent with the following SOAP action.

<http://tempuri.org/IMachineIdentityProvider/ReturnSid>

The body of the SOAP message MUST contain the **ReturnSid** element.

3.4.5.3.2 Elements

3.4.5.3.2.1 ReturnSid

This element specifies input values for the **ReturnSid** operation.

```
<xs:element name="ReturnSid">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" name="sid" nillable="true" type="xs:string" />
```

```

<xs:element minOccurs="0" name="returnCode" nillable="true"
  xmlns:q3="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.Devices.Id
  entity" type="q3:ReturnClass" />
  </xs:sequence>
</xs:complexType>
</xs:element>

```

sid: A string that contains the security identifier of the response.

resultCode: A **ReturnClass** (section [2.2.4.5.5](#)) complex type that contains the return code of the response.

3.4.5.4 IMachineIdentityProvider.ReturnRevokeCert

This operation is the callback for the **IMachineIdentityProvider.RevokeCert** operation.

```

<wsdl:operation name="ReturnRevokeCert">
  <wsdl:output wsam:Action="http://tempuri.org/IMachineIdentityProvider/ReturnRevokeCert">
    message="tns:IMachineIdentityProvider_ReturnRevokeCert_OutputCallbackMessage" />
</wsdl:operation>

```

3.4.5.4.1 Messages

3.4.5.4.1.1 IMachineIdentityProvider_ReturnRevokeCert_OutputCallbackMessage

This is the request for the **ReturnRevokeCert** operation.

```

<wsdl:message name="IMachineIdentityProvider_ReturnRevokeCert_OutputCallbackMessage">
  <wsdl:part name="parameters" element="tns:ReturnRevokeCert" />
</wsdl:message>

```

This message MUST be sent with the following SOAP action.

<http://tempuri.org/IMachineIdentityProvider/ReturnRevokeCert>

The body of the SOAP message MUST contain the **ReturnRevokeCert** element.

3.4.5.4.2 Elements

3.4.5.4.2.1 ReturnRevokeCert

This element specifies input values for the **ReturnRevokeCert** operation.

```

<xs:element name="ReturnRevokeCert">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" name="returnCode" nillable="true"
        xmlns:q4="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.Devices.Id
        entity" type="q4:ReturnClass" />
      </xs:sequence>
    </xs:complexType>
  </xs:element>

```

resultCode: A **ReturnClass** (section [2.2.4.5.5](#)) complex type that contains the return code of the response.

3.4.5.5 IMachineIdentityProvider.ReturnRemoveMachine

This operation is the callback for the **IMachineIdentityProvider.RemoveMachine** operation[<13>](#).

```
<wsdl:operation name="ReturnRemoveMachine">
  <wsdl:output wsam:Action="http://tempuri.org/IMachineIdentityProvider/ReturnRemoveMachine"
    message="tns:IMachineIdentityProvider_ReturnRemoveMachine_OutputCallbackMessage" />
</wsdl:operation>
```

3.4.5.5.1 Messages

3.4.5.5.1.1 IMachineIdentityProvider_ReturnRemoveMachine_OutputCallbackMessage

This is the request for the **ReturnRemoveMachine** operation.

```
<wsdl:message name="IMachineIdentityProvider_ReturnRemoveMachine_OutputCallbackMessage">
  <wsdl:part name="parameters" element="tns:ReturnRemoveMachine" />
</wsdl:message>
```

This message MUST be sent with the following SOAP action.

<http://tempuri.org/IMachineIdentityProvider/ReturnRemoveMachine>

The body of the SOAP message MUST contain the **ReturnRemoveMachine** element.

3.4.5.5.2 Elements

3.4.5.5.2.1 ReturnRemoveMachine

This element specifies input values for the **ReturnRemoveMachine** operation.

```
<xss:element name="ReturnRemoveMachine">
  <xss:complexType>
    <xss:sequence>
      <xss:element minOccurs="0" name="resultCode" nillable="true"
        xmlns:q5="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.Devices.Id
        entity" type="q5:ReturnClass" />
    </xss:sequence>
  </xss:complexType>
</xss:element>
```

resultCode: A **ReturnClass** (section [2.2.4.5.5](#)) complex type that contains the return code of the response.

3.4.5.6 IMachineIdentityProvider.ReturnGetMachineStatus

This operation is the callback for the **IMachineIdentityProvider.GetMachineStatus** operation.

```
<wsdl:operation name="ReturnGetMachineStatus">
```

```

<wsdl:output
wsam:Action="http://tempuri.org/IMachineIdentityProvider/ReturnGetMachineStatus"
message="tns:IMachineIdentityProvider_ReturnGetMachineStatus_OutputCallbackMessage" />
</wsdl:operation>

```

3.4.5.6.1 Messages

3.4.5.6.1.1 IMachineIdentityProvider_ReturnGetMachineStatus_OutputCallbackMessage

This is the request for the **ReturnGetMachineStatus** operation.

```

<wsdl:message name="IMachineIdentityProvider_ReturnGetMachineStatus_OutputCallbackMessage">
  <wsdl:part name="parameters" element="tns:ReturnGetMachineStatus" />
</wsdl:message>

```

This message MUST be sent with the following SOAP action.
<http://tempuri.org/IMachineIdentityProvider/ReturnGetMachineStatus>

The body of the SOAP message MUST contain the **ReturnGetMachineStatus** element.

3.4.5.6.2 Elements

3.4.5.6.2.1 ReturnGetMachineStatus

This element specifies input values for the **ReturnGetMachineStatus** operation.

```

<xss:element name="ReturnGetMachineStatus">
  <xss:complexType>
    <xss:sequence>
      <xss:element minOccurs="0" name="status" nillable="true"
        xmlns:q6="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.Devices.Id
        entity" type="q6:GetMachineStatusType" />
      <xss:element minOccurs="0" name="resultCode" nillable="true"
        xmlns:q7="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.Devices.Id
        entity" type="q7:ReturnClass" />
    </xss:sequence>
  </xss:complexType>
</xss:element>

```

status: A **GetMachineStatusType** (section [2.2.4.4.2](#)) complex type that contains the status of the specified machine.

resultCode: A **ReturnClass** (section [2.2.4.5.5](#)) complex type that contains the return code of the response.

3.4.5.7 IMachineIdentityProvider.ReturnMakeUserRemoteDesktopMapping

This operation is the callback for the **IMachineIdentityProvider.MakeUserRemoteDesktopMapping** operation.

```

<wsdl:operation name="ReturnMakeUserRemoteDesktopMapping">
  <wsdl:output
  wsam:Action="http://tempuri.org/IMachineIdentityProvider/ReturnMakeUserRemoteDesktopMapping"
  message="tns:IMachineIdentityProvider_ReturnMakeUserRemoteDesktopMapping_OutputCallbackMessag
  e" />
</wsdl:operation>

```

3.4.5.7.1 Messages

3.4.5.7.1.1 IMachineIdentityProvider_ReturnMakeUserRemoteDesktopMapping_Out putCallbackMessage

This is the request for the **ReturnMakeUserRemoteDesktopMapping** operation.

```
<wsdl:message  
name="IMachineIdentityProvider_ReturnMakeUserRemoteDesktopMapping_OutputCallbackMessage">  
    <wsdl:part name="parameters" element="tns:ReturnMakeUserRemoteDesktopMapping" />  
</wsdl:message>
```

This message MUST be sent with the following SOAP action.

```
http://tempuri.org/IMachineIdentityProvider/ReturnMakeUserRemoteDesktopMapping
```

The body of the SOAP message MUST contain the **ReturnMakeUserRemoteDesktopMapping** element.

3.4.5.7.2 Elements

3.4.5.7.2.1 ReturnMakeUserRemoteDesktopMapping

This element specifies input values for the **ReturnMakeUserRemoteDesktopMapping** operation.

```
<xs:element name="ReturnMakeUserRemoteDesktopMapping">  
    <xs:complexType>  
        <xs:sequence>  
            <xs:element minOccurs="0" name="returnCode" nillable="true"  
                xmlns:q8="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.Devices.Id  
                entity" type="q8:ReturnClass" />  
        </xs:sequence>  
    </xs:complexType>  
</xs:element>
```

returnCode: A **ReturnClass** (section [2.2.4.5.5](#)) complex type that contains the return code of the response.

3.4.5.8 IMachineIdentityProvider.RemoveMachine

This operation removes a machine from the managed network.[<14>](#)

```
<wsdl:operation name="RemoveMachine">  
    <wsdl:input wsam:Action="http://tempuri.org/IMachineIdentityProvider/RemoveMachine"  
    message="tns:IMachineIdentityProvider_RemoveMachine_InputMessage" />  
</wsdl:operation>
```

Upon receiving the **IMachineIdentityProvider_RemoveMachine_InputMessage** request message, the protocol server is notified to remove the specific machine. In the event of a failure, an appropriate SOAP fault MUST be sent to the client as specified in section [2.2.2.1](#).

3.4.5.8.1 Messages

3.4.5.8.1.1 IMachineIdentityProvider_RemoveMachine_InputMessage

This is the request for the **RemoveMachine** operation.

```
<wsdl:message name="IMachineIdentityProvider_RemoveMachine_InputMessage">
  <wsdl:part name="parameters" element="tns:RemoveMachine" />
</wsdl:message>
```

This message MUST be sent with the following SOAP action.

```
http://tempuri.org/IMachineIdentityProvider/RemoveMachine
```

The body of the SOAP message MUST contain the **RemoveMachine** element.

3.4.5.8.2 Elements

3.4.5.8.2.1 RemoveMachine

This element specifies input values for the **RemoveMachine** operation.

```
<xs:element name="RemoveMachine">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" name="machineID" type="xs:string" />
      <xs:element minOccurs="0" name="serialNo" type="xs:string" />
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

machineID: A string that contains the ID of the machine to be removed.

serialNo: A string that contains the serial number of the machine to be removed.

3.4.5.9 IMachineIdentityProvider.RenewCert

This operation renews the caller's certificate.

```
<wsdl:operation name="RenewCert">
  <wsdl:input wsam:Action="http://tempuri.org/IMachineIdentityProvider/RenewCert"
  message="tns:IMachineIdentityProvider RenewCert InputMessage" />
</wsdl:operation>
```

Upon receiving the **IMachineIdentityProvider_RenewCert_InputMessage** request message, the protocol server is notified to renew the caller's certificate. In the event of a failure, an appropriate SOAP fault MUST be sent to the client as specified in section [2.2.2.1](#).

3.4.5.9.1 Messages

3.4.5.9.1.1 IMachineIdentityProvider_RenewCert_InputMessage

This is the request for the **RenewCert** operation.

```
<wsdl:message name="IMachineIdentityProvider_RenewCert_InputMessage">
  <wsdl:part name="parameters" element="tns:RenewCert" />
</wsdl:message>
```

This message MUST be sent with the following SOAP action.

```
http://tempuri.org/IMachineIdentityProvider/RenewCert
```

The body of the SOAP message MUST contain the **RenewCert** element.

3.4.5.9.2 Elements

3.4.5.9.2.1 RenewCert

This element specifies input values for the **RenewCert** operation.

```
<xs:element name="RenewCert">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" name="strCSR" type="xs:string" />
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

strCSR: A string that contains the CSR for the certificate.

3.4.5.10 IMachineIdentityProvider.RevokeCert

This operation revokes the caller's certificate.

```
<wsdl:operation name="RevokeCert">
  <wsdl:output wsaw:Action="net.tcp://Microsoft.WindowsServerSolutions.Devices.Identity/
  IMachineIdentityProvider/RevokeCertResponse"
  message="IMachineIdentityProvider RevokeCert InputMessage" />
</wsdl:operation>
```

Upon receiving the **IMachineIdentityProvider_RevokeCert_InputMessage** request message, the protocol server is notified to revoke the caller's certificate. In the event of a failure, an appropriate SOAP fault MUST be sent to the client as specified in section [2.2.2.1](#).

3.4.5.10.1 Messages

3.4.5.10.1.1 IMachineIdentityProvider_RevokeCert_InputMessage

This is the response for the **RevokeCert** operation.

```
<wsdl:message name="IMachineIdentityProvider_RevokeCert_InputMessage">
  <wsdl:part name="parameters" element="tns:RevokeCert" />
</wsdl:message>
```

This message MUST be sent with the following SOAP action.

```
http://tempuri.org/IMachineIdentityProvider/RevokeCert
```

The body of the SOAP message MUST contain the **RevokeCertResponse** element.

3.4.5.10.2 Elements

3.4.5.10.2.1 RevokeCert

This element specifies input values for the **RevokeCert** operation. This element has no parameters.

```
<xs:element name="RevokeCert">
  <xs:complexType>
    <xs:sequence />
  </xs:complexType>
</xs:element>
```

3.4.5.11 IMachineIdentityProvider.GenerateCertResponse

This operation generates a certificate for a machine.

```
<wsdl:operation name="GenerateCertResponse">
  <wsdl:input wsam:Action="http://tempuri.org/IMachineIdentityProvider/GenerateCertResponse"
  message="tns:IMachineIdentityProvider_GenerateCertResponse_InputMessage" />
</wsdl:operation>
```

Upon receiving the **IMachineIdentityProvider_GenerateCertResponse_InputMessage** request message, the protocol server is notified to generate a certificate for the machine. In the event of a failure, an appropriate SOAP fault MUST be sent to the client as specified in section [2.2.2.1](#).

3.4.5.11.1 Messages

3.4.5.11.1.1 IMachineIdentityProvider_GenerateCertResponse_InputMessage

This is the request for the **GenerateCertResponse** operation.

```
<wsdl:message name="IMachineIdentityProvider_GenerateCertResponse_InputMessage">
  <wsdl:part name="parameters" element="tns:GenerateCertResponse" />
</wsdl:message>
```

This message MUST be sent with the following SOAP action.

<http://tempuri.org/IMachineIdentityProvider/GenerateCertResponse>

The body of the SOAP message MUST contain the **GenerateCertResponse** element.

3.4.5.11.2 Elements

3.4.5.11.2.1 GenerateCertResponse

This element specifies input values for the **GenerateCertResponse** operation.

```
<xs:element name="GenerateCertResponse">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" name="userName" type="xs:string" />
      <xs:element minOccurs="0" name="password" type="xs:string" />
      <xs:element minOccurs="0" name="strCSR" type="xs:string" />
      <xs:element minOccurs="0" name="machineName" type="xs:string" />
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

username: A string that contains the user name of the credential performing the operation.

password: A string that contains the password of the credential performing the operation.

strCSR: A string that contains the CSR for the certificate.

machineName: A string that contains the name of the machine to which the certificate is issued.

3.4.5.12 IMachineIdentityProvider.GenerateSid

This operation generates the SID for a machine.

```
<wsdl:operation name="GenerateSid">
  <wsdl:input wsam:Action="http://tempuri.org/IMachineIdentityProvider/GenerateSid"
  message="tns:IMachineIdentityProvider_GenerateSid_InputMessage" />
</wsdl:operation>
```

Upon receiving the **IMachineIdentityProvider_GenerateSid_InputMessage** request message, the protocol server is notified to generate the SID for the machine. In the event of a failure, an appropriate SOAP fault MUST be sent to the client as specified in section [2.2.2.1](#).

3.4.5.12.1 Messages

3.4.5.12.1.1 IMachineIdentityProvider_GenerateSid_InputMessage

This is the request for the **GenerateSid** operation.

```
<wsdl:message name="IMachineIdentityProvider_GenerateSid_InputMessage">
  <wsdl:part name="parameters" element="tns:GenerateSid" />
</wsdl:message>
```

This message MUST be sent with the following SOAP action.

<http://tempuri.org/IMachineIdentityProvider/GenerateSid>

The body of the SOAP message MUST contain the **GenerateSid** element.

3.4.5.12.2 Elements

3.4.5.12.2.1 GenerateSid

This element specifies input values for the **GenerateSid** operation.

```
<xss:element name="GenerateSid">
  <xss:complexType>
    <xss:sequence>
      <xss:element minOccurs="0" name="userName" type="xss:string" />
      <xss:element minOccurs="0" name="password" type="xss:string" />
      <xss:element minOccurs="0" name="machineName" type="xss:string" />
      <xss:element minOccurs="0" name="bForce" type="xss:boolean" />
    </xss:sequence>
  </xss:complexType>
</xss:element>
```

username: A string that contains the user name of the credential performing the operation.

password: A string that contains the password of the credential performing the operation.

machineName: A string that contains the name of the machine to which the certificate is issued.

bForce: A Boolean where TRUE indicates that the existing machine name will be overwritten; otherwise, the value is FALSE.

3.4.5.13 IMachineIdentityProvider.GetMachineStatus

This operation returns the status of the machine named by the callback.

```
<wsdl:operation name="GetMachineStatus">
  <wsdl:input wsam:Action="http://tempuri.org/IMachineIdentityProvider/GetMachineStatus"
  message="tns:IMachineIdentityProvider_GetMachineStatus_InputMessage" />
</wsdl:operation>
```

Upon receiving the **IMachineIdentityProvider_GetMachineStatus_InputMessage** request message, the protocol server is notified to return the status of the machine. In the event of a failure, an appropriate SOAP fault MUST be sent to the client as specified in section [2.2.2.1](#).

3.4.5.13.1 Messages

3.4.5.13.1.1 IMachineIdentityProvider_GetMachineStatus_InputMessage

This is the request for the **GetMachineStatus** operation.

```
<wsdl:message name="IMachineIdentityProvider_GetMachineStatus_InputMessage">
  <wsdl:part name="parameters" element="tns:GetMachineStatus" />
</wsdl:message>
```

This message MUST be sent with the following SOAP action.

`http://tempuri.org/IMachineIdentityProvider/GetMachineStatus`

The body of the SOAP message MUST contain the **GetMachineStatus** element.

3.4.5.13.2 Elements

3.4.5.13.2.1 GetMachineStatus

This element specifies input values for the **GetMachineStatus** operation.

```
<xs:element name="GetMachineStatus">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" name="userName" type="xs:string" />
      <xs:element minOccurs="0" name="password" type="xs:string" />
      <xs:element minOccurs="0" name="machineName" type="xs:string" />
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

username: A string that contains the user name of the credential performing the operation.

password: A string that contains the password of the credential performing the operation.

machineName: A string that contains the name of the machine to which the certificate is issued.

3.4.5.14 IMachineIdentityProvider.MakeUserRemoteDesktopMapping

This operation maps a user to a particular computer.

```
<wsdl:operation name="MakeUserRemoteDesktopMapping">
  <wsdl:input
    wsam:Action="http://tempuri.org/IMachineIdentityProvider/MakeUserRemoteDesktopMapping"
    messages="tns:IMachineIdentityProvider_MakeUserRemoteDesktopMapping_InputMessage" />
</wsdl:operation>
```

Upon receiving the **IMachineIdentityProvider_MakeUserRemoteDesktopMapping_InputMessage** request message, the protocol server is notified to map a user to a particular computer. In the event of a failure, an appropriate SOAP fault MUST be sent to the client as specified in section [2.2.2.1](#).

3.4.5.14.1 Messages

3.4.5.14.1.1 IMachineIdentityProvider_MakeUserRemoteDesktopMapping_InputMessage

This is the request for the **MakeUserRemoteDesktopMapping** operation.

```
<wsdl:message name="IMachineIdentityProvider_MakeUserRemoteDesktopMapping_InputMessage">
  <wsdl:part name="parameters" element="tns:MakeUserRemoteDesktopMapping" />
</wsdl:message>
```

This message MUST be sent with the following SOAP action.

`http://tempuri.org/IMachineIdentityProvider/MakeUserRemoteDesktopMapping`

The body of the SOAP message MUST contain the **MakeUserRemoteDesktopMapping** element.

3.4.5.14.2 Elements

3.4.5.14.2.1 MakeUserRemoteDesktopMapping

This element specifies input values for the **MakeUserRemoteDesktopMapping** operation.

```
<xss:element name="MakeUserRemoteDesktopMapping">
  <xss:complexType>
    <xss:sequence>
      <xss:element minOccurs="0" name="userName" type="xss:string" />
    </xss:sequence>
  </xss:complexType>
</xss:element>
```

username: A string that contains the name of the user that will be the owner of the remote machine.

3.4.6 Timer Events

None.

3.4.7 Other Local Events

None.

3.5 User Identity Provider Service Contract Details

3.5.1 Abstract Data Model

This section describes a conceptual service contract that an implementation maintains to participate in this protocol. The described operations of the service contract are provided to facilitate the explanation of how the protocol behaves. This document does not mandate that implementations adhere to this service contract as long as their external behavior is consistent with how it is described in this document.

3.5.1.1 ADM_KeyValueOfUser

This is a dictionary of user information for all domain users.

Key: The SID of the user.

Value: Information about the given user.

3.5.1.1.1 Data Model

3.5.1.1.1.1 UserInfo

Note that the UserInfo data model also has a corresponding SOAP complex type defined in section [2.2.4.5.2](#).

FullUserName: The domain/ServerName of the user. Mainly used in Launchpad.

PersonalInfo: Detailed personal information about the given user. The PersonalInfo type is defined in section [2.2.4.5.1](#); see also the details in section [3.5.1.1.1.1](#).

UserName: The name of the user.

UserStatus: The status of the user. The UserStatus type is defined in section [2.2.5.5.5](#).

Warning: The last error of import/update/add user.

WindowsAccount: The account of this user.[<15>](#)

WindowsSID: The SID of this user.[<16>](#)

3.5.1.1.1.1.1 PersonalInfo

AccessLevel: The access level of the user. The AccessLevelType is defined in section [2.2.5.5.4](#).

FirstName: The first name of the user.

IsBuiltIn: TRUE if the user is built-in; otherwise FALSE.

IsLocalUser: TRUE if the user is local; otherwise FALSE.

IsShowInUI: TRUE if this user shows in the UI; otherwise FALSE.

LastName: The last name of the user.

RemoteAccess: The remote access status of the user. RemoteAccessType is defined in section [2.2.5.5.3](#).

UserFolder: The path of the shared folder belonging to this user.

VpnAccess: The VPN access status of the user. VPNAccessType is defined in section 2.2.5.5.3.

3.5.2 Timers

None.

3.5.3 Initialization

None.

3.5.4 Higher-Layer Triggered Events

None.

3.5.5 Message Processing Events and Sequencing Rules

OperationContract	Description
IUserIdentityProvider.ChangePassword	Change the user password.
IUserLogonProvider.LogonUser	Log on a user (who provides the correct password) and display the requested UserInfo.
IUserChangePasswordProvider.ChangePassword	Change the user password.
IUserInfoProvider.ReturnGroups	Callback to OM after GetGroups.
IUserInfoProvider.ReturnWSServerGroups	Callback to OM after GetWSServerGroups.
IUserInfoProvider.ReturnIsPartOfServerUsers	Callback to OM after IsPartOfServerUsers.
IUserInfoProvider.GetGroups	Get groups for the current user.
IUserInfoProvider.GetWSServerGroups	Get WSServer Groups for the current user.
IUserInfoProvider.IsPartOfServerUsers	Check whether the use is server users.

3.5.5.1 IUserLogonProvider.LogonUser

This operation logs a user on and displays the requested UserInfo. [<17>](#)

```
<wsdl:operation name="LogonUser">
  <wsdl:input
    wsam:Action="http://www.microsoft.com/WindowsServerSolutions/ProviderFramework/Notifications/
    3/2010/IUserLogonProvider/LogonUser" message="tns:IUserLogonProvider_LogonUser_InputMessage"
  />
  <wsdl:output
    wsam:Action="http://www.microsoft.com/WindowsServerSolutions/ProviderFramework/Notifications/
    3/2010/IUserLogonProvider/LogonUserResponse"
    message="tns:IUserLogonProvider_LogonUser_OutputMessage" />
  <wsdl:fault
    wsam:Action="http://www.microsoft.com/WindowsServerSolutions/ProviderFramework/Notifications/
    3/2010/IUserLogonProvider/LogonUserUserFaultFault" name="UserFaultFault"
    message="tns:IUserLogonProvider_LogonUser_UserFaultFault_FaultMessage" />
```

```

<wsdl:fault
wsam:Action="http://www.microsoft.com/WindowsServerSolutions/ProviderFramework/Notifications/
3/2010/IUserLogonProvider/LogonUserUserExceptionFaultFault" name="UserExceptionFaultFault"
message="tns:IUserLogonProvider_LogonUser_UserExceptionFaultFault_FaultMessage" />
<wsdl:fault
wsam:Action="http://www.microsoft.com/WindowsServerSolutions/ProviderFramework/Notifications/
3/2010/IUserLogonProvider/LogonUserUserExceptionFault" name="UserExceptionFault"
message="tns:IUserLogonProvider_LogonUser_UserExceptionFault_FaultMessage" />
</wsdl:operation>
```

Upon receiving the **IUserLogonProvider_LogonUser_InputMessage** request message, the protocol server logs on the user if they provided the correct password. Upon successful completion of the action, the server MUST respond with **IUserLogonProvider_LogonUser_OutputMessage**, which includes the user information object. In the event of a failure, an appropriate SOAP fault MUST be sent to the client as specified in section [2.2.2.1](#).

3.5.5.1.1 Messages

3.5.5.1.1.1 IUserLogonProvider_LogonUser_InputMessage

This is the request for the **LogonUser** operation.

```
<wsdl:message name="IUserLogonProvider_LogonUser_InputMessage">
  <wsdl:part name="parameters" element="tns:LogonUser" />
</wsdl:message>
```

This message MUST be sent with the following SOAP action.

<http://www.microsoft.com/WindowsServerSolutions/ProviderFramework/Notifications/3/2010/IUserLogonProvider/LogonUser>

The body of the SOAP message MUST contain the **LogonUser** element.

3.5.5.1.1.2 IUserLogonProvider_LogonUser_OutputMessage

This is the response for the **LogonUser** operation.

```
<wsdl:message name="IUserLogonProvider_LogonUser_OutputMessage">
  <wsdl:part name="parameters" element="tns:LogonUserResponse" />
</wsdl:message>
```

This message MUST be sent with the following SOAP action.

<http://www.microsoft.com/WindowsServerSolutions/ProviderFramework/Notifications/3/2010/IUserIdentityProvider/LogonUserResponse>

The body of the SOAP message MUST contain the **LogonUserResponse** element.

3.5.5.1.2 Elements

3.5.5.1.2.1 LogonUser

This element specifies input values for the **LogonUser** operation.

```

<xs:element name="LogonUser">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" name="userName" nillable="true" type="xs:string" />
      <xs:element minOccurs="0" name="password" nillable="true" type="xs:string" />
      <xs:element minOccurs="0" name="bCleanSession" type="xs:boolean" />
    </xs:sequence>
  </xs:complexType>
</xs:element>

```

username: A string that contains the name of the user that is attempting to log on.

password: A string that contains the password of the user that is attempting to log on.

bCleanSession: A Boolean where TRUE indicates that the session should be cleaned; otherwise, the value is FALSE.

3.5.5.1.2.2 LogonUserResponse

This element specifies output values for the **LogonUser** operation.

```

<xs:element name="LogonUserResponse">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" name="LogonUserResult" nillable="true"
      xmlns:q1="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.Users"
      type="q1:UserInfo" />
    </xs:sequence>
  </xs:complexType>
</xs:element>

```

LogonUserResult: A **UserInfo** (section [2.2.4.5.2](#)) complex type that contains the result of the specified user's logon attempt.

3.5.5.2 IUserChangePasswordProvider.ChangePassword

This operation changes a user's password. [<18>](#)

```

<wsdl:operation name="ChangePassword">
  <wsdl:input
  wsam:Action="http://www.microsoft.com/WindowsServerSolutions/ProviderFramework/Notifications/
  3/2010/ IUserChangePasswordProvider /ChangePassword" message="tns:
  IUserChangePasswordProvider ChangePassword InputMessage" />
  <wsdl:output
  wsam:Action="http://www.microsoft.com/WindowsServerSolutions/ProviderFramework/Notifications/
  3/2010/ IUserChangePasswordProvider /ChangePasswordResponse" message="tns:
  IUserChangePasswordProvider _ChangePassword_OutputMessage" />
  <wsdl:fault
  wsam:Action="http://www.microsoft.com/WindowsServerSolutions/ProviderFramework/Notifications/
  3/2010/ IUserChangePasswordProvider /ChangePasswordUserExceptionFault"
  name="UserExceptionFault" message="tns: IUserChangePasswordProvider
  _ChangePassword_UserExceptionFault_FaultMessage" />
  <wsdl:fault
  wsam:Action="http://www.microsoft.com/WindowsServerSolutions/ProviderFramework/Notifications/
  3/2010/ IUserChangePasswordProvider /ChangePasswordUserExceptionFaultFault"
  name="UserExceptionFaultFault" message="tns: IUserChangePasswordProvider
  _ChangePassword_UserExceptionFaultFault_FaultMessage" />
  <wsdl:fault
  wsam:Action="http://www.microsoft.com/WindowsServerSolutions/ProviderFramework/Notifications/
  3/2010/ IUserChangePasswordProvider /ChangePasswordUserFaultFault" name="UserFaultFault"
  message="tns: IUserChangePasswordProvider _ChangePassword_UserFaultFault_FaultMessage" />

```

```
</wsdl:operation>
```

Upon receiving the **IUserChangePasswordProvider _ChangePassword_InputMessage** request message, the protocol server changes the specified user's password. Upon successful completion of the action, the server MUST respond with **IUserChangePasswordProvider _ChangePassword_OutputMessage**. In the event of a failure, an appropriate SOAP fault MUST be sent to the client as specified in section [2.2.2.1](#).

3.5.5.2.1 Messages

3.5.5.2.1.1 IUserChangePasswordProvider_ChangePassword_InputMessage

This is the request for the **ChangePassword** operation.

```
<wsdl:message name="IUserChangePasswordProvider_ChangePassword_InputMessage">
  <wsdl:part name="parameters" element="tns:ChangePassword" />
</wsdl:message>
```

This message MUST be sent with the following SOAP action.

```
http://www.microsoft.com/WindowsServerSolutions/ProviderFramework/Notifications/3/2010/IUserC
hangePasswordProvider/ChangePassword
```

The body of the SOAP message MUST contain the **ChangePassword** element.

3.5.5.2.1.2 IUserChangePasswordProvider_ChangePassword_OutputMessage

This is the response for the **ChangePassword** operation.

```
<wsdl:message name="IUserChangePasswordProvider ChangePassword OutputMessage">
  <wsdl:part name="parameters" element="tns:ChangePasswordResponse" />
</wsdl:message>
```

This message MUST be sent with the following SOAP action.

```
http://www.microsoft.com/WindowsServerSolutions/ProviderFramework/Notifications/3/2010/IUserC
hangePasswordProvider/ChangePasswordResponse
```

The body of the SOAP message MUST contain the **ChangePasswordResponse** element.

3.5.5.2.2 Elements

3.5.5.2.2.1 ChangePassword

This element specifies input values for the **ChangePassword** operation.

```
<xs:element name="ChangePassword">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" name="userName" nillable="true" type="xs:string" />
      <xs:element minOccurs="0" name="oldPassword" nillable="true" type="xs:string" />
      <xs:element minOccurs="0" name="newPassword" nillable="true" type="xs:string" />
    </xs:sequence>
```

```
</xs:complexType>
</xs:element>
```

username: A string that contains the name of the user whose password will be changed.

oldPassword: A string that contains the specified user's old password.

newPassword: A string that contains the specified user's new password.

3.5.5.2.2.2 ChangePasswordResponse

This element specifies output values for the **ChangePassword** operation.

```
<xs:element name="ChangePasswordResponse">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="1" maxOccurs="1" name="ChangePasswordResult" type="UserInfo" />
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

ChangePasswordResult: A **UserInfo** (section [2.2.4.5.2](#)) complex type that contains the result of the password change attempt.

3.5.5.3 IUserInfoProvider.ReturnGroups

This operation is a callback for the **IUserInfoProvider.GetGroups** operation. This operation MUST NOT be invoked by the management client and MUST be ignored by the server.

```
<wsdl:operation name="ReturnGroups">
  <wsdl:output
    wsam:Action="http://www.microsoft.com/WindowsServerSolutions/ProviderFramework/Notifications/
  3/2010/IUserInfoProvider/ReturnGroups"
    message="tns:IUserInfoProvider_ReturnGroups_OutputCallbackMessage" />
</wsdl:operation>
```

Upon receiving the **IUserInfoProvider_ReturnGroups_OutputCallbackMessage** request message, the protocol client performs the following processing steps. In the event of a failure, an appropriate SOAP fault MUST be sent to the server as specified in section [2.2.2.1](#).

3.5.5.3.1 Messages

3.5.5.3.1.1 IUserInfoProvider_ReturnGroups_OutputCallbackMessage

This is the request for the **ReturnGroups** operation.

```
<wsdl:message name="IUserInfoProviderCallback_ReturnGroups_OutputCallbackMessage">
  <wsdl:part name="parameters" element="tns:ReturnGroups" />
</wsdl:message>
```

This message MUST be sent with the following SOAP action.

```
http://www.microsoft.com/WindowsServerSolutions/ProviderFramework/Notifications/3/2010/IUserInfoProviderCallback/ReturnGroups
```

The body of the SOAP message MUST contain the **ReturnGroups** element.

3.5.5.3.2 Elements

3.5.5.3.2.1 ReturnGroups

This element specifies input values for the **ReturnGroups** operation.

```
<xs:element name="ReturnGroups">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" name="groups" nillable="true"
        xmlns:q1="http://schemas.microsoft.com/2003/10/Serialization/Arrays" type="q1:ArrayOfstring"
      />
      <xs:element minOccurs="0" name="ret" nillable="true"
        xmlns:q2="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.Users"
        type="q2:ReturnClass" />
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

groups: An array of strings that contains the server groups to which the current user belongs.

ret: A **ReturnClass** (section [2.2.4.5.5](#)) complex type representing the return code from the operation.

3.5.5.4 IUserInfoProvider.ReturnWSServerGroups

This operation is callback for the **IUserInfoProvider.GetWSServerGroups** operation. This operation MUST NOT be invoked by the management client and MUST be ignored by the server.

```
<wsdl:operation name="ReturnWSServerGroups">
  <wsdl:output
    wsam:Action="http://www.microsoft.com/WindowsServerSolutions/ProviderFramework/Notifications/
    3/2010/IUserInfoProvider/ReturnWSServerGroups"
    message="tns:IUserInfoProvider_ReturnWSServerGroups_OutputCallbackMessage" />
</wsdl:operation>
```

Upon receiving the **IUserInfoProvider_ReturnWSServerGroups_OutputCallbackMessage** request message, the protocol client performs the following processing steps. In the event of a failure, an appropriate SOAP fault MUST be sent to the server as specified in section [2.2.2.1](#).

3.5.5.4.1 Messages

3.5.5.4.1.1 IUserInfoProvider_ReturnWSServerGroups_OutputCallbackMessage

This is the request for the **ReturnWSServerGroups** operation.

```
<wsdl:message name="IUserInfoProviderCallback_ReturnWSServerGroups_OutputCallbackMessage">
  <wsdl:part name="parameters" element="ReturnWSServerGroups" />
</wsdl:message>
```

This message MUST be sent with the following SOAP action.

<http://Microsoft.WindowsServerSolutions.Users/IUserInfoProviderCallback/ReturnWSServerGroups>

The body of the SOAP message MUST contain the **ReturnWSServerGroups** element.

3.5.5.4.2 Elements

3.5.5.4.2.1 ReturnWSServerGroups

This element specifies input values for the **ReturnWSServerGroups** operation.

```
<xs:element name="ReturnWSServerGroups">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" name="groups" nillable="true"
        xmlns:q3="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.Users"
        type="q3:ArrayOfWSServerGroupType" />
      <xs:element minOccurs="0" name="ret" nillable="true"
        xmlns:q4="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.Users"
        type="q4:ReturnClass" />
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

groups: An array of **WSServerGroupType** (section [2.2.5.5.1](#)) strings that contains the server groups to which the current user belongs.

ret: A **ReturnClass** (section [2.2.4.5.5](#)) complex type representing the return code from the operation.

3.5.5 IUserInfoProvider.ReturnIsPartOfServerUsers

This operation is a callback for the **IUserInfoProvider.IsPartOfServerUsers** operation. This operation MUST NOT be invoked by the management client and MUST be ignored by the server.

```
<wsdl:operation name="ReturnIsPartOfServerUsers">
  <wsdl:output
    wsam:Action="http://www.microsoft.com/WindowsServerSolutions/ProviderFramework/Notifications/
    3/2010/IUserInfoProvider/ReturnIsPartOfServerUsers"
    message="tns:IUserInfoProvider_ReturnIsPartOfServerUsers_OutputCallbackMessage" />
</wsdl:operation>
```

Upon receiving the **IUserInfoProvider_ReturnIsPartOfServerUsers_OutputCallbackMessage** request message, the protocol client performs the following processing steps. In the event of a failure, an appropriate SOAP fault MUST be sent to the server as specified in section [2.2.2.1](#).

3.5.5.5.1 Messages

3.5.5.5.1.1 IUserInfoProvider_ReturnIsPartOfServerUsers_OutputCallbackMessage

This is the request for the **ReturnIsPartOfServerUsers** operation.

```
<wsdl:message
  name="IUserInfoProviderCallback_ReturnIsPartOfServerUsers_OutputCallbackMessage">
  <wsdl:part name="parameters" element="tns:ReturnIsPartOfServerUsers" />
</wsdl:message>
```

This message MUST be sent with the following SOAP action.

<http://www.microsoft.com/WindowsServerSolutions/ProviderFramework/Notifications/3/2010/IUserInfoProviderCallback/ReturnIsPartOfServerUsers>

The body of the SOAP message MUST contain the **ReturnIsPartOfServerUsers** element.

3.5.5.2 Elements

3.5.5.2.1 ReturnIsPartOfServerUsers

This element specifies input values for the **ReturnIsPartOfServerUsers** operation.

```
<xs:element name="ReturnIsPartOfServerUsers">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" name="bIsPartOfServerUsers" type="xs:boolean" />
      <xs:element minOccurs="0" name="ret" nillable="true"
        xmlns:q5="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.Users"
        type="q5:ReturnClass" />
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

bIsPartOfServerUsers: A Boolean where TRUE indicates that the current user is a part of server users; otherwise, the value is FALSE.

ret: A **ReturnClass** (section [2.2.4.5.5](#)) complex type that contains the return code from the operation.

3.5.6 IUserInfoProvider.GetGroups

This operation returns the groups for the current user.

```
<wsdl:operation name="GetGroups">
  <wsdl:input
    wsam:Action="http://www.microsoft.com/WindowsServerSolutions/ProviderFramework/Notifications/
    3/2010/IUserInfoProvider/GetGroups" message="tns:IUserInfoProvider GetGroups InputMessage" />
</wsdl:operation>
```

Upon receiving the **IUserInfoProvider_GetGroups_InputMessage** request message, the protocol server starts to get the groups for current user. In the event of a failure, an appropriate SOAP fault MUST be sent to the client as specified in section [2.2.2.1](#).

3.5.6.1 Messages

3.5.6.1.1 IUserInfoProvider_GetGroups_InputMessage

This is the request for the **GetGroups** operation.

```
<wsdl:message name="IUserInfoProvider_GetGroups_InputMessage">
  <wsdl:part name="parameters" element="tns:GetGroups" />
</wsdl:message>
```

This message MUST be sent with the following SOAP action.

<http://www.microsoft.com/WindowsServerSolutions/ProviderFramework/Notifications/3/2010/IUserInfoProvider/GetGroups>

The body of the SOAP message MUST contain the **GetGroups** element.

3.5.5.6.2 Elements

3.5.5.6.2.1 GetGroups

This element specifies input values for the **GetGroups** operation. This element has no parameters.

```
<xs:element name="GetGroups">
  <xs:complexType>
    <xs:sequence />
  </xs:complexType>
</xs:element>
```

3.5.5.7 IUserInfoProvider.GetWSSServerGroups

This operation returns the WSSServer groups for the current user.

```
<wsdl:operation name="GetWSSServerGroups">
  <wsdl:input
    wsam:Action="http://www.microsoft.com/WindowsServerSolutions/ProviderFramework/Notifications/
  3/2010/IUserInfoProvider/GetWSSServerGroups"
    message="tns:IUserInfoProvider_GetWSSServerGroups_InputMessage" />
</wsdl:operation>
```

Upon receiving the **IUserInfoProvider_GetWSSServerGroups_InputMessage** request message, the protocol server starts to get the WSSServer Groups for current user. In the event of a failure, an appropriate SOAP fault MUST be sent to the client as specified in section [2.2.2.1](#).

3.5.5.7.1 Messages

3.5.5.7.1.1 IUserInfoProvider_GetWSSServerGroups_InputMessage

This is the request for the **GetWSSServerGroups** operation.

```
<wsdl:message name="IUserInfoProvider_GetWSSServerGroups_InputMessage">
  <wsdl:part name="parameters" element="tns:GetWSSServerGroups" />
</wsdl:message>
```

This message MUST be sent with the following SOAP action.

<http://www.microsoft.com/WindowsServerSolutions/ProviderFramework/Notifications/3/2010/IUserInfoProvider/GetWSSServerGroups>

The body of the SOAP message MUST contain the **GetWSSServerGroups** element.

3.5.5.7.2 Elements

3.5.5.7.2.1 GetWSSServerGroups

This element specifies input values for the **GetWSSServerGroups** operation. This element has no parameters.

```
<xs:element name="GetWSSServerGroups">
  <xs:complexType>
    <xs:sequence />
  </xs:complexType>
</xs:element>
```

3.5.5.8 IUserInfoProvider.IsPartOfServerUsers

This operation returns a value indicating whether the user is a member of the set of server users.

```
<wsdl:operation name="IsPartOfServerUsers">
  <wsdl:input
    wsam:Action="http://www.microsoft.com/WindowsServerSolutions/ProviderFramework/Notifications/
    3/2010/IUserInfoProvider/IsPartOfServerUsers"
    message="tns:IUserInfoProvider_IsPartOfServerUsers_InputMessage" />
</wsdl:operation>
```

Upon receiving the **IUserInfoProvider_IsPartOfServerUsers_InputMessage** request message, the protocol server starts to get a Boolean indicating whether the current user is part of server users. In the event of a failure, an appropriate SOAP fault MUST be sent to the client as specified in section [2.2.2.1](#).

3.5.5.8.1 Messages

3.5.5.8.1.1 IUserInfoProvider_IsPartOfServerUsers_InputMessage

This is the request for the **IsPartOfServerUsers** operation.

```
<wsdl:message name="IUserInfoProvider_IsPartOfServerUsers_InputMessage">
  <wsdl:part name="parameters" element="tns:IsPartOfServerUsers" />
</wsdl:message>
```

This message MUST be sent with the following SOAP action.

```
http://www.microsoft.com/WindowsServerSolutions/ProviderFramework/Notifications/3/2010/IUserInfoProvider/IsPartOfServerUsers
```

The body of the SOAP message MUST contain the **IsPartOfServerUsers** element.

3.5.5.8.2 Elements

3.5.5.8.2.1 IsPartOfServerUsers

This element specifies input values for the **IsPartOfServerUsers** operation. This element has no parameters.

```
<xs:element name="IsPartOfServerUsers">
  <xs:complexType>
    <xs:sequence />
  </xs:complexType>
</xs:element>
```

3.5.6 Timer Events

None.

3.5.7 Other Local Events

None.

3.6 Provider Registry Service Contract Details

3.6.1 Abstract Data Model

None.

3.6.2 Timers

None.

3.6.3 Initialization

None.

3.6.4 Higher-Layer Triggered Events

None.

3.6.5 Message Processing Events and Sequencing Rules

OperationContract	Description
IProviderRegistry.Disconnect	Signal the ProviderRegistryService that the connection is terminating.
IProviderRegistry.Query	Return a list of ProviderInfo data for a given contract.
IProviderRegistry.QueryAll	Get all registered providers.
IProviderRegistry.RequestProviderInfoUpdate	Request an update for specific providers.
IProviderRegistry.GetVersion	Get the provider version.
IProviderRegistry.InformOfProviderUpdate	Send an updated ProviderInfo object to the connected client.
INotificationProviderServiceAdminOnly.Connect	Connect to the notification provider.
INotificationProviderServiceAdminOnly.RaiseNotifications	Send persistent notifications to be raised on the provider.
INotificationProviderServiceAdminOnly.ClearNotifications	Send persistent notifications to be cleared on the provider.
INotificationProviderServiceAdminOnly.RequestNotificationChange	Request a change to the specified persistent notification.
INotificationProviderServiceAdminOnly.FireEvent	Send a one-time notification to be raised on the provider.

OperationContract	Description
INotificationProviderServiceAdminOnly.AddCategoryFilters	Indicate that the caller is interested in additional categories of notifications.
INotificationProviderServiceAdminOnly.RemoveCategoryFilters	Indicate that the caller is no longer interested in the specified categories.
INotificationProviderServiceAdminOnly.Disconnect	Disconnect from the notification provider.

3.6.5.1 IProviderRegistry.Disconnect

This operation signals the **ProviderRegistryService** that the connection is terminating.

```
<wsdl:operation msc:isInitiating="true" msc:isTerminating="true" name="Disconnect">
  <wsdl:input wsam:Action="http://tempuri.org/IProviderRegistryConnection/Disconnect"
  message="tns:IProviderRegistry Disconnect InputMessage" />
</wsdl:operation>
```

Upon receiving the **IProviderRegistry_Disconnect_InputMessage** request message, the protocol server is notified that the connection is terminating. In the event of a failure, an appropriate SOAP fault MUST be sent to the client as specified in section [2.2.2.1](#).

3.6.5.1.1 Messages

3.6.5.1.1.1 IProviderRegistry_Disconnect_InputMessage

This is the request for the **Disconnect** operation.

```
<wsdl:message name="IProviderRegistry Disconnect InputMessage">
  <wsdl:part name="parameters" element="tns:Disconnect" />
</wsdl:message>
```

This message MUST be sent with the following SOAP action.

<http://tempuri.org/IProviderRegistryConnection/Disconnect>

The body of the SOAP message MUST contain the **Disconnect** element.

3.6.5.1.2 Elements

3.6.5.1.2.1 Disconnect

This element specifies input values for the **Disconnect** operation. This element has no parameters.

```
<xss:element name="Disconnect">
  <xss:complexType>
    <xss:sequence />
  </xss:complexType>
</xss:element>
```

3.6.5.2 IProviderRegistry.Query

This operation returns a list of **ProviderInfo** data for a given contract.

```

<wsdl:operation msc:isInitiating="true" msc:isTerminating="false" name="Query">
  <wsdl:input wsam:Action="http://tempuri.org/IProviderRegistry/Query"
  message="tns:IProviderRegistry_Query_InputMessage" />
  <wsdl:output wsam:Action="http://tempuri.org/IProviderRegistry/QueryResponse"
  message="tns:IProviderRegistry_Query_OutputMessage" />
</wsdl:operation>

```

Upon receiving the **IProviderRegistry_Query_InputMessage** request message, the protocol server returns a list of **ProviderInfo** data for a given contract. Upon successful completion of the action, the server MUST respond with **IProviderRegistry_Query_OutputMessage**. In the event of a failure, an appropriate SOAP fault MUST be sent to the client as specified in section [2.2.1](#).

3.6.5.2.1 Messages

3.6.5.2.1.1 IProviderRegistry_Query_InputMessage

This is the request for the **Query** operation.

```

<wsdl:message name="IProviderRegistry_Query_InputMessage">
  <wsdl:part name="parameters" element="tns:Query" />
</wsdl:message>

```

This message MUST be sent with the following SOAP action.

<http://tempuri.org/IProviderRegistry/Query>

The body of the SOAP message MUST contain the **Query** element.

3.6.5.2.1.2 IProviderRegistry_Query_OutputMessage

This is the response for the **Query** operation.

```

<wsdl:message name="IProviderRegistry_Query_OutputMessage">
  <wsdl:part name="parameters" element="tns:QueryResponse" />
</wsdl:message>

```

This message MUST be sent with the following SOAP action.

<http://tempuri.org/IProviderRegistry/QueryResponse>

The body of the SOAP message MUST contain the **QueryResponse** element.

3.6.5.2.2 Elements

3.6.5.2.2.1 Query

This element specifies input values for the **Query** operation.

```

<xss:element name="Query">
  <xss:complexType>
    <xss:sequence>
      <xss:element minOccurs="0" name="specification" nillable="true"
      xmlns:q1="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.Common.ProviderFramework" type="q1:QuerySpecification" />

```

```

        </xs:sequence>
    </xs:complexType>
</xs:element>
```

specification: A **QuerySpecification** (section [2.2.4.6.4](#)) complex type that contains details for the specified providers.

3.6.5.2.2.2 QueryResponse

This element specifies output values for the **Query** operation.

```

<xs:element name="QueryResponse">
    <xs:complexType>
        <xs:sequence>
            <xs:element minOccurs="0" name="QueryResult" nillable="true"
                xmlns:q2="http://www.microsoft.com/2010/06/Microsoft.WindowsServerSolutions.Common.ProviderFr
                amework" type="q2:ArrayOfProviderInfo" />
        </xs:sequence>
    </xs:complexType>
</xs:element>
```

QueryResult: An array of **ProviderInfo** (section [2.2.4.6.2](#)) complex types that contains the results of the **Query** operation.

3.6.5.3 IProviderRegistry.QueryAll

This operation returns all registered providers.

```

<wsdl:operation msc:isInitiating="true" msc:isTerminating="false" name="QueryAll">
    <wsdl:input wsam:Action="http://tempuri.org/IProviderRegistry/QueryAll"
        message="tns:IProviderRegistry_QueryAll_InputMessage" />
    <wsdl:output wsam:Action="http://tempuri.org/IProviderRegistry/QueryAllResponse"
        message="tns:IProviderRegistry_QueryAll_OutputMessage" />
</wsdl:operation>
```

Upon receiving the **IProviderRegistry_QueryAll_InputMessage** request message, the protocol server returns the list of data for all providers. Upon successful completion of the action, the server MUST respond with **IProviderRegistry_QueryAll_OutputMessage**. In the event of a failure, an appropriate SOAP fault MUST be sent to the client as specified in section [2.2.2.1](#).

3.6.5.3.1 Messages

3.6.5.3.1.1 IProviderRegistry_QueryAll_InputMessage

This is the request for the **QueryAll** operation.

```

<wsdl:message name="IProviderRegistry_QueryAll_InputMessage">
    <wsdl:part name="parameters" element="tns:QueryAll" />
</wsdl:message>
```

This message MUST be sent with the following SOAP action.

<http://tempuri.org/IProviderRegistry/QueryAll>

The body of the SOAP message MUST contain the **QueryAll** element.

3.6.5.3.1.2 IProviderRegistry_QueryAll_OutputMessage

This is the response for the **QueryAll** operation.

```
<wsdl:message name="IProviderRegistry_QueryAll_OutputMessage">
  <wsdl:part name="parameters" element="tns:QueryAllResponse" />
</wsdl:message>
```

This message MUST be sent with the following SOAP action.

```
http://tempuri.org/IProviderRegistry/QueryAllResponse
```

The body of the SOAP message MUST contain the **QueryAllResponse** element.

3.6.5.3.2 Elements

3.6.5.3.2.1 QueryAll

This element specifies input values for the **QueryAll** operation. This element has no parameters.

```
<xs:element name="QueryAll">
  <xs:complexType>
    <xs:sequence />
  </xs:complexType>
</xs:element>
```

3.6.5.3.2.2 QueryAllResponse

This element specifies output values for the **QueryAll** operation.

```
<xs:element name="QueryAllResponse">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" name="QueryAllResult" nillable="true"
        xmlns:q3="http://www.microsoft.com/2010/06/Microsoft.WindowsServerSolutions.Common.ProviderFr
        amework" type="q3:ArrayOfProviderInfo" />
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

QueryAllResult: An array of **ProviderInfo** (section [2.2.4.6.2](#)) complex types that contains the results of the **QueryAll** operation.

3.6.5.4 IProviderRegistry.RequestProviderInfoUpdate

This operation requests an update for specific providers.

```
<wsdl:operation msc:isInitiating="true" msc:isTerminating="false"
  name="RequestProviderInfoUpdate">
  <wsdl:input wsam:Action="http://tempuri.org/IProviderRegistry/RequestProviderInfoUpdate"
    message="tns:IProviderRegistry_RequestProviderInfoUpdate_InputMessage" />
  <wsdl:output
    wsam:Action="http://tempuri.org/IProviderRegistry/RequestProviderInfoUpdateResponse"
    message="tns:IProviderRegistry_RequestProviderInfoUpdate_OutputMessage" />
```

```
</wsdl:operation>
```

Upon receiving the **IProviderRegistry_RequestProviderInfoUpdate_InputMessage** request message, the protocol server performs an update for specific providers. Upon successful completion of the action, the server MUST respond with **IProviderRegistry_RequestProviderInfoUpdate_OutputMessage**. In the event of a failure, an appropriate SOAP fault MUST be sent to the client as specified in section [2.2.2.1](#).

3.6.5.4.1 Messages

3.6.5.4.1.1 IProviderRegistry_RequestProviderInfoUpdate_InputMessage

This is the request for the **RequestProviderInfoUpdate** operation.

```
<wsdl:message name="IProviderRegistry_RequestProviderInfoUpdate_InputMessage">
  <wsdl:part name="parameters" element="tns:RequestProviderInfoUpdate" />
</wsdl:message>
```

This message MUST be sent with the following SOAP action.

```
http://tempuri.org/IProviderRegistry/RequestProviderInfoUpdate
```

The body of the SOAP message MUST contain the **RequestProviderInfoUpdate** element.

3.6.5.4.1.2 IProviderRegistry_RequestProviderInfoUpdate_OutputMessage

This is the response for the **RequestProviderInfoUpdate** operation.

```
<wsdl:message name="IProviderRegistry_RequestProviderInfoUpdate_OutputMessage">
  <wsdl:part name="parameters" element="tns:RequestProviderInfoUpdateResponse" />
</wsdl:message>
```

This message MUST be sent with the following SOAP action.

```
http://tempuri.org/IProviderRegistry/RequestProviderInfoUpdateResponse
```

The body of the SOAP message MUST contain the **RequestProviderInfoUpdateResponse** element.

3.6.5.4.2 Elements

3.6.5.4.2.1 RequestProviderInfoUpdate

This element specifies input values for the **RequestProviderInfoUpdate** operation.

```
<xs:element name="RequestProviderInfoUpdate">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" name="providersToUpdate" nillable="true"
        xmlns:q4="http://www.microsoft.com/2010/06/Microsoft.WindowsServerSolutions.Common.ProviderFr
        amework" type="q4:ArrayOfProviderInfo" />
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

3.6.5.4.2.2 RequestProviderInfoUpdateResponse

This element specifies output values for the **RequestProviderInfoUpdate** operation.

```
<xs:element name="RequestProviderInfoUpdateResponse">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" name="RequestProviderInfoUpdateResult" nillable="true"
        xmlns:q5="http://www.microsoft.com/2010/06/Microsoft.WindowsServerSolutions.Common.ProviderFr
        amework" type="q5:ArrayOfProviderInfo" />
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

RequestProviderInfoUpdateResult: An array of **ProviderInfo** (section [2.2.4.6.2](#)) complex types that contains the provider information update results.

3.6.5.5 IProviderRegistry.GetVersion

This operation returns the provider version number.

```
<wsdl:operation msc:isInitiating="true" msc:isTerminating="false" name="GetVersion">
  <wsdl:input wsam:Action="http://tempuri.org/IProviderRegistry/GetVersion"
    message="tns:IProviderRegistry_GetVersion_InputMessage" />
  <wsdl:output wsam:Action="http://tempuri.org/IProviderRegistry/GetVersionResponse"
    message="tns:IProviderRegistry_GetVersion_OutputMessage" />
</wsdl:operation>
```

Upon receiving the **IProviderRegistry_GetVersion_InputMessage** request message, the protocol server returns the version of the protocol server. Upon successful completion of the action, the server MUST respond with **IProviderRegistry_GetVersion_OutputMessage**. In the event of a failure, an appropriate SOAP fault MUST be sent to the client as specified in section [2.2.2.1](#).

3.6.5.5.1 Messages

3.6.5.5.1.1 IProviderRegistry_GetVersion_InputMessage

This is the request for the **GetVersion** operation.

```
<wsdl:message name="IProviderRegistry_GetVersion_InputMessage">
  <wsdl:part name="parameters" element="tns:GetVersion" />
</wsdl:message>
```

This message MUST be sent with the following SOAP action.

<http://temporg.uri/IProviderRegistry/GetVersion>

The body of the SOAP message MUST contain the **GetVersion** element.

3.6.5.5.1.2 IProviderRegistry_GetVersion_OutputMessage

This is the response for the **GetVersion** operation.

```
<wsdl:message name="IProviderRegistry_GetVersion_OutputMessage">
  <wsdl:part name="parameters" element="tns:GetVersionResponse" />
```

```
</wsdl:message>
```

This message MUST be sent with the following SOAP action.

```
http://tempuri.org/IProviderRegistry/GetVersionResponse
```

The body of the SOAP message MUST contain the **GetVersionResponse** element.

3.6.5.5.2 Elements

3.6.5.5.2.1 GetVersion

This element specifies input values for the **GetVersion** operation. This element has no parameters.

```
<xs:element name="GetVersion">
  <xs:complexType>
    <xs:sequence />
  </xs:complexType>
</xs:element>
```

3.6.5.5.2.2 GetVersionResponse

This element specifies output values for the **GetVersion** operation.

```
<xs:element name="GetVersionResponse">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" name="GetVersionResult" nillable="true" type="xs:string" />
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

GetVersionResult: A string that contains the version of the specified provider.

3.6.5.6 IProviderRegistry.InformOfProviderUpdate

This operation sends an updated **ProviderInfo** object to a connected client. This operation MUST NOT be invoked by the management client and MUST be ignored by the server.

```
<wsdl:operation msc:isInitiating="true" msc:isTerminating="false"
  name="InformOfProviderUpdate">
  <wsdl:output wsam:Action="http://tempuri.org/IProviderRegistry/InformOfProviderUpdate"
    message="tns:IProviderRegistry_InformOfProviderUpdate_OutputCallbackMessage" />
</wsdl:operation>
```

Upon receiving the **IProviderRegistry_InformOfProviderUpdate_OutputCallbackMessage** request message, the protocol client receives an updated **ProviderInfo** object. In the event of a failure, an appropriate SOAP fault MUST be sent to the client as specified in section [2.2.2.1](#).

3.6.5.6.1 Messages

3.6.5.6.1.1 IProviderRegistry_InformOfProviderUpdate_OutputCallbackMessage

This is the request for the **InformOfProviderUpdate** operation.

```
<wsdl:message name="IProviderRegistry_InformOfProviderUpdate_OutputCallbackMessage">
  <wsdl:part name="parameters" element="tns:InformOfProviderUpdate" />
</wsdl:message>
```

This message MUST be sent with the following SOAP action.

```
http://tempuri.org/IProviderRegistry/InformOfProviderUpdate
```

The body of the SOAP message MUST contain the **InformOfProviderUpdate** element.

3.6.5.6.2 Elements

3.6.5.6.2.1 InformOfProviderUpdate

This element specifies input values for the **InformOfProviderUpdate** operation.

```
<xs:element name="InformOfProviderUpdate">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" name="info" nillable="true"
        xmlns:q6="http://www.microsoft.com/2010/06/Microsoft.WindowsServerSolutions.Common.ProviderFr
        amework" type="q6:ProviderInfo" />
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

info: A **ProviderInfo** (section [2.2.4.6.2](#)) complex type that contains the updated information for the specified provider.

3.6.5.7 INotificationProviderServiceAdminOnly.Connect

This operation connects to the notification provider.

```
<wsdl:operation msc:isInitiating="true" msc:isTerminating="false" name="Connect">
  <wsdl:input
    wsam:Action="http://www.microsoft.com/WindowsServerSolutions/ProviderFramework/Notifications/
    3/2010/INotificationProviderService/Connect"
    message="tns:INotificationProviderServiceAdminOnly_Connect_InputMessage" />
</wsdl:operation>
```

Upon receiving the **INotificationProviderServiceAdminOnly_Connect_InputMessage** request message, the protocol server establishes a connection with the protocol client. In the event of a failure, an appropriate SOAP fault MUST be sent to the client as specified in section [2.2.2.1](#).

3.6.5.7.1 Messages

3.6.5.7.1.1 INotificationProviderServiceAdminOnly_Connect_InputMessage

This is the request for the **Connect** operation.

```
<wsdl:message name="INotificationProviderServiceAdminOnly_Connect_InputMessage">
  <wsdl:part name="parameters" element="tns:Connect" />
</wsdl:message>
```

This message MUST be sent with the following SOAP action.

```
http://www.microsoft.com/WindowsServerSolutions/ProviderFramework/Notifications/3/2010/INotificationProviderService/Connect
```

The body of the SOAP message MUST contain the **Connect** element.

3.6.5.7.2 Elements

3.6.5.7.2.1 Connect

This element specifies input values for the **Connect** operation.

```
<xs:element name="Connect">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" name="name" nillable="true" type="xs:string" />
      <xs:element minOccurs="0" name="categoryFilter" nillable="true"
        xmlns:q1="http://schemas.microsoft.com/2003/10/Serialization/Arrays" type="q1:ArrayOfstring"
      />
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

name: A string that contains the name of the remote provider.

categoryFilter: An array of string values representing the notification categories that the caller is interested in receiving.

3.6.5.8 INotificationProviderServiceAdminOnly.RaiseNotifications

This operation raises persistent notifications on the provider.

```
<wsdl:operation msc:isInitiating="false" msc:isTerminating="false" name="RaiseNotifications">
  <wsdl:input
    wsam:Action="http://www.microsoft.com/WindowsServerSolutions/ProviderFramework/Notifications/3/2010/INotificationProviderService/RaiseNotifications"
    message="tns:INotificationProviderServiceAdminOnly_RaiseNotifications_InputMessage" />
</wsdl:operation>
```

Upon receiving the **INotificationProviderServiceAdminOnly_RaiseNotifications_InputMessage** request message, the protocol server raises persistent notifications. In the event of a failure, an appropriate SOAP fault MUST be sent to the client as specified in section [2.2.1](#).

If any notification already exists, it will be replaced.

3.6.5.8.1 Messages

3.6.5.8.1.1 INotificationProviderServiceAdminOnly_RaiseNotifications_InputMessage

This is the request for the **RaiseNotifications** operation.

```
<wsdl:message name="INotificationProviderServiceAdminOnly_RaiseNotifications_InputMessage">
  <wsdl:part name="parameters" element="tns:RaiseNotifications" />
</wsdl:message>
```

This message MUST be sent with the following SOAP action.

```
http://www.microsoft.com/WindowsServerSolutions/ProviderFramework/Notifications/3/2010/INotificationProviderService/RaiseNotifications
```

The body of the SOAP message MUST contain the **RaiseNotifications** element.

3.6.5.8.2 Elements

3.6.5.8.2.1 RaiseNotifications

This element specifies input values for the **RaiseNotifications** operation.

```
<xs:element name="RaiseNotifications">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" name="newNotificationListChunk" nillable="true" type="xs:base64Binary" />
      <xs:element minOccurs="0" name="moreData" type="xs:boolean" />
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

newNotificationListChunk: A BASE64 binary that contains the persistent notifications to be raised, in serialized and chunked format.

moreData: A Boolean where True indicates that there are more chunks coming; otherwise, the value is FALSE.

3.6.5.9 INotificationProviderServiceAdminOnly.ClearNotifications

This operation clears persistent notifications on the provider.

```
<wsdl:operation msc:isInitiating="false" msc:isTerminating="false" name="ClearNotifications">
  <wsdl:input
    wsam:Action="http://www.microsoft.com/WindowsServerSolutions/ProviderFramework/Notifications/3/2010/INotificationProviderService/ClearNotifications"
    message="tns:INotificationProviderServiceAdminOnly_ClearNotifications_InputMessage" />
</wsdl:operation>
```

Upon receiving the **INotificationProviderServiceAdminOnly_ClearNotifications_InputMessage** request message, the protocol server clears persistent notifications. In the event of a failure, an appropriate SOAP fault MUST be sent to the client as specified in section [2.2.2.1](#).

3.6.5.9.1 Messages

3.6.5.9.1.1 INotificationProviderServiceAdminOnly_ClearNotifications_InputMessage

This is the request for the **ClearNotifications** operation.

```
<wsdl:message name="INotificationProviderServiceAdminOnly_ClearNotifications_InputMessage">
  <wsdl:part name="parameters" element="tns:ClearNotifications" />
</wsdl:message>
```

This message MUST be sent with the following SOAP action.

```
http://www.microsoft.com/WindowsServerSolutions/ProviderFramework/Notifications/3/2010/INotificationProviderService/ClearNotifications
```

The body of the SOAP message MUST contain the **ClearNotifications** element.

3.6.5.9.2 Elements

3.6.5.9.2.1 ClearNotifications

This element specifies input values for the **ClearNotifications** operation.

```
<xs:element name="ClearNotifications">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" name="oldNotificationListChunk" nillable="true" type="xs:base64Binary" />
      <xs:element minOccurs="0" name="moreData" type="xs:boolean" />
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

oldNotificationListChunk: A BASE64 binary that contains the persistent notifications to be raised, in serialized and chunked format.

moreData: A Boolean where TRUE indicates that there are more chunks coming; otherwise, the value is FALSE.

3.6.5.10 INotificationProviderServiceAdminOnly.RequestNotificationChange

This operation requests a change to the specified persistent notification.

```
<wsdl:operation msc:isInitiating="false" msc:isTerminating="false" name="RequestNotificationChange">
  <wsdl:input wsam:Action="http://www.microsoft.com/WindowsServerSolutions/ProviderFramework/Notifications/3/2010/INotificationProviderService/RequestNotificationChange" message="tns:INotificationProviderServiceAdminOnly_RequestNotificationChange_InputMessage" />
</wsdl:operation>
```

Upon receiving the **INotificationProviderServiceAdminOnly_RequestNotificationChange_InputMessage** request message, the protocol server changes the persistent notification. In the event of a failure, an appropriate SOAP fault MUST be sent to the client as specified in section [2.2.2.1](#).

3.6.5.10.1 Messages

3.6.5.10.1.1 INotificationProviderServiceAdminOnly_RequestNotificationChange_InputMessage

This is the request for the **RequestNotificationChange** operation.

```
<wsdl:message name="INotificationProviderServiceAdminOnly_RequestNotificationChange_InputMessage">
  <wsdl:part name="parameters" element="tns:RequestNotificationChange" />
```

```
</wsdl:message>
```

This message MUST be sent with the following SOAP action.

```
http://www.microsoft.com/WindowsServerSolutions/ProviderFramework/Notifications/3/2010/INotificationProviderService/RequestNotificationChange
```

The body of the SOAP message MUST contain the **RequestNotificationChange** element.

3.6.5.10.2 Elements

3.6.5.10.2.1 RequestNotificationChange

This element specifies input values for the **RequestNotificationChange** operation.

```
<xs:element name="RequestNotificationChange">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" name="changeRequestChunk" nillable="true"
        type="xs:base64Binary" />
      <xs:element minOccurs="0" name="moreData" type="xs:boolean" />
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

changeRequestChunk: A BASE64 binary that contains the persistent notifications to be raised, in serialized and chunked format.

moreData: A Boolean where TRUE indicates that there are more chunks coming; otherwise, the value is FALSE.

3.6.5.11 INotificationProviderServiceAdminOnly.FireEvent

This operation sends a one-time notification to be raised on the provider.

```
<wsdl:operation msc:isInitiating="false" msc:isTerminating="false" name="FireEvent">
  <wsdl:input
    wsam:Action="http://www.microsoft.com/WindowsServerSolutions/ProviderFramework/Notifications/
    3/2010/INotificationProviderService/FireEvent"
    message="tns:INotificationProviderServiceAdminOnly_FireEvent_InputMessage" />
</wsdl:operation>
```

Upon receiving the **INotificationProviderServiceAdminOnly_FireEvent_InputMessage** request message, the protocol server raises a one-time notification. In the event of a failure, the appropriate SOAP fault MUST be sent to the client as specified in section [2.2.2.1](#).

3.6.5.11.1 Messages

3.6.5.11.1.1 INotificationProviderServiceAdminOnly_FireEvent_InputMessage

This is the request for the **FireEvent** operation.

```
<wsdl:message name="INotificationProviderServiceAdminOnly_FireEvent_InputMessage">
  <wsdl:part name="parameters" element="tns:FireEvent" />
```

```
</wsdl:message>
```

This message MUST be sent with the following SOAP action.

```
http://www.microsoft.com/WindowsServerSolutions/ProviderFramework/Notifications/3/2010/INotificationProviderService/FireEvent
```

The body of the SOAP message MUST contain the **FireEvent** element.

3.6.5.11.2 Elements

3.6.5.11.2.1 FireEvent

This element specifies input values for the **FireEvent** operation.

```
<xs:element name="FireEvent">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" name="oneShotChunk" nillable="true" type="xs:base64Binary" />
      <xs:element minOccurs="0" name="moreData" type="xs:boolean" />
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

oneShotChunk: A BASE64 binary that contains the one-shot notification to be fired, in serialized and chunked format.

moreData: A Boolean where TRUE indicates that there are more chunks coming; otherwise, the value is FALSE.

3.6.5.12 INotificationProviderServiceAdminOnly.AddCategoryFilters

This operation indicates that the caller is interested in additional categories of filters.

```
<wsdl:operation msc:isInitiating="false" msc:isTerminating="false" name="AddCategoryFilters">
  <wsdl:input
    wsam:Action="http://www.microsoft.com/WindowsServerSolutions/ProviderFramework/Notifications/3/2010/INotificationProviderService/AddCategoryFilters"
    message="tns:INotificationProviderServiceAdminOnly AddCategoryFilters InputMessage" />
</wsdl:operation>
```

Upon receiving the

INotificationProviderServiceAdminOnly_AddCategoryFilters_InputMessage request message, the protocol server treats the caller as being interested in additional categories of notifications. In the event of a failure, the appropriate SOAP fault MUST be sent to the client as specified in section [2.2.2.1](#).

3.6.5.12.1 Messages

3.6.5.12.1.1 INotificationProviderServiceAdminOnly_AddCategoryFilters_InputMessage

This is the request for the **AddCategoryFilters** operation.

```
<wsdl:message name="INotificationProviderServiceAdminOnly_AddCategoryFilters_InputMessage">
  <wsdl:part name="parameters" element="tns:AddCategoryFilters" />
</wsdl:message>
```

This message MUST be sent with the following SOAP action.

```
http://www.microsoft.com/WindowsServerSolutions/ProviderFramework/Notifications/3/2010/INotificationProviderService/AddCategoryFilters
```

The body of the SOAP message MUST contain the **AddCategoryFilters** element.

3.6.5.12.2 Elements

3.6.5.12.2.1 AddCategoryFilters

This element specifies input values for the **AddCategoryFilters** operation.

```
<xs:element name="AddCategoryFilters">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" name="addFilters" nillable="true"
        xmlns:q2="http://schemas.microsoft.com/2003/10/Serialization/Arrays" type="q2:ArrayOfstring"
      />
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

addFilters: An array of string values representing the additional notification categories that the caller is interested in receiving.

3.6.5.13 INotificationProviderServiceAdminOnly.RemoveCategoryFilters

This operation indicates that the caller is no longer interested in the specified categories of Notifications.

```
<wsdl:operation msc:isInitiating="false" msc:isTerminating="false"
  name="RemoveCategoryFilters">
  <wsdl:input
    wsam:Action="http://www.microsoft.com/WindowsServerSolutions/ProviderFramework/Notifications/3/2010/INotificationProviderService/RemoveCategoryFilters"
    message="tns:INotificationProviderServiceAdminOnly_RemoveCategoryFilters_InputMessage" />
</wsdl:operation>
```

Upon receiving the **INotificationProviderServiceAdminOnly_RemoveCategoryFilters_InputMessage** request message, the protocol server treats the caller as no longer being interested in additional categories of notifications. In the event of a failure, the appropriate SOAP fault MUST be sent to the client as specified in section [2.2.2.1](#).

3.6.5.13.1 Messages

3.6.5.13.1.1 INotificationProviderServiceAdminOnly_RemoveCategoryFilters_InputMessage

This is the request for the **RemoveCategoryFilters** operation.

```

<wsdl:message
name="INotificationProviderServiceAdminOnly_RemoveCategoryFilters_InputMessage">
  <wsdl:part name="parameters" element="tns:RemoveCategoryFilters" />
</wsdl:message>

```

This message MUST be sent with the following SOAP action.

```
http://www.microsoft.com/WindowsServerSolutions/ProviderFramework/Notifications/3/2010/INotificationProviderService/RemoveCategoryFilters
```

The body of the SOAP message MUST contain the **RemoveCategoryFilters** element.

3.6.5.13.2 Elements

3.6.5.13.2.1 RemoveCategoryFilters

This element specifies input values for the **RemoveCategoryFilters** operation.

```

<xs:element name="RemoveCategoryFilters">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" name="removeFilters" nillable="true"
        xmlns:q3="http://schemas.microsoft.com/2003/10/Serialization/Arrays" type="q3:ArrayOfstring"
      />
    </xs:sequence>
  </xs:complexType>
</xs:element>

```

removeFilters: An array of string values representing the notification categories that the caller is no longer interested in receiving.

3.6.5.14 INotificationProviderServiceAdminOnly.Disconnect

This operation disconnects from the notification provider.

```

<wsdl:operation msc:isInitiating="false" msc:isTerminating="true" name="Disconnect">
  <wsdl:input
    wsam:Action="http://www.microsoft.com/WindowsServerSolutions/ProviderFramework/Notifications/3/2010/INotificationProviderService/Disconnect"
    message="tns:INotificationProviderServiceAdminOnly_Disconnect_InputMessage" />
</wsdl:operation>

```

Upon receiving the **INotificationProviderServiceAdminOnly_Disconnect_InputMessage** request message, the protocol server disconnects the caller. In the event of a failure, the appropriate SOAP fault MUST be sent to the client as specified in section [2.2.2.1](#).

3.6.5.14.1 Messages

3.6.5.14.1.1 INotificationProviderServiceAdminOnly_Disconnect_InputMessage

This is the request for the **Disconnect** operation.

```

<wsdl:message name="INotificationProviderServiceAdminOnly_Disconnect_InputMessage">
  <wsdl:part name="parameters" element="tns:Disconnect" />

```

```
</wsdl:message>
```

This message MUST be sent with the following SOAP action.

```
http://www.microsoft.com/WindowsServerSolutions/ProviderFramework/Notifications/3/2010/INotificationProviderService/Disconnect
```

The body of the SOAP message MUST contain the **Disconnect** element.

3.6.5.14.2 Elements

3.6.5.14.2.1 Disconnect

This element specifies input values for the **Disconnect** operation. This element has no parameters.

```
<xs:element name="Disconnect">
  <xs:complexType>
    <xs:sequence />
  </xs:complexType>
</xs:element>
```

3.6.6 Timer Events

None.

3.6.7 Other Local Events

None.

3.7 Addin Management Service Contract Details

None.

3.7.1 Abstract Data Model

None.

3.7.2 Timers

None.

3.7.3 Initialization

None.

3.7.4 Higher-Layer Triggered Events

None.

3.7.5 Message Processing Events and Sequencing Rules

The following table specifies the message processing events and sequencing rules that are associated with this specification.

OperationContract	Description
IAddInMetadata.GetPackagePath	Gets the server path where the add-in package will be copied.
IAddInMetadata.GetAddInIds	Gets the installed and uninstalled add-ins.
IAddInMetadata.GetAddInInformation	Gets details about the add-in.
IAddInMetadata.RegisterForChanges	Registers for changes to the add-in infrastructure.
IAddInMetadata.OperationInProgress	Checks whether there are any current installs or uninstalls that would block another operation.
IAddInMetadata.ChangeOccured	Callback triggered when the metadata for an add-in has changed.
IAddInMetadataInstall.CheckCredentials	Checks whether administrator credentials are valid by validating that the user is an administrator.
IAddInMetadataInstall.InstallAddIn	Installs the given add-in.
IAddInMetadataInstall.DownloadInstallAddIn	Downloads and installs the given add-in.
IAddInMetadataInstall.UninstallAddIn	Uninstalls the add-in with the given ID. There is no effect if there is no add-in with that ID.
IAddInMetadataInstall.CancelOperation	Cancels the current operation.
IAddInMetadataInstall.StartUploadAddinFile	Starts the upload of the add-in with the given ID.
IAddInMetadataInstall.UploadAddinFile	Uploads a chunk of a file.
IAddInMetadataInstall.EndUploadAddinFile	Ends the upload of a file.
IAddInMetadataInstall.ProgressChanged	Callback triggered when the progress for the given installation has changed, or the installation is complete.
IAddInMetadataInstall.ErrorOccured	Callback triggered when an error has occurred during installation.
IAddInMetadataInstall.RebootRequired	Callback triggered if the installation requires a reboot.
IAddInMetadataInstall.RestartDashboardRequired	Callback triggered if the installation requires a restart of the dashboard.

3.7.5.1 IAddInMetadata.GetPackagePath

This operation returns the server path where the add-in package will be copied.

```

<wsdl:operation name="GetPackagePath">
  <wsdl:input wsam:Action="http://tempuri.org/IAddInMetadata/GetPackagePath"
  message="tns:IAddInMetadata_GetPackagePath_InputMessage" />
  <wsdl:output wsam:Action="http://tempuri.org/IAddInMetadata/GetPackagePathResponse"
  message="tns:IAddInMetadata_GetPackagePath_OutputMessage" />
```

```
<wsdl:fault wsam:Action="http://tempuri.org/IAddInMetadata/GetPackagePathAddInErrorFault"
name="AddInErrorFault"
message="tns:IAddInMetadata_GetPackagePath_AddInErrorFault_FaultMessage" />
</wsdl:operation>
```

Upon receiving the **IAddInMetadata_GetPackagePath_InputMessage** request message, the protocol server is notified that the connection is terminating. Upon successful completion of the action, the server MUST respond with **IAddInMetadata_GetPackagePath_OutputMessage**. In the event of a failure, an appropriate SOAP fault MUST be sent to the client as specified in section [2.2.2.1](#).

3.7.5.1.1 Messages

3.7.5.1.1.1 IAddInMetadata_GetPackagePath_InputMessage

This is the request for the **GetPackagePath** operation.

```
<wsdl:message name="IAddInMetadata_GetPackagePath_InputMessage">
  <wsdl:part name="parameters" element="tns:GetPackagePath" />
</wsdl:message>
```

This message MUST be sent with the following SOAP action.

<http://tempuri.org/IAddInMetadata/GetPackagePath>

The body of the SOAP message MUST contain the **GetPackagePath** element.

3.7.5.1.1.2 IAddInMetadata_GetPackagePath_OutputMessage

This is the response for the **GetPackagePath** operation.

```
<wsdl:message name="IAddInMetadata_GetPackagePath_OutputMessage">
  <wsdl:part name="parameters" element="tns:GetPackagePathResponse" />
</wsdl:message>
```

This message MUST be sent with the following SOAP action.

<http://tempuri.org/IAddInMetadata/GetPackagePathResponse>

The body of the SOAP message MUST contain the **GetPackagePathResponse** element.

3.7.5.1.2 Elements

3.7.5.1.2.1 GetPackagePath

This element specifies input values for the **GetPackagePath** operation.

```
<xs:element name="GetPackagePath">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" name="packageId"
        xmlns:q1="http://schemas.microsoft.com/2003/10/Serialization/" type="q1:guid" />
    </xs:sequence>
  </xs:complexType>
```

```
</xs:element>
```

packageId: A GUID representing the package ID.

3.7.5.1.2.2 GetPackagePathResponse

This element specifies output values for the **GetPackagePath** operation.

```
<xs:element name="GetPackagePathResponse">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" name="GetPackagePathResult" type="xs:string" />
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

GetPackagePathResult: A string that contains the path for the package.

3.7.5.2 IAddInMetadata.GetAddInIds

This operation returns the installed and uninstalled add-ins.

```
<wsdl:operation name="GetAddInIds">
  <wsdl:input wsam:Action="http://tempuri.org/IAddInMetadata/GetAddInIds"
  message="tns:IAddInMetadata_GetAddInIds_InputMessage" />
  <wsdl:output wsam:Action="http://tempuri.org/IAddInMetadata/GetAddInIdsResponse"
  message="tns:IAddInMetadata_GetAddInIds_OutputMessage" />
  <wsdl:fault wsam:Action="http://tempuri.org/IAddInMetadata/GetAddInIdsAddInErrorFault"
  name="AddInErrorFault" message="tns:IAddInMetadata_GetAddInIds_AddInErrorFault_FaultMessage"
  />
</wsdl:operation>
```

Upon receiving the **IAddInMetadata_GetAddInIds_InputMessage** request message, the protocol server is notified that the connection is terminating. Upon successful completion of the action, the server MUST respond with **IAddInMetadata_GetAddInIds_OutputMessage**. In the event of a failure, an appropriate SOAP fault MUST be sent to the client as specified in section [2.2.2.1](#).

3.7.5.2.1 Messages

3.7.5.2.1.1 IAddInMetadata_GetAddInIds_InputMessage

This is the request for the **GetAddInIds** operation.

```
<wsdl:message name="IAddInMetadata_GetAddInIds_InputMessage">
  <wsdl:part name="parameters" element="tns:GetAddInIds" />
</wsdl:message>
```

This message MUST be sent with the following SOAP action.

```
http://tempuri.org/IAddInMetadata/GetAddInIds
```

The body of the SOAP message MUST contain the **GetAddInIds** element.

3.7.5.2.1.2 IAddInMetadata_GetAddInIds_OutputMessage

This is the response for the **GetAddInIds** operation.

```
<wsdl:message name="IAddInMetadata_GetAddInIds_OutputMessage">
  <wsdl:part name="parameters" element="tns:GetAddInIdsResponse" />
</wsdl:message>
```

This message MUST be sent with the following SOAP action.

```
http://tempuri.org/IAddInMetadata/GetAddInIdsResponse
```

The body of the SOAP message MUST contain the **GetAddInIdsResponse** element.

3.7.5.2.2 Elements

3.7.5.2.2.1 GetAddInIds

This element specifies input values for the **GetAddInIds** operation. This element has no parameters.

```
<xs:element name="GetAddInIds">
  <xs:complexType>
    <xs:sequence />
  </xs:complexType>
</xs:element>
```

3.7.5.2.2.2 GetAddInIdsResponse

This element specifies output values for the **GetAddInIds** operation.

```
<xs:element name="GetAddInIdsResponse">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" name="GetAddInIdsResult" nillable="true"
        xmlns:q2="http://schemas.datacontract.org/2004/07/System.Collections.ObjectModel"
        type="q2:ReadOnlyCollectionOfguid" />
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

GetAddInIdsResult: An array of GUIDs representing the AddIn IDs.

3.7.5.3 IAddInMetadata.GetAddInInformation

This operation returns details about an add-in.

```
<wsdl:operation name="GetAddInInformation">
  <wsdl:input wsam:Action="http://tempuri.org/IAddInMetadata/GetAddInInformation"
    message="tns:IAddInMetadata_GetAddInInformation_InputMessage" />
  <wsdl:output wsam:Action="http://tempuri.org/IAddInMetadata/GetAddInInformationResponse"
    message="tns:IAddInMetadata_GetAddInInformation_OutputMessage" />
  <wsdl:fault
    wsam:Action="http://tempuri.org/IAddInMetadata/GetAddInInformationAddInErrorFault"
    name="AddInErrorFault"
    message="tns:IAddInMetadata_GetAddInInformation_AddInErrorFault_FaultMessage" />
</wsdl:operation>
```

Upon receiving the **IAddInMetadata_GetAddInInformation_InputMessage** request message, the protocol server is notified that the connection is terminating. Upon successful completion of the action, the server MUST respond with **IAddInMetadata_GetAddInInformation_OutputMessage**. In the event of a failure, an appropriate SOAP fault MUST be sent to the client as specified in section [2.2.2.1](#).

3.7.5.3.1 Messages

3.7.5.3.1.1 IAddInMetadata_GetAddInInformation_InputMessage

This is the request for the **GetAddInInformation** operation.

```
<wsdl:message name="IAddInMetadata_GetAddInInformation_InputMessage">
  <wsdl:part name="parameters" element="tns:GetAddInInformation" />
</wsdl:message>
```

This message MUST be sent with the following SOAP action.

<http://tempuri.org/IAddInMetadata/GetAddInInformation>

The body of the SOAP message MUST contain the **GetAddInInformation** element.

3.7.5.3.1.2 IAddInMetadata_GetAddInInformation_OutputMessage

This is the response for the **GetAddInInformation** operation.

```
<wsdl:message name="IAddInMetadata_GetAddInInformation_OutputMessage">
  <wsdl:part name="parameters" element="tns:GetAddInInformationResponse" />
</wsdl:message>
```

This message MUST be sent with the following SOAP action.

<http://tempuri.org/IAddInMetadata/GetAddInInformationResponse>

The body of the SOAP message MUST contain the **GetAddInInformationResponse** element.

3.7.5.3.2 Elements

3.7.5.3.2.1 GetAddInInformation

This element specifies input values for the **GetAddInInformation** operation.

```
<xs:element name="GetAddInInformation">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" name="packageId"
        xmlns:q3="http://schemas.microsoft.com/2003/10/Serialization/" type="q3:guid" />
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

packageId: A GUID that represents the package Id.

3.7.5.3.2.2 GetAddInInformationResponse

This element specifies output values for the **GetAddInInformation** operation.

```
<xs:element name="GetAddInInformationResponse">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" name="GetAddInInformationResult" nillable="true"
        xmlns:q4="http://schemas.microsoft.com/WindowsServerSolutions/2010/03/Addins"
        type="q4:PackageInfo" />
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

GetAddInInformationResult: A **PackageInfo** (section [2.2.4.7.1](#)) complex type that contains the requested AddIn information.

3.7.5.4 IAddInMetadata.RegisterForChanges

This operation registers for changes to an add-in.

```
<wsdl:operation name="RegisterForChanges">
  <wsdl:input wsam:Action="http://tempuri.org/IAddInMetadata/RegisterForChanges"
    message="tns:IAddInMetadata_RegisterForChanges_InputMessage" />
  <wsdl:output wsam:Action="http://tempuri.org/IAddInMetadata/RegisterForChangesResponse"
    message="tns:IAddInMetadata_RegisterForChanges_OutputMessage" />
</wsdl:operation>
```

Upon receiving the **IAddInMetadata_RegisterForChanges_InputMessage** request message, the protocol server is notified that the connection is terminating. Upon successful completion of the action, the server MUST respond with **IAddInMetadata_RegisterForChanges_OutputMessage**. In the event of a failure, an appropriate SOAP fault MUST be sent to the client as specified in section [2.2.2.1](#).

3.7.5.4.1 Messages

3.7.5.4.1.1 IAddInMetadata_RegisterForChanges_InputMessage

This is the request for the **RegisterForChanges** operation.

```
<wsdl:message name="IAddInMetadata_RegisterForChanges_InputMessage">
  <wsdl:part name="parameters" element="tns:RegisterForChanges" />
</wsdl:message>
```

This message MUST be sent with the following SOAP action.

<http://tempuri.org/IAddInMetadata/RegisterForChanges>

The body of the SOAP message MUST contain the **RegisterForChanges** element.

3.7.5.4.1.2 IAddInMetadata_RegisterForChanges_OutputMessage

This is the response for the **RegisterForChanges** operation.

```
<wsdl:message name="IAddInMetadata_RegisterForChanges_OutputMessage">
  <wsdl:part name="parameters" element="tns:RegisterForChangesResponse" />
</wsdl:message>
```

This message MUST be sent with the following SOAP action.

```
http://tempuri.org/IAddInMetadata/RegisterForChangesResponse
```

The body of the SOAP message MUST contain the **RegisterForChangesResponse** element.

3.7.5.4.2 Elements

3.7.5.4.2.1 RegisterForChanges

This element specifies input values for the **RegisterForChanges** operation.

```
<xs:element name="RegisterForChanges">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" name="server" type="xs:boolean" />
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

server: A Boolean where TRUE indicates that server callbacks should be listened for; otherwise, the value is FALSE.

3.7.5.4.2.2 RegisterForChangesResponse

This element specifies output values for the **RegisterForChanges** operation. This element has no parameters.

```
<xs:element name="RegisterForChangesResponse">
  <xs:complexType>
    <xs:sequence />
  </xs:complexType>
</xs:element>
```

3.7.5.5 IAddInMetadata.OperationInProgress

This operation checks whether there are any active install or uninstall processes that would block another operation.

```
<wsdl:operation name="OperationInProgress">
  <wsdl:input wsam:Action="http://tempuri.org/IAddInMetadata/OperationInProgress"
  message="tns:IAddInMetadata_OperationInProgress_InputMessage" />
  <wsdl:output wsam:Action="http://tempuri.org/IAddInMetadata/OperationInProgressResponse"
  message="tns:IAddInMetadata_OperationInProgress_OutputMessage" />
  <wsdl:fault
  wsam:Action="http://tempuri.org/IAddInMetadata/OperationInProgressAddInErrorFault"
  name="AddInErrorFault"
  message="tns:IAddInMetadata_OperationInProgress_AddInErrorFault_FaultMessage" />
</wsdl:operation>
```

Upon receiving the **IAddInMetadata_OperationInProgress_InputMessage** request message, the protocol server is notified that the connection is terminating. Upon successful completion of the action, the server MUST respond with **IAddInMetadata_OperationInProgress_OutputMessage**. In the event of a failure, an appropriate SOAP fault MUST be sent to the client as specified in section [2.2.2.1](#).

3.7.5.5.1 Messages

3.7.5.5.1.1 IAddInMetadata_OperationInProgress_InputMessage

This is the request for the **OperationInProgress** operation.

```
<wsdl:message name="IAddInMetadata_OperationInProgress_InputMessage">
  <wsdl:part name="parameters" element="tns:OperationInProgress" />
</wsdl:message>
```

This message MUST be sent with the following SOAP action.

<http://tempuri.org/IAddInMetadata/OperationInProgress>

The body of the SOAP message MUST contain the **OperationInProgress** element.

3.7.5.5.1.2 IAddInMetadata_OperationInProgress_OutputMessage

This is the response for the **OperationInProgress** operation.

```
<wsdl:message name="IAddInMetadata_OperationInProgress_OutputMessage">
  <wsdl:part name="parameters" element="tns:OperationInProgressResponse" />
</wsdl:message>
```

This message MUST be sent with the following SOAP action.

<http://tempuri.org/IAddInMetadata/OperationInProgressResponse>

The body of the SOAP message MUST contain the **OperationInProgressResponse** element.

3.7.5.5.2 Elements

3.7.5.5.2.1 OperationInProgress

This element specifies input values for the **OperationInProgress** operation. This element has no parameters.

```
<xss:element name="OperationInProgress">
  <xss:complexType>
    <xss:sequence />
  </xss:complexType>
</xss:element>
```

3.7.5.5.2.2 OperationInProgressResponse

This element specifies output values for the **OperationInProgress** operation.

```
<xss:element name="OperationInProgressResponse">
  <xss:complexType>
    <xss:sequence>
      <xss:element minOccurs="0" name="OperationInProgressResult" type="xs:boolean" />
    </xss:sequence>
  </xss:complexType>
</xss:element>
```

OperationInProgressResult: A Boolean where TRUE indicates that the operation is in progress; otherwise, the value is FALSE.

3.7.5.6 IAddInMetadata.ChangeOccured

This callback operation is called when a change has occurred.

```
<wsdl:operation name="ChangeOccured">
  <wsdl:output wsam:Action="http://tempuri.org/IAddInMetadata/ChangeOccured"
    message="tns:IAddInMetadata_ChangeOccured_OutputCallbackMessage" />
</wsdl:operation>
```

3.7.5.6.1 Messages

3.7.5.6.1.1 IAddInMetadata_ChangeOccured_OutputCallbackMessage

This is the request for the **ChangeOccured** operation.

```
<wsdl:message name="IAddInMetadata_ChangeOccured_OutputCallbackMessage">
  <wsdl:part name="parameters" element="tns:ChangeOccured" />
</wsdl:message>
```

This message MUST be sent with the following SOAP action.

<http://tempuri.org/IAddInMetadata/ChangeOccured>

The body of the SOAP message MUST contain the **ChangeOccured** element.

3.7.5.6.2 Elements

3.7.5.6.2.1 ChangeOccured

This element specifies input values for the **ChangeOccured** operation. This element has no parameters.

```
<xss:element name="ChangeOccured">
  <xss:complexType>
    <xss:sequence />
  </xss:complexType>
</xss:element>
```

3.7.5.7 IAddInMetadataInstall.CheckCredentials

This operation validates that the user is an administrator.

```
<wsdl:operation name="CheckCredentials">
  <wsdl:input wsam:Action="http://tempuri.org/IAddInMetadataInstall/CheckCredentials"
    message="tns:IAddInMetadataInstall_CheckCredentials_InputMessage" />
  <wsdl:output
    wsam:Action="http://tempuri.org/IAddInMetadataInstall/CheckCredentialsResponse"
    message="tns:IAddInMetadataInstall_CheckCredentials_OutputMessage" />
  <wsdl:fault
    wsam:Action="http://tempuri.org/IAddInMetadataInstall/CheckCredentialsAddInErrorFault"
    name="AddInErrorFault"
    message="tns:IAddInMetadataInstall_CheckCredentials_AddInErrorFault_FaultMessage" />
```

```
</wsdl:operation>
```

Upon receiving the **IAddInMetadataInstall_CheckCredentials_InputMessage** request message, the protocol server is notified that the connection is terminating. Upon successful completion of the action, the server MUST respond with **IAddInMetadataInstall_CheckCredentials_OutputMessage**. In the event of a failure, an appropriate SOAP fault MUST be sent to the client as specified in section [2.2.2.1](#).

3.7.5.7.1 Messages

3.7.5.7.1.1 IAddInMetadataInstall_CheckCredentials_InputMessage

This is the request for the **CheckCredentials** operation.

```
<wsdl:message name="IAddInMetadataInstall_CheckCredentials_InputMessage">
  <wsdl:part name="parameters" element="tns:CheckCredentials" />
</wsdl:message>
```

This message MUST be sent with the following SOAP action.

```
http://tempuri.org/IAddInMetadataInstall/CheckCredentials
```

The body of the SOAP message MUST contain the **CheckCredentials** element.

3.7.5.7.1.2 IAddInMetadataInstall_CheckCredentials_OutputMessage

This is the response for the **CheckCredentials** operation.

```
<wsdl:message name="IAddInMetadataInstall_CheckCredentials_OutputMessage">
  <wsdl:part name="parameters" element="tns:CheckCredentialsResponse" />
</wsdl:message>
```

This message MUST be sent with the following SOAP action.

```
http://tempuri.org/IAddInMetadataInstall/CheckCredentialsResponse
```

The body of the SOAP message MUST contain the **CheckCredentialsResponse** element.

3.7.5.7.2 Elements

3.7.5.7.2.1 CheckCredentials

This element specifies input values for the **CheckCredentials** operation. This element has no parameters.

```
<xss:element name="CheckCredentials">
  <xss:complexType>
    <xss:sequence />
  </xss:complexType>
</xss:element>
```

3.7.5.7.2.2 CheckCredentialsResponse

This element specifies output values for the **CheckCredentials** operation. This element has no parameters.

```
<xs:element name="CheckCredentialsResponse">
  <xs:complexType>
    <xs:sequence />
  </xs:complexType>
</xs:element>
```

3.7.5.8 IAddInMetadataInstall.InstallAddIn

This operation installs the given add-in.

```
<wsdl:operation name="InstallAddIn">
  <wsdl:input wsam:Action="http://tempuri.org/IAddInMetadataInstall/InstallAddIn"
  message="tns:IAddInMetadataInstall InstallAddIn InputMessage" />
</wsdl:operation>
```

Upon receiving the **IAddInMetadataInstall_InstallAddIn_InputMessage** request message, the protocol server is notified that the connection is terminating. In the event of a failure, an appropriate SOAP fault MUST be sent to the client as specified in section [2.2.2.1](#).

3.7.5.8.1 Messages

3.7.5.8.1.1 IAddInMetadataInstall_InstallAddIn_InputMessage

This is the request for the **InstallAddIn** operation.

```
<wsdl:message name="IAddInMetadataInstall_InstallAddIn_InputMessage">
  <wsdl:part name="parameters" element="tns:InstallAddIn" />
</wsdl:message>
```

This message MUST be sent with the following SOAP action.

<http://tempuri.org/IAddInMetadataInstall/InstallAddIn>

The body of the SOAP message MUST contain the **InstallAddIn** element.

3.7.5.8.2 Elements

3.7.5.8.2.1 InstallAddIn

This element specifies input values for the **InstallAddIn** operation.

```
<xs:element name="InstallAddIn">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" name="addin" nillable="true"
      xmlns:q1="http://schemas.microsoft.com/WindowsServerSolutions/2010/03/Addins"
      type="q1:Package" />
      <xs:element minOccurs="0" name="installOnClients" nillable="true"
      xmlns:q2="http://schemas.microsoft.com/WindowsServerSolutions/2010/03/Addins"
      type="q2:ClientInstallFilter" />
    </xs:sequence>
  </xs:complexType>
```

```
</xs:element>
```

addin: A **Package** (section [2.2.4.7.3](#)) complex type that contains details for the AddIn to be installed.

installOnClients: A **ClientInstallFilter** (section [2.2.4.7.2](#)) complex type that contains the client installation filter details.

3.7.5.9 IAddInMetadataInstall.DownloadInstallAddIn

This operation downloads and installs the given add-in.

```
<wsdl:operation name="DownloadInstallAddIn">
  <wsdl:input wsam:Action="http://tempuri.org/IAddInMetadataInstall/DownloadInstallAddIn"
  message="tns:IAddInMetadataInstall_DownloadInstallAddIn_InputMessage" />
</wsdl:operation>
```

Upon receiving the **IAddInMetadataInstall_DownloadInstallAddIn_InputMessage** request message, the protocol server is notified that the connection is terminating. In the event of a failure, an appropriate SOAP fault MUST be sent to the client as specified in section [2.2.2.1](#).

3.7.5.9.1 Messages

3.7.5.9.1.1 IAddInMetadataInstall_DownloadInstallAddIn_InputMessage

This is the request for the **DownloadInstallAddIn** operation.

```
<wsdl:message name="IAddInMetadataInstall_DownloadInstallAddIn_InputMessage">
  <wsdl:part name="parameters" element="tns:DownloadInstallAddIn" />
</wsdl:message>
```

This message MUST be sent with the following SOAP action.

```
http://tempuri.org/IAddInMetadataInstall/DownloadInstallAddIn
```

The body of the SOAP message MUST contain the **DownloadInstallAddIn** element.

3.7.5.9.2 Elements

3.7.5.9.2.1 DownloadInstallAddIn

This element specifies input values for the **DownloadInstallAddIn** operation.

```
<xs:element name="DownloadInstallAddIn">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" name="address" nillable="true" type="xs:anyURI" />
      <xs:element minOccurs="0" name="certThumbprint" nillable="true" type="xs:string" />
      <xs:element minOccurs="0" name="expectedPackageId"
      xmlns:q3="http://schemas.microsoft.com/2003/10/Serialization/" type="q3:guid" />
      <xs:element minOccurs="0" name="installOnClients" nillable="true"
      xmlns:q4="http://schemas.microsoft.com/WindowsServerSolutions/2010/03/Addins"
      type="q4:ClientInstallFilter" />
    </xs:sequence>
  </xs:complexType>
```

```
</xs:element>
```

address: A URI that represents the address of the addin package.

certThumbprint: A string that contains the thumbprint of the certificate that the package is signed with.

expectedPackageId: A GUID that represents the ID of the expected package.

installOnClients: A **ClientInstallFilter** (section [2.2.4.7.2](#)) complex type that contains the client installation filter details.

3.7.5.10 IAddInMetadataInstall.UninstallAddIn

This operation uninstalls the given add-in. This operation has no effect if there is no add-in that matches the supplied ID.

```
<wsdl:operation name="UninstallAddIn">
  <wsdl:input wsam:Action="http://tempuri.org/IAddInMetadataInstall/UninstallAddIn"
    message="tns:IAddInMetadataInstall_UninstallAddIn_InputMessage" />
</wsdl:operation>
```

Upon receiving the **IAddInMetadataInstall_UninstallAddIn_InputMessage** request message, the protocol server is notified that the connection is terminating. In the event of a failure, an appropriate SOAP fault MUST be sent to the client as specified in section [2.2.2.1](#).

3.7.5.10.1 Messages

3.7.5.10.1.1 IAddInMetadataInstall_UninstallAddIn_InputMessage

This is the request for the **UninstallAddIn** operation.

```
<wsdl:message name="IAddInMetadataInstall UninstallAddIn InputMessage">
  <wsdl:part name="parameters" element="tns:UninstallAddIn" />
</wsdl:message>
```

This message MUST be sent with the following SOAP action.

```
http://tempuri.org/IAddInMetadataInstall/UninstallAddIn
```

The body of the SOAP message MUST contain the **UninstallAddIn** element.

3.7.5.10.2 Elements

3.7.5.10.2.1 UninstallAddIn

This element specifies input values for the **UninstallAddIn** operation.

```
<xs:element name="UninstallAddIn">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" name="id"
        xmlns:q5="http://schemas.microsoft.com/2003/10/Serialization/" type="q5:guid" />
    </xs:sequence>
```

```
</xs:complexType>
</xs:element>
```

id: A GUID that represents the AddIn ID.

3.7.5.11 IAddInMetadataInstall.CancelOperation

This operation cancels the current operation.

```
<wsdl:operation name="CancelOperation">
  <wsdl:input wsam:Action="http://tempuri.org/IAddInMetadataInstall/CancelOperation"
  message="tns:IAddInMetadataInstall_CancelOperation_InputMessage" />
</wsdl:operation>
```

Upon receiving the **IAddInMetadataInstall_CancelOperation_InputMessage** request message, the protocol server is notified that the connection is terminating. In the event of a failure, an appropriate SOAP fault MUST be sent to the client as specified in section [2.2.2.1](#).

3.7.5.11.1 Messages

3.7.5.11.1.1 IAddInMetadataInstall_CancelOperation_InputMessage

This is the request for the **CancelOperation** operation.

```
<wsdl:message name="IAddInMetadataInstall_CancelOperation_InputMessage">
  <wsdl:part name="parameters" element="tns:CancelOperation" />
</wsdl:message>
```

This message MUST be sent with the following SOAP action.

```
http://tempuri.org/IAddInMetadataInstall/CancelOperation
```

The body of the SOAP message MUST contain the **CancelOperation** element.

3.7.5.11.2 Elements

3.7.5.11.2.1 CancelOperation

This element specifies input values for the **CancelOperation** operation. This element has no parameters.

```
<xs:element name="CancelOperation">
  <xs:complexType>
    <xs:sequence />
  </xs:complexType>
</xs:element>
```

3.7.5.12 IAddInMetadataInstall.StartUploadAddinFile

This operation starts the upload of the add-in with the given ID value.

```
<wsdl:operation name="StartUploadAddinFile">
```

```

<wsdl:input wsam:Action="http://tempuri.org/IAddInMetadataInstall/StartUploadAddinFile"
message="tns:IAddInMetadataInstall_StartUploadAddinFile_InputMessage" />
<wsdl:output
wsam:Action="http://tempuri.org/IAddInMetadataInstall/StartUploadAddinFileResponse"
message="tns:IAddInMetadataInstall_StartUploadAddinFile_OutputMessage" />
<wsdl:fault
wsam:Action="http://tempuri.org/IAddInMetadataInstall/StartUploadAddinFileAddInErrorFault"
name="AddInErrorFault"
message="tns:IAddInMetadataInstall_StartUploadAddinFile_AddInErrorFault_FaultMessage" />
</wsdl:operation>

```

Upon receiving the **IAddInMetadataInstall_StartUploadAddinFile_InputMessage** request message, the protocol server is notified that the connection is terminating. Upon successful completion of the action, the server MUST respond with **IAddInMetadataInstall_StartUploadAddinFile_OutputMessage**. In the event of a failure, an appropriate SOAP fault MUST be sent to the client as specified in section [2.2.2.1](#).

3.7.5.12.1 Messages

3.7.5.12.1.1 IAddInMetadataInstall_StartUploadAddinFile_InputMessage

This is the request for the **StartUploadAddinFile** operation.

```

<wsdl:message name="IAddInMetadataInstall_StartUploadAddinFile_InputMessage">
  <wsdl:part name="parameters" element="tns:StartUploadAddinFile" />
</wsdl:message>

```

This message MUST be sent with the following SOAP action.

<http://tempuri.org/IAddInMetadataInstall/StartUploadAddinFile>

The body of the SOAP message MUST contain the **StartUploadAddinFile** element.

3.7.5.12.1.2 IAddInMetadataInstall_StartUploadAddinFile_OutputMessage

This is the response for the **StartUploadAddinFile** operation.

```

<wsdl:message name="IAddInMetadataInstall_StartUploadAddinFile_OutputMessage">
  <wsdl:part name="parameters" element="tns:StartUploadAddinFileResponse" />
</wsdl:message>

```

This message MUST be sent with the following SOAP action.

<http://tempuri.org/IAddInMetadataInstall/StartUploadAddinFileResponse>

The body of the SOAP message MUST contain the **StartUploadAddinFileResponse** element.

3.7.5.12.2 Elements

3.7.5.12.2.1 StartUploadAddinFile

This element specifies input values for the **StartUploadAddinFile** operation.

```

<xs:element name="StartUploadAddinFile">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" name="addinId"
        xmlns:q6="http://schemas.microsoft.com/2003/10/Serialization/" type="q6:guid" />
    </xs:sequence>
  </xs:complexType>
</xs:element>

```

addinId: A GUID that represents the AddIn ID.

3.7.5.12.2.2 StartUploadAddinFileResponse

This element specifies output values for the **StartUploadAddinFile** operation.

```

<xs:element name="StartUploadAddinFileResponse">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" name="StartUploadAddinFileResult"
        xmlns:q7="http://schemas.microsoft.com/2003/10/Serialization/" type="q7:guid" />
    </xs:sequence>
  </xs:complexType>
</xs:element>

```

StartUploadAddinFileResult: A GUID that represents the upload session ID.

3.7.5.13 IAddInMetadataInstall.UploadAddinFile

This operation uploads a chunk of an add-in file.

```

<wsdl:operation name="UploadAddinFile">
  <wsdl:input wsam:Action="http://tempuri.org/IAddInMetadataInstall/UploadAddinFile"
    message="tns:IAddInMetadataInstall_UploadAddinFile_InputMessage" />
  <wsdl:output wsam:Action="http://tempuri.org/IAddInMetadataInstall/UploadAddinFileResponse"
    message="tns:IAddInMetadataInstall_UploadAddinFile_OutputMessage" />
  <wsdl:fault
    wsam:Action="http://tempuri.org/IAddInMetadataInstall/UploadAddinFileAddInErrorFault"
    name="AddInErrorFault"
    message="tns:IAddInMetadataInstall_UploadAddinFile_AddInErrorFault_FaultMessage" />
</wsdl:operation>

```

Upon receiving the **IAddInMetadataInstall_UploadAddinFile_InputMessage** request message, the protocol server is notified that the connection is terminating. Upon successful completion of the action, the server MUST respond with **IAddInMetadataInstall_UploadAddinFile_OutputMessage**. In the event of a failure, an appropriate SOAP fault MUST be sent to the client as specified in section [2.2.2.1](#).

3.7.5.13.1 Messages

3.7.5.13.1.1 IAddInMetadataInstall_UploadAddinFile_InputMessage

This is the request for the **UploadAddinFile** operation.

```

<wsdl:message name="IAddInMetadataInstall_UploadAddinFile_InputMessage">
  <wsdl:part name="parameters" element="tns:UploadAddinFile" />
</wsdl:message>

```

This message MUST be sent with the following SOAP action.

```
http://tempuri.org/IAddInMetadataInstall/UploadAddinFile
```

The body of the SOAP message MUST contain the **UploadAddinFile** element.

3.7.5.13.1.2 IAddInMetadataInstall_UploadAddinFile_OutputMessage

This is the response for the **UploadAddinFile** operation.

```
<wsdl:message name="IAddInMetadataInstall_UploadAddinFile_OutputMessage">
  <wsdl:part name="parameters" element="tns:UploadAddinFileResponse" />
</wsdl:message>
```

This message MUST be sent with the following SOAP action.

```
http://tempuri.org/IAddInMetadataInstall/UploadAddinFileResponse
```

The body of the SOAP message MUST contain the **UploadAddinFileResponse** element.

3.7.5.13.2 Elements

3.7.5.13.2.1 UploadAddinFile

This element specifies input values for the **UploadAddinFile** operation.

```
<xss:element name="UploadAddinFile">
  <xss:complexType>
    <xss:sequence>
      <xss:element minOccurs="0" name="sessionId"
        xmlns:q8="http://schemas.microsoft.com/2003/10/Serialization/" type="q8:guid" />
      <xss:element minOccurs="0" name="data" nillable="true" type="xs:base64Binary" />
    </xss:sequence>
  </xss:complexType>
</xss:element>
```

sessionId: A GUID that represents the session ID.

data: A BASE64 binary that contains the AddIn data to be uploaded.

3.7.5.13.2.2 UploadAddinFileResponse

This element specifies output values for the **UploadAddinFile** operation. This element has no parameters.

```
<xss:element name="UploadAddinFileResponse">
  <xss:complexType>
    <xss:sequence />
  </xss:complexType>
</xss:element>
```

3.7.5.14 IAddInMetadataInstall.EndUploadAddinFile

This operation ends the upload of an add-in file.

```

<wsdl:operation name="EndUploadAddinFile">
  <wsdl:input wsam:Action="http://tempuri.org/IAddInMetadataInstall/EndUploadAddinFile"
  message="tns:IAddInMetadataInstall_EndUploadAddinFile_InputMessage" />
  <wsdl:output
  wsam:Action="http://tempuri.org/IAddInMetadataInstall/EndUploadAddinFileResponse"
  message="tns:IAddInMetadataInstall_EndUploadAddinFile_OutputMessage" />
  <wsdl:fault
  wsam:Action="http://tempuri.org/IAddInMetadataInstall/EndUploadAddinFileAddInErrorFault"
  name="AddInErrorFault"
  message="tns:IAddInMetadataInstall_EndUploadAddinFile_AddInErrorFault_FaultMessage" />
</wsdl:operation>

```

Upon receiving the **IAddInMetadataInstall_EndUploadAddinFile_InputMessage** request message, the protocol server is notified that the connection is terminating. Upon successful completion of the action, the server MUST respond with **IAddInMetadataInstall_EndUploadAddinFile_OutputMessage**. In the event of a failure, an appropriate SOAP fault MUST be sent to the client as specified in section [2.2.2.1](#).

3.7.5.14.1 Messages

3.7.5.14.1.1 IAddInMetadataInstall_EndUploadAddinFile_InputMessage

This is the request for the **EndUploadAddinFile** operation.

```

<wsdl:message name="IAddInMetadataInstall_EndUploadAddinFile_InputMessage">
  <wsdl:part name="parameters" element="tns:EndUploadAddinFile" />
</wsdl:message>

```

This message MUST be sent with the following SOAP action.

<http://tempuri.org/IAddInMetadataInstall/EndUploadAddinFile>

The body of the SOAP message MUST contain the **EndUploadAddinFile** element.

3.7.5.14.1.2 IAddInMetadataInstall_EndUploadAddinFile_OutputMessage

This is the response for the **EndUploadAddinFile** operation.

```

<wsdl:message name="IAddInMetadataInstall_EndUploadAddinFile_OutputMessage">
  <wsdl:part name="parameters" element="tns:EndUploadAddinFileResponse" />
</wsdl:message>

```

This message MUST be sent with the following SOAP action.

<http://tempuri.org/IAddInMetadataInstall/EndUploadAddinFileResponse>

The body of the SOAP message MUST contain the **EndUploadAddinFileResponse** element.

3.7.5.14.2 Elements

3.7.5.14.2.1 EndUploadAddinFile

This element specifies input values for the **EndUploadAddinFile** operation.

```

<xs:element name="EndUploadAddinFile">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" name="sessionId"
        xmlns:q9="http://schemas.microsoft.com/2003/10/Serialization/" type="q9:guid" />
    </xs:sequence>
  </xs:complexType>
</xs:element>

```

sessionId: A GUID that represents the session ID.

3.7.5.14.2.2 EndUploadAddinFileResponse

This element specifies output values for the **EndUploadAddinFile** operation. This element has no parameters.

```

<xs:element name="EndUploadAddinFileResponse">
  <xs:complexType>
    <xs:sequence />
  </xs:complexType>
</xs:element>

```

3.7.5.15 IAddInMetadataInstall.ProgressChanged

This callback operation is triggered when the progress for the given operation has changed, or the operation has completed.

```

<wsdl:operation name="ProgressChanged">
  <wsdl:output wsam:Action="http://tempuri.org/IAddInMetadataInstall/ProgressChanged"
    message="tns:IAddInMetadataInstall_ProgressChanged_OutputCallbackMessage" />
</wsdl:operation>

```

3.7.5.15.1 Messages

3.7.5.15.1.1 IAddInMetadataInstall_ProgressChanged_OutputCallbackMessage

This is the request for the **ProgressChanged** operation.

```

<wsdl:message name="IAddInMetadataInstall_ProgressChanged_OutputCallbackMessage">
  <wsdl:part name="parameters" element="tns:ProgressChanged" />
</wsdl:message>

```

This message MUST be sent with the following SOAP action.

<http://tempuri.org/IAddInMetadataInstall/ProgressChanged>

The body of the SOAP message MUST contain the **ProgressChanged** element.

3.7.5.15.2 Elements

3.7.5.15.2.1 ProgressChanged

This element specifies input values for the **ProgressChanged** operation.

```

<xs:element name="ProgressChanged">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" name="p" type="xs:int" />
      <xs:element minOccurs="0" name="completed" type="xs:boolean" />
    </xs:sequence>
  </xs:complexType>
</xs:element>

```

p: An integer representing the installation progress of the AddIn, from 0 to 100 percent.

completed: A Boolean where TRUE indicates that the installation was completed; otherwise, the value is FALSE.

3.7.5.16 IAddInMetadataInstall.ErrorOccured

This callback operation is triggered when an error has occurred during the operation.

```

<wsdl:operation name="ErrorOccured">
  <wsdl:output wsam:Action="http://tempuri.org/IAddInMetadataInstall/ErrorOccured"
  messages="tns:IAddInMetadataInstall_ErrorOccured_OutputCallbackMessage" />
</wsdl:operation>

```

3.7.5.16.1 Messages

3.7.5.16.1.1 IAddInMetadataInstall_ErrorOccured_OutputCallbackMessage

This is the request for the **ErrorOccured** operation.

```

<wsdl:message name="IAddInMetadataInstall_ErrorOccured_OutputCallbackMessage">
  <wsdl:part name="parameters" element="tns:ErrorOccured" />
</wsdl:message>

```

This message MUST be sent with the following SOAP action.

<http://tempuri.org/IAddInMetadataInstall/ErrorOccured>

The body of the SOAP message MUST contain the **ErrorOccured** element.

3.7.5.16.2 Elements

3.7.5.16.2.1 ErrorOccured

This element specifies input values for the **ErrorOccured** operation.

```

<xs:element name="ErrorOccured">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" name="messageId"
      xmlns:q10="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.AddinInfr
      astructure" type="q10:AddInError" />
    </xs:sequence>
  </xs:complexType>
</xs:element>

```

messageId: An **AddInError** (section [2.2.5.7.3](#)) string that contains the ID of the error message.

3.7.5.17 IAddInMetadataInstall.RebootRequired

This callback operation is triggered if the operation required a reboot.

```
<wsdl:operation name="RebootRequired">
  <wsdl:output wsam:Action="http://tempuri.org/IAddInMetadataInstall/RebootRequired"
    message="tns:IAddInMetadataInstall_RebootRequired_OutputCallbackMessage" />
</wsdl:operation>
```

3.7.5.17.1 Messages

3.7.5.17.1.1 IAddInMetadataInstall_RebootRequired_OutputCallbackMessage

This is the request for the **RebootRequired** operation.

```
<wsdl:message name="IAddInMetadataInstall_RebootRequired_OutputCallbackMessage">
  <wsdl:part name="parameters" element="tns:RebootRequired" />
</wsdl:message>
```

This message MUST be sent with the following SOAP action.

<http://tempuri.org/IAddInMetadataInstall/RebootRequired>

The body of the SOAP message MUST contain the **RebootRequired** element.

3.7.5.17.2 Elements

3.7.5.17.2.1 RebootRequired

This element specifies input values for the **RebootRequired** operation. This element has no parameters.

```
<xss:element name="RebootRequired">
  <xss:complexType>
    <xss:sequence />
  </xss:complexType>
</xss:element>
```

3.7.5.18 IAddInMetadataInstall.RestartDashboardRequired

This callback operation is triggered if the operation required a restart of the dashboard.

```
<wsdl:operation name="RestartDashboardRequired">
  <wsdl:output
    wsam:Action="http://tempuri.org/IAddInMetadataInstall/RestartDashboardRequired"
    message="tns:IAddInMetadataInstall_RestartDashboardRequired_OutputCallbackMessage" />
</wsdl:operation>
```

3.7.5.18.1 Messages

3.7.5.18.1.1 IAddInMetadataInstall_RestartDashboardRequired_OutputCallbackMessage

This is the request for the **RestartDashboardRequired** operation.

```
<wsdl:message name="IAddInMetadataInstall_RestartDashboardRequired_OutputCallbackMessage">
  <wsdl:part name="parameters" element="tns:RestartDashboardRequired" />
</wsdl:message>
```

This message MUST be sent with the following SOAP action.

```
http://tempuri.org/IAddInMetadataInstall/RerstartDashboardRequired
```

The body of the SOAP message MUST contain the **RestartDashboardRequired** element.

3.7.5.18.2 Elements

3.7.5.18.2.1 RestartDashboardRequired

This element specifies input values for the **RestartDashboardRequired** operation. This element has no parameters.

```
<xs:element name="RestartDashboardRequired">
  <xs:complexType>
    <xs:sequence />
  </xs:complexType>
</xs:element>
```

3.7.6 Timer Events

None.

3.7.7 Other Local Events

None.

3.8 Network Service Contract Details

3.8.1 Abstract Data Model

None.

3.8.2 Timers

None.

3.8.3 Initialization

None.

3.8.4 Higher-Layer Triggered Events

None.

3.8.5 Message Processing Events and Sequencing Rules

OperationContract	Description
INetworkingService.UpdateClientAddress	Called by the client to notify the server of the client's current IP address.
INetworkingService.RemoveClient	Called when the client is permanently removed in the dashboard. Requires administrator access and can only be called locally.
INetworkingService.Ping	Used to implement IsServerOnline API.
INetworkingService.GetVPNServerSetting	Used to retrieve VPN server settings.
INetworkingService.GetVirtualNetworkSettings	Used to retrieve Azure Virtual Network settings.

3.8.5.1 INetworkingService.UpdateClientAddress

This operation notifies the server of the client's current IP address.

```
<wsdl:operation name="UpdateClientAddress">
  <wsdl:input wsam:Action="http://tempuri.org/INetworkingService/UpdateClientAddress"
    message="tns:INetworkingService_UpdateClientAddress_InputMessage" />
  <wsdl:output
    wsam:Action="http://tempuri.org/INetworkingService/UpdateClientAddressResponse"
    message="tns:INetworkingService_UpdateClientAddress_OutputMessage" />
  <wsdl:fault
    wsam:Action="http://tempuri.org/INetworkingService/UpdateClientAddressArgumentExceptionFault"
    name="ArgumentExceptionFault"
    message="tns:INetworkingService_UpdateClientAddress_ArgumentExceptionFault_FaultMessage" />
</wsdl:operation>
```

Upon receiving the **INetworkingService_UpdateClientAddress_InputMessage** request message, the protocol server is notified that the connection is terminating. Upon successful completion of the action, the server MUST respond with

INetworkingService_UpdateClientAddress_OutputMessage. In the event of a failure, an appropriate SOAP fault MUST be sent to the client as specified in section [2.2.2.1](#).

3.8.5.1.1 Messages

3.8.5.1.1.1 INetworkingService_UpdateClientAddress_InputMessage

This is the request for the **UpdateClientAddress** operation.

```
<wsdl:message name="INetworkingService_UpdateClientAddress_InputMessage">
  <wsdl:part name="parameters" element="tns:UpdateClientAddress" />
</wsdl:message>
```

This message MUST be sent with the following SOAP action.

<http://tempuri.org/INetworkingService/UpdateClientAddress>

The body of the SOAP message MUST contain the **UpdateClientAddress** element.

3.8.5.1.1.2 INetworkingService_UpdateClientAddress_OutputMessage

This is the response for the **UpdateClientAddress** operation.

```
<wsdl:message name="IProviderRegistry_UpdateClientAddress_OutputMessage">
  <wsdl:part name="parameters" element="tns:UpdateClientAddressResponse" />
</wsdl:message>
```

This message MUST be sent with the following SOAP action.

<http://tempuri.org/IProviderRegistry/UpdateClientAddressResponse>

The body of the SOAP message MUST contain the **UpdateClientAddressResponse** element.

3.8.5.1.2 Elements

3.8.5.1.2.1 UpdateClientAddress

This element specifies input values for the **UpdateClientAddress** operation.

```
<xs:element name="UpdateClientAddress">
  <xs:complexType>
    <xs:element minOccurs="0" name="client" nillable="true" type="xs:string" />
  </xs:complexType>
</xs:element>
```

client: A string that contains the address of the specified client.

3.8.5.1.2.2 UpdateClientAddressResponse

This element specifies output values for the **UpdateClientAddress** operation. This element has no parameters.

```
<xs:element name="UpdateClientAddressResponse">
  <xs:complexType>
    <xs:sequence />
  </xs:complexType>
</xs:element>
```

3.8.5.2 INetworkingService.RemoveClient

This operation permanently removes a client from the dashboard. This operation requires administrator access and can only be called locally.

```
<wsdl:operation name="RemoveClient">
  <wsdl:input wsam:Action="http://tempuri.org/INetworkingService/RemoveClient"
  message="tns:INetworkingService_RemoveClient_InputMessage" />
  <wsdl:output wsam:Action="http://tempuri.org/INetworkingService/RemoveClientResponse"
  message="tns:INetworkingService_RemoveClient_OutputMessage" />
```

```

<wsdl:fault
  wsam:Action="http://tempuri.org/INetworkingService/RemoveClientArgumentExceptionFault"
  name="ArgumentExceptionFault"
  message="tns:INetworkingService_RemoveClient_ArgumentExceptionFault_FaultMessage" />
</wsdl:operation>

```

Upon receiving the **INetworkingService_RemoveClient_InputMessage** request message, the protocol server is notified that the connection is terminating. Upon successful completion of the action, the server MUST respond with **INetworkingService_RemoveClient_OutputMessage**. In the event of a failure, an appropriate SOAP fault MUST be sent to the client as specified in section [2.2.2.1](#).

3.8.5.2.1 Messages

3.8.5.2.1.1 INetworkingService_RemoveClient_InputMessage

This is the request for the **RemoveClient** operation.

```

<wsdl:message name="INetworkingService_RemoveClient_InputMessage">
  <wsdl:part name="parameters" element="tns:RemoveClient" />
</wsdl:message>

```

This message MUST be sent with the following SOAP action.

<http://tempuri.org/INetworkingService/RemoveClient>

The body of the SOAP message MUST contain the **RemoveClient** element.

3.8.5.2.1.2 INetworkingService_RemoveClient_OutputMessage

This is the response for the **RemoveClient** operation.

```

<wsdl:message name="IProviderRegistry_RemoveClient_OutputMessage">
  <wsdl:part name="parameters" element="tns:RemoveClientResponse" />
</wsdl:message>

```

This message MUST be sent with the following SOAP action.

<http://tempuri.org/IProviderRegistry/RemoveClientResponse>

The body of the SOAP message MUST contain the **RemoveClientResponse** element.

3.8.5.2.2 Elements

3.8.5.2.2.1 RemoveClient

This element specifies input values for the **RemoveClient** operation.

```

<xss:element name="RemoveClient">
  <xss:complexType>
    <xss:element minOccurs="0" name="client" nillable="true" type="xss:string" />
  </xss:complexType>
</xss:element>

```

client: A string that contains the address of the specified client.

3.8.5.2.2.2 RemoveClientResponse

This element specifies output values for the **RemoveClient** operation. This element has no parameters.

```
<xs:element name="RemoveClientResponse">
  <xs:complexType>
    <xs:sequence />
  </xs:complexType>
</xs:element>
```

3.8.5.3 INetworkingService.Ping

This operation is used to implement the **IsServerOnline** API.

```
<wsdl:operation name="Ping">
  <wsdl:input wsam:Action="http://tempuri.org/INetworkingService/Ping"
  message="tns:INetworkingService_Ping_InputMessage" />
  <wsdl:output wsam:Action="http://tempuri.org/INetworkingService/PingResponse"
  message="tns:INetworkingService_Ping_OutputMessage" />
</wsdl:operation>
```

Upon receiving the **INetworkingService_Ping_InputMessage** request message, the protocol server is notified that the connection is terminating. Upon successful completion of the action, the server MUST respond with **INetworkingService_Ping_OutputMessage**. In the event of a failure, an appropriate SOAP fault MUST be sent to the client as specified in section [2.2.2.1](#).

3.8.5.3.1 Messages

3.8.5.3.1.1 INetworkingService_Ping_InputMessage

This is the request for the **Ping** operation.

```
<wsdl:message name="INetworkingService_Ping_InputMessage">
  <wsdl:part name="parameters" element="tns:Ping" />
</wsdl:message>
```

This message MUST be sent with the following SOAP action.

<http://tempuri.org/INetworkingService/Ping>

The body of the SOAP message MUST contain the **Ping** element.

3.8.5.3.1.2 INetworkingService_Ping_OutputMessage

This is the response for the **Ping** operation.

```
<wsdl:message name="IProviderRegistry_Ping_OutputMessage">
  <wsdl:part name="parameters" element="tns:PingResponse" />
</wsdl:message>
```

This message MUST be sent with the following SOAP action.

<http://tempuri.org/IProviderRegistry/PingResponse>

The body of the SOAP message MUST contain the **PingResponse** element.

3.8.5.3.2 Elements

3.8.5.3.2.1 Ping

This element specifies input values for the **Ping** operation. This element has no parameters.

```
<xs:element name="Ping">
  <xs:complexType>
    <xs:sequence />
  </xs:complexType>
</xs:element>
```

3.8.5.3.2.2 PingResponse

This element specifies output values for the **Ping** operation. This element has no parameters.

```
<xs:element name="PingResponse">
  <xs:complexType>
    <xs:sequence />
  </xs:complexType>
</xs:element>
```

3.8.5.4 INetworkingService.GetVPNServerSetting

This operation returns the server's VPN settings.

```
<wsdl:operation name="GetVPNServerSetting">
  <wsdl:input wsam:Action="http://tempuri.org/INetworkingService/GetVPNServerSetting"
  message="tns:INetworkingService_GetVPNServerSetting_InputMessage" />
  <wsdl:output
  wsam:Action="http://tempuri.org/INetworkingService/GetVPNServerSettingResponse"
  message="tns:INetworkingService GetVPNServerSetting OutputMessage" />
</wsdl:operation>
```

Upon receiving the **INetworkingService_GetVPNServerSetting_InputMessage** request message, the protocol server is notified that the connection is terminating. Upon successful completion of the action, the server MUST respond with

INetworkingService_GetVPNServerSetting_OutputMessage. In the event of a failure, an appropriate SOAP fault MUST be sent to the client as specified in section [2.2.2.1](#).

3.8.5.4.1 Messages

3.8.5.4.1.1 INetworkingService_GetVPNServerSetting_InputMessage

This is the request for the **GetVPNServerSetting** operation.

```
<wsdl:message name="INetworkingService_GetVPNServerSetting_InputMessage">
  <wsdl:part name="parameters" element="tns:GetVPNServerSetting" />
</wsdl:message>
```

This message MUST be sent with the following SOAP action.

```
http://tempuri.org/INetworkingService/GetVPNServerSetting
```

The body of the SOAP message MUST contain the **GetVPNServerSetting** element.

3.8.5.4.1.2 INetworkingService_GetVPNServerSetting_OutputMessage

This is the response for the **GetVPNServerSetting** operation.

```
<wsdl:message name="IProviderRegistry_GetVPNServerSetting_OutputMessage">
  <wsdl:part name="parameters" element="tns:GetVPNServerSettingResponse" />
</wsdl:message>
```

This message MUST be sent with the following SOAP action.

```
http://tempuri.org/IProviderRegistry/GetVPNServerSettingResponse
```

The body of the SOAP message MUST contain the **GetVPNServerSettingResponse** element.

3.8.5.4.2 Elements

3.8.5.4.2.1 GetVPNServerSetting

This element specifies input values for the **GetVPNServerSetting** operation. This element has no parameters.

```
<xs:element name="GetVPNServerSetting">
  <xs:complexType>
    <xs:sequence />
  </xs:complexType>
</xs:element>
```

3.8.5.4.2.2 GetVPNServerSettingResponse

This element specifies output values for the **GetVPNServerSetting** operation.

```
<xs:element name="GetVPNServerSettingResponse">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" name="GetVPNServerSettingResult" nillable="true"
        xmlns:q1="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.RemoteAcce
        ss" type="q1:VPNSetting" />
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

GetVPNServerSettingResult: A **VPNSetting** (section [2.2.4.8.1](#)) complex type that contains the requested VPN server settings details.

3.8.5.5 INetworkService.GetVirtualNetworkSettings

This operation returns the server's Azure Virtual Network settings (section [2.2.4.8.2](#)).

```

<wsdl:operation name="GetVirtualNetworkSettings">
  <wsdl:input wsam:Action="http://tempuri.org/INetworkingService/GetVirtualNetworkSettings"
  message="tns:INetworkingService_GetVirtualNetworkSettings_InputMessage" />
  <wsdl:output wsam:Action="http://tempuri.org/INetworkingService/GetVirtualNetworkSettings"
  message="tns:INetworkingService_GetVirtualNetworkSettings_OutputMessage" />
</wsdl:operation>

```

Upon receiving the **INetworkingService_GetVirtualNetworkSettings_InputMessage** request message, the protocol server is notified that the connection is terminating. Upon successful completion of the action, the server MUST respond with **INetworkingService_GetVirtualNetworkSettings_OutputMessage**. In the event of a failure, an appropriate SOAP fault MUST be sent to the client as specified in section [2.2.1](#).

3.8.5.5.1 Messages

3.8.5.5.1.1 INetworkService_GetVirtualNetworkSettings_InputMessage

This is the request for the **GetVirtualNetworkSettings** operation.

```

<wsdl:message name="INetworkingService GetVirtualNetworkSettings InputMessage">
  <wsdl:part name="parameters" element="tns:GetVirtualNetworkSettings" />
</wsdl:message>

```

This message MUST be sent with the following SOAP action.

```
http://tempuri.org/INetworkingService/GetVirtualNetworkSettings
```

The body of the SOAP message MUST contain the **GetVirtualNetworkSettings** element.

3.8.5.5.1.2 INetworkService_GetVirtualNetworkSettings_OutputMessage

This is the response for the **GetVirtualNetworkSettings** operation.

```

<wsdl:message name="IProviderRegistry_GetVirtualNetworkSettings_OutputMessage">
  <wsdl:part name="parameters" element="tns:GetVirtualNetworkSettingsResponse" />
</wsdl:message>

```

This message MUST be sent with the following SOAP action.

```
http://tempuri.org/IProviderRegistry/GetVirtualNetworkSettingsResponse
```

The body of the SOAP message MUST contain the **GetVirtualNetworkSettingsResponse** element.

3.8.5.5.2 Elements

3.8.5.5.2.1 GetVirtualNetworkSettings

This element specifies input values for the **GetVirtualNetworkSettings** operation. This element has no parameters.

```

<xs:element name="GetVirtualNetworkSettings">
  <xs:complexType>
    <xs:sequence />

```

```
</xs:complexType>
</xs:element>
```

3.8.5.5.2.2 GetVirtualNetworkSettingsResponse

This element specifies output values for the **GetVirtualNetworkSettings** operation.

```
<xs:element name="GetVirtualNetworkSettingsResponse">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" name=" GetVirtualNetworkSettingsResult" nillable="true"
        xmlns:q1="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.RemoteAccess"
        type="q1:VirtualNetworkSettings" />
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

GetVirtualNetworkSettingsResult: A **VirtualNetworkSettings** (section [2.2.4.8.2](#)) complex type that contains the requested virtual network settings details.

3.8.6 Timer Events

None.

3.8.7 Other Local Events

None.

3.9 Domain Infrastructure Service Contract Details

3.9.1 Abstract Data Model

None.

3.9.2 Timers

None.

3.9.3 Initialization

None.

3.9.4 Higher-Layer Triggered Events

None.

3.9.5 Message Processing Events and Sequencing Rules

OperationContract	Description
IDomainMaintenanceManager.SetCredentials	Set and validate user credentials for current domain configuration. This API is intended for repair scenarios when credentials provided previously become stale (for example, a password

OperationContract	Description
	has changed) and need to be updated before domain maintenance can continue successfully.
IDomainMaintenanceManager.ValidateCredentials	Validate the current user credentials.
IDomainMaintenanceManager.UpdateDnsRecords	Update DNS records for the domain.
IDomainMaintenanceManager.QueryAddressFromDNS	Determine the public IP address (IPv4 or IPv6) corresponding to the currently configured domain name using public DNS infrastructure.
IDomainMaintenanceManager.QueryAddressFromProvider	Query the active maintenance provider for the server's public IP address.
IDomainMaintenanceManager.TestConnection	Verify whether the connection to the current provider's backend service can be established. This method is used for diagnostics only, as no guarantees of network/service conditions can be made immediately after this method returns.
IDomainMaintenanceManager.GetDomainState	Query the active maintenance provider for current domain state.
IDomainMaintenanceManager.GetCertificateState	Query the active maintenance provider for current certificate state.
IDomainMaintenanceManager.GetDomainNameConfiguration	Return the currently active domain name configuration.
IDomainMaintenanceManager.GetDynamicDNSInfo	Return data about dynamic DNS updates (the time of the most recent successful update, for example).
IDomainMaintenanceManager.GetSettings	Return current domain manager settings.

3.9.5.1 IDomainMaintenanceManager.SetCredentials

This operation sets and validates user credentials for the current domain configuration.

```

<wsdl:operation name="SetCredentials">
  <wsdl:input wsam:Action="http://tempuri.org/IDomainMaintenanceManager/SetCredentials"
  message="tns:IDomainMaintenanceManager_SetCredentials_InputMessage" />
  <wsdl:output
  wsam:Action="http://tempuri.org/IDomainMaintenanceManager/SetCredentialsResponse"
  message="tns:IDomainMaintenanceManager_SetCredentials_OutputMessage" />
  <wsdl:fault
  wsam:Action="http://tempuri.org/IDomainMaintenanceManager/SetCredentialsDomainManagerFaultFault"
  name="DomainManagerFaultFault"
  message="tns:IDomainMaintenanceManager_SetCredentials_DomainManagerFaultFault_FaultMessage"
  />
</wsdl:operation>
```

Upon receiving the **IDomainMaintenanceManager_SetCredentials_InputMessage** request message, the protocol server sets and validates user credentials. Upon successful completion of the action, the server MUST respond with

IDomainMaintenanceManager_SetCredentials_OutputMessage. In the event of a failure, an appropriate SOAP fault MUST be sent to the client as specified in section [2.2.2.1](#).

3.9.5.1.1 Messages

3.9.5.1.1.1 IDomainMaintenanceManager_SetCredentials_InputMessage

This is the request for the **SetCredentials** operation.

```
<wsdl:message name="IDomainMaintenanceManager_SetCredentials_InputMessage">
  <wsdl:part name="parameters" element="tns:SetCredentials" />
</wsdl:message>
```

This message MUST be sent with the following SOAP action.

<http://tempuri.org/IDomainMaintenanceManager/SetCredentials>

The body of the SOAP message MUST contain the **SetCredentials** element.

3.9.5.1.1.2 IDomainMaintenanceManager_SetCredentials_OutputMessage

This is the response for the **SetCredentials** operation.

```
<wsdl:message name="IDomainMaintenanceManager_SetCredentials_OutputMessage">
  <wsdl:part name="parameters" element="tns:SetCredentialsResponse" />
</wsdl:message>
```

This message MUST be sent with the following SOAP action.

<http://tempuri.org/IDomainMaintenanceManager/SetCredentialsResponse>

The body of the SOAP message MUST contain the **SetCredentialsResponse** element.

3.9.5.1.2 Elements

3.9.5.1.2.1 SetCredentials

This element specifies input values for the **SetCredentials** operation.

```
<xs:element name="SetCredentials">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" name="SetCredentialsResult" type="xs:boolean" />
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

SetCredentialsResult: A Boolean where TRUE indicates that the credentials were set successfully; otherwise, the value is FALSE.

3.9.5.1.2.2 SetCredentialsResponse

This element specifies output values for the **SetCredentials** operation.

```
<xs:element name="SetCredentialsResponse">
  <xs:complexType>
```

```

<xs:sequence>
    <xs:element minOccurs="0" name="SetCredentialsResult" type="xs:boolean" />
</xs:sequence>
</xs:complexType>
</xs:element>

```

SetCredentialsResult: A Boolean where TRUE indicates that the credentials were set successfully; otherwise, the value is FALSE.

3.9.5.2 IDomainMaintenanceManager.ValidateCredentials

This operation validates the current user credentials.

```

<wsdl:operation name="ValidateCredentials">
    <wsdl:input wsam:Action="http://tempuri.org/IDomainMaintenanceManager/ValidateCredentials">
        message="tns:IDomainMaintenanceManager_ValidateCredentials_InputMessage" />
        <wsdl:output
            wsam:Action="http://tempuri.org/IDomainMaintenanceManager/ValidateCredentialsResponse">
                message="tns:IDomainMaintenanceManager_ValidateCredentials_OutputMessage" />
            <wsdl:fault
                wsam:Action="http://tempuri.org/IDomainMaintenanceManager/ValidateCredentialsDomainManagerFault"
                name="DomainManagerFaultFault"
                message="tns:IDomainMaintenanceManager ValidateCredentials DomainManagerFaultFault FaultMessage" />
        </wsdl:output>
    </wsdl:input>
</wsdl:operation>

```

Upon receiving the **IDomainMaintenanceManager_ValidateCredentials_InputMessage** request message, the protocol server validates user credentials. Upon successful completion of the action, the server MUST respond with **IDomainMaintenanceManager_ValidateCredentials_OutputMessage**. In the event of a failure, an appropriate SOAP fault MUST be sent to the client as specified in section [2.2.2.1](#).

3.9.5.2.1 Messages

3.9.5.2.1.1 IDomainMaintenanceManager_ValidateCredentials_InputMessage

This is the request for the **ValidateCredentials** operation.

```

<wsdl:message name="IDomainMaintenanceManager_ValidateCredentials_InputMessage">
    <wsdl:part name="parameters" element="tns:ValidateCredentials" />
</wsdl:message>

```

This message MUST be sent with the following SOAP action.

<http://tempuri.org/IDomainMaintenanceManager/ValidateCredentials>

The body of the SOAP message MUST contain the **ValidateCredentials** element.

3.9.5.2.1.2 IDomainMaintenanceManager_ValidateCredentials_OutputMessage

This is the response for the **ValidateCredentials** operation.

```

<wsdl:message name="IDomainMaintenanceManager_ValidateCredentials_OutputMessage">
    <wsdl:part name="parameters" element="tns:ValidateCredentialsResponse" />
</wsdl:message>

```

This message MUST be sent with the following SOAP action.

```
http://tempuri.org/IDomainMaintenanceManager/ValidateCredentialsResponse
```

The body of the SOAP message MUST contain the **ValidateCredentialsResponse** element.

3.9.5.2.2 Elements

3.9.5.2.2.1 ValidateCredentials

This element specifies input values for the **ValidateCredentials** operation. This element has no parameters.

```
<xs:element name="ValidateCredentials">
  <xs:complexType>
    <xs:sequence />
  </xs:complexType>
</xs:element>
```

3.9.5.2.2.2 ValidateCredentialsResponse

This element specifies output values for the **ValidateCredentials** operation.

```
<xs:element name="ValidateCredentialsResponse">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" name="ValidateCredentialsResult" type="xs:boolean" />
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

ValidateCredentialsResult: A Boolean where TRUE indicates that the credentials were validated successfully; otherwise, the value is FALSE.

3.9.5.3 IDomainMaintenanceManager.UpdateDnsRecords

This operation updates the DNS records for the domain.

```
<wsdl:operation name="UpdateDnsRecords">
  <wsdl:input wsam:Action="http://tempuri.org/IDomainMaintenanceManager/UpdateDnsRecords"
  message="tns:IDomainMaintenanceManager_UpdateDnsRecords_InputMessage" />
  <wsdl:output
  wsam:Action="http://tempuri.org/IDomainMaintenanceManager/UpdateDnsRecordsResponse"
  message="tns:IDomainMaintenanceManager_UpdateDnsRecords_OutputMessage" />
  <wsdl:fault
  wsam:Action="http://tempuri.org/IDomainMaintenanceManager/UpdateDnsRecordsDomainManagerFaultF
ault" name="DomainManagerFaultFault"
  message="tns:IDomainMaintenanceManager_UpdateDnsRecords_DomainManagerFaultFault_FaultMessage"
  />
  <wsdl:fault
  wsam:Action="http://tempuri.org/IDomainMaintenanceManager/UpdateDnsRecordsArgumentExceptionFa
ult" name="ArgumentExceptionFault"
  message="tns:IDomainMaintenanceManager_UpdateDnsRecords_ArgumentExceptionFault_FaultMessage"
  />
</wsdl:operation>
```

Upon receiving the **IDomainMaintenanceManager_UpdateDnsRecords_InputMessage** request message, the protocol server updates DNS records for the domain. Upon successful completion of the action, the server MUST respond with **IDomainMaintenanceManager_UpdateDnsRecords_OutputMessage**. In the event of a failure, an appropriate SOAP fault MUST be sent to the client as specified in section [2.2.2.1](#).

3.9.5.3.1 Messages

3.9.5.3.1.1 IDomainMaintenanceManager_UpdateDnsRecords_InputMessage

This is the request for the **UpdateDnsRecords** operation.

```
<wsdl:message name="IDomainMaintenanceManager_UpdateDnsRecords_InputMessage">
  <wsdl:part name="parameters" element="tns:UpdateDnsRecords" />
</wsdl:message>
```

This message MUST be sent with the following SOAP action.

<http://tempuri.org/IDomainMaintenanceManager/UpdateDnsRecords>

The body of the SOAP message MUST contain the **UpdateDnsRecords** element.

3.9.5.3.1.2 IDomainMaintenanceManager_UpdateDnsRecords_OutputMessage

This is the response for the **UpdateDnsRecords** operation.

```
<wsdl:message name="IDomainMaintenanceManager_UpdateDnsRecords_OutputMessage">
  <wsdl:part name="parameters" element="tns:UpdateDnsRecordsResponse" />
</wsdl:message>
```

This message MUST be sent with the following SOAP action.

<http://tempuri.org/IDomainMaintenanceManager/UpdateDnsRecordsResponse>

The body of the SOAP message MUST contain the **UpdateDnsRecordsResponse** element.

3.9.5.3.2 Elements

3.9.5.3.2.1 UpdateDnsRecords

This element specifies input values for the **UpdateDnsRecords** operation.

```
<xs:element name="UpdateDnsRecords">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" name="records" nillable="true"
        xmlns:q2="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.RemoteAcce
        ss.Domains" type="q2:ArrayOfDnsRecord" />
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

records: A list of **DnsRecord** (section [2.2.4.9.3](#)) objects representing the DNS records to be updated.

3.9.5.3.2.2 UpdateDnsRecordsResponse

This element specifies output values for the **UpdateDnsRecords** operation.

```
<xs:element name="UpdateDnsRecordsResponse">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" name="UpdateDnsRecordsResult" type="xs:boolean" />
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

UpdateDnsRecordsResult: A Boolean where TRUE indicates that the DNS records were updated successfully; otherwise, this value is FALSE.

3.9.5.4 IDomainMaintenanceManager.QueryAddressFromDNS

This operation returns the public IPv4 or IPv6 address corresponding to the currently configured domain name, using the public DNS infrastructure.

```
<wsdl:operation name="QueryAddressFromDNS">
  <wsdl:input wsam:Action="http://tempuri.org/IDomainMaintenanceManager/QueryAddressFromDNS"
  message="tns:IDomainMaintenanceManager_QueryAddressFromDNS_InputMessage" />
  <wsdl:output
  wsam:Action="http://tempuri.org/IDomainMaintenanceManager/QueryAddressFromDNSResponse"
  message="tns:IDomainMaintenanceManager_QueryAddressFromDNS_OutputMessage" />
  <wsdl:fault
  wsam:Action="http://tempuri.org/IDomainMaintenanceManager/QueryAddressFromDNSDomainManagerFault"
  name="DomainManagerFaultFault"
  message="tns:IDomainMaintenanceManager_QueryAddressFromDNS_DomainManagerFaultFault_FaultMessage" />
</wsdl:operation>
```

Upon receiving the **IDomainMaintenanceManager_QueryAddressFromDNS_InputMessage** request message, the protocol server determines the public IP address (IPv4 or IPv6) corresponding to the currently configured domain name using the public DNS infrastructure. Upon successful completion of the action, the server MUST respond with

IDomainMaintenanceManager_QueryAddressFromDNS_OutputMessage. In the event of a failure, an appropriate SOAP fault MUST be sent to the client as specified in section [2.2.2.1](#).

3.9.5.4.1 Messages

3.9.5.4.1.1 IDomainMaintenanceManager_QueryAddressFromDNS_InputMessage

This is the request for the **QueryAddressFromDNS** operation.

```
<wsdl:message name="IDomainMaintenanceManager_QueryAddressFromDNS_InputMessage">
  <wsdl:part name="parameters" element="tns:QueryAddressFromDNS" />
</wsdl:message>
```

This message MUST be sent with the following SOAP action.

<http://tempuri.org/IDomainMaintenanceManager/QueryAddressFromDNS>

The body of the SOAP message MUST contain the **QueryAddressFromDNS** element.

3.9.5.4.1.2 IDomainMaintenanceManager_QueryAddressFromDNS_OutputMessage

This is the response for the **QueryAddressFromDNS** operation.

```
<wsdl:message name="IDomainMaintenanceManager_QueryAddressFromDNS_OutputMessage">
  <wsdl:part name="parameters" element="tns:QueryAddressFromDNSResponse" />
</wsdl:message>
```

This message MUST be sent with the following SOAP action.

```
http://tempuri.org/IDomainMaintenanceManager/QueryAddressFromDNSResponse
```

The body of the SOAP message MUST contain the **QueryAddressFromDNSResponse** element.

3.9.5.4.2 Elements

3.9.5.4.2.1 QueryAddressFromDNS

This element specifies input values for the **QueryAddressFromDNS** operation. This element has no parameters.

```
<xs:element name="QueryAddressFromDNS">
  <xs:complexType>
    <xs:sequence />
  </xs:complexType>
</xs:element>
```

3.9.5.4.2.2 QueryAddressFromDNSResponse

This element specifies output values for the **QueryAddressFromDNS** operation.

```
<xs:element name="QueryAddressFromDNSResponse">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" name="QueryAddressFromDNSResult" nillable="true"
        xmlns:q3="http://schemas.datacontract.org/2004/07/System.Net" type="q3:IPAddress" />
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

QueryAddressFromDNSResult: A value of type **IPAddress** (section [2.2.4.8.4](#)) that contains the requested address from the DNS.

3.9.5.5 IDomainMaintenanceManager.QueryAddressFromProvider

This operation returns the server's public IPv4 or IPv6 address by using the active maintenance provider.

```
<wsdl:operation name="QueryAddressFromProvider">
  <wsdl:input
    wsam:Action="http://tempuri.org/IDomainMaintenanceManager/QueryAddressFromProvider"
    message="tns:IDomainMaintenanceManager QueryAddressFromProvider InputMessage" />
  <wsdl:output
    wsam:Action="http://tempuri.org/IDomainMaintenanceManager/QueryAddressFromProviderResponse"
    message="tns:IDomainMaintenanceManager_QueryAddressFromProvider_OutputMessage" />
```

```

<wsdl:fault
    wsam:Action="http://tempuri.org/IDomainMaintenanceManager/QueryAddressFromProviderDomainManagerFaultFault"
    name="DomainManagerFaultFault"
    message="tns:IDomainMaintenanceManager_QueryAddressFromProvider_DomainManagerFaultFault_Fault
    Message" />
</wsdl:operation>
```

Upon receiving the **IDomainMaintenanceManager_QueryAddressFromProvider_InputMessage** request message, the protocol server queries the active maintenance provider for the server's public IP address. Upon successful completion of the action, the server MUST respond with **IDomainMaintenanceManager_QueryAddressFromProvider_OutputMessage**. In the event of a failure, an appropriate SOAP fault MUST be sent to the client as specified in section [2.2.2.1](#).

3.9.5.5.1 Messages

3.9.5.5.1.1 IDomainMaintenanceManager_QueryAddressFromProvider_InputMessage

This is the request for the **QueryAddressFromProvider** operation.

```
<wsdl:message name="IDomainMaintenanceManager_QueryAddressFromProvider_InputMessage">
    <wsdl:part name="parameters" element="tns:QueryAddressFromProvider" />
</wsdl:message>
```

This message MUST be sent with the following SOAP action.

```
http://tempuri.org/IDomainMaintenanceManager/QueryAddressFromProvider
```

The body of the SOAP message MUST contain the **QueryAddressFromProvider** element.

3.9.5.5.1.2 IDomainMaintenanceManager_QueryAddressFromProvider_OutputMessage

This is the response for the **QueryAddressFromProvider** operation.

```
<wsdl:message name="IDomainMaintenanceManager_QueryAddressFromProvider_OutputMessage">
    <wsdl:part name="parameters" element="tns:QueryAddressFromProviderResponse" />
</wsdl:message>
```

This message MUST be sent with the following SOAP action.

```
http://tempuri.org/IDomainMaintenanceManager/QueryAddressFromProviderResponse
```

The body of the SOAP message MUST contain the **QueryAddressFromProviderResponse** element.

3.9.5.5.2 Elements

3.9.5.5.2.1 QueryAddressFromProvider

This element specifies input values for the **QueryAddressFromProvider** operation. This element has no parameters.

```

<xs:element name="QueryAddressFromProvider">
  <xs:complexType>
    <xs:sequence />
  </xs:complexType>
</xs:element>

```

3.9.5.5.2.2 QueryAddressFromProviderResponse

This element specifies output values for the **QueryAddressFromProvider** operation.

```

<xs:element name="QueryAddressFromProviderResponse">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" name="QueryAddressFromProviderResult" nillable="true"
        xmlns:q4="http://schemas.datacontract.org/2004/07/System.Net" type="q4:IPAddress" />
    </xs:sequence>
  </xs:complexType>
</xs:element>

```

QueryAddressFromProviderResult: A value of type **IPAddress** (section [2.2.4.8.4](#)) that contains the requested IP address from the specified provider.

3.9.5.6 IDomainMaintenanceManager.TestConnection

This operation returns a value indicating whether a connection to the current provider's backend service can be established.

```

<wsdl:operation name="TestConnection">
  <wsdl:input wsam:Action="http://tempuri.org/IDomainMaintenanceManager/TestConnection"
    message="tns:IDomainMaintenanceManager_TestConnection_InputMessage" />
  <wsdl:output
    wsam:Action="http://tempuri.org/IDomainMaintenanceManager/TestConnectionResponse"
    message="tns:IDomainMaintenanceManager_TestConnection_OutputMessage" />
  <wsdl:fault
    wsam:Action="http://tempuri.org/IDomainMaintenanceManager/TestConnectionDomainManagerFaultFault"
    name="DomainManagerFaultFault"
    message="tns:IDomainMaintenanceManager_TestConnection_DomainManagerFaultFault_FaultMessage"
  />
</wsdl:operation>

```

Upon receiving the **IDomainMaintenanceManager_TestConnection_InputMessage** request message, the protocol server verifies whether a connection to the current provider's backend service can be established. Upon successful completion of the action, the server MUST respond with **IDomainMaintenanceManager_TestConnection_OutputMessage**. In the event of a failure, an appropriate SOAP fault MUST be sent to the client as specified in section [2.2.2.1](#).

3.9.5.6.1 Messages

3.9.5.6.1.1 IDomainMaintenanceManager_TestConnection_InputMessage

This is the request for the **TestConnection** operation.

```

<wsdl:message name="IDomainMaintenanceManager_TestConnection_InputMessage">
  <wsdl:part name="parameters" element="tns:TestConnection" />
</wsdl:message>

```

This message MUST be sent with the following SOAP action.

```
http://tempuri.org/IDomainMaintenanceManager/TestConnection
```

The body of the SOAP message MUST contain the **TestConnection** element.

3.9.5.6.1.2 IDomainMaintenanceManager_TestConnection_OutputMessage

This is the response for the **TestConnection** operation.

```
<wsdl:message name="IDomainMaintenanceManager_TestConnection_OutputMessage">
  <wsdl:part name="parameters" element="tns:TestConnectionResponse" />
</wsdl:message>
```

This message MUST be sent with the following SOAP action.

```
http://tempuri.org/IDomainMaintenanceManager/TestConnectionResponse
```

The body of the SOAP message MUST contain the **TestConnectionResponse** element.

3.9.5.6.2 Elements

3.9.5.6.2.1 TestConnection

This element specifies input values for the **TestConnection** operation. This element has no parameters.

```
<xss:element name="TestConnection">
  <xss:complexType>
    <xss:sequence />
  </xss:complexType>
</xss:element>
```

3.9.5.6.2.2 TestConnectionResponse

This element specifies output values for the **TestConnection** operation.

```
<xss:element name="TestConnectionResponse">
  <xss:complexType>
    <xss:sequence>
      <xss:element minOccurs="0" name="TestConnectionResult" type="xs:boolean" />
    </xss:sequence>
  </xss:complexType>
</xss:element>
```

TestConnectionResult: A Boolean where TRUE indicates that the connection is good; otherwise, the value is FALSE.

3.9.5.7 IDomainMaintenanceManager.GetDomainState

This operation returns the current domain state from the active maintenance provider.

```
<wsdl:operation name="GetDomainState">
  <wsdl:input wsam:Action="http://tempuri.org/IDomainMaintenanceManager/GetDomainState"
  message="tns:IDomainMaintenanceManager_GetDomainState_InputMessage" />
```

```

<wsdl:output
wsam:Action="http://tempuri.org/IDomainMaintenanceManager/GetDomainStateResponse"
message="tns:IDomainMaintenanceManager_GetDomainState_OutputMessage" />
<wsdl:fault
wsam:Action="http://tempuri.org/IDomainMaintenanceManager/GetDomainStateDomainManagerFaultFault"
name="DomainManagerFaultFault"
message="tns:IDomainMaintenanceManager_GetDomainState_DomainManagerFaultFault_FaultMessage"
/>
</wsdl:operation>
```

Upon receiving the **IDomainMaintenanceManager_GetDomainState_InputMessage** request message, the protocol server queries the active maintenance provider for the current domain state. Upon successful completion of the action, the server MUST respond with **IDomainMaintenanceManager_GetDomainState_OutputMessage**. In the event of a failure, an appropriate SOAP fault MUST be sent to the client as specified in section [2.2.2.1](#).

3.9.5.7.1 Messages

3.9.5.7.1.1 IDomainMaintenanceManager_GetDomainState_InputMessage

This is the request for the **GetDomainState** operation.

```
<wsdl:message name="IDomainMaintenanceManager_GetDomainState_InputMessage">
  <wsdl:part name="parameters" element="tns:GetDomainState" />
</wsdl:message>
```

This message MUST be sent with the following SOAP action.

```
http://tempuri.org/IDomainMaintenanceManager/GetDomainState
```

The body of the SOAP message MUST contain the **GetDomainState** element.

3.9.5.7.1.2 IDomainMaintenanceManager_GetDomainState_OutputMessage

This is the response for the **GetDomainState** operation.

```
<wsdl:message name="IDomainMaintenanceManager_GetDomainState_OutputMessage">
  <wsdl:part name="parameters" element="tns:GetDomainStateResponse" />
</wsdl:message>
```

This message MUST be sent with the following SOAP action.

```
http://tempuri.org/IDomainMaintenanceManager/GetDomainStateResponse
```

The body of the SOAP message MUST contain the **GetDomainStateResponse** element.

3.9.5.7.2 Elements

3.9.5.7.2.1 GetDomainState

This element specifies input values for the **GetDomainState** operation. This element has no parameters.

```

<xs:element name="GetDomainState">
  <xs:complexType>
    <xs:sequence />
  </xs:complexType>
</xs:element>

```

3.9.5.7.2.2 GetDomainStateResponse

This element specifies output values for the **GetDomainState** operation.

```

<xs:element name="GetDomainStateResponse">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" name="GetDomainStateResult" nillable="true"
        xmlns:q5="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.RemoteAcce
        ss.Domains" type="q5:DomainState" />
    </xs:sequence>
  </xs:complexType>
</xs:element>

```

GetDomainStateResult: A **DomainState** (section [2.2.4.9.9](#)) complex type that contains the requested domain state details.

3.9.5.8 IDomainMaintenanceManager.GetCertificateState

This operation returns the current certificate state from the active maintenance provider.

```

<wsdl:operation name="GetCertificateState">
  <wsdl:input wsam:Action="http://tempuri.org/IDomainMaintenanceManager/GetCertificateState">
    message="tns:IDomainMaintenanceManager_GetCertificateState_InputMessage" />
  <wsdl:output
    wsam:Action="http://tempuri.org/IDomainMaintenanceManager/GetCertificateStateResponse">
    message="tns:IDomainMaintenanceManager_GetCertificateState_OutputMessage" />
  <wsdl:fault
    wsam:Action="http://tempuri.org/IDomainMaintenanceManager/GetCertificateStateDomainManagerFau
    ltFault" name="DomainManagerFaultFault"
    message="tns:IDomainMaintenanceManager_GetCertificateState_DomainManagerFaultFault_FaultMessa
    ge" />
</wsdl:operation>

```

Upon receiving the **IDomainMaintenanceManager_GetCertificateState_InputMessage** request message, the protocol server queries the active maintenance provider for the current certificate state. Upon successful completion of the action, the server MUST respond with **IDomainMaintenanceManager_GetCertificateState_OutputMessage**. In the event of a failure, an appropriate SOAP fault MUST be sent to the client as specified in section [2.2.2.1](#).

3.9.5.8.1 Messages

3.9.5.8.1.1 IDomainMaintenanceManager_GetCertificateState_InputMessage

This is the request for the **GetCertificateState** operation.

```

<wsdl:message name="IDomainMaintenanceManager_GetCertificateState_InputMessage">
  <wsdl:part name="parameters" element="tns:GetCertificateState" />
</wsdl:message>

```

This message MUST be sent with the following SOAP action.

```
http://tempuri.org/IDomainMaintenanceManager/GetCertificateState
```

The body of the SOAP message MUST contain the **GetCertificateState** element.

3.9.5.8.1.2 IDomainMaintenanceManager_GetCertificateState_OutputMessage

This is the response for the **GetCertificateState** operation.

```
<wsdl:message name="IDomainMaintenanceManager_GetCertificateState_OutputMessage">
  <wsdl:part name="parameters" element="tns:GetCertificateStateResponse" />
</wsdl:message>
```

This message MUST be sent with the following SOAP action.

```
http://tempuri.org/IDomainMaintenanceManager/GetCertificateStateResponse
```

The body of the SOAP message MUST contain the **GetCertificateStateResponse** element.

3.9.5.8.2 Elements

3.9.5.8.2.1 GetCertificateState

This element specifies input values for the **GetCertificateState** operation. This element has no parameters.

```
<xs:element name="GetCertificateState">
  <xs:complexType>
    <xs:sequence />
  </xs:complexType>
</xs:element>
```

3.9.5.8.2.2 GetCertificateStateResponse

This element specifies output values for the **GetCertificateState** operation.

```
<xs:element name="GetCertificateStateResponse">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" name="GetCertificateStateResult" nillable="true"
        xmlns:q6="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.RemoteAcce
        ss.Domains" type="q6:CertificateState" />
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

GetCertificateStateResult: A **CertificateState** (section [2.2.4.9.10](#)) complex type that contains the requested certificate state details.

3.9.5.9 IDomainMaintenanceManager.GetDomainNameConfiguration

This operation returns the currently active domain name configuration.

```
<wsdl:operation name="GetDomainNameConfiguration">
```

```

<wsdl:input
wsam:Action="http://tempuri.org/IDomainMaintenanceManager/GetDomainNameConfiguration"
message="tns:IDomainMaintenanceManager_GetDomainNameConfiguration_InputMessage" />
<wsdl:output
wsam:Action="http://tempuri.org/IDomainMaintenanceManager/GetDomainNameConfigurationResponse"
message="tns:IDomainMaintenanceManager GetDomainNameConfiguration OutputMessage" />
</wsdl:operation>
```

Upon receiving the **IDomainMaintenanceManager_GetDomainNameConfiguration_InputMessage** request message, the protocol server returns the currently active domain name configuration. Upon successful completion of the action, the server MUST respond with **IDomainMaintenanceManager_GetDomainNameConfiguration_OutputMessage**. In the event of a failure, an appropriate SOAP fault MUST be sent to the client as specified in section [2.2.2.1](#).

3.9.5.9.1 Messages

3.9.5.9.1.1 IDomainMaintenanceManager_GetDomainNameConfiguration_InputMessage

This is the request for the **GetDomainNameConfiguration** operation.

```

<wsdl:message name="IDomainMaintenanceManager GetDomainNameConfiguration InputMessage">
  <wsdl:part name="parameters" element="tns:GetDomainNameConfiguration" />
</wsdl:message>
```

This message MUST be sent with the following SOAP action.

<http://tempuri.org/IDomainMaintenanceManager/GetDomainNameConfiguration>

The body of the SOAP message MUST contain the **GetDomainNameConfiguration** element.

3.9.5.9.1.2 IDomainMaintenanceManager_GetDomainNameConfiguration_OutputMessage

This is the response for the **GetDomainNameConfiguration** operation.

```

<wsdl:message name="IDomainMaintenanceManager GetDomainNameConfiguration OutputMessage">
  <wsdl:part name="parameters" element="tns:GetDomainNameConfigurationResponse" />
</wsdl:message>
```

This message MUST be sent with the following SOAP action.

<http://tempuri.org/IDomainMaintenanceManager/GetDomainNameConfigurationResponse>

The body of the SOAP message MUST contain the **GetDomainNameConfigurationResponse** element.

3.9.5.9.2 Elements

3.9.5.9.2.1 GetDomainNameConfiguration

This element specifies input values for the **GetDomainNameConfiguration** operation. This element has no parameters.

```
<xs:element name="GetDomainNameConfiguration">
  <xs:complexType>
    <xs:sequence />
  </xs:complexType>
</xs:element>
```

3.9.5.9.2.2 GetDomainNameConfigurationResponse

This element specifies output values for the **GetDomainNameConfiguration** operation.

```
<xs:element name="GetDomainNameConfigurationResponse">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" name="GetDomainNameConfigurationResult" nillable="true"
        xmlns:q7="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.RemoteAcce
        ss.Domains" type="q7:DomainNameConfiguration" />
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

GetDomainNameConfigurationResult: A **DomainNameConfiguration** (section [2.2.4.9.11](#)) complex type that contains the requested domain name configuration details.

3.9.5.10 IDomainMaintenanceManager.GetDynamicDNSInfo

This operation returns data about dynamic DNS updates, for example, the time of the most recent successful update.

```
<wsdl:operation name="GetDynamicDNSInfo">
  <wsdl:input wsam:Action="http://tempuri.org/IDomainMaintenanceManager/GetDynamicDNSInfo"
    message="tns:IDomainMaintenanceManager GetDynamicDNSInfo_InputMessage" />
  <wsdl:output
    wsam:Action="http://tempuri.org/IDomainMaintenanceManager/GetDynamicDNSInfoResponse"
    message="tns:IDomainMaintenanceManager_GetDynamicDNSInfo_OutputMessage" />
</wsdl:operation>
```

Upon receiving the **IDomainMaintenanceManager_GetDynamicDNSInfo_InputMessage** request message, the protocol server returns data about dynamic DNS updates (the time of the last most recent successful update, for example). Upon successful completion of the action, the server MUST respond with **IDomainMaintenanceManager_GetDynamicDNSInfo_OutputMessage**. In the event of a failure, an appropriate SOAP fault MUST be sent to the client as specified in section [2.2.2.1](#).

3.9.5.10.1 Messages

3.9.5.10.1.1 IDomainMaintenanceManager_GetDynamicDNSInfo_InputMessage

This is the request for the **GetDynamicDNSInfo** operation.

```
<wsdl:message name="IDomainMaintenanceManager_GetDynamicDNSInfo_InputMessage">
  <wsdl:part name="parameters" element="tns:GetDynamicDNSInfo" />
</wsdl:message>
```

This message MUST be sent with the following SOAP action.

```
http://tempuri.org/IDomainMaintenanceManager/GetDynamicDNSInfo
```

The body of the SOAP message MUST contain the **GetDynamicDNSInfo** element.

3.9.5.10.1.2 IDomainMaintenanceManager_GetDynamicDNSInfo_OutputMessage

This is the response for the **GetDynamicDNSInfo** operation.

```
<wsdl:message name="IDomainMaintenanceManager_GetDynamicDNSInfo_OutputMessage">
  <wsdl:part name="parameters" element="tns:GetDynamicDNSInfoResponse" />
</wsdl:message>
```

This message MUST be sent with the following SOAP action.

```
http://tempuri.org/IDomainMaintenanceManager/GetDynamicDNSInfoResponse
```

The body of the SOAP message MUST contain the **GetDynamicDNSInfoResponse** element.

3.9.5.10.2 Elements

3.9.5.10.2.1 GetDynamicDNSInfo

This element specifies input values for the **GetDynamicDNSInfo** operation. This element has no parameters.

```
<xs:element name="GetDynamicDNSInfo">
  <xs:complexType>
    <xs:sequence />
  </xs:complexType>
</xs:element>
```

3.9.5.10.2.2 GetDynamicDNSInfoResponse

This element specifies output values for the **GetDynamicDNSInfo** operation.

```
<xs:element name="GetDynamicDNSInfoResponse">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" name="GetDynamicDNSInfoResult" nillable="true"
        xmlns:q8="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.RemoteAcce
        ss.Domains" type="q8:DynamicDNSInfo" />
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

GetDynamicDNSInfoResult: A **DynamicDNSInfo** (section [2.2.4.9.13](#)) complex type that contains the requested dynamic DNS information.

3.9.5.11 IDomainMaintenanceManager.GetSettings

This operation returns the current domain manager settings.

```
<wsdl:operation name="GetSettings">
```

```
<wsdl:input wsam:Action="http://tempuri.org/IDomainMaintenanceManager/GetSettings"
message="tns:IDomainMaintenanceManager_GetSettings_InputMessage" />
<wsdl:output wsam:Action="http://tempuri.org/IDomainMaintenanceManager/GetSettingsResponse"
message="tns:IDomainMaintenanceManager_GetSettings_OutputMessage" />
</wsdl:operation>
```

Upon receiving the **IDomainMaintenanceManager_GetSettings_InputMessage** request message, the protocol server returns the current domain manager settings. Upon successful completion of the action, the server MUST respond with **IDomainMaintenanceManager_GetSettings_OutputMessage**. In the event of a failure, an appropriate SOAP fault MUST be sent to the client as specified in section [2.2.2.1](#).

3.9.5.11.1 Messages

3.9.5.11.1.1 IDomainMaintenanceManager_GetSettings_InputMessage

This is the request for the **GetSettings** operation.

```
<wsdl:message name="IDomainMaintenanceManager_GetSettings_InputMessage">
  <wsdl:part name="parameters" element="tns:GetSettings" />
</wsdl:message>
```

This message MUST be sent with the following SOAP action.

<http://tempuri.org/IDomainMaintenanceManager/GetSettings>

The body of the SOAP message MUST contain the **GetSettings** element.

3.9.5.11.1.2 IDomainMaintenanceManager_GetSettings_OutputMessage

This is the response for the **GetSettings** operation.

```
<wsdl:message name="IDomainMaintenanceManager_GetSettings_OutputMessage">
  <wsdl:part name="parameters" element="tns:GetSettingsResponse" />
</wsdl:message>
```

This message MUST be sent with the following SOAP action.

<http://tempuri.org/IDomainMaintenanceManager/GetSettingsResponse>

The body of the SOAP message MUST contain the **GetSettingsResponse** element.

3.9.5.11.2 Elements

3.9.5.11.2.1 GetSettings

This element specifies input values for the **GetSettings** operation. This element has no parameters.

```
<xss:element name="GetSettings">
  <xss:complexType>
    <xss:sequence />
  </xss:complexType>
</xss:element>
```

3.9.5.11.2.2 GetSettingsResponse

This element specifies output values for the **GetSettings** operation.

```
<xs:element name="GetSettingsResponse">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" name="GetSettingsResult" nillable="true"
        xmlns:q9="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.RemoteAcce
        ss.Domains" type="q9:DomainProviderManagerSettings" />
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

GetSettingsResult: A **DomainProviderManagerSettings** (section [2.2.4.9.14](#)) complex type that indicates the result of getting domain provider manager settings.

3.9.6 Timer Events

None.

3.9.7 Other Local Events

None.

3.10 AzureAD and HostedEmail Integration Service Contract Details

3.10.1 Abstract Data Model

None.

3.10.2 Timers

None.

3.10.3 Initialization

None.

3.10.4 Higher-Layer Triggered Events

None

3.10.5 Message Processing Events and Sequencing Rules

OperationContract	Description
IPasswordSyncClientProvider.Disconnect	Disconnects from the provider service.
IPasswordSyncClientProvider.RaiseOperationInvokeEvent	Raises an operation invoke event.
IO365ClientProvider.GetSharePointAddress<19>	Returns the address of the SharePoint web portal associated with the Microsoft Office 365 subscription.
IO365ClientProvider.IsActive	Checks whether Office 365 integration is activated.

OperationContract	Description
IPasswordSyncClientProvider.GetPasswordChangeStatus	Gets password change status.
IPasswordSyncClientProvider.MarkPasswordChangeFixed	Marks password change status as fixed.
IO365ClientProvider.GetEmailAddress	Gets the email address for the caller.

3.10.5.1 IPasswordSyncClientProvider.Disconnect

This operation disconnects from the provider service.

```
<wsdl:operation msc:isInitiating="true" msc:isTerminating="true" name="Disconnect">
  <wsdl:input wsam:Action="http://tempuri.org/IProvider/Disconnect" message="tns:
    IPasswordSyncClientProvider Disconnect InputMessage" />
</wsdl:operation>
```

Upon receiving the **IPasswordSyncClientProvider_Disconnect_InputMessage** request message, the protocol server disconnects the caller from the provider service. In the event of a failure, an appropriate SOAP fault MUST be sent to the client as specified in section [2.2.1](#).

3.10.5.1.1 Messages

3.10.5.1.1.1 IPasswordSyncClientProvider_Disconnect_InputMessage

This is the request for the **Disconnect** operation.

```
<wsdl:message name="IPasswordSyncClientProvider Disconnect InputMessage">
  <wsdl:part name="parameters" element="tns:Disconnect" />
</wsdl:message>
```

This message MUST be sent with the following SOAP action.

<http://tempuri.org/IProvider/Disconnect>

The body of the SOAP message MUST contain the **Disconnect** element.

3.10.5.1.2 Elements

3.10.5.1.2.1 Disconnect

This element specifies input values for the **Disconnect** operation. This element has no parameters.

```
<xss:element name="Disconnect">
  <xss:complexType>
    <xss:sequence />
  </xss:complexType>
</xss:element>
```

3.10.5.2 IPasswordSyncClientProvider.RaiseOperationInvokeEvent

This operation raises an operation invoke event.[<20>](#)

```

<wsdl:operation msc:isInitiating="true" msc:isTerminating="false"
name="RaiseOperationInvokeEvent">
  <wsdl:output wsam:Action="http://tempuri.org/IProvider/RaiseOperationInvokeEvent"
message="tns: IPasswordSyncClientProvider_RaiseOperationInvokeEvent_OutputCallbackMessage" />
</wsdl:operation>

```

3.10.5.2.1 Messages

3.10.5.2.1.1 IO365ClientProvider_RaiseOperationInvokeEvent_OutputCallbackMessage

This is the request for the **RaiseOperationInvoke** operation.

```

<wsdl:message name="IO365ClientProvider_RaiseOperationInvokeEvent_OutputCallbackMessage">
  <wsdl:part name="parameters" element="tns:RaiseOperationInvokeEvent" />
</wsdl:message>

```

This message MUST be sent with the following SOAP action.

<http://tempuri.org/IProvider/RaiseOperationInvokeEvent>

The body of the SOAP message MUST contain the **RaiseOperationInvokeEvent** element.

3.10.5.2.2 Elements

3.10.5.2.2.1 RaiseOperationInvokeEvent

This element specifies input values for the **RaiseOperationInvoke** operation.

```

<xs:element name="RaiseOperationInvokeEvent">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" name="operationName" nillable="true" type="xs:string" />
      <xs:element minOccurs="0" name="result" nillable="true" type="xs:anyType" />
      <xs:element minOccurs="0" name="errorException" nillable="true"
      xmlns:ql="http://schemas.datacontract.org/2004/07/System" type="ql:Exception" />
    </xs:sequence>
  </xs:complexType>
</xs:element>

```

operationName: A string that contains the name of the operation.

result: A value that indicates the result of the operation.

errorException: A value of type **Exception** (section [2.2.4.11.3](#)) that describes any exception thrown in the operation, if there is any; otherwise, this value is null.

3.10.5.3 IO365ClientProvider.GetSharePointAddress

This operation MAY [<21>](#) return the address of the SharePoint web portal associated with the Office 365 subscription.

```

<wsdl:operation msc:isInitiating="true" msc:isTerminating="false"
name="GetSharePointAddress">

```

```

<wsdl:input wsam:Action="http://tempuri.org/IO365ClientProvider/GetSharePointAddress"
message="tns:IO365ClientProvider_GetSharePointAddress_InputMessage" />
<wsdl:output
wsam:Action="http://tempuri.org/IO365ClientProvider/GetSharePointAddressResponse"
message="tns:IO365ClientProvider_GetSharePointAddress_OutputMessage" />
<wsdl:fault
wsam:Action="http://tempuri.org/IO365ClientProvider/GetSharePointAddressO365ConfigureExceptionFault"
name="O365ConfigureExceptionFault"
message="tns:IO365ClientProvider_GetSharePointAddress_O365ConfigureExceptionFault_FaultMessage" />
</wsdl:operation>
```

Upon receiving the **IO365ClientProvider_GetSharePointAddress_InputMessage** request message, the protocol server returns the SharePoint address. Upon successful completion of the action, the server MUST respond with

IO365ClientProvider_GetSharePointAddress_OutputMessage. In the event of a failure, an appropriate SOAP fault MUST be sent to the client as specified in section [2.2.2.1](#).

3.10.5.3.1 Messages

3.10.5.3.1.1 IO365ClientProvider_GetSharePointAddress_InputMessage

This is the request for the **GetSharePointAddress** operation.

```

<wsdl:message name="IO365ClientProvider_GetSharePointAddress_InputMessage">
  <wsdl:part name="parameters" element="tns:GetSharePointAddress" />
</wsdl:message>
```

This message MUST be sent with the following SOAP action.

<http://tempuri.org/IProvider/GetSharePointAddress>

The body of the SOAP message MUST contain the **GetSharePointAddress** element.

3.10.5.3.1.2 IO365ClientProvider_GetSharePointAddress_OutputMessage

This is the response for the **GetSharePointAddress** operation.

```

<wsdl:message name="IO365ClientProvider_GetSharePointAddress_OutputMessage">
  <wsdl:part name="parameters" element="tns:GetSharePointAddressResponse" />
</wsdl:message>
```

This message MUST be sent with the following SOAP action.

<http://tempuri.org/IProvider/GetSharePointAddressResponse>

The body of the SOAP message MUST contain the **GetSharePointAddressResponse** element.

3.10.5.3.2 Elements

3.10.5.3.2.1 GetSharePointAddress

This element specifies input values for the **GetSharePointAddress** operation. This element has no parameters.

```

<xs:element name="GetSharePointAddress">
  <xs:complexType>
    <xs:sequence />
  </xs:complexType>
</xs:element>

```

3.10.5.3.2.2 GetSharePointAddressResponse

This element specifies output values for the **GetSharePointAddress** operation.

```

<xs:element name="GetSharePointAddressResponse">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" name="GetSharePointAddressResult" nillable="true"
        type="xs:string" />
    </xs:sequence>
  </xs:complexType>
</xs:element>

```

GetSharePointAddressResult: A string that contains the address of the requested SharePoint site.

3.10.5.4 IO365ClientProvider.IsActive

This operation MAY [22](#) return a value indicating whether Office 365 integration is activated.

```

<wsdl:operation msc:isInitiating="true" msc:isTerminating="false" name="IsActive">
  <wsdl:input wsam:Action="http://tempuri.org/IO365ClientProvider/IsActive"
    message="tns:IO365ClientProvider_IsActivated_InputMessage" />
  <wsdl:output wsam:Action="http://tempuri.org/IO365ClientProvider/IsActiveResponse"
    message="tns:IO365ClientProvider IsActive OutputMessage" />
  <wsdl:fault
    wsam:Action="http://tempuri.org/IO365ClientProvider/IsActiveO365ConfigureExceptionFault"
    name="O365ConfigureExceptionFault"
    message="tns:IO365ClientProvider IsActive O365ConfigureExceptionFault FaultMessage" />
</wsdl:operation>

```

Upon receiving the **IO365ClientProvider_IsActivated_InputMessage** request message, the protocol server checks whether the Office 365 integration is activated. Upon successful completion of the action, the server MUST respond with **IO365ClientProvider_IsActivated_OutputMessage**. In the event of a failure, an appropriate SOAP fault MUST be sent to the client as specified in section [2.2.1](#).

3.10.5.4.1 Messages

3.10.5.4.1.1 IO365ClientProvider_IsActivated_InputMessage

This is the request for the **IsActive** operation.

```

<wsdl:message name="IO365ClientProvider_IsActivated_InputMessage">
  <wsdl:part name="parameters" element="tns:IsActive" />
</wsdl:message>

```

This message MUST be sent with the following SOAP action.

<http://tempuri.org/IProvider/IsActive>

The body of the SOAP message MUST contain the **IsActivated** element.

3.10.5.4.1.2 IO365ClientProvider_IsActivated_OutputMessage

This is the response for the **IsActivated** operation.

```
<wsdl:message name="IO365ClientProvider_IsActivated_OutputMessage">
  <wsdl:part name="parameters" element="tns:IsActivatedResponse" />
</wsdl:message>
```

This message MUST be sent with the following SOAP action.

```
http://tempuri.org/IProvider/IsActivatedResponse
```

The body of the SOAP message MUST contain the **IsActivatedResponse** element.

3.10.5.4.2 Elements

3.10.5.4.2.1 IsActivated

This element specifies input values for the **IsActivated** operation. This element has no parameters.

```
<xs:element name="IsActivated">
  <xs:complexType>
    <xs:sequence />
  </xs:complexType>
</xs:element>
```

3.10.5.4.2.2 IsActivatedResponse

This element specifies output values for the **IsActivated** operation.

```
<xs:element name="IsActivatedResponse">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" name="IsActivatedResult" type="xs:boolean" />
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

IsActivatedResult: A Boolean where TRUE indicates that the Office 365 integration is activated; otherwise, the value is FALSE.

3.10.5.5 IPasswordSyncClientProvider.GetPasswordChangeStatus

This operation returns the password change status.

```
name="GetPasswordChangeStatus">
  <wsdl:input
    wsam:Action="http://tempuri.org/IPasswordSyncClientProvider/GetPasswordChangeStatus"
    message="tns:IPasswordSyncClientProvider_GetPasswordChangeStatus_InputMessage" />
  <wsdl:output
    wsam:Action="http://tempuri.org/IPasswordSyncClientProvider/GetPasswordChangeStatusResponse"
    message="tns:IPasswordSyncClientProvider_GetPasswordChangeStatus_OutputMessage" />
  <wsdl:fault
    wsam:Action="http://tempuri.org/IPasswordSyncClientProvider/GetPasswordChangeStatusPwdSyncCon
```

```
figureExceptionFault" name="PwdSyncConfigureExceptionFault"
message="tns:IPasswordSyncClientProvider GetPasswordChangeStatus PwdSyncConfigureExceptionFault FaultMessage" />
```

Upon receiving the **IPasswordSyncClientProvider_GetPasswordChangeStatus_InputMessage** request message, the protocol server returns the password change status. Upon successful completion of the action, the server MUST respond with **IPasswordSyncClientProvider_GetPasswordChangeStatus_OutputMessage**. In the event of a failure, an appropriate SOAP fault MUST be sent to the client as specified in section [2.2.2.1](#).

3.10.5.5.1 Messages

3.10.5.5.1.1 IPasswordSyncClientProvider_GetPasswordChangeStatus_InputMessage

This is the request for the **GetPasswordChangeStatus** operation.

```
<wsdl:message name="IPasswordSyncClientProvider GetPasswordChangeStatus InputMessage">
  <wsdl:part name="parameters" element="tns:GetPasswordChangeStatus" />
</wsdl:message>
```

This message MUST be sent with the following SOAP action.

<http://tempuri.org/IProvider/GetPasswordChangeStatus>

The body of the SOAP message MUST contain the **GetPasswordChangeStatus** element.

3.10.5.5.1.2 IPasswordSyncClientProvider_GetPasswordChangeStatus_OutputMessage

This is the response for the **GetPasswordChangeStatus** operation.

```
<wsdl:message name="IPasswordSyncClientProvider GetPasswordChangeStatus OutputMessage">
  <wsdl:part name="parameters" element="tns:GetPasswordChangeStatusResponse" />
</wsdl:message>
```

This message MUST be sent with the following SOAP action.

<http://tempuri.org/IProvider/GetPasswordChangeStatusResponse>

The body of the SOAP message MUST contain the **GetPasswordChangeStatusResponse** element.

3.10.5.5.2 Elements

3.10.5.5.2.1 GetPasswordChangeStatus

This element specifies input values for the **GetPasswordChangeStatus** operation.

```
<xs:element name="GetPasswordChangeStatus">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" name="localuser" nillable="true" type="xs:string" />
    </xs:sequence>
  </xs:complexType>
```

```
</xs:element>
```

localuser: A string that contains the name of the local user whose password change status has been queried.

3.10.5.5.2.2 GetPasswordChangeStatusResponse

This element specifies output values for the **GetPasswordChangeStatus** operation.

```
<xs:element name="GetPasswordChangeStatusResponse">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" name="GetPasswordChangeStatusResult"
        xmlns:q2="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.
        PasswordSync" type="q3:PasswordChangeStatus" />
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

GetPasswordChangeStatusResult: A **PasswordChangeStatus** (section [2.2.5.10.2](#)) string that contains the password change status of the specified user.

3.10.5.6 IPasswordSyncClientProvider.MarkUserPasswordChangeFixed

This operation marks the password change status as fixed.

```
</wsdl:operation>
<wsdl:operation msc:isInitiating="true" msc:isTerminating="false"
  name="MarkPasswordChangeFixed">
  <wsdl:input
    wsam:Action="http://tempuri.org/IPasswordSyncClientProvider/MarkUserPasswordChangeFixed"
    message="tns:IPasswordSyncClientProvider_MarkUserPasswordChangeFixed_InputMessage" />
  <wsdl:output
    wsam:Action="http://tempuri.org/IPasswordSyncClientProvider/MarkUserPasswordChangeFixedRespon
    se" message="tns:IPasswordSyncClientProvider_MarkUserPasswordChangeFixed_OutputMessage" />
  <wsdl:fault
    wsam:Action="http://tempuri.org/IPasswordSyncClientProvider/MarkUserPasswordChangeFixedPwdSyn
    cConfigureExceptionFault" name="PwdSyncConfigureExceptionFault"
    message="tns:IPasswordSyncClientProvider_MarkUserPasswordChangeFixed_PwdSyncConfigureExceptio
    nFault_FaultMessage" />
```

Upon receiving the **IPasswordSyncClientProvider_MarkPasswordChangeFixed_InputMessage** request message, the protocol server marks the password change status as fixed. Upon successful completion of the action, the server MUST respond with **IPasswordSyncClientProvider_MarkPasswordChangeFixed_OutputMessage**. In the event of a failure, an appropriate SOAP fault MUST be sent to the client as specified in section [2.2.2.1](#).

3.10.5.6.1 Messages

3.10.5.6.1.1 IPasswordSyncClientProvider_MarkUserPasswordChangeFixed_InputMe ssage

This is the request for the **MarkPasswordChangeFixed** operation.

```
<wsdl:message name="IPasswordSyncClientProvider_MarkUserPasswordChangeFixed_InputMessage">
  <wsdl:part name="parameters" element="tns:MarkPasswordChangeFixed" />
```

```
</wsdl:message>
```

This message MUST be sent with the following SOAP action.

```
http://tempuri.org/IProvider/MarkUserPasswordChangeFixed
```

The body of the SOAP message MUST contain the **MarkUserPasswordChangeFixed** element.

3.10.5.6.1.2 IPasswordSyncClientProvider_MarkUserPasswordChangeFixed_OutputMessage

This is the response for the **MarkPasswordChangeFixed** operation.

```
<wsdl:message name="IPasswordSyncClientProvider_MarkPasswordChangeFixed_OutputMessage">
  <wsdl:part name="parameters" element="tns:MarkPasswordChangeFixedResponse" />
</wsdl:message>
```

This message MUST be sent with the following SOAP action.

```
http://tempuri.org/IProvider/MarkUserPasswordChangeFixedResponse
```

The body of the SOAP message MUST contain the **MarkUserPasswordChangeFixedResponse** element.

3.10.5.6.2 Elements

3.10.5.6.2.1 MarkUserPasswordChangeFixed

This element specifies input values for the **MarkUserPasswordChangeFixed** operation.

```
<xs:element name="MarkUserPasswordChangeFixed">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" name="localuser" nillable="true" type="xs:string" />
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

localuser: A string that contains the name of the local user whose password change status needs to be marked fixed.

3.10.5.6.2.2 MarkUserPasswordChangeFixedResponse

This element specifies output values for the **MarkUserPasswordChangeFixed** operation. This element has no parameters.

```
<xs:element name="MarkUserPasswordChangeFixedResponse">
  <xs:complexType>
    <xs:sequence />
  </xs:complexType>
</xs:element>
```

3.10.5.7 IO365ClientProvider.GetEmailAddress

This operation MAY [23](#) return the email address for the caller.

```
</wsdl:operation>
<wsdl:operation msc:isInitiating="true" msc:isTerminating="false" name="GetEmailAddress">
  <wsdl:input wsam:Action="http://tempuri.org/IO365ClientProvider/GetEmailAddress"
    message="tns:IO365ClientProvider_GetEmailAddress_InputMessage" />
  <wsdl:output wsam:Action="http://tempuri.org/IO365ClientProvider/GetEmailAddressResponse"
    message="tns:IO365ClientProvider_GetEmailAddress_OutputMessage" />
  <wsdl:fault
    wsam:Action="http://tempuri.org/IO365ClientProvider/GetEmailAddressO365ConfigureExceptionFault"
    name="O365ConfigureExceptionFault"
    message="tns:IO365ClientProvider_GetEmailAddress_O365ConfigureExceptionFault_FaultMessage" />
</wsdl:operation>
```

Upon receiving the **IO365ClientProvider_GetEmailAddress_InputMessage** request message, the protocol server marks the password change status as fixed. Upon successful completion of the action, the server MUST respond with **IO365ClientProvider_GetEmailAddress_OutputMessage**. In the event of a failure, an appropriate SOAP fault MUST be sent to the client as specified in section [2.2.2.1](#).

3.10.5.7.1 Messages

3.10.5.7.1.1 IO365ClientProvider_GetEmailAddress_InputMessage

This is the request for the **GetEmailAddress** operation.

```
<wsdl:message name="IO365ClientProvider_GetEmailAddress_InputMessage">
  <wsdl:part name="parameters" element="tns:GetEmailAddress" />
</wsdl:message>
```

This message MUST be sent with the following SOAP action.

<http://tempuri.org/IProvider/GetEmailAddress>

The body of the SOAP message MUST contain the **GetEmailAddress** element.

3.10.5.7.1.2 IO365ClientProvider_GetEmailAddress_OutputMessage

This is the response for the **GetEmailAddress** operation.

```
<wsdl:message name="IO365ClientProvider_GetEmailAddress_OutputMessage">
  <wsdl:part name="parameters" element="tns:GetEmailAddressResponse" />
</wsdl:message>
```

This message MUST be sent with the following SOAP action.

<http://tempuri.org/IProvider/GetEmailAddressResponse>

The body of the SOAP message MUST contain the **GetEmailAddressResponse** element.

3.10.5.7.2 Elements

3.10.5.7.2.1 GetEmailAddress

This element specifies input values for the **GetEmailAddress** operation.

```
<xs:element name="GetEmailAddress">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" name="localuser" nillable="true" type="xs:string" />
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

localuser: A string that contains the name of the local user whose email address was queried.

3.10.5.7.2.2 GetEmailAddressResponse

This element specifies output values for the **GetEmailAddress** operation.

```
<xs:element name="GetEmailAddressResponse">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" name="GetEmailAddressResult" nillable="true" type="xs:string" />
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

GetEmailAddressResult: A string that contains the email address of the specified user.

3.10.6 Timer Events

None.

3.10.7 Other Local Events

None.

3.11 Client Notification Service Contract Details

3.11.1 Abstract Data Model

None.[<24>](#)

3.11.2 Timers

None.

3.11.3 Initialization

None.

3.11.4 Higher-Layer Triggered Events

None.

3.11.5 Message Processing Events and Sequencing Rules

OperationContract	Description
IClientRegistrationService.RegisterClient	Registers a client callback channel to the server.
IClientNotificationCallback.NotificationReceived	Indicates a notification event has been received from server.
IClientNotificationProvider.NotifyClientByName	Sends a notification to a client with the specified machine name.
IClientNotificationProvider.NotifyClientById	Sends a notification to a client with the specified SID.
IClientNotificationProvider.NotifyAllClients	Sends a notification to all online clients.

3.11.5.1 IClientRegistrationService.RegisterClient

The operation registers the client callback channel to the server.

```
<wsdl:operation name="RegisterClient">
  <wsdl:input wsam:Action="http://tempuri.org/IClientRegistrationService/RegisterClient"
  message="tns:IClientRegistrationService RegisterClient InputMessage" />
</wsdl:operation>
```

Upon receiving the **IClientRegistrationService_RegisterClient_InputMessage** request message, the protocol server adds the callback channel handle to its dictionary and the server, the protocol server MAY send notification messages through this channel.

3.11.5.1.1 Messages

3.11.5.1.1.1 IClientRegistrationService_RegisterClient_InputMessage

This is the request for the **RegisterClient** operation.

```
<wsdl:message name="IClientRegistrationService_RegisterClient_InputMessage">
  <wsdl:part name="parameters" element="tns:RegisterClient" />
</wsdl:message>
```

The message MUST be sent with the following SOAP action.

```
http://tempuri.org/IClientRegistrationService/RegisterClient
```

The body of the SOAP message MUST contain the **RegisterClient** element.

3.11.5.1.2 Elements

3.11.5.1.2.1 RegisterClient

This element specifies input values for the RegisterClient operation.

```
<xss:element name="RegisterClient">
  <xss:complexType>
    <xss:sequence>
      <xss:element minOccurs="0" name="clientId" nillable="true" type="xss:string" />
    </xss:sequence>
  </xss:complexType>
</xss:element>
```

```
</xs:complexType>
</xs:element>
```

clientId: A string representing the ID of the client.

3.11.5.2 IClientNotificationCallback.NotificationReceived

The operation is a callback that processes a notification message from the server.

```
<wsdl:operation name="NotificationReceived">
  <wsdl:output
    wsam:Action="http://tempuri.org/IClientRegistrationService/NotificationReceived"
    message="tns:IClientRegistrationService_NotificationReceived_OutputCallbackMessage" />
  <wsdl:input
    wsam:Action="http://tempuri.org/IClientRegistrationService/NotificationReceivedResponse"
    message="tns:IClientRegistrationService NotificationReceived InputCallbackMessage" />
</wsdl:operation>
```

3.11.5.2.1 Messages

3.11.5.2.1.1 IClientNotificationCallback_NotificationReceived_OutputCallbackMessage

This message is the request for the **NotificationReceived** operation.

```
<wsdl:message name="IClientRegistrationService_NotificationReceived_OutputCallbackMessage">
  <wsdl:part name="parameters" element="tns:NotificationReceived" />
</wsdl:message>
```

The message MUST be sent with the following SOAP action:

```
http://tempuri.org/IClientRegistrationService/NotificationReceived
```

The body of the SOAP message MUST contain the **NotificationReceived** element.

3.11.5.2.1.2 IClientNotificationCallback_NotificationReceived_InputCallbackMessage

This message is the response for the **NotificationReceived** operation.

```
<wsdl:message name="IClientRegistrationService_NotificationReceived_InputCallbackMessage">
  <wsdl:part name="parameters" element="tns:NotificationReceivedResponse" />
</wsdl:message>
```

The message MUST be sent with the following SOAP action:

```
http://tempuri.org/IClientRegistrationService/NotificationReceived
```

The body of the SOAP message MUST contain the **NotificationReceivedResponse** element.

3.11.5.2.2 Elements

3.11.5.2.2.1 NotificationReceived

This element specifies input values for the **NotificationReceived** operation.

```
<xs:element name="NotificationReceived">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" name="messageId" type="xs:unsignedInt" />
      <xs:element minOccurs="0" name="message" nillable="true" type="xs:string" />
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

messageId: An integer representing the ID of the notification message.

message: A string that contains the content of the notification message.

3.11.5.2.2 NotificationReceivedResponse

This element specifies input values for the **NotificationReceivedResponse** operation.

```
<xs:element name="NotificationReceivedResponse">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" name="NotificationReceivedResult" type="xs:boolean" />
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

NotificationReceivedResult: A Boolean where TRUE indicates that the notification was successfully written; otherwise, the value is FALSE.

3.11.5.3 IClientNotificationProvider.NotifyClientByName

The operation sends a notification message to a client by using the machine name.

```
<wsdl:operation name="NotifyClientByName">
  <wsdl:input
    wsam:Action="http://tempuri.org/IClientNotificationProvider/NotifyClientByName"
    message="tns:IClientNotificationProvider_NotifyClientByName_InputMessage" />
  <wsdl:output
    wsam:Action="http://tempuri.org/ClientNotificationProvider/NotifyClientByNameResponse"
    message="tns:IClientNotificationProvider_NotifyClientByName_OutputMessage" />
</wsdl:operation>
```

3.11.5.3.1 Messages

3.11.5.3.1.1 IClientNotificationProvider_NotifyClientByName_InputMessage

This message is the request for the **NotifyClientByName** operation.

```
<wsdl:message name="IClientNotificationProvider_NotifyClientByName_InputMessage">
  <wsdl:part name="parameters" element="tns:NotifyClientByName" />
</wsdl:message>
```

The message MUST be sent with the following SOAP action:

```
http://tempuri.org/IClientNotificationProvider/NotifyClientByName
```

The body of the SOAP message MUST contain the **NotifyClientByName** element.

3.11.5.3.1.2 IClientNotificationProvider_NotifyClientByName_OutputMessage

This message is the response for the **NotifyClientByName** operation.

```
<wsdl:message name="IClientNotificationProvider NotifyClientByName OutputMessage">
  <wsdl:part name="parameters" element="tns:NotifyClientByNameResponse" />
</wsdl:message>
```

The message MUST be sent with the following SOAP action:

```
http://tempuri.org/ClientNotificationProvider/NotifyClientByNameResponse
```

The body of the SOAP message MUST contain the **NotifyClientByNameResponse** element.

3.11.5.3.2 Elements

3.11.5.3.2.1 NotifyClientByName

This element specifies input values for the **NotifyClientByName** operation.

```
<xs:element name="NotifyClientByName">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" name="name" nillable="true" type="xs:string" />
      <xs:element minOccurs="0" name="messageId" type="xs:unsignedInt" />
      <xs:element minOccurs="0" name="message" nillable="true" type="xs:string" />
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

name: A string representing the ID of the client.

messageId: An integer representing the ID of the client notification message.

message: A string that contains the content of the client notification message.

3.11.5.3.2.2 NotifyClientByNameResponse

This element specifies output values for the **NotifyClientByName** operation.

```
<xs:element name="NotifyClientByNameResponse">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" name="NotifyClientByNameResult" type="xs:boolean" />
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

NotifyClientByNameResult: A Boolean where TRUE indicates that the notification was successfully sent to the client; otherwise, it is FALSE.

3.11.5.4 IClientNotificationProvider.NotifyClientId

The operation sends a notification message to a client by using the machine **SID**.

```

<wsdl:operation name="NotifyClientById">
  <wsdl:input
    wsam:Action="http://tempuri.org/IClientNotificationProvider/NotifyClientById"
    message="tns:IClientNotificationProvider_NotifyClientById_InputMessage" />
  <wsdl:output
    wsam:Action="http://tempuri.org/ClientNotificationProvider/NotifyClientByIdResponse"
    message="tns:IClientNotificationProvider_NotifyClientById_OutputMessage" />
</wsdl:operation>

```

3.11.5.4.1 Messages

3.11.5.4.1.1 IClientNotificationProvider_NotifyClientById_InputMessage

This message is the request for the **NotifyClientById** operation.

```

<wsdl:message name="IClientNotificationProvider_NotifyClientById_InputMessage">
  <wsdl:part name="parameters" element="tns:NotifyClientById" />
</wsdl:message>

```

The message MUST be sent with the following SOAP action:

<http://tempuri.org/IClientNotificationProvider/NotifyClientById>

The body of the SOAP message MUST contain the **NotifyClientById** element.

3.11.5.4.1.2 IClientNotificationProvider_NotifyClientById_OutputMessage

This message is the response for the **NotifyClientById** operation.

```

<wsdl:message name="IClientNotificationProvider_NotifyClientById_OutputMessage">
  <wsdl:part name="parameters" element="tns:NotifyClientByIdResponse" />
</wsdl:message>

```

The message MUST be sent with the following SOAP action:

<http://tempuri.org/ClientNotificationProvider/NotifyClientByIdResponse>

The body of the SOAP message MUST contain the **NotifyClientByIdResponse** element.

3.11.5.4.2 Elements

3.11.5.4.2.1 NotifyClientById

This element specifies input values for the **NotifyClientById** operation.

```

<xs:element name="NotifyClientById">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" name="id" nillable="true" type="xs:string" />
      <xs:element minOccurs="0" name="messageId" type="xs:unsignedInt" />
      <xs:element minOccurs="0" name="message" nillable="true" type="xs:string" />
    </xs:sequence>
  </xs:complexType>
</xs:element>

```

id: A string representing the ID of the client.

messageId: An integer representing the ID of the client notification message.

message: A string that contains the content of the client notification message.

3.11.5.4.2.2 NotifyClientIdResponse

This element specifies output values for the **NotifyClientId** operation.

```
<xs:element name="NotifyClientIdResponse">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" name="NotifyClientIdResult" type="xs:boolean" />
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

NotifyClientIdResult: A Boolean where TRUE indicates that the notification was successfully sent to the client; otherwise, it is FALSE.

3.11.5 IClientNotificationProvider.NotifyAllClients

The operation sends notification messages to all the online clients.

```
<wsdl:operation name="NotifyAllClients">
  <wsdl:input
    wsam:Action="http://tempuri.org/IClientNotificationProvider/NotifyAllClients"
    message="tns:IClientNotificationProvider_NotifyAllClients_InputMessage" />
  <wsdl:output
    wsam:Action="http://tempuri.org/ClientNotificationProvider/NotifyAllClientsResponse"
    message="tns:IClientNotificationProvider_NotifyAllClients_OutputMessage" />
</wsdl:operation>
```

3.11.5.1 Messages

3.11.5.1.1 IClientNotificationProvider_NotifyAllClients_InputMessage

This message is the request for the **NotifyAllClients** operation.

```
<wsdl:message name="IClientNotificationProvider_NotifyAllClients_InputMessage">
  <wsdl:part name="parameters" element="tns:NotifyAllClients" />
</wsdl:message>
```

The message MUST be sent with the following SOAP action:

```
http://tempuri.org/IClientNotificationProvider/NotifyAllClients
```

The body of the SOAP message MUST contain the **NotifyAllClients** element.

3.11.5.1.2 IClientNotificationProvider_NotifyAllClients_OutputMessage

This message is the response for the **NotifyAllClients** operation.

```
<wsdl:message name="IClientNotificationProvider_NotifyAllClients_OutputMessage">
```

```
<wsdl:part name="parameters" element="tns:NotifyAllClientsResponse" />
</wsdl:message>
```

The message MUST be sent with the following SOAP action:

```
http://tempuri.org/ClientNotificationProvider/NotifyAllClientsResponse
```

The body of the SOAP message MUST contain the **NotifyAllClientsResponse** element.

3.11.5.5.2 Elements

3.11.5.5.2.1 NotifyAllClients

This element specifies input values for the **NotifyAllClients** operation.

```
<xs:element name="NotifyAllClients">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" name="messageId" type="xs:unsignedInt" />
      <xs:element minOccurs="0" name="message" nillable="true" type="xs:string" />
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

messageId: An integer representing the ID of the notification message sent to all the clients.

message: A string that contains the content of the notification message sent to all the clients.

3.11.5.5.2.2 NotifyAllClientsResponse

This element specifies output values for the **NotifyAllClients** operation.

```
<xs:element name="NotifyAllClientsResponse">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" name="NotifyAllClientsResult" type="NotificationResults"
    />
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

NotifyAllClientsResult: A **NotificationResults** (section [2.2.4.11.2](#)) complex type where TRUE indicates that the notification was successfully sent to all the clients; otherwise, the value is FALSE.

4 Protocol Examples

4.1 Get the Computer Backup Service Status

The following is the SOAP request message that can be sent to get the status of the Client Computer Backup Service.

```
<s:Envelope xmlns:a="http://www.w3.org/2005/08/addressing"
xmlns:s="http://www.w3.org/2003/05/soap-envelope">
  <s:Header>
    <a:Action
s:mustUnderstand="1">http://tempuri.org/IPCBackupServerProvider/GetServiceStatus</a:Action>
    <a:MessageID>urn:uuid:18c442b8-7715-4895-ae63-1d036d073091</a:MessageID>
    <a:ReplyTo>
      <a:Address>http://www.w3.org/2005/08/addressing/anonymous</a:Address>
    </a:ReplyTo>
    <a:To s:mustUnderstand="1">net.tcp://liming-
sbs1:6602/Microsoft.WindowsServerSolutions.wssg_pc_backup_server/Microsoft.WindowsServerSolutions.DataProtection.PCBackup.BackupUtil.WcfContracts.IPCBackupServerProvider</a:To>
  </s:Header>
  <s:Body>
    <GetServiceStatus xmlns="http://tempuri.org/"></GetServiceStatus>
  </s:Body>
</s:Envelope>
```

The following is one example of the SOAP response message for the above request.

```
<s:Envelope xmlns:a="http://www.w3.org/2005/08/addressing"
xmlns:s="http://www.w3.org/2003/05/soap-envelope">
  <s:Header>
    <a:Action
s:mustUnderstand="1">http://tempuri.org/IPCBackupServerProvider/GetServiceStatusResponse</a:Action>
  </s:Header>
  <s:Body>
    <GetServiceStatusResponse xmlns="http://tempuri.org/">
      <GetServiceStatusResult
        xmlns:d4p1="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.DataProtection.PCBackup.BackupUtil.WcfContracts" xmlns:i="http://www.w3.org/2001/XMLSchema-instance">
        <d4p1:Ready>true</d4p1:Ready>
      </GetServiceStatusResult>
    </GetServiceStatusResponse>
  </s:Body>
</s:Envelope>
```

5 Security

5.1 Security Considerations for Implementers

The Provider Framework protocol is recommended to use TCP transport security in order to secure the communication between protocol client and protocol server, as well as to support authentication. The protocol is recommended to support two authentication types:

1. By user identity
2. By machine identity

Each provider can specify its appropriate authentication type.

5.1.1 User Identity

Stream security settings are recommended to be bound to the endpoint, with protection level configured to support encryption and sign. The channel factory client credential is recommended to be set to the credential of current application logon user, or from the current user of the logon session. Kerberos authentication protocol is used. For more information about Kerberos authentication protocol, see [\[RFC4120\]](#) and [\[MS-KILE\]](#).

More specifically, implementation is recommended to use WindowsStreamSecurityBindingElement, setting ProtectionLevel = EncryptAndSign.

5.1.2 Machine Identity

Channel security using an SSL stream is recommended to be bound to the endpoint, specifying to require client certificate. SSL authentication protocol is used. For more information about SSL authentication protocol, see [\[RFC2246\]](#).

More specifically, use SslStreamSecurityBindingElement, setting RequireClientCertificate to true.[<25>](#)

5.2 Index of Security Parameters

None.

6 Appendix A: Full WSDL

6.1 Client File Backup Provider Service WSDL

6.1.1 wsdl

```
<?xml version="1.0" encoding="utf-8"?>
<wsdl:definitions xmlns:wsap="http://schemas.xmlsoap.org/ws/2004/08/addressing/policy"
  xmlns:wsa10="http://www.w3.org/2005/08/addressing" xmlns:tns="http://tempuri.org/"
  xmlns:msc="http://schemas.microsoft.com/ws/2005/12/wsdl/contract"
  xmlns:soapenc="http://schemas.xmlsoap.org/soap/encoding/"
  xmlns:soap="http://schemas.xmlsoap.org/wsdl/soap/"
  xmlns:wp="http://schemas.xmlsoap.org/ws/2004/09/policy"
  xmlns:wsam="http://www.w3.org/2007/05/addressing/metadata"
  xmlns:wsa="http://schemas.xmlsoap.org/ws/2004/08/addressing"
  xmlns:wsaw="http://www.w3.org/2006/05/addressing/wsdl"
  xmlns:soap12="http://schemas.xmlsoap.org/wsdl/soap12/" xmlns:wsu="http://docs.oasis-
  open.org/wss/2004/01/oasis-200401-wss-wssecurity-utility-1.0.xsd"
  xmlns:xsd="http://www.w3.org/2001/XMLSchema" name="UserConfigProvider"
  targetNamespace="http://tempuri.org/" xmlns:wsdl="http://schemas.xmlsoap.org/wsdl/">
  <wsp:Policy wsu:Id="CustomBinding_IUserConfigProvider_policy">
    <wsp:ExactlyOne>
      <wsp:All>
        <msb:BinaryEncoding
          xmlns:msb="http://schemas.microsoft.com/ws/2004/mspolicy/netbinary1" />
        <sp:TransportBinding xmlns:sp="http://schemas.xmlsoap.org/ws/2005/07/securitypolicy">
          <wsp:Policy>
            <sp:TransportToken>
              <wsp:Policy>
                <msf:WindowsTransportSecurity
                  xmlns:msf="http://schemas.microsoft.com/ws/2006/05/framing/policy">
                  <msf:ProtectionLevel>EncryptAndSign</msf:ProtectionLevel>
                  </msf:WindowsTransportSecurity>
                </wsp:Policy>
              </sp:TransportToken>
              <sp:AlgorithmSuite>
                <wsp:Policy>
                  <sp:Basic256 />
                </wsp:Policy>
              </sp:AlgorithmSuite>
              <sp:Layout>
                <wsp:Policy>
                  <sp:Strict />
                </wsp:Policy>
              </sp:Layout>
            </wsp:Policy>
          </sp:TransportBinding>
          <wsaw:UsingAddressing />
        </wsp:All>
      </wsp:ExactlyOne>
    </wsp:Policy>
  <wsdl:types>
    <xsd:schema targetNamespace="http://tempuri.org/Imports">
      <xsd:import schemaLocation="" namespace="http://tempuri.org/" />
      <xsd:import schemaLocation="" namespace="http://schemas.microsoft.com/2003/10/Serialization/" />
      <xsd:import schemaLocation="" namespace="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.DataProte
      ction.FileBackup" />
      <xsd:import schemaLocation="" namespace="http://schemas.datacontract.org/2004/07/System" />
    </xsd:schema>
  </wsdl:types>
  <wsdl:message name="IUserConfigProvider_GetUserSettingAsync_InputMessage">
    <wsdl:part name="parameters" element="tns:GetUserSettingAsync" />
  </wsdl:message>
```

```

<wsdl:message name="IUserConfigProvider_GetUserManagedSettingAsync_InputMessage">
  <wsdl:part name="parameters" element="tns:GetUserManagedSettingAsync" />
</wsdl:message>
<wsdl:message name="IUserConfigProvider.GetUserSettingCompleted_OutputCallbackMessage">
  <wsdl:part name="parameters" element="tns:GetUserSettingCompleted" />
</wsdl:message>
<wsdl:message name="IUserConfigProvider_GetClientManagedCompleted_OutputCallbackMessage">
  <wsdl:part name="parameters" element="tns:GetClientManagedCompleted" />
</wsdl:message>
<wsdl:portType name="IUserConfigProvider">
  <wsdl:operation name=" GetUserSettingAsync">
    <wsdl:input wsaw:Action="http://tempuri.org/IUserConfigProvider/ GetUserSettingAsync"
message="tns:IUserConfigProvider.GetUserSettingAsync_InputMessage" />
  </wsdl:operation>
  <wsdl:operation name=" GetUserManagedSettingAsync">
    <wsdl:input
      wsaw:Action="http://tempuri.org/IUserConfigProvider/ GetUserManagedSettingAsync"
message="tns:IUserConfigProvider.GetUserManagedSettingAsync_InputMessage" />
  </wsdl:operation>
  <wsdl:operation name=" GetUserSettingCompleted">
    <wsdl:output
      wsaw:Action="http://tempuri.org/IUserConfigProvider/ GetUserSettingCompleted"
message="tns:IUserConfigProvider.GetUserSettingCompleted_OutputCallbackMessage" />
  </wsdl:operation>
  <wsdl:operation name=" GetClientManagedCompleted">
    <wsdl:output
      wsaw:Action="http://tempuri.org/IUserConfigProvider/ GetClientManagedCompleted"
message="tns:IUserConfigProvider.GetClientManagedCompleted_OutputCallbackMessage" />
  </wsdl:operation>
</wsdl:portType>
<wsdl:binding name="CustomBinding_IUserConfigProvider" type="tns:IUserConfigProvider">
  <wsp:PolicyReference URI="#CustomBinding_IUserConfigProvider_policy" />
  <soap12:binding transport="http://schemas.microsoft.com/soap/tcp" />
  <wsdl:operation name=" GetUserSettingAsync">
    <soap12:operation
      soapAction="http://tempuri.org/IUserConfigProvider/ GetUserSettingAsync" style="document" />
    <wsdl:input>
      <soap12:body use="literal" />
    </wsdl:input>
  </wsdl:operation>
  <wsdl:operation name=" GetUserManagedSettingAsync">
    <soap12:operation
      soapAction="http://tempuri.org/IUserConfigProvider/ GetUserManagedSettingAsync"
style="document" />
    <wsdl:input>
      <soap12:body use="literal" />
    </wsdl:input>
  </wsdl:operation>
  <wsdl:operation name=" GetUserSettingCompleted">
    <soap12:operation
      soapAction="http://tempuri.org/IUserConfigProvider/ GetUserSettingCompleted" style="document"
/>
    <wsdl:output>
      <soap12:body use="literal" />
    </wsdl:output>
  </wsdl:operation>
  <wsdl:operation name=" GetClientManagedCompleted">
    <soap12:operation
      soapAction="http://tempuri.org/IUserConfigProvider/ GetClientManagedCompleted"
style="document" />
    <wsdl:output>
      <soap12:body use="literal" />
    </wsdl:output>
  </wsdl:operation>
</wsdl:binding>
<wsdl:service name="UserConfigProvider">
  <wsdl:port name="CustomBinding_IUserConfigProvider"
binding="tns:CustomBinding_IUserConfigProvider">

```

```

<soap12:address
location="net.tcp://serverName:6602/Microsoft.WindowsServerSolutions.DataProtection.FileBackup.UserConfigProvider/Microsoft.WindowsServerSolutions.DataProtection.FileBackup.IUserConfigProvider" />
<wsa10:EndpointReference>

<wsa10:Address>net.tcp://serverName:6602/Microsoft.WindowsServerSolutions.DataProtection.FileBackup.UserConfigProvider/Microsoft.WindowsServerSolutions.DataProtection.FileBackup.IUserConfigProvider</wsa10:Address>
    <Identity xmlns="http://schemas.xmlsoap.org/ws/2006/02/addressingidentity">
        <Spn>host/serverName.domain</Spn>
    </Identity>
    <wsa10:EndpointReference>
    </wsdl:port>
    </wsdl:service>
</wsdl:definitions>
```

6.1.2 <http://tempuri.org/>

```

<?xml version="1.0" encoding="utf-8"?>
<xss:schema xmlns:tns="http://tempuri.org/" elementFormDefault="qualified"
targetNamespace="http://tempuri.org/" xmlns:xs="http://www.w3.org/2001/XMLSchema">
    <xss:import schemaLocation="" namespace="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.DataProtection.FileBackup" />
    <xss:element name=" GetUserSettingAsync">
        <xss:complexType>
            <xss:sequence />
        </xss:complexType>
    </xss:element>
    <xss:element name=" GetUserManagedSettingAsync">
        <xss:complexType>
            <xss:sequence>
                <xss:element minOccurs="0" name="userName" nillable="true" type="xs:string" />
            </xss:sequence>
        </xss:complexType>
    </xss:element>
    <xss:element name=" GetUserSettingCompleted">
        <xss:complexType>
            <xss:sequence>
                <xss:element
xmlns:q1="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.DataProtection.FileBackup" minOccurs="0" name="exception" nillable="true" type="q1:ClientFileBackupException" />
            <xss:element
xmlns:q2="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.DataProtection.FileBackup" minOccurs="0" name="configSet" nillable="true" type="q2:ConfigurationSet" />
            </xss:sequence>
        </xss:complexType>
    </xss:element>
    <xss:element name=" GetClientManagedCompleted">
        <xss:complexType>
            <xss:sequence>
                <xss:element
xmlns:q3="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.DataProtection.FileBackup" minOccurs="0" name="exception" nillable="true" type="q3:ClientFileBackupException" />
            <xss:element
xmlns:q4="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.DataProtection.FileBackup" minOccurs="0" name="isManaged" type="q4:ManagedStatus" />
            </xss:sequence>
        </xss:complexType>
    </xss:element>
</xss:schema>
```

6.1.3 <http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.DataProtection.FileBackup>

```
<?xml version="1.0" encoding="utf-8"?>
<xss:schema
  xmlns:tns="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.DataProtection.FileBackup" elementFormDefault="qualified"
  targetNamespace="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.DataProtection.FileBackup" xmlns:xss="http://www.w3.org/2001/XMLSchema">
  <xss:import schemaLocation="" namespace="http://schemas.datacontract.org/2004/07/System" />
  <xss:complexType name="ClientFileBackupException">
    <xss:complexContent mixed="false">
      <xss:extension xmlns:q1="http://schemas.datacontract.org/2004/07/System"
        base="q1:Exception" />
    </xss:complexContent>
  </xss:complexType>
  <xss:element name="ClientFileBackupException" nillable="true"
    type="tns:ClientFileBackupException" />
  <xss:complexType name="ConfigurationSet">
    <xss:sequence>
      <xss:element xmlns:q2="http://schemas.datacontract.org/2004/07/System" minOccurs="0"
        name="CfgVersion" nillable="true" type="q2:Version" />
      <xss:element minOccurs="0" name="FrequencyInMinutes" type="xs:unsignedInt" />
      <xss:element minOccurs="0" name="IsEnabled" type="xs:boolean" />
      <xss:element minOccurs="0" name="RetentionInMonths" type="xs:unsignedInt" />
      <xss:element minOccurs="0" name="SourceLibraries" type="tns:SourceLibrary" />
      <xss:element minOccurs="0" name="TargetPath" nillable="true" type="xs:string" />
      <xss:element minOccurs="0" name="UnmanagedUsers" nillable="true" type="xs:string" />
    </xss:sequence>
  </xss:complexType>
  <xss:element name="ConfigurationSet" nillable="true" type="tns:ConfigurationSet" />
  <xss:simpleType name="SourceLibrary">
    <xss:restriction base="xs:string">
      <xss:enumeration value="DocumentsAndDesktop" />
      <xss:enumeration value="NoMediaLibraries" />
      <xss:enumeration value="All" />
    </xss:restriction>
  </xss:simpleType>
  <xss:element name="SourceLibrary" nillable="true" type="tns:SourceLibrary" />
  <xss:simpleType name="ManagedStatus">
    <xss:restriction base="xs:string">
      <xss:enumeration value="Managed" />
      <xss:enumeration value="NotManaged" />
      <xss:enumeration value="Unknown" />
    </xss:restriction>
  </xss:simpleType>
  <xss:element name="ManagedStatus" nillable="true" type="tns:ManagedStatus" />
</xss:schema>
```

6.1.4 <http://schemas.microsoft.com/2003/10/Serialization/>

```
<?xml version="1.0" encoding="utf-8"?>
<xss:schema xmlns:tns="http://schemas.microsoft.com/2003/10/Serialization/"
  attributeFormDefault="qualified" elementFormDefault="qualified"
  targetNamespace="http://schemas.microsoft.com/2003/10/Serialization/"
  xmlns:xss="http://www.w3.org/2001/XMLSchema">
  <xss:element name="anyType" nillable="true" type="xs:anyType" />
  <xss:element name="anyURI" nillable="true" type="xs:anyURI" />
  <xss:element name="base64Binary" nillable="true" type="xs:base64Binary" />
  <xss:element name="boolean" nillable="true" type="xs:boolean" />
  <xss:element name="byte" nillable="true" type="xs:byte" />
  <xss:element name="dateTime" nillable="true" type="xs:dateTime" />
  <xss:element name="decimal" nillable="true" type="xs:decimal" />
  <xss:element name="double" nillable="true" type="xs:double" />
  <xss:element name="float" nillable="true" type="xs:float" />
  <xss:element name="int" nillable="true" type="xs:int" />
  <xss:element name="long" nillable="true" type="xs:long" />
```

```

<xs:element name="QName" nillable="true" type="xs:QName" />
<xs:element name="short" nillable="true" type="xs:short" />
<xs:element name="string" nillable="true" type="xs:string" />
<xs:element name="unsignedByte" nillable="true" type="xs:unsignedByte" />
<xs:element name="unsignedInt" nillable="true" type="xs:unsignedInt" />
<xs:element name="unsignedLong" nillable="true" type="xs:unsignedLong" />
<xs:element name="unsignedShort" nillable="true" type="xs:unsignedShort" />
<xs:element name="char" nillable="true" type="tns:char" />
<xs:simpleType name="char">
    <xs:restriction base="xs:int" />
</xs:simpleType>
<xs:element name="duration" nillable="true" type="tns:duration" />
<xs:simpleType name="duration">
    <xs:restriction base="xs:duration">
        <xs:pattern value="\-?P{(\d*D)?(T{(\d*M)?(\d*(\.\.\d*)?S)?})?}" />
        <xs:minInclusive value="-P10675199DT2H48M5.4775808S" />
        <xs:maxInclusive value="P10675199DT2H48M5.4775807S" />
    </xs:restriction>
</xs:simpleType>
<xs:element name="guid" nillable="true" type="tns:guid" />
<xs:simpleType name="guid">
    <xs:restriction base="xs:string">
        <xs:pattern value="[\da-fA-F]{8}-[\da-fA-F]{4}-[\da-fA-F]{4}-[\da-fA-F]{12}" />
    </xs:restriction>
</xs:simpleType>
<xs:attribute name="FactoryType" type="xs:QName" />
<xs:attribute name="Id" type="xs:ID" />
<xs:attribute name="Ref" type="xs:IDREF" />
</xs:schema>

```

6.1.5 <http://schemas.datacontract.org/2004/07/System>

```

<?xml version="1.0" encoding="utf-8"?>
<xs:schema xmlns:ser="http://schemas.microsoft.com/2003/10/Serialization/" 
xmlns:tns="http://schemas.datacontract.org/2004/07/System" elementFormDefault="qualified"
targetNamespace="http://schemas.datacontract.org/2004/07/System"
xmlns:xs="http://www.w3.org/2001/XMLSchema">
    <xs:import schemaLocation="" 
namespace="http://schemas.microsoft.com/2003/10/Serialization/" />
    <xs:complexType name="Exception">
        <xs:sequence>
            <xs:any minOccurs="0" maxOccurs="unbounded" namespace="##local" processContents="skip"
/>
        </xs:sequence>
        <xs:attribute ref="ser:FactoryType" />
    </xs:complexType>
    <xs:element name="Exception" nillable="true" type="tns:Exception" />
    <xs:complexType name="Version">
        <xs:sequence>
            <xs:element name="_Build" type="xs:int" />
            <xs:element name="_Major" type="xs:int" />
            <xs:element name="_Minor" type="xs:int" />
            <xs:element name="_Revision" type="xs:int" />
        </xs:sequence>
    </xs:complexType>
    <xs:element name="Version" nillable="true" type="tns:Version" />
</xs:schema>

```

6.2 Client Backup Provider Service WSDL

6.2.1 IPCBackupServerRegister

6.2.1.1 wsdl

```
<?xml version="1.0" encoding="utf-8"?>
<wsdl:definitions xmlns:wsap="http://schemas.xmlsoap.org/ws/2004/08/addressing/policy"
  xmlns:wsa10="http://www.w3.org/2005/08/addressing" xmlns:tns="http://tempuri.org/"
  xmlns:msc="http://schemas.microsoft.com/ws/2005/12/wsdl/contract"
  xmlns:soapenc="http://schemas.xmlsoap.org/soap/encoding/"
  xmlns:soap="http://schemas.xmlsoap.org/wsdl/soap/"
  xmlns:wsp="http://schemas.xmlsoap.org/ws/2004/09/policy"
  xmlns:wsam="http://www.w3.org/2007/05/addressing/metadata"
  xmlns:wsa="http://schemas.xmlsoap.org/ws/2004/08/addressing"
  xmlns:wsaw="http://www.w3.org/2006/05/addressing/wsdl"
  xmlns:soap12="http://schemas.xmlsoap.org/wsdl/soap12/" xmlns:wsu="http://docs.oasis-
  open.org/wss/2004/01/oasis-200401-wss-wssecurity-utility-1.0.xsd"
  xmlns:xsd="http://www.w3.org/2001/XMLSchema" name="PCBackupServerRegisterImpl"
  targetNamespace="http://tempuri.org/" xmlns:wsdl="http://schemas.xmlsoap.org/wsdl/">
  <wsp:Policy wsu:Id="CustomBinding_IPCBackupServerRegister_policy">
    <wsp:ExactlyOne>
      <wsp:All>
        <msb:BinaryEncoding
          xmlns:msb="http://schemas.microsoft.com/ws/2004/mspolicy/netbinary1" />
        <sp:TransportBinding xmlns:sp="http://schemas.xmlsoap.org/ws/2005/07/securitypolicy">
          <wsp:Policy>
            <sp:TransportToken>
              <wsp:Policy>
                <msf:SslTransportSecurity
                  xmlns:msf="http://schemas.microsoft.com/ws/2006/05/framing/policy">
                  <msf:RequireClientCertificate />
                  </msf:SslTransportSecurity>
                </wsp:Policy>
              </sp:TransportToken>
              <sp:AlgorithmSuite>
                <wsp:Policy>
                  <sp:Basic256 />
                </wsp:Policy>
              </sp:AlgorithmSuite>
              <sp:Layout>
                <wsp:Policy>
                  <sp:Strict />
                </wsp:Policy>
              </sp:Layout>
            </wsp:Policy>
          </sp:TransportBinding>
          <wsaw:UsingAddressing />
        </wsp:All>
      </wsp:ExactlyOne>
    </wsp:Policy>
  <wsdl:types>
    <xsd:schema targetNamespace="http://tempuri.org/Imports">
      <xsd:import schemaLocation="" namespace="http://tempuri.org/" />
      <xsd:import schemaLocation="" namespace="http://schemas.datacontract.org/2004/07/System" />
      <xsd:import schemaLocation="" namespace="http://schemas.microsoft.com/2003/10/Serialization/" />
      <xsd:import schemaLocation="" namespace="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.DataProte
      ction.PCBackup.BackupUtil.WcfContracts" />
      <xsd:import schemaLocation="" namespace="http://schemas.microsoft.com/2003/10/Serialization/Arrays" />
    </xsd:schema>
  </wsdl:types>
  <wsdl:message name="IPCBackupServerRegister_RegisterBackupClient_InputMessage">
    <wsdl:part name="parameters" element="tns:RegisterBackupClient" />
```

```

    </wsdl:message>
<wsdl:message name="IPCBBackupServerRegister_RegisterBackupClient_OutputMessage">
    <wsdl:part name="parameters" element="tns:RegisterBackupClientResponse" />
</wsdl:message>
<wsdl:message
name="IPCBBackupServerRegister RegisterBackupClient InvalidOperationExceptionFault FaultMessage">
    <wsdl:part xmlns:q1="http://schemas.datacontract.org/2004/07/System" name="detail"
element="q1:InvalidOperationException" />
</wsdl:message>
<wsdl:message name="IPCBBackupServerRegister KeepAlive InputMessage">
    <wsdl:part name="parameters" element="tns:KeepAlive" />
</wsdl:message>
<wsdl:message name="IPCBBackupServerRegister_KeepAlive_OutputMessage">
    <wsdl:part name="parameters" element="tns:KeepAliveResponse" />
</wsdl:message>
<wsdl:message name="IPCBBackupServerRegister VolumeCalculatorProgress InputMessage">
    <wsdl:part name="parameters" element="tns:VolumeCalculatorProgress" />
</wsdl:message>
<wsdl:message name="IPCBBackupServerRegister_GetClientPriority_OutputCallbackMessage">
    <wsdl:part name="parameters" element="tns:GetClientPriority" />
</wsdl:message>
<wsdl:message name="IPCBBackupServerRegister_GetClientPriority InputCallbackMessage">
    <wsdl:part name="parameters" element="tns:GetClientPriorityResponse" />
</wsdl:message>
<wsdl:message name="IPCBBackupServerRegister_OnBatteryPower_OutputCallbackMessage">
    <wsdl:part name="parameters" element="tns:OnBatteryPower" />
</wsdl:message>
<wsdl:message name="IPCBBackupServerRegister OnBatteryPower InputCallbackMessage">
    <wsdl:part name="parameters" element="tns:OnBatteryPowerResponse" />
</wsdl:message>
<wsdl:message name="IPCBBackupServerRegister_StartBackup_OutputCallbackMessage">
    <wsdl:part name="parameters" element="tns:StartBackup" />
</wsdl:message>
<wsdl:message name="IPCBBackupServerRegister_StartBackup_InputCallbackMessage">
    <wsdl:part name="parameters" element="tns:StartBackupResponse" />
</wsdl:message>
<wsdl:message
name="IPCBBackupServerRegister_StartBackup_PCBBackupClientFaultFault_FaultMessage">
    <wsdl:part
xmlns:q2="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.DataProtection.PCBackup.BackupUtil.WcfContracts" name="detail" element="q2:PCBackupClientFault" />
</wsdl:message>
<wsdl:message name="IPCBBackupServerRegister_CancelBackup_OutputCallbackMessage">
    <wsdl:part name="parameters" element="tns:CancelBackup" />
</wsdl:message>
<wsdl:message name="IPCBBackupServerRegister_CancelBackup_InputCallbackMessage">
    <wsdl:part name="parameters" element="tns:CancelBackupResponse" />
</wsdl:message>
<wsdl:message
name="IPCBBackupServerRegister_CancelBackup_PCBBackupClientFaultFault_FaultMessage">
    <wsdl:part
xmlns:q3="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.DataProtection.PCBackup.BackupUtil.WcfContracts" name="detail" element="q3:PCBackupClientFault" />
</wsdl:message>
<wsdl:message
name="IPCBBackupServerRegister_UpdateBackupConfiguration_OutputCallbackMessage">
    <wsdl:part name="parameters" element="tns:UpdateBackupConfiguration" />
</wsdl:message>
<wsdl:message name="IPCBBackupServerRegister_SendBackupProgress_OutputCallbackMessage">
    <wsdl:part name="parameters" element="tns:SendBackupProgress" />
</wsdl:message>
<wsdl:message name="IPCBBackupServerRegister_GetFolderChildren_OutputCallbackMessage">
    <wsdl:part name="parameters" element="tns:GetFolderChildren" />
</wsdl:message>
<wsdl:message name="IPCBBackupServerRegister_GetFolderChildren_InputCallbackMessage">
    <wsdl:part name="parameters" element="tns:GetFolderChildrenResponse" />
</wsdl:message>

```

```

<wsdl:message
  name="IPCBBackupServerRegister_GetFolderChildren_PCBBackupClientFaultFault_FaultMessage">
  <wsdl:part
    xmlns:q4="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.DataProtection.PCBackup.BackupUtil.WcfContracts" name="detail" element="q4:PCBackupClientFault" />
</wsdl:message>
<wsdl:message name="IPCBBackupServerRegister_CalculateVolumeAsync_OutputCallbackMessage">
  <wsdl:part name="parameters" element="tns:CalculateVolumeAsync" />
</wsdl:message>
<wsdl:message name="IPCBBackupServerRegister_CalculateVolumeAsync_InputCallbackMessage">
  <wsdl:part name="parameters" element="tns:CalculateVolumeAsyncResponse" />
</wsdl:message>
<wsdl:message
  name="IPCBBackupServerRegister_CalculateVolumeAsync_PCBBackupClientFaultFault_FaultMessage">
  <wsdl:part
    xmlns:q5="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.DataProtection.PCBackup.BackupUtil.WcfContracts" name="detail" element="q5:PCBackupClientFault" />
</wsdl:message>
<wsdl:message
  name="IPCBBackupServerRegister_CleanFolderSizeCalculation_OutputCallbackMessage">
  <wsdl:part name="parameters" element="tns:CleanFolderSizeCalculation" />
</wsdl:message>
<wsdl:message name="IPCBBackupServerRegister_GetConnectedVolumes_OutputCallbackMessage">
  <wsdl:part name="parameters" element="tns:GetConnectedVolumes" />
</wsdl:message>
<wsdl:message name="IPCBBackupServerRegister_GetConnectedVolumes_InputCallbackMessage">
  <wsdl:part name="parameters" element="tns:GetConnectedVolumesResponse" />
</wsdl:message>
<wsdl:message
  name="IPCBBackupServerRegister_GetConnectedVolumes_PCBBackupClientFaultFault_FaultMessage">
  <wsdl:part
    xmlns:q6="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.DataProtection.PCBackup.BackupUtil.WcfContracts" name="detail" element="q6:PCBackupClientFault" />
</wsdl:message>
<wsdl:message name="IPCBBackupServerRegister_RescanVolumesAsync_OutputCallbackMessage">
  <wsdl:part name="parameters" element="tns:RescanVolumesAsync" />
</wsdl:message>
<wsdl:portType name="IPCBBackupServerRegister">
  <wsdl:operation name="RegisterBackupClient">
    <wsdl:input
      wsaw:Action="http://tempuri.org/IPCBBackupServerRegister/RegisterBackupClient"
      message="tns:IPCBBackupServerRegister_RegisterBackupClient_InputMessage" />
    <wsdl:output
      wsaw:Action="http://tempuri.org/IPCBBackupServerRegister/RegisterBackupClientResponse"
      message="tns:IPCBBackupServerRegister_RegisterBackupClient_OutputMessage" />
    <wsdl:fault
      wsaw:Action="http://tempuri.org/IPCBBackupServerRegister/RegisterBackupClientInvalidOperationExceptionFault"
      name="InvalidOperationExceptionFault"
      message="tns:IPCBBackupServerRegister_RegisterBackupClient_InvalidOperationExceptionFault_FaultMessage" />
  </wsdl:operation>
  <wsdl:operation name="KeepAlive">
    <wsdl:input wsaw:Action="http://tempuri.org/IPCBBackupServerRegister/KeepAlive"
      message="tns:IPCBBackupServerRegister_KeepAlive_InputMessage" />
    <wsdl:output wsaw:Action="http://tempuri.org/IPCBBackupServerRegister/KeepAliveResponse"
      message="tns:IPCBBackupServerRegister_KeepAlive_OutputMessage" />
  </wsdl:operation>
  <wsdl:operation name="VolumeCalculatorProgress">
    <wsdl:input
      wsaw:Action="http://tempuri.org/IPCBBackupServerRegister/VolumeCalculatorProgress"
      message="tns:IPCBBackupServerRegister_VolumeCalculatorProgress_InputMessage" />
  </wsdl:operation>
  <wsdl:operation name="GetClientPriority">
    <wsdl:output wsaw:Action="http://tempuri.org/IPCBBackupServerRegister/GetClientPriority"
      message="tns:IPCBBackupServerRegister_GetClientPriority_OutputCallbackMessage" />
    <wsdl:input
      wsaw:Action="http://tempuri.org/IPCBBackupServerRegister/GetClientPriorityResponse"
      message="tns:IPCBBackupServerRegister_GetClientPriority_InputCallbackMessage" />
  </wsdl:operation>

```

```

<wsdl:operation name="OnBatteryPower">
    <wsdl:output wsaw:Action="http://tempuri.org/IPCBackupServerRegister/OnBatteryPower"
message="tns:IPCBackupServerRegister_OnBatteryPower_OutputCallbackMessage" />
    <wsdl:input
wsaw:Action="http://tempuri.org/IPCBackupServerRegister/OnBatteryPowerResponse"
message="tns:IPCBackupServerRegister OnBatteryPower InputCallbackMessage" />
</wsdl:operation>
<wsdl:operation name="StartBackup">
    <wsdl:output wsaw:Action="http://tempuri.org/IPCBackupServerRegister/StartBackup"
message="tns:IPCBackupServerRegister_StartBackup_OutputCallbackMessage" />
    <wsdl:input
wsaw:Action="http://tempuri.org/IPCBackupServerRegister/StartBackupResponse"
message="tns:IPCBackupServerRegister_StartBackup_InputCallbackMessage" />
    <wsdl:fault
wsaw:Action="http://tempuri.org/IPCBackupServerRegister/StartBackupPCBackupClientFaultFault"
name="PCBackupClientFaultFault"
message="tns:IPCBackupServerRegister StartBackup PCBackupClientFaultFault FaultMessage" />
</wsdl:operation>
<wsdl:operation name="CancelBackup">
    <wsdl:output wsaw:Action="http://tempuri.org/IPCBackupServerRegister/CancelBackup"
message="tns:IPCBackupServerRegister_CancelBackup_OutputCallbackMessage" />
    <wsdl:input
wsaw:Action="http://tempuri.org/IPCBackupServerRegister/CancelBackupResponse"
message="tns:IPCBackupServerRegister_CancelBackup_InputCallbackMessage" />
    <wsdl:fault
wsaw:Action="http://tempuri.org/IPCBackupServerRegister/CancelBackupPCBackupClientFaultFault"
name="PCBackupClientFaultFault"
message="tns:IPCBackupServerRegister_CancelBackup_PCBackupClientFaultFault_FaultMessage" />
</wsdl:operation>
<wsdl:operation name="UpdateBackupConfiguration">
    <wsdl:output
wsaw:Action="http://tempuri.org/IPCBackupServerRegister/UpdateBackupConfiguration"
message="tns:IPCBackupServerRegister_UpdateBackupConfiguration_OutputCallbackMessage" />
</wsdl:operation>
<wsdl:operation name="SendBackupProgress">
    <wsdl:output
wsaw:Action="http://tempuri.org/IPCBackupServerRegister/SendBackupProgress"
message="tns:IPCBackupServerRegister_SendBackupProgress_OutputCallbackMessage" />
</wsdl:operation>
<wsdl:operation name="GetFolderChildren">
    <wsdl:output wsaw:Action="http://tempuri.org/IPCBackupServerRegister/GetFolderChildren"
message="tns:IPCBackupServerRegister GetFolderChildren OutputCallbackMessage" />
    <wsdl:input
wsaw:Action="http://tempuri.org/IPCBackupServerRegister/GetFolderChildrenResponse"
message="tns:IPCBackupServerRegister_GetFolderChildren_InputCallbackMessage" />
    <wsdl:fault
wsaw:Action="http://tempuri.org/IPCBackupServerRegister/GetFolderChildrenPCBackupClientFaultF
ault" name="PCBackupClientFaultFault"
message="tns:IPCBackupServerRegister_GetFolderChildren_PCBackupClientFaultFault_FaultMessage"
/>
</wsdl:operation>
<wsdl:operation name="CalculateVolumeAsync">
    <wsdl:output
wsaw:Action="http://tempuri.org/IPCBackupServerRegister/CalculateVolumeAsync"
message="tns:IPCBackupServerRegister_CalculateVolumeAsync_OutputCallbackMessage" />
    <wsdl:input
wsaw:Action="http://tempuri.org/IPCBackupServerRegister/CalculateVolumeAsyncResponse"
message="tns:IPCBackupServerRegister CalculateVolumeAsync InputCallbackMessage" />
    <wsdl:fault
wsaw:Action="http://tempuri.org/IPCBackupServerRegister/CalculateVolumeAsyncPCBackupClientFau
ltFault" name="PCBackupClientFaultFault"
message="tns:IPCBackupServerRegister_CalculateVolumeAsync_PCBackupClientFaultFault_FaultMessa
ge" />
</wsdl:operation>
<wsdl:operation name="CleanFolderPathCalculation">
    <wsdl:output
wsaw:Action="http://tempuri.org/IPCBackupServerRegister/CleanFolderPathCalculation"
message="tns:IPCBackupServerRegister_CleanFolderPathCalculation_OutputCallbackMessage" />
</wsdl:operation>

```

```

<wsdl:operation name="GetConnectedVolumes">
    <wsdl:output
        wsaw:Action="http://tempuri.org/IPCBackupServerRegister/GetConnectedVolumes"
        message="tns:IPCBackupServerRegister_GetConnectedVolumes_OutputCallbackMessage" />
    <wsdl:input
        wsaw:Action="http://tempuri.org/IPCBackupServerRegister/GetConnectedVolumesResponse"
        message="tns:IPCBackupServerRegister_GetConnectedVolumes_InputCallbackMessage" />
    <wsdl:fault
        wsaw:Action="http://tempuri.org/IPCBackupServerRegister/GetConnectedVolumesPCBackupClientFault"
        name="PCBackupClientFaultFault"
        message="tns:IPCBackupServerRegister GetConnectedVolumes PCBackupClientFaultFault FaultMessage" />
</wsdl:operation>
<wsdl:operation name="RescanVolumesAsync">
    <wsdl:output
        wsaw:Action="http://tempuri.org/IPCBackupServerRegister/RescanVolumesAsync"
        message="tns:IPCBackupServerRegister RescanVolumesAsync OutputCallbackMessage" />
    </wsdl:operation>
</wsdl:portType>
<wsdl:binding name="CustomBinding_IPCBackupServerRegister"
type="tns:IPCBackupServerRegister">
    <wsp:PolicyReference URI="#CustomBinding_IPCBackupServerRegister_policy" />
    <soap12:binding transport="http://schemas.microsoft.com/soap/tcp" />
    <wsdl:operation name="RegisterBackupClient">
        <soap12:operation
            soapAction="http://tempuri.org/IPCBackupServerRegister/RegisterBackupClient" style="document" />
        <wsdl:input>
            <soap12:body use="literal" />
        </wsdl:input>
        <wsdl:output>
            <soap12:body use="literal" />
        </wsdl:output>
        <wsdl:fault name="InvalidOperationExceptionFault">
            <soap12:fault use="literal" name="InvalidOperationExceptionFault" namespace="" />
        </wsdl:fault>
    </wsdl:operation>
    <wsdl:operation name="KeepAlive">
        <soap12:operation soapAction="http://tempuri.org/IPCBackupServerRegister/KeepAlive" style="document" />
        <wsdl:input>
            <soap12:body use="literal" />
        </wsdl:input>
        <wsdl:output>
            <soap12:body use="literal" />
        </wsdl:output>
    </wsdl:operation>
    <wsdl:operation name="VolumeCalculatorProgress">
        <soap12:operation
            soapAction="http://tempuri.org/IPCBackupServerRegister/VolumeCalculatorProgress" style="document" />
        <wsdl:input>
            <soap12:body use="literal" />
        </wsdl:input>
    </wsdl:operation>
    <wsdl:operation name="GetClientPriority">
        <soap12:operation
            soapAction="http://tempuri.org/IPCBackupServerRegister/GetClientPriority" style="document" />
        <wsdl:input>
            <soap12:body use="literal" />
        </wsdl:input>
        <wsdl:output>
            <soap12:body use="literal" />
        </wsdl:output>
    </wsdl:operation>
    <wsdl:operation name="OnBatteryPower">
        <soap12:operation
            soapAction="http://tempuri.org/IPCBackupServerRegister/OnBatteryPower" style="document" />
        <wsdl:input>

```

```

        <soap12:body use="literal" />
    </wsdl:input>
    <wsdl:output>
        <soap12:body use="literal" />
    </wsdl:output>
</wsdl:operation>
<wsdl:operation name="StartBackup">
    <soap12:operation soapAction="http://tempuri.org/IPCBackupServerRegister/StartBackup"
style="document" />
    <wsdl:input>
        <soap12:body use="literal" />
    </wsdl:input>
    <wsdl:output>
        <soap12:body use="literal" />
    </wsdl:output>
    <wsdl:fault name="PCBackupClientFaultFault">
        <soap12:fault use="literal" name="PCBackupClientFaultFault" namespace="" />
    </wsdl:fault>
</wsdl:operation>
<wsdl:operation name="CancelBackup">
    <soap12:operation soapAction="http://tempuri.org/IPCBackupServerRegister/CancelBackup"
style="document" />
    <wsdl:input>
        <soap12:body use="literal" />
    </wsdl:input>
    <wsdl:output>
        <soap12:body use="literal" />
    </wsdl:output>
    <wsdl:fault name="PCBackupClientFaultFault">
        <soap12:fault use="literal" name="PCBackupClientFaultFault" namespace="" />
    </wsdl:fault>
</wsdl:operation>
<wsdl:operation name="UpdateBackupConfiguration">
    <soap12:operation
soapAction="http://tempuri.org/IPCBackupServerRegister/UpdateBackupConfiguration"
style="document" />
    <wsdl:output>
        <soap12:body use="literal" />
    </wsdl:output>
</wsdl:operation>
<wsdl:operation name="SendBackupProgress">
    <soap12:operation
soapAction="http://tempuri.org/IPCBackupServerRegister/SendBackupProgress" style="document"
/>
    <wsdl:output>
        <soap12:body use="literal" />
    </wsdl:output>
</wsdl:operation>
<wsdl:operation name="GetFolderChildren">
    <soap12:operation
soapAction="http://tempuri.org/IPCBackupServerRegister/GetFolderChildren" style="document" />
    <wsdl:input>
        <soap12:body use="literal" />
    </wsdl:input>
    <wsdl:output>
        <soap12:body use="literal" />
    </wsdl:output>
    <wsdl:fault name="PCBackupClientFaultFault">
        <soap12:fault use="literal" name="PCBackupClientFaultFault" namespace="" />
    </wsdl:fault>
</wsdl:operation>
<wsdl:operation name="CalculateVolumeAsync">
    <soap12:operation
soapAction="http://tempuri.org/IPCBackupServerRegister/CalculateVolumeAsync" style="document"
/>
    <wsdl:input>
        <soap12:body use="literal" />
    </wsdl:input>
    <wsdl:output>

```

```

        <soap12:body use="literal" />
    </wsdl:output>
    <wsdl:fault name="PCBackupClientFaultFault">
        <soap12:fault use="literal" name="PCBackupClientFaultFault" namespace="" />
    </wsdl:fault>
</wsdl:operation>
<wsdl:operation name="CleanFolderSizeCalculation">
    <soap12:operation
        soapAction="http://tempuri.org/IPCBackupServerRegister/CleanFolderSizeCalculation"
        style="document" />
    <wsdl:output>
        <soap12:body use="literal" />
    </wsdl:output>
</wsdl:operation>
<wsdl:operation name="GetConnectedVolumes">
    <soap12:operation
        soapAction="http://tempuri.org/IPCBackupServerRegister/GetConnectedVolumes" style="document"
    />
    <wsdl:input>
        <soap12:body use="literal" />
    </wsdl:input>
    <wsdl:output>
        <soap12:body use="literal" />
    </wsdl:output>
    <wsdl:fault name="PCBackupClientFaultFault">
        <soap12:fault use="literal" name="PCBackupClientFaultFault" namespace="" />
    </wsdl:fault>
</wsdl:operation>
<wsdl:operation name="RescanVolumesAsync">
    <soap12:operation
        soapAction="http://tempuri.org/IPCBackupServerRegister/RescanVolumesAsync" style="document"
    />
    <wsdl:output>
        <soap12:body use="literal" />
    </wsdl:output>
</wsdl:operation>
</wsdl:binding>
<wsdl:service name="PCBackupServerRegisterImpl">
    <wsdl:port name="CustomBinding_IPCBackupServerRegister"
    binding="tns:CustomBinding_IPCBackupServerRegister">
        <soap12:address
            location="net.tcp://serverName:6602/Microsoft.WindowsServerSolutions.wssg_pc_backup_register/
Microsoft.WindowsServerSolutions.DataProtection.PCBackup.BackupUtil.WcfContracts.IPCBackupSer
verRegister" />
        <wsa10:EndpointReference>
            <wsa10:Address>net.tcp://serverName:6602/Microsoft.WindowsServerSolutions.wssg_pc_backup_regi
ster/Microsoft.WindowsServerSolutions.DataProtection.PCBackup.BackupUtil.WcfContracts.IPCBack
upServerRegister</wsa10:Address>
                <Identity xmlns="http://schemas.xmlsoap.org/ws/2006/02/addressingidentity">
                    <Dns>SERVERNAME</Dns>
                </Identity>
            </wsa10:EndpointReference>
        </wsdl:port>
    </wsdl:service>
</wsdl:definitions>
```

6.2.1.2 <http://tempuri.org>

```

<?xml version="1.0" encoding="utf-8"?>
<xss:schema xmlns:tns="http://tempuri.org/" elementFormDefault="qualified"
targetNamespace="http://tempuri.org/" xmlns:xss="http://www.w3.org/2001/XMLSchema">
    <xss:import schemaLocation="" namespace="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.DataProte
ction.PCBackup.BackupUtil.WcfContracts" />
    <xss:import schemaLocation="" namespace="http://schemas.microsoft.com/2003/10/Serialization/" />
```

```

<xs:import schemaLocation="" namespace="http://schemas.microsoft.com/2003/10/Serialization/Arrays" />
<xs:element name="RegisterBackupClient">
  <xs:complexType>
    <xs:sequence />
  </xs:complexType>
</xs:element>
<xs:element name="RegisterBackupClientResponse">
  <xs:complexType>
    <xs:sequence>
      <xs:element
        xmlns:q1="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.DataProtec
tion.PCBackup.BackupUtil.WcfContracts" minOccurs="0" name="RegisterBackupClientResult"
nillable="true" type="q1:ClientConfig" />
    </xs:sequence>
  </xs:complexType>
</xs:element>
<xs:element name="KeepAlive">
  <xs:complexType>
    <xs:sequence />
  </xs:complexType>
</xs:element>
<xs:element name="KeepAliveResponse">
  <xs:complexType>
    <xs:sequence />
  </xs:complexType>
</xs:element>
<xs:element name="VolumeCalculatorProgress">
  <xs:complexType>
    <xs:sequence>
      <xs:element xmlns:q2="http://schemas.microsoft.com/2003/10/Serialization/" minOccurs="0" name="guid" type="q2:guid" />
      <xs:element minOccurs="0" name="percentDone" type="xs:int" />
    <xs:element
      xmlns:q3="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.DataProtec
tion.PCBackup.BackupUtil.WcfContracts" minOccurs="0" name="folders" nillable="true"
type="q3:ArrayOfFolderInfo" />
    </xs:sequence>
  </xs:complexType>
</xs:element>
<xs:element name="GetClientPriority">
  <xs:complexType>
    <xs:sequence />
  </xs:complexType>
</xs:element>
<xs:element name="GetClientPriorityResponse">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" name="GetClientPriorityResult" type="xs:int" />
    </xs:sequence>
  </xs:complexType>
</xs:element>
<xs:element name="OnBatteryPower">
  <xs:complexType>
    <xs:sequence />
  </xs:complexType>
</xs:element>
<xs:element name="OnBatteryPowerResponse">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" name="OnBatteryPowerResult" type="xs:boolean" />
    </xs:sequence>
  </xs:complexType>
</xs:element>
<xs:element name="StartBackup">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" name="automatic" type="xs:boolean" />
      <xs:element minOccurs="0" name="description" nillable="true" type="xs:string" />
    </xs:sequence>
  </xs:complexType>
</xs:element>

```

```

        <xs:element minOccurs="0" name="allowPostpone" type="xs:boolean" />
    </xs:sequence>
</xs:complexType>
</xs:element>
<xs:element name="StartBackupResponse">
    <xs:complexType>
        <xs:sequence />
    </xs:complexType>
</xs:element>
<xs:element name="CancelBackup">
    <xs:complexType>
        <xs:sequence />
    </xs:complexType>
</xs:element>
<xs:element name="CancelBackupResponse">
    <xs:complexType>
        <xs:sequence />
    </xs:complexType>
</xs:element>
<xs:element name="UpdateBackupConfiguration">
    <xs:complexType>
        <xs:sequence>
            <xs:element
                xmlns:q4="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.DataProtection.PCBackup.BackupUtil.WcfContracts" minOccurs="0" name="backupConfig" nillable="true"
                type="q4:ClientConfig" />
            </xs:sequence>
        </xs:complexType>
</xs:element>
<xs:element name="SendBackupProgress">
    <xs:complexType>
        <xs:sequence>
            <xs:element minOccurs="0" name="progress" type="xs:int" />
        </xs:sequence>
    </xs:complexType>
</xs:element>
<xs:element name="GetFolderChildren">
    <xs:complexType>
        <xs:sequence>
            <xs:element
                xmlns:q5="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.DataProtection.PCBackup.BackupUtil.WcfContracts" minOccurs="0" name="folderRequest" nillable="true"
                type="q5:FolderRequest" />
            <xs:element minOccurs="0" name="index" type="xs:int" />
        </xs:sequence>
    </xs:complexType>
</xs:element>
<xs:element name="GetFolderChildrenResponse">
    <xs:complexType>
        <xs:sequence>
            <xs:element
                xmlns:q6="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.DataProtection.PCBackup.BackupUtil.WcfContracts" minOccurs="0" name="GetFolderChildrenResult"
                nillable="true" type="q6:FolderInfoGroup" />
        </xs:sequence>
    </xs:complexType>
</xs:element>
<xs:element name="CalculateVolumeAsync">
    <xs:complexType>
        <xs:sequence>
            <xs:element xmlns:q7="http://schemas.microsoft.com/2003/10/Serialization/" minOccurs="0" name="volumeGuid" type="q7:guid" />
            <xs:element xmlns:q8="http://schemas.microsoft.com/2003/10/Serialization/Arrays" minOccurs="0" name="excludedFolders" nillable="true" type="q8:ArrayOfstring" />
        </xs:sequence>
    </xs:complexType>
</xs:element>
<xs:element name="CalculateVolumeAsyncResponse">
    <xs:complexType>

```

```

<xs:sequence>
    <xs:element minOccurs="0" name="CalculateVolumeAsyncResult" type="xs:boolean" />
</xs:sequence>
</xs:complexType>
</xs:element>
<xs:element name="CleanFolderSizeCalculation">
    <xs:complexType>
        <xs:sequence />
    </xs:complexType>
</xs:element>
<xs:element name="GetConnectedVolumes">
    <xs:complexType>
        <xs:sequence />
    </xs:complexType>
</xs:element>
<xs:element name="GetConnectedVolumesResponse">
    <xs:complexType>
        <xs:sequence>
            <xs:element
                xmlns:q9="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.DataProtection.PCBackup.BackupUtil.WcfContracts" minOccurs="0" name="GetConnectedVolumesResult"
                nillable="true" type="q9:ArrayOfClientVolumeInfo" />
        </xs:sequence>
    </xs:complexType>
</xs:element>
<xs:element name="RescanVolumesAsync">
    <xs:complexType>
        <xs:sequence />
    </xs:complexType>
</xs:element>
</xs:schema>

```

6.2.1.3 http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolution.s.DataProtection.PCBackup.BackupUtil.WcfContracts

```

<?xml version="1.0" encoding="utf-8"?>
<xs:schema xmlns:ser="http://schemas.microsoft.com/2003/10/Serialization/" xmlns:tns="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.DataProtection.PCBackup.BackupUtil.WcfContracts" elementFormDefault="qualified" targetNamespace="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.DataProtection.PCBackup.BackupUtil.WcfContracts" xmlns:xs="http://www.w3.org/2001/XMLSchema">
    <xs:import schemaLocation="" namespace="http://schemas.microsoft.com/2003/10/Serialization/" />
    <xs:import schemaLocation="" namespace="http://schemas.microsoft.com/2003/10/Serialization/Arrays" />
    <xs:complexType name="ClientConfig">
        <xs:sequence>
            <xs:element minOccurs="0" name="AnyVolumesIncluded" type="xs:boolean" />
            <xs:element minOccurs="0" name="IsConfigured" type="xs:boolean" />
            <xs:element minOccurs="0" name="WindowEnd" type="xs:int" />
            <xs:element minOccurs="0" name="WindowStart" type="xs:int" />
        </xs:sequence>
    </xs:complexType>
    <xs:element name="ClientConfig" nillable="true" type="tns:ClientConfig" />
    <xs:complexType name="ArrayOfFolderInfo">
        <xs:sequence>
            <xs:element minOccurs="0" maxOccurs="unbounded" name="FolderInfo" nillable="true" type="tns:FolderInfo" />
        </xs:sequence>
    </xs:complexType>
    <xs:element name="ArrayOfFolderInfo" nillable="true" type="tns:ArrayOfFolderInfo" />
    <xs:complexType name="FolderInfo">
        <xs:sequence>
            <xs:element minOccurs="0" name="ExclusionReason" type="tns:ExclusionReason" />
            <xs:element minOccurs="0" name="FileRecordIndex" type="xs:long" />
            <xs:element minOccurs="0" name="HasChildren" type="xs:boolean" />
            <xs:element minOccurs="0" name="IsFolder" type="xs:boolean" />
        </xs:sequence>
    </xs:complexType>

```

```

<xs:element minOccurs="0" name="Name" nillable="true" type="xs:string" />
<xs:element minOccurs="0" name="UsedBytes" type="xs:long" />
</xs:sequence>
</xs:complexType>
<xs:element name="FolderInfo" nillable="true" type="tns:FolderInfo" />
<xs:simpleType name="ExclusionReason">
    <xs:restriction base="xs:string">
        <xs:enumeration value="NotExcluded" />
        <xs:enumeration value="ClientSideCache" />
        <xs:enumeration value="TemporaryFiles" />
        <xs:enumeration value="DigitalVideoRecorder" />
        <xs:enumeration value="PageFile" />
        <xs:enumeration value="RecycleBin" />
        <xs:enumeration value="HibernationFile" />
        <xs:enumeration value="MemoryDump" />
        <xs:enumeration value="ShadowVolumes" />
        <xs:enumeration value="Other" />
        <xs:enumeration value="Count" />
    </xs:restriction>
</xs:simpleType>
<xs:element name="ExclusionReason" nillable="true" type="tns:ExclusionReason" />
<xs:complexType name="PCBackupClientFault">
    <xs:sequence>
        <xs:element minOccurs="0" name="Description" nillable="true" type="xs:string" />
        <xs:element minOccurs="0" name="Other" nillable="true" type="xs:string" />
        <xs:element minOccurs="0" name="Reason" type="tns:PCBackupClientFaultReason" />
    </xs:sequence>
</xs:complexType>
<xs:element name="PCBackupClientFault" nillable="true" type="tns:PCBackupClientFault" />
<xs:simpleType name="PCBackupClientFaultReason">
    <xs:restriction base="xs:string">
        <xs:enumeration value="ServerNotReachable" />
        <xs:enumeration value="ClientNotConfigured" />
        <xs:enumeration value="Unknown" />
    </xs:restriction>
</xs:simpleType>
<xs:element name="PCBackupClientFaultReason" nillable="true"
type="tns:PCBackupClientFaultReason" />
<xs:complexType name="FolderRequest">
    <xs:sequence>
        <xs:element minOccurs="0" name="fileRecordIndex" type="xs:long" />
        <xs:element minOccurs="0" name="volumeGuid" type="ser:guid" />
    </xs:sequence>
</xs:complexType>
<xs:element name="FolderRequest" nillable="true" type="tns:FolderRequest" />
<xs:complexType name="FolderInfoGroup">
    <xs:sequence>
        <xs:element minOccurs="0" name="FolderInfoList" nillable="true"
type="tns:ArrayOfFolderInfo" />
            <xs:element minOccurs="0" name="TotalNumChildren" type="xs:int" />
        </xs:sequence>
</xs:complexType>
<xs:element name="FolderInfoGroup" nillable="true" type="tns:FolderInfoGroup" />
<xs:complexType name="ArrayOfClientVolumeInfo">
    <xs:sequence>
        <xs:element minOccurs="0" maxOccurs="unbounded" name="ClientVolumeInfo" nillable="true"
type="tns:ClientVolumeInfo" />
    </xs:sequence>
</xs:complexType>
<xs:element name="ArrayOfClientVolumeInfo" nillable="true"
type="tns:ArrayOfClientVolumeInfo" />
<xs:complexType name="ClientVolumeInfo">
    <xs:sequence>
        <xs:element minOccurs="0" name="BackupBytes" type="xs:long" />
        <xs:element minOccurs="0" name="BytesPerCluster" type="xs:int" />
        <xs:element minOccurs="0" name="BytesPerSector" type="xs:int" />
        <xs:element minOccurs="0" name="BytesUsed" type="xs:long" />
        <xs:element minOccurs="0" name="Capacity" type="xs:long" />
    </xs:sequence>
</xs:complexType>

```

```

<xs:element xmlns:q1="http://schemas.microsoft.com/2003/10/Serialization/Arrays"
minOccurs="0" name="ExcludedFolders" nillable="true" type="q1:ArrayOfstring" />
<xs:element minOccurs="0" name="FileSystem" nillable="true" type="xs:string" />
<xs:element minOccurs="0" name="IsEligibleForBackup" type="xs:boolean" />
<xs:element minOccurs="0" name="JobsExist" type="xs:boolean" />
<xs:element minOccurs="0" name="Location" type="tns:VolumeLocation" />
<xs:element minOccurs="0" name="MountPoint" nillable="true" type="xs:string" />
<xs:element minOccurs="0" name="Status" type="tns:VolumeStatus" />
<xs:element minOccurs="0" name="VolumeName" nillable="true" type="xs:string" />
<xs:element minOccurs="0" name="guid" type="ser:guid" />
<xs:element xmlns:q2="http://schemas.microsoft.com/2003/10/Serialization/Arrays"
minOccurs="0" name="uniqueIdBytes" nillable="true" type="q2:ArrayOfunsignedByte" />
</xs:sequence>
</xs:complexType>
<xs:element name="ClientVolumeInfo" nillable="true" type="tns:ClientVolumeInfo" />
<xs:simpleType name="VolumeLocation">
<xs:restriction base="xs:string">
<xs:enumeration value="Missing" />
<xs:enumeration value="Internal" />
<xs:enumeration value="External" />
</xs:restriction>
</xs:simpleType>
<xs:element name="VolumeLocation" nillable="true" type="tns:VolumeLocation" />
<xs:simpleType name="VolumeStatus">
<xs:restriction base="xs:string">
<xs:enumeration value="NotConfigured" />
<xs:enumeration value="Exclude" />
<xs:enumeration value="Include" />
</xs:restriction>
</xs:simpleType>
<xs:element name="VolumeStatus" nillable="true" type="tns:VolumeStatus" />
</xs:schema>

```

6.2.1.4 http://schemas.microsoft.com/2003/10/Serialization/Arrays

```

<?xml version="1.0" encoding="utf-8"?>
<xs:schema xmlns:tns="http://schemas.microsoft.com/2003/10/Serialization/Arrays"
elementFormDefault="qualified"
targetNamespace="http://schemas.microsoft.com/2003/10/Serialization/Arrays"
xmlns:xs="http://www.w3.org/2001/XMLSchema">
<xs:complexType name="ArrayOfstring">
<xs:sequence>
<xs:element minOccurs="0" maxOccurs="unbounded" name="string" nillable="true"
type="xs:string" />
</xs:sequence>
</xs:complexType>
<xs:element name="ArrayOfstring" nillable="true" type="tns:ArrayOfstring" />
<xs:complexType name="ArrayOfunsignedByte">
<xs:sequence>
<xs:element minOccurs="0" maxOccurs="unbounded" name="unsignedByte"
type="xs:unsignedByte" />
</xs:sequence>
</xs:complexType>
<xs:element name="ArrayOfunsignedByte" nillable="true" type="tns:ArrayOfunsignedByte" />
</xs:schema>

```

6.2.1.5 http://schemas.microsoft.com/2003/10/Serialization

```

<?xml version="1.0" encoding="utf-8"?>
<xs:schema xmlns:tns="http://schemas.microsoft.com/2003/10/Serialization/"
attributeFormDefault="qualified" elementFormDefault="qualified"
targetNamespace="http://schemas.microsoft.com/2003/10/Serialization/"
xmlns:xs="http://www.w3.org/2001/XMLSchema">
<xs:element name="anyType" nillable="true" type="xs:anyType" />
<xs:element name="anyURI" nillable="true" type="xs:anyURI" />

```

```

<xs:element name="base64Binary" nillable="true" type="xs:base64Binary" />
<xs:element name="boolean" nillable="true" type="xs:boolean" />
<xs:element name="byte" nillable="true" type="xs:byte" />
<xs:element name="dateTime" nillable="true" type="xs:dateTime" />
<xs:element name="decimal" nillable="true" type="xs:decimal" />
<xs:element name="double" nillable="true" type="xs:double" />
<xs:element name="float" nillable="true" type="xs:float" />
<xs:element name="int" nillable="true" type="xs:int" />
<xs:element name="long" nillable="true" type="xs:long" />
<xs:element name="QName" nillable="true" type="xs:QName" />
<xs:element name="short" nillable="true" type="xs:short" />
<xs:element name="string" nillable="true" type="xs:string" />
<xs:element name="unsignedByte" nillable="true" type="xs:unsignedByte" />
<xs:element name="unsignedInt" nillable="true" type="xs:unsignedInt" />
<xs:element name="unsignedLong" nillable="true" type="xs:unsignedLong" />
<xs:element name="unsignedShort" nillable="true" type="xs:unsignedShort" />
<xs:element name="char" nillable="true" type="tns:char" />
<xs:simpleType name="char">
    <xs:restriction base="xs:int" />
</xs:simpleType>
<xs:element name="duration" nillable="true" type="tns:duration" />
<xs:simpleType name="duration">
    <xs:restriction base="xs:duration">
        <xs:pattern value="\-?P(\d*D)?(T(\d*H)?(\d*M)?(\d*(\.\.\d*)?S)?)?" />
        <xs:minInclusive value="-P10675199DT2H48M5.4775808S" />
        <xs:maxInclusive value="P10675199DT2H48M5.4775807S" />
    </xs:restriction>
</xs:simpleType>
<xs:element name="guid" nillable="true" type="tns:guid" />
<xs:simpleType name="guid">
    <xs:restriction base="xs:string">
        <xs:pattern value="[\da-fA-F]{8}-[\da-fA-F]{4}-[\da-fA-F]{4}-[\da-fA-F]{4}-[\da-fA-F]{12}" />
    </xs:restriction>
</xs:simpleType>
<xs:attribute name="FactoryType" type="xs:QName" />
<xs:attribute name="Id" type="xs:ID" />
<xs:attribute name="Ref" type="xs:IDREF" />
</xs:schema>

```

6.2.1.6 <http://schemas.datacontract.org/2004/07/System>

```

<?xml version="1.0" encoding="utf-8"?>
<xs:schema xmlns:ser="http://schemas.microsoft.com/2003/10/Serialization/"
    xmlns:tns="http://schemas.datacontract.org/2004/07/System" elementFormDefault="qualified"
    targetNamespace="http://schemas.datacontract.org/2004/07/System"
    xmlns:xs="http://www.w3.org/2001/XMLSchema">
    <xs:import schemaLocation=""
        namespace="http://schemas.microsoft.com/2003/10/Serialization/" />
    <xs:complexType name="InvalidOperationException">
        <xs:complexContent mixed="false">
            <xs:extension base="tns:SystemException" />
        </xs:complexContent>
    </xs:complexType>
    <xs:element name="InvalidOperationException" nillable="true"
        type="tns:InvalidOperationException" />
    <xs:complexType name="SystemException">
        <xs:complexContent mixed="false">
            <xs:extension base="tns:Exception" />
        </xs:complexContent>
    </xs:complexType>
    <xs:element name="SystemException" nillable="true" type="tns:SystemException" />
    <xs:complexType name="Exception">
        <xs:sequence>
            <xs:any minOccurs="0" maxOccurs="unbounded" namespace="##local" processContents="skip"
        />
        </xs:sequence>
    </xs:complexType>

```

```

<xs:attribute ref="ser:FactoryType" />
</xs:complexType>
<xs:element name="Exception" nillable="true" type="tns:Exception" />
</xs:schema>

```

6.2.2 IPCBackupServerProvider

6.2.2.1 wsdl

```

<?xml version="1.0" encoding="utf-8"?>
<wsdl:definitions xmlns:wsap="http://schemas.xmlsoap.org/ws/2004/08/addressing/policy"
  xmlns:wsa10="http://www.w3.org/2005/08/addressing" xmlns:tns="http://tempuri.org/"
  xmlns:msc="http://schemas.microsoft.com/ws/2005/12/wsdl/contract"
  xmlns:soapenc="http://schemas.xmlsoap.org/soap/encoding/"
  xmlns:soap="http://schemas.xmlsoap.org/wsdl/soap/"
  xmlns: wsp="http://schemas.xmlsoap.org/ws/2004/09/policy"
  xmlns: wsam="http://www.w3.org/2007/05/addressing/metadata"
  xmlns: wsa="http://schemas.xmlsoap.org/ws/2004/08/addressing"
  xmlns: wsaw="http://www.w3.org/2006/05/addressing/wsdl"
  xmlns: soap12="http://schemas.xmlsoap.org/wsdl/soap12/" xmlns:wsu="http://docs.oasis-
  open.org/wss/2004/01/oasis-200401-wss-wssecurity-utility-1.0.xsd"
  xmlns: xsd="http://www.w3.org/2001/XMLSchema" name="PCBackupServerProviderImpl"
  targetNamespace="http://tempuri.org/" xmlns:wsdl="http://schemas.xmlsoap.org/wsdl/">
  <wsp:Policy wsu:Id="CustomBinding_IPCBackupServerProvider_policy">
    <wsp:ExactlyOne>
      <wsp:All>
        <msb:BinaryEncoding
          xmlns:msb="http://schemas.microsoft.com/ws/2004/mspolicy/netbinary1" />
        <sp:TransportBinding xmlns:sp="http://schemas.xmlsoap.org/ws/2005/07/securitypolicy">
          <wsp:Policy>
            <sp:TransportToken>
              <wsp:Policy>
                <msf:WindowsTransportSecurity
                  xmlns:msf="http://schemas.microsoft.com/ws/2006/05/framing/policy">
                  <msf:ProtectionLevel>EncryptAndSign</msf:ProtectionLevel>
                  </msf:WindowsTransportSecurity>
                </wsp:Policy>
              </sp:TransportToken>
              <sp:AlgorithmSuite>
                <wsp:Policy>
                  <sp:Basic256 />
                </wsp:Policy>
              </sp:AlgorithmSuite>
              <sp:Layout>
                <wsp:Policy>
                  <sp:Strict />
                </wsp:Policy>
              </sp:Layout>
            </wsp:Policy>
          </sp:TransportBinding>
          <wsaw:UsingAddressing />
        </wsp:All>
      </wsp:ExactlyOne>
    </wsp:Policy>
  </wsdl:types>
  <xsd:schema targetNamespace="http://tempuri.org/Imports">
    <xsd:import schemaLocation="" namespace="http://tempuri.org/" />
    <xsd:import schemaLocation="" namespace="http://schemas.datacontract.org/2004/07/System.ServiceModel.Security" />
    <xsd:import schemaLocation="" namespace="http://schemas.microsoft.com/2003/10/Serialization/" />
    <xsd:import schemaLocation="" namespace="http://schemas.datacontract.org/2004/07/System.ServiceModel" />
    <xsd:import schemaLocation="" namespace="http://schemas.datacontract.org/2004/07/System" />
  
```

```

<xsd:import schemaLocation="" namespace="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.DataProtection.PCBackup.BackupUtil.WcfContracts" />
  <xsd:import schemaLocation="" namespace="http://schemas.microsoft.com/2003/10/Serialization/Arrays" />
</xsd:schema>
</wsdl:types>
<wsdl:message name="IPCBBackupServerProvider_Register_InputMessage">
  <wsdl:part name="parameters" element="tns:Register" />
</wsdl:message>
<wsdl:message name="IPCBBackupServerProvider Register OutputMessage">
  <wsdl:part name="parameters" element="tns:RegisterResponse" />
</wsdl:message>
<wsdl:message name="IPCBBackupServerProvider_Register_SecurityAccessDeniedExceptionFault_FaultMessage">
  <wsdl:part
    xmlns:q1="http://schemas.datacontract.org/2004/07/System.ServiceModel.Security" name="detail" element="q1:SecurityAccessDeniedException" />
</wsdl:message>
<wsdl:message name="IPCBBackupServerProvider_GetClients_InputMessage">
  <wsdl:part name="parameters" element="tns:GetClients" />
</wsdl:message>
<wsdl:message name="IPCBBackupServerProvider GetClients OutputMessage">
  <wsdl:part name="parameters" element="tns:GetClientsResponse" />
</wsdl:message>
<wsdl:message name="IPCBBackupServerProvider_GetClients_PCBBackupServerFaultFault_FaultMessage">
  <wsdl:part
    xmlns:q2="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.DataProtection.PCBackup.BackupUtil.WcfContracts" name="detail" element="q2:PCBackupServerFault" />
</wsdl:message>
<wsdl:message name="IPCBBackupServerProvider_GetClients_SecurityAccessDeniedExceptionFault_FaultMessage">
  <wsdl:part
    xmlns:q3="http://schemas.datacontract.org/2004/07/System.ServiceModel.Security" name="detail" element="q3:SecurityAccessDeniedException" />
</wsdl:message>
<wsdl:message name="IPCBBackupServerProvider_GetClient_InputMessage">
  <wsdl:part name="parameters" element="tns:GetClient" />
</wsdl:message>
<wsdl:message name="IPCBBackupServerProvider_GetClient_OutputMessage">
  <wsdl:part name="parameters" element="tns:GetClientResponse" />
</wsdl:message>
<wsdl:message name="IPCBBackupServerProvider_GetClient_PCBBackupServerFaultFault_FaultMessage">
  <wsdl:part
    xmlns:q4="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.DataProtection.PCBackup.BackupUtil.WcfContracts" name="detail" element="q4:PCBackupServerFault" />
</wsdl:message>
<wsdl:message name="IPCBBackupServerProvider_GetClient_SecurityAccessDeniedExceptionFault_FaultMessage">
  <wsdl:part
    xmlns:q5="http://schemas.datacontract.org/2004/07/System.ServiceModel.Security" name="detail" element="q5:SecurityAccessDeniedException" />
</wsdl:message>
<wsdl:message name="IPCBBackupServerProvider_OnBattery_InputMessage">
  <wsdl:part name="parameters" element="tns:OnBattery" />
</wsdl:message>
<wsdl:message name="IPCBBackupServerProvider OnBattery OutputMessage">
  <wsdl:part name="parameters" element="tns:OnBatteryResponse" />
</wsdl:message>
<wsdl:message name="IPCBBackupServerProvider OnBattery PCBackupServerFaultFault FaultMessage">
  <wsdl:part
    xmlns:q6="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.DataProtection.PCBackup.BackupUtil.WcfContracts" name="detail" element="q6:PCBackupServerFault" />
</wsdl:message>
<wsdl:message name="IPCBBackupServerProvider_OnBattery_SecurityAccessDeniedExceptionFault_FaultMessage">

```

```

<wsdl:part
xmlns:q7="http://schemas.datacontract.org/2004/07/System.ServiceModel.Security" name="detail"
element="q7:SecurityAccessDeniedException" />
</wsdl:message>
<wsdl:message name="IPCBBackupServerProvider_GetClientJobs_InputMessage">
    <wsdl:part name="parameters" element="tns:GetClientJobs" />
</wsdl:message>
<wsdl:message name="IPCBBackupServerProvider_GetClientJobs_OutputMessage">
    <wsdl:part name="parameters" element="tns:GetClientJobsResponse" />
</wsdl:message>
<wsdl:message
name="IPCBBackupServerProvider_GetClientJobs_PCBBackupServerFaultFault_FaultMessage">
    <wsdl:part
xmlns:q8="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.DataProtec
tion.PCBackup.BackupUtil.WcfContracts" name="detail" element="q8:PCBackupServerFault" />
</wsdl:message>
<wsdl:message
name="IPCBBackupServerProvider_GetClientJobs_SecurityAccessDeniedExceptionFault_FaultMessage">
    <wsdl:part
xmlns:q9="http://schemas.datacontract.org/2004/07/System.ServiceModel.Security" name="detail"
element="q9:SecurityAccessDeniedException" />
</wsdl:message>
<wsdl:message name="IPCBBackupServerProvider_GetVolumeJobs_InputMessage">
    <wsdl:part name="parameters" element="tns:GetVolumeJobs" />
</wsdl:message>
<wsdl:message name="IPCBBackupServerProvider_GetVolumeJobs_OutputMessage">
    <wsdl:part name="parameters" element="tns:GetVolumeJobsResponse" />
</wsdl:message>
<wsdl:message
name="IPCBBackupServerProvider_GetVolumeJobs_PCBBackupServerFaultFault_FaultMessage">
    <wsdl:part
xmlns:q10="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.DataProte
ction.PCBackup.BackupUtil.WcfContracts" name="detail" element="q10:PCBackupServerFault" />
</wsdl:message>
<wsdl:message
name="IPCBBackupServerProvider_GetVolumeJobs_SecurityAccessDeniedExceptionFault_FaultMessage">
    <wsdl:part
xmlns:q11="http://schemas.datacontract.org/2004/07/System.ServiceModel.Security"
name="detail" element="q11:SecurityAccessDeniedException" />
</wsdl:message>
<wsdl:message name="IPCBBackupServerProvider_GetClientVolumes_InputMessage">
    <wsdl:part name="parameters" element="tns:GetClientVolumes" />
</wsdl:message>
<wsdl:message name="IPCBBackupServerProvider_GetClientVolumes_OutputMessage">
    <wsdl:part name="parameters" element="tns:GetClientVolumesResponse" />
</wsdl:message>
<wsdl:message
name="IPCBBackupServerProvider_GetClientVolumes_PCBBackupServerFaultFault_FaultMessage">
    <wsdl:part
xmlns:q12="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.DataProte
ction.PCBackup.BackupUtil.WcfContracts" name="detail" element="q12:PCBackupServerFault" />
</wsdl:message>
<wsdl:message
name="IPCBBackupServerProvider_GetClientVolumes_SecurityAccessDeniedExceptionFault_FaultMessag
e">
    <wsdl:part
xmlns:q13="http://schemas.datacontract.org/2004/07/System.ServiceModel.Security"
name="detail" element="q13:SecurityAccessDeniedException" />
</wsdl:message>
<wsdl:message name="IPCBBackupServerProvider_SetClientJobDescription_InputMessage">
    <wsdl:part name="parameters" element="tns:SetClientJobDescription" />
</wsdl:message>
<wsdl:message name="IPCBBackupServerProvider_SetClientJobDescription_OutputMessage">
    <wsdl:part name="parameters" element="tns:SetClientJobDescriptionResponse" />
</wsdl:message>
<wsdl:message
name="IPCBBackupServerProvider_SetClientJobDescription_PCBBackupServerFaultFault_FaultMessage">

```

```

<wsdl:part
xmlns:q14="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.DataProtection.PCBackup.BackupUtil.WcfContracts" name="detail" element="q14:PCBackupServerFault" />
</wsdl:message>
<wsdl:message
name="IPCBBackupServerProvider SetClientJobDescription SecurityAccessDeniedExceptionFault FaultMessage">
    <wsdl:part
xmlns:q15="http://schemas.datacontract.org/2004/07/System.ServiceModel.Security"
name="detail" element="q15:SecurityAccessDeniedException" />
    </wsdl:message>
    <wsdl:message name="IPCBBackupServerProvider_SetClientJobRetentionState_InputMessage">
        <wsdl:part name="parameters" element="tns:SetClientJobRetentionState" />
    </wsdl:message>
    <wsdl:message name="IPCBBackupServerProvider_SetClientJobRetentionState_OutputMessage">
        <wsdl:part name="parameters" element="tns:SetClientJobRetentionStateResponse" />
    </wsdl:message>
    <wsdl:message
name="IPCBBackupServerProvider SetClientJobRetentionState PCBackupServerFaultFault FaultMessage">
        <wsdl:part
xmlns:q16="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.DataProtection.PCBackup.BackupUtil.WcfContracts" name="detail" element="q16:PCBackupServerFault" />
        </wsdl:message>
        <wsdl:message
name="IPCBBackupServerProvider_SetClientJobRetentionState_SecurityAccessDeniedExceptionFault_FaultMessage">
            <wsdl:part
xmlns:q17="http://schemas.datacontract.org/2004/07/System.ServiceModel.Security"
name="detail" element="q17:SecurityAccessDeniedException" />
            </wsdl:message>
            <wsdl:message name="IPCBBackupServerProvider_SetClientVolumeStatus_InputMessage">
                <wsdl:part name="parameters" element="tns:SetClientVolumeStatus" />
            </wsdl:message>
            <wsdl:message name="IPCBBackupServerProvider_SetClientVolumeStatus_OutputMessage">
                <wsdl:part name="parameters" element="tns:SetClientVolumeStatusResponse" />
            </wsdl:message>
            <wsdl:message
name="IPCBBackupServerProvider_SetClientVolumeStatus_PCBackupServerFaultFault_FaultMessage">
                <wsdl:part
xmlns:q18="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.DataProtection.PCBackup.BackupUtil.WcfContracts" name="detail" element="q18:PCBackupServerFault" />
                </wsdl:message>
                <wsdl:message
name="IPCBBackupServerProvider_SetClientVolumeStatus_SecurityAccessDeniedExceptionFault_FaultMessage">
                    <wsdl:part
xmlns:q19="http://schemas.datacontract.org/2004/07/System.ServiceModel.Security"
name="detail" element="q19:SecurityAccessDeniedException" />
                    </wsdl:message>
                    <wsdl:message name="IPCBBackupServerProvider_SetExcludedFolders_InputMessage">
                        <wsdl:part name="parameters" element="tns:SetExcludedFolders" />
                    </wsdl:message>
                    <wsdl:message name="IPCBBackupServerProvider_SetExcludedFolders_OutputMessage">
                        <wsdl:part name="parameters" element="tns:SetExcludedFoldersResponse" />
                    </wsdl:message>
                    <wsdl:message
name="IPCBBackupServerProvider SetExcludedFolders SecurityAccessDeniedExceptionFault FaultMessage">
                        <wsdl:part
xmlns:q20="http://schemas.datacontract.org/2004/07/System.ServiceModel.Security"
name="detail" element="q20:SecurityAccessDeniedException" />
                        </wsdl:message>
                        <wsdl:message
name="IPCBBackupServerProvider_SetExcludedFolders PCBackupServerFaultFault FaultMessage">
                            <wsdl:part
xmlns:q21="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.DataProtection.PCBackup.BackupUtil.WcfContracts" name="detail" element="q21:PCBackupServerFault" />
                            </wsdl:message>

```

```

<wsdl:message name="IPCBBackupServerProvider_EnableBackups_InputMessage">
  <wsdl:part name="parameters" element="tns:EnableBackups" />
</wsdl:message>
<wsdl:message name="IPCBBackupServerProvider_EnableBackups_OutputMessage">
  <wsdl:part name="parameters" element="tns:EnableBackupsResponse" />
</wsdl:message>
<wsdl:message
  name="IPCBBackupServerProvider_EnableBackups_PCBBackupServerFaultFault_FaultMessage">
  <wsdl:part
    xmlns:q22="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.DataProtection.PCBackup.BackupUtil.WcfContracts" name="detail" element="q22:PCBackupServerFault" />
</wsdl:message>
<wsdl:message
  name="IPCBBackupServerProvider_EnableBackups_SecurityAccessDeniedExceptionFault_FaultMessage">
  <wsdl:part
    xmlns:q23="http://schemas.datacontract.org/2004/07/System.ServiceModel.Security"
    name="detail" element="q23:SecurityAccessDeniedException" />
</wsdl:message>
<wsdl:message name="IPCBBackupServerProvider_DisableBackups_InputMessage">
  <wsdl:part name="parameters" element="tns:DisableBackups" />
</wsdl:message>
<wsdl:message name="IPCBBackupServerProvider_DisableBackups_OutputMessage">
  <wsdl:part name="parameters" element="tns:DisableBackupsResponse" />
</wsdl:message>
<wsdl:message
  name="IPCBBackupServerProvider_DisableBackups_PCBBackupServerFaultFault_FaultMessage">
  <wsdl:part
    xmlns:q24="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.DataProtection.PCBackup.BackupUtil.WcfContracts" name="detail" element="q24:PCBackupServerFault" />
</wsdl:message>
<wsdl:message
  name="IPCBBackupServerProvider_DisableBackups_SecurityAccessDeniedExceptionFault_FaultMessage">
</wsdl:message>
<wsdl:message name="IPCBBackupServerProvider_GetBackupConfiguration_InputMessage">
  <wsdl:part name="parameters" element="tns:GetBackupConfiguration" />
</wsdl:message>
<wsdl:message name="IPCBBackupServerProvider_GetBackupConfiguration_OutputMessage">
  <wsdl:part name="parameters" element="tns:GetBackupConfigurationResponse" />
</wsdl:message>
<wsdl:message
  name="IPCBBackupServerProvider_GetBackupConfiguration_PCBBackupServerFaultFault_FaultMessage">
  <wsdl:part
    xmlns:q26="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.DataProtection.PCBackup.BackupUtil.WcfContracts" name="detail" element="q26:PCBackupServerFault" />
</wsdl:message>
<wsdl:message
  name="IPCBBackupServerProvider_GetBackupConfiguration_SecurityAccessDeniedExceptionFault_FaultMessage">
</wsdl:message>
<wsdl:message name="IPCBBackupServerProvider_GetDefaultBackupConfiguration_InputMessage">
  <wsdl:part name="parameters" element="tns:GetDefaultBackupConfiguration" />
</wsdl:message>
<wsdl:message name="IPCBBackupServerProvider_GetDefaultBackupConfiguration_OutputMessage">
  <wsdl:part name="parameters" element="tns:GetDefaultBackupConfigurationResponse" />
</wsdl:message>
<wsdl:message
  name="IPCBBackupServerProvider_GetDefaultBackupConfiguration_PCBBackupServerFaultFault_FaultMessage">
  <wsdl:part
    xmlns:q28="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.DataProtection.PCBackup.BackupUtil.WcfContracts" name="detail" element="q28:PCBackupServerFault" />
</wsdl:message>

```

```

<wsdl:message
name="IPCBBackupServerProvider_GetDefaultBackupConfiguration_SecurityAccessDeniedExceptionFault
t_FaultMessage">
    <wsdl:part
xmlns:q29="http://schemas.datacontract.org/2004/07/System.ServiceModel.Security"
name="detail" element="q29:SecurityAccessDeniedException" />
    </wsdl:message>
    <wsdl:message name="IPCBBackupServerProvider_GetBackupOperationStatus_InputMessage">
        <wsdl:part name="parameters" element="tns:GetBackupOperationStatus" />
    </wsdl:message>
    <wsdl:message name="IPCBBackupServerProvider_GetBackupOperationStatus_OutputMessage">
        <wsdl:part name="parameters" element="tns:GetBackupOperationStatusResponse" />
    </wsdl:message>
    <wsdl:message
name="IPCBBackupServerProvider_GetBackupOperationStatus_PCBBackupServerFaultFault_FaultMessage">
    <wsdl:part
xmlns:q30="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.DataProte
ction.PCBackup.BackupUtil.WcfContracts" name="detail" element="q30:PCBackupServerFault" />
    </wsdl:message>
    <wsdl:message
name="IPCBBackupServerProvider_GetBackupOperationStatus_SecurityAccessDeniedExceptionFault_Fau
ltMessage">
    <wsdl:part
xmlns:q31="http://schemas.datacontract.org/2004/07/System.ServiceModel.Security"
name="detail" element="q31:SecurityAccessDeniedException" />
    </wsdl:message>
    <wsdl:message name="IPCBBackupServerProvider.GetServiceStatus_InputMessage">
        <wsdl:part name="parameters" element="tns:GetServiceStatus" />
    </wsdl:message>
    <wsdl:message name="IPCBBackupServerProvider.GetServiceStatus_OutputMessage">
        <wsdl:part name="parameters" element="tns:GetServiceStatusResponse" />
    </wsdl:message>
    <wsdl:message
name="IPCBBackupServerProvider.GetServiceStatus_PCBBackupServerFaultFault_FaultMessage">
    <wsdl:part
xmlns:q32="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.DataProte
ction.PCBackup.BackupUtil.WcfContracts" name="detail" element="q32:PCBackupServerFault" />
    </wsdl:message>
    <wsdl:message
name="IPCBBackupServerProvider.GetServiceStatus_SecurityAccessDeniedExceptionFault_FaultMessag
e">
    <wsdl:part
xmlns:q33="http://schemas.datacontract.org/2004/07/System.ServiceModel.Security"
name="detail" element="q33:SecurityAccessDeniedException" />
    </wsdl:message>
    <wsdl:message name="IPCBBackupServerProvider_GetWaitingOperations_InputMessage">
        <wsdl:part name="parameters" element="tns:GetWaitingOperations" />
    </wsdl:message>
    <wsdl:message name="IPCBBackupServerProvider_GetWaitingOperations_OutputMessage">
        <wsdl:part name="parameters" element="tns:GetWaitingOperationsResponse" />
    </wsdl:message>
    <wsdl:message
name="IPCBBackupServerProvider_GetWaitingOperations_PCBBackupServerFaultFault_FaultMessage">
    <wsdl:part
xmlns:q34="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.DataProte
ction.PCBackup.BackupUtil.WcfContracts" name="detail" element="q34:PCBackupServerFault" />
    </wsdl:message>
    <wsdl:message
name="IPCBBackupServerProvider_GetWaitingOperations_SecurityAccessDeniedExceptionFault_FaultMe
ssage">
    <wsdl:part
xmlns:q35="http://schemas.datacontract.org/2004/07/System.ServiceModel.Security"
name="detail" element="q35:SecurityAccessDeniedException" />
    </wsdl:message>
    <wsdl:message name="IPCBBackupServerProvider_SetBackupConfiguration_InputMessage">
        <wsdl:part name="parameters" element="tns:SetBackupConfiguration" />
    </wsdl:message>
    <wsdl:message name="IPCBBackupServerProvider_SetBackupConfiguration_OutputMessage">

```

```

<wsdl:part name="parameters" element="tns:SetBackupConfigurationResponse" />
</wsdl:message>
<wsdl:message
name="IPCBBackupServerProvider_SetBackupConfiguration_PCTBackupServerFaultFault_FaultMessage">
    <wsdl:part
xmlns:q36="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.DataProtection.PCBackup.BackupUtil.WcfContracts" name="detail" element="q36:PCBackupServerFault" />
    </wsdl:message>
    <wsdl:message
name="IPCBBackupServerProvider_SetBackupConfiguration_SecurityAccessDeniedExceptionFault_FaultMessage">
    <wsdl:part
xmlns:q37="http://schemas.datacontract.org/2004/07/System.ServiceModel.Security"
name="detail" element="q37:SecurityAccessDeniedException" />
    </wsdl:message>
    <wsdl:message name="IPCBBackupServerProvider_GetUsedBytes_InputMessage">
        <wsdl:part name="parameters" element="tns:GetUsedBytes" />
    </wsdl:message>
    <wsdl:message name="IPCBBackupServerProvider_GetUsedBytes_OutputMessage">
        <wsdl:part name="parameters" element="tns:GetUsedBytesResponse" />
    </wsdl:message>
    <wsdl:message
name="IPCBBackupServerProvider GetUsedBytes PCBackupServerFault FaultMessage">
        <wsdl:part
xmlns:q38="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.DataProtection.PCBackup.BackupUtil.WcfContracts" name="detail" element="q38:PCBackupServerFault" />
        </wsdl:message>
        <wsdl:message
name="IPCBBackupServerProvider GetUsedBytes SecurityAccessDeniedExceptionFault FaultMessage">
        <wsdl:part
xmlns:q39="http://schemas.datacontract.org/2004/07/System.ServiceModel.Security"
name="detail" element="q39:SecurityAccessDeniedException" />
        </wsdl:message>
        <wsdl:message name="IPCBBackupServerProvider StartCleanup_InputMessage">
            <wsdl:part name="parameters" element="tns:StartCleanup" />
        </wsdl:message>
        <wsdl:message name="IPCBBackupServerProvider_StartCleanup_OutputMessage">
            <wsdl:part name="parameters" element="tns:StartCleanupResponse" />
        </wsdl:message>
        <wsdl:message
name="IPCBBackupServerProvider_StartCleanup_PCTBackupServerFaultFault_FaultMessage">
            <wsdl:part
xmlns:q40="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.DataProtection.PCBackup.BackupUtil.WcfContracts" name="detail" element="q40:PCBackupServerFault" />
            </wsdl:message>
            <wsdl:message
name="IPCBBackupServerProvider_StartCleanup_SecurityAccessDeniedExceptionFault_FaultMessage">
            <wsdl:part
xmlns:q41="http://schemas.datacontract.org/2004/07/System.ServiceModel.Security"
name="detail" element="q41:SecurityAccessDeniedException" />
            </wsdl:message>
            <wsdl:message name="IPCBBackupServerProvider_CancelCleanup_InputMessage">
                <wsdl:part name="parameters" element="tns:CancelCleanup" />
            </wsdl:message>
            <wsdl:message name="IPCBBackupServerProvider_CancelCleanup_OutputMessage">
                <wsdl:part name="parameters" element="tns:CancelCleanupResponse" />
            </wsdl:message>
            <wsdl:message
name="IPCBBackupServerProvider CancelCleanup PCBackupServerFault FaultMessage">
                <wsdl:part
xmlns:q42="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.DataProtection.PCBackup.BackupUtil.WcfContracts" name="detail" element="q42:PCBackupServerFault" />
                </wsdl:message>
                <wsdl:message
name="IPCBBackupServerProvider CancelCleanup SecurityAccessDeniedExceptionFault FaultMessage">
                <wsdl:part
xmlns:q43="http://schemas.datacontract.org/2004/07/System.ServiceModel.Security"
name="detail" element="q43:SecurityAccessDeniedException" />
                </wsdl:message>

```

```

<wsdl:message name="IPCBackupServerProvider_StartRepair_InputMessage">
  <wsdl:part name="parameters" element="tns:StartRepair" />
</wsdl:message>
<wsdl:message name="IPCBackupServerProvider_StartRepair_OutputMessage">
  <wsdl:part name="parameters" element="tns:StartRepairResponse" />
</wsdl:message>
<wsdl:message
  name="IPCBackupServerProvider_StartRepair_PCB backupServerFault_FaultMessage">
  <wsdl:part
    xmlns:q44="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.DataProtection.PCBackup.BackupUtil.WcfContracts" name="detail" element="q44:PCBackupServerFault" />
</wsdl:message>
<wsdl:message
  name="IPCBackupServerProvider_StartRepair_SecurityAccessDeniedExceptionFault_FaultMessage">
  <wsdl:part
    xmlns:q45="http://schemas.datacontract.org/2004/07/System.ServiceModel.Security"
    name="detail" element="q45:SecurityAccessDeniedException" />
</wsdl:message>
<wsdl:message name="IPCBackupServerProvider_CancelRepair_InputMessage">
  <wsdl:part name="parameters" element="tns:CancelRepair" />
</wsdl:message>
<wsdl:message name="IPCBackupServerProvider_CancelRepair_OutputMessage">
  <wsdl:part name="parameters" element="tns:CancelRepairResponse" />
</wsdl:message>
<wsdl:message
  name="IPCBackupServerProvider_CancelRepair_PCB backupServerFault_FaultMessage">
  <wsdl:part
    xmlns:q46="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.DataProtection.PCBackup.BackupUtil.WcfContracts" name="detail" element="q46:PCBackupServerFault" />
</wsdl:message>
<wsdl:message
  name="IPCBackupServerProvider_CancelRepair_SecurityAccessDeniedExceptionFault_FaultMessage">
  <wsdl:part
    xmlns:q47="http://schemas.datacontract.org/2004/07/System.ServiceModel.Security"
    name="detail" element="q47:SecurityAccessDeniedException" />
</wsdl:message>
<wsdl:message name="IPCBackupServerProvider_GetLastRepairResult_InputMessage">
  <wsdl:part name="parameters" element="tns:GetLastRepairResult" />
</wsdl:message>
<wsdl:message name="IPCBackupServerProvider_GetLastRepairResult_OutputMessage">
  <wsdl:part name="parameters" element="tns:GetLastRepairResultResponse" />
</wsdl:message>
<wsdl:message
  name="IPCBackupServerProvider_GetLastRepairResult_PCB backupServerFault_FaultMessage">
  <wsdl:part
    xmlns:q48="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.DataProtection.PCBackup.BackupUtil.WcfContracts" name="detail" element="q48:PCBackupServerFault" />
</wsdl:message>
<wsdl:message
  name="IPCBackupServerProvider_GetLastRepairResult_SecurityAccessDeniedExceptionFault_FaultMessage">
  <wsdl:part
    xmlns:q49="http://schemas.datacontract.org/2004/07/System.ServiceModel.Security"
    name="detail" element="q49:SecurityAccessDeniedException" />
</wsdl:message>
<wsdl:message name="IPCBackupServerProvider_StartConsistencyChecker_InputMessage">
  <wsdl:part name="parameters" element="tns:StartConsistencyChecker" />
</wsdl:message>
<wsdl:message name="IPCBackupServerProvider_StartConsistencyChecker_OutputMessage">
  <wsdl:part name="parameters" element="tns:StartConsistencyCheckerResponse" />
</wsdl:message>
<wsdl:message
  name="IPCBackupServerProvider_StartConsistencyChecker_PCB backupServerFault_FaultMessage">
  <wsdl:part
    xmlns:q50="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.DataProtection.PCBackup.BackupUtil.WcfContracts" name="detail" element="q50:PCBackupServerFault" />
</wsdl:message>

```

```

<wsdl:message
name="IPCBBackupServerProvider_StartConsistencyChecker_SecurityAccessDeniedExceptionFault_FaultMessage">
    <wsdl:part
xmlns:q51="http://schemas.datacontract.org/2004/07/System.ServiceModel.Security"
name="detail" element="q51:SecurityAccessDeniedException" />
</wsdl:message>
<wsdl:message name="IPCBBackupServerProvider_CancelConsistencyChecker_InputMessage">
    <wsdl:part name="parameters" element="tns:CancelConsistencyChecker" />
</wsdl:message>
<wsdl:message name="IPCBBackupServerProvider_CancelConsistencyChecker_OutputMessage">
    <wsdl:part name="parameters" element="tns:CancelConsistencyCheckerResponse" />
</wsdl:message>
<wsdl:message
name="IPCBBackupServerProvider_CancelConsistencyChecker_PCBBackupServerFaultFault_FaultMessage">
    <wsdl:part
xmlns:q52="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.DataProtection.PCBackup.BackupUtil.WcfContracts" name="detail" element="q52:PCBackupServerFault" />
</wsdl:message>
<wsdl:message
name="IPCBBackupServerProvider_CancelConsistencyChecker_SecurityAccessDeniedExceptionFault_FaultMessage">
    <wsdl:part
xmlns:q53="http://schemas.datacontract.org/2004/07/System.ServiceModel.Security"
name="detail" element="q53:SecurityAccessDeniedException" />
</wsdl:message>
<wsdl:message name="IPCBBackupServerProvider_Remove_InputMessage">
    <wsdl:part name="parameters" element="tns:Remove" />
</wsdl:message>
<wsdl:message name="IPCBBackupServerProvider_Remove_OutputMessage">
    <wsdl:part name="parameters" element="tns:RemoveResponse" />
</wsdl:message>
<wsdl:message name="IPCBBackupServerProvider_Remove_PCBBackupServerFaultFault_FaultMessage">
    <wsdl:part
xmlns:q54="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.DataProtection.PCBackup.BackupUtil.WcfContracts" name="detail" element="q54:PCBackupServerFault" />
</wsdl:message>
<wsdl:message
name="IPCBBackupServerProvider_Remove_SecurityAccessDeniedExceptionFault_FaultMessage">
    <wsdl:part
xmlns:q55="http://schemas.datacontract.org/2004/07/System.ServiceModel.Security"
name="detail" element="q55:SecurityAccessDeniedException" />
</wsdl:message>
<wsdl:message name="IPCBBackupServerProvider_CalculateVolumeAsync_InputMessage">
    <wsdl:part name="parameters" element="tns:CalculateVolumeAsync" />
</wsdl:message>
<wsdl:message name="IPCBBackupServerProvider_CalculateVolumeAsync_OutputMessage">
    <wsdl:part name="parameters" element="tns:CalculateVolumeAsyncResponse" />
</wsdl:message>
<wsdl:message
name="IPCBBackupServerProvider_CalculateVolumeAsync_PCBBackupServerFaultFault_FaultMessage">
    <wsdl:part
xmlns:q56="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.DataProtection.PCBackup.BackupUtil.WcfContracts" name="detail" element="q56:PCBackupServerFault" />
</wsdl:message>
<wsdl:message
name="IPCBBackupServerProvider_CalculateVolumeAsync_SecurityAccessDeniedExceptionFault_FaultMessage">
    <wsdl:part
xmlns:q57="http://schemas.datacontract.org/2004/07/System.ServiceModel.Security"
name="detail" element="q57:SecurityAccessDeniedException" />
</wsdl:message>
<wsdl:message name="IPCBBackupServerProvider_GetFolderChildren_InputMessage">
    <wsdl:part name="parameters" element="tns:GetFolderChildren" />
</wsdl:message>
<wsdl:message name="IPCBBackupServerProvider_GetFolderChildren_OutputMessage">
    <wsdl:part name="parameters" element="tns:GetFolderChildrenResponse" />
</wsdl:message>

```

```

<wsdl:message
name="IPCBackupServerProvider_GetFolderChildren_PCBackupServerFault_FaultMessage">
  <wsdl:part
  xmlns:q58="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.DataProtection.PCBackup.BackupUtil.WcfContracts" name="detail" element="q58:PCBackupServerFault" />
</wsdl:message>
<wsdl:message
name="IPCBackupServerProvider_GetFolderChildren_SecurityAccessDeniedExceptionFault_FaultMessage">
  <wsdl:part
  xmlns:q59="http://schemas.datacontract.org/2004/07/System.ServiceModel.Security"
name="detail" element="q59:SecurityAccessDeniedException" />
</wsdl:message>
<wsdl:message name="IPCBackupServerProvider_GetConnectedVolumes_InputMessage">
  <wsdl:part name="parameters" element="tns:GetConnectedVolumes" />
</wsdl:message>
<wsdl:message name="IPCBackupServerProvider_GetConnectedVolumes_OutputMessage">
  <wsdl:part name="parameters" element="tns:GetConnectedVolumesResponse" />
</wsdl:message>
<wsdl:message
name="IPCBackupServerProvider_GetConnectedVolumes_PCBackupServerFault_FaultMessage">
  <wsdl:part
  xmlns:q60="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.DataProtection.PCBackup.BackupUtil.WcfContracts" name="detail" element="q60:PCBackupServerFault" />
</wsdl:message>
<wsdl:message
name="IPCBackupServerProvider_GetConnectedVolumes_SecurityAccessDeniedExceptionFault_FaultMessage">
  <wsdl:part
  xmlns:q61="http://schemas.datacontract.org/2004/07/System.ServiceModel.Security"
name="detail" element="q61:SecurityAccessDeniedException" />
</wsdl:message>
<wsdl:message name="IPCBackupServerProvider_CleanFolderSizeCalculation_InputMessage">
  <wsdl:part name="parameters" element="tns:CleanFolderSizeCalculation" />
</wsdl:message>
<wsdl:message name="IPCBackupServerProvider_StartBackup_InputMessage">
  <wsdl:part name="parameters" element="tns:StartBackup" />
</wsdl:message>
<wsdl:message name="IPCBackupServerProvider_StartBackup_OutputMessage">
  <wsdl:part name="parameters" element="tns:StartBackupResponse" />
</wsdl:message>
<wsdl:message
name="IPCBackupServerProvider_StartBackup_PCBackupServerFault_FaultMessage">
  <wsdl:part
  xmlns:q62="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.DataProtection.PCBackup.BackupUtil.WcfContracts" name="detail" element="q62:PCBackupServerFault" />
</wsdl:message>
<wsdl:message
name="IPCBackupServerProvider_StartBackup_SecurityAccessDeniedExceptionFault_FaultMessage">
  <wsdl:part
  xmlns:q63="http://schemas.datacontract.org/2004/07/System.ServiceModel.Security"
name="detail" element="q63:SecurityAccessDeniedException" />
</wsdl:message>
<wsdl:message name="IPCBackupServerProvider_CancelBackup_InputMessage">
  <wsdl:part name="parameters" element="tns:CancelBackup" />
</wsdl:message>
<wsdl:message name="IPCBackupServerProvider_CancelBackup_OutputMessage">
  <wsdl:part name="parameters" element="tns:CancelBackupResponse" />
</wsdl:message>
<wsdl:message
name="IPCBackupServerProvider_CancelBackup_PCBackupServerFault_FaultMessage">
  <wsdl:part
  xmlns:q64="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.DataProtection.PCBackup.BackupUtil.WcfContracts" name="detail" element="q64:PCBackupServerFault" />
</wsdl:message>
<wsdl:message
name="IPCBackupServerProvider_CancelBackup_SecurityAccessDeniedExceptionFault_FaultMessage">

```

```

<wsdl:part
xmlns:q65="http://schemas.datacontract.org/2004/07/System.ServiceModel.Security"
name="detail" element="q65:SecurityAccessDeniedException" />
</wsdl:message>
<wsdl:message name="IPCBBackupServerProvider_StartBackupService_InputMessage">
    <wsdl:part name="parameters" element="tns:StartBackupService" />
</wsdl:message>
<wsdl:message name="IPCBBackupServerProvider_StartBackupService_OutputMessage">
    <wsdl:part name="parameters" element="tns:StartBackupServiceResponse" />
</wsdl:message>
<wsdl:message
name="IPCBBackupServerProvider_StartBackupService_PCBBackupServerFaultFault_FaultMessage">
    <wsdl:part
xmlns:q66="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.DataProtection.PCBackup.BackupUtil.WcfContracts" name="detail" element="q66:PCBackupServerFault" />
    </wsdl:message>
<wsdl:message
name="IPCBBackupServerProvider_StartBackupService_SecurityAccessDeniedExceptionFault_FaultMessage">
    <wsdl:part
xmlns:q67="http://schemas.datacontract.org/2004/07/System.ServiceModel.Security"
name="detail" element="q67:SecurityAccessDeniedException" />
    </wsdl:message>
<wsdl:message name="IPCBBackupServerProvider_StopBackupService_InputMessage">
    <wsdl:part name="parameters" element="tns:StopBackupService" />
</wsdl:message>
<wsdl:message name="IPCBBackupServerProvider_StopBackupService_OutputMessage">
    <wsdl:part name="parameters" element="tns:StopBackupServiceResponse" />
</wsdl:message>
<wsdl:message
name="IPCBBackupServerProvider_StopBackupService_PCBBackupServerFaultFault_FaultMessage">
    <wsdl:part
xmlns:q68="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.DataProtection.PCBackup.BackupUtil.WcfContracts" name="detail" element="q68:PCBackupServerFault" />
    </wsdl:message>
<wsdl:message
name="IPCBBackupServerProvider_StopBackupService_SecurityAccessDeniedExceptionFault_FaultMessage">
    <wsdl:part
xmlns:q69="http://schemas.datacontract.org/2004/07/System.ServiceModel.Security"
name="detail" element="q69:SecurityAccessDeniedException" />
    </wsdl:message>
<wsdl:message
name="IPCBBackupServerProvider_NotifyBackupOperationStatusChange_OutputCallbackMessage">
    <wsdl:part name="parameters" element="tns:NotifyBackupOperationStatusChange" />
</wsdl:message>
<wsdl:message
name="IPCBBackupServerProvider_VolumeCalculatorProgress_OutputCallbackMessage">
    <wsdl:part name="parameters" element="tns:VolumeCalculatorProgress" />
</wsdl:message>
<wsdl:message
name="IPCBBackupServerProvider_NotifyServiceStatusChange_OutputCallbackMessage">
    <wsdl:part name="parameters" element="tns:NotifyServiceStatusChange" />
</wsdl:message>
<wsdl:message
name="IPCBBackupServerProvider_NotifyBackupClientProviderStatus_OutputCallbackMessage">
    <wsdl:part name="parameters" element="tns:NotifyBackupClientProviderStatus" />
</wsdl:message>
<wsdl:portType name="IPCBBackupServerProvider">
    <wsdl:operation name="Register">
        <wsdl:input wsaw:Action="http://tempuri.org/IPCBBackupServerProvider/Register"
message="tns:IPCBBackupServerProvider_Register_InputMessage" />
        <wsdl:output wsaw:Action="http://tempuri.org/IPCBBackupServerProvider/RegisterResponse"
message="tns:IPCBBackupServerProvider_Register_OutputMessage" />
        <wsdl:fault
wsaw:Action="http://tempuri.org/IPCBBackupServerProvider/RegisterSecurityAccessDeniedException
Fault" name="SecurityAccessDeniedExceptionFault"
message="tns:IPCBBackupServerProvider_Register_SecurityAccessDeniedExceptionFault_FaultMessage
" />

```

```

        </wsdl:operation>
        <wsdl:operation name="GetClients">
            <wsdl:input wsaw:Action="http://tempuri.org/IPCBackupServerProvider/GetClients"
message="tns:IPCBackupServerProvider_GetClients_InputMessage" />
            <wsdl:output
wsaw:Action="http://tempuri.org/IPCBackupServerProvider/GetClientsResponse"
message="tns:IPCBackupServerProvider_GetClients_OutputMessage" />
            <wsdl:fault
wsaw:Action="http://tempuri.org/IPCBackupServerProvider/GetClientsPCBackupServerFaultFault"
name="PCBackupServerFaultFault"
message="tns:IPCBackupServerProvider GetClients PCBackupServerFaultFault FaultMessage" />
            <wsdl:fault
wsaw:Action="http://tempuri.org/IPCBackupServerProvider/GetClientsSecurityAccessDeniedExceptionFault"
name="SecurityAccessDeniedExceptionFault"
message="tns:IPCBackupServerProvider_GetClients_SecurityAccessDeniedExceptionFault_FaultMessage" />
        </wsdl:operation>
        <wsdl:operation name="GetClient">
            <wsdl:input wsaw:Action="http://tempuri.org/IPCBackupServerProvider/GetClient"
message="tns:IPCBackupServerProvider_GetClient_InputMessage" />
            <wsdl:output wsaw:Action="http://tempuri.org/IPCBackupServerProvider/GetClientResponse"
message="tns:IPCBackupServerProvider_GetClient_OutputMessage" />
            <wsdl:fault
wsaw:Action="http://tempuri.org/IPCBackupServerProvider/GetClientPCBackupServerFaultFault"
name="PCBackupServerFaultFault"
message="tns:IPCBackupServerProvider_GetClient_PCBackupServerFaultFault_FaultMessage" />
            <wsdl:fault
wsaw:Action="http://tempuri.org/IPCBackupServerProvider/GetClientSecurityAccessDeniedExceptionFault"
name="SecurityAccessDeniedExceptionFault"
message="tns:IPCBackupServerProvider_GetClient_SecurityAccessDeniedExceptionFault_FaultMessage" />
        </wsdl:operation>
        <wsdl:operation name="OnBattery">
            <wsdl:input wsaw:Action="http://tempuri.org/IPCBackupServerProvider/OnBattery"
message="tns:IPCBackupServerProvider_OnBattery_InputMessage" />
            <wsdl:output wsaw:Action="http://tempuri.org/IPCBackupServerProvider/OnBatteryResponse"
message="tns:IPCBackupServerProvider_OnBattery_OutputMessage" />
            <wsdl:fault
wsaw:Action="http://tempuri.org/IPCBackupServerProvider/OnBatteryPCBackupServerFaultFault"
name="PCBackupServerFaultFault"
message="tns:IPCBackupServerProvider_OnBattery_PCBackupServerFaultFault_FaultMessage" />
            <wsdl:fault
wsaw:Action="http://tempuri.org/IPCBackupServerProvider/OnBatterySecurityAccessDeniedExceptionFault"
name="SecurityAccessDeniedExceptionFault"
message="tns:IPCBackupServerProvider_OnBattery_SecurityAccessDeniedExceptionFault_FaultMessage" />
        </wsdl:operation>
        <wsdl:operation name="GetClientJobs">
            <wsdl:input wsaw:Action="http://tempuri.org/IPCBackupServerProvider/GetClientJobs"
message="tns:IPCBackupServerProvider_GetClientJobs_InputMessage" />
            <wsdl:output
wsaw:Action="http://tempuri.org/IPCBackupServerProvider/GetClientJobsResponse"
message="tns:IPCBackupServerProvider_GetClientJobs_OutputMessage" />
            <wsdl:fault
wsaw:Action="http://tempuri.org/IPCBackupServerProvider/GetClientJobsPCBackupServerFaultFault"
name="PCBackupServerFaultFault"
message="tns:IPCBackupServerProvider GetClientJobs PCBackupServerFaultFault FaultMessage" />
            <wsdl:fault
wsaw:Action="http://tempuri.org/IPCBackupServerProvider/GetClientJobsSecurityAccessDeniedExceptionFault"
name="SecurityAccessDeniedExceptionFault"
message="tns:IPCBackupServerProvider_GetClientJobs_SecurityAccessDeniedExceptionFault_FaultMessage" />
        </wsdl:operation>
        <wsdl:operation name="GetVolumeJobs">
            <wsdl:input wsaw:Action="http://tempuri.org/IPCBackupServerProvider/GetVolumeJobs"
message="tns:IPCBackupServerProvider_GetVolumeJobs_InputMessage" />
            <wsdl:output
wsaw:Action="http://tempuri.org/IPCBackupServerProvider/GetVolumeJobsResponse"
message="tns:IPCBackupServerProvider_GetVolumeJobs_OutputMessage" />

```

```

<wsdl:fault
wsaw:Action="http://tempuri.org/IPCBackupServerProvider/GetVolumeJobsPCBackupServerFaultFault"
" name="PCBackupServerFaultFault"
message="tns:IPCBackupServerProvider_GetVolumeJobs_PCB backupServerFaultFault_FaultMessage" />
<wsdl:fault
wsaw:Action="http://tempuri.org/IPCBackupServerProvider/GetVolumeJobsSecurityAccessDeniedExceptionFault" name="SecurityAccessDeniedExceptionFault"
message="tns:IPCBackupServerProvider_GetVolumeJobs_SecurityAccessDeniedExceptionFault_FaultMessage" />
</wsdl:operation>
<wsdl:operation name="GetClientVolumes">
<wsdl:input wsaw:Action="http://tempuri.org/IPCBackupServerProvider/GetClientVolumes"
message="tns:IPCBackupServerProvider_GetClientVolumes_InputMessage" />
<wsdl:output
wsaw:Action="http://tempuri.org/IPCBackupServerProvider/GetClientVolumesResponse"
message="tns:IPCBackupServerProvider_GetClientVolumes_OutputMessage" />
<wsdl:fault
wsaw:Action="http://tempuri.org/IPCBackupServerProvider/GetClientVolumesPCBackupServerFaultFault"
" name="PCBackupServerFaultFault"
message="tns:IPCBackupServerProvider_GetClientVolumes_PCB backupServerFaultFault_FaultMessage" />
<wsdl:fault
wsaw:Action="http://tempuri.org/IPCBackupServerProvider/GetClientVolumesSecurityAccessDeniedExceptionFault" name="SecurityAccessDeniedExceptionFault"
message="tns:IPCBackupServerProvider_GetClientVolumes_SecurityAccessDeniedExceptionFault_FaultMessage" />
</wsdl:operation>
<wsdl:operation name="SetClientJobDescription">
<wsdl:input
wsaw:Action="http://tempuri.org/IPCBackupServerProvider/SetClientJobDescription"
message="tns:IPCBackupServerProvider_SetClientJobDescription_InputMessage" />
<wsdl:output
wsaw:Action="http://tempuri.org/IPCBackupServerProvider/SetClientJobDescriptionResponse"
message="tns:IPCBackupServerProvider_SetClientJobDescription_OutputMessage" />
<wsdl:fault
wsaw:Action="http://tempuri.org/IPCBackupServerProvider/SetClientJobDescriptionPCBackupServerFaultFault"
" name="PCBackupServerFaultFault"
message="tns:IPCBackupServerProvider_SetClientJobDescription_PCB backupServerFaultFault_FaultMessage" />
<wsdl:fault
wsaw:Action="http://tempuri.org/IPCBackupServerProvider/SetClientJobDescriptionSecurityAccessDeniedExceptionFault" name="SecurityAccessDeniedExceptionFault"
message="tns:IPCBackupServerProvider_SetClientJobDescription_SecurityAccessDeniedExceptionFault_FaultMessage" />
</wsdl:operation>
<wsdl:operation name="SetClientJobRetentionState">
<wsdl:input
wsaw:Action="http://tempuri.org/IPCBackupServerProvider/SetClientJobRetentionState"
message="tns:IPCBackupServerProvider_SetClientJobRetentionState_InputMessage" />
<wsdl:output
wsaw:Action="http://tempuri.org/IPCBackupServerProvider/SetClientJobRetentionStateResponse"
message="tns:IPCBackupServerProvider_SetClientJobRetentionState_OutputMessage" />
<wsdl:fault
wsaw:Action="http://tempuri.org/IPCBackupServerProvider/SetClientJobRetentionStatePCBackupServerFaultFault"
" name="PCBackupServerFaultFault"
message="tns:IPCBackupServerProvider_SetClientJobRetentionState_PCB backupServerFaultFault_FaultMessage" />
<wsdl:fault
wsaw:Action="http://tempuri.org/IPCBackupServerProvider/SetClientJobRetentionStateSecurityAccessDeniedExceptionFault" name="SecurityAccessDeniedExceptionFault"
message="tns:IPCBackupServerProvider_SetClientJobRetentionState_SecurityAccessDeniedExceptionFault_FaultMessage" />
</wsdl:operation>
<wsdl:operation name="SetClientVolumeStatus">
<wsdl:input
wsaw:Action="http://tempuri.org/IPCBackupServerProvider/SetClientVolumeStatus"
message="tns:IPCBackupServerProvider_SetClientVolumeStatus_InputMessage" />

```

```

<wsdl:output
wsaw:Action="http://tempuri.org/IPCBackupServerProvider/SetClientVolumeStatusResponse"
message="tns:IPCBackupServerProvider_SetClientVolumeStatus_OutputMessage" />
    <wsdl:fault
wsaw:Action="http://tempuri.org/IPCBackupServerProvider/SetClientVolumeStatusPCBackupServerFa
ultFault" name="PCBackupServerFaultFault"
message="tns:IPCBackupServerProvider_SetClientVolumeStatus_PCBackupServerFaultFault_FaultMess
age" />
    <wsdl:fault
wsaw:Action="http://tempuri.org/IPCBackupServerProvider/SetClientVolumeStatusSecurityAccessDe
niedExceptionFault" name="SecurityAccessDeniedExceptionFault"
message="tns:IPCBackupServerProvider_SetClientVolumeStatus_SecurityAccessDeniedExceptionFault
_FaultMessage" />
</wsdl:operation>
<wsdl:operation name="SetExcludedFolders">
    <wsdl:input wsaw:Action="http://tempuri.org/IPCBackupServerProvider/SetExcludedFolders"
message="tns:IPCBackupServerProvider_SetExcludedFolders_InputMessage" />
    <wsdl:output
wsaw:Action="http://tempuri.org/IPCBackupServerProvider/SetExcludedFoldersResponse"
message="tns:IPCBackupServerProvider_SetExcludedFolders_OutputMessage" />
    <wsdl:fault
wsaw:Action="http://tempuri.org/IPCBackupServerProvider/SetExcludedFoldersSecurityAccessDenie
dExceptionFault" name="SecurityAccessDeniedExceptionFault"
message="tns:IPCBackupServerProvider_SetExcludedFolders_SecurityAccessDeniedExceptionFault_Fa
ultMessage" />
    <wsdl:fault
wsaw:Action="http://tempuri.org/IPCBackupServerProvider/SetExcludedFoldersPCBackupServerFault
Fault" name="PCBackupServerFaultFault"
message="tns:IPCBackupServerProvider_SetExcludedFolders_PCBackupServerFaultFault_FaultMessage
" />
    </wsdl:operation>
    <wsdl:operation name="EnableBackups">
        <wsdl:input wsaw:Action="http://tempuri.org/IPCBackupServerProvider/EnableBackups"
message="tns:IPCBackupServerProvider_EnableBackups_InputMessage" />
        <wsdl:output
wsaw:Action="http://tempuri.org/IPCBackupServerProvider/EnableBackupsResponse"
message="tns:IPCBackupServerProvider_EnableBackups_OutputMessage" />
        <wsdl:fault
wsaw:Action="http://tempuri.org/IPCBackupServerProvider/EnableBackupsPCBackupServerFaultFault
" name="PCBackupServerFaultFault"
message="tns:IPCBackupServerProvider_EnableBackups_PCBackupServerFaultFault_FaultMessage" />
        <wsdl:fault
wsaw:Action="http://tempuri.org/IPCBackupServerProvider/EnableBackupsSecurityAccessDeniedExce
ptionFault" name="SecurityAccessDeniedExceptionFault"
message="tns:IPCBackupServerProvider_EnableBackups_SecurityAccessDeniedExceptionFault_FaultMe
ssage" />
        </wsdl:operation>
        <wsdl:operation name="DisableBackups">
            <wsdl:input wsaw:Action="http://tempuri.org/IPCBackupServerProvider/DisableBackups"
message="tns:IPCBackupServerProvider_DisableBackups_InputMessage" />
            <wsdl:output
wsaw:Action="http://tempuri.org/IPCBackupServerProvider/DisableBackupsResponse"
message="tns:IPCBackupServerProvider_DisableBackups_OutputMessage" />
            <wsdl:fault
wsaw:Action="http://tempuri.org/IPCBackupServerProvider/DisableBackupsPCBackupServerFaultFaul
t" name="PCBackupServerFaultFault"
message="tns:IPCBackupServerProvider_DisableBackups_PCBackupServerFaultFault_FaultMessage" />
            <wsdl:fault
wsaw:Action="http://tempuri.org/IPCBackupServerProvider/DisableBackupsSecurityAccessDeniedExc
eptionFault" name="SecurityAccessDeniedExceptionFault"
message="tns:IPCBackupServerProvider_DisableBackups_SecurityAccessDeniedExceptionFault_FaultM
essage" />
        </wsdl:operation>
        <wsdl:operation name="GetBackupConfiguration">
            <wsdl:input
wsaw:Action="http://tempuri.org/IPCBackupServerProvider/GetBackupConfiguration"
message="tns:IPCBackupServerProvider_GetBackupConfiguration_InputMessage" />

```

```

<wsdl:output
wsaw:Action="http://tempuri.org/IPCBackupServerProvider/GetBackupConfigurationResponse"
message="tns:IPCBackupServerProvider_GetBackupConfiguration_OutputMessage" />
    <wsdl:fault
wsaw:Action="http://tempuri.org/IPCBackupServerProvider/GetBackupConfigurationPCBackupServerF
aultFault" name="PCBackupServerFaultFault"
message="tns:IPCBackupServerProvider_GetBackupConfiguration_PCB backupServerFaultFault_FaultMes
sage" />
    <wsdl:fault
wsaw:Action="http://tempuri.org/IPCBackupServerProvider/GetBackupConfigurationSecurityAccessD
eniedExceptionFault" name="SecurityAccessDeniedExceptionFault"
message="tns:IPCBackupServerProvider_GetBackupConfiguration_SecurityAccessDeniedExceptionFa
ult_FaultMessage" />
    </wsdl:operation>
    <wsdl:operation name="GetDefaultBackupConfiguration">
        <wsdl:input
wsaw:Action="http://tempuri.org/IPCBackupServerProvider/GetDefaultBackupConfiguration"
message="tns:IPCBackupServerProvider_GetDefaultBackupConfiguration_InputMessage" />
        <wsdl:output
wsaw:Action="http://tempuri.org/IPCBackupServerProvider/GetDefaultBackupConfigurationResponse"
" message="tns:IPCBackupServerProvider_GetDefaultBackupConfiguration_OutputMessage" />
        <wsdl:fault
wsaw:Action="http://tempuri.org/IPCBackupServerProvider/GetDefaultBackupConfigurationPCBackup
ServerFaultFault" name="PCBackupServerFaultFault"
message="tns:IPCBackupServerProvider_GetDefaultBackupConfiguration_PCB backupServerFaultFault_F
aultMessage" />
        <wsdl:fault
wsaw:Action="http://tempuri.org/IPCBackupServerProvider/GetDefaultBackupConfigurationSecurity
AccessDeniedExceptionFault" name="SecurityAccessDeniedExceptionFault"
message="tns:IPCBackupServerProvider_GetDefaultBackupConfiguration_SecurityAccessDeniedExcept
ionFault FaultMessage" />
        </wsdl:operation>
        <wsdl:operation name="GetBackupOperationStatus">
            <wsdl:input
wsaw:Action="http://tempuri.org/IPCBackupServerProvider/GetBackupOperationStatus"
message="tns:IPCBackupServerProvider_GetBackupOperationStatus_InputMessage" />
            <wsdl:output
wsaw:Action="http://tempuri.org/IPCBackupServerProvider/GetBackupOperationStatusResponse"
message="tns:IPCBackupServerProvider_GetBackupOperationStatus_OutputMessage" />
            <wsdl:fault
wsaw:Action="http://tempuri.org/IPCBackupServerProvider/GetBackupOperationStatusPCBackupS
erve rFaultFault" name="PCBackupServerFaultFault"
message="tns:IPCBackupServerProvider_GetBackupOperationStatus_PCB backupServerFaultFault_FaultM
essage" />
            <wsdl:fault
wsaw:Action="http://tempuri.org/IPCBackupServerProvider/GetBackupOperationStatusSecurityAcces
sDeniedExceptionFault" name="SecurityAccessDeniedExceptionFault"
message="tns:IPCBackupServerProvider_GetBackupOperationStatus_SecurityAccessDeniedExceptionFa
ult_FaultMessage" />
            </wsdl:operation>
            <wsdl:operation name="GetServiceStatus">
                <wsdl:input wsaw:Action="http://tempuri.org/IPCBackupServerProvider/GetServiceStatus"
message="tns:IPCBackupServerProvider_GetServiceStatus_InputMessage" />
                <wsdl:output
wsaw:Action="http://tempuri.org/IPCBackupServerProvider/GetServiceStatusResponse"
message="tns:IPCBackupServerProvider_GetServiceStatus_OutputMessage" />
                <wsdl:fault
wsaw:Action="http://tempuri.org/IPCBackupServerProvider/GetServiceStatusPCBackupServerFaultFa
ult" name="PCBackupServerFaultFault"
message="tns:IPCBackupServerProvider_GetServiceStatus_PCB backupServerFaultFault_FaultMessage"
/>
                <wsdl:fault
wsaw:Action="http://tempuri.org/IPCBackupServerProvider/GetServiceStatusSecurityAccessDeniedE
xceptionFault" name="SecurityAccessDeniedExceptionFault"
message="tns:IPCBackupServerProvider_GetServiceStatus_SecurityAccessDeniedExceptionFault Fa
ultMessage" />
            </wsdl:operation>
            <wsdl:operation name="GetWaitingOperations">

```

```

<wsdl:input
wsaw:Action="http://tempuri.org/IPCBackupServerProvider/GetWaitingOperations"
message="tns:IPCBackupServerProvider_GetWaitingOperations_InputMessage" />
    <wsdl:output
wsaw:Action="http://tempuri.org/IPCBackupServerProvider/GetWaitingOperationsResponse"
message="tns:IPCBackupServerProvider GetWaitingOperations OutputMessage" />
    <wsdl:fault
wsaw:Action="http://tempuri.org/IPCBackupServerProvider/GetWaitingOperationsPCBackupServerFau
ltFault" name="PCBackupServerFaultFault"
message="tns:IPCBackupServerProvider_GetWaitingOperations_PCB backupServerFaultFault_FaultMessa
ge" />
    <wsdl:fault
wsaw:Action="http://tempuri.org/IPCBackupServerProvider/GetWaitingOperationsSecurityAccessDen
iedExceptionFault" name="SecurityAccessDeniedExceptionFault"
message="tns:IPCBackupServerProvider_GetWaitingOperations_SecurityAccessDeniedExceptionFault_
FaultMessage" />
</wsdl:operation>
<wsdl:operation name="SetBackupConfiguration">
    <wsdl:input
wsaw:Action="http://tempuri.org/IPCBackupServerProvider/SetBackupConfiguration"
messages="tns:IPCBackupServerProvider_SetBackupConfiguration_InputMessage" />
        <wsdl:output
wsaw:Action="http://tempuri.org/IPCBackupServerProvider/SetBackupConfigurationResponse"
message="tns:IPCBackupServerProvider_SetBackupConfiguration_OutputMessage" />
        <wsdl:fault
wsaw:Action="http://tempuri.org/IPCBackupServerProvider/SetBackupConfigurationPCBackupServerF
aultFault" name="PCBackupServerFaultFault"
message="tns:IPCBackupServerProvider_SetBackupConfiguration_PCB backupServerFaultFault_FaultMes
age" />
        <wsdl:fault
wsaw:Action="http://tempuri.org/IPCBackupServerProvider/SetBackupConfigurationSecurityAccessD
eniedExceptionFault" name="SecurityAccessDeniedExceptionFault"
message="tns:IPCBackupServerProvider_SetBackupConfiguration_SecurityAccessDeniedExceptionFaul
t FaultMessage" />
</wsdl:operation>
<wsdl:operation name="GetUsedBytes">
    <wsdl:input wsaw:Action="http://tempuri.org/IPCBackupServerProvider/GetUsedBytes"
message="tns:IPCBackupServerProvider_GetUsedBytes_InputMessage" />
        <wsdl:output
wsaw:Action="http://tempuri.org/IPCBackupServerProvider/GetUsedBytesResponse"
message="tns:IPCBackupServerProvider_GetUsedBytes_OutputMessage" />
        <wsdl:fault
wsaw:Action="http://tempuri.org/IPCBackupServerProvider/GetUsedBytesPCBackupServerFaultFault"
name="PCBackupServerFaultFault"
message="tns:IPCBackupServerProvider_GetUsedBytes_PCB backupServerFaultFault_FaultMessage" />
        <wsdl:fault
wsaw:Action="http://tempuri.org/IPCBackupServerProvider/GetUsedBytesSecurityAccessDeniedExcep
tionFault" name="SecurityAccessDeniedExceptionFault"
message="tns:IPCBackupServerProvider_GetUsedBytes_SecurityAccessDeniedExceptionFault_FaultMes
age" />
</wsdl:operation>
<wsdl:operation name="StartCleanup">
    <wsdl:input wsaw:Action="http://tempuri.org/IPCBackupServerProvider/StartCleanup"
message="tns:IPCBackupServerProvider_StartCleanup_InputMessage" />
        <wsdl:output
wsaw:Action="http://tempuri.org/IPCBackupServerProvider/StartCleanupResponse"
message="tns:IPCBackupServerProvider_StartCleanup_OutputMessage" />
        <wsdl:fault
wsaw:Action="http://tempuri.org/IPCBackupServerProvider/StartCleanupPCBackupServerFaultFault"
name="PCBackupServerFaultFault"
message="tns:IPCBackupServerProvider_StartCleanup_PCB backupServerFaultFault_FaultMessage" />
        <wsdl:fault
wsaw:Action="http://tempuri.org/IPCBackupServerProvider/StartCleanupSecurityAccessDeniedExcep
tionFault" name="SecurityAccessDeniedExceptionFault"
message="tns:IPCBackupServerProvider_StartCleanup_SecurityAccessDeniedExceptionFault_FaultMes
age" />
</wsdl:operation>
<wsdl:operation name="CancelCleanup">

```

```

<wsdl:input wsaw:Action="http://tempuri.org/IPCBackupServerProvider/CancelCleanup"
message="tns:IPCBackupServerProvider_CancelCleanup_InputMessage" />
    <wsdl:output
wsaw:Action="http://tempuri.org/IPCBackupServerProvider/CancelCleanupResponse"
message="tns:IPCBackupServerProvider_CancelCleanup_OutputMessage" />
    <wsdl:fault
wsaw:Action="http://tempuri.org/IPCBackupServerProvider/CancelCleanupPCBackupServerFaultFault
" name="PCBackupServerFaultFault"
message="tns:IPCBackupServerProvider_CancelCleanup_PCBackupServerFaultFault_FaultMessage" />
    <wsdl:fault
wsaw:Action="http://tempuri.org/IPCBackupServerProvider/CancelCleanupSecurityAccessDeniedExce
ptionFault" name="SecurityAccessDeniedExceptionFault"
message="tns:IPCBackupServerProvider_CancelCleanup_SecurityAccessDeniedExceptionFault_FaultMe
ssage" />
    </wsdl:operation>
<wsdl:operation name="StartRepair">
    <wsdl:input wsaw:Action="http://tempuri.org/IPCBackupServerProvider/StartRepair"
message="tns:IPCBackupServerProvider_StartRepair_InputMessage" />
    <wsdl:output
wsaw:Action="http://tempuri.org/IPCBackupServerProvider/StartRepairResponse"
message="tns:IPCBackupServerProvider_StartRepair_OutputMessage" />
    <wsdl:fault
wsaw:Action="http://tempuri.org/IPCBackupServerProvider/StartRepairPCBackupServerFaultFault"
name="PCBackupServerFaultFault"
message="tns:IPCBackupServerProvider_StartRepair_PCBackupServerFaultFault_FaultMessage" />
    <wsdl:fault
wsaw:Action="http://tempuri.org/IPCBackupServerProvider/StartRepairSecurityAccessDeniedExcep
tionFault" name="SecurityAccessDeniedExceptionFault"
message="tns:IPCBackupServerProvider_StartRepair_SecurityAccessDeniedExceptionFault_FaultMess
age" />
    </wsdl:operation>
<wsdl:operation name="CancelRepair">
    <wsdl:input wsaw:Action="http://tempuri.org/IPCBackupServerProvider/CancelRepair"
message="tns:IPCBackupServerProvider_CancelRepair_InputMessage" />
    <wsdl:output
wsaw:Action="http://tempuri.org/IPCBackupServerProvider/CancelRepairResponse"
message="tns:IPCBackupServerProvider_CancelRepair_OutputMessage" />
    <wsdl:fault
wsaw:Action="http://tempuri.org/IPCBackupServerProvider/CancelRepairPCBackupServerFaultFault"
name="PCBackupServerFaultFault"
message="tns:IPCBackupServerProvider_CancelRepair_PCBackupServerFaultFault_FaultMessage" />
    <wsdl:fault
wsaw:Action="http://tempuri.org/IPCBackupServerProvider/CancelRepairSecurityAccessDeniedExcep
tionFault" name="SecurityAccessDeniedExceptionFault"
message="tns:IPCBackupServerProvider_CancelRepair_SecurityAccessDeniedExceptionFault_FaultMes
age" />
    </wsdl:operation>
<wsdl:operation name="GetLastRepairResult">
    <wsdl:input
wsaw:Action="http://tempuri.org/IPCBackupServerProvider/GetLastRepairResult"
message="tns:IPCBackupServerProvider_GetLastRepairResult_InputMessage" />
    <wsdl:output
wsaw:Action="http://tempuri.org/IPCBackupServerProvider/GetLastRepairResultResponse"
message="tns:IPCBackupServerProvider_GetLastRepairResult_OutputMessage" />
    <wsdl:fault
wsaw:Action="http://tempuri.org/IPCBackupServerProvider/GetLastRepairResultPCBackupServerFau
ltFault" name="PCBackupServerFaultFault"
message="tns:IPCBackupServerProvider_GetLastRepairResult_PCBackupServerFaultFault_FaultMessag
e" />
    <wsdl:fault
wsaw:Action="http://tempuri.org/IPCBackupServerProvider/GetLastRepairResultSecurityAccessDeni
edExceptionFault" name="SecurityAccessDeniedExceptionFault"
message="tns:IPCBackupServerProvider_GetLastRepairResult_SecurityAccessDeniedExceptionFault_F
aultMessage" />
    </wsdl:operation>
<wsdl:operation name="StartConsistencyChecker">
    <wsdl:input
wsaw:Action="http://tempuri.org/IPCBackupServerProvider/StartConsistencyChecker"
message="tns:IPCBackupServerProvider_StartConsistencyChecker_InputMessage" />

```

```

<wsdl:output
wsaw:Action="http://tempuri.org/IPCBackupServerProvider/StartConsistencyCheckerResponse"
message="tns:IPCBackupServerProvider_StartConsistencyChecker_OutputMessage" />
    <wsdl:fault
wsaw:Action="http://tempuri.org/IPCBackupServerProvider/StartConsistencyCheckerPCBackupServer
FaultFault" name="PCBackupServerFaultFault"
message="tns:IPCBackupServerProvider_StartConsistencyChecker_PCBackupServerFaultFault_FaultMe
ssage" />
        <wsdl:fault
wsaw:Action="http://tempuri.org/IPCBackupServerProvider/StartConsistencyCheckerSecurityAccess
DeniedExceptionFault" name="SecurityAccessDeniedExceptionFault"
message="tns:IPCBackupServerProvider_StartConsistencyChecker_SecurityAccessDeniedExceptionFa
lt_FaultMessage" />
    </wsdl:operation>
    <wsdl:operation name="CancelConsistencyChecker">
        <wsdl:input
wsaw:Action="http://tempuri.org/IPCBackupServerProvider/CancelConsistencyChecker"
message="tns:IPCBackupServerProvider_CancelConsistencyChecker_InputMessage" />
        <wsdl:output
wsaw:Action="http://tempuri.org/IPCBackupServerProvider/CancelConsistencyCheckerResponse"
message="tns:IPCBackupServerProvider_CancelConsistencyChecker_OutputMessage" />
        <wsdl:fault
wsaw:Action="http://tempuri.org/IPCBackupServerProvider/CancelConsistencyCheckerPCBackupServ
erFaultFault" name="PCBackupServerFaultFault"
message="tns:IPCBackupServerProvider_CancelConsistencyChecker_PCBackupServerFaultFault_FaultM
essage" />
        <wsdl:fault
wsaw:Action="http://tempuri.org/IPCBackupServerProvider/CancelConsistencyCheckerSecurityAcces
sDeniedExceptionFault" name="SecurityAccessDeniedExceptionFault"
message="tns:IPCBackupServerProvider_CancelConsistencyChecker_SecurityAccessDeniedExceptionFa
ult_FaultMessage" />
    </wsdl:operation>
    <wsdl:operation name="Remove">
        <wsdl:input wsaw:Action="http://tempuri.org/IPCBackupServerProvider/Remove"
message="tns:IPCBackupServerProvider_Remove_InputMessage" />
        <wsdl:output wsaw:Action="http://tempuri.org/IPCBackupServerProvider/RemoveResponse"
message="tns:IPCBackupServerProvider_Remove_OutputMessage" />
        <wsdl:fault
wsaw:Action="http://tempuri.org/IPCBackupServerProvider/RemovePCBackupServerFaultFault"
name="PCBackupServerFaultFault"
message="tns:IPCBackupServerProvider_Remove_PCBackupServerFaultFault_FaultMessage" />
        <wsdl:fault
wsaw:Action="http://tempuri.org/IPCBackupServerProvider/RemoveSecurityAccessDeniedExceptionFa
ult" name="SecurityAccessDeniedExceptionFault"
message="tns:IPCBackupServerProvider_Remove_SecurityAccessDeniedExceptionFault_FaultMessage"
/>
    </wsdl:operation>
    <wsdl:operation name="CalculateVolumeAsync">
        <wsdl:input
wsaw:Action="http://tempuri.org/IPCBackupServerProvider/CalculateVolumeAsync"
message="tns:IPCBackupServerProvider_CalculateVolumeAsync_InputMessage" />
        <wsdl:output
wsaw:Action="http://tempuri.org/IPCBackupServerProvider/CalculateVolumeAsyncResponse"
message="tns:IPCBackupServerProvider_CalculateVolumeAsync_OutputMessage" />
        <wsdl:fault
wsaw:Action="http://tempuri.org/IPCBackupServerProvider/CalculateVolumeAsyncPCBackupServerFau
ltFault" name="PCBackupServerFaultFault"
message="tns:IPCBackupServerProvider_CalculateVolumeAsync_PCBackupServerFaultFault_FaultMessa
ge" />
        <wsdl:fault
wsaw:Action="http://tempuri.org/IPCBackupServerProvider/CalculateVolumeAsyncSecurityAccessDen
iedExceptionFault" name="SecurityAccessDeniedExceptionFault"
message="tns:IPCBackupServerProvider_CalculateVolumeAsync_SecurityAccessDeniedExceptionFault
FaultMessage" />
    </wsdl:operation>
    <wsdl:operation name="GetFolderChildren">
        <wsdl:input wsaw:Action="http://tempuri.org/IPCBackupServerProvider/GetFolderChildren"
message="tns:IPCBackupServerProvider_GetFolderChildren_InputMessage" />

```

```

<wsdl:output
wsaw:Action="http://tempuri.org/IPCBackupServerProvider/GetFolderChildrenResponse"
message="tns:IPCBackupServerProvider_GetFolderChildren_OutputMessage" />
    <wsdl:fault
wsaw:Action="http://tempuri.org/IPCBackupServerProvider/GetFolderChildrenPCBackupServerFault
Fault" name="PCBackupServerFaultFault"
message="tns:IPCBackupServerProvider_GetFolderChildren_PCBackupServerFaultFault_FaultMessage"
/>
    <wsdl:fault
wsaw:Action="http://tempuri.org/IPCBackupServerProvider/GetFolderChildrenSecurityAccessDenied
ExceptionFault" name="SecurityAccessDeniedExceptionFault"
message="tns:IPCBackupServerProvider_GetFolderChildren_SecurityAccessDeniedExceptionFault_Fau
ltMessage" />
</wsdl:operation>
<wsdl:operation name="GetConnectedVolumes">
    <wsdl:input
wsaw:Action="http://tempuri.org/IPCBackupServerProvider/GetConnectedVolumes"
message="tns:IPCBackupServerProvider_GetConnectedVolumes_InputMessage" />
    <wsdl:output
wsaw:Action="http://tempuri.org/IPCBackupServerProvider/GetConnectedVolumesResponse"
message="tns:IPCBackupServerProvider_GetConnectedVolumes_OutputMessage" />
    <wsdl:fault
wsaw:Action="http://tempuri.org/IPCBackupServerProvider/GetConnectedVolumesPCBackupServerFa
ultFault" name="PCBackupServerFaultFault"
message="tns:IPCBackupServerProvider_GetConnectedVolumes_PCBackupServerFaultFault_FaultMessag
e" />
    <wsdl:fault
wsaw:Action="http://tempuri.org/IPCBackupServerProvider/GetConnectedVolumesSecurityAccessDeni
edExceptionFault" name="SecurityAccessDeniedExceptionFault"
message="tns:IPCBackupServerProvider_GetConnectedVolumes_SecurityAccessDeniedExceptionFault_F
aultMessage" />
</wsdl:operation>
<wsdl:operation name="CleanFolderPathCalculation">
    <wsdl:input
wsaw:Action="http://tempuri.org/IPCBackupServerProvider/CleanFolderPathCalculation"
message="tns:IPCBackupServerProvider_CleanFolderPathCalculation_InputMessage" />
    </wsdl:operation>
    <wsdl:operation name="StartBackup">
        <wsdl:input wsaw:Action="http://tempuri.org/IPCBackupServerProvider/StartBackup"
message="tns:IPCBackupServerProvider_StartBackup_InputMessage" />
        <wsdl:output
wsaw:Action="http://tempuri.org/IPCBackupServerProvider/StartBackupResponse"
message="tns:IPCBackupServerProvider_StartBackup_OutputMessage" />
        <wsdl:fault
wsaw:Action="http://tempuri.org/IPCBackupServerProvider/StartBackupPCBackupServerFaultFault"
name="PCBackupServerFaultFault"
message="tns:IPCBackupServerProvider_StartBackup_PCBackupServerFaultFault_FaultMessage" />
        <wsdl:fault
wsaw:Action="http://tempuri.org/IPCBackupServerProvider/StartBackupSecurityAccessDeniedExcept
ionFault" name="SecurityAccessDeniedExceptionFault"
message="tns:IPCBackupServerProvider_StartBackup_SecurityAccessDeniedExceptionFault_FaultMes
age" />
    </wsdl:operation>
    <wsdl:operation name="CancelBackup">
        <wsdl:input wsaw:Action="http://tempuri.org/IPCBackupServerProvider/CancelBackup"
message="tns:IPCBackupServerProvider_CancelBackup_InputMessage" />
        <wsdl:output
wsaw:Action="http://tempuri.org/IPCBackupServerProvider/CancelBackupResponse"
message="tns:IPCBackupServerProvider_CancelBackup_OutputMessage" />
        <wsdl:fault
wsaw:Action="http://tempuri.org/IPCBackupServerProvider/CancelBackupPCBackupServerFaultFault"
name="PCBackupServerFaultFault"
message="tns:IPCBackupServerProvider_CancelBackup_PCBackupServerFaultFault_FaultMessage" />
        <wsdl:fault
wsaw:Action="http://tempuri.org/IPCBackupServerProvider/CancelBackupSecurityAccessDeniedExcep
tionFault" name="SecurityAccessDeniedExceptionFault"
message="tns:IPCBackupServerProvider_CancelBackup_SecurityAccessDeniedExceptionFault_FaultMes
age" />
    </wsdl:operation>

```

```

<wsdl:operation name="StartBackupService">
    <wsdl:input wsaw:Action="http://tempuri.org/IPCBackupServerProvider/StartBackupService"
    message="tns:IPCBackupServerProvider_StartBackupService_InputMessage" />
    <wsdl:output
    wsaw:Action="http://tempuri.org/IPCBackupServerProvider/StartBackupServiceResponse"
    message="tns:IPCBackupServerProvider StartBackupService OutputMessage" />
    <wsdl:fault
    wsaw:Action="http://tempuri.org/IPCBackupServerProvider/StartBackupServicePCBackupServerFault
    Fault" name="PCBackupServerFaultFault"
    message="tns:IPCBackupServerProvider_StartBackupService_PCBackupServerFaultFault_FaultMessage
    " />
    <wsdl:fault
    wsaw:Action="http://tempuri.org/IPCBackupServerProvider/StartBackupServiceSecurityAccessDenie
    dExceptionFault" name="SecurityAccessDeniedExceptionFault"
    message="tns:IPCBackupServerProvider_StartBackupService_SecurityAccessDeniedExceptionFault_Fa
    ultMessage" />
</wsdl:operation>
<wsdl:operation name="StopBackupService">
    <wsdl:input wsaw:Action="http://tempuri.org/IPCBackupServerProvider/StopBackupService"
    message="tns:IPCBackupServerProvider_StopBackupService_InputMessage" />
    <wsdl:output
    wsaw:Action="http://tempuri.org/IPCBackupServerProvider/StopBackupServiceResponse"
    message="tns:IPCBackupServerProvider StopBackupService OutputMessage" />
    <wsdl:fault
    wsaw:Action="http://tempuri.org/IPCBackupServerProvider/StopBackupServicePCBackupServerFaultF
    ault" name="PCBackupServerFaultFault"
    message="tns:IPCBackupServerProvider_StopBackupService_PCBackupServerFaultFault_FaultMessage"
    />
    <wsdl:fault
    wsaw:Action="http://tempuri.org/IPCBackupServerProvider/StopBackupServiceSecurityAccessDenied
    ExceptionFault" name="SecurityAccessDeniedExceptionFault"
    message="tns:IPCBackupServerProvider_StopBackupService_SecurityAccessDeniedExceptionFault_Fau
    ltMessage" />
</wsdl:operation>
<wsdl:operation name="NotifyBackupOperationStatusChange">
    <wsdl:output
    wsaw:Action="http://tempuri.org/IPCBackupServerProvider/NotifyBackupOperationStatusChange"
    message="tns:IPCBackupServerProvider_NotifyBackupOperationStatusChange_OutputCallbackMessage"
    />
</wsdl:operation>
<wsdl:operation name="VolumeCalculatorProgress">
    <wsdl:output
    wsaw:Action="http://tempuri.org/IPCBackupServerProvider/VolumeCalculatorProgress"
    message="tns:IPCBackupServerProvider_VolumeCalculatorProgress_OutputCallbackMessage" />
</wsdl:operation>
<wsdl:operation name="NotifyServiceStatusChange">
    <wsdl:output
    wsaw:Action="http://tempuri.org/IPCBackupServerProvider/NotifyServiceStatusChange"
    message="tns:IPCBackupServerProvider_NotifyServiceStatusChange_OutputCallbackMessage" />
</wsdl:operation>
<wsdl:operation name="NotifyBackupClientProviderStatus">
    <wsdl:output
    wsaw:Action="http://tempuri.org/IPCBackupServerProvider/NotifyBackupClientProviderStatus"
    message="tns:IPCBackupServerProvider NotifyBackupClientProviderStatus OutputCallbackMessage"
    />
    </wsdl:operation>
</wsdl:portType>
<wsdl:binding name="CustomBinding_IPCBackupServerProvider"
type="tns:IPCBackupServerProvider">
    <wsp:PolicyReference URI="#CustomBinding_IPCBackupServerProvider_policy" />
    <soap12:binding transport="http://schemas.microsoft.com/soap/tcp" />
    <wsdl:operation name="Register">
        <soap12:operation soapAction="http://tempuri.org/IPCBackupServerProvider/Register"
        style="document" />
        <wsdl:input>
            <soap12:body use="literal" />
        </wsdl:input>
        <wsdl:output>
            <soap12:body use="literal" />
        </wsdl:output>
    </wsdl:operation>
</wsdl:binding>

```

```

        </wsdl:output>
        <wsdl:fault name="SecurityAccessDeniedExceptionFault">
            <soap12:fault use="literal" name="SecurityAccessDeniedExceptionFault" namespace="" />
        </wsdl:fault>
    </wsdl:operation>
    <wsdl:operation name="GetClients">
        <soap12:operation soapAction="http://tempuri.org/IPCBackupServerProvider/GetClients"
style="document" />
        <wsdl:input>
            <soap12:body use="literal" />
        </wsdl:input>
        <wsdl:output>
            <soap12:body use="literal" />
        </wsdl:output>
        <wsdl:fault name="PCBackupServerFaultFault">
            <soap12:fault use="literal" name="PCBackupServerFaultFault" namespace="" />
        </wsdl:fault>
        <wsdl:fault name="SecurityAccessDeniedExceptionFault">
            <soap12:fault use="literal" name="SecurityAccessDeniedExceptionFault" namespace="" />
        </wsdl:fault>
    </wsdl:operation>
    <wsdl:operation name="GetClient">
        <soap12:operation soapAction="http://tempuri.org/IPCBackupServerProvider/GetClient"
style="document" />
        <wsdl:input>
            <soap12:body use="literal" />
        </wsdl:input>
        <wsdl:output>
            <soap12:body use="literal" />
        </wsdl:output>
        <wsdl:fault name="PCBackupServerFaultFault">
            <soap12:fault use="literal" name="PCBackupServerFaultFault" namespace="" />
        </wsdl:fault>
        <wsdl:fault name="SecurityAccessDeniedExceptionFault">
            <soap12:fault use="literal" name="SecurityAccessDeniedExceptionFault" namespace="" />
        </wsdl:fault>
    </wsdl:operation>
    <wsdl:operation name="OnBattery">
        <soap12:operation soapAction="http://tempuri.org/IPCBackupServerProvider/OnBattery"
style="document" />
        <wsdl:input>
            <soap12:body use="literal" />
        </wsdl:input>
        <wsdl:output>
            <soap12:body use="literal" />
        </wsdl:output>
        <wsdl:fault name="PCBackupServerFaultFault">
            <soap12:fault use="literal" name="PCBackupServerFaultFault" namespace="" />
        </wsdl:fault>
        <wsdl:fault name="SecurityAccessDeniedExceptionFault">
            <soap12:fault use="literal" name="SecurityAccessDeniedExceptionFault" namespace="" />
        </wsdl:fault>
    </wsdl:operation>
    <wsdl:operation name="GetClientJobs">
        <soap12:operation soapAction="http://tempuri.org/IPCBackupServerProvider/GetClientJobs"
style="document" />
        <wsdl:input>
            <soap12:body use="literal" />
        </wsdl:input>
        <wsdl:output>
            <soap12:body use="literal" />
        </wsdl:output>
        <wsdl:fault name="PCBackupServerFaultFault">
            <soap12:fault use="literal" name="PCBackupServerFaultFault" namespace="" />
        </wsdl:fault>
        <wsdl:fault name="SecurityAccessDeniedExceptionFault">
            <soap12:fault use="literal" name="SecurityAccessDeniedExceptionFault" namespace="" />
        </wsdl:fault>
    </wsdl:operation>

```

```

<wsdl:operation name="GetVolumeJobs">
    <soap12:operation soapAction="http://tempuri.org/IPCBackupServerProvider/GetVolumeJobs"
style="document" />
    <wsdl:input>
        <soap12:body use="literal" />
    </wsdl:input>
    <wsdl:output>
        <soap12:body use="literal" />
    </wsdl:output>
    <wsdl:fault name="PCBackupServerFaultFault">
        <soap12:fault use="literal" name="PCBackupServerFaultFault" namespace="" />
    </wsdl:fault>
    <wsdl:fault name="SecurityAccessDeniedExceptionFault">
        <soap12:fault use="literal" name="SecurityAccessDeniedExceptionFault" namespace="" />
    </wsdl:fault>
</wsdl:operation>
<wsdl:operation name="GetClientVolumes">
    <soap12:operation
soapAction="http://tempuri.org/IPCBackupServerProvider/GetClientVolumes" style="document" />
    <wsdl:input>
        <soap12:body use="literal" />
    </wsdl:input>
    <wsdl:output>
        <soap12:body use="literal" />
    </wsdl:output>
    <wsdl:fault name="PCBackupServerFaultFault">
        <soap12:fault use="literal" name="PCBackupServerFaultFault" namespace="" />
    </wsdl:fault>
    <wsdl:fault name="SecurityAccessDeniedExceptionFault">
        <soap12:fault use="literal" name="SecurityAccessDeniedExceptionFault" namespace="" />
    </wsdl:fault>
</wsdl:operation>
<wsdl:operation name="SetClientJobDescription">
    <soap12:operation
soapAction="http://tempuri.org/IPCBackupServerProvider/SetClientJobDescription"
style="document" />
    <wsdl:input>
        <soap12:body use="literal" />
    </wsdl:input>
    <wsdl:output>
        <soap12:body use="literal" />
    </wsdl:output>
    <wsdl:fault name="PCBackupServerFaultFault">
        <soap12:fault use="literal" name="PCBackupServerFaultFault" namespace="" />
    </wsdl:fault>
    <wsdl:fault name="SecurityAccessDeniedExceptionFault">
        <soap12:fault use="literal" name="SecurityAccessDeniedExceptionFault" namespace="" />
    </wsdl:fault>
</wsdl:operation>
<wsdl:operation name="SetClientJobRetentionState">
    <soap12:operation
soapAction="http://tempuri.org/IPCBackupServerProvider/SetClientJobRetentionState"
style="document" />
    <wsdl:input>
        <soap12:body use="literal" />
    </wsdl:input>
    <wsdl:output>
        <soap12:body use="literal" />
    </wsdl:output>
    <wsdl:fault name="PCBackupServerFaultFault">
        <soap12:fault use="literal" name="PCBackupServerFaultFault" namespace="" />
    </wsdl:fault>
    <wsdl:fault name="SecurityAccessDeniedExceptionFault">
        <soap12:fault use="literal" name="SecurityAccessDeniedExceptionFault" namespace="" />
    </wsdl:fault>
</wsdl:operation>
<wsdl:operation name="SetClientVolumeStatus">

```

```

<soap12:operation
soapAction="http://tempuri.org/IPCBackupServerProvider/SetClientVolumeStatus"
style="document" />
<wsdl:input>
    <soap12:body use="literal" />
</wsdl:input>
<wsdl:output>
    <soap12:body use="literal" />
</wsdl:output>
<wsdl:fault name="PCBackupServerFaultFault">
    <soap12:fault use="literal" name="PCBackupServerFaultFault" namespace="" />
</wsdl:fault>
<wsdl:fault name="SecurityAccessDeniedExceptionFault">
    <soap12:fault use="literal" name="SecurityAccessDeniedExceptionFault" namespace="" />
</wsdl:fault>
</wsdl:operation>
<wsdl:operation name="SetExcludedFolders">
    <soap12:operation
soapAction="http://tempuri.org/IPCBackupServerProvider/SetExcludedFolders" style="document"
/>
    <wsdl:input>
        <soap12:body use="literal" />
    </wsdl:input>
    <wsdl:output>
        <soap12:body use="literal" />
    </wsdl:output>
    <wsdl:fault name="SecurityAccessDeniedExceptionFault">
        <soap12:fault use="literal" name="SecurityAccessDeniedExceptionFault" namespace="" />
    </wsdl:fault>
    <wsdl:fault name="PCBackupServerFaultFault">
        <soap12:fault use="literal" name="PCBackupServerFaultFault" namespace="" />
    </wsdl:fault>
    </wsdl:operation>
    <wsdl:operation name="EnableBackups">
        <soap12:operation soapAction="http://tempuri.org/IPCBackupServerProvider/EnableBackups"
style="document" />
        <wsdl:input>
            <soap12:body use="literal" />
        </wsdl:input>
        <wsdl:output>
            <soap12:body use="literal" />
        </wsdl:output>
        <wsdl:fault name="PCBackupServerFaultFault">
            <soap12:fault use="literal" name="PCBackupServerFaultFault" namespace="" />
        </wsdl:fault>
        <wsdl:fault name="SecurityAccessDeniedExceptionFault">
            <soap12:fault use="literal" name="SecurityAccessDeniedExceptionFault" namespace="" />
        </wsdl:fault>
        </wsdl:operation>
        <wsdl:operation name="DisableBackups">
            <soap12:operation
soapAction="http://tempuri.org/IPCBackupServerProvider/DisableBackups" style="document" />
            <wsdl:input>
                <soap12:body use="literal" />
            </wsdl:input>
            <wsdl:output>
                <soap12:body use="literal" />
            </wsdl:output>
            <wsdl:fault name="PCBackupServerFaultFault">
                <soap12:fault use="literal" name="PCBackupServerFaultFault" namespace="" />
            </wsdl:fault>
            <wsdl:fault name="SecurityAccessDeniedExceptionFault">
                <soap12:fault use="literal" name="SecurityAccessDeniedExceptionFault" namespace="" />
            </wsdl:fault>
            </wsdl:operation>
            <wsdl:operation name="GetBackupConfiguration">
                <soap12:operation
soapAction="http://tempuri.org/IPCBackupServerProvider/GetBackupConfiguration"
style="document" />

```

```

<wsdl:input>
    <soap12:body use="literal" />
</wsdl:input>
<wsdl:output>
    <soap12:body use="literal" />
</wsdl:output>
<wsdl:fault name="PCBackupServerFaultFault">
    <soap12:fault use="literal" name="PCBackupServerFaultFault" namespace="" />
</wsdl:fault>
<wsdl:fault name="SecurityAccessDeniedExceptionFault">
    <soap12:fault use="literal" name="SecurityAccessDeniedExceptionFault" namespace="" />
</wsdl:fault>
</wsdl:operation>
<wsdl:operation name="GetDefaultBackupConfiguration">
    <soap12:operation
        soapAction="http://tempuri.org/IPCBackupServerProvider/GetDefaultBackupConfiguration"
        style="document" />
        <wsdl:input>
            <soap12:body use="literal" />
        </wsdl:input>
        <wsdl:output>
            <soap12:body use="literal" />
        </wsdl:output>
        <wsdl:fault name="PCBackupServerFaultFault">
            <soap12:fault use="literal" name="PCBackupServerFaultFault" namespace="" />
        </wsdl:fault>
        <wsdl:fault name="SecurityAccessDeniedExceptionFault">
            <soap12:fault use="literal" name="SecurityAccessDeniedExceptionFault" namespace="" />
        </wsdl:fault>
    </wsdl:operation>
    <wsdl:operation name="GetBackupOperationStatus">
        <soap12:operation
            soapAction="http://tempuri.org/IPCBackupServerProvider/GetBackupOperationStatus"
            style="document" />
            <wsdl:input>
                <soap12:body use="literal" />
            </wsdl:input>
            <wsdl:output>
                <soap12:body use="literal" />
            </wsdl:output>
            <wsdl:fault name="PCBackupServerFaultFault">
                <soap12:fault use="literal" name="PCBackupServerFaultFault" namespace="" />
            </wsdl:fault>
            <wsdl:fault name="SecurityAccessDeniedExceptionFault">
                <soap12:fault use="literal" name="SecurityAccessDeniedExceptionFault" namespace="" />
            </wsdl:fault>
        </wsdl:operation>
        <wsdl:operation name="GetServiceStatus">
            <soap12:operation
                soapAction="http://tempuri.org/IPCBackupServerProvider/GetServiceStatus" style="document" />
                <wsdl:input>
                    <soap12:body use="literal" />
                </wsdl:input>
                <wsdl:output>
                    <soap12:body use="literal" />
                </wsdl:output>
                <wsdl:fault name="PCBackupServerFaultFault">
                    <soap12:fault use="literal" name="PCBackupServerFaultFault" namespace="" />
                </wsdl:fault>
                <wsdl:fault name="SecurityAccessDeniedExceptionFault">
                    <soap12:fault use="literal" name="SecurityAccessDeniedExceptionFault" namespace="" />
                </wsdl:fault>
            </wsdl:operation>
            <wsdl:operation name="GetWaitingOperations">
                <soap12:operation
                    soapAction="http://tempuri.org/IPCBackupServerProvider/GetWaitingOperations" style="document" />
                    <wsdl:input>
                        <soap12:body use="literal" />

```

```

    </wsdl:input>
    <wsdl:output>
        <soap12:body use="literal" />
    </wsdl:output>
    <wsdl:fault name="PCBackupServerFaultFault">
        <soap12:fault use="literal" name="PCBackupServerFaultFault" namespace="" />
    </wsdl:fault>
    <wsdl:fault name="SecurityAccessDeniedExceptionFault">
        <soap12:fault use="literal" name="SecurityAccessDeniedExceptionFault" namespace="" />
    </wsdl:fault>
</wsdl:operation>
<wsdl:operation name="SetBackupConfiguration">
    <soap12:operation
soapAction="http://tempuri.org/IPCBackupServerProvider/SetBackupConfiguration"
style="document" />
    <wsdl:input>
        <soap12:body use="literal" />
    </wsdl:input>
    <wsdl:output>
        <soap12:body use="literal" />
    </wsdl:output>
    <wsdl:fault name="PCBackupServerFaultFault">
        <soap12:fault use="literal" name="PCBackupServerFaultFault" namespace="" />
    </wsdl:fault>
    <wsdl:fault name="SecurityAccessDeniedExceptionFault">
        <soap12:fault use="literal" name="SecurityAccessDeniedExceptionFault" namespace="" />
    </wsdl:fault>
</wsdl:operation>
<wsdl:operation name="GetUsedBytes">
    <soap12:operation soapAction="http://tempuri.org/IPCBackupServerProvider/GetUsedBytes"
style="document" />
    <wsdl:input>
        <soap12:body use="literal" />
    </wsdl:input>
    <wsdl:output>
        <soap12:body use="literal" />
    </wsdl:output>
    <wsdl:fault name="PCBackupServerFaultFault">
        <soap12:fault use="literal" name="PCBackupServerFaultFault" namespace="" />
    </wsdl:fault>
    <wsdl:fault name="SecurityAccessDeniedExceptionFault">
        <soap12:fault use="literal" name="SecurityAccessDeniedExceptionFault" namespace="" />
    </wsdl:fault>
</wsdl:operation>
<wsdl:operation name="StartCleanup">
    <soap12:operation soapAction="http://tempuri.org/IPCBackupServerProvider/StartCleanup"
style="document" />
    <wsdl:input>
        <soap12:body use="literal" />
    </wsdl:input>
    <wsdl:output>
        <soap12:body use="literal" />
    </wsdl:output>
    <wsdl:fault name="PCBackupServerFaultFault">
        <soap12:fault use="literal" name="PCBackupServerFaultFault" namespace="" />
    </wsdl:fault>
    <wsdl:fault name="SecurityAccessDeniedExceptionFault">
        <soap12:fault use="literal" name="SecurityAccessDeniedExceptionFault" namespace="" />
    </wsdl:fault>
</wsdl:operation>
<wsdl:operation name="CancelCleanup">
    <soap12:operation soapAction="http://tempuri.org/IPCBackupServerProvider/CancelCleanup"
style="document" />
    <wsdl:input>
        <soap12:body use="literal" />
    </wsdl:input>
    <wsdl:output>
        <soap12:body use="literal" />
    </wsdl:output>

```

```

<wsdl:fault name="PCBackupServerFaultFault">
    <soap12:fault use="literal" name="PCBackupServerFaultFault" namespace="" />
</wsdl:fault>
<wsdl:fault name="SecurityAccessDeniedExceptionFault">
    <soap12:fault use="literal" name="SecurityAccessDeniedExceptionFault" namespace="" />
</wsdl:fault>
</wsdl:operation>
<wsdl:operation name="StartRepair">
    <soap12:operation soapAction="http://tempuri.org/IPCBackupServerProvider/StartRepair"
style="document" />
    <wsdl:input>
        <soap12:body use="literal" />
    </wsdl:input>
    <wsdl:output>
        <soap12:body use="literal" />
    </wsdl:output>
<wsdl:fault name="PCBackupServerFaultFault">
    <soap12:fault use="literal" name="PCBackupServerFaultFault" namespace="" />
</wsdl:fault>
<wsdl:fault name="SecurityAccessDeniedExceptionFault">
    <soap12:fault use="literal" name="SecurityAccessDeniedExceptionFault" namespace="" />
</wsdl:fault>
</wsdl:operation>
<wsdl:operation name="CancelRepair">
    <soap12:operation soapAction="http://tempuri.org/IPCBackupServerProvider/CancelRepair"
style="document" />
    <wsdl:input>
        <soap12:body use="literal" />
    </wsdl:input>
    <wsdl:output>
        <soap12:body use="literal" />
    </wsdl:output>
<wsdl:fault name="PCBackupServerFaultFault">
    <soap12:fault use="literal" name="PCBackupServerFaultFault" namespace="" />
</wsdl:fault>
<wsdl:fault name="SecurityAccessDeniedExceptionFault">
    <soap12:fault use="literal" name="SecurityAccessDeniedExceptionFault" namespace="" />
</wsdl:fault>
</wsdl:operation>
<wsdl:operation name="GetLastRepairResult">
    <soap12:operation
soapAction="http://tempuri.org/IPCBackupServerProvider/GetLastRepairResult" style="document"
/>
    <wsdl:input>
        <soap12:body use="literal" />
    </wsdl:input>
    <wsdl:output>
        <soap12:body use="literal" />
    </wsdl:output>
<wsdl:fault name="PCBackupServerFaultFault">
    <soap12:fault use="literal" name="PCBackupServerFaultFault" namespace="" />
</wsdl:fault>
<wsdl:fault name="SecurityAccessDeniedExceptionFault">
    <soap12:fault use="literal" name="SecurityAccessDeniedExceptionFault" namespace="" />
</wsdl:fault>
</wsdl:operation>
<wsdl:operation name="StartConsistencyChecker">
    <soap12:operation
soapAction="http://tempuri.org/IPCBackupServerProvider/StartConsistencyChecker"
style="document" />
    <wsdl:input>
        <soap12:body use="literal" />
    </wsdl:input>
    <wsdl:output>
        <soap12:body use="literal" />
    </wsdl:output>
<wsdl:fault name="PCBackupServerFaultFault">
    <soap12:fault use="literal" name="PCBackupServerFaultFault" namespace="" />
</wsdl:fault>

```

```

<wsdl:fault name="SecurityAccessDeniedExceptionFault">
    <soap12:fault use="literal" name="SecurityAccessDeniedExceptionFault" namespace="" />
</wsdl:fault>
</wsdl:operation>
<wsdl:operation name="CancelConsistencyChecker">
    <soap12:operation
soapAction="http://tempuri.org/IPCBackupServerProvider/CancelConsistencyChecker"
style="document" />
    <wsdl:input>
        <soap12:body use="literal" />
    </wsdl:input>
    <wsdl:output>
        <soap12:body use="literal" />
    </wsdl:output>
<wsdl:fault name="PCBackupServerFaultFault">
    <soap12:fault use="literal" name="PCBackupServerFaultFault" namespace="" />
</wsdl:fault>
<wsdl:fault name="SecurityAccessDeniedExceptionFault">
    <soap12:fault use="literal" name="SecurityAccessDeniedExceptionFault" namespace="" />
</wsdl:fault>
</wsdl:operation>
<wsdl:operation name="Remove">
    <soap12:operation soapAction="http://tempuri.org/IPCBackupServerProvider/Remove"
style="document" />
    <wsdl:input>
        <soap12:body use="literal" />
    </wsdl:input>
    <wsdl:output>
        <soap12:body use="literal" />
    </wsdl:output>
<wsdl:fault name="PCBackupServerFaultFault">
    <soap12:fault use="literal" name="PCBackupServerFaultFault" namespace="" />
</wsdl:fault>
<wsdl:fault name="SecurityAccessDeniedExceptionFault">
    <soap12:fault use="literal" name="SecurityAccessDeniedExceptionFault" namespace="" />
</wsdl:fault>
</wsdl:operation>
<wsdl:operation name="CalculateVolumeAsync">
    <soap12:operation
soapAction="http://tempuri.org/IPCBackupServerProvider/CalculateVolumeAsync" style="document"
/>
    <wsdl:input>
        <soap12:body use="literal" />
    </wsdl:input>
    <wsdl:output>
        <soap12:body use="literal" />
    </wsdl:output>
<wsdl:fault name="PCBackupServerFaultFault">
    <soap12:fault use="literal" name="PCBackupServerFaultFault" namespace="" />
</wsdl:fault>
<wsdl:fault name="SecurityAccessDeniedExceptionFault">
    <soap12:fault use="literal" name="SecurityAccessDeniedExceptionFault" namespace="" />
</wsdl:fault>
</wsdl:operation>
<wsdl:operation name="GetFolderChildren">
    <soap12:operation
soapAction="http://tempuri.org/IPCBackupServerProvider/GetFolderChildren" style="document" />
    <wsdl:input>
        <soap12:body use="literal" />
    </wsdl:input>
    <wsdl:output>
        <soap12:body use="literal" />
    </wsdl:output>
<wsdl:fault name="PCBackupServerFaultFault">
    <soap12:fault use="literal" name="PCBackupServerFaultFault" namespace="" />
</wsdl:fault>
<wsdl:fault name="SecurityAccessDeniedExceptionFault">
    <soap12:fault use="literal" name="SecurityAccessDeniedExceptionFault" namespace="" />
</wsdl:fault>
</wsdl:operation>

```

```

        </wsdl:operation>
        <wsdl:operation name="GetConnectedVolumes">
            <soap12:operation
soapAction="http://tempuri.org/IPCBackupServerProvider/GetConnectedVolumes" style="document"
/>
            <wsdl:input>
                <soap12:body use="literal" />
            </wsdl:input>
            <wsdl:output>
                <soap12:body use="literal" />
            </wsdl:output>
            <wsdl:fault name="PCBackupServerFaultFault">
                <soap12:fault use="literal" name="PCBackupServerFaultFault" namespace="" />
            </wsdl:fault>
            <wsdl:fault name="SecurityAccessDeniedExceptionFault">
                <soap12:fault use="literal" name="SecurityAccessDeniedExceptionFault" namespace="" />
            </wsdl:fault>
        </wsdl:operation>
        <wsdl:operation name="CleanFolderSizeCalculation">
            <soap12:operation
soapAction="http://tempuri.org/IPCBackupServerProvider/CleanFolderSizeCalculation" style="document" />
            <wsdl:input>
                <soap12:body use="literal" />
            </wsdl:input>
        </wsdl:operation>
        <wsdl:operation name="StartBackup">
            <soap12:operation soapAction="http://tempuri.org/IPCBackupServerProvider/StartBackup" style="document" />
            <wsdl:input>
                <soap12:body use="literal" />
            </wsdl:input>
            <wsdl:output>
                <soap12:body use="literal" />
            </wsdl:output>
            <wsdl:fault name="PCBackupServerFaultFault">
                <soap12:fault use="literal" name="PCBackupServerFaultFault" namespace="" />
            </wsdl:fault>
            <wsdl:fault name="SecurityAccessDeniedExceptionFault">
                <soap12:fault use="literal" name="SecurityAccessDeniedExceptionFault" namespace="" />
            </wsdl:fault>
        </wsdl:operation>
        <wsdl:operation name="CancelBackup">
            <soap12:operation soapAction="http://tempuri.org/IPCBackupServerProvider/CancelBackup" style="document" />
            <wsdl:input>
                <soap12:body use="literal" />
            </wsdl:input>
            <wsdl:output>
                <soap12:body use="literal" />
            </wsdl:output>
            <wsdl:fault name="PCBackupServerFaultFault">
                <soap12:fault use="literal" name="PCBackupServerFaultFault" namespace="" />
            </wsdl:fault>
            <wsdl:fault name="SecurityAccessDeniedExceptionFault">
                <soap12:fault use="literal" name="SecurityAccessDeniedExceptionFault" namespace="" />
            </wsdl:fault>
        </wsdl:operation>
        <wsdl:operation name="StartBackupService">
            <soap12:operation
soapAction="http://tempuri.org/IPCBackupServerProvider/StartBackupService" style="document" />
            <wsdl:input>
                <soap12:body use="literal" />
            </wsdl:input>
            <wsdl:output>
                <soap12:body use="literal" />
            </wsdl:output>
            <wsdl:fault name="PCBackupServerFaultFault">

```

```

        <soap12:fault use="literal" name="PCBackupServerFaultFault" namespace="" />
    </wsdl:fault>
    <wsdl:fault name="SecurityAccessDeniedExceptionFault">
        <soap12:fault use="literal" name="SecurityAccessDeniedExceptionFault" namespace="" />
    </wsdl:fault>
</wsdl:operation>
<wsdl:operation name="StopBackupService">
    <soap12:operation
        soapAction="http://tempuri.org/IPCBackupServiceProvider/StopBackupService" style="document" />
    <wsdl:input>
        <soap12:body use="literal" />
    </wsdl:input>
    <wsdl:output>
        <soap12:body use="literal" />
    </wsdl:output>
    <wsdl:fault name="PCBackupServerFaultFault">
        <soap12:fault use="literal" name="PCBackupServerFaultFault" namespace="" />
    </wsdl:fault>
    <wsdl:fault name="SecurityAccessDeniedExceptionFault">
        <soap12:fault use="literal" name="SecurityAccessDeniedExceptionFault" namespace="" />
    </wsdl:fault>
</wsdl:operation>
<wsdl:operation name="NotifyBackupOperationStatusChange">
    <soap12:operation
        soapAction="http://tempuri.org/IPCBackupServiceProvider/NotifyBackupOperationStatusChange"
        style="document" />
    <wsdl:output>
        <soap12:body use="literal" />
    </wsdl:output>
</wsdl:operation>
<wsdl:operation name="VolumeCalculatorProgress">
    <soap12:operation
        soapAction="http://tempuri.org/IPCBackupServiceProvider/VolumeCalculatorProgress"
        style="document" />
    <wsdl:output>
        <soap12:body use="literal" />
    </wsdl:output>
</wsdl:operation>
<wsdl:operation name="NotifyServiceStatusChange">
    <soap12:operation
        soapAction="http://tempuri.org/IPCBackupServiceProvider/NotifyServiceStatusChange"
        style="document" />
    <wsdl:output>
        <soap12:body use="literal" />
    </wsdl:output>
</wsdl:operation>
<wsdl:operation name="NotifyBackupClientProviderStatus">
    <soap12:operation
        soapAction="http://tempuri.org/IPCBackupServiceProvider/NotifyBackupClientProviderStatus"
        style="document" />
    <wsdl:output>
        <soap12:body use="literal" />
    </wsdl:output>
</wsdl:operation>
</wsdl:binding>
<wsdl:service name="PCBackupServiceProviderImpl">
    <wsdl:port name="CustomBinding_IPCBackupServiceProvider"
        binding="tns:CustomBinding_IPCBackupServiceProvider">
        <soap12:address
            location="net.tcp://serverName:6602/Microsoft.WindowsServerSolutions.wssg_pc_backup_server/Microsoft.WindowsServerSolutions.DataProtection.PCBackup.BackupUtil.WcfContracts.IPCBackupServerProvider" />
        <wsa10:EndpointReference>
            <wsa10:Address>net.tcp://serverName:6602/Microsoft.WindowsServerSolutions.wssg_pc_backup_server/Microsoft.WindowsServerSolutions.DataProtection.PCBackup.BackupUtil.WcfContracts.IPCBackupServerProvider</wsa10:Address>
            <Identity xmlns="http://schemas.xmlsoap.org/ws/2006/02/addressingidentity">
                <Spn>host/serverName.domain</Spn>

```

```

        </Identity>
    </wsa10:EndpointReference>
</wsdl:port>
</wsdl:service>
</wsdl:definitions>

```

6.2.2.2 http://tempuri.org

```

<?xml version="1.0" encoding="utf-8"?>
<xss:schema xmlns:tns="http://tempuri.org/" elementFormDefault="qualified"
targetNamespace="http://tempuri.org/" xmlns:xs="http://www.w3.org/2001/XMLSchema">
    <xss:import schemaLocation="" namespace="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.DataProtection.PCBackup.BackupUtil.WcfContracts" />
    <xss:import schemaLocation="" namespace="http://schemas.microsoft.com/2003/10/Serialization/" />
    <xss:import schemaLocation="" namespace="http://schemas.microsoft.com/2003/10/Serialization/Arrays" />
    <xss:element name="Register">
        <xss:complexType>
            <xss:sequence />
        </xss:complexType>
    </xss:element>
    <xss:element name="RegisterResponse">
        <xss:complexType>
            <xss:sequence />
        </xss:complexType>
    </xss:element>
    <xss:element name="GetClients">
        <xss:complexType>
            <xss:sequence />
        </xss:complexType>
    </xss:element>
    <xss:element name="GetClientsResponse">
        <xss:complexType>
            <xss:sequence>
                <xss:element
                    xmlns:q1="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.DataProtection.PCBackup.BackupUtil.WcfContracts" minOccurs="0" name="GetClientsResult" nillable="true"
                    type="q1:ArrayOfClientConfigurationInfo" />
            </xss:sequence>
        </xss:complexType>
    </xss:element>
    <xss:element name="GetClient">
        <xss:complexType>
            <xss:sequence>
                <xss:element minOccurs="0" name="clientSid" nillable="true" type="xs:string" />
            </xss:sequence>
        </xss:complexType>
    </xss:element>
    <xss:element name="GetClientResponse">
        <xss:complexType>
            <xss:sequence>
                <xss:element
                    xmlns:q2="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.DataProtection.PCBackup.BackupUtil.WcfContracts" minOccurs="0" name="GetClientResult" nillable="true"
                    type="q2:ClientConfigurationInfo" />
            </xss:sequence>
        </xss:complexType>
    </xss:element>
    <xss:element name="OnBattery">
        <xss:complexType>
            <xss:sequence>
                <xss:element minOccurs="0" name="clientSid" nillable="true" type="xs:string" />
            </xss:sequence>
        </xss:complexType>
    </xss:element>

```

```

<xs:element name="OnBatteryResponse">
  <xs:complexType>
    <xs:sequence>
      <xs:element
        xmlns:q3="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.DataProtection.PCBackup.BackupUtil.WcfContracts" minOccurs="0" name="OnBatteryResult"
        type="q3:GetOnBatteryResult" />
    </xs:sequence>
  </xs:complexType>
</xs:element>
<xs:element name="GetClientJobs">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" name="clientSid" nillable="true" type="xs:string" />
      <xs:element minOccurs="0" name="index" type="xs:int" />
    </xs:sequence>
  </xs:complexType>
</xs:element>
<xs:element name="GetClientJobsResponse">
  <xs:complexType>
    <xs:sequence>
      <xs:element
        xmlns:q4="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.DataProtection.PCBackup.BackupUtil.WcfContracts" minOccurs="0" name="GetClientJobsResult"
        nillable="true" type="q4:ArrayOfClientJobInfo" />
    </xs:sequence>
  </xs:complexType>
</xs:element>
<xs:element name="GetVolumeJobs">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" name="clientSid" nillable="true" type="xs:string" />
      <xs:element minOccurs="0" name="jobIndex" type="xs:int" />
    </xs:sequence>
  </xs:complexType>
</xs:element>
<xs:element name="GetVolumeJobsResponse">
  <xs:complexType>
    <xs:sequence>
      <xs:element
        xmlns:q5="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.DataProtection.PCBackup.BackupUtil.WcfContracts" minOccurs="0" name="GetVolumeJobsResult"
        nillable="true" type="q5:ArrayOfVolumeJobInfo" />
    </xs:sequence>
  </xs:complexType>
</xs:element>
<xs:element name="GetClientVolumes">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" name="clientSid" nillable="true" type="xs:string" />
    </xs:sequence>
  </xs:complexType>
</xs:element>
<xs:element name="GetClientVolumesResponse">
  <xs:complexType>
    <xs:sequence>
      <xs:element
        xmlns:q6="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.DataProtection.PCBackup.BackupUtil.WcfContracts" minOccurs="0" name="GetClientVolumesResult"
        nillable="true" type="q6:ArrayOfClientVolumeInfo" />
    </xs:sequence>
  </xs:complexType>
</xs:element>
<xs:element name="SetClientJobDescription">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" name="clientSid" nillable="true" type="xs:string" />
      <xs:element minOccurs="0" name="clientJobIndex" type="xs:int" />
      <xs:element minOccurs="0" name="Description" nillable="true" type="xs:string" />
    </xs:sequence>
  </xs:complexType>
</xs:element>

```

```

        </xs:sequence>
    </xs:complexType>
</xs:element>
<xs:element name="SetClientJobDescriptionResponse">
    <xs:complexType>
        <xs:sequence />
    </xs:complexType>
</xs:element>
<xs:element name="SetClientJobRetentionState">
    <xs:complexType>
        <xs:sequence>
            <xs:element minOccurs="0" name="clientSid" nillable="true" type="xs:string" />
            <xs:element minOccurs="0" name="clientJobIndex" type="xs:int" />
        </xs:sequence>
    </xs:complexType>
</xs:element>
<xs:element name="SetClientJobRetentionStateResponse">
    <xs:complexType>
        <xs:sequence />
    </xs:complexType>
</xs:element>
<xs:element name="SetClientVolumeStatus">
    <xs:complexType>
        <xs:sequence>
            <xs:element minOccurs="0" name="clientSid" nillable="true" type="xs:string" />
            <xs:element xmlns:q8="http://schemas.microsoft.com/2003/10/Serialization/" minOccurs="0" name="volumeGuid" type="q8:guid" />
        </xs:sequence>
    </xs:complexType>
</xs:element>
<xs:element name="SetClientVolumeStatusResponse">
    <xs:complexType>
        <xs:sequence />
    </xs:complexType>
</xs:element>
<xs:element name="SetExcludedFolders">
    <xs:complexType>
        <xs:sequence>
            <xs:element minOccurs="0" name="clientSid" nillable="true" type="xs:string" />
            <xs:element xmlns:q10="http://schemas.microsoft.com/2003/10/Serialization/" minOccurs="0" name="volumeGuid" type="q10:guid" />
            <xs:element xmlns:q11="http://schemas.microsoft.com/2003/10/Serialization/Arrays" minOccurs="0" name="excludedFolders" nillable="true" type="q11:ArrayOfstring" />
        </xs:sequence>
    </xs:complexType>
</xs:element>
<xs:element name="SetExcludedFoldersResponse">
    <xs:complexType>
        <xs:sequence />
    </xs:complexType>
</xs:element>
<xs:element name="EnableBackups">
    <xs:complexType>
        <xs:sequence>
            <xs:element minOccurs="0" name="clientSid" nillable="true" type="xs:string" />
        </xs:sequence>
    </xs:complexType>
</xs:element>
<xs:element name="EnableBackupsResponse">
    <xs:complexType>
        <xs:sequence />
    </xs:complexType>
</xs:element>

```

```

        </xs:complexType>
    </xs:element>
<xs:element name="DisableBackups">
    <xs:complexType>
        <xs:sequence>
            <xs:element minOccurs="0" name="clientSid" nillable="true" type="xs:string" />
            <xs:element minOccurs="0" name="deleteAllJobs" type="xs:boolean" />
        </xs:sequence>
    </xs:complexType>
</xs:element>
<xs:element name="DisableBackupsResponse">
    <xs:complexType>
        <xs:sequence />
    </xs:complexType>
</xs:element>
<xs:element name="GetBackupConfiguration">
    <xs:complexType>
        <xs:sequence />
    </xs:complexType>
</xs:element>
<xs:element name="GetBackupConfigurationResponse">
    <xs:complexType>
        <xs:sequence>
            <xs:element
                xmlns:q12="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.DataProtection.PCBackup.BackupUtil.WcfContracts" minOccurs="0" name="GetBackupConfigurationResult"
                nillable="true" type="q12:PCBackupConfiguration" />
        </xs:sequence>
    </xs:complexType>
</xs:element>
<xs:element name="GetDefaultBackupConfiguration">
    <xs:complexType>
        <xs:sequence />
    </xs:complexType>
</xs:element>
<xs:element name="GetDefaultBackupConfigurationResponse">
    <xs:complexType>
        <xs:sequence>
            <xs:element
                xmlns:q13="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.DataProtection.PCBackup.BackupUtil.WcfContracts" minOccurs="0"
                name="GetDefaultBackupConfigurationResult" nillable="true" type="q13:PCBackupConfiguration" />
        </xs:sequence>
    </xs:complexType>
</xs:element>
<xs:element name="GetBackupOperationStatus">
    <xs:complexType>
        <xs:sequence />
    </xs:complexType>
</xs:element>
<xs:element name="GetBackupOperationStatusResponse">
    <xs:complexType>
        <xs:sequence>
            <xs:element
                xmlns:q14="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.DataProtection.PCBackup.BackupUtil.WcfContracts" minOccurs="0" name="GetBackupOperationStatusResult"
                nillable="true" type="q14:OperationStatusResponse" />
        </xs:sequence>
    </xs:complexType>
</xs:element>
<xs:element name="GetServiceStatus">
    <xs:complexType>
        <xs:sequence />
    </xs:complexType>
</xs:element>
<xs:element name="GetServiceStatusResponse">
    <xs:complexType>
        <xs:sequence>

```

```

<xs:element
  xmlns:q15="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.DataProtection.PCBackup.BackupUtil.WcfContracts" minOccurs="0" name="GetServiceStatusResult"
  nillable="true" type="q15:ServiceStatusResponse" />
  </xs:sequence>
  </xs:complexType>
</xs:element>
<xs:element name="GetWaitingOperations">
  <xs:complexType>
    <xs:sequence />
  </xs:complexType>
</xs:element>
<xs:element name="GetWaitingOperationsResponse">
  <xs:complexType>
    <xs:sequence>
      <xs:element
        xmlns:q16="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.DataProtection.PCBackup.BackupUtil.WcfContracts" minOccurs="0" name="GetWaitingOperationsResult"
        nillable="true" type="q16:ArrayOfWaitingOperation" />
        </xs:sequence>
      </xs:complexType>
    </xs:element>
<xs:element name="SetBackupConfiguration">
  <xs:complexType>
    <xs:sequence>
      <xs:element
        xmlns:q17="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.DataProtection.PCBackup.BackupUtil.WcfContracts" minOccurs="0" name="backupConfig" nillable="true"
        type="q17:PCBackupConfiguration" />
        </xs:sequence>
      </xs:complexType>
    </xs:element>
<xs:element name="SetBackupConfigurationResponse">
  <xs:complexType>
    <xs:sequence />
  </xs:complexType>
</xs:element>
<xs:element name="GetUsedBytes">
  <xs:complexType>
    <xs:sequence />
  </xs:complexType>
</xs:element>
<xs:element name="GetUsedBytesResponse">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" name="GetUsedBytesResult" type="xs:long" />
    </xs:sequence>
  </xs:complexType>
</xs:element>
<xs:element name="StartCleanup">
  <xs:complexType>
    <xs:sequence />
  </xs:complexType>
</xs:element>
<xs:element name="StartCleanupResponse">
  <xs:complexType>
    <xs:sequence />
  </xs:complexType>
</xs:element>
<xs:element name="CancelCleanup">
  <xs:complexType>
    <xs:sequence />
  </xs:complexType>
</xs:element>
<xs:element name="CancelCleanupResponse">
  <xs:complexType>
    <xs:sequence />
  </xs:complexType>
</xs:element>

```

```

<xs:element name="StartRepair">
  <xs:complexType>
    <xs:sequence />
  </xs:complexType>
</xs:element>
<xs:element name="StartRepairResponse">
  <xs:complexType>
    <xs:sequence />
  </xs:complexType>
</xs:element>
<xs:element name="CancelRepair">
  <xs:complexType>
    <xs:sequence />
  </xs:complexType>
</xs:element>
<xs:element name="CancelRepairResponse">
  <xs:complexType>
    <xs:sequence />
  </xs:complexType>
</xs:element>
<xs:element name="GetLastRepairResult">
  <xs:complexType>
    <xs:sequence />
  </xs:complexType>
</xs:element>
<xs:element name="GetLastRepairResultResponse">
  <xs:complexType>
    <xs:sequence>
      <xs:element
        xmlns:q18="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.DataProtection.PCBackup.BackupUtil.WcfContracts" minOccurs="0" name="GetLastRepairResultResult"
        nillable="true" type="q18:RepairResult" />
    </xs:sequence>
  </xs:complexType>
</xs:element>
<xs:element name="StartConsistencyChecker">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" name="fPreempt" type="xs:boolean" />
    </xs:sequence>
  </xs:complexType>
</xs:element>
<xs:element name="StartConsistencyCheckerResponse">
  <xs:complexType>
    <xs:sequence />
  </xs:complexType>
</xs:element>
<xs:element name="CancelConsistencyChecker">
  <xs:complexType>
    <xs:sequence />
  </xs:complexType>
</xs:element>
<xs:element name="CancelConsistencyCheckerResponse">
  <xs:complexType>
    <xs:sequence />
  </xs:complexType>
</xs:element>
<xs:element name="Remove">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" name="clientSid" nillable="true" type="xs:string" />
    </xs:sequence>
  </xs:complexType>
</xs:element>
<xs:element name="RemoveResponse">
  <xs:complexType>
    <xs:sequence />
  </xs:complexType>
</xs:element>

```

```

<xs:element name="CalculateVolumeAsync">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" name="clientSid" nillable="true" type="xs:string" />
      <xs:element xmlns:q19="http://schemas.microsoft.com/2003/10/Serialization/" minOccurs="0" name="volumeGuid" type="q19:guid" />
      <xs:element xmlns:q20="http://schemas.microsoft.com/2003/10/Serialization/Arrays" minOccurs="0" name="excludedFolders" nillable="true" type="q20:ArrayOfstring" />
    </xs:sequence>
  </xs:complexType>
</xs:element>
<xs:element name="CalculateVolumeAsyncResponse">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" name="CalculateVolumeAsyncResult" type="xs:boolean" />
    </xs:sequence>
  </xs:complexType>
</xs:element>
<xs:element name="GetFolderChildren">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" name="clientSid" nillable="true" type="xs:string" />
      <xs:element
        xmlns:q21="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.DataProtection.PCBackup.BackupUtil.WcfContracts" minOccurs="0" name="folderRequest" nillable="true" type="q21:FolderRequest" />
      <xs:element minOccurs="0" name="index" type="xs:int" />
    </xs:sequence>
  </xs:complexType>
</xs:element>
<xs:element name="GetFolderChildrenResponse">
  <xs:complexType>
    <xs:sequence>
      <xs:element
        xmlns:q22="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.DataProtection.PCBackup.BackupUtil.WcfContracts" minOccurs="0" name="GetFolderChildrenResult" nillable="true" type="q22:FolderInfoGroup" />
    </xs:sequence>
  </xs:complexType>
</xs:element>
<xs:element name="GetConnectedVolumes">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" name="clientSid" nillable="true" type="xs:string" />
    </xs:sequence>
  </xs:complexType>
</xs:element>
<xs:element name="GetConnectedVolumesResponse">
  <xs:complexType>
    <xs:sequence>
      <xs:element
        xmlns:q23="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.DataProtection.PCBackup.BackupUtil.WcfContracts" minOccurs="0" name="GetConnectedVolumesResult" nillable="true" type="q23:ArrayOfClientVolumeInfo" />
    </xs:sequence>
  </xs:complexType>
</xs:element>
<xs:element name="CleanFolderSizeCalculation">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" name="clientSid" nillable="true" type="xs:string" />
    </xs:sequence>
  </xs:complexType>
</xs:element>
<xs:element name="StartBackup">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" name="clientSid" nillable="true" type="xs:string" />
      <xs:element minOccurs="0" name="description" nillable="true" type="xs:string" />
    </xs:sequence>
  </xs:complexType>
</xs:element>

```

```

        </xs:sequence>
    </xs:complexType>
</xs:element>
<xs:element name="StartBackupResponse">
    <xs:complexType>
        <xs:sequence />
    </xs:complexType>
</xs:element>
<xs:element name="CancelBackup">
    <xs:complexType>
        <xs:sequence>
            <xs:element minOccurs="0" name="clientSid" nillable="true" type="xs:string" />
        </xs:sequence>
    </xs:complexType>
</xs:element>
<xs:element name="CancelBackupResponse">
    <xs:complexType>
        <xs:sequence />
    </xs:complexType>
</xs:element>
<xs:element name="StartBackupService">
    <xs:complexType>
        <xs:sequence />
    </xs:complexType>
</xs:element>
<xs:element name="StartBackupServiceResponse">
    <xs:complexType>
        <xs:sequence />
    </xs:complexType>
</xs:element>
<xs:element name="StopBackupService">
    <xs:complexType>
        <xs:sequence>
            <xs:element
                xmlns:q24="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.DataProtection.PCBackup.BackupUtil.WcfContracts" minOccurs="0" name="reason" type="q24:StopReason" />
        </xs:sequence>
    </xs:complexType>
</xs:element>
<xs:element name="StopBackupServiceResponse">
    <xs:complexType>
        <xs:sequence />
    </xs:complexType>
</xs:element>
<xs:element name="NotifyBackupOperationStatusChange">
    <xs:complexType>
        <xs:sequence>
            <xs:element
                xmlns:q25="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.DataProtection.PCBackup.BackupUtil.WcfContracts" minOccurs="0" name="backupOperationStatus"
                nillable="true" type="q25:OperationStatusResponse" />
        </xs:sequence>
    </xs:complexType>
</xs:element>
<xs:element name="VolumeCalculatorProgress">
    <xs:complexType>
        <xs:sequence>
            <xs:element
                xmlns:q26="http://schemas.microsoft.com/2003/10/Serialization/" minOccurs="0" name="guid" type="q26:guid" />
            <xs:element minOccurs="0" name="percentDone" type="xs:int" />
        <xs:element
                xmlns:q27="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.DataProtection.PCBackup.BackupUtil.WcfContracts" minOccurs="0" name="folders" nillable="true"
                type="q27:ArrayOfFolderInfo" />
        </xs:sequence>
    </xs:complexType>
</xs:element>
<xs:element name="NotifyServiceStatusChange">
    <xs:complexType>

```

```

<xs:sequence>
  <xs:element
    xmlns:q28="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.DataProtection.PCBackup.BackupUtil.WcfContracts" minOccurs="0" name="serviceStatus" nillable="true"
    type="q28:ServiceStatusResponse" />
  </xs:sequence>
</xs:complexType>
</xs:element>
<xs:element name="NotifyBackupClientProviderStatus">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" name="clientSid" nillable="true" type="xs:string" />
    </xs:sequence>
  </xs:complexType>
</xs:element>
</xs:schema>

```

6.2.2.3 http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.DataProtection.PCBackup.BackupUtil.WcfContracts

```

<?xml version="1.0" encoding="utf-8"?>
<xs:schema xmlns:ser="http://schemas.microsoft.com/2003/10/Serialization/"
  xmlns:tns="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.DataProtection.PCBackup.BackupUtil.WcfContracts" elementFormDefault="qualified"
  targetNamespace="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.DataProtection.PCBackup.BackupUtil.WcfContracts" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:import schemaLocation="" namespace="http://schemas.microsoft.com/2003/10/Serialization/" />
  <xs:import schemaLocation="" namespace="http://schemas.microsoft.com/2003/10/Serialization/Arrays" />
  <xs:complexType name="ArrayOfClientConfigurationInfo">
    <xs:sequence>
      <xs:element minOccurs="0" maxOccurs="unbounded" name="ClientConfigurationInfo" nillable="true" type="tns:ClientConfigurationInfo" />
    </xs:sequence>
  </xs:complexType>
  <xs:element name="ArrayOfClientConfigurationInfo" nillable="true" type="tns:ArrayOfClientConfigurationInfo" />
  <xs:complexType name="ClientConfigurationInfo">
    <xs:sequence>
      <xs:element minOccurs="0" name="AllVolumesConfigured" type="xs:boolean" />
      <xs:element minOccurs="0" name="AnyVolumesIncluded" type="xs:boolean" />
      <xs:element minOccurs="0" name="IsConfigured" type="xs:boolean" />
      <xs:element minOccurs="0" name="IsOnline" type="xs:boolean" />
      <xs:element minOccurs="0" name="JobsExist" type="xs:boolean" />
      <xs:element minOccurs="0" name="LastBackupEnabledTime" type="xs:dateTime" />
      <xs:element minOccurs="0" name="LastGoodBackupTime" type="xs:dateTime" />
      <xs:element minOccurs="0" name="LastStatus" type="tns:ClientJobStatus" />
      <xs:element minOccurs="0" name="Name" nillable="true" type="xs:string" />
      <xs:element minOccurs="0" name="Sid" nillable="true" type="xs:string" />
    </xs:sequence>
  </xs:complexType>
  <xs:element name="ClientConfigurationInfo" nillable="true" type="tns:ClientConfigurationInfo" />
  <xs:simpleType name="ClientJobStatus">
    <xs:restriction base="xs:string">
      <xs:enumeration value="Complete" />
      <xs:enumeration value="Incomplete" />
      <xs:enumeration value="Failed" />
      <xs:enumeration value="InProgress" />
      <xs:enumeration value="InQueue" />
    </xs:restriction>
  </xs:simpleType>
  <xs:element name="ClientJobStatus" nillable="true" type="tns:ClientJobStatus" />
  <xs:complexType name="PCBackupServerFault">
    <xs:sequence>
      <xs:element minOccurs="0" name="Description" nillable="true" type="xs:string" />
    
```

```

<xs:element minOccurs="0" name="Other" nillable="true" type="xs:string" />
<xs:element minOccurs="0" name="Reason" type="tns:PCBackupServerFaultReason" />
</xs:sequence>
</xs:complexType>
<xs:element name="PCBackupServerFault" nillable="true" type="tns:PCBackupServerFault" />
<xs:simpleType name="PCBackupServerFaultReason">
    <xs:restriction base="xs:string">
        <xs:enumeration value="ClientNotReachable" />
        <xs:enumeration value="ClientNotConfigured" />
        <xs:enumeration value="ServiceBusy" />
        <xs:enumeration value="ServiceNotReachable" />
        <xs:enumeration value="ClientNotFound" />
        <xs:enumeration value="ClientJobNotFound" />
        <xs:enumeration value="ClientVolumeNotFound" />
        <xs:enumeration value="RepairRunning" />
        <xs:enumeration value="DBHasErrors" />
        <xs:enumeration value="DBIsOffline" />
        <xs:enumeration value="ArgumentOutOfRange" />
        <xs:enumeration value="UnexpectedError" />
    </xs:restriction>
</xs:simpleType>
<xs:element name="PCBackupServerFaultReason" nillable="true"
type="tns:PCBackupServerFaultReason" />
<xs:simpleType name="GetOnBatteryResult">
    <xs:restriction base="xs:string">
        <xs:enumeration value="Failed" />
        <xs:enumeration value="OnBattery" />
        <xs:enumeration value="NotOnBattery" />
    </xs:restriction>
</xs:simpleType>
<xs:element name="GetOnBatteryResult" nillable="true" type="tns:GetOnBatteryResult" />
<xs:complexType name="ArrayOfClientJobInfo">
    <xs:sequence>
        <xs:element minOccurs="0" maxOccurs="unbounded" name="ClientJobInfo" nillable="true"
type="tns:ClientJobInfo" />
    </xs:sequence>
</xs:complexType>
<xs:element name="ArrayOfClientJobInfo" nillable="true" type="tns:ArrayOfClientJobInfo" />
<xs:complexType name="ClientJobInfo">
    <xs:sequence>
        <xs:element minOccurs="0" name="BytesUsed" type="xs:long" />
        <xs:element minOccurs="0" name="Description" nillable="true" type="xs:string" />
        <xs:element minOccurs="0" name="Duration" type="ser:duration" />
        <xs:element xmlns:q1="http://schemas.microsoft.com/2003/10/Serialization/Arrays"
minOccurs="0" name="FailureDetails" nillable="true" type="q1:ArrayOfstring" />
        <xs:element minOccurs="0" name="Index" type="xs:int" />
        <xs:element minOccurs="0" name="IsAutomatic" type="xs:boolean" />
        <xs:element minOccurs="0" name="StartTime" type="xs:dateTime" />
        <xs:element minOccurs="0" name="Status" type="tns:ClientJobStatus" />
        <xs:element minOccurs="0" name="failureReason" type="tns:AbortReason" />
        <xs:element minOccurs="0" name="retentionState" type="tns:RetentionState" />
    </xs:sequence>
</xs:complexType>
<xs:element name="ClientJobInfo" nillable="true" type="tns:ClientJobInfo" />
<xs:simpleType name="AbortReason">
    <xs:restriction base="xs:string">
        <xs:enumeration value="None" />
        <xs:enumeration value="Authentication" />
        <xs:enumeration value="VersionMismatch" />
        <xs:enumeration value="Cancel" />
        <xs:enumeration value="ServerUnreachable" />
        <xs:enumeration value="ClientVssProblem" />
        <xs:enumeration value="ClientVssInsufficientSpace" />
        <xs:enumeration value="ClientIoError" />
        <xs:enumeration value="ClientException" />
        <xs:enumeration value="DBErrors" />
        <xs:enumeration value="ConnectionLost" />
        <xs:enumeration value="NotConfigured" />
        <xs:enumeration value="ServerFailure" />
    </xs:restriction>
</xs:simpleType>

```

```

<xs:enumeration value="Unknown" />
<xs:enumeration value="VolumeMissing">
    <xs:annotation>
        <xs:appinfo>
            <EnumerationValue
                xmlns="http://schemas.microsoft.com/2003/10/Serialization/">21</EnumerationValue>
            </xs:appinfo>
        </xs:annotation>
    </xs:enumeration>
<xs:enumeration value="CantOpenVolume">
    <xs:annotation>
        <xs:appinfo>
            <EnumerationValue
                xmlns="http://schemas.microsoft.com/2003/10/Serialization/">22</EnumerationValue>
            </xs:appinfo>
        </xs:annotation>
    </xs:enumeration>
<xs:enumeration value="BadFileSystem">
    <xs:annotation>
        <xs:appinfo>
            <EnumerationValue
                xmlns="http://schemas.microsoft.com/2003/10/Serialization/">23</EnumerationValue>
            </xs:appinfo>
        </xs:annotation>
    </xs:enumeration>
<xs:enumeration value="DBIsOffline">
    <xs:annotation>
        <xs:appinfo>
            <EnumerationValue
                xmlns="http://schemas.microsoft.com/2003/10/Serialization/">24</EnumerationValue>
            </xs:appinfo>
        </xs:annotation>
    </xs:enumeration>
<xs:enumeration value="EspCaptureFailed">
    <xs:annotation>
        <xs:appinfo>
            <EnumerationValue
                xmlns="http://schemas.microsoft.com/2003/10/Serialization/">25</EnumerationValue>
            </xs:appinfo>
        </xs:annotation>
    </xs:enumeration>
</xs:restriction>
</xs:simpleType>
<xs:element name="AbortReason" nillable="true" type="tns:AbortReason" />
<xs:simpleType name="RetentionState">
    <xs:restriction base="xs:string">
        <xs:enumeration value="Delete" />
        <xs:enumeration value="Normal" />
        <xs:enumeration value="Locked" />
    </xs:restriction>
</xs:simpleType>
<xs:element name="RetentionState" nillable="true" type="tns:RetentionState" />
<xs:complexType name="ArrayOfVolumeJobInfo">
    <xs:sequence>
        <xs:element minOccurs="0" maxOccurs="unbounded" name="VolumeJobInfo" nillable="true"
            type="tns:VolumeJobInfo" />
    </xs:sequence>
</xs:complexType>
<xs:element name="ArrayOfVolumeJobInfo" nillable="true" type="tns:ArrayOfVolumeJobInfo" />
<xs:complexType name="VolumeJobInfo">
    <xs:sequence>
        <xs:element minOccurs="0" name="BadFiles" nillable="true" type="tns:ArrayOfBadFileInfo"
            type="tns:VolumeJobInfo" />
        <xs:element minOccurs="0" name="BytesPerCluster" type="xs:int" />
        <xs:element minOccurs="0" name="BytesPerSector" type="xs:int" />
        <xs:element minOccurs="0" name="BytesUsed" type="xs:long" />
        <xs:element minOccurs="0" name="Duration" type="ser:duration" />
        <xs:element minOccurs="0" name="ExcludedFolders" nillable="true"
            type="tns:ArrayOfExcludedFolderInfo" />
    </xs:sequence>
</xs:complexType>

```

```

<xs:element xmlns:q2="http://schemas.microsoft.com/2003/10/Serialization/Arrays"
minOccurs="0" name="FailureDetails" nillable="true" type="q2:ArrayOfstring" />
<xs:element minOccurs="0" name="FileSystem" nillable="true" type="xs:string" />
<xs:element minOccurs="0" name="InitialCapacity" type="xs:long" />
<xs:element minOccurs="0" name="MinimumCapacity" type="xs:long" />
<xs:element minOccurs="0" name="MountPoint" nillable="true" type="xs:string" />
<xs:element minOccurs="0" name="StartTimeUtc" type="xs:dateTime" />
<xs:element minOccurs="0" name="Status" type="tns:VolumeJobStatus" />
<xs:element minOccurs="0" name="VolumeName" nillable="true" type="xs:string" />
<xs:element minOccurs="0" name="autoExclusionSizes" nillable="true"
type="tns:AutoExclusionSizesInfo" />
<xs:element minOccurs="0" name="failureReason" type="tns:AbortReason" />
<xs:element minOccurs="0" name="uniqueIdBytes" nillable="true" type="xs:base64Binary"
/>
</xs:sequence>
</xs:complexType>
<xs:element name="VolumeJobInfo" nillable="true" type="tns:VolumeJobInfo" />
<xs:complexType name="ArrayOfBadFileInfo">
<xs:sequence>
<xs:element minOccurs="0" maxOccurs="unbounded" name="BadFileInfo" nillable="true"
type="tns:BadFileInfo" />
</xs:sequence>
</xs:complexType>
<xs:element name="ArrayOfBadFileInfo" nillable="true" type="tns:ArrayOfBadFileInfo" />
<xs:complexType name="BadFileInfo">
<xs:sequence>
<xs:element minOccurs="0" name="Name" nillable="true" type="xs:string" />
<xs:element minOccurs="0" name="Size" type="xs:long" />
</xs:sequence>
</xs:complexType>
<xs:element name="BadFileInfo" nillable="true" type="tns:BadFileInfo" />
<xs:complexType name="ArrayOfExcludedFolderInfo">
<xs:sequence>
<xs:element minOccurs="0" maxOccurs="unbounded" name="ExcludedFolderInfo"
nillable="true" type="tns:ExcludedFolderInfo" />
</xs:sequence>
</xs:complexType>
<xs:element name="ArrayOfExcludedFolderInfo" nillable="true"
type="tns:ArrayOfExcludedFolderInfo" />
<xs:complexType name="ExcludedFolderInfo">
<xs:sequence>
<xs:element minOccurs="0" name="IsAutomatic" type="xs:boolean" />
<xs:element minOccurs="0" name="Name" nillable="true" type="xs:string" />
<xs:element minOccurs="0" name="Size" type="xs:long" />
</xs:sequence>
</xs:complexType>
<xs:element name="ExcludedFolderInfo" nillable="true" type="tns:ExcludedFolderInfo" />
<xs:simpleType name="VolumeJobStatus">
<xs:restriction base="xs:string">
<xs:enumeration value="Complete" />
<xs:enumeration value="Broken" />
<xs:enumeration value="Failed" />
<xs:enumeration value="Cancelled" />
<xs:enumeration value="Skipped" />
<xs:enumeration value="CheckPoint" />
<xs:enumeration value="NotStarted" />
<xs:enumeration value="InProgress" />
</xs:restriction>
</xs:simpleType>
<xs:element name="VolumeJobStatus" nillable="true" type="tns:VolumeJobStatus" />
<xs:complexType name="AutoExclusionSizesInfo">
<xs:sequence>
<xs:element minOccurs="0" name="ClientSideCache" type="xs:long" />
<xs:element minOccurs="0" name="DigitalVideoRecorder" type="xs:long" />
<xs:element minOccurs="0" name="HibernationFile" type="xs:long" />
<xs:element minOccurs="0" name="MemoryDump" type="xs:long" />
<xs:element minOccurs="0" name="Other" type="xs:long" />

```

```

<xs:element minOccurs="0" name="PageFile" type="xs:long" />
<xs:element minOccurs="0" name="RecycleBin" type="xs:long" />
<xs:element minOccurs="0" name="ShadowVolumes" type="xs:long" />
<xs:element minOccurs="0" name="TemporaryFiles" type="xs:long" />
</xs:sequence>
</xs:complexType>
<xs:element name="AutoExclusionSizesInfo" nillable="true" type="tns:AutoExclusionSizesInfo"
/>
<xs:complexType name="ClientVolumeInfo">
<xs:sequence>
<xs:element minOccurs="0" name="BackupBytes" type="xs:long" />
<xs:element minOccurs="0" name="BytesPerCluster" type="xs:int" />
<xs:element minOccurs="0" name="BytesPerSector" type="xs:int" />
<xs:element minOccurs="0" name="BytesUsed" type="xs:long" />
<xs:element minOccurs="0" name="Capacity" type="xs:long" />
<xs:element xmlns:q3="http://schemas.microsoft.com/2003/10/Serialization/Arrays"
minOccurs="0" name="ExcludedFolders" nillable="true" type="q3:ArrayOfstring" />
<xs:element minOccurs="0" name="FileSystem" nillable="true" type="xs:string" />
<xs:element minOccurs="0" name="IsEligibleForBackup" type="xs:boolean" />
<xs:element minOccurs="0" name="JobsExist" type="xs:boolean" />
<xs:element minOccurs="0" name="Location" type="tns:VolumeLocation" />
<xs:element minOccurs="0" name="MountPoint" nillable="true" type="xs:string" />
<xs:element minOccurs="0" name="Status" type="tns:VolumeStatus" />
<xs:element minOccurs="0" name="VolumeName" nillable="true" type="xs:string" />
<xs:element minOccurs="0" name="guid" type="ser:guid" />
<xs:element xmlns:q4="http://schemas.microsoft.com/2003/10/Serialization/Arrays"
minOccurs="0" name="uniqueIdBytes" nillable="true" type="q4:ArrayOfunsignedByte" />
</xs:sequence>
</xs:complexType>
<xs:element name="ClientVolumeInfo" nillable="true" type="tns:ClientVolumeInfo" />
<xs:simpleType name="VolumeLocation">
<xs:restriction base="xs:string">
<xs:enumeration value="Missing" />
<xs:enumeration value="Internal" />
<xs:enumeration value="External" />
</xs:restriction>
</xs:simpleType>
<xs:element name="VolumeLocation" nillable="true" type="tns:VolumeLocation" />
<xs:simpleType name="VolumeStatus">
<xs:restriction base="xs:string">
<xs:enumeration value="NotConfigured" />
<xs:enumeration value="Exclude" />
<xs:enumeration value="Include" />
</xs:restriction>
</xs:simpleType>
<xs:element name="VolumeStatus" nillable="true" type="tns:VolumeStatus" />
<xs:complexType name="ArrayOfClientVolumeInfo">
<xs:sequence>
<xs:element minOccurs="0" maxOccurs="unbounded" name="ClientVolumeInfo" nillable="true"
type="tns:ClientVolumeInfo" />
</xs:sequence>
</xs:complexType>
<xs:element name="ArrayOfClientVolumeInfo" nillable="true"
type="tns:ArrayOfClientVolumeInfo" />
<xs:complexType name="PCBackupConfiguration">
<xs:sequence>
<xs:element minOccurs="0" name="alertDiskBytes" type="xs:long" />
<xs:element minOccurs="0" name="dailyRetainCount" type="xs:unsignedInt" />
<xs:element minOccurs="0" name="monthlyRetainCount" type="xs:unsignedInt" />
<xs:element minOccurs="0" name="weeklyRetainCount" type="xs:unsignedInt" />
<xs:element minOccurs="0" name="windowEndTime" type="ser:duration" />
<xs:element minOccurs="0" name="windowStartTime" type="ser:duration" />
<xs:element minOccurs="0" name="yearlyRetainCount" type="xs:unsignedInt" />
</xs:sequence>
</xs:complexType>
<xs:element name="PCBackupConfiguration" nillable="true" type="tns:PCBackupConfiguration"
/>
<xs:complexType name="OperationStatusResponse">
<xs:sequence>

```

```

<xs:element minOccurs="0" name="ClientSid" nillable="true" type="xs:string" />
<xs:element minOccurs="0" name="Machine" nillable="true" type="xs:string" />
<xs:element minOccurs="0" name="Operation" type="tns:PCBackupStatusOperation" />
<xs:element minOccurs="0" name="PercentDone" type="xs:int" />
<xs:element minOccurs="0" name="Phase" type="tns:PCBackupVolumePhase" />
<xs:element minOccurs="0" name="RepairState" type="tns:PCBackupRepairState" />
</xs:sequence>
</xs:complexType>
<xs:element name="OperationStatusResponse" nillable="true"
type="tns:OperationStatusResponse" />
<xs:simpleType name="PCBackupStatusOperation">
<xs:restriction base="xs:string">
<xs:enumeration value="None" />
<xs:enumeration value="DeleteBackup" />
<xs:enumeration value="Cleanup" />
<xs:enumeration value="Backup" />
<xs:enumeration value="PrepareRestore" />
<xs:enumeration value="BasicChecker" />
<xs:enumeration value="ComprehensiveChecker" />
<xs:enumeration value="Suspend" />
<xs:enumeration value="Repair">
<xs:annotation>
<xs:appinfo>
<EnumerationValue
xmlns="http://schemas.microsoft.com/2003/10/Serialization/">20</EnumerationValue>
</xs:appinfo>
</xs:annotation>
</xs:enumeration>
<xs:enumeration value="Unknown">
<xs:annotation>
<xs:appinfo>
<EnumerationValue
xmlns="http://schemas.microsoft.com/2003/10/Serialization/">100</EnumerationValue>
</xs:appinfo>
</xs:annotation>
</xs:enumeration>
</xs:restriction>
</xs:simpleType>
<xs:element name="PCBackupStatusOperation" nillable="true"
type="tns:PCBackupStatusOperation" />
<xs:simpleType name="PCBackupVolumePhase">
<xs:restriction base="xs:string">
<xs:enumeration value="Idle" />
<xs:enumeration value="ScanFileRecords" />
<xs:enumeration value="ScanClusters" />
<xs:enumeration value="Reorganize1" />
<xs:enumeration value="SendClusters" />
<xs:enumeration value="Reorganize2" />
<xs:enumeration value="Complete" />
</xs:restriction>
</xs:simpleType>
<xs:element name="PCBackupVolumePhase" nillable="true" type="tns:PCBackupVolumePhase" />
<xs:simpleType name="PCBackupRepairState">
<xs:restriction base="xs:string">
<xs:enumeration value="NotStarted" />
<xs:enumeration value="RepairNoErrors" />
<xs:enumeration value="RepairDBIsNew" />
<xs:enumeration value="RepairDBIsOld" />
<xs:enumeration value="RepairInProgress" />
<xs:enumeration value="RepairSucceeded" />
<xs:enumeration value="RepairFailed" />
<xs:enumeration value="RepairCanceled" />
<xs:enumeration value="Unknown" />
</xs:restriction>
</xs:simpleType>
<xs:element name="PCBackupRepairState" nillable="true" type="tns:PCBackupRepairState" />
<xs:complexType name="ServiceStatusResponse">
<xs:sequence>
<xs:element minOccurs="0" name="Ready" type="xs:boolean" />

```

```

        </xs:sequence>
    </xs:complexType>
    <xs:element name="ServiceStatusResponse" nillable="true" type="tns:ServiceStatusResponse">
    />
    <xs:complexType name="ArrayOfWaitingOperation">
        <xs:sequence>
            <xs:element minOccurs="0" maxOccurs="unbounded" name="WaitingOperation" nillable="true" type="tns:WaitingOperation" />
        </xs:sequence>
    </xs:complexType>
    <xs:element name="ArrayOfWaitingOperation" nillable="true" type="tns:ArrayOfWaitingOperation" />
    <xs:complexType name="WaitingOperation">
        <xs:sequence>
            <xs:element minOccurs="0" name="MachineName" nillable="true" type="xs:string" />
            <xs:element minOccurs="0" name="MachineSID" nillable="true" type="xs:string" />
            <xs:element minOccurs="0" name="Operation" type="tns:PCBackupStatusOperation" />
            <xs:element minOccurs="0" name="PercentComplete" type="xs:int" />
        </xs:sequence>
    </xs:complexType>
    <xs:element name="WaitingOperation" nillable="true" type="tns:WaitingOperation" />
    <xs:complexType name="RepairResult">
        <xs:sequence>
            <xs:element minOccurs="0" name="ClientStatus" nillable="true" type="tns:ArrayOfClientRepairStatus" />
            <xs:element minOccurs="0" name="RepairStartTime" type="xs:dateTime" />
            <xs:element minOccurs="0" name="RepairState" type="tns:PCBackupRepairState" />
        </xs:sequence>
    </xs:complexType>
    <xs:element name="RepairResult" nillable="true" type="tns:RepairResult" />
    <xs:complexType name="ArrayOfClientRepairStatus">
        <xs:sequence>
            <xs:element minOccurs="0" maxOccurs="unbounded" name="ClientRepairStatus" nillable="true" type="tns:ClientRepairStatus" />
        </xs:sequence>
    </xs:complexType>
    <xs:element name="ArrayOfClientRepairStatus" nillable="true" type="tns:ArrayOfClientRepairStatus" />
    <xs:complexType name="ClientRepairStatus">
        <xs:sequence>
            <xs:element minOccurs="0" name="DataStatus" type="tns:PCClientDataStatus" />
            <xs:element minOccurs="0" name="Name" nillable="true" type="xs:string" />
            <xs:element minOccurs="0" name="Sid" nillable="true" type="xs:string" />
        </xs:sequence>
    </xs:complexType>
    <xs:element name="ClientRepairStatus" nillable="true" type="tns:ClientRepairStatus" />
    <xs:simpleType name="PCClientDataStatus">
        <xs:restriction base="xs:string">
            <xs:enumeration value="NoLoss" />
            <xs:enumeration value="PartialLoss" />
            <xs:enumeration value="FullLoss" />
        </xs:restriction>
    </xs:simpleType>
    <xs:element name="PCClientDataStatus" nillable="true" type="tns:PCClientDataStatus" />
    <xs:complexType name="FolderRequest">
        <xs:sequence>
            <xs:element minOccurs="0" name="fileRecordIndex" type="xs:long" />
            <xs:element minOccurs="0" name="volumeGuid" type="ser:guid" />
        </xs:sequence>
    </xs:complexType>
    <xs:element name="FolderRequest" nillable="true" type="tns:FolderRequest" />
    <xs:complexType name="FolderInfoGroup">
        <xs:sequence>
            <xs:element minOccurs="0" name="FolderInfoList" nillable="true" type="tns:ArrayOfFolderInfo" />
            <xs:element minOccurs="0" name="TotalNumChildren" type="xs:int" />
        </xs:sequence>
    </xs:complexType>
    <xs:element name="FolderInfoGroup" nillable="true" type="tns:FolderInfoGroup" />

```

```

<xs:complexType name="ArrayOfFolderInfo">
  <xs:sequence>
    <xs:element minOccurs="0" maxOccurs="unbounded" name="FolderInfo" nillable="true"
type="tns:FolderInfo" />
  </xs:sequence>
</xs:complexType>
<xs:element name="ArrayOfFolderInfo" nillable="true" type="tns:ArrayOfFolderInfo" />
<xs:complexType name="FolderInfo">
  <xs:sequence>
    <xs:element minOccurs="0" name="ExclusionReason" type="tns:ExclusionReason" />
    <xs:element minOccurs="0" name="FileRecordIndex" type="xs:long" />
    <xs:element minOccurs="0" name="HasChildren" type="xs:boolean" />
    <xs:element minOccurs="0" name="IsFolder" type="xs:boolean" />
    <xs:element minOccurs="0" name="Name" nillable="true" type="xs:string" />
    <xs:element minOccurs="0" name="UsedBytes" type="xs:long" />
  </xs:sequence>
</xs:complexType>
<xs:element name="FolderInfo" nillable="true" type="tns:FolderInfo" />
<xs:simpleType name="ExclusionReason">
  <xs:restriction base="xs:string">
    <xs:enumeration value="NotExcluded" />
    <xs:enumeration value="ClientSideCache" />
    <xs:enumeration value="TemporaryFiles" />
    <xs:enumeration value="DigitalVideoRecorder" />
    <xs:enumeration value="PageFile" />
    <xs:enumeration value="RecycleBin" />
    <xs:enumeration value="HibernationFile" />
    <xs:enumeration value="MemoryDump" />
    <xs:enumeration value="ShadowVolumes" />
    <xs:enumeration value="Other" />
    <xs:enumeration value="Count" />
  </xs:restriction>
</xs:simpleType>
<xs:element name="ExclusionReason" nillable="true" type="tns:ExclusionReason" />
<xs:simpleType name="StopReason">
  <xs:restriction base="xs:string">
    <xs:enumeration value="None" />
    <xs:enumeration value="DatabaseRestore" />
    <xs:enumeration value="DatabaseRepair" />
    <xs:enumeration value="DatabaseLocationChanged" />
  </xs:restriction>
</xs:simpleType>
<xs:element name="StopReason" nillable="true" type="tns:StopReason" />
</xs:schema>

```

6.2.2.4 <http://schemas.microsoft.com/2003/10/Serialization/Arrays>

```

<?xml version="1.0" encoding="utf-8"?>
<xs:schema xmlns:tns="http://schemas.microsoft.com/2003/10/Serialization/Arrays"
elementFormDefault="qualified"
targetNamespace="http://schemas.microsoft.com/2003/10/Serialization/Arrays"
xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexType name="ArrayOfstring">
    <xs:sequence>
      <xs:element minOccurs="0" maxOccurs="unbounded" name="string" nillable="true"
type="xs:string" />
    </xs:sequence>
  </xs:complexType>
  <xs:element name="ArrayOfstring" nillable="true" type="tns:ArrayOfstring" />
  <xs:complexType name="ArrayOfunsignedByte">
    <xs:sequence>
      <xs:element minOccurs="0" maxOccurs="unbounded" name="unsignedByte"
type="xs:unsignedByte" />
    </xs:sequence>
  </xs:complexType>
  <xs:element name="ArrayOfunsignedByte" nillable="true" type="tns:ArrayOfunsignedByte" />

```

```
</xs:schema>
```

6.2.2.5 http://schemas.microsoft.com/2003/10/Serialization

```
<?xml version="1.0" encoding="utf-8"?>
<xs:schema xmlns:tns="http://schemas.microsoft.com/2003/10/Serialization/"
attributeFormDefault="qualified" elementFormDefault="qualified"
targetNamespace="http://schemas.microsoft.com/2003/10/Serialization/"
xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:element name="anyType" nillable="true" type="xs:anyType" />
  <xs:element name="anyURI" nillable="true" type="xs:anyURI" />
  <xs:element name="base64Binary" nillable="true" type="xs:base64Binary" />
  <xs:element name="boolean" nillable="true" type="xs:boolean" />
  <xs:element name="byte" nillable="true" type="xs:byte" />
  <xs:element name="dateTime" nillable="true" type="xs:dateTime" />
  <xs:element name="decimal" nillable="true" type="xs:decimal" />
  <xs:element name="double" nillable="true" type="xs:double" />
  <xs:element name="float" nillable="true" type="xs:float" />
  <xs:element name="int" nillable="true" type="xs:int" />
  <xs:element name="long" nillable="true" type="xs:long" />
  <xs:element name="QName" nillable="true" type="xs:QName" />
  <xs:element name="short" nillable="true" type="xs:short" />
  <xs:element name="string" nillable="true" type="xs:string" />
  <xs:element name="unsignedByte" nillable="true" type="xs:unsignedByte" />
  <xs:element name="unsignedInt" nillable="true" type="xs:unsignedInt" />
  <xs:element name="unsignedLong" nillable="true" type="xs:unsignedLong" />
  <xs:element name="unsignedShort" nillable="true" type="xs:unsignedShort" />
  <xs:element name="char" nillable="true" type="tns:char" />
  <xs:simpleType name="char">
    <xs:restriction base="xs:int" />
  </xs:simpleType>
  <xs:element name="duration" nillable="true" type="tns:duration" />
  <xs:simpleType name="duration">
    <xs:restriction base="xs:duration">
      <xs:pattern value="\-?P(\d*D)?(T(\d*M)?(\d*(\.\.\d*)?S)?)?" />
      <xs:minInclusive value="-P10675199DT2H48M5.4775808S" />
      <xs:maxInclusive value="P10675199DT2H48M5.4775807S" />
    </xs:restriction>
  </xs:simpleType>
  <xs:element name="guid" nillable="true" type="tns:guid" />
  <xs:simpleType name="guid">
    <xs:restriction base="xs:string">
      <xs:pattern value="[\da-fA-F]{8}-[\da-fA-F]{4}-[\da-fA-F]{4}-[\da-fA-F]{4}-[\da-fA-F]{12}" />
    </xs:restriction>
  </xs:simpleType>
  <xs:attribute name="FactoryType" type="xs:QName" />
  <xs:attribute name="Id" type="xs:ID" />
  <xs:attribute name="Ref" type="xs:IDREF" />
</xs:schema>
```

6.2.2.6 http://schemas.datacontract.org/2004/07/System.ServiceModel.Security

```
<?xml version="1.0" encoding="utf-8"?>
<xs:schema xmlns:tns="http://schemas.datacontract.org/2004/07/System.ServiceModel.Security"
elementFormDefault="qualified"
targetNamespace="http://schemas.datacontract.org/2004/07/System.ServiceModel.Security"
xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:import schemaLocation="" namespace="http://schemas.datacontract.org/2004/07/System.ServiceModel" />
  <xs:complexType name="SecurityAccessDeniedException">
    <xs:complexContent mixed="false">
      <xs:extension xmlns:q1="http://schemas.datacontract.org/2004/07/System.ServiceModel"
base="q1:CommunicationException" />
    </xs:complexContent>
  </xs:complexType>
</xs:schema>
```

```

</xs:complexType>
<xs:element name="SecurityAccessDeniedException" nillable="true"
type="tns:SecurityAccessDeniedException" />
</xs:schema>

```

6.2.2.7 http://schemas.datacontract.org/2004/07/System.ServiceModel

```

<?xml version="1.0" encoding="utf-8"?>
<xs:schema xmlns:tns="http://schemas.datacontract.org/2004/07/System.ServiceModel"
elementFormDefault="qualified"
targetNamespace="http://schemas.datacontract.org/2004/07/System.ServiceModel"
xmlns:xs="http://www.w3.org/2001/XMLSchema">
    <xs:import schemaLocation="" namespace="http://schemas.datacontract.org/2004/07/System" />
    <xs:complexType name="CommunicationException">
        <xs:complexContent mixed="false">
            <xs:extension xmlns:q1="http://schemas.datacontract.org/2004/07/System"
base="q1:SystemException" />
        </xs:complexContent>
    </xs:complexType>
    <xs:element name="CommunicationException" nillable="true" type="tns:CommunicationException"
/>
</xs:schema>

```

6.2.2.8 http://schemas.datacontract.org/2004/07/System

```

<?xml version="1.0" encoding="utf-8"?>
<xs:schema xmlns:ser="http://schemas.microsoft.com/2003/10/Serialization/"
xmlns:tns="http://schemas.datacontract.org/2004/07/System" elementFormDefault="qualified"
targetNamespace="http://schemas.datacontract.org/2004/07/System"
xmlns:xs="http://www.w3.org/2001/XMLSchema">
    <xs:import schemaLocation=""
namespace="http://schemas.microsoft.com/2003/10/Serialization/" />
    <xs:complexType name="SystemException">
        <xs:complexContent mixed="false">
            <xs:extension base="tns:Exception" />
        </xs:complexContent>
    </xs:complexType>
    <xs:element name="SystemException" nillable="true" type="tns:SystemException" />
    <xs:complexType name="Exception">
        <xs:sequence>
            <xs:any minOccurs="0" maxOccurs="unbounded" namespace="##local" processContents="skip"
/>
        </xs:sequence>
        <xs:attribute ref="ser:FactoryType" />
    </xs:complexType>
    <xs:element name="Exception" nillable="true" type="tns:Exception" />
</xs:schema>

```

6.3 Health Provider Service WSDL

6.3.1 wsdl

```

<?xml version="1.0" encoding="utf-8"?>
<wsdl:definitions xmlns:wsap="http://schemas.xmlsoap.org/ws/2004/08/addressing/policy"
xmlns:wsa10="http://www.w3.org/2005/08/addressing" xmlns:tns="http://tempuri.org/"
xmlns:msc="http://schemas.microsoft.com/ws/2005/12/wsdl/contract"
xmlns:soapenc="http://schemas.xmlsoap.org/soap/encoding/"
xmlns:soap="http://schemas.xmlsoap.org/wsdl/soap/"
xmlns: wsp="http://schemas.xmlsoap.org/ws/2004/09/policy"
xmlns: wsam="http://www.w3.org/2007/05/addressing/metadata"
xmlns: wsa="http://schemas.xmlsoap.org/ws/2004/08/addressing"
xmlns: wsaw="http://www.w3.org/2006/05/addressing/wsdl"

```

```

xmlns:soap12="http://schemas.xmlsoap.org/wsdl/soap12/" xmlns:wsu="http://docs.oasis-
open.org/wss/2004/01/oasis-200401-wss-wssecurity-utility-1.0.xsd"
xmlns:xsd="http://www.w3.org/2001/XMLSchema" name="AlertMgmtandSynchProviderService"
targetNamespace="http://tempuri.org/" xmlns:wsdl="http://schemas.xmlsoap.org/wsdl/">
<wsp:Policy wsu:Id="CustomBinding_IAlertManagementProviderService_policy">
    <wsp:ExactlyOne>
        <wsp:All>
            <msb:BinaryEncoding
                xmlns:msb="http://schemas.microsoft.com/ws/2004/06/mspolicy/netbinary1" />
                <sp:TransportBinding xmlns:sp="http://schemas.xmlsoap.org/ws/2005/07/securitypolicy">
                    <wsp:Policy>
                        <sp:TransportToken>
                            <wsp:Policy>
                                <msf:WindowsTransportSecurity
                                    xmlns:msf="http://schemas.microsoft.com/ws/2006/05/framing/policy">
                                        <msf:ProtectionLevel>EncryptAndSign</msf:ProtectionLevel>
                                    </msf:WindowsTransportSecurity>
                                </wsp:Policy>
                            </sp:TransportToken>
                            <sp:AlgorithmSuite>
                                <wsp:Policy>
                                    <sp:Basic256 />
                                </wsp:Policy>
                            </sp:AlgorithmSuite>
                            <sp:Layout>
                                <wsp:Policy>
                                    <sp:Strict />
                                </wsp:Policy>
                            </sp:Layout>
                            </wsp:Policy>
                        </sp:TransportBinding>
                        <wsaw:UsingAddressing />
                    </wsp:All>
                </wsp:ExactlyOne>
            <wsp:Policy wsu:Id="CustomBinding_IAlertSynchProviderService_policy">
                <wsp:ExactlyOne>
                    <wsp:All>
                        <msb:BinaryEncoding
                            xmlns:msb="http://schemas.microsoft.com/ws/2004/06/mspolicy/netbinary1" />
                            <sp:TransportBinding xmlns:sp="http://schemas.xmlsoap.org/ws/2005/07/securitypolicy">
                                <wsp:Policy>
                                    <sp:TransportToken>
                                        <wsp:Policy>
                                            <msf:SslTransportSecurity
                                                xmlns:msf="http://schemas.microsoft.com/ws/2006/05/framing/policy">
                                                    <msf:RequireClientCertificate />
                                                </msf:SslTransportSecurity>
                                            </wsp:Policy>
                                        </sp:TransportToken>
                                        <sp:AlgorithmSuite>
                                            <wsp:Policy>
                                                <sp:Basic256 />
                                            </wsp:Policy>
                                        </sp:AlgorithmSuite>
                                        <sp:Layout>
                                            <wsp:Policy>
                                                <sp:Strict />
                                            </wsp:Policy>
                                        </sp:Layout>
                                        </wsp:Policy>
                                    </sp:TransportBinding>
                                    <wsaw:UsingAddressing />
                                </wsp:All>
                            </wsp:ExactlyOne>
                        </wsp:Policy>
                    </wsp:All>
                </wsp:ExactlyOne>
            </wsdl:types>
            <xsd:schema targetNamespace="http://tempuri.org/Imports">
                <xsd:import schemaLocation="" namespace="http://tempuri.org/" />

```

```

<xsd:import schemaLocation="" namespace="http://schemas.datacontract.org/2004/07/System.ServiceModel.Security" />
<xsd:import schemaLocation="" namespace="http://schemas.microsoft.com/2003/10/Serialization/" />
<xsd:import schemaLocation="" namespace="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.NetworkHealth.AlertFramework.Service" />
<xsd:import schemaLocation="" namespace="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.NetworkHealth.AlertFramework" />
<xsd:import schemaLocation="" namespace="http://schemas.microsoft.com/2003/10/Serialization/Arrays" />
<xsd:import schemaLocation="" namespace="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.NetworkHealth.Engine" />
<xsd:import schemaLocation="" namespace="http://schemas.datacontract.org/2004/07/System.ServiceModel" />
<xsd:import schemaLocation="" namespace="http://schemas.datacontract.org/2004/07/System" />
<xsd:import schemaLocation="" namespace="http://schemas.microsoft.com/Message" />
<xsd:import schemaLocation="" namespace="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.NetworkHealth.AlertFramework.Commands" />
</xsd:schema>
</wsdl:types>
<wsdl:message name="IAlertManagementProviderService_GetAllNetworkAlerts_InputMessage">
<wsdl:part name="parameters" element="tns:GetAllNetworkAlerts" />
</wsdl:message>
<wsdl:message name="IAlertManagementProviderService_GetAllNetworkAlerts_OutputMessage">
<wsdl:part name="parameters" element="tns:GetAllNetworkAlertsResponse" />
</wsdl:message>
<wsdl:message name="IAlertManagementProviderService_GetAllNetworkAlerts_SecurityAccessDeniedExceptionFault_FaultMessage">
<wsdl:part xmlns:q1="http://schemas.datacontract.org/2004/07/System.ServiceModel.Security" name="detail" element="q1:SecurityAccessDeniedException" />
</wsdl:message>
<wsdl:message name="IAlertManagementProviderService_GetAllNetworkAlerts_StringFault_FaultMessage">
<wsdl:part xmlns:q2="http://schemas.microsoft.com/2003/10/Serialization/" name="detail" element="q2:string" />
</wsdl:message>
<wsdl:message name="IAlertManagementProviderService_ClearAlertOneWay_InputMessage">
<wsdl:part name="parameters" element="tns:ClearAlertOneWay" />
</wsdl:message>
<wsdl:message name="IAlertManagementProviderService_ClearAlert_InputMessage">
<wsdl:part name="parameters" element="tns:ClearAlert" />
</wsdl:message>
<wsdl:message name="IAlertManagementProviderService_ClearAlert_OutputMessage">
<wsdl:part name="parameters" element="tns:ClearAlertResponse" />
</wsdl:message>
<wsdl:message name="IAlertManagementProviderService_ClearAlert_SecurityAccessDeniedExceptionFault_FaultMessage">
<wsdl:part xmlns:q3="http://schemas.datacontract.org/2004/07/System.ServiceModel.Security" name="detail" element="q3:SecurityAccessDeniedException" />
</wsdl:message>
<wsdl:message name="IAlertManagementProviderService_ClearAlert_StringFault_FaultMessage">
<wsdl:part xmlns:q4="http://schemas.microsoft.com/2003/10/Serialization/" name="detail" element="q4:string" />
</wsdl:message>
<wsdl:message name="IAlertManagementProviderService_SuppressAlertOneWay_InputMessage">
<wsdl:part name="parameters" element="tns:SuppressAlertOneWay" />
</wsdl:message>
<wsdl:message name="IAlertManagementProviderService_SuppressAlert_InputMessage">
<wsdl:part name="parameters" element="tns:SuppressAlert" />
</wsdl:message>

```

```

<wsdl:message name="IAlertManagementProviderService_SuppressAlert_OutputMessage">
    <wsdl:part name="parameters" element="tns:SuppressAlertResponse" />
</wsdl:message>
<wsdl:message
name="IAlertManagementProviderService_SuppressAlert_SecurityAccessDeniedExceptionFault_FaultMessage">
    <wsdl:part
xmlns:q5="http://schemas.datacontract.org/2004/07/System.ServiceModel.Security" name="detail"
element="q5:SecurityAccessDeniedException" />
</wsdl:message>
<wsdl:message
name="IAlertManagementProviderService_SuppressAlert_StringFault_FaultMessage">
    <wsdl:part xmlns:q6="http://schemas.microsoft.com/2003/10/Serialization/" name="detail"
elements="q6:string" />
</wsdl:message>
<wsdl:message name="IAlertManagementProviderService_RaiseAlertOneWay_InputMessage">
    <wsdl:part name="parameters" element="tns:RaiseAlertOneWay" />
</wsdl:message>
<wsdl:message name="IAlertManagementProviderService_RaiseAlert_InputMessage">
    <wsdl:part name="parameters" element="tns:RaiseAlert" />
</wsdl:message>
<wsdl:message name="IAlertManagementProviderService_RaiseAlert_OutputMessage">
    <wsdl:part name="parameters" element="tns:RaiseAlertResponse" />
</wsdl:message>
<wsdl:message
name="IAlertManagementProviderService_RaiseAlert_SecurityAccessDeniedExceptionFault_FaultMessage">
    <wsdl:part
xmlns:q7="http://schemas.datacontract.org/2004/07/System.ServiceModel.Security" name="detail"
element="q7:SecurityAccessDeniedException" />
</wsdl:message>
<wsdl:message name="IAlertManagementProviderService_RaiseAlert_StringFault_FaultMessage">
    <wsdl:part xmlns:q8="http://schemas.microsoft.com/2003/10/Serialization/" name="detail"
element="q8:string" />
</wsdl:message>
<wsdl:message name="IAlertManagementProviderService_IsAuthorized_InputMessage">
    <wsdl:part name="parameters" element="tns:IsAuthorized" />
</wsdl:message>
<wsdl:message name="IAlertManagementProviderService_IsAuthorized_OutputMessage">
    <wsdl:part name="parameters" element="tns:IsAuthorizedResponse" />
</wsdl:message>
<wsdl:message
name="IAlertManagementProviderService_RaiseAlertCompleted_OutputCallbackMessage">
    <wsdl:part name="parameters" element="tns:RaiseAlertCompleted" />
</wsdl:message>
<wsdl:message
name="IAlertManagementProviderService_ClearAlertCompleted_OutputCallbackMessage">
    <wsdl:part name="parameters" element="tns:ClearAlertCompleted" />
</wsdl:message>
<wsdl:message
name="IAlertManagementProviderService_SuppressAlertCompleted_OutputCallbackMessage">
    <wsdl:part name="parameters" element="tns:SuppressAlertCompleted" />
</wsdl:message>
<wsdl:message
name="IAlertManagementProviderService_RepairAlertCompleted_OutputCallbackMessage">
    <wsdl:part name="parameters" element="tns:RepairAlertCompleted" />
</wsdl:message>
<wsdl:message
name="IAlertManagementProviderService_EvaluateAlertsCompleted_OutputCallbackMessage">
    <wsdl:part name="parameters" element="tns:EvaluateAlertsCompleted" />
</wsdl:message>
<wsdl:message name="IAlertManagementProviderService_RaisedAlerts_OutputCallbackMessage">
    <wsdl:part name="parameters" element="tns:RaisedAlerts" />
</wsdl:message>
<wsdl:message name="IAlertManagementProviderService_ClearedAlerts_OutputCallbackMessage">
    <wsdl:part name="parameters" element="tns:ClearedAlerts" />
</wsdl:message>
<wsdl:message name="IAlertSyncProviderService_RegisterClientAgent_InputMessage">
    <wsdl:part name="parameters" element="tns:RegisterClientAgent" />

```

```

        </wsdl:message>
        <wsdl:message name="IAlertSynchProviderService_RegisterClientAgent_OutputMessage">
            <wsdl:part name="parameters" element="tns:RegisterClientAgentResponse" />
        </wsdl:message>
        <wsdl:message
name="IAlertSynchProviderService RegisterClientAgent ArgumentNullException FaultMessage"
>
    <wsdl:part xmlns:q9="http://schemas.datacontract.org/2004/07/System" name="detail"
element="q9:ArgumentNullException" />
</wsdl:message>
        <wsdl:message name="IAlertSynchProviderService SynchronizeAlerts InputMessage">
            <wsdl:part name="parameters" element="tns:SynchronizeAlerts" />
        </wsdl:message>
        <wsdl:message name="IAlertSynchProviderService_ClearCallbackCommandQueue_InputMessage">
            <wsdl:part name="parameters" element="tns:ClearCallbackCommandQueue" />
        </wsdl:message>
        <wsdl:message name="IAlertSynchProviderService ClearCallbackCommandQueue OutputMessage">
            <wsdl:part name="parameters" element="tns:ClearCallbackCommandQueueResponse" />
        </wsdl:message>
        <wsdl:message name="IAlertSynchProviderService_GetPlugInInformation_InputMessage">
            <wsdl:part name="parameters" element="tns:GetPlugInInformation" />
        </wsdl:message>
        <wsdl:message name="IAlertSynchProviderService GetPlugInInformation OutputMessage">
            <wsdl:part name="parameters" element="tns:GetPlugInInformationResponse" />
        </wsdl:message>
        <wsdl:message name="IAlertSynchProviderService_DownloadDefinition_InputMessage">
            <wsdl:part name="parameters" element="tns:DownloadDefinition" />
        </wsdl:message>
        <wsdl:message name="IAlertSynchProviderService DownloadDefinition OutputMessage">
            <wsdl:part name="parameters" element="tns:DownloadDefinitionResponse" />
        </wsdl:message>
        <wsdl:message name="IAlertSynchProviderService_DownloadConfiguration_InputMessage">
            <wsdl:part name="parameters" element="tns:DownloadConfiguration" />
        </wsdl:message>
        <wsdl:message name="IAlertSynchProviderService_DownloadConfiguration_OutputMessage">
            <wsdl:part name="parameters" element="tns:DownloadConfigurationResponse" />
        </wsdl:message>
        <wsdl:message name="IAlertSynchProviderService_AlertChanged_OutputCallbackMessage">
            <wsdl:part name="parameters" element="tns:AlertChanged" />
        </wsdl:message>
        <wsdl:portType name="IAlertManagementProviderService">
            <wsdl:operation name="GetAllNetworkAlerts">
                <wsdl:input
wsaw:Action="http://tempuri.org/IAlertManagementProviderService/GetAllNetworkAlerts"
message="tns:IAlertManagementProviderService_GetAllNetworkAlerts_InputMessage" />
                <wsdl:output
wsaw:Action="http://tempuri.org/IAlertManagementProviderService/GetAllNetworkAlertsResponse"
message="tns:IAlertManagementProviderService GetAllNetworkAlerts OutputMessage" />
                <wsdl:fault
wsaw:Action="http://tempuri.org/IAlertManagementProviderService/GetAllNetworkAlertsSecurityAccessDeniedExceptionFault"
name="SecurityAccessDeniedExceptionFault"
message="tns:IAlertManagementProviderService GetAllNetworkAlerts SecurityAccessDeniedExceptionFault"
FaultMessage" />
                <wsdl:fault
wsaw:Action="http://tempuri.org/IAlertManagementProviderService/GetStringFault"
name="StringFault"
message="tns:IAlertManagementProviderService GetAllNetworkAlerts StringFault FaultMessage" />
            </wsdl:operation>
            <wsdl:operation name="ClearAlertOneWay">
                <wsdl:input
wsaw:Action="http://tempuri.org/IAlertManagementProviderService/ClearAlertOneWay"
message="tns:IAlertManagementProviderService_ClearAlertOneWay_InputMessage" />
            </wsdl:operation>
            <wsdl:operation name="ClearAlert">
                <wsdl:input wsaw:Action="http://tempuri.org/IAlertManagementProviderService/ClearAlert"
message="tns:IAlertManagementProviderService_ClearAlert_InputMessage" />
                <wsdl:output
wsaw:Action="http://tempuri.org/IAlertManagementProviderService/ClearAlertResponse"
message="tns:IAlertManagementProviderService_ClearAlert_OutputMessage" />
            </wsdl:operation>
        </wsdl:portType>
    </wsdl:service>

```

```

<wsdl:fault
wsaw:Action="http://tempuri.org/IAlertManagementProviderService/ClearAlertSecurityAccessDenie
dExceptionFault" name="SecurityAccessDeniedExceptionFault"
message="tns:IAlertManagementProviderService_ClearAlert_SecurityAccessDeniedExceptionFault_Fa
ultMessage" />
    <wsdl:fault
wsaw:Action="http://tempuri.org/IAlertManagementProviderService/ClearAlertStringFault"
name="StringFault"
message="tns:IAlertManagementProviderService_ClearAlert_StringFault_FaultMessage" />
    </wsdl:operation>
    <wsdl:operation name="SuppressAlertOneWay">
        <wsdl:input
wsaw:Action="http://tempuri.org/IAlertManagementProviderService/SuppressAlertOneWay"
message="tns:IAlertManagementProviderService_SuppressAlertOneWay_InputMessage" />
    </wsdl:operation>
    <wsdl:operation name="SuppressAlert">
        <wsdl:input
wsaw:Action="http://tempuri.org/IAlertManagementProviderService/SuppressAlert"
message="tns:IAlertManagementProviderService_SuppressAlert_InputMessage" />
        <wsdl:output
wsaw:Action="http://tempuri.org/IAlertManagementProviderService/SuppressAlertResponse"
message="tns:IAlertManagementProviderService_SuppressAlert_OutputMessage" />
        <wsdl:fault
wsaw:Action="http://tempuri.org/IAlertManagementProviderService/SuppressAlertSecurityAccessDe
niedExceptionFault" name="SecurityAccessDeniedExceptionFault"
message="tns:IAlertManagementProviderService_SuppressAlert_SecurityAccessDeniedExceptionFault
_FaultMessage" />
        <wsdl:fault
wsaw:Action="http://tempuri.org/IAlertManagementProviderService/SuppressAlertStringFault"
name="StringFault"
message="tns:IAlertManagementProviderService_SuppressAlert_StringFault_FaultMessage" />
        </wsdl:operation>
        <wsdl:operation name="RaiseAlertOneWay">
            <wsdl:input
wsaw:Action="http://tempuri.org/IAlertManagementProviderService/RaiseAlertOneWay"
message="tns:IAlertManagementProviderService_RaiseAlertOneWay_InputMessage" />
        </wsdl:operation>
        <wsdl:operation name="RaiseAlert">
            <wsdl:input wsaw:Action="http://tempuri.org/IAlertManagementProviderService/RaiseAlert"
message="tns:IAlertManagementProviderService_RaiseAlert_InputMessage" />
            <wsdl:output
wsaw:Action="http://tempuri.org/IAlertManagementProviderService/RaiseAlertResponse"
message="tns:IAlertManagementProviderService_RaiseAlert_OutputMessage" />
            <wsdl:fault
wsaw:Action="http://tempuri.org/IAlertManagementProviderService/RaiseAlertSecurityAccessDenie
dExceptionFault" name="SecurityAccessDeniedExceptionFault"
message="tns:IAlertManagementProviderService_RaiseAlert_SecurityAccessDeniedExceptionFault_Fa
ultMessage" />
            <wsdl:fault
wsaw:Action="http://tempuri.org/IAlertManagementProviderService/RaiseAlertStringFault"
name="StringFault"
message="tns:IAlertManagementProviderService_RaiseAlert_StringFault_FaultMessage" />
            </wsdl:operation>
            <wsdl:operation name="IsAuthorized">
                <wsdl:input
wsaw:Action="http://tempuri.org/IAlertManagementProviderService/IsAuthorized"
message="tns:IAlertManagementProviderService_IsAuthorized_InputMessage" />
                <wsdl:output
wsaw:Action="http://tempuri.org/IAlertManagementProviderService/IsAuthorizedResponse"
message="tns:IAlertManagementProviderService_IsAuthorized_OutputMessage" />
            </wsdl:operation>
            <wsdl:operation name="RaiseAlertCompleted">
                <wsdl:output
wsaw:Action="http://tempuri.org/IAlertManagementProviderService/RaiseAlertCompleted"
message="tns:IAlertManagementProviderService_RaiseAlertCompleted_OutputCallbackMessage" />
            </wsdl:operation>
            <wsdl:operation name="ClearAlertCompleted">

```

```

<wsdl:output
wsaw:Action="http://tempuri.org/IAlertManagementProviderService/ClearAlertCompleted"
message="tns:IAlertManagementProviderService_ClearAlertCompleted_OutputCallbackMessage" />
</wsdl:operation>
<wsdl:operation name="SuppressAlertCompleted">
<wsdl:output
wsaw:Action="http://tempuri.org/IAlertManagementProviderService/SuppressAlertCompleted"
message="tns:IAlertManagementProviderService_SuppressAlertCompleted_OutputCallbackMessage" />
</wsdl:operation>
<wsdl:operation name="RepairAlertCompleted">
<wsdl:output
wsaw:Action="http://tempuri.org/IAlertManagementProviderService/RepairAlertCompleted"
message="tns:IAlertManagementProviderService_RepairAlertCompleted_OutputCallbackMessage" />
</wsdl:operation>
<wsdl:operation name="EvaluateAlertsCompleted">
<wsdl:output
wsaw:Action="http://tempuri.org/IAlertManagementProviderService/EvaluateAlertsCompleted"
message="tns:IAlertManagementProviderService_EvaluateAlertsCompleted_OutputCallbackMessage"
/>
</wsdl:operation>
<wsdl:operation name="RaisedAlerts">
<wsdl:output
wsaw:Action="http://tempuri.org/IAlertManagementProviderService/RaisedAlerts"
message="tns:IAlertManagementProviderService_RaisedAlerts_OutputCallbackMessage" />
</wsdl:operation>
<wsdl:operation name="ClearedAlerts">
<wsdl:output
wsaw:Action="http://tempuri.org/IAlertManagementProviderService/ClearedAlerts"
message="tns:IAlertManagementProviderService_ClearedAlerts_OutputCallbackMessage" />
</wsdl:operation>
</wsdl:portType>
<wsdl:portType name="IAlertSynchProviderService">
<wsdl:operation name="RegisterClientAgent">
<wsdl:input
wsaw:Action="http://tempuri.org/IAlertSynchProviderService/RegisterClientAgent"
message="tns:IAlertSynchProviderService_RegisterClientAgent_InputMessage" />
<wsdl:output
wsaw:Action="http://tempuri.org/IAlertSynchProviderService/RegisterClientAgentResponse"
message="tns:IAlertSynchProviderService_RegisterClientAgent_OutputMessage" />
<wsdl:fault
wsaw:Action="http://tempuri.org/IAlertSynchProviderService/RegisterClientAgentArgumentNullExceptionFault"
name="ArgumentNullExceptionFault"
message="tns:IAlertSynchProviderService_RegisterClientAgent_ArgumentNullExceptionFault_Message" />
</wsdl:operation>
<wsdl:operation name="SynchronizeAlerts">
<wsdl:input
wsaw:Action="http://tempuri.org/IAlertSynchProviderService/SynchronizeAlerts"
message="tns:IAlertSynchProviderService_SynchronizeAlerts_InputMessage" />
</wsdl:operation>
<wsdl:operation name="ClearCallbackCommandQueue">
<wsdl:input
wsaw:Action="http://tempuri.org/IAlertSynchProviderService/ClearCallbackCommandQueue"
message="tns:IAlertSynchProviderService_ClearCallbackCommandQueue_InputMessage" />
<wsdl:output
wsaw:Action="http://tempuri.org/IAlertSynchProviderService/ClearCallbackCommandQueueResponse"
message="tns:IAlertSynchProviderService_ClearCallbackCommandQueue_OutputMessage" />
</wsdl:operation>
<wsdl:operation name="GetPlugInInformation">
<wsdl:input
wsaw:Action="http://tempuri.org/IAlertSynchProviderService/GetPlugInInformation"
message="tns:IAlertSynchProviderService_GetPlugInInformation_InputMessage" />
<wsdl:output
wsaw:Action="http://tempuri.org/IAlertSynchProviderService/GetPlugInInformationResponse"
message="tns:IAlertSynchProviderService_GetPlugInInformation_OutputMessage" />
</wsdl:operation>
<wsdl:operation name="DownloadDefinition">

```

```

<wsdl:input
wsaw:Action="http://tempuri.org/IAlertSynchProviderService/DownloadDefinition"
message="tns:IAlertSynchProviderService_DownloadDefinition_InputMessage" />
    <wsdl:output
wsaw:Action="http://tempuri.org/IAlertSynchProviderService/DownloadDefinitionResponse"
message="tns:IAlertSynchProviderService DownloadDefinition OutputMessage" />
</wsdl:operation>
<wsdl:operation name="DownloadConfiguration">
    <wsdl:input
wsaw:Action="http://tempuri.org/IAlertSynchProviderService/DownloadConfiguration"
message="tns:IAlertSynchProviderService DownloadConfiguration InputMessage" />
    <wsdl:output
wsaw:Action="http://tempuri.org/IAlertSynchProviderService/DownloadConfigurationResponse"
message="tns:IAlertSynchProviderService_DownloadConfiguration_OutputMessage" />
</wsdl:operation>
<wsdl:operation name="AlertChanged">
    <wsdl:output wsaw:Action="http://tempuri.org/IAlertSynchProviderService/AlertChanged"
message="tns:IAlertSynchProviderService_AlertChanged_OutputCallbackMessage" />
</wsdl:operation>
</wsdl:portType>
<wsdl:binding name="CustomBinding_IAlertManagementProviderService"
type="tns:IAlertManagementProviderService">
    <wsp:PolicyReference URI="#CustomBinding_IAlertManagementProviderService policy" />
    <soap12:binding transport="http://schemas.microsoft.com/soap/tcp" />
    <wsdl:operation name="GetAllNetworkAlerts">
        <soap12:operation
soapAction="http://tempuri.org/IAlertManagementProviderService/GetAllNetworkAlerts"
style="document" />
            <wsdl:input>
                <soap12:body use="literal" />
            </wsdl:input>
            <wsdl:output>
                <soap12:body use="literal" />
            </wsdl:output>
            <wsdl:fault name="SecurityAccessDeniedExceptionFault">
                <soap12:fault use="literal" name="SecurityAccessDeniedExceptionFault" namespace="" />
            </wsdl:fault>
            <wsdl:fault name="StringFault">
                <soap12:fault use="literal" name="StringFault" namespace="" />
            </wsdl:fault>
        </wsdl:operation>
        <wsdl:operation name="ClearAlertOneWay">
            <soap12:operation
soapAction="http://tempuri.org/IAlertManagementProviderService/ClearAlertOneWay"
style="document" />
                <wsdl:input>
                    <soap12:body use="literal" />
                </wsdl:input>
                <wsdl:output>
                    <soap12:body use="literal" />
                </wsdl:output>
                <wsdl:fault name="SecurityAccessDeniedExceptionFault">
                    <soap12:fault use="literal" name="SecurityAccessDeniedExceptionFault" namespace="" />
                </wsdl:fault>
                <wsdl:fault name="StringFault">
                    <soap12:fault use="literal" name="StringFault" namespace="" />
                </wsdl:fault>
            </wsdl:operation>
            <wsdl:operation name="SuppressAlertOneWay">

```

```

<soap12:operation
soapAction="http://tempuri.org/IAlertManagementProviderService/SuppressAlertOneWay"
style="document" />
<wsdl:input>
    <soap12:body use="literal" />
</wsdl:input>
</wsdl:operation>
<wsdl:operation name="SuppressAlert">
    <soap12:operation
soapAction="http://tempuri.org/IAlertManagementProviderService/SuppressAlert"
style="document" />
    <wsdl:input>
        <soap12:body use="literal" />
    </wsdl:input>
    <wsdl:output>
        <soap12:body use="literal" />
    </wsdl:output>
<wsdl:fault name="SecurityAccessDeniedExceptionFault">
    <soap12:fault use="literal" name="SecurityAccessDeniedExceptionFault" namespace="" />
</wsdl:fault>
<wsdl:fault name="StringFault">
    <soap12:fault use="literal" name="StringFault" namespace="" />
</wsdl:fault>
</wsdl:operation>
<wsdl:operation name="RaiseAlertOneWay">
    <soap12:operation
soapAction="http://tempuri.org/IAlertManagementProviderService/RaiseAlertOneWay"
style="document" />
    <wsdl:input>
        <soap12:body use="literal" />
    </wsdl:input>
</wsdl:operation>
<wsdl:operation name="RaiseAlert">
    <soap12:operation
soapAction="http://tempuri.org/IAlertManagementProviderService/RaiseAlert" style="document"
/>
    <wsdl:input>
        <soap12:body use="literal" />
    </wsdl:input>
    <wsdl:output>
        <soap12:body use="literal" />
    </wsdl:output>
<wsdl:fault name="SecurityAccessDeniedExceptionFault">
    <soap12:fault use="literal" name="SecurityAccessDeniedExceptionFault" namespace="" />
</wsdl:fault>
<wsdl:fault name="StringFault">
    <soap12:fault use="literal" name="StringFault" namespace="" />
</wsdl:fault>
</wsdl:operation>
<wsdl:operation name="IsAuthorized">
    <soap12:operation
soapAction="http://tempuri.org/IAlertManagementProviderService/IsAuthorized" style="document"
/>
    <wsdl:input>
        <soap12:body use="literal" />
    </wsdl:input>
    <wsdl:output>
        <soap12:body use="literal" />
    </wsdl:output>
</wsdl:operation>
<wsdl:operation name="RaiseAlertCompleted">
    <soap12:operation
soapAction="http://tempuri.org/IAlertManagementProviderService/RaiseAlertCompleted"
style="document" />
    <wsdl:output>
        <soap12:body use="literal" />
    </wsdl:output>
</wsdl:operation>
<wsdl:operation name="ClearAlertCompleted">

```

```

<soap12:operation
soapAction="http://tempuri.org/IAlertManagementProviderService/ClearAlertCompleted"
style="document" />
<wsdl:output>
    <soap12:body use="literal" />
</wsdl:output>
</wsdl:operation>
<wsdl:operation name="SuppressAlertCompleted">
    <soap12:operation
soapAction="http://tempuri.org/IAlertManagementProviderService/SuppressAlertCompleted"
style="document" />
    <wsdl:output>
        <soap12:body use="literal" />
    </wsdl:output>
</wsdl:operation>
<wsdl:operation name="RepairAlertCompleted">
    <soap12:operation
soapAction="http://tempuri.org/IAlertManagementProviderService/RepairAlertCompleted"
style="document" />
    <wsdl:output>
        <soap12:body use="literal" />
    </wsdl:output>
</wsdl:operation>
<wsdl:operation name="EvaluateAlertsCompleted">
    <soap12:operation
soapAction="http://tempuri.org/IAlertManagementProviderService/EvaluateAlertsCompleted"
style="document" />
    <wsdl:output>
        <soap12:body use="literal" />
    </wsdl:output>
</wsdl:operation>
<wsdl:operation name="RaisedAlerts">
    <soap12:operation
soapAction="http://tempuri.org/IAlertManagementProviderService/RaisedAlerts" style="document"
/>
    <wsdl:output>
        <soap12:body use="literal" />
    </wsdl:output>
</wsdl:operation>
<wsdl:operation name="ClearedAlerts">
    <soap12:operation
soapAction="http://tempuri.org/IAlertManagementProviderService/ClearedAlerts"
style="document" />
    <wsdl:output>
        <soap12:body use="literal" />
    </wsdl:output>
</wsdl:operation>
</wsdl:binding>
<wsdl:binding name="CustomBinding_IAlertSynchProviderService"
type="tns:IAlertSynchProviderService">
    <wsp:PolicyReference URI="#CustomBinding_IAlertSynchProviderService_policy" />
    <soap12:binding transport="http://schemas.microsoft.com/soap/tcp" />
    <wsdl:operation name="RegisterClientAgent">
        <soap12:operation
soapAction="http://tempuri.org/IAlertSynchProviderService/RegisterClientAgent"
style="document" />
        <wsdl:input>
            <soap12:body use="literal" />
        </wsdl:input>
        <wsdl:output>
            <soap12:body use="literal" />
        </wsdl:output>
        <wsdl:fault name="ArgumentNullExceptionFault">
            <soap12:fault use="literal" name="ArgumentNullExceptionFault" namespace="" />
        </wsdl:fault>
    </wsdl:operation>
    <wsdl:operation name="SynchronizeAlerts">

```

```

<soap12:operation
soapAction="http://tempuri.org/IAlertSynchProviderService/SynchronizeAlerts" style="document"
/>
<wsdl:input>
    <soap12:body use="literal" />
</wsdl:input>
</wsdl:operation>
<wsdl:operation name="ClearCallbackCommandQueue">
    <soap12:operation
soapAction="http://tempuri.org/IAlertSynchProviderService/ClearCallbackCommandQueue"
style="document" />
    <wsdl:input>
        <soap12:body use="literal" />
    </wsdl:input>
    <wsdl:output>
        <soap12:body use="literal" />
    </wsdl:output>
</wsdl:operation>
<wsdl:operation name="GetPlugInInformation">
    <soap12:operation
soapAction="http://tempuri.org/IAlertSynchProviderService/GetPlugInInformation"
style="document" />
    <wsdl:input>
        <soap12:body use="literal" />
    </wsdl:input>
    <wsdl:output>
        <soap12:body use="literal" />
    </wsdl:output>
</wsdl:operation>
<wsdl:operation name="DownloadDefinition">
    <soap12:operation
soapAction="http://tempuri.org/IAlertSynchProviderService/DownloadDefinition"
style="document" />
    <wsdl:input>
        <soap12:body use="literal" />
    </wsdl:input>
    <wsdl:output>
        <soap12:body use="literal" />
    </wsdl:output>
</wsdl:operation>
<wsdl:operation name="DownloadConfiguration">
    <soap12:operation
soapAction="http://tempuri.org/IAlertSynchProviderService/DownloadConfiguration"
style="document" />
    <wsdl:input>
        <soap12:body use="literal" />
    </wsdl:input>
    <wsdl:output>
        <soap12:body use="literal" />
    </wsdl:output>
</wsdl:operation>
<wsdl:operation name="AlertChanged">
    <soap12:operation
soapAction="http://tempuri.org/IAlertSynchProviderService/AlertChanged" style="document" />
    <wsdl:output>
        <soap12:body use="literal" />
    </wsdl:output>
</wsdl:operation>
</wsdl:binding>
<wsdl:service name="AlertMgmtAndSyncProviderService">
    <wsdl:port name="CustomBinding_IAlertManagementProviderService"
binding="tns:CustomBinding_IAlertManagementProviderService">
        <soap12:address
location="net.tcp://serverName:6602/Microsoft.WindowsServerSolutions.wssg_alert_mgmt_and_sync
/Microsoft.WindowsServerSolutions.NetworkHealth.AlertFramework.Service.IAlertManagementProvid
erService" />
        <wsa10:EndpointReference>
            <wsa10:Address>net.tcp://serverName:6602/Microsoft.WindowsServerSolutions.wssg_alert_mgmt_and

```

```

_sync/Microsoft.WindowsServerSolutions.NetworkHealth.AlertFramework.Service.IAlertManagementProviderService</wsa10:Address>
    <Identity xmlns="http://schemas.xmlsoap.org/ws/2006/02/addressingidentity">
        <Spn>host/serverName.domain</Spn>
    </Identity>
</wsa10:EndpointReference>
</wsdl:port>
<wsdl:port name="CustomBinding_IAlertSyncProviderService"
binding="tns:CustomBinding_IAlertSyncProviderService">
    <soap12:address
location="net.tcp://serverName:6602/Microsoft.WindowsServerSolutions.wssg_alert_mgmt_and_sync
/Microsoft.WindowsServerSolutions.NetworkHealth.AlertFramework.Service.IAlertSyncProviderService" />
    <wsa10:EndpointReference>

<wsa10:Address>net.tcp://serverName:6602/Microsoft.WindowsServerSolutions.wssg alert mgmt and
_sync/Microsoft.WindowsServerSolutions.NetworkHealth.AlertFramework.Service.IAlertSyncProviderService</wsa10:Address>
    <Identity xmlns="http://schemas.xmlsoap.org/ws/2006/02/addressingidentity">
        <Dns>SERVERNAME</Dns>
    </Identity>
</wsa10:EndpointReference>
</wsdl:port>
</wsdl:service>
</wsdl:definitions>

```

6.3.2 http://tempuri.org

```

<?xml version="1.0" encoding="utf-8"?>
<xss:schema xmlns:tns="http://tempuri.org/" elementFormDefault="qualified"
targetNamespace="http://tempuri.org/" xmlns:xs="http://www.w3.org/2001/XMLSchema">
    <xss:import schemaLocation="" namespace="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.NetworkHe
alth.AlertFramework.Service" />
    <xss:import schemaLocation="" namespace="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.NetworkHe
alth.AlertFramework" />
    <xss:import schemaLocation="" namespace="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.NetworkHe
alth.Engine" />
    <xss:import schemaLocation="" namespace="http://schemas.microsoft.com/Message" />
    <xss:import schemaLocation="" namespace="http://schemas.microsoft.com/2003/10/Serialization/Arrays" />
<xss:element name="GetAllNetworkAlerts">
    <xss:complexType>
        <xss:sequence />
    </xss:complexType>
</xss:element>
<xss:element name="GetAllNetworkAlertsResponse">
    <xss:complexType>
        <xss:sequence>
            <xss:element
                xmlns:q1="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.NetworkHe
alth.AlertFramework.Service" minOccurs="0" name="GetAllNetworkAlertsResult" nillable="true"
type="q1:AlertListChunk" />
            </xss:sequence>
        </xss:complexType>
</xss:element>
<xss:element name="ClearAlertOneWay">
    <xss:complexType>
        <xss:sequence>
            <xss:element minOccurs="0" name="alertKey" nillable="true" type="xs:string" />
        </xss:sequence>
    </xss:complexType>
</xss:element>
<xss:element name="ClearAlert">
    <xss:complexType>
        <xss:sequence>

```

```

        <xs:element minOccurs="0" name="alertKey" nillable="true" type="xs:string" />
    </xs:sequence>
</xs:complexType>
</xs:element>
<xs:element name="ClearAlertResponse">
    <xs:complexType>
        <xs:sequence />
    </xs:complexType>
</xs:element>
<xs:element name="SuppressAlertOneWay">
    <xs:complexType>
        <xs:sequence>
            <xs:element minOccurs="0" name="alertKey" nillable="true" type="xs:string" />
            <xs:element minOccurs="0" name="value" type="xs:boolean" />
        </xs:sequence>
    </xs:complexType>
</xs:element>
<xs:element name="SuppressAlert">
    <xs:complexType>
        <xs:sequence>
            <xs:element minOccurs="0" name="alertKey" nillable="true" type="xs:string" />
            <xs:element minOccurs="0" name="value" type="xs:boolean" />
        </xs:sequence>
    </xs:complexType>
</xs:element>
<xs:element name="SuppressAlertResponse">
    <xs:complexType>
        <xs:sequence />
    </xs:complexType>
</xs:element>
<xs:element name="RaiseAlertOneWay">
    <xs:complexType>
        <xs:sequence>
            <xs:element
                xmlns:q2="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.NetworkHea
lth.AlertFramework" minOccurs="0" name="alertInfo" nillable="true" type="q2:AlertInfo" />
        </xs:sequence>
    </xs:complexType>
</xs:element>
<xs:element name="RaiseAlert">
    <xs:complexType>
        <xs:sequence>
            <xs:element
                xmlns:q3="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.NetworkHea
lth.AlertFramework" minOccurs="0" name="alertInfo" nillable="true" type="q3:AlertInfo" />
        </xs:sequence>
    </xs:complexType>
</xs:element>
<xs:element name="RaiseAlertResponse">
    <xs:complexType>
        <xs:sequence>
            <xs:element
                xmlns:q4="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.NetworkHea
lth.AlertFramework" minOccurs="0" name="RaiseAlertResult" nillable="true" type="q4:AlertInfo" />
        </xs:sequence>
    </xs:complexType>
</xs:element>
<xs:element name="IsAuthorized">
    <xs:complexType>
        <xs:sequence />
    </xs:complexType>
</xs:element>
<xs:element name="IsAuthorizedResponse">
    <xs:complexType>
        <xs:sequence>
            <xs:element minOccurs="0" name="IsAuthorizedResult" type="xs:boolean" />
        </xs:sequence>
    </xs:complexType>

```

```

</xs:element>
<xs:element name="RaiseAlertCompleted">
    <xs:complexType>
        <xs:sequence>
            <xs:element
                xmlns:q5="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.NetworkHea
lth.AlertFramework" minOccurs="0" name="alertInfo" nillable="true" type="q5:AlertInfo" />
                <xs:element minOccurs="0" name="errMessage" nillable="true" type="xs:string" />
            </xs:sequence>
        </xs:complexType>
    </xs:element>
<xs:element name="ClearAlertCompleted">
    <xs:complexType>
        <xs:sequence>
            <xs:element minOccurs="0" name="alertKey" nillable="true" type="xs:string" />
            <xs:element minOccurs="0" name="errMessage" nillable="true" type="xs:string" />
        </xs:sequence>
    </xs:complexType>
    </xs:element>
<xs:element name="SuppressAlertCompleted">
    <xs:complexType>
        <xs:sequence>
            <xs:element minOccurs="0" name="alertKey" nillable="true" type="xs:string" />
            <xs:element minOccurs="0" name="errMessage" nillable="true" type="xs:string" />
        </xs:sequence>
    </xs:complexType>
    </xs:element>
<xs:element name="RepairAlertCompleted">
    <xs:complexType>
        <xs:sequence>
            <xs:element minOccurs="0" name="alertKey" nillable="true" type="xs:string" />
            <xs:element minOccurs="0" name="errMessage" nillable="true" type="xs:string" />
        </xs:sequence>
    </xs:complexType>
    </xs:element>
<xs:element name="EvaluateAlertsCompleted">
    <xs:complexType>
        <xs:sequence>
            <xs:element minOccurs="0" name="machineId" nillable="true" type="xs:string" />
            <xs:element minOccurs="0" name="ignoreSchedule" type="xs:boolean" />
            <xs:element minOccurs="0" name="errMessage" nillable="true" type="xs:string" />
        </xs:sequence>
    </xs:complexType>
    </xs:element>
<xs:element name="RaisedAlerts">
    <xs:complexType>
        <xs:sequence>
            <xs:element
                xmlns:q6="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.NetworkHea
lth.AlertFramework" minOccurs="0" name="alertInfoList" nillable="true"
                type="q6:ArrayOfAlertInfo" />
            <xs:element
                xmlns:q7="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.NetworkHea
lth.AlertFramework" minOccurs="0" name="task" type="q7:TaskType" />
                <xs:element minOccurs="0" name="machineId" nillable="true" type="xs:string" />
            </xs:sequence>
        </xs:complexType>
    </xs:element>
<xs:element name="ClearedAlerts">
    <xs:complexType>
        <xs:sequence>
            <xs:element
                xmlns:q8="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.NetworkHea
lth.AlertFramework" minOccurs="0" name="alertInfoList" nillable="true"
                type="q8:ArrayOfAlertInfo" />
            <xs:element
                xmlns:q9="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.NetworkHea
lth.AlertFramework" minOccurs="0" name="task" type="q9:TaskType" />
                <xs:element minOccurs="0" name="machineId" nillable="true" type="xs:string" />
            </xs:sequence>
        </xs:complexType>
    </xs:element>

```

```

        </xs:sequence>
    </xs:complexType>
</xs:element>
<xs:element name="RegisterClientAgent">
    <xs:complexType>
        <xs:sequence>
            <xs:element minOccurs="0" name="networkMachineId" nillable="true" type="xs:string" />
        </xs:sequence>
    </xs:complexType>
</xs:element>
<xs:element name="RegisterClientAgentResponse">
    <xs:complexType>
        <xs:sequence />
    </xs:complexType>
</xs:element>
<xs:element name="SynchronizeAlerts">
    <xs:complexType>
        <xs:sequence>
            <xs:element
                xmlns:q10="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.NetworkHe
alh.AlertFramework" minOccurs="0" name="alerts" nillable="true" type="q10:ArrayOfAlertInfo"
/>
            <xs:element minOccurs="0" name="networkMachineId" nillable="true" type="xs:string" />
        <xs:element
                xmlns:q11="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.NetworkHe
alh.AlertFramework" minOccurs="0" name="task" type="q11:TaskType" />
            <xs:sequence>
        </xs:complexType>
</xs:element>
<xs:element name="ClearCallbackCommandQueue">
    <xs:complexType>
        <xs:sequence>
            <xs:element minOccurs="0" name="networkMachineId" nillable="true" type="xs:string" />
        </xs:sequence>
    </xs:complexType>
</xs:element>
<xs:element name="ClearCallbackCommandQueueResponse">
    <xs:complexType>
        <xs:sequence />
    </xs:complexType>
</xs:element>
<xs:element name="GetPlugInInformation">
    <xs:complexType>
        <xs:sequence />
    </xs:complexType>
</xs:element>
<xs:element name="GetPlugInInformationResponse">
    <xs:complexType>
        <xs:sequence>
            <xs:element
                xmlns:q12="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.NetworkHe
alh.Engine" minOccurs="0" name="GetPlugInInformationResult" nillable="true"
type="q12:ArrayOfPlugInInfo" />
        </xs:sequence>
    </xs:complexType>
</xs:element>
<xs:element name="DownloadDefinition">
    <xs:complexType>
        <xs:sequence>
            <xs:element minOccurs="0" name="featureName" nillable="true" type="xs:string" />
        </xs:sequence>
    </xs:complexType>
</xs:element>
<xs:element name="DownloadDefinitionResponse">
    <xs:complexType>
        <xs:sequence>
            <xs:element xmlns:q13="http://schemas.microsoft.com/Message"
name="DownloadDefinitionResult" type="q13:StreamBody" />
        </xs:sequence>
    </xs:complexType>
</xs:element>

```

```

        </xs:complexType>
    </xs:element>
<xs:element name="DownloadConfiguration">
    <xs:complexType>
        <xs:sequence>
            <xs:element minOccurs="0" name="featureName" nillable="true" type="xs:string" />
        </xs:sequence>
    </xs:complexType>
</xs:element>
<xs:element name="DownloadConfigurationResponse">
    <xs:complexType>
        <xs:sequence>
            <xs:element xmlns:q14="http://schemas.microsoft.com/Message"
name="DownloadConfigurationResult" type="q14:StreamBody" />
        </xs:sequence>
    </xs:complexType>
</xs:element>
<xs:element name="AlertChanged">
    <xs:complexType>
        <xs:sequence>
            <xs:element xmlns:q15="http://schemas.microsoft.com/2003/10/Serialization/Arrays"
minOccurs="0" name="commands" nillable="true" type="q15:ArrayOfanyType" />
        </xs:sequence>
    </xs:complexType>
</xs:element>
</xs:schema>

```

6.3.3 <http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.NetworkHealth.AlertFramework.Commands>

```

<?xml version="1.0" encoding="utf-8"?>
<xs:schema xmlns:ser="http://schemas.microsoft.com/2003/10/Serialization/"
xmlns:tns="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.NetworkHe
alth.AlertFramework.Commands" elementFormDefault="qualified"
targetNamespace="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.Net
workHealth.AlertFramework.Commands" xmlns:xs="http://www.w3.org/2001/XMLSchema">
    <xs:import schemaLocation="" namespace="http://schemas.microsoft.com/2003/10/Serialization/" />
    <xs:import schemaLocation="" namespace="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.NetworkHe
alth.AlertFramework" />
    <xs:complexType name="ClearCommand">
        <xs:sequence>
            <xs:element minOccurs="0" name="AlertDateAndTime" type="xs:dateTime" />
            <xs:element minOccurs="0" name="AlertInstanceId" type="ser:guid" />
            <xs:element minOccurs="0" name="MachineId" nillable="true" type="xs:string" />
        </xs:sequence>
    </xs:complexType>
    <xs:element name="ClearCommand" nillable="true" type="tns:ClearCommand" />
    <xs:complexType name="SuppressCommand">
        <xs:sequence>
            <xs:element minOccurs="0" name="AlertDateAndTime" type="xs:dateTime" />
            <xs:element minOccurs="0" name="AlertInstanceId" type="ser:guid" />
            <xs:element minOccurs="0" name="MachineId" nillable="true" type="xs:string" />
            <xs:element minOccurs="0" name="Suppress" type="xs:boolean" />
            <xs:element minOccurs="0" name="SuppressTime" type="xs:dateTime" />
        </xs:sequence>
    </xs:complexType>
    <xs:element name="SuppressCommand" nillable="true" type="tns:SuppressCommand" />
    <xs:complexType name="RaiseCommand">
        <xs:sequence>
            <xs:element
                xmlns:q1="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.NetworkHea
lth.AlertFramework" minOccurs="0" name="RaisedAlert" nillable="true" type="q1:AlertInfo" />
        </xs:sequence>
    </xs:complexType>
    <xs:element name="RaiseCommand" nillable="true" type="tns:RaiseCommand" />

```

```
</xs:schema>
```

6.3.4 http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.NetworkHealth.AlertFramework.Service

```
<?xml version="1.0" encoding="utf-8"?>
<xs:schema
  xmlns:tns="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.NetworkHe
  alth.AlertFramework.Service" elementFormDefault="qualified"
  targetNamespace="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.Net
  workHealth.AlertFramework.Service" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:import schemaLocation=""
    namespace="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.NetworkHe
    alth.AlertFramework" />
  <xs:complexType name="AlertListChunk">
    <xs:sequence>
      <xs:element
        xmlns:q1="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.NetworkHe
        alth.AlertFramework" minOccurs="0" name="Alerts" nillable="true" type="q1:ArrayOfAlertInfo" />
        <xs:element minOccurs="0" name="HasMore" type="xs:boolean" />
      </xs:sequence>
    </xs:complexType>
    <xs:element name="AlertListChunk" nillable="true" type="tns:AlertListChunk" />
  </xs:schema>
```

6.3.5 http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.NetworkHealth.AlertFramework

```
<?xml version="1.0" encoding="utf-8"?>
<xs:schema xmlns:ser="http://schemas.microsoft.com/2003/10/Serialization/"
  xmlns:tns="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.NetworkHe
  alth.AlertFramework" elementFormDefault="qualified"
  targetNamespace="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.Net
  workHealth.AlertFramework" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:import schemaLocation=""
    namespace="http://schemas.microsoft.com/2003/10/Serialization/Arrays" />
    <xs:import schemaLocation=""
      namespace="http://schemas.microsoft.com/2003/10/Serialization/" />
      <xs:import schemaLocation=""
        namespace="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.NetworkHe
        alth.Engine" />
        <xs:complexType name="ArrayOfAlertInfo">
          <xs:sequence>
            <xs:element minOccurs="0" maxOccurs="unbounded" name="AlertInfo" nillable="true"
              type="tns:AlertInfo" />
            </xs:sequence>
          </xs:complexType>
          <xs:element name="ArrayOfAlertInfo" nillable="true" type="tns:ArrayOfAlertInfo" />
          <xs:complexType name="AlertInfo">
            <xs:sequence>
              <xs:element minOccurs="0" name="ActionPerformed" nillable="true" type="xs:string" />
              <xs:element xmlns:q1="http://schemas.microsoft.com/2003/10/Serialization/Arrays"
                minOccurs="0" name="AdditionalInfo" nillable="true" type="q1:ArrayOfstring" />
                <xs:element minOccurs="0" name="DateAndTime" type="xs:dateTime" />
                <xs:element minOccurs="0" name="Description" nillable="true" type="xs:string" />
                <xs:element minOccurs="0" name="Escalate" type="xs:boolean" />
                <xs:element minOccurs="0" name="FeatureName" nillable="true" type="xs:string" />
                <xs:element minOccurs="0" name="FeatureTitle" nillable="true" type="xs:string" />
                <xs:element minOccurs="0" name="HealthDefinitionName" nillable="true" type="xs:string" />
              />
              <xs:element minOccurs="0" name="HealthDefinitionTitle" nillable="true" type="xs:string" />
            />
            <xs:element minOccurs="0" name="InstanceId" type="ser:guid" />
            <xs:element minOccurs="0" name="IsNew" type="xs:boolean" />
          </xs:sequence>
        </xs:complexType>
      </xs:element>
    </xs:sequence>
  </xs:complexType>
</xs:schema>
```

```

<xs:element minOccurs="0" name="IsRepairDefined" type="xs:boolean" />
<xs:element minOccurs="0" name="IsSuppressed" type="xs:boolean" />
<xs:element minOccurs="0" name="IsSystem" type="xs:boolean" />
<xs:element minOccurs="0" name="LastSuppressedDateTime" type="xs:dateTime" />
<xs:element minOccurs="0" name="MachineId" nillable="true" type="xs:string" />
<xs:element minOccurs="0" name="MachineName" nillable="true" type="xs:string" />
<xs:element minOccurs="0" name="RepairActionPerformed" nillable="true" type="xs:string"
/>
</xs:sequence>
<xs:complexType>
<xs:element name="AlertInfo" nillable="true" type="tns:AlertInfo" />
<xs:complexType name="UserContextTask">
<xs:sequence>
<xs:element minOccurs="0" name="Arguments" nillable="true" type="xs:string" />
<xs:element minOccurs="0" name="Program" nillable="true" type="xs:string" />
<xs:element minOccurs="0" name="Title" nillable="true" type="xs:string" />
</xs:sequence>
</xs:complexType>
<xs:element name="UserContextTask" nillable="true" type="tns:UserContextTask" />
<xs:simpleType name="TaskType">
<xs:restriction base="xs:string">
<xs:enumeration value="Raise" />
<xs:enumeration value="Evaluate" />
<xs:enumeration value="Clear" />
<xs:enumeration value="Update" />
</xs:restriction>
</xs:simpleType>
<xs:element name="TaskType" nillable="true" type="tns:TaskType" />
</xs:schema>

```

6.3.6 <http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.NetworkHealth.Engine>

```

<?xml version="1.0" encoding="utf-8"?>
<xs:schema
xmlns:tns="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.NetworkHe
alth.Engine" elementFormDefault="qualified"
targetNamespace="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.Net
workHealth.Engine" xmlns:xs="http://www.w3.org/2001/XMLSchema">
<xs:simpleType name="HealthStatus">
<xs:restriction base="xs:string">
<xs:enumeration value="OK" />
<xs:enumeration value="Information" />
<xs:enumeration value="Warning" />
<xs:enumeration value="Critical" />
<xs:enumeration value="Report" />
</xs:restriction>
</xs:simpleType>
<xs:element name="HealthStatus" nillable="true" type="tns:HealthStatus" />
<xs:complexType name="ArrayOfPlugInInfo">
<xs:sequence>
<xs:element minOccurs="0" maxOccurs="unbounded" name="PlugInInfo" nillable="true"
type="tns:PlugInInfo" />
</xs:sequence>
</xs:complexType>
<xs:element name="ArrayOfPlugInInfo" nillable="true" type="tns:ArrayOfPlugInInfo" />
<xs:complexType name="PlugInInfo">
<xs:sequence>
<xs:element name="x003C_ConfigHashCode_x003E_k__BackingField" nillable="true"
type="xs:base64Binary" />

```

```

<xs:element name="_x003C_DefinitionHashCode_x003E_k__BackingField" nillable="true"
type="xs:base64Binary" />
    <xs:element name="_x003C_FeatureName_x003E_k__BackingField" nillable="true"
type="xs:string" />
        <xs:element name="_x003C_RelativePath_x003E_k__BackingField" nillable="true"
type="xs:string" />
    </xs:sequence>
</xs:complexType>
<xs:element name="PlugInInfo" nillable="true" type="tns:PlugInInfo" />
</xs:schema>

```

6.3.7 http://schemas.microsoft.com/2003/10/Serialization/Arrays

```

<?xml version="1.0" encoding="utf-8"?>
<xs:schema xmlns:tns="http://schemas.microsoft.com/2003/10/Serialization/Arrays"
elementFormDefault="qualified"
targetNamespace="http://schemas.microsoft.com/2003/10/Serialization/Arrays"
xmlns:xs="http://www.w3.org/2001/XMLSchema">
    <xs:complexType name="ArrayOfstring">
        <xs:sequence>
            <xs:element minOccurs="0" maxOccurs="unbounded" name="string" nillable="true"
type="xs:string" />
        </xs:sequence>
    </xs:complexType>
    <xs:element name="ArrayOfstring" nillable="true" type="tns:ArrayOfstring" />
    <xs:complexType name="ArrayOfanyType">
        <xs:sequence>
            <xs:element minOccurs="0" maxOccurs="unbounded" name="anyType" nillable="true"
type="xs:anyType" />
        </xs:sequence>
    </xs:complexType>
    <xs:element name="ArrayOfanyType" nillable="true" type="tns:ArrayOfanyType" />
</xs:schema>

```

6.3.8 http://schemas.microsoft.com/2003/10/Serialization

```

<?xml version="1.0" encoding="utf-8"?>
<xs:schema xmlns:tns="http://schemas.microsoft.com/2003/10/Serialization/"
attributeFormDefault="qualified" elementFormDefault="qualified"
targetNamespace="http://schemas.microsoft.com/2003/10/Serialization/"
xmlns:xs="http://www.w3.org/2001/XMLSchema">
    <xs:element name="anyType" nillable="true" type="xs:anyType" />
    <xs:element name="anyURI" nillable="true" type="xs:anyURI" />
    <xs:element name="base64Binary" nillable="true" type="xs:base64Binary" />
    <xs:element name="boolean" nillable="true" type="xs:boolean" />
    <xs:element name="byte" nillable="true" type="xs:byte" />
    <xs:element name="dateTime" nillable="true" type="xs:dateTime" />
    <xs:element name="decimal" nillable="true" type="xs:decimal" />
    <xs:element name="double" nillable="true" type="xs:double" />
    <xs:element name="float" nillable="true" type="xs:float" />
    <xs:element name="int" nillable="true" type="xs:int" />
    <xs:element name="long" nillable="true" type="xs:long" />
    <xs:element name="QName" nillable="true" type="xs:QName" />
    <xs:element name="short" nillable="true" type="xs:short" />
    <xs:element name="string" nillable="true" type="xs:string" />
    <xs:element name="unsignedByte" nillable="true" type="xs:unsignedByte" />
    <xs:element name="unsignedInt" nillable="true" type="xs:unsignedInt" />
    <xs:element name="unsignedLong" nillable="true" type="xs:unsignedLong" />
    <xs:element name="unsignedShort" nillable="true" type="xs:unsignedShort" />
    <xs:element name="char" nillable="true" type="tns:char" />
    <xs:simpleType name="char">
        <xs:restriction base="xs:int" />
    </xs:simpleType>
    <xs:element name="duration" nillable="true" type="tns:duration" />
    <xs:simpleType name="duration">

```

```

<xs:restriction base="xs:duration">
    <xs:pattern value="-?P(\d*D)?(T(\d*H)?(\d*M)?(\d*(\.\.\d*)?S)?)?" />
    <xs:minInclusive value="-P10675199DT2H48M5.4775808S" />
    <xs:maxInclusive value="P10675199DT2H48M5.4775807S" />
</xs:restriction>
</xs:simpleType>
<xs:element name="guid" nillable="true" type="tns:guid" />
<xs:simpleType name="guid">
    <xs:restriction base="xs:string">
        <xs:pattern value="[\da-fA-F]{8}-[\da-fA-F]{4}-[\da-fA-F]{4}-[\da-fA-F]{4}-[\da-fA-F]{12}" />
    </xs:restriction>
</xs:simpleType>
<xs:attribute name="FactoryType" type="xs:QName" />
<xs:attribute name="Id" type="xs:ID" />
<xs:attribute name="Ref" type="xs:IDREF" />
</xs:schema>

```

6.3.9 <http://schemas.microsoft.com/Message>

```

<?xml version="1.0" encoding="utf-8"?>
<xs:schema xmlns:tns="http://schemas.microsoft.com/Message" elementFormDefault="qualified"
targetNamespace="http://schemas.microsoft.com/Message"
xmlns:xs="http://www.w3.org/2001/XMLSchema">
    <xs:simpleType name="StreamBody">
        <xs:restriction base="xs:base64Binary" />
    </xs:simpleType>
</xs:schema>

```

6.3.10 <http://schemas.datacontract.org/2004/07/System.ServiceModel.Security>

```

<?xml version="1.0" encoding="utf-8"?>
<xs:schema xmlns:tns="http://schemas.datacontract.org/2004/07/System.ServiceModel.Security"
elementFormDefault="qualified"
targetNamespace="http://schemas.datacontract.org/2004/07/System.ServiceModel.Security"
xmlns:xs="http://www.w3.org/2001/XMLSchema">
    <xs:import schemaLocation="" namespace="http://schemas.datacontract.org/2004/07/System.ServiceModel" />
    <xs:complexType name="SecurityAccessDeniedException">
        <xs:complexContent mixed="false">
            <xs:extension xmlns:q1="http://schemas.datacontract.org/2004/07/System.ServiceModel"
base="q1:CommunicationException" />
        </xs:complexContent>
    </xs:complexType>
    <xs:element name="SecurityAccessDeniedException" nillable="true"
type="tns:SecurityAccessDeniedException" />
</xs:schema>

```

6.3.11 <http://schemas.datacontract.org/2004/07/System.ServiceModel>

```

<?xml version="1.0" encoding="utf-8"?>
<xs:schema xmlns:tns="http://schemas.datacontract.org/2004/07/System.ServiceModel"
elementFormDefault="qualified"
targetNamespace="http://schemas.datacontract.org/2004/07/System.ServiceModel"
xmlns:xs="http://www.w3.org/2001/XMLSchema">
    <xs:import schemaLocation="" namespace="http://schemas.datacontract.org/2004/07/System" />
    <xs:complexType name="CommunicationException">
        <xs:complexContent mixed="false">
            <xs:extension xmlns:q1="http://schemas.datacontract.org/2004/07/System"
base="q1:SystemException" />
        </xs:complexContent>
    </xs:complexType>
</xs:schema>

```

```

<xs:element name="CommunicationException" nillable="true" type="tns:CommunicationException"
/>

</xs:schema>

```

6.3.12 http://schemas.datacontract.org/2004/07/System

```

<?xml version="1.0" encoding="utf-8"?>
<xs:schema xmlns:ser="http://schemas.microsoft.com/2003/10/Serialization/"
  xmlns:tns="http://schemas.datacontract.org/2004/07/System" elementFormDefault="qualified"
  targetNamespace="http://schemas.datacontract.org/2004/07/System"
  xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:import schemaLocation="" namespace="http://schemas.microsoft.com/2003/10/Serialization/" />
  <xs:complexType name="SystemException">
    <xs:complexContent mixed="false">
      <xs:extension base="tns:Exception" />
    </xs:complexContent>
  </xs:complexType>
  <xs:element name="SystemException" nillable="true" type="tns:SystemException" />
  <xs:complexType name="Exception">
    <xs:sequence>
      <xs:any minOccurs="0" maxOccurs="unbounded" namespace="#local" processContents="skip"
    />
    </xs:sequence>
    <xs:attribute ref="ser:FactoryType" />
  </xs:complexType>
  <xs:element name="Exception" nillable="true" type="tns:Exception" />
  <xs:complexType name="ArgumentNullException">
    <xs:complexContent mixed="false">
      <xs:extension base="tns:ArgumentException" />
    </xs:complexContent>
  </xs:complexType>
  <xs:element name="ArgumentNullException" nillable="true" type="tns:ArgumentNullException"
  />
  <xs:complexType name="ArgumentException">
    <xs:complexContent mixed="false">
      <xs:extension base="tns:SystemException" />
    </xs:complexContent>
  </xs:complexType>
  <xs:element name="ArgumentException" nillable="true" type="tns:ArgumentException" />
</xs:schema>

```

6.4 Machine Identity Provider Service WSDL

6.4.1 wsdl

```

<?xml version="1.0" encoding="utf-8"?>
<wsdl:definitions xmlns:wsap="http://schemas.xmlsoap.org/ws/2004/08/addressing/policy"
  xmlns:wsa10="http://www.w3.org/2005/08/addressing" xmlns:tns="http://tempuri.org/"
  xmlns:msc="http://schemas.microsoft.com/ws/2005/12/wsdl/contract"
  xmlns:soapenc="http://schemas.xmlsoap.org/soap/encoding/"
  xmlns:soap="http://schemas.xmlsoap.org/wsdl/soap/"
  xmlns:wsp="http://schemas.xmlsoap.org/ws/2004/09/policy"
  xmlns:wsam="http://www.w3.org/2007/05/addressing/metadata"
  xmlns:wsa="http://schemas.xmlsoap.org/ws/2004/08/addressing"
  xmlns:wsaw="http://www.w3.org/2006/05/addressing/wsdl"
  xmlns:soap12="http://schemas.xmlsoap.org/wsdl/soap12/" xmlns:wsu="http://docs.oasis-
  open.org/wss/2004/01/oasis-200401-wss-wsseutility-1.0.xsd"
  xmlns:xs="http://www.w3.org/2001/XMLSchema" name="MachineIdentityProvider"
  targetNamespace="http://tempuri.org/" xmlns:wsdl="http://schemas.xmlsoap.org/wsdl/">
  <wsp:Policy wsu:Id="CustomBinding_IMachineIdentityProvider_policy">
    <wsp:ExactlyOne>

```

```

<wsp:All>
  <msb:BinaryEncoding
  xmlns:msb="http://schemas.microsoft.com/ws/2004/2004/mspolicy/netbinary1" />
  <sp:TransportBinding xmlns:sp="http://schemas.xmlsoap.org/ws/2005/07/securitypolicy">
    <wsp:Policy>
      <sp:TransportToken>
        <wsp:Policy>
          <msf:SslTransportSecurity
  xmlns:msf="http://schemas.microsoft.com/ws/2006/05/framing/policy">
            <msf:RequireClientCertificate />
          </msf:SslTransportSecurity>
        </wsp:Policy>
      </sp:TransportToken>
      <sp:AlgorithmSuite>
        <wsp:Policy>
          <sp:Basic256 />
        </wsp:Policy>
      </sp:AlgorithmSuite>
      <sp:Layout>
        <wsp:Policy>
          <sp:Strict />
        </wsp:Policy>
      </sp:Layout>
    </wsp:Policy>
  </sp:TransportBinding>
  <wsaw:UsingAddressing />
</wsp:All>
</wsp:ExactlyOne>
</wsp:Policy>
<wsdl:types>
  <xsd:schema targetNamespace="http://tempuri.org/Imports">
    <xsd:import schemaLocation="" namespace="http://tempuri.org/" />
    <xsd:import schemaLocation="" namespace="http://schemas.microsoft.com/2003/10/Serialization/" />
    <xsd:import schemaLocation="" namespace="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.Devices.IIdentity" />
  </xsd:schema>
</wsdl:types>
<wsdl:message name="IMachineIdentityProvider_RenewCert_InputMessage">
  <wsdl:part name="parameters" element="tns:RenewCert" />
</wsdl:message>
<wsdl:message name="IMachineIdentityProvider_RevokeCert_InputMessage">
  <wsdl:part name="parameters" element="tns:RevokeCert" />
</wsdl:message>
<wsdl:message name="IMachineIdentityProvider_GenerateCertResponse_InputMessage">
  <wsdl:part name="parameters" element="tns:GenerateCertResponse" />
</wsdl:message>
<wsdl:message name="IMachineIdentityProvider_GenerateSid_InputMessage">
  <wsdl:part name="parameters" element="tns:GenerateSid" />
</wsdl:message>
<wsdl:message name="IMachineIdentityProvider_GetMachineStatus_InputMessage">
  <wsdl:part name="parameters" element="tns:GetMachineStatus" />
</wsdl:message>
<wsdl:message name="IMachineIdentityProvider_MakeUserRemoteDesktopMapping_InputMessage">
  <wsdl:part name="parameters" element="tns:MakeUserRemoteDesktopMapping" />
</wsdl:message>
<wsdl:message name="IMachineIdentityProvider_ReturnNewCertResponse_OutputCallbackMessage">
  <wsdl:part name="parameters" element="tns:ReturnNewCertResponse" />
</wsdl:message>
<wsdl:message name="IMachineIdentityProvider_ReturnRenewCert_OutputCallbackMessage">
  <wsdl:part name="parameters" element="tns:ReturnRenewCert" />
</wsdl:message>
<wsdl:message name="IMachineIdentityProvider_ReturnSid_OutputCallbackMessage">
  <wsdl:part name="parameters" element="tns:ReturnSid" />
</wsdl:message>
<wsdl:message name="IMachineIdentityProvider_ReturnRevokeCert_OutputCallbackMessage">
  <wsdl:part name="parameters" element="tns:ReturnRevokeCert" />
</wsdl:message>

```

```

<wsdl:message name="IMachineIdentityProvider_ReturnGetMachineStatus_OutputCallbackMessage">
    <wsdl:part name="parameters" element="tns:ReturnGetMachineStatus" />
</wsdl:message>
<wsdl:message
name="IMachineIdentityProvider_ReturnMakeUserRemoteDesktopMapping_OutputCallbackMessage">
    <wsdl:part name="parameters" element="tns:ReturnMakeUserRemoteDesktopMapping" />
</wsdl:message>
<wsdl:portType name="IMachineIdentityProvider">
    <wsdl:operation name="RenewCert">
        <wsdl:input wsaw:Action="http://tempuri.org/IMachineIdentityProvider/RenewCert" message="tns:IMachineIdentityProvider_RenewCert_InputMessage" />
    </wsdl:operation>
    <wsdl:operation name="RevokeCert">
        <wsdl:input wsaw:Action="http://tempuri.org/IMachineIdentityProvider/RevokeCert" message="tns:IMachineIdentityProvider_RevokeCert_InputMessage" />
    </wsdl:operation>
    <wsdl:operation name="GenerateCertResponse">
        <wsdl:input wsaw:Action="http://tempuri.org/IMachineIdentityProvider/GenerateCertResponse" message="tns:IMachineIdentityProvider_GenerateCertResponse_InputMessage" />
    </wsdl:operation>
    <wsdl:operation name="GenerateSid">
        <wsdl:input wsaw:Action="http://tempuri.org/IMachineIdentityProvider/GenerateSid" message="tns:IMachineIdentityProvider_GenerateSid_InputMessage" />
    </wsdl:operation>
    <wsdl:operation name="GetMachineStatus">
        <wsdl:input wsaw:Action="http://tempuri.org/IMachineIdentityProvider/GetMachineStatus" message="tns:IMachineIdentityProvider_GetMachineStatus_InputMessage" />
    </wsdl:operation>
    <wsdl:operation name="MakeUserRemoteDesktopMapping">
        <wsdl:input wsaw:Action="http://tempuri.org/IMachineIdentityProvider/MakeUserRemoteDesktopMapping" message="tns:IMachineIdentityProvider_MakeUserRemoteDesktopMapping_InputMessage" />
    </wsdl:operation>
    <wsdl:operation name="ReturnNewCertResponse">
        <wsdl:output wsaw:Action="http://tempuri.org/IMachineIdentityProvider/ReturnNewCertResponse" message="tns:IMachineIdentityProvider_ReturnNewCertResponse_OutputCallbackMessage" />
    </wsdl:operation>
    <wsdl:operation name="ReturnRenewCert">
        <wsdl:output wsaw:Action="http://tempuri.org/IMachineIdentityProvider/ReturnRenewCert" message="tns:IMachineIdentityProvider_ReturnRenewCert_OutputCallbackMessage" />
    </wsdl:operation>
    <wsdl:operation name="ReturnSid">
        <wsdl:output wsaw:Action="http://tempuri.org/IMachineIdentityProvider/ReturnSid" message="tns:IMachineIdentityProvider_ReturnSid_OutputCallbackMessage" />
    </wsdl:operation>
    <wsdl:operation name="ReturnRevokeCert">
        <wsdl:output wsaw:Action="http://tempuri.org/IMachineIdentityProvider/ReturnRevokeCert" message="tns:IMachineIdentityProvider_ReturnRevokeCert_OutputCallbackMessage" />
    </wsdl:operation>
    <wsdl:operation name="ReturnGetMachineStatus">
        <wsdl:output wsaw:Action="http://tempuri.org/IMachineIdentityProvider/ReturnGetMachineStatus" message="tns:IMachineIdentityProvider_ReturnGetMachineStatus_OutputCallbackMessage" />
    </wsdl:operation>
    <wsdl:operation name="ReturnMakeUserRemoteDesktopMapping">
        <wsdl:output wsaw:Action="http://tempuri.org/IMachineIdentityProvider/ReturnMakeUserRemoteDesktopMapping" message="tns:IMachineIdentityProvider_ReturnMakeUserRemoteDesktopMapping_OutputCallbackMessage" />
    </wsdl:operation>
</wsdl:portType>
<wsdl:binding name="CustomBinding_IMachineIdentityProvider" type="tns:IMachineIdentityProvider">
    <wsp:PolicyReference URI="#CustomBinding_IMachineIdentityProvider_policy" />
    <soap12:binding transport="http://schemas.microsoft.com/soap/tcp" />
    <wsdl:operation name="RenewCert">
```

```

<soap12:operation soapAction="http://tempuri.org/IMachineIdentityProvider/RenewCert"
style="document" />
<wsdl:input>
    <soap12:body use="literal" />
</wsdl:input>
</wsdl:operation>
<wsdl:operation name="RevokeCert">
    <soap12:operation soapAction="http://tempuri.org/IMachineIdentityProvider/RevokeCert"
style="document" />
<wsdl:input>
    <soap12:body use="literal" />
</wsdl:input>
</wsdl:operation>
<wsdl:operation name="GenerateCertResponse">
    <soap12:operation
soapAction="http://tempuri.org/IMachineIdentityProvider/GenerateCertResponse"
style="document" />
<wsdl:input>
    <soap12:body use="literal" />
</wsdl:input>
</wsdl:operation>
<wsdl:operation name="GenerateSid">
    <soap12:operation soapAction="http://tempuri.org/IMachineIdentityProvider/GenerateSid"
style="document" />
<wsdl:input>
    <soap12:body use="literal" />
</wsdl:input>
</wsdl:operation>
<wsdl:operation name="GetMachineStatus">
    <soap12:operation
soapAction="http://tempuri.org/IMachineIdentityProvider/GetMachineStatus" style="document" />
<wsdl:input>
    <soap12:body use="literal" />
</wsdl:input>
</wsdl:operation>
<wsdl:operation name="MakeUserRemoteDesktopMapping">
    <soap12:operation
soapAction="http://tempuri.org/IMachineIdentityProvider/MakeUserRemoteDesktopMapping"
style="document" />
<wsdl:input>
    <soap12:body use="literal" />
</wsdl:input>
</wsdl:operation>
<wsdl:operation name="ReturnNewCertResponse">
    <soap12:operation
soapAction="http://tempuri.org/IMachineIdentityProvider/ReturnNewCertResponse"
style="document" />
<wsdl:output>
    <soap12:body use="literal" />
</wsdl:output>
</wsdl:operation>
<wsdl:operation name="ReturnRenewCert">
    <soap12:operation
soapAction="http://tempuri.org/IMachineIdentityProvider/ReturnRenewCert" style="document" />
<wsdl:output>
    <soap12:body use="literal" />
</wsdl:output>
</wsdl:operation>
<wsdl:operation name="ReturnSid">
    <soap12:operation soapAction="http://tempuri.org/IMachineIdentityProvider/ReturnSid"
style="document" />
<wsdl:output>
    <soap12:body use="literal" />
</wsdl:output>
</wsdl:operation>
<wsdl:operation name="ReturnRevokeCert">
    <soap12:operation
soapAction="http://tempuri.org/IMachineIdentityProvider/ReturnRevokeCert" style="document" />
<wsdl:output>

```

```

        <soap12:body use="literal" />
    </wsdl:output>
</wsdl:operation>
<wsdl:operation name="ReturnGetMachineStatus">
    <soap12:operation
soapAction="http://tempuri.org/IMachineIdentityProvider/ReturnGetMachineStatus"
style="document" />
    <wsdl:output>
        <soap12:body use="literal" />
    </wsdl:output>
</wsdl:operation>
<wsdl:operation name="ReturnMakeUserRemoteDesktopMapping">
    <soap12:operation
soapAction="http://tempuri.org/IMachineIdentityProvider/ReturnMakeUserRemoteDesktopMapping"
style="document" />
    <wsdl:output>
        <soap12:body use="literal" />
    </wsdl:output>
</wsdl:operation>
</wsdl:binding>
<wsdl:service name="MachineIdentityProvider">
    <wsdl:port name="CustomBinding_IMachineIdentityProvider"
binding="tns:CustomBinding_IMachineIdentityProvider">
        <soap12:address
location="net.tcp://serverName:6602/Microsoft.WindowsServerSolutions.MachineIdentityProvider/
Microsoft.WindowsServerSolutions.Devices.Identity.IMachineIdentityProvider" />
        <wsa10:EndpointReference>

<wsa10:Address>net.tcp://serverName:6602/Microsoft.WindowsServerSolutions.MachineIdentityProv
ider/Microsoft.WindowsServerSolutions.Devices.Identity.IMachineIdentityProvider</wsa10:Addres
s>
        <Identity xmlns="http://schemas.xmlsoap.org/ws/2006/02/addressingidentity">
            <Dns>SERVERNAME</Dns>
        </Identity>
    </wsa10:EndpointReference>
</wsdl:port>
</wsdl:service>
</wsdl:definitions>
```

6.4.2 http://tempuri.org

```

<?xml version="1.0" encoding="utf-8"?>
<xs:schema xmlns:tns="http://tempuri.org/" elementFormDefault="qualified"
targetNamespace="http://tempuri.org/" xmlns:xs="http://www.w3.org/2001/XMLSchema">
    <xs:import schemaLocation="" namespace="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.Devices.Identity" />
    <xs:element name="RenewCert">
        <xs:complexType>
            <xs:sequence>
                <xs:element minOccurs="0" name="strCSR" nillable="true" type="xs:string" />
            </xs:sequence>
        </xs:complexType>
    </xs:element>
    <xs:element name="RevokeCert">
        <xs:complexType>
            <xs:sequence />
        </xs:complexType>
    </xs:element>
    <xs:element name="GenerateCertResponse">
        <xs:complexType>
            <xs:sequence>
                <xs:element minOccurs="0" name="userName" nillable="true" type="xs:string" />
                <xs:element minOccurs="0" name="password" nillable="true" type="xs:string" />
                <xs:element minOccurs="0" name="strCSR" nillable="true" type="xs:string" />
                <xs:element minOccurs="0" name="machineName" nillable="true" type="xs:string" />
            </xs:sequence>
```

```

        </xs:complexType>
    </xs:element>
    <xs:element name="GenerateSid">
        <xs:complexType>
            <xs:sequence>
                <xs:element minOccurs="0" name="userName" nillable="true" type="xs:string" />
                <xs:element minOccurs="0" name="password" nillable="true" type="xs:string" />
                <xs:element minOccurs="0" name="machineName" nillable="true" type="xs:string" />
                <xs:element minOccurs="0" name="bForce" type="xs:boolean" />
            </xs:sequence>
        </xs:complexType>
    </xs:element>
    <xs:element name="GetMachineStatus">
        <xs:complexType>
            <xs:sequence>
                <xs:element minOccurs="0" name="userName" nillable="true" type="xs:string" />
                <xs:element minOccurs="0" name="password" nillable="true" type="xs:string" />
                <xs:element minOccurs="0" name="machineName" nillable="true" type="xs:string" />
            </xs:sequence>
        </xs:complexType>
    </xs:element>
    <xs:element name="MakeUserRemoteDesktopMapping">
        <xs:complexType>
            <xs:sequence>
                <xs:element minOccurs="0" name="username" nillable="true" type="xs:string" />
            </xs:sequence>
        </xs:complexType>
    </xs:element>
    <xs:element name="ReturnNewCertResponse">
        <xs:complexType>
            <xs:sequence>
                <xs:element minOccurs="0" name="newCert" nillable="true" type="xs:string" />
            </xs:sequence>
        </xs:complexType>
    </xs:element>
    <xs:element name="ReturnRenewCert">
        <xs:complexType>
            <xs:sequence>
                <xs:element minOccurs="0" name="newCert" nillable="true" type="xs:string" />
            </xs:sequence>
        </xs:complexType>
    </xs:element>
    <xs:element name="ReturnSid">
        <xs:complexType>
            <xs:sequence>
                <xs:element minOccurs="0" name="sid" nillable="true" type="xs:string" />
            </xs:sequence>
        </xs:complexType>
    </xs:element>
    <xs:element name="ReturnRevokeCert">
        <xs:complexType>
            <xs:sequence>
                <xs:element
                    xmlns:q3="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.Devices.Identity"
                    minOccurs="0" name="returnCode" nillable="true" type="q3:ReturnClass" />
            </xs:sequence>
        </xs:complexType>
    </xs:element>
    <xs:element name="ReturnGetMachineStatus">
        <xs:complexType>

```

```

<xs:sequence>
  <xs:element
    xmlns:q5="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.Devices.Id
entity" minOccurs="0" name="status" nillable="true" type="q5:GetMachineStatusType" />
  <xs:element
    xmlns:q6="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.Devices.Id
entity" minOccurs="0" name="returnCode" nillable="true" type="q6:ReturnClass" />
</xs:sequence>
</xs:complexType>
</xs:element>
<xs:element name="ReturnMakeUserRemoteDesktopMapping">
  <xs:complexType>
    <xs:sequence>
      <xs:element
        xmlns:q7="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.Devices.Id
entity" minOccurs="0" name="returnCode" nillable="true" type="q7:ReturnClass" />
    </xs:sequence>
  </xs:complexType>
</xs:element>
</xs:schema>

```

6.4.3 http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.Devices.Identity

```

<?xml version="1.0" encoding="utf-8"?>
<xs:schema
  xmlns:tns="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.Devices.I
dentity" elementFormDefault="qualified"
  targetNamespace="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.Dev
ices.Identity" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexType name="ReturnClass">
    <xs:sequence>
      <xs:element minOccurs="0" name="ErrorCatalog" type="tns:ErrorCatalogType" />
      <xs:element minOccurs="0" name="NativeError" type="xs:int" />
    </xs:sequence>
  </xs:complexType>
  <xs:element name="ReturnClass" nillable="true" type="tns:ReturnClass" />
  <xs:simpleType name="ErrorCatalogType">
    <xs:restriction base="xs:string">
      <xs:enumeration value="Succeeded" />
      <xs:enumeration value="MachineExists" />
      <xs:enumeration value="NetworkError" />
      <xs:enumeration value="CAEror" />
      <xs:enumeration value="InvalidUser" />
      <xs:enumeration value="InvalidOwnerOfMachine" />
      <xs:enumeration value="InvalidCert" />
      <xs:enumeration value="ProviderNotAvailable" />
      <xs:enumeration value="AccessDenied" />
      <xs:enumeration value="TooManyComputers" />
      <xs:enumeration value="OtherError" />
    </xs:restriction>
  </xs:simpleType>
  <xs:element name="ErrorCatalogType" nillable="true" type="tns:ErrorCatalogType" />
  <xs:complexType name="GetMachineStatusType">
    <xs:sequence>
      <xs:element minOccurs="0" name="CurrentClientComputer" type="xs:int" />
      <xs:element minOccurs="0" name="MachineStatus" type="tns:MachineStatus" />
      <xs:element minOccurs="0" name="MaxClientComputer" type="xs:int" />
    </xs:sequence>
  </xs:complexType>
  <xs:element name="GetMachineStatusType" nillable="true" type="tns:GetMachineStatusType" />
  <xs:simpleType name="MachineStatus">
    <xs:restriction base="xs:string">
      <xs:enumeration value="Active" />
      <xs:enumeration value="Deactive" />
      <xs:enumeration value="ActiveWithCert" />
      <xs:enumeration value="DeactiveWithCert" />
    </xs:restriction>
  </xs:simpleType>

```

```

        <xs:enumeration value="NotExists" />
    </xs:restriction>
</xs:simpleType>
<xs:element name="MachineStatus" nillable="true" type="tns:MachineStatus" />
</xs:schema>

```

6.4.4 <http://schemas.microsoft.com/2003/10/Serialization>

```

<?xml version="1.0" encoding="utf-8"?>
<xs:schema xmlns:tns="http://schemas.microsoft.com/2003/10/Serialization/" attributeFormDefault="qualified" elementFormDefault="qualified" targetNamespace="http://schemas.microsoft.com/2003/10/Serialization/" xmlns:xs="http://www.w3.org/2001/XMLSchema">
    <xs:element name="anyType" nillable="true" type="xs:anyType" />
    <xs:element name="anyURI" nillable="true" type="xs:anyURI" />
    <xs:element name="base64Binary" nillable="true" type="xs:base64Binary" />
    <xs:element name="boolean" nillable="true" type="xs:boolean" />
    <xs:element name="byte" nillable="true" type="xs:byte" />
    <xs:element name="dateTime" nillable="true" type="xs:dateTime" />
    <xs:element name="decimal" nillable="true" type="xs:decimal" />
    <xs:element name="double" nillable="true" type="xs:double" />
    <xs:element name="float" nillable="true" type="xs:float" />
    <xs:element name="int" nillable="true" type="xs:int" />
    <xs:element name="long" nillable="true" type="xs:long" />
    <xs:element name="QName" nillable="true" type="xs:QName" />
    <xs:element name="short" nillable="true" type="xs:short" />
    <xs:element name="string" nillable="true" type="xs:string" />
    <xs:element name="unsignedByte" nillable="true" type="xs:unsignedByte" />
    <xs:element name="unsignedInt" nillable="true" type="xs:unsignedInt" />
    <xs:element name="unsignedLong" nillable="true" type="xs:unsignedLong" />
    <xs:element name="unsignedShort" nillable="true" type="xs:unsignedShort" />
    <xs:element name="char" nillable="true" type="tns:char" />
    <xs:simpleType name="char">
        <xs:restriction base="xs:int" />
    </xs:simpleType>
    <xs:element name="duration" nillable="true" type="tns:duration" />
    <xs:simpleType name="duration">
        <xs:restriction base="xs:duration">
            <xs:pattern value="\-?P(\d*D)?(T(\d*H)?(\d*M)?(\d*(\.\d*)?S)?)?" />
            <xs:minInclusive value="-P10675199DT2H48M5.4775808S" />
            <xs:maxInclusive value="P10675199DT2H48M5.4775807S" />
        </xs:restriction>
    </xs:simpleType>
    <xs:element name="guid" nillable="true" type="tns:guid" />
    <xs:simpleType name="guid">
        <xs:restriction base="xs:string">
            <xs:pattern value="[\da-fA-F]{8}-[\da-fA-F]{4}-[\da-fA-F]{4}-[\da-fA-F]{4}-[\da-fA-F]{12}" />
        </xs:restriction>
    </xs:simpleType>
    <xs:attribute name="FactoryType" type="xs:QName" />
    <xs:attribute name="Id" type="xs:ID" />
    <xs:attribute name="Ref" type="xs:IDREF" />
</xs:schema>

```

6.5 User Identity Provider Service WSDL

6.5.1 IUserLogonProvider

6.5.1.1 wsdl1

```
<?xml version="1.0" encoding="utf-8"?>
```

```

<wsdl:definitions xmlns:wsap="http://schemas.xmlsoap.org/ws/2004/08/addressing/policy"
  xmlns:wsa10="http://www.w3.org/2005/08/addressing" xmlns:tns="http://tempuri.org/"
  xmlns:msc="http://schemas.microsoft.com/ws/2005/12/wsdl/contract"
  xmlns:soapenc="http://schemas.xmlsoap.org/soap/encoding/"
  xmlns: wsp="http://schemas.xmlsoap.org/ws/2004/09/policy"
  xmlns:i0="http://www.microsoft.com/WindowsServerSolutions/ProviderFramework/Notifications/3/2
  010" xmlns:wsam="http://www.w3.org/2007/05/addressing/metadata"
  xmlns:wsa="http://schemas.xmlsoap.org/ws/2004/08/addressing"
  xmlns:soap12="http://schemas.xmlsoap.org/wsdl/soap12/"
  xmlns:wsaw="http://www.w3.org/2006/05/addressing/wsdl"
  xmlns:soap="http://schemas.xmlsoap.org/wsdl/soap/" xmlns:wsu="http://docs.oasis-
  open.org/wss/2004/01/oasis-200401-wss-wssecurity-utility-1.0.xsd"
  xmlns:xsd="http://www.w3.org/2001/XMLSchema" name="UserLogonProvider"
  targetNamespace="http://tempuri.org/" xmlns:wsdl="http://schemas.xmlsoap.org/wsdl/">
  <wsp:Policy wsu:Id="CustomBinding_IUserLogonProvider_policy">
    <wsp:ExactlyOne>
      <wsp:All>
        <msb:BinaryEncoding
  xmlns:msb="http://schemas.microsoft.com/ws/06/2004/mspolicy/netbinary1" />
        <sp:TransportBinding xmlns:sp="http://schemas.xmlsoap.org/ws/2005/07/securitypolicy">
          <wsp:Policy>
            <sp:TransportToken>
              <wsp:Policy>
                <msf:SslTransportSecurity
  xmlns:msf="http://schemas.microsoft.com/ws/2006/05/framing/policy" />
              </wsp:Policy>
            </sp:TransportToken>
            <sp:AlgorithmSuite>
              <wsp:Policy>
                <sp:Basic256 />
              </wsp:Policy>
            </sp:AlgorithmSuite>
            <sp:Layout>
              <wsp:Policy>
                <sp:Strict />
              </wsp:Policy>
            </sp:Layout>
          </wsp:Policy>
        </sp:TransportBinding>
        <wsaw:UsingAddressing />
      </wsp:All>
    </wsp:ExactlyOne>
  </wsp:Policy>
  <wsdl:import
  namespace="http://www.microsoft.com/WindowsServerSolutions/ProviderFramework/Notifications/3/
  2010" location="" />
  <wsdl:types />
  <wsdl:binding name="CustomBinding_IUserLogonProvider" type="i0:IUserLogonProvider">
    <wsp:PolicyReference URI="#CustomBinding_IUserLogonProvider_policy" />
    <soap12:binding transport="http://schemas.microsoft.com/soap/tcp" />
    <wsdl:operation name="LogonUser">
      <soap12:operation
  soapAction="http://www.microsoft.com/WindowsServerSolutions/ProviderFramework/Notifications/3
  /2010/IUserLogonProvider/LogonUser" style="document" />
      <wsdl:input>
        <soap12:body use="literal" />
      </wsdl:input>
      <wsdl:output>
        <soap12:body use="literal" />
      </wsdl:output>
      <wsdl:fault name="UserFaultFault">
        <soap12:fault use="literal" name="UserFaultFault" namespace="" />
      </wsdl:fault>
      <wsdl:fault name="UserExceptionFault">
        <soap12:fault use="literal" name="UserExceptionFault" namespace="" />
      </wsdl:fault>
      <wsdl:fault name="UserExceptionFaultFault">
        <soap12:fault use="literal" name="UserExceptionFaultFault" namespace="" />
      </wsdl:fault>
    </wsdl:operation>
  </wsdl:binding>

```

```

        </wsdl:operation>
    </wsdl:binding>
<wsdl:service name="UserLogonProvider">
    <wsdl:port name="CustomBinding_IUserLogonProvider"
binding="tns:CustomBinding_IUserLogonProvider">
        <soap12:address
location="net.tcp://serverName:6602/Microsoft.WindowsServerSolutions.wssg_user_logon/Microsof
t.WindowsServerSolutions.Users.IUserLogonProvider" />
        <wsa10:EndpointReference>

<wsa10:Address>net.tcp://serverName:6602/Microsoft.WindowsServerSolutions.wssg user logon/Mic
rosoft.WindowsServerSolutions.Users.IUserLogonProvider</wsa10:Address>
        <Identity xmlns="http://schemas.xmlsoap.org/ws/2006/02/addressing/identity">
            <Dns>SERVERNAME</Dns>
        </Identity>
    </wsa10:EndpointReference>
</wsdl:port>
</wsdl:service>
</wsdl:definitions>

```

6.5.1.2 wsdl2

```

<?xml version="1.0" encoding="utf-8"?>
<wsdl:definitions xmlns:wsap="http://schemas.xmlsoap.org/ws/2004/08/addressing/policy"
xmlns:wsa10="http://www.w3.org/2005/08/addressing"
xmlns:tns="http://www.microsoft.com/WindowsServerSolutions/ProviderFramework/Notifications/3/
2010" xmlns:msc="http://schemas.microsoft.com/ws/2005/12/wsdl/contract"
xmlns:soapenc="http://schemas.xmlsoap.org/soap/encoding/"
xmlns:soap="http://schemas.xmlsoap.org/wsdl/soap/"
xmlns:ws="http://schemas.xmlsoap.org/ws/2004/09/policy"
xmlns:wsam="http://www.w3.org/2007/05/addressing/metadata"
xmlns:wsa="http://schemas.xmlsoap.org/ws/2004/08/addressing"
xmlns:wsaw="http://www.w3.org/2006/05/addressing/wsdl"
xmlns:soap12="http://schemas.xmlsoap.org/wsdl/soap12/" xmlns:wsu="http://docs.oasis-
open.org/wss/2004/01/oasis-200401-wss-wssecurity-utility-1.0.xsd"
xmlns:xsd="http://www.w3.org/2001/XMLSchema"
targetNamespace="http://www.microsoft.com/WindowsServerSolutions/ProviderFramework/Notificati
ons/3/2010" xmlns:wsdl="http://schemas.xmlsoap.org/wsdl/">
    <wsdl:types>
        <xsd:schema
targetNamespace="http://www.microsoft.com/WindowsServerSolutions/ProviderFramework/Notificati
ons/3/2010/Imports">
            <xsd:import schemaLocation="" namespace="http://www.microsoft.com/WindowsServerSolutions/ProviderFramework/Notifications/3/
2010" />
            <xsd:import schemaLocation="" namespace="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.Users" />
            <xsd:import schemaLocation="" namespace="http://schemas.microsoft.com/2003/10/Serialization/" />
            <xsd:import schemaLocation="" namespace="http://schemas.microsoft.com/2003/10/Serialization/Arrays" />
            <xsd:import schemaLocation="" namespace="http://schemas.datacontract.org/2004/07/System" />
        </xsd:schema>
    </wsdl:types>
    <wsdl:message name="IUserLogonProvider_LogonUser_InputMessage">
        <wsdl:part name="parameters" element="tns:LogonUser" />
    </wsdl:message>
    <wsdl:message name="IUserLogonProvider_LogonUser_OutputMessage">
        <wsdl:part name="parameters" element="tns:LogonUserResponse" />
    </wsdl:message>
    <wsdl:message name="IUserLogonProvider_LogonUser_UserFaultFault_FaultMessage">
        <wsdl:part
xmlns:q1="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.Users" name="detail" element="q1:UserFault" />
    </wsdl:message>
    <wsdl:message name="IUserLogonProvider_LogonUser_UserExceptionFault_FaultMessage">

```

```

<wsdl:part
xmlns:q2="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.Users"
name="detail" element="q2:UserException" />
</wsdl:message>
<wsdl:message name="IUserLogonProvider_LogonUser_UserExceptionFaultFault_FaultMessage">
<wsdl:part
xmlns:q3="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.Users"
name="detail" element="q3:UserExceptionFault" />
</wsdl:message>
<wsdl:portType name="IUserLogonProvider">
<wsdl:operation name="LogonUser">
<wsdl:input
wsaw:Action="http://www.microsoft.com/WindowsServerSolutions/ProviderFramework/Notifications/
3/2010/IUserLogonProvider/LogonUser" message="tns:IUserLogonProvider_LogonUser_InputMessage"
/>
<wsdl:output
wsaw:Action="http://www.microsoft.com/WindowsServerSolutions/ProviderFramework/Notifications/
3/2010/IUserLogonProvider/LogonUserResponse"
message="tns:IUserLogonProvider LogonUser OutputMessage" />
<wsdl:fault
wsaw:Action="http://www.microsoft.com/WindowsServerSolutions/ProviderFramework/Notifications/
3/2010/IUserLogonProvider/LogonUserUserFaultFault" name="UserFaultFault"
message="tns:IUserLogonProvider LogonUser UserFaultFault FaultMessage" />
<wsdl:fault
wsaw:Action="http://www.microsoft.com/WindowsServerSolutions/ProviderFramework/Notifications/
3/2010/IUserLogonProvider/LogonUserUserExceptionFault" name="UserExceptionFault"
message="tns:IUserLogonProvider_LogonUser_UserExceptionFault_FaultMessage" />
<wsdl:fault
wsaw:Action="http://www.microsoft.com/WindowsServerSolutions/ProviderFramework/Notifications/
3/2010/IUserLogonProvider/LogonUserUserExceptionFaultFault" name="UserExceptionFaultFault"
message="tns:IUserLogonProvider LogonUser UserExceptionFaultFault FaultMessage" />
</wsdl:operation>
</wsdl:portType>
</wsdl:definitions>

```

6.5.1.3 http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.Users

```

<?xml version="1.0" encoding="utf-8"?>
<xss:schema xmlns:ser="http://schemas.microsoft.com/2003/10/Serialization/"
xmlns:tns="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.Users"
elementFormDefault="qualified"
targetNamespace="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.Use
rs" xmlns:xs="http://www.w3.org/2001/XMLSchema">
<xss:import schemaLocation="" namespace="http://schemas.microsoft.com/2003/10/Serialization/Arrays" />
<xss:import schemaLocation="" namespace="http://schemas.microsoft.com/2003/10/Serialization/" />
<xss:import schemaLocation="" namespace="http://schemas.datacontract.org/2004/07/System" />
<xss:complexType name="UserInfo">
<xss:sequence>
<xss:element minOccurs="0" name="FullUserName" nillable="true" type="xs:string" />
<xss:element minOccurs="0" name="PersonalInfo" nillable="true" type="tns:PersonalInfo"
/>
<xss:element minOccurs="0" name="UserName" nillable="true" type="xs:string" />
<xss:element minOccurs="0" name="UserStatus" type="tns:UserStatus" />
<xss:element minOccurs="0" name="Warning" type="tns:UserCustomExceptionCode" />
<xss:element minOccurs="0" name="WindowsAccount" nillable="true" type="xs:string" />
<xss:element minOccurs="0" name="WindowsSID" nillable="true" type="xs:string" />
</xss:sequence>
</xss:complexType>
<xss:element name="UserInfo" nillable="true" type="tns:UserInfo" />
<xss:complexType name="PersonalInfo">
<xss:complexContent mixed="false">
<xss:extension base="tns:UserGroupCommonInfoContract">
<xss:sequence>

```

```

<xs:element xmlns:q1="http://schemas.microsoft.com/2003/10/Serialization/Arrays"
minOccurs="0" name="ContainerGroups" nillable="true" type="q1:ArrayOfguid" />
<xs:element minOccurs="0" name="DisplayName" nillable="true" type="xs:string" />
<xs:element minOccurs="0" name="FirstName" nillable="true" type="xs:string" />
<xs:element minOccurs="0" name="Guid" type="ser:guid" />
<xs:element minOccurs="0" name="IsBuiltIn" type="xs:boolean" />
<xs:element minOccurs="0" name="IsLocalUser" type="xs:boolean" />
<xs:element minOccurs="0" name="IsShowInUI" type="xs:boolean" />
<xs:element minOccurs="0" name="LastName" nillable="true" type="xs:string" />
<xs:element minOccurs="0" name="NetworkAlertAccess" type="tns:RemoteAccessType" />
<xs:element minOccurs="0" name="UserFolder" nillable="true" type="xs:string" />
</xs:sequence>
</xs:extension>
</xs:complexContent>
</xs:complexType>
<xs:element name="PersonalInfo" nillable="true" type="tns:PersonalInfo" />
<xs:complexType name="UserGroupCommonInfoContract">
<xs:sequence>
<xs:element minOccurs="0" name="AccessLevel" type="tns:AccessLevelType" />
<xs:element minOccurs="0" name="ComputerAccess" type="tns:RemoteAccessType" />
<xs:element minOccurs="0" name="ComputerAccessInherited" type="xs:boolean" />
<xs:element minOccurs="0" name="DashboardAccess" type="tns:RemoteAccessType" />
<xs:element minOccurs="0" name="DashboardAccessInherited" type="xs:boolean" />
<xs:element minOccurs="0" name="HomePageLinksAccess" type="tns:RemoteAccessType" />
<xs:element minOccurs="0" name="HomePageLinksAccessInherited" type="xs:boolean" />
<xs:element minOccurs="0" name="MediaAccess" type="tns:RemoteAccessType" />
<xs:element minOccurs="0" name="MediaAccessInherited" type="xs:boolean" />
<xs:element minOccurs="0" name="RemoteAccess" type="tns:RemoteAccessType" />
<xs:element minOccurs="0" name="RemoteAccessInherited" type="xs:boolean" />
<xs:element minOccurs="0" name="ShareAccess" type="tns:RemoteAccessType" />
<xs:element minOccurs="0" name="ShareAccessInherited" type="xs:boolean" />
<xs:element minOccurs="0" name="VpnAccess" type="tns:RemoteAccessType" />
<xs:element minOccurs="0" name="VpnAccessInherited" type="xs:boolean" />
</xs:sequence>
</xs:complexType>
<xs:element name="UserGroupCommonInfoContract" nillable="true"
type="tns:UserGroupCommonInfoContract" />
<xs:simpleType name="AccessLevelType">
<xs:restriction base="xs:string">
<xs:enumeration value="Unknown" />
<xs:enumeration value="Guest" />
<xs:enumeration value="User" />
<xs:enumeration value="Administrator" />
</xs:restriction>
</xs:simpleType>
<xs:element name="AccessLevelType" nillable="true" type="tns:AccessLevelType" />
<xs:simpleType name="RemoteAccessType">
<xs:restriction base="xs:string">
<xs:enumeration value="Unknown" />
<xs:enumeration value="Allowed" />
<xs:enumeration value="NotAllowed" />
</xs:restriction>
</xs:simpleType>
<xs:element name="RemoteAccessType" nillable="true" type="tns:RemoteAccessType" />
<xs:simpleType name="UserStatus">
<xs:restriction base="xs:string">
<xs:enumeration value="Disabled" />
<xs:enumeration value="Enabled" />
<xs:enumeration value="Error" />
</xs:restriction>
</xs:simpleType>
<xs:element name="UserStatus" nillable="true" type="tns:UserStatus" />
<xs:simpleType name="UserCustomExceptionCode">
<xs:restriction base="xs:string">
<xs:enumeration value="Succeeded" />
<xs:enumeration value="WinLogonFailed" />
<xs:enumeration value="UserExists" />
<xs:enumeration value="UserNotExist" />
<xs:enumeration value="ProviderNotAvailable" />

```

```

<xs:enumeration value="AccessDenied" />
<xs:enumeration value="TooManyUsers" />
<xs:enumeration value="CreateUserSharedFolderFailed" />
<xs:enumeration value="Failed" />
<xs:enumeration value="ActiveDirectoryNotAvailable" />
<xs:enumeration value="ModifySecurityGroupMembershipFailed" />
<xs:enumeration value="CannotRevokeInheritedPermission" />
<xs:enumeration value="GroupNotExist" />
<xs:enumeration value="WeakPassword" />
</xs:restriction>
</xs:simpleType>
<xs:element name="UserCustomExceptionCode" nillable="true"
type="tns:UserCustomExceptionCode" />
<xs:complexType name="UserFault">
<xs:sequence>
<xs:element minOccurs="0" name="ExceptionCode" type="xs:int" />
<xs:element minOccurs="0" name="Message" nillable="true" type="xs:string" />
<xs:element minOccurs="0" name="UserCode" type="tns:UserCustomExceptionCode" />
</xs:sequence>
</xs:complexType>
<xs:element name="UserFault" nillable="true" type="tns:UserFault" />
<xs:complexType name="UserException">
<xs:complexContent mixed="false">
<xs:extension xmlns:q2="http://schemas.datacontract.org/2004/07/System"
base="q2:Exception" />
</xs:complexContent>
</xs:complexType>
<xs:element name="UserException" nillable="true" type="tns:UserException" />
<xs:complexType name="UserExceptionFault">
<xs:sequence>
<xs:element minOccurs="0" name="ErrorCode" type="xs:int" />
<xs:element minOccurs="0" name="Message" nillable="true" type="xs:string" />
<xs:element minOccurs="0" name="UserErrorCode" type="tns:UserCustomExceptionCode" />
</xs:sequence>
</xs:complexType>
<xs:element name="UserExceptionFault" nillable="true" type="tns:UserExceptionFault" />
</xs:schema>

```

6.5.1.4 http://schemas.microsoft.com/2003/10/Serialization/Arrays

```

<?xml version="1.0" encoding="utf-8"?>
<xs:schema xmlns:ser="http://schemas.microsoft.com/2003/10/Serialization/"
xmlns:tns="http://schemas.microsoft.com/2003/10/Serialization/Arrays"
elementFormDefault="qualified"
targetNamespace="http://schemas.microsoft.com/2003/10/Serialization/Arrays"
xmlns:xs="http://www.w3.org/2001/XMLSchema">
<xs:import schemaLocation=""
namespace="http://schemas.microsoft.com/2003/10/Serialization/" />
<xs:complexType name="ArrayOfguid">
<xs:sequence>
<xs:element minOccurs="0" maxOccurs="unbounded" name="guid" type="ser:guid" />
</xs:sequence>
</xs:complexType>
<xs:element name="ArrayOfguid" nillable="true" type="tns:ArrayOfguid" />
</xs:schema>

```

6.5.1.5 http://schemas.microsoft.com/2003/10/Serialization

```

<?xml version="1.0" encoding="utf-8"?>
<xs:schema xmlns:tns="http://schemas.microsoft.com/2003/10/Serialization/"
attributeFormDefault="qualified" elementFormDefault="qualified"
targetNamespace="http://schemas.microsoft.com/2003/10/Serialization/"
xmlns:xs="http://www.w3.org/2001/XMLSchema">
<xs:element name="anyType" nillable="true" type="xs:anyType" />
<xs:element name="anyURI" nillable="true" type="xs:anyURI" />

```

```

<xs:element name="base64Binary" nillable="true" type="xs:base64Binary" />
<xs:element name="boolean" nillable="true" type="xs:boolean" />
<xs:element name="byte" nillable="true" type="xs:byte" />
<xs:element name="dateTime" nillable="true" type="xs:dateTime" />
<xs:element name="decimal" nillable="true" type="xs:decimal" />
<xs:element name="double" nillable="true" type="xs:double" />
<xs:element name="float" nillable="true" type="xs:float" />
<xs:element name="int" nillable="true" type="xs:int" />
<xs:element name="long" nillable="true" type="xs:long" />
<xs:element name="QName" nillable="true" type="xs:QName" />
<xs:element name="short" nillable="true" type="xs:short" />
<xs:element name="string" nillable="true" type="xs:string" />
<xs:element name="unsignedByte" nillable="true" type="xs:unsignedByte" />
<xs:element name="unsignedInt" nillable="true" type="xs:unsignedInt" />
<xs:element name="unsignedLong" nillable="true" type="xs:unsignedLong" />
<xs:element name="unsignedShort" nillable="true" type="xs:unsignedShort" />
<xs:element name="char" nillable="true" type="tns:char" />
<xs:simpleType name="char">
    <xs:restriction base="xs:int" />
</xs:simpleType>
<xs:element name="duration" nillable="true" type="tns:duration" />
<xs:simpleType name="duration">
    <xs:restriction base="xs:duration">
        <xs:pattern value="\-?P(\d*D)?(T(\d*M)?(\d*(\.\.\d*)?S)?)?" />
        <xs:minInclusive value="-P10675199DT2H48M5.4775808S" />
        <xs:maxInclusive value="P10675199DT2H48M5.4775807S" />
    </xs:restriction>
</xs:simpleType>
<xs:element name="guid" nillable="true" type="tns:guid" />
<xs:simpleType name="guid">
    <xs:restriction base="xs:string">
        <xs:pattern value="[\da-fA-F]{8}-[\da-fA-F]{4}-[\da-fA-F]{4}-[\da-fA-F]{4}-[\da-fA-F]{12}" />
    </xs:restriction>
</xs:simpleType>
<xs:attribute name="FactoryType" type="xs:QName" />
<xs:attribute name="Id" type="xs:ID" />
<xs:attribute name="Ref" type="xs:IDREF" />
</xs:schema>

```

6.5.1.6 <http://schemas.datacontract.org/2004/07/System>

```

<?xml version="1.0" encoding="utf-8"?>
<xs:schema xmlns:ser="http://schemas.microsoft.com/2003/10/Serialization/"
    xmlns:tns="http://schemas.datacontract.org/2004/07/System" elementFormDefault="qualified"
    targetNamespace="http://schemas.datacontract.org/2004/07/System"
    xmlns:xs="http://www.w3.org/2001/XMLSchema">
    <xs:import schemaLocation=""
        namespace="http://schemas.microsoft.com/2003/10/Serialization/" />
    <xs:complexType name="Exception">
        <xs:sequence>
            <xs:any minOccurs="0" maxOccurs="unbounded" namespace="##local" processContents="skip"
        />
        </xs:sequence>
        <xs:attribute ref="ser:FactoryType" />
    </xs:complexType>
    <xs:element name="Exception" nillable="true" type="tns:Exception" />
</xs:schema>

```

6.5.1.7 <http://www.microsoft.com/WindowsServerSolutions/ProviderFramework/Notifications/3/2010>

```

<?xml version="1.0" encoding="utf-8"?>
<xs:schema
    xmlns:tns="http://www.microsoft.com/WindowsServerSolutions/ProviderFramework/Notifications/3/

```

```

2010" elementFormDefault="qualified"
targetNamespace="http://www.microsoft.com/WindowsServerSolutions/ProviderFramework/Notifications/3/2010" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:import schemaLocation=""/>
  namespace="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.Users" />
  <xs:element name="LogonUser">
    <xs:complexType>
      <xs:sequence>
        <xs:element minOccurs="0" name="userName" nillable="true" type="xs:string" />
        <xs:element minOccurs="0" name="password" nillable="true" type="xs:string" />
        <xs:element minOccurs="0" name="bCleanSession" type="xs:boolean" />
      </xs:sequence>
    </xs:complexType>
  </xs:element>
  <xs:element name="LogonUserResponse">
    <xs:complexType>
      <xs:sequence>
        <xs:element
          xmlns:ql="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.Users"
          minOccurs="0" name="LogonUserResult" nillable="true" type="ql:UserInfo" />
      </xs:sequence>
    </xs:complexType>
  </xs:element>
</xs:schema>

```

6.5.2 IUserChangePasswordProvider

6.5.2.1 wsdl

```

<?xml version="1.0" encoding="utf-8"?>
<wsdl:definitions xmlns:wsap="http://schemas.xmlsoap.org/ws/2004/08/addressing/policy"
  xmlns:wsa10="http://www.w3.org/2005/08/addressing" xmlns:tns="http://tempuri.org/"
  xmlns:msc="http://schemas.microsoft.com/ws/2005/12/wsdl/contract"
  xmlns:soapenc="http://schemas.xmlsoap.org/soap/encoding/"
  xmlns: wsp="http://schemas.xmlsoap.org/ws/2004/09/policy"
  xmlns:i0="http://www.microsoft.com/WindowsServerSolutions/ProviderFramework/Notifications/3/2010"
  xmlns:wsam="http://www.w3.org/2007/05/addressing/metadata"
  xmlns:wsa="http://schemas.xmlsoap.org/ws/2004/08/addressing"
  xmlns:soap12="http://schemas.xmlsoap.org/wsdl/soap12/"
  xmlns:wsaw="http://www.w3.org/2006/05/addressing/wsdl"
  xmlns:soap="http://schemas.xmlsoap.org/wsdl/soap/" xmlns:wsu="http://docs.oasis-open.org/wss/2004/01/oasis-200401-wss-wssecurity-utility-1.0.xsd"
  xmlns:xsd="http://www.w3.org/2001/XMLSchema" name="UserChangePasswordProvider"
  targetNamespace="http://tempuri.org/" xmlns:wsdl="http://schemas.xmlsoap.org/wsdl/">
  <wsp:Policy wsu:Id="CustomBinding_IUserChangePasswordProvider_policy">
    <wsp:ExactlyOne>
      <wsp:All>
        <msb:BinaryEncoding
          xmlns:msb="http://schemas.microsoft.com/ws/2004/mspolicy/netbinary1" />
        <sp:TransportBinding xmlns:sp="http://schemas.xmlsoap.org/ws/2005/07/securitypolicy">
          <wsp:Policy>
            <sp:TransportToken>
              <wsp:Policy>
                <msf:WindowsTransportSecurity
                  xmlns:msf="http://schemas.microsoft.com/ws/2006/05/framing/policy">
                  <msf:ProtectionLevel>EncryptAndSign</msf:ProtectionLevel>
                </msf:WindowsTransportSecurity>
              </wsp:Policy>
            </sp:TransportToken>
            <sp:AlgorithmSuite>
              <wsp:Policy>
                <sp:Basic256 />
              </wsp:Policy>
            </sp:AlgorithmSuite>
            <sp:Layout>
              <wsp:Policy>
                <sp:Strict />
              </wsp:Policy>
            </sp:Layout>
          </wsp:Policy>
        </sp:TransportBinding>
      </wsp:All>
    </wsp:ExactlyOne>
  </wsp:Policy>
</wsdl:definitions>

```

```

        </wsp:Policy>
    </sp:Layout>
</wsp:Policy>
</sp:TransportBinding>
<wsaw:UsingAddressing />
</wsp:All>
</wsp:ExactlyOne>
</wsp:Policy>
<wsdl:import
namespace="http://www.microsoft.com/WindowsServerSolutions/ProviderFramework/Notifications/3/
2010" location="" />
<wsdl:types />
<wsdl:binding name="CustomBinding_IUserChangePasswordProvider"
type="i0:IUserChangePasswordProvider">
    <wsp:PolicyReference URI="#CustomBinding_IUserChangePasswordProvider_policy" />
    <soap12:binding transport="http://schemas.microsoft.com/soap/tcp" />
    <wsdl:operation name="ChangePassword">
        <soap12:operation
soapAction="http://www.microsoft.com/WindowsServerSolutions/ProviderFramework/Notifications/3/
2010/IUserChangePasswordProvider/ChangePassword" style="document" />
        <wsdl:input>
            <soap12:body use="literal" />
        </wsdl:input>
        <wsdl:output>
            <soap12:body use="literal" />
        </wsdl:output>
        <wsdl:fault name="UserFaultFault">
            <soap12:fault use="literal" name="UserFaultFault" namespace="" />
        </wsdl:fault>
        <wsdl:fault name="UserExceptionFault">
            <soap12:fault use="literal" name="UserExceptionFault" namespace="" />
        </wsdl:fault>
        <wsdl:fault name="UserExceptionFaultFault">
            <soap12:fault use="literal" name="UserExceptionFaultFault" namespace="" />
        </wsdl:fault>
        </wsdl:operation>
    </wsdl:binding>
    <wsdl:service name="UserChangePasswordProvider">
        <wsdl:port name="CustomBinding_IUserChangePasswordProvider"
binding="tns:CustomBinding IUserChangePasswordProvider">
            <soap12:address
location="net.tcp://serverName:6602/Microsoft.WindowsServerSolutions.wssg user changepassword
/Microsoft.WindowsServerSolutions.Users.IUserChangePasswordProvider" />
            <wsa10:EndpointReference>

<wsa10:Address>net.tcp://serverName:6602/Microsoft.WindowsServerSolutions.wssg user changepas-
sword/Microsoft.WindowsServerSolutions.Users.IUserChangePasswordProvider</wsa10:Address>
            <Identity xmlns="http://schemas.xmlsoap.org/ws/2006/02/addressing/identity">
                <Spn>host/serverName.domain</Spn>
            </Identity>
        </wsa10:EndpointReference>
    </wsdl:port>
</wsdl:service>
</wsdl:definitions>

```

6.5.2.2 wsdl2

```

<?xml version="1.0" encoding="utf-8"?>
<wsdl:definitions xmlns:wsap="http://schemas.xmlsoap.org/ws/2004/08/addressing/policy"
xmlns:wsa10="http://www.w3.org/2005/08/addressing"
xmlns:tns="http://www.microsoft.com/WindowsServerSolutions/ProviderFramework/Notifications/3/
2010" xmlns:msc="http://schemas.microsoft.com/ws/2005/12/wsdl/contract"
xmlns:soapenc="http://schemas.xmlsoap.org/soap/encoding/"
xmlns:soap="http://schemas.xmlsoap.org/wsdl/soap/"
xmlns:wsp="http://schemas.xmlsoap.org/ws/2004/09/policy"
xmlns:wsam="http://www.w3.org/2007/05/addressing/metadata"
xmlns:wsa="http://schemas.xmlsoap.org/ws/2004/08/addressing"

```

```

xmlns:wsaw="http://www.w3.org/2006/05/addressing/wsdl"
xmlns:soap12="http://schemas.xmlsoap.org/wsdl/soap12/" xmlns:wsu="http://docs.oasis-
open.org/wss/2004/01/oasis-200401-wss-wsseecurity-utility-1.0.xsd"
xmlns:xsd="http://www.w3.org/2001/XMLSchema"
targetNamespace="http://www.microsoft.com/WindowsServerSolutions/ProviderFramework/Notificati-
ons/3/2010" xmlns:wsdl="http://schemas.xmlsoap.org/wsdl/">
    <wsdl:types>
        <xsd:schema
targetNamespace="http://www.microsoft.com/WindowsServerSolutions/ProviderFramework/Notificati-
ons/3/2010/Imports">
            <xsd:import schemaLocation="" namespace="http://www.microsoft.com/WindowsServerSolutions/ProviderFramework/Notifications/3/
2010" />
            <xsd:import schemaLocation="" namespace="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.Users" />
            <xsd:import schemaLocation="" namespace="http://schemas.microsoft.com/2003/10/Serialization/" />
            <xsd:import schemaLocation="" namespace="http://schemas.datacontract.org/2004/07/System" />
        </xsd:schema>
    </wsdl:types>
    <wsdl:message name="IUserChangePasswordProvider ChangePassword InputMessage">
        <wsdl:part name="parameters" element="tns:ChangePassword" />
    </wsdl:message>
    <wsdl:message name="IUserChangePasswordProvider ChangePassword OutputMessage">
        <wsdl:part name="parameters" element="tns:ChangePasswordResponse" />
    </wsdl:message>
    <wsdl:message
name="IUserChangePasswordProvider_ChangePassword_UserFaultFault_FaultMessage">
        <wsdl:part
xmlns:q1="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.Users"
name="detail" element="q1:UserFault" />
    </wsdl:message>
    <wsdl:message
name="IUserChangePasswordProvider_ChangePassword_UserExceptionFault_FaultMessage">
        <wsdl:part
xmlns:q2="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.Users"
name="detail" element="q2:UserException" />
    </wsdl:message>
    <wsdl:message
name="IUserChangePasswordProvider_ChangePassword_UserExceptionFaultFault_FaultMessage">
        <wsdl:part
xmlns:q3="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.Users"
name="detail" element="q3:UserExceptionFault" />
    </wsdl:message>
        <wsdl:portType name="IUserChangePasswordProvider">
            <wsdl:operation name="ChangePassword">
                <wsdl:input
wsaw:Action="http://www.microsoft.com/WindowsServerSolutions/ProviderFramework/Notifications/
3/2010/IUserChangePasswordProvider/ChangePassword"
message="tns:IUserChangePasswordProvider_ChangePassword_InputMessage" />
                <wsdl:output
wsaw:Action="http://www.microsoft.com/WindowsServerSolutions/ProviderFramework/Notifications/
3/2010/IUserChangePasswordProvider/ChangePasswordResponse"
message="tns:IUserChangePasswordProvider_ChangePassword_OutputMessage" />
                <wsdl:fault
wsaw:Action="http://www.microsoft.com/WindowsServerSolutions/ProviderFramework/Notifications/
3/2010/IUserChangePasswordProvider/ChangePasswordUserFaultFault" name="UserFaultFault"
message="tns:IUserChangePasswordProvider_ChangePassword_UserFaultFault_FaultMessage" />
                <wsdl:fault
wsaw:Action="http://www.microsoft.com/WindowsServerSolutions/ProviderFramework/Notifications/
3/2010/IUserChangePasswordProvider/ChangePasswordUserExceptionFault"
name="UserExceptionFault"
message="tns:IUserChangePasswordProvider ChangePassword UserExceptionFault FaultMessage" />
                <wsdl:fault
wsaw:Action="http://www.microsoft.com/WindowsServerSolutions/ProviderFramework/Notifications/
3/2010/IUserChangePasswordProvider/ChangePasswordUserExceptionFaultFault"
name="UserExceptionFaultFault"
message="tns:IUserChangePasswordProvider ChangePassword UserExceptionFaultFault FaultMessage"
/>

```

```

        </wsdl:operation>
    </wsdl:portType>
</wsdl:definitions>
```

6.5.2.3 http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolution.s.Users

```

<?xml version="1.0" encoding="utf-8"?>
<xs:schema
  xmlns:tns="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.Users"
  elementFormDefault="qualified"
  targetNamespace="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.Us
  rs" xmlns:xs="http://www.w3.org/2001/XMLSchema">
    <xs:import schemaLocation="" namespace="http://schemas.datacontract.org/2004/07/System" />
    <xs:complexType name="UserFault">
      <xs:sequence>
        <xs:element minOccurs="0" name="ExceptionCode" type="xs:int" />
        <xs:element minOccurs="0" name="Message" nillable="true" type="xs:string" />
        <xs:element minOccurs="0" name="UserCode" type="tns:UserCustomExceptionCode" />
      </xs:sequence>
    </xs:complexType>
    <xs:element name="UserFault" nillable="true" type="tns:UserFault" />
    <xs:simpleType name="UserCustomExceptionCode">
      <xs:restriction base="xs:string">
        <xs:enumeration value="Succeeded" />
        <xs:enumeration value="WinLogonFailed" />
        <xs:enumeration value="UserExists" />
        <xs:enumeration value="UserNotExist" />
        <xs:enumeration value="ProviderNotAvailable" />
        <xs:enumeration value="AccessDenied" />
        <xs:enumeration value="TooManyUsers" />
        <xs:enumeration value="CreateUserSharedFolderFailed" />
        <xs:enumeration value="Failed" />
        <xs:enumeration value="ActiveDirectoryNotAvailable" />
        <xs:enumeration value="ModifySecurityGroupMembershipFailed" />
        <xs:enumeration value="CannotRevokeInheritedPermission" />
        <xs:enumeration value="GroupNotExist" />
        <xs:enumeration value="WeakPassword" />
      </xs:restriction>
    </xs:simpleType>
    <xs:element name="UserCustomExceptionCode" nillable="true"
      type="tns:UserCustomExceptionCode" />
    <xs:complexType name="UserException">
      <xs:complexContent mixed="false">
        <xs:extension xmlns:q1="http://schemas.datacontract.org/2004/07/System"
          base="q1:Exception" />
      </xs:complexContent>
    </xs:complexType>
    <xs:element name="UserException" nillable="true" type="tns:UserException" />
    <xs:complexType name="UserExceptionFault">
      <xs:sequence>
        <xs:element minOccurs="0" name="ErrorCode" type="xs:int" />
        <xs:element minOccurs="0" name="Message" nillable="true" type="xs:string" />
        <xs:element minOccurs="0" name="UserErrorCode" type="tns:UserCustomExceptionCode" />
      </xs:sequence>
    </xs:complexType>
    <xs:element name="UserExceptionFault" nillable="true" type="tns:UserExceptionFault" />
  </xs:schema>
```

6.5.2.4 http://schemas.microsoft.com/2003/10/Serialization

```

<?xml version="1.0" encoding="utf-8"?>
<xs:schema xmlns:tns="http://schemas.microsoft.com/2003/10/Serialization/"
  attributeFormDefault="qualified" elementFormDefault="qualified"
```

```

targetNamespace="http://schemas.microsoft.com/2003/10/Serialization/"
xmlns:xs="http://www.w3.org/2001/XMLSchema"
  <xs:element name="anyType" nillable="true" type="xs:anyType" />
  <xs:element name="anyURI" nillable="true" type="xs:anyURI" />
  <xs:element name="base64Binary" nillable="true" type="xs:base64Binary" />
  <xs:element name="boolean" nillable="true" type="xs:boolean" />
  <xs:element name="byte" nillable="true" type="xs:byte" />
  <xs:element name="dateTime" nillable="true" type="xs:dateTime" />
  <xs:element name="decimal" nillable="true" type="xs:decimal" />
  <xs:element name="double" nillable="true" type="xs:double" />
  <xs:element name="float" nillable="true" type="xs:float" />
  <xs:element name="int" nillable="true" type="xs:int" />
  <xs:element name="long" nillable="true" type="xs:long" />
  <xs:element name="QName" nillable="true" type="xs:QName" />
  <xs:element name="short" nillable="true" type="xs:short" />
  <xs:element name="string" nillable="true" type="xs:string" />
  <xs:element name="unsignedByte" nillable="true" type="xs:unsignedByte" />
  <xs:element name="unsignedInt" nillable="true" type="xs:unsignedInt" />
  <xs:element name="unsignedLong" nillable="true" type="xs:unsignedLong" />
  <xs:element name="unsignedShort" nillable="true" type="xs:unsignedShort" />
  <xs:element name="char" nillable="true" type="tns:char" />
<xs:simpleType name="char">
  <xs:restriction base="xs:int" />
</xs:simpleType>
<xs:element name="duration" nillable="true" type="tns:duration" />
<xs:simpleType name="duration">
  <xs:restriction base="xs:duration">
    <xs:pattern value="-?P(\d*D)?(T(\d*H)?(\d*M)?(\d*(\.\d*)?S)?)?" />
    <xs:minInclusive value="-P10675199DT2H48M5.4775808S" />
    <xs:maxInclusive value="P10675199DT2H48M5.4775807S" />
  </xs:restriction>
</xs:simpleType>
<xs:element name="guid" nillable="true" type="tns:guid" />
<xs:simpleType name="guid">
  <xs:restriction base="xs:string">
    <xs:pattern value="[\da-fA-F]{8}-[\da-fA-F]{4}-[\da-fA-F]{4}-[\da-fA-F]{4}-[\da-fA-F]{12}" />
  </xs:restriction>
</xs:simpleType>
<xs:attribute name="FactoryType" type="xs:QName" />
<xs:attribute name="Id" type="xs:ID" />
<xs:attribute name="Ref" type="xs:IDREF" />
</xs:schema>

```

6.5.2.5 <http://schemas.datacontract.org/2004/07/System>

```

<?xml version="1.0" encoding="utf-8"?>
<xs:schema xmlns:ser="http://schemas.microsoft.com/2003/10/Serialization/" 
  xmlns:tns="http://schemas.datacontract.org/2004/07/System" elementFormDefault="qualified"
  targetNamespace="http://schemas.datacontract.org/2004/07/System"
  xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:import schemaLocation="" 
    namespace="http://schemas.microsoft.com/2003/10/Serialization/" />
  <xs:complexType name="Exception">
    <xs:sequence>
      <xs:any minOccurs="0" maxOccurs="unbounded" namespace="##local" processContents="skip" />
    </xs:sequence>
    <xs:attribute ref="ser:FactoryType" />
  </xs:complexType>
  <xs:element name="Exception" nillable="true" type="tns:Exception" />
</xs:schema>

```

6.5.2.6 <http://www.microsoft.com/WindowsServerSolutions/ProviderFramework/Notifications/3/2010>

```
<?xml version="1.0" encoding="utf-8"?>
<xss:schema
  xmlns:tns="http://www.microsoft.com/WindowsServerSolutions/ProviderFramework/Notifications/3/2010" elementFormDefault="qualified"
  targetNamespace="http://www.microsoft.com/WindowsServerSolutions/ProviderFramework/Notifications/3/2010" xmlns:xss="http://www.w3.org/2001/XMLSchema">
  <xss:element name="ChangePassword">
    <xss:complexType>
      <xss:sequence>
        <xss:element minOccurs="0" name="userName" nillable="true" type="xs:string" />
        <xss:element minOccurs="0" name="oldPassword" nillable="true" type="xs:string" />
        <xss:element minOccurs="0" name="newPassword" nillable="true" type="xs:string" />
      </xss:sequence>
    </xss:complexType>
  </xss:element>
  <xss:element name="ChangePasswordResponse">
    <xss:complexType>
      <xss:sequence />
    </xss:complexType>
  </xss:element>
</xss:schema>
```

6.5.3 IUserInfoProvider

6.5.3.1 wsdl

```
<?xml version="1.0" encoding="utf-8"?>
<wsdl:definitions xmlns:wsap="http://schemas.xmlsoap.org/ws/2004/08/addressing/policy"
  xmlns:wsa10="http://www.w3.org/2005/08/addressing" xmlns:tns="http://tempuri.org/"
  xmlns:msc="http://schemas.microsoft.com/ws/2005/12/wsdl/contract"
  xmlns:soapenc="http://schemas.xmlsoap.org/soap/encoding/"
  xmlns:wsp="http://schemas.xmlsoap.org/ws/2004/09/policy"
  xmlns:i0="http://www.microsoft.com/WindowsServerSolutions/ProviderFramework/Notifications/3/2010" xmlns:wsam="http://www.w3.org/2007/05/addressing/metadata"
  xmlns:wsa="http://schemas.xmlsoap.org/ws/2004/08/addressing"
  xmlns:soap12="http://schemas.xmlsoap.org/wsdl/soap12/"
  xmlns:wsaw="http://www.w3.org/2006/05/addressing/wsdl"
  xmlns:soap="http://schemas.xmlsoap.org/wsdl/soap/" xmlns:wsu="http://docs.oasis-open.org/wss/2004/01/oasis-200401-wss-wssecurity-utility-1.0.xsd"
  xmlns:xsd="http://www.w3.org/2001/XMLSchema" name="UserInfoProvider"
  targetNamespace="http://tempuri.org/" xmlns:wsdl="http://schemas.xmlsoap.org/wsdl/">
  <wsp:Policy wsu:Id="CustomBinding_IUserInfoProvider_policy">
    <wsp:ExactlyOne>
      <wsp:All>
        <msb:BinaryEncoding
          xmlns:msb="http://schemas.microsoft.com/ws/2004/06/mspolicy/netbinary1" />
        <sp:TransportBinding xmlns:sp="http://schemas.xmlsoap.org/ws/2005/07/securitypolicy">
          <wsp:Policy>
            <sp:TransportToken>
              <wsp:Policy>
                <msf:WindowsTransportSecurity
                  xmlns:msf="http://schemas.microsoft.com/ws/2006/05/framing/policy">
                  <msf:ProtectionLevel>EncryptAndSign</msf:ProtectionLevel>
                </msf:WindowsTransportSecurity>
              </wsp:Policy>
            </sp:TransportToken>
            <sp:AlgorithmSuite>
              <wsp:Policy>
                <sp:Basic256 />
              </wsp:Policy>
            </sp:AlgorithmSuite>
            <sp:Layout>
              <wsp:Policy>
```

```

        <sp:Strict />
    </wsp:Policy>
</sp:Layout>
</wsp:Policy>
</sp:TransportBinding>
<wsaw:UsingAddressing />
</wsp:All>
</wsp:ExactlyOne>
</wsp:Policy>
<wsdl:import
namespace="http://www.microsoft.com/WindowsServerSolutions/ProviderFramework/Notifications/3/
2010" location="" />
<wsdl:types />
<wsdl:binding name="CustomBinding_IUserInfoProvider" type="i0:IUserInfoProvider">
    <wsp:PolicyReference URI="#CustomBinding_IUserInfoProvider_policy" />
    <soap12:binding transport="http://schemas.microsoft.com/soap/tcp" />
    <wsdl:operation name="GetGroups">
        <soap12:operation
soapAction="http://www.microsoft.com/WindowsServerSolutions/ProviderFramework/Notifications/3/
2010/IUserInfoProvider/GetGroups" style="document" />
        <wsdl:input>
            <soap12:body use="literal" />
        </wsdl:input>
    </wsdl:operation>
    <wsdl:operation name="GetWSServerGroups">
        <soap12:operation
soapAction="http://www.microsoft.com/WindowsServerSolutions/ProviderFramework/Notifications/3/
2010/IUserInfoProvider/GetWSServerGroups" style="document" />
        <wsdl:input>
            <soap12:body use="literal" />
        </wsdl:input>
    </wsdl:operation>
    <wsdl:operation name="IsPartOfServerUsers">
        <soap12:operation
soapAction="http://www.microsoft.com/WindowsServerSolutions/ProviderFramework/Notifications/3/
2010/IUserInfoProvider/IsPartOfServerUsers" style="document" />
        <wsdl:input>
            <soap12:body use="literal" />
        </wsdl:input>
    </wsdl:operation>
    <wsdl:operation name="ReturnGroups">
        <soap12:operation
soapAction="http://www.microsoft.com/WindowsServerSolutions/ProviderFramework/Notifications/3/
2010/IUserInfoProvider/ReturnGroups" style="document" />
        <wsdl:output>
            <soap12:body use="literal" />
        </wsdl:output>
    </wsdl:operation>
    <wsdl:operation name="ReturnWSServerGroups">
        <soap12:operation
soapAction="http://www.microsoft.com/WindowsServerSolutions/ProviderFramework/Notifications/3/
2010/IUserInfoProvider/ReturnWSServerGroups" style="document" />
        <wsdl:output>
            <soap12:body use="literal" />
        </wsdl:output>
    </wsdl:operation>
    <wsdl:operation name="ReturnIsPartOfServerUsers">
        <soap12:operation
soapAction="http://www.microsoft.com/WindowsServerSolutions/ProviderFramework/Notifications/3/
2010/IUserInfoProvider/ReturnIsPartOfServerUsers" style="document" />
        <wsdl:output>
            <soap12:body use="literal" />
        </wsdl:output>
    </wsdl:operation>
</wsdl:binding>
<wsdl:service name="UserInfoProvider">
    <wsdl:port name="CustomBinding_IUserInfoProvider"
binding="tns:CustomBinding_IUserInfoProvider">

```

```

<soap12:address
location="net.tcp://serverName:6602/Microsoft.WindowsServerSolutions.wssg_user_info/Microsoft
.WindowsServerSolutions.Users.IUserInfoProvider" />
<wsa10:EndpointReference>

<wsa10:Address>net.tcp://serverName:6602/Microsoft.WindowsServerSolutions.wssg user info/Micr
osoft.WindowsServerSolutions.Users.IUserInfoProvider</wsa10:Address>
<Identity xmlns="http://schemas.xmlsoap.org/ws/2006/02/addressing/identity">
<Spn>host/serverName.domain</Spn>
</Identity>
</wsa10:EndpointReference>
</wsdl:port>
</wsdl:service>
</wsdl:definitions>

```

6.5.3.2 wsdl2

```

<?xml version="1.0" encoding="utf-8"?>
<wsdl:definitions xmlns:wsap="http://schemas.xmlsoap.org/ws/2004/08/addressing/policy"
xmlns:wsa10="http://www.w3.org/2005/08/addressing"
xmlns:tns="http://www.microsoft.com/WindowsServerSolutions/ProviderFramework/Notifications/3/
2010" xmlns:msc="http://schemas.microsoft.com/ws/2005/12/wsdl/contract"
xmlns:soapenc="http://schemas.xmlsoap.org/soap/encoding/"
xmlns:soap="http://schemas.xmlsoap.org/wsdl/soap/"
xmlns:wp="http://schemas.xmlsoap.org/ws/2004/09/policy"
xmlns:wsam="http://www.w3.org/2007/05/addressing/metadata"
xmlns:wsa="http://schemas.xmlsoap.org/ws/2004/08/addressing"
xmlns:wsaw="http://www.w3.org/2006/05/addressing/wsdl"
xmlns:soap12="http://schemas.xmlsoap.org/wsdl/soap12/" xmlns:wsu="http://docs.oasis-
open.org/wss/2004/01/oasis-200401-wss-wssecurity-utility-1.0.xsd"
xmlns:xsd="http://www.w3.org/2001/XMLSchema"
targetNamespace="http://www.microsoft.com/WindowsServerSolutions/ProviderFramework/Notificati
ons/3/2010" xmlns:wsdl="http://schemas.xmlsoap.org/wsdl/">
<wsdl:types>
<xsd:schema
targetNamespace="http://www.microsoft.com/WindowsServerSolutions/ProviderFramework/Notificati
ons/3/2010/Imports">
<xsd:import schemaLocation="" namespace="http://www.microsoft.com/WindowsServerSolutions/ProviderFramework/Notifications/3/
2010" />
<xsd:import schemaLocation="" namespace="http://schemas.microsoft.com/2003/10/Serialization/" />
<xsd:import schemaLocation="" namespace="http://schemas.microsoft.com/2003/10/Serialization/Arrays" />
<xsd:import schemaLocation="" namespace="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.Users" />
</xsd:schema>
</wsdl:types>
<wsdl:message name="IUserInfoProvider_GetGroups_InputMessage">
<wsdl:part name="parameters" element="tns:GetGroups" />
</wsdl:message>
<wsdl:message name="IUserInfoProvider_GetWSServerGroups_InputMessage">
<wsdl:part name="parameters" element="tns:GetWSServerGroups" />
</wsdl:message>
<wsdl:message name="IUserInfoProvider_IsPartOfServerUsers_InputMessage">
<wsdl:part name="parameters" element="tns:IsPartOfServerUsers" />
</wsdl:message>
<wsdl:message name="IUserInfoProvider_ReturnGroups_OutputCallbackMessage">
<wsdl:part name="parameters" element="tns:ReturnGroups" />
</wsdl:message>
<wsdl:message name="IUserInfoProvider_ReturnWSServerGroups_OutputCallbackMessage">
<wsdl:part name="parameters" element="tns:ReturnWSServerGroups" />
</wsdl:message>
<wsdl:message name="IUserInfoProvider_ReturnIsPartOfServerUsers_OutputCallbackMessage">
<wsdl:part name="parameters" element="tns:ReturnIsPartOfServerUsers" />
</wsdl:message>
<wsdl:portType name="IUserInfoProvider">

```

```

<wsdl:operation name="GetGroups">
    <wsdl:input
        wsaw:Action="http://www.microsoft.com/WindowsServerSolutions/ProviderFramework/Notifications/
3/2010/IUserInfoProvider/GetGroups" message="tns:IUserInfoProvider_GetGroups_InputMessage" />
    </wsdl:operation>
    <wsdl:operation name="GetWSServerGroups">
        <wsdl:input
            wsaw:Action="http://www.microsoft.com/WindowsServerSolutions/ProviderFramework/Notifications/
3/2010/IUserInfoProvider/GetWSServerGroups"
            message="tns:IUserInfoProvider_GetWSServerGroups_InputMessage" />
        </wsdl:operation>
        <wsdl:operation name="IsPartOfServerUsers">
            <wsdl:input
                wsaw:Action="http://www.microsoft.com/WindowsServerSolutions/ProviderFramework/Notifications/
3/2010/IUserInfoProvider/IsPartOfServerUsers"
                message="tns:IUserInfoProvider_IsPartOfServerUsers_InputMessage" />
            </wsdl:operation>
            <wsdl:operation name="ReturnGroups">
                <wsdl:output
                    wsaw:Action="http://www.microsoft.com/WindowsServerSolutions/ProviderFramework/Notifications/
3/2010/IUserInfoProvider/ReturnGroups"
                    message="tns:IUserInfoProvider_ReturnGroups_OutputCallbackMessage" />
                </wsdl:operation>
                <wsdl:operation name="ReturnWSServerGroups">
                    <wsdl:output
                        wsaw:Action="http://www.microsoft.com/WindowsServerSolutions/ProviderFramework/Notifications/
3/2010/IUserInfoProvider/ReturnWSServerGroups"
                        message="tns:IUserInfoProvider_ReturnWSServerGroups_OutputCallbackMessage" />
                </wsdl:operation>
                <wsdl:operation name="ReturnIsPartOfServerUsers">
                    <wsdl:output
                        wsaw:Action="http://www.microsoft.com/WindowsServerSolutions/ProviderFramework/Notifications/
3/2010/IUserInfoProvider/ReturnIsPartOfServerUsers"
                        message="tns:IUserInfoProvider_ReturnIsPartOfServerUsers_OutputCallbackMessage" />
                </wsdl:operation>
            </wsdl:portType>
        </wsdl:definitions>

```

6.5.3.3 http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.Users

```

<?xml version="1.0" encoding="utf-8"?>
<xss:schema
    xmlns:tns="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.Users"
    elementFormDefault="qualified"
    targetNamespace="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.Use
rs" xmlns:xs="http://www.w3.org/2001/XMLSchema">
    <xss:complexType name="ReturnClass">
        <xss:sequence>
            <xss:element minOccurs="0" name="NativeError" type="xs:int" />
            <xss:element minOccurs="0" name="UserCode" type="tns:UserCustomExceptionCode" />
        </xss:sequence>
    </xss:complexType>
    <xss:element name="ReturnClass" nillable="true" type="tns:ReturnClass" />
    <xss:simpleType name="UserCustomExceptionCode">
        <xss:restriction base="xs:string">
            <xss:enumeration value="Succeeded" />
            <xss:enumeration value="WinLogonFailed" />
            <xss:enumeration value="UserExists" />
            <xss:enumeration value="UserNotExist" />
            <xss:enumeration value="ProviderNotAvailable" />
            <xss:enumeration value="AccessDenied" />
            <xss:enumeration value="TooManyUsers" />
            <xss:enumeration value="CreateUserSharedFolderFailed" />
            <xss:enumeration value="Failed" />
            <xss:enumeration value="ActiveDirectoryNotAvailable" />
            <xss:enumeration value="ModifySecurityGroupMembershipFailed" />

```

```

<xs:enumeration value="CannotRevokeInheritedPermission" />
<xs:enumeration value="GroupNotExist" />
<xs:enumeration value="WeakPassword" />
</xs:restriction>
</xs:simpleType>
<xs:element name="UserCustomExceptionCode" nillable="true"
type="tns:UserCustomExceptionCode" />
<xs:complexType name="ArrayOfWSServerGroupType">
<xs:sequence>
<xs:element minOccurs="0" maxOccurs="unbounded" name="WSServerGroupType"
type="tns:WSServerGroupType" />
</xs:sequence>
</xs:complexType>
<xs:element name="ArrayOfWSServerGroupType" nillable="true"
type="tns:ArrayOfWSServerGroupType" />
<xs:simpleType name="WSServerGroupType">
<xs:restriction base="xs:string">
<xs:enumeration value="InvalidAccess" />
<xs:enumeration value="RemoteAccess" />
<xs:enumeration value="ShareAccess" />
<xs:enumeration value="ComputerAccess" />
<xs:enumeration value="MediaAccess" />
<xs:enumeration value="AddInAccess" />
<xs:enumeration value="DashboardAccess" />
<xs:enumeration value="HomePageLinks" />
<xs:enumeration value="NetworkAlertAccess" />
<xs:enumeration value="VpnAccess" />
<xs:enumeration value="InvisibleToDashboard" />
</xs:restriction>
</xs:simpleType>
<xs:element name="WSServerGroupType" nillable="true" type="tns:WSServerGroupType" />
</xs:schema>

```

6.5.3.4 <http://schemas.microsoft.com/2003/10/Serialization/Arrays>

```

<?xml version="1.0" encoding="utf-8"?>
<xs:schema xmlns:tns="http://schemas.microsoft.com/2003/10/Serialization/Arrays"
elementFormDefault="qualified"
targetNamespace="http://schemas.microsoft.com/2003/10/Serialization/Arrays"
xmlns:xs="http://www.w3.org/2001/XMLSchema">
<xs:complexType name="ArrayOfstring">
<xs:sequence>
<xs:element minOccurs="0" maxOccurs="unbounded" name="string" nillable="true"
type="xs:string" />
</xs:sequence>
</xs:complexType>
<xs:element name="ArrayOfstring" nillable="true" type="tns:ArrayOfstring" />
</xs:schema>

```

6.5.3.5 <http://schemas.microsoft.com/2003/10/Serialization>

```

<?xml version="1.0" encoding="utf-8"?>
<xs:schema xmlns:tns="http://schemas.microsoft.com/2003/10/Serialization/"
attributeFormDefault="qualified" elementFormDefault="qualified"
targetNamespace="http://schemas.microsoft.com/2003/10/Serialization/"
xmlns:xs="http://www.w3.org/2001/XMLSchema">
<xs:element name="anyType" nillable="true" type="xs:anyType" />
<xs:element name="anyURI" nillable="true" type="xs:anyURI" />
<xs:element name="base64Binary" nillable="true" type="xs:base64Binary" />
<xs:element name="boolean" nillable="true" type="xs:boolean" />
<xs:element name="byte" nillable="true" type="xs:byte" />
<xs:element name="dateTime" nillable="true" type="xs:dateTime" />
<xs:element name="decimal" nillable="true" type="xs:decimal" />
<xs:element name="double" nillable="true" type="xs:double" />
<xs:element name="float" nillable="true" type="xs:float" />

```

```

<xs:element name="int" nillable="true" type="xs:int" />
<xs:element name="long" nillable="true" type="xs:long" />
<xs:element name="QName" nillable="true" type="xs:QName" />
<xs:element name="short" nillable="true" type="xs:short" />
<xs:element name="string" nillable="true" type="xs:string" />
<xs:element name="unsignedByte" nillable="true" type="xs:unsignedByte" />
<xs:element name="unsignedInt" nillable="true" type="xs:unsignedInt" />
<xs:element name="unsignedLong" nillable="true" type="xs:unsignedLong" />
<xs:element name="unsignedShort" nillable="true" type="xs:unsignedShort" />
<xs:element name="char" nillable="true" type="tns:char" />
<xs:simpleType name="char">
    <xs:restriction base="xs:int" />
</xs:simpleType>
<xs:element name="duration" nillable="true" type="tns:duration" />
<xs:simpleType name="duration">
    <xs:restriction base="xs:duration">
        <xs:pattern value="\-?P(\d*D)?(T(\d*H)?(\d*M)?(\d*(\.\d*)?S)?)?" />
        <xs:minInclusive value="-P10675199DT2H48M5.4775808S" />
        <xs:maxInclusive value="P10675199DT2H48M5.4775807S" />
    </xs:restriction>
</xs:simpleType>
<xs:element name="guid" nillable="true" type="tns:guid" />
<xs:simpleType name="guid">
    <xs:restriction base="xs:string">
        <xs:pattern value="[\da-fA-F]{8}-[\da-fA-F]{4}-[\da-fA-F]{4}-[\da-fA-F]{4}-[\da-fA-F]{12}" />
    </xs:restriction>
</xs:simpleType>
<xs:attribute name="FactoryType" type="xs:QName" />
<xs:attribute name="Id" type="xs:ID" />
<xs:attribute name="Ref" type="xs:IDREF" />
</xs:schema>

```

6.5.3.6 <http://www.microsoft.com/WindowsServerSolutions/ProviderFramework/Notifications/3/2010>

```

<?xml version="1.0" encoding="utf-8"?>
<xs:schema
  xmlns:tns="http://www.microsoft.com/WindowsServerSolutions/ProviderFramework/Notifications/3/2010" elementFormDefault="qualified"
  targetNamespace="http://www.microsoft.com/WindowsServerSolutions/ProviderFramework/Notifications/3/2010" xmlns:xs="http://www.w3.org/2001/XMLSchema">
    <xs:import schemaLocation="" namespace="http://schemas.microsoft.com/2003/10/Serialization/Arrays" />
    <xs:import schemaLocation="" namespace="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.Users" />
    <xs:element name="GetGroups">
        <xs:complexType>
            <xs:sequence />
        </xs:complexType>
    </xs:element>
    <xs:element name="GetWSSServerGroups">
        <xs:complexType>
            <xs:sequence />
        </xs:complexType>
    </xs:element>
    <xs:element name="IsPartOfServerUsers">
        <xs:complexType>
            <xs:sequence />
        </xs:complexType>
    </xs:element>
    <xs:element name="ReturnGroups">
        <xs:complexType>
            <xs:sequence>
                <xs:element xmlns:q1="http://schemas.microsoft.com/2003/10/Serialization/Arrays" minOccurs="0" name="groups" nillable="true" type="q1:ArrayOfstring" />
            </xs:sequence>
        </xs:complexType>
    </xs:element>

```

```

<xs:element
  xmlns:q2="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.Users"
  minOccurs="0" name="ret" nillable="true" type="q2:ReturnClass" />
  </xs:sequence>
</xs:complexType>
</xs:element>
<xs:element name="ReturnWSServerGroups">
  <xs:complexType>
    <xs:sequence>
      <xs:element
        xmlns:q3="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.Users"
        minOccurs="0" name="groups" nillable="true" type="q3:ArrayOfWSServerGroupType" />
        <xs:element
      xmlns:q4="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.Users"
      minOccurs="0" name="ret" nillable="true" type="q4:ReturnClass" />
        </xs:sequence>
      </xs:complexType>
    </xs:element>
    <xs:element name="ReturnIsPartOfServerUsers">
      <xs:complexType>
        <xs:sequence>
          <xs:element minOccurs="0" name="bIsPartOfServerUsers" type="xs:boolean" />
          <xs:element
        xmlns:q5="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.Users"
        minOccurs="0" name="ret" nillable="true" type="q5:ReturnClass" />
          </xs:sequence>
        </xs:complexType>
      </xs:element>
    </xs:schema>

```

6.6 Provider Registry Service WSDL

6.6.1 IProviderRegistry

6.6.1.1 wsdl

```

<?xml version="1.0" encoding="utf-8"?>
<wsdl:definitions xmlns:wsap="http://schemas.xmlsoap.org/ws/2004/08/addressing/policy"
  xmlns:wsa10="http://www.w3.org/2005/08/addressing" xmlns:tns="http://tempuri.org/"
  xmlns:msc="http://schemas.microsoft.com/ws/2005/12/wsdl/contract"
  xmlns:soapenc="http://schemas.xmlsoap.org/soap/encoding/"
  xmlns:soap="http://schemas.xmlsoap.org/wsdl/soap/"
  xmlns:wp="http://schemas.xmlsoap.org/ws/2004/09/policy"
  xmlns:wsam="http://www.w3.org/2007/05/addressing/metadata"
  xmlns:wsa="http://schemas.xmlsoap.org/ws/2004/08/addressing"
  xmlns:wsaw="http://www.w3.org/2006/05/addressing/wsdl"
  xmlns:soap12="http://schemas.xmlsoap.org/wsdl/soap12/" xmlns:wsu="http://docs.oasis-
  open.org/wss/2004/01/oasis-200401-wss-wssecurity-utility-1.0.xsd"
  xmlns:xs="http://www.w3.org/2001/XMLSchema" name="ProviderRegistryService"
  targetNamespace="http://tempuri.org/" xmlns:wsdl="http://schemas.xmlsoap.org/wsdl/">
  <wsp:Policy wsu:Id="CustomBinding_IProviderRegistry_policy">
    <wsp:ExactlyOne>
      <wsp:All>
        <msb:BinaryEncoding
          xmlns:msb="http://schemas.microsoft.com/ws/06/2004/mspolicy/netbinary1" />
          <sp:TransportBinding xmlns:sp="http://schemas.xmlsoap.org/ws/2005/07/securitypolicy">
            <wsp:Policy>
              <sp:TransportToken>
                <wsp:Policy>
                  <msf:SslTransportSecurity
                    xmlns:msf="http://schemas.microsoft.com/ws/2006/05/framing/policy" />
                    </wsp:Policy>
                  </sp:TransportToken>
                  <sp:AlgorithmSuite>
                    <wsp:Policy>

```

```

        <sp:Basic256 />
    </wsp:Policy>
</sp:AlgorithmSuite>
<sp:Layout>
    <wsp:Policy>
        <sp:Strict />
    </wsp:Policy>
</sp:Layout>
</wsp:Policy>
</sp:TransportBinding>
<wsaw:UsingAddressing />
</wsp:All>
</wsp:ExactlyOne>
</wsp:Policy>
<wsp:Policy wsu:Id="CustomBinding_IProviderRegistration_policy">
    <wsp:ExactlyOne>
        <wsp:All>
            <msb:BinaryEncoding
                xmlns:msb="http://schemas.microsoft.com/ws/2004/06/mspolicy/netbinary1" />
            <sp:TransportBinding xmlns:sp="http://schemas.xmlsoap.org/ws/2005/07/securitypolicy">
                <wsp:Policy>
                    <sp:TransportToken>
                        <wsp:Policy>
                            <msf:WindowsTransportSecurity
                                xmlns:msf="http://schemas.microsoft.com/ws/2006/05/framing/policy">
                                    <msf:ProtectionLevel>EncryptAndSign</msf:ProtectionLevel>
                                </msf:WindowsTransportSecurity>
                            </wsp:Policy>
                        </sp:TransportToken>
                    <sp:AlgorithmSuite>
                        <wsp:Policy>
                            <sp:Basic256 />
                        </wsp:Policy>
                    </sp:AlgorithmSuite>
                    <sp:Layout>
                        <wsp:Policy>
                            <sp:Strict />
                        </wsp:Policy>
                    </sp:Layout>
                </wsp:Policy>
            </sp:TransportBinding>
            <wsaw:UsingAddressing />
        </wsp:All>
        </wsp:ExactlyOne>
    </wsp:Policy>
</wsdl:types>
<xsd:schema targetNamespace="http://tempuri.org/Imports">
    <xsd:import namespace="http://tempuri.org/" />
    <xsd:import namespace="http://schemas.microsoft.com/2003/10/Serialization/" />
    <xsd:import
        namespace="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.Common.ProviderFramework" />
    <xsd:import
        namespace="http://www.microsoft.com/2010/06/Microsoft.WindowsServerSolutions.Common.ProviderFramework" />
    <xsd:import namespace="http://schemas.datacontract.org/2004/07/System" />
</xsd:schema>
</wsdl:types>
<wsdl:message name="IProviderRegistry_Disconnect_InputMessage">
    <wsdl:part name="parameters" element="tns:Disconnect" />
</wsdl:message>
<wsdl:message name="IProviderRegistry_Query_InputMessage">
    <wsdl:part name="parameters" element="tns:Query" />
</wsdl:message>
<wsdl:message name="IProviderRegistry_Query_OutputMessage">
    <wsdl:part name="parameters" element="tns:QueryResponse" />
</wsdl:message>
<wsdl:message name="IProviderRegistry_QueryAll_InputMessage">
    <wsdl:part name="parameters" element="tns:QueryAll" />

```

```

    </wsdl:message>
<wsdl:message name="IProviderRegistry_QueryAll_OutputMessage">
    <wsdl:part name="parameters" element="tns:QueryAllResponse" />
</wsdl:message>
<wsdl:message name="IProviderRegistry_RequestProviderInfoUpdate_InputMessage">
    <wsdl:part name="parameters" element="tns:RequestProviderInfoUpdate" />
</wsdl:message>
<wsdl:message name="IProviderRegistry_RequestProviderInfoUpdate_OutputMessage">
    <wsdl:part name="parameters" element="tns:RequestProviderInfoUpdateResponse" />
</wsdl:message>
<wsdl:message name="IProviderRegistry_GetVersion_InputMessage">
    <wsdl:part name="parameters" element="tns:GetVersion" />
</wsdl:message>
<wsdl:message name="IProviderRegistry_GetVersion_OutputMessage">
    <wsdl:part name="parameters" element="tns:GetVersionResponse" />
</wsdl:message>
<wsdl:message name="IProviderRegistry_InformOfProviderUpdate_OutputCallbackMessage">
    <wsdl:part name="parameters" element="tns:InformOfProviderUpdate" />
</wsdl:message>
<wsdl:message name="IProviderRegistration_Register_InputMessage">
    <wsdl:part name="parameters" element="tns:Register" />
</wsdl:message>
<wsdl:message name="IProviderRegistration_InformOfProviderUpdate_OutputCallbackMessage">
    <wsdl:part name="parameters" element="tns:InformOfProviderUpdate" />
</wsdl:message>
<wsdl:portType msc:usingSession="true" name="IProviderRegistry">
    <wsdl:operation msc:isInitiating="true" msc:isTerminating="true" name="Disconnect">
        <wsdl:input wsaw:Action="http://tempuri.org/IProviderRegistryConnection/Disconnect"
message="tns:IProviderRegistry Disconnect InputMessage" />
    </wsdl:operation>
    <wsdl:operation msc:isInitiating="true" msc:isTerminating="false" name="Query">
        <wsdl:input wsaw:Action="http://tempuri.org/IProviderRegistry/Query"
message="tns:IProviderRegistry_Query_InputMessage" />
        <wsdl:output wsaw:Action="http://tempuri.org/IProviderRegistry/QueryResponse"
message="tns:IProviderRegistry_Query_OutputMessage" />
    </wsdl:operation>
    <wsdl:operation msc:isInitiating="true" msc:isTerminating="false" name="QueryAll">
        <wsdl:input wsaw:Action="http://tempuri.org/IProviderRegistry/QueryAll"
message="tns:IProviderRegistry_QueryAll_InputMessage" />
        <wsdl:output wsaw:Action="http://tempuri.org/IProviderRegistry/QueryAllResponse"
message="tns:IProviderRegistry_QueryAll_OutputMessage" />
    </wsdl:operation>
    <wsdl:operation msc:isInitiating="true" msc:isTerminating="false"
name="RequestProviderInfoUpdate">
        <wsdl:input
wsaw:Action="http://tempuri.org/IProviderRegistry/RequestProviderInfoUpdate"
message="tns:IProviderRegistry_RequestProviderInfoUpdate_InputMessage" />
        <wsdl:output
wsaw:Action="http://tempuri.org/IProviderRegistry/RequestProviderInfoUpdateResponse"
message="tns:IProviderRegistry_RequestProviderInfoUpdate_OutputMessage" />
    </wsdl:operation>
    <wsdl:operation msc:isInitiating="true" msc:isTerminating="false" name="GetVersion">
        <wsdl:input wsaw:Action="http://tempuri.org/IProviderRegistry/GetVersion"
message="tns:IProviderRegistry_GetVersion_InputMessage" />
        <wsdl:output wsaw:Action="http://tempuri.org/IProviderRegistry/GetVersionResponse"
message="tns:IProviderRegistry_GetVersion_OutputMessage" />
    </wsdl:operation>
    <wsdl:operation msc:isInitiating="true" msc:isTerminating="false"
name="InformOfProviderUpdate">
        <wsdl:output wsaw:Action="http://tempuri.org/IProviderRegistry/InformOfProviderUpdate"
message="tns:IProviderRegistry_InformOfProviderUpdate_OutputCallbackMessage" />
    </wsdl:operation>
</wsdl:portType>
<wsdl:portType msc:usingSession="true" name="IProviderRegistration">
    <wsdl:operation msc:isInitiating="true" msc:isTerminating="true" name="Disconnect">
        <wsdl:input wsaw:Action="http://tempuri.org/IProviderRegistryConnection/Disconnect"
message="tns:IProviderRegistry_Disconnect_InputMessage" />
    </wsdl:operation>
    <wsdl:operation msc:isInitiating="true" msc:isTerminating="false" name="Register">

```

```

<wsdl:input wsaw:Action="http://tempuri.org/IProviderRegistration/Register"
message="tns:IProviderRegistration_Register_InputMessage" />
</wsdl:operation>
<wsdl:operation msc:isInitiating="true" msc:isTerminating="false"
name="InformOfProviderUpdate">
    <wsdl:output
wsaw:Action="http://tempuri.org/IProviderRegistration/InformOfProviderUpdate"
message="tns:IProviderRegistration_InformOfProviderUpdate_OutputCallbackMessage" />
    </wsdl:operation>
</wsdl:portType>
<wsdl:binding name="CustomBinding_IProviderRegistry" type="tns:IProviderRegistry">
    <wsp:PolicyReference URI="#CustomBinding_IProviderRegistry_policy" />
    <soap12:binding transport="http://schemas.microsoft.com/soap/tcp" />
    <wsdl:operation name="Disconnect">
        <soap12:operation
soapAction="http://tempuri.org/IProviderRegistryConnection/Disconnect" style="document" />
        <wsdl:input>
            <soap12:body use="literal" />
        </wsdl:input>
    </wsdl:operation>
    <wsdl:operation name="Query">
        <soap12:operation soapAction="http://tempuri.org/IProviderRegistry/Query"
style="document" />
        <wsdl:input>
            <soap12:body use="literal" />
        </wsdl:input>
        <wsdl:output>
            <soap12:body use="literal" />
        </wsdl:output>
    </wsdl:operation>
    <wsdl:operation name="QueryAll">
        <soap12:operation soapAction="http://tempuri.org/IProviderRegistry/QueryAll"
style="document" />
        <wsdl:input>
            <soap12:body use="literal" />
        </wsdl:input>
        <wsdl:output>
            <soap12:body use="literal" />
        </wsdl:output>
    </wsdl:operation>
    <wsdl:operation name="RequestProviderInfoUpdate">
        <soap12:operation
soapAction="http://tempuri.org/IProviderRegistry/RequestProviderInfoUpdate" style="document"
/>
        <wsdl:input>
            <soap12:body use="literal" />
        </wsdl:input>
        <wsdl:output>
            <soap12:body use="literal" />
        </wsdl:output>
    </wsdl:operation>
    <wsdl:operation name="GetVersion">
        <soap12:operation soapAction="http://tempuri.org/IProviderRegistry/GetVersion"
style="document" />
        <wsdl:input>
            <soap12:body use="literal" />
        </wsdl:input>
        <wsdl:output>
            <soap12:body use="literal" />
        </wsdl:output>
    </wsdl:operation>
    <wsdl:operation name="InformOfProviderUpdate">
        <soap12:operation
soapAction="http://tempuri.org/IProviderRegistry/InformOfProviderUpdate" style="document" />
        <wsdl:output>
            <soap12:body use="literal" />
        </wsdl:output>
    </wsdl:operation>
</wsdl:binding>
```

```

<wsdl:binding name="CustomBinding_IProviderRegistration" type="tns:IProviderRegistration">
    <wsp:PolicyReference URI="#CustomBinding_IProviderRegistration_policy" />
    <soap12:binding transport="http://schemas.microsoft.com/soap/tcp" />
    <wsdl:operation name="Disconnect">
        <soap12:operation
            soapAction="http://tempuri.org/IProviderRegistryConnection/Disconnect" style="document" />
            <wsdl:input>
                <soap12:body use="literal" />
            </wsdl:input>
        </wsdl:operation>
        <wsdl:operation name="Register">
            <soap12:operation soapAction="http://tempuri.org/IProviderRegistration/Register" style="document" />
            <wsdl:input>
                <soap12:body use="literal" />
            </wsdl:input>
        </wsdl:operation>
        <wsdl:operation name="InformOfProviderUpdate">
            <soap12:operation
                soapAction="http://tempuri.org/IProviderRegistration/InformOfProviderUpdate" style="document" />
                <wsdl:output>
                    <soap12:body use="literal" />
                </wsdl:output>
            </wsdl:operation>
        </wsdl:binding>
        <wsdl:service name="ProviderRegistryService">
            <wsdl:port name="CustomBinding_IProviderRegistry" binding="tns:CustomBinding_IProviderRegistry">
                <soap12:address
                    location="net.tcp://serverName:6602//Microsoft.WindowsServerSolutions.Common.ProviderFramework.IProviderRegistry" />
                    <wsa10:EndpointReference>

<wsa10:Address>net.tcp://serverName:6602//Microsoft.WindowsServerSolutions.Common.ProviderFramework.IProviderRegistry</wsa10:Address>
                <Identity xmlns="http://schemas.xmlsoap.org/ws/2006/02/addressingidentity">
                    <Dns>SERVERNAME</Dns>
                </Identity>
                </wsa10:EndpointReference>
            </wsdl:port>
            <wsdl:port name="CustomBinding_IProviderRegistration" binding="tns:CustomBinding_IProviderRegistration">
                <soap12:address
                    location="net.tcp://localhost:65532//Microsoft.WindowsServerSolutions.Common.ProviderFramework.IProviderRegistration" />
                    <wsa10:EndpointReference>

<wsa10:Address>net.tcp://localhost:65532//Microsoft.WindowsServerSolutions.Common.ProviderFramework.IProviderRegistration</wsa10:Address>
                <Identity xmlns="http://schemas.xmlsoap.org/ws/2006/02/addressingidentity">
                    <Spn>host/serverName.domain</Spn>
                </Identity>
                </wsa10:EndpointReference>
            </wsdl:port>
        </wsdl:service>
    </wsdl:definitions>

```

6.6.1.2 http://tempuri.org

```

<?xml version="1.0" encoding="utf-8"?>
<xss:schema xmlns:tns="http://tempuri.org/" elementFormDefault="qualified"
targetNamespace="http://tempuri.org/" xmlns:xs="http://www.w3.org/2001/XMLSchema">
    <xss:import
        namespace="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.Common.ProviderFramework" />

```

```

<xs:import
namespace="http://www.microsoft.com/2010/06/Microsoft.WindowsServerSolutions.Common.ProviderF
ramework" />
<xs:element name="Disconnect">
  <xs:complexType>
    <xs:sequence />
  </xs:complexType>
</xs:element>
<xs:element name="Query">
  <xs:complexType>
    <xs:sequence>
      <xs:element
        xmlns:q1="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.Common.Pro
viderFramework" minOccurs="0" name="specification" nillable="true"
        type="q1:QuerySpecification" />
      <xs:sequence>
    </xs:complexType>
</xs:element>
<xs:element name="QueryResponse">
  <xs:complexType>
    <xs:sequence>
      <xs:element
        xmlns:q2="http://www.microsoft.com/2010/06/Microsoft.WindowsServerSolutions.Common.ProviderFr
amework" minOccurs="0" name="QueryResult" nillable="true" type="q2:ArrayOfProviderInfo" />
      <xs:sequence>
    </xs:complexType>
</xs:element>
<xs:element name="QueryAll">
  <xs:complexType>
    <xs:sequence />
  </xs:complexType>
</xs:element>
<xs:element name="QueryAllResponse">
  <xs:complexType>
    <xs:sequence>
      <xs:element
        xmlns:q3="http://www.microsoft.com/2010/06/Microsoft.WindowsServerSolutions.Common.ProviderFr
amework" minOccurs="0" name="QueryAllResult" nillable="true" type="q3:ArrayOfProviderInfo" />
      <xs:sequence>
    </xs:complexType>
</xs:element>
<xs:element name="RequestProviderInfoUpdate">
  <xs:complexType>
    <xs:sequence>
      <xs:element
        xmlns:q4="http://www.microsoft.com/2010/06/Microsoft.WindowsServerSolutions.Common.ProviderFr
amework" minOccurs="0" name="providersToUpdate" nillable="true" type="q4:ArrayOfProviderInfo"
        />
      <xs:sequence>
    </xs:complexType>
</xs:element>
<xs:element name="RequestProviderInfoUpdateResponse">
  <xs:complexType>
    <xs:sequence>
      <xs:element
        xmlns:q5="http://www.microsoft.com/2010/06/Microsoft.WindowsServerSolutions.Common.ProviderFr
amework" minOccurs="0" name="RequestProviderInfoUpdateResult" nillable="true"
        type="q5:ArrayOfProviderInfo" />
      <xs:sequence>
    </xs:complexType>
</xs:element>
<xs:element name="GetVersion">
  <xs:complexType>
    <xs:sequence />
  </xs:complexType>
</xs:element>
<xs:element name="GetVersionResponse">
  <xs:complexType>
    <xs:sequence>

```

```

        <xs:element minOccurs="0" name="GetVersionResult" nillable="true" type="xs:string" />
    </xs:sequence>
</xs:complexType>
</xs:element>
<xs:element name="InformOfProviderUpdate">
    <xs:complexType>
        <xs:sequence>
            <xs:element
                xmlns:q6="http://www.microsoft.com/2010/06/Microsoft.WindowsServerSolutions.Common.ProviderFr
amework" minOccurs="0" name="info" nillable="true" type="q6:ProviderInfo" />
        </xs:sequence>
    </xs:complexType>
</xs:element>
<xs:element name="Register">
    <xs:complexType>
        <xs:sequence>
            <xs:element
                xmlns:q7="http://www.microsoft.com/2010/06/Microsoft.WindowsServerSolutions.Common.ProviderFr
amework" minOccurs="0" name="info" nillable="true" type="q7:ProviderInfo" />
        </xs:sequence>
    </xs:complexType>
</xs:element>
</xs:schema>

```

6.6.1.3 <http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolution.s.Common.ProviderFramework>

```

<?xml version="1.0" encoding="utf-8"?>
<xs:schema
    xmlns:tns="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.Common.
    ProviderFramework" elementFormDefault="qualified"
    targetNamespace="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.C
    ommon.ProviderFramework" xmlns:xs="http://www.w3.org/2001/XMLSchema">
    <xs:import namespace="http://schemas.datacontract.org/2004/07/System" />
    <xs:complexType name="QuerySpecification">
        <xs:sequence>
            <xs:element minOccurs="0" name="Contract" nillable="true" type="xs:string" />
            <xs:element minOccurs="0" name="ProviderId" nillable="true" type="xs:string" />
            <xs:element minOccurs="0" name="Server" type="xs:boolean" />
        </xs:sequence>
    </xs:complexType>
    <xs:element name="QuerySpecification" nillable="true" type="tns:QuerySpecification" />
    <xs:complexType name="ProviderEndpointBehaviorAttribute">
        <xs:complexContent mixed="false">
            <xs:extension xmlns:q1="http://schemas.datacontract.org/2004/07/System"
                base="q1:Attribute">
                <xs:sequence>
                    <xs:element minOccurs="0" name="AllowedConnectionType"
                        type="tns:ConnectionSetting" />
                    <xs:element minOccurs="0" name="EndpointCredentialType"
                        type="tns:CredentialType" />
                </xs:sequence>
            </xs:extension>
        </xs:complexContent>
    </xs:complexType>
    <xs:element name="ProviderEndpointBehaviorAttribute" nillable="true"
        type="tns:ProviderEndpointBehaviorAttribute" />
    <xs:simpleType name="ConnectionSetting">
        <xs:restriction base="xs:string">
            <xs:enumeration value="AllowLocalAccessOnly" />
            <xs:enumeration value="AllowRemoteAccess" />
        </xs:restriction>
    </xs:simpleType>
    <xs:element name="ConnectionSetting" nillable="true" type="tns:ConnectionSetting" />
    <xs:simpleType name="CredentialType">
        <xs:restriction base="xs:string">

```

```

<xs:enumeration value="User" />
<xs:enumeration value="Machine" />
<xs:enumeration value="None" />
</xs:restriction>
</xs:simpleType>
<xs:element name="CredentialType" nillable="true" type="tns:CredentialType" />
<xs:complexType name="RequiredImpersonationLevelAttribute">
    <xs:complexContent mixed="false">
        <xs:extension xmlns:q2="http://schemas.datacontract.org/2004/07/System"
base="q2:Attribute">
            <xs:sequence>
                <xs:element minOccurs="0" name="Level" type="tns:ImpersonationLevel" />
            </xs:sequence>
        </xs:extension>
    </xs:complexContent>
</xs:complexType>
<xs:element name="RequiredImpersonationLevelAttribute" nillable="true"
type="tns:RequiredImpersonationLevelAttribute" />
<xs:simpleType name="ImpersonationLevel">
    <xs:restriction base="xs:string">
        <xs:enumeration value="Identification" />
        <xs:enumeration value="Impersonation" />
    </xs:restriction>
</xs:simpleType>
<xs:element name="ImpersonationLevel" nillable="true" type="tns:ImpersonationLevel"
/>
</xs:schema>

```

6.6.1.4 http://schemas.microsoft.com/2003/10/Serialization

```

<?xml version="1.0" encoding="utf-8"?>
<xs:schema xmlns:tns="http://schemas.microsoft.com/2003/10/Serialization/"
attributeFormDefault="qualified" elementFormDefault="qualified"
targetNamespace="http://schemas.microsoft.com/2003/10/Serialization/"
xmlns:xs="http://www.w3.org/2001/XMLSchema">
    <xs:element name="anyType" nillable="true" type="xs:anyType" />
    <xs:element name="anyURI" nillable="true" type="xs:anyURI" />
    <xs:element name="base64Binary" nillable="true" type="xs:base64Binary" />
    <xs:element name="boolean" nillable="true" type="xs:boolean" />
    <xs:element name="byte" nillable="true" type="xs:byte" />
    <xs:element name="dateTime" nillable="true" type="xs:dateTime" />
    <xs:element name="decimal" nillable="true" type="xs:decimal" />
    <xs:element name="double" nillable="true" type="xs:double" />
    <xs:element name="float" nillable="true" type="xs:float" />
    <xs:element name="int" nillable="true" type="xs:int" />
    <xs:element name="long" nillable="true" type="xs:long" />
    <xs:element name="QName" nillable="true" type="xs:QName" />
    <xs:element name="short" nillable="true" type="xs:short" />
    <xs:element name="string" nillable="true" type="xs:string" />
    <xs:element name="unsignedByte" nillable="true" type="xs:unsignedByte" />
    <xs:element name="unsignedInt" nillable="true" type="xs:unsignedInt" />
    <xs:element name="unsignedLong" nillable="true" type="xs:unsignedLong" />
    <xs:element name="unsignedShort" nillable="true" type="xs:unsignedShort" />
    <xs:element name="char" nillable="true" type="tns:char" />
    <xs:simpleType name="char">
        <xs:restriction base="xs:int" />
    </xs:simpleType>
    <xs:element name="duration" nillable="true" type="tns:duration" />
    <xs:simpleType name="duration">
        <xs:restriction base="xs:duration">
            <xs:pattern value="-?-P(\d*D)?(T(\d*H)?(\d*M)?(\d*(\.\d*)?S)?)?" />
            <xs:minInclusive value="-P10675199DT2H48M5.4775808S" />
            <xs:maxInclusive value="P10675199DT2H48M5.4775807S" />
        </xs:restriction>
    </xs:simpleType>
    <xs:element name="guid" nillable="true" type="tns:guid" />
    <xs:simpleType name="guid">

```

```

<xs:restriction base="xs:string">
    <xs:pattern value="[\da-fA-F]{8}-[\da-fA-F]{4}-[\da-fA-F]{4}-[\da-fA-F]{4}-[\da-fA-F]{12}" />
</xs:restriction>
</xs:simpleType>
<xs:attribute name="FactoryType" type="xs:QName" />
<xs:attribute name="Id" type="xs:ID" />
<xs:attribute name="Ref" type="xs:IDREF" />
</xs:schema>

```

6.6.1.5 <http://schemas.datacontract.org/2004/07/System>

```

<?xml version="1.0" encoding="utf-8"?>
<xs:schema xmlns:tns="http://schemas.datacontract.org/2004/07/System"
elementFormDefault="qualified"
targetNamespace="http://schemas.datacontract.org/2004/07/System"
xmlns:xs="http://www.w3.org/2001/XMLSchema">
    <xs:complexType name="Attribute">
        <xs:sequence />
    </xs:complexType>
    <xs:element name="Attribute" nillable="true" type="tns:Attribute" />
</xs:schema>

```

6.6.1.6 <http://www.microsoft.com/2010/06/Microsoft.WindowsServerSolutions.Common.ProviderFramework>

```

<?xml version="1.0" encoding="utf-8"?>
<xs:schema
xmlns:tns="http://www.microsoft.com/2010/06/Microsoft.WindowsServerSolutions.Common.ProviderFramework" elementFormDefault="qualified"
targetNamespace="http://www.microsoft.com/2010/06/Microsoft.WindowsServerSolutions.Common.ProviderFramework" xmlns:xs="http://www.w3.org/2001/XMLSchema">
    <xs:import
namespace="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.Common.ProviderFramework" />
    <xs:complexType name="ArrayOfProviderInfo">
        <xs:sequence>
            <xs:element minOccurs="0" maxOccurs="unbounded" name="ProviderInfo" nillable="true" type="tns:ProviderInfo" />
        </xs:sequence>
    </xs:complexType>
    <xs:element name="ArrayOfProviderInfo" nillable="true" type="tns:ArrayOfProviderInfo" />
    <xs:complexType name="ProviderInfo">
        <xs:sequence>
            <xs:element minOccurs="0" name="Address" nillable="true" type="xs:anyURI" />
            <xs:element minOccurs="0" name="Binding" nillable="true" type="xs:string" />
            <xs:element minOccurs="0" name="Connected" type="xs:boolean" />
            <xs:element minOccurs="0" name="Contract" nillable="true" type="xs:string" />
            <xs:element minOccurs="0" name="Host" nillable="true" type="xs:string" />
            <xs:element minOccurs="0" name="Identifier" nillable="true" type="xs:string" />
            <xs:element minOccurs="0" name="IsInProc" type="xs:boolean" />
        </xs:sequence>
    </xs:complexType>
    <xs:element name="ProviderEndpointBehavior" nillable="true" type="q1:ProviderEndpointBehaviorAttribute" />
    <xs:element name="RequiredImpersonationLevel" nillable="true" type="q2:RequiredImpersonationLevelAttribute" />
</xs:schema>

```

6.6.2 INotificationProviderServiceAdminOnly

6.6.2.1 wsdl

```
<?xml version="1.0" encoding="utf-8"?>
<wsdl:definitions xmlns:wsap="http://schemas.xmlsoap.org/ws/2004/08/addressing/policy"
xmlns:wsa10="http://www.w3.org/2005/08/addressing" xmlns:tns="http://tempuri.org/"
xmlns:msc="http://schemas.microsoft.com/ws/2005/12/wsdl/contract"
xmlns:soapenc="http://schemas.xmlsoap.org/soap/encoding/"
xmlns:wsp="http://schemas.xmlsoap.org/ws/2004/09/policy"
xmlns:i0="http://www.microsoft.com/WindowsServerSolutions/ProviderFramework/Notifications/3
/2010" xmlns:wsam="http://www.w3.org/2007/05/addressing/metadata"
xmlns:wsa="http://schemas.xmlsoap.org/ws/2004/08/addressing"
xmlns:soap12="http://schemas.xmlsoap.org/wsdl/soap12/"
xmlns:wsaw="http://www.w3.org/2006/05/addressing/wsdl"
xmlns:soap="http://schemas.xmlsoap.org/wsdl/soap/" xmlns:wsu="http://docs.oasis-
open.org/wss/2004/01/oasis-200401-wss-wssecurity-utility-1.0.xsd"
xmlns:xsd="http://www.w3.org/2001/XMLSchema" name="NotificationProviderServiceAdminOnly"
targetNamespace="http://tempuri.org/" xmlns:wsdl="http://schemas.xmlsoap.org/wsdl/">
    <wsp:Policy wsu:Id="CustomBinding_INotificationProviderServiceAdminOnly_policy">
        <wsp:ExactlyOne>
            <wsp:All>
                <msb:BinaryEncoding
xmlns:msb="http://schemas.microsoft.com/ws/2004/06/2004/mspolicy/netbinary1" />
                <sp:TransportBinding
xmlns:sp="http://schemas.xmlsoap.org/ws/2005/07/securitypolicy">
                    <wsp:Policy>
                        <sp:TransportToken>
                            <wsp:Policy>
                                <msf:WindowsTransportSecurity
xmlns:msf="http://schemas.microsoft.com/ws/2006/05/framing/policy">
                                    <msf:ProtectionLevel>EncryptAndSign</msf:ProtectionLevel>
                                    </msf:WindowsTransportSecurity>
                                </wsp:Policy>
                            </sp:TransportToken>
                            <sp:AlgorithmSuite>
                                <wsp:Policy>
                                    <sp:Basic256 />
                                </wsp:Policy>
                            </sp:AlgorithmSuite>
                            <sp:Layout>
                                <wsp:Policy>
                                    <sp:Strict />
                                </wsp:Policy>
                            </sp:Layout>
                        </wsp:Policy>
                    </sp:TransportBinding>
                    <wsaw:UsingAddressing />
                </wsp:All>
            </wsp:ExactlyOne>
        </wsp:Policy>
        <wsdl:import
namespace="http://www.microsoft.com/WindowsServerSolutions/ProviderFramework/Notifications/
3/2010" location="" />
        <wsdl:types />
        <wsdl:binding name="CustomBinding_INotificationProviderServiceAdminOnly"
type="i0:INotificationProviderServiceAdminOnly">
            <wsp:PolicyReference
URI="#CustomBinding_INotificationProviderServiceAdminOnly_policy" />
            <soap12:binding transport="http://schemas.microsoft.com/soap/tcp" />
            <wsdl:operation name="Connect">
                <soap12:operation
soapAction="http://www.microsoft.com/WindowsServerSolutions/ProviderFramework/Notifications
/3/2010/INotificationProviderService/Connect" style="document" />
                <wsdl:input>
                    <soap12:body use="literal" />
                </wsdl:input>
            </wsdl:operation>
```

```

        <wsdl:operation name="RaiseNotifications">
            <soap12:operation
                soapAction="http://www.microsoft.com/WindowsServerSolutions/ProviderFramework/Notifications
/3/2010/INotificationProviderService/RaiseNotifications" style="document" />
            <wsdl:input>
                <soap12:body use="literal" />
            </wsdl:input>
        </wsdl:operation>
        <wsdl:operation name="ClearNotifications">
            <soap12:operation
                soapAction="http://www.microsoft.com/WindowsServerSolutions/ProviderFramework/Notifications
/3/2010/INotificationProviderService/ClearNotifications" style="document" />
            <wsdl:input>
                <soap12:body use="literal" />
            </wsdl:input>
        </wsdl:operation>
        <wsdl:operation name="RequestNotificationChange">
            <soap12:operation
                soapAction="http://www.microsoft.com/WindowsServerSolutions/ProviderFramework/Notifications
/3/2010/INotificationProviderService/RequestNotificationChange" style="document" />
            <wsdl:input>
                <soap12:body use="literal" />
            </wsdl:input>
        </wsdl:operation>
        <wsdl:operation name="FireEvent">
            <soap12:operation
                soapAction="http://www.microsoft.com/WindowsServerSolutions/ProviderFramework/Notifications
/3/2010/INotificationProviderService/FireEvent" style="document" />
            <wsdl:input>
                <soap12:body use="literal" />
            </wsdl:input>
        </wsdl:operation>
        <wsdl:operation name="AddCategoryFilters">
            <soap12:operation
                soapAction="http://www.microsoft.com/WindowsServerSolutions/ProviderFramework/Notifications
/3/2010/INotificationProviderService/AddCategoryFilters" style="document" />
            <wsdl:input>
                <soap12:body use="literal" />
            </wsdl:input>
        </wsdl:operation>
        <wsdl:operation name="RemoveCategoryFilters">
            <soap12:operation
                soapAction="http://www.microsoft.com/WindowsServerSolutions/ProviderFramework/Notifications
/3/2010/INotificationProviderService/RemoveCategoryFilters" style="document" />
            <wsdl:input>
                <soap12:body use="literal" />
            </wsdl:input>
        </wsdl:operation>
        <wsdl:operation name="Disconnect">
            <soap12:operation
                soapAction="http://www.microsoft.com/WindowsServerSolutions/ProviderFramework/Notifications
/3/2010/INotificationProviderService/Disconnect" style="document" />
            <wsdl:input>
                <soap12:body use="literal" />
            </wsdl:input>
        </wsdl:operation>
        <wsdl:operation name="Connect">
            <soap12:operation
                soapAction="http://www.microsoft.com/WindowsServerSolutions/ProviderFramework/Notifications
/3/2010/INotificationProviderService/Connect" style="document" />
            <wsdl:output>
                <soap12:body use="literal" />
            </wsdl:output>
        </wsdl:operation>
        <wsdl:operation name="RaiseNotifications">
            <soap12:operation
                soapAction="http://www.microsoft.com/WindowsServerSolutions/ProviderFramework/Notifications
/3/2010/INotificationProviderService/RaiseNotifications" style="document" />
            <wsdl:output>

```

```

        <soap12:body use="literal" />
    </wsdl:output>
</wsdl:operation>
<wsdl:operation name="ClearNotifications">
    <soap12:operation
soapAction="http://www.microsoft.com/WindowsServerSolutions/ProviderFramework/Notifications
/3/2010/INotificationProviderService/ClearNotifications" style="document" />
    <wsdl:output>
        <soap12:body use="literal" />
    </wsdl:output>
</wsdl:operation>
<wsdl:operation name="RequestNotificationChange">
    <soap12:operation
soapAction="http://www.microsoft.com/WindowsServerSolutions/ProviderFramework/Notifications
/3/2010/INotificationProviderService/RequestNotificationChange" style="document" />
    <wsdl:output>
        <soap12:body use="literal" />
    </wsdl:output>
</wsdl:operation>
<wsdl:operation name="FireEvent">
    <soap12:operation
soapAction="http://www.microsoft.com/WindowsServerSolutions/ProviderFramework/Notifications
/3/2010/INotificationProviderService/FireEvent" style="document" />
    <wsdl:output>
        <soap12:body use="literal" />
    </wsdl:output>
</wsdl:operation>
<wsdl:operation name="AddCategoryFilters">
    <soap12:operation
soapAction="http://www.microsoft.com/WindowsServerSolutions/ProviderFramework/Notifications
/3/2010/INotificationProviderService/AddCategoryFilters" style="document" />
    <wsdl:output>
        <soap12:body use="literal" />
    </wsdl:output>
</wsdl:operation>
<wsdl:operation name="RemoveCategoryFilters">
    <soap12:operation
soapAction="http://www.microsoft.com/WindowsServerSolutions/ProviderFramework/Notifications
/3/2010/INotificationProviderService/RemoveCategoryFilters" style="document" />
    <wsdl:output>
        <soap12:body use="literal" />
    </wsdl:output>
</wsdl:operation>
<wsdl:operation name="Disconnect">
    <soap12:operation
soapAction="http://www.microsoft.com/WindowsServerSolutions/ProviderFramework/Notifications
/3/2010/INotificationProviderService/Disconnect" style="document" />
    <wsdl:output>
        <soap12:body use="literal" />
    </wsdl:output>
</wsdl:operation>
</wsdl:binding>
<wsdl:service name="NotificationProviderServiceAdminOnly">
    <wsdl:port name="CustomBinding_INotificationProviderServiceAdminOnly"
binding="tns:CustomBinding_INotificationProviderServiceAdminOnly">
        <soap12:address
location="net.tcp://serverName:6602/Microsoft.WindowsServerSolutions.ProviderFramework.Serv
erNotificationProvider/Microsoft.WindowsServerSolutions.Common.ProviderFramework.Internal.I
NotificationProviderServiceAdminOnly" />
        <wsa10:EndpointReference>
            <wsa10:Address>net.tcp://serverName:6602/Microsoft.WindowsServerSolutions.ProviderFramework
.ServerNotificationProvider/Microsoft.WindowsServerSolutions.Common.ProviderFramework.Inter
nal.INotificationProviderServiceAdminOnly</wsa10:Address>
                <Identity xmlns="http://schemas.xmlsoap.org/ws/2006/02/addressingidentity">
                    <Spn>host/serverName.domain</Spn>
                </Identity>
            </wsa10:EndpointReference>
        </wsdl:port>

```

```
</wsdl:service>
</wsdl:definitions>
```

6.6.2.2 wsdl2

```
<?xml version="1.0" encoding="utf-8"?>
<wsdl:definitions xmlns:wsap="http://schemas.xmlsoap.org/ws/2004/08/addressing/policy"
xmlns:wsa10="http://www.w3.org/2005/08/addressing"
xmlns:tns="http://www.microsoft.com/WindowsServerSolutions/ProviderFramework/Notifications/
3/2010" xmlns:msc="http://schemas.microsoft.com/ws/2005/12/wsdl/contract"
xmlns:soapenc="http://schemas.xmlsoap.org/soap/encoding/"
xmlns:soap="http://schemas.xmlsoap.org/wsdl/soap/"
xmlns:wp="http://schemas.xmlsoap.org/ws/2004/09/policy"
xmlns:wsam="http://www.w3.org/2007/05/addressing/metadata"
xmlns:wsa="http://schemas.xmlsoap.org/ws/2004/08/addressing"
xmlns:wsaw="http://www.w3.org/2006/05/addressing/wsdl"
xmlns:soap12="http://schemas.xmlsoap.org/wsdl/soap12/" xmlns:wsu="http://docs.oasis-
open.org/wss/2004/01/oasis-200401-wss-wssecurity-utility-1.0.xsd"
xmlns:xsd="http://www.w3.org/2001/XMLSchema"
targetNamespace="http://www.microsoft.com/WindowsServerSolutions/ProviderFramework/Notifica-
tions/3/2010" xmlns:wsdl="http://schemas.xmlsoap.org/wsdl/">
    <wsdl:types>
        <xsd:schema
targetNamespace="http://www.microsoft.com/WindowsServerSolutions/ProviderFramework/Notifica-
tions/3/2010/Imports">
            <xsd:import schemaLocation="" namespace="http://www.microsoft.com/WindowsServerSolutions/ProviderFramework/Notifica-
tions/3/2010" />
            <xsd:import schemaLocation="" namespace="http://schemas.microsoft.com/2003/10/Serialization/" />
            <xsd:import schemaLocation="" namespace="http://schemas.microsoft.com/2003/10/Serialization/Arrays" />
        </xsd:schema>
    </wsdl:types>
    <wsdl:message name="INotificationProviderServiceAdminOnly_Connect_InputMessage">
        <wsdl:part name="parameters" element="tns:Connect" />
    </wsdl:message>
    <wsdl:message
name="INotificationProviderServiceAdminOnly_RaiseNotifications_InputMessage">
        <wsdl:part name="parameters" element="tns:RaiseNotifications" />
    </wsdl:message>
    <wsdl:message
name="INotificationProviderServiceAdminOnly_ClearNotifications_InputMessage">
        <wsdl:part name="parameters" element="tns:ClearNotifications" />
    </wsdl:message>
    <wsdl:message
name="INotificationProviderServiceAdminOnly_RequestNotificationChange_InputMessage">
        <wsdl:part name="parameters" element="tns:RequestNotificationChange" />
    </wsdl:message>
    <wsdl:message name="INotificationProviderServiceAdminOnly_FireEvent_InputMessage">
        <wsdl:part name="parameters" element="tns:FireEvent" />
    </wsdl:message>
    <wsdl:message
name="INotificationProviderServiceAdminOnly_AddCategoryFilters_InputMessage">
        <wsdl:part name="parameters" element="tns:AddCategoryFilters" />
    </wsdl:message>
    <wsdl:message
name="INotificationProviderServiceAdminOnly_RemoveCategoryFilters_InputMessage">
        <wsdl:part name="parameters" element="tns:RemoveCategoryFilters" />
    </wsdl:message>
    <wsdl:message name="INotificationProviderServiceAdminOnly_Disconnect_InputMessage">
        <wsdl:part name="parameters" element="tns:Disconnect" />
    </wsdl:message>
    <wsdl:portType msc:usingSession="true" name="INotificationProviderServiceAdminOnly">
        <wsdl:operation msc:isInitiating="true" msc:isTerminating="false" name="Connect">
            <wsdl:input
wsaw:Action="http://www.microsoft.com/WindowsServerSolutions/ProviderFramework/Notification
```

```

s/3/2010/INotificationProviderService/Connect"
message="tns:INotificationProviderServiceAdminOnly Connect InputMessage" />
    </wsdl:operation>
        <wsdl:operation msc:isInitiating="false" msc:isTerminating="false"
name="RaiseNotifications">
            <wsdl:input
wsaw:Action="http://www.microsoft.com/WindowsServerSolutions/ProviderFramework/Notification
s/3/2010/INotificationProviderService/RaiseNotifications"
message="tns:INotificationProviderServiceAdminOnly_RaiseNotifications_InputMessage" />
    </wsdl:operation>
        <wsdl:operation msc:isInitiating="false" msc:isTerminating="false"
name="ClearNotifications">
            <wsdl:input
wsaw:Action="http://www.microsoft.com/WindowsServerSolutions/ProviderFramework/Notification
s/3/2010/INotificationProviderService/ClearNotifications"
message="tns:INotificationProviderServiceAdminOnly_ClearNotifications_InputMessage" />
    </wsdl:operation>
        <wsdl:operation msc:isInitiating="false" msc:isTerminating="false"
name="RequestNotificationChange">
            <wsdl:input
wsaw:Action="http://www.microsoft.com/WindowsServerSolutions/ProviderFramework/Notification
s/3/2010/INotificationProviderService/RequestNotificationChange"
message="tns:INotificationProviderServiceAdminOnly_RequestNotificationChange_InputMessage"
/>
    </wsdl:operation>
        <wsdl:operation msc:isInitiating="false" msc:isTerminating="false"
name="FireEvent">
            <wsdl:input
wsaw:Action="http://www.microsoft.com/WindowsServerSolutions/ProviderFramework/Notification
s/3/2010/INotificationProviderService/FireEvent"
message="tns:INotificationProviderServiceAdminOnly_FireEvent_InputMessage" />
    </wsdl:operation>
        <wsdl:operation msc:isInitiating="false" msc:isTerminating="false"
name="AddCategoryFilters">
            <wsdl:input
wsaw:Action="http://www.microsoft.com/WindowsServerSolutions/ProviderFramework/Notification
s/3/2010/INotificationProviderService/AddCategoryFilters"
message="tns:INotificationProviderServiceAdminOnly_AddCategoryFilters_InputMessage" />
    </wsdl:operation>
        <wsdl:operation msc:isInitiating="false" msc:isTerminating="false"
name="RemoveCategoryFilters">
            <wsdl:input
wsaw:Action="http://www.microsoft.com/WindowsServerSolutions/ProviderFramework/Notification
s/3/2010/INotificationProviderService/RemoveCategoryFilters"
message="tns:INotificationProviderServiceAdminOnly_RemoveCategoryFilters_InputMessage" />
    </wsdl:operation>
        <wsdl:operation msc:isInitiating="false" msc:isTerminating="true"
name="Disconnect">
            <wsdl:input
wsaw:Action="http://www.microsoft.com/WindowsServerSolutions/ProviderFramework/Notification
s/3/2010/INotificationProviderService/Disconnect"
message="tns:INotificationProviderServiceAdminOnly_Disconnect_InputMessage" />
    </wsdl:operation>
        <wsdl:operation msc:isInitiating="true" msc:isTerminating="false" name="Connect">
            <wsdl:output
wsaw:Action="http://www.microsoft.com/WindowsServerSolutions/ProviderFramework/Notification
s/3/2010/INotificationProviderService/Connect"
message="tns:INotificationProviderServiceAdminOnly Connect InputMessage" />
    </wsdl:operation>
        <wsdl:operation msc:isInitiating="false" msc:isTerminating="false"
name="RaiseNotifications">
            <wsdl:output
wsaw:Action="http://www.microsoft.com/WindowsServerSolutions/ProviderFramework/Notification
s/3/2010/INotificationProviderService/RaiseNotifications"
message="tns:INotificationProviderServiceAdminOnly_RaiseNotifications_InputMessage" />
    </wsdl:operation>
        <wsdl:operation msc:isInitiating="false" msc:isTerminating="false"
name="ClearNotifications">
            <wsdl:output
wsaw:Action="http://www.microsoft.com/WindowsServerSolutions/ProviderFramework/Notification

```

```

s/3/2010/INotificationProviderService/ClearNotifications"
message="tns:INotificationProviderServiceAdminOnly_ClearNotifications_InputMessage" />
    </wsdl:operation>
        <wsdl:operation msc:isInitiating="false" msc:isTerminating="false">
name="RequestNotificationChange">
    <wsdl:output
wsaw:Action="http://www.microsoft.com/WindowsServerSolutions/ProviderFramework/Notification
s/3/2010/INotificationProviderService/RequestNotificationChange"
message="tns:INotificationProviderServiceAdminOnly_RequestNotificationChange_InputMessage"
/>
    </wsdl:operation>
        <wsdl:operation msc:isInitiating="false" msc:isTerminating="false">
name="FireEvent">
    <wsdl:output
wsaw:Action="http://www.microsoft.com/WindowsServerSolutions/ProviderFramework/Notification
s/3/2010/INotificationProviderService/FireEvent"
message="tns:INotificationProviderServiceAdminOnly_FireEvent_InputMessage" />
    </wsdl:operation>
        <wsdl:operation msc:isInitiating="false" msc:isTerminating="false">
name="AddCategoryFilters">
    <wsdl:output
wsaw:Action="http://www.microsoft.com/WindowsServerSolutions/ProviderFramework/Notification
s/3/2010/INotificationProviderService/AddCategoryFilters"
message="tns:INotificationProviderServiceAdminOnly_AddCategoryFilters_InputMessage" />
    </wsdl:operation>
        <wsdl:operation msc:isInitiating="false" msc:isTerminating="false">
name="RemoveCategoryFilters">
    <wsdl:output
wsaw:Action="http://www.microsoft.com/WindowsServerSolutions/ProviderFramework/Notification
s/3/2010/INotificationProviderService/RemoveCategoryFilters"
message="tns:INotificationProviderServiceAdminOnly_RemoveCategoryFilters_InputMessage" />
    </wsdl:operation>
        <wsdl:operation msc:isInitiating="false" msc:isTerminating="true">
name="Disconnect">
    <wsdl:output
wsaw:Action="http://www.microsoft.com/WindowsServerSolutions/ProviderFramework/Notification
s/3/2010/INotificationProviderService/Disconnect"
message="tns:INotificationProviderServiceAdminOnly_Disconnect_InputMessage" />
    </wsdl:operation>
</wsdl:portType>
</wsdl:definitions>

```

6.6.2.3 http://schemas.microsoft.com/2003/10/Serialization/Arrays

```

<?xml version="1.0" encoding="utf-8"?>
<xss:schema xmlns:tns="http://schemas.microsoft.com/2003/10/Serialization/Arrays"
elementFormDefault="qualified"
targetNamespace="http://schemas.microsoft.com/2003/10/Serialization/Arrays"
xmlns:xss="http://www.w3.org/2001/XMLSchema">
    <xss:complexType name="ArrayOfstring">
        <xss:sequence>
            <xss:element minOccurs="0" maxOccurs="unbounded" name="string" nillable="true"
type="xss:string" />
        </xss:sequence>
    </xss:complexType>
    <xss:element name="ArrayOfstring" nillable="true" type="tns:ArrayOfstring" />
</xss:schema>

```

6.6.2.4 http://schemas.microsoft.com/2003/10/Serialization

```

<?xml version="1.0" encoding="utf-8"?>
<xss:schema xmlns:tns="http://schemas.microsoft.com/2003/10/Serialization/"
attributeFormDefault="qualified" elementFormDefault="qualified"
targetNamespace="http://schemas.microsoft.com/2003/10/Serialization/"
xmlns:xss="http://www.w3.org/2001/XMLSchema">
    <xss:element name="anyType" nillable="true" type="xss:anyType" />

```

```

<xs:element name="anyURI" nillable="true" type="xs:anyURI" />
<xs:element name="base64Binary" nillable="true" type="xs:base64Binary" />
<xs:element name="boolean" nillable="true" type="xs:boolean" />
<xs:element name="byte" nillable="true" type="xs:byte" />
<xs:element name="dateTime" nillable="true" type="xs:dateTime" />
<xs:element name="decimal" nillable="true" type="xs:decimal" />
<xs:element name="double" nillable="true" type="xs:double" />
<xs:element name="float" nillable="true" type="xs:float" />
<xs:element name="int" nillable="true" type="xs:int" />
<xs:element name="long" nillable="true" type="xs:long" />
<xs:element name="QName" nillable="true" type="xs:QName" />
<xs:element name="short" nillable="true" type="xs:short" />
<xs:element name="string" nillable="true" type="xs:string" />
<xs:element name="unsignedByte" nillable="true" type="xs:unsignedByte" />
<xs:element name="unsignedInt" nillable="true" type="xs:unsignedInt" />
<xs:element name="unsignedLong" nillable="true" type="xs:unsignedLong" />
<xs:element name="unsignedShort" nillable="true" type="xs:unsignedShort" />
<xs:element name="char" nillable="true" type="tns:char" />
<xs:simpleType name="char">
    <xs:restriction base="xs:int" />
</xs:simpleType>
<xs:element name="duration" nillable="true" type="tns:duration" />
<xs:simpleType name="duration">
    <xs:restriction base="xs:duration">
        <xs:pattern value="-?P(\d*D)?(T(\d*H)?(\d*M)?(\d*(\.\d*)?S)?)?" />
        <xs:minInclusive value="-P10675199DT2H48M5.4775808S" />
        <xs:maxInclusive value="P10675199DT2H48M5.4775807S" />
    </xs:restriction>
</xs:simpleType>
<xs:element name="guid" nillable="true" type="tns:guid" />
<xs:simpleType name="guid">
    <xs:restriction base="xs:string">
        <xs:pattern value="[\da-fA-F]{8}-[\da-fA-F]{4}-[\da-fA-F]{4}-[\da-fA-F]{4}-[\da-fA-F]{12}" />
    </xs:restriction>
</xs:simpleType>
<xs:attribute name="FactoryType" type="xs:QName" />
<xs:attribute name="Id" type="xs:ID" />
<xs:attribute name="Ref" type="xs:IDREF" />
</xs:schema>

```

6.6.2.5 <http://www.microsoft.com/WindowsServerSolutions/ProviderFramework/Notifications/3/2010>

```

<?xml version="1.0" encoding="utf-8"?>
<xs:schema
xmlns:tns="http://www.microsoft.com/WindowsServerSolutions/ProviderFramework/Notifications/3/2010" elementFormDefault="qualified"
targetNamespace="http://www.microsoft.com/WindowsServerSolutions/ProviderFramework/Notifications/3/2010" xmlns:xs="http://www.w3.org/2001/XMLSchema">
    <xs:import schemaLocation="" namespace="http://schemas.microsoft.com/2003/10/Serialization/Arrays" />
    <xs:element name="Connect">
        <xs:complexType>
            <xs:sequence>
                <xs:element minOccurs="0" name="name" nillable="true" type="xs:string" />
            <xs:element
        xmlns:q1="http://schemas.microsoft.com/2003/10/Serialization/Arrays" minOccurs="0" name="categoryFilter" nillable="true" type="q1:ArrayOfString" />
            </xs:sequence>
        </xs:complexType>
    </xs:element>
    <xs:element name="RaiseNotifications">
        <xs:complexType>
            <xs:sequence>
                <xs:element minOccurs="0" name="newNotificationListChunk" nillable="true" type="xs:base64Binary" />

```

```

        <xs:element minOccurs="0" name="moreData" type="xs:boolean" />
    </xs:sequence>
</xs:complexType>
</xs:element>
<xs:element name="ClearNotifications">
    <xs:complexType>
        <xs:sequence>
            <xs:element minOccurs="0" name="oldNotificationListChunk" nillable="true"
type="xs:base64Binary" />
                <xs:element minOccurs="0" name="moreData" type="xs:boolean" />
            </xs:sequence>
        </xs:complexType>
    </xs:element>
<xs:element name="RequestNotificationChange">
    <xs:complexType>
        <xs:sequence>
            <xs:element minOccurs="0" name="changeRequestChunk" nillable="true"
type="xs:base64Binary" />
                <xs:element minOccurs="0" name="moreData" type="xs:boolean" />
            </xs:sequence>
        </xs:complexType>
    </xs:element>
<xs:element name="FireEvent">
    <xs:complexType>
        <xs:sequence>
            <xs:element minOccurs="0" name="oneShotChunk" nillable="true"
type="xs:base64Binary" />
                <xs:element minOccurs="0" name="moreData" type="xs:boolean" />
            </xs:sequence>
        </xs:complexType>
    </xs:element>
<xs:element name="AddCategoryFilters">
    <xs:complexType>
        <xs:sequence>
            <xs:element
xmlns:q2="http://schemas.microsoft.com/2003/10/Serialization/Arrays" minOccurs="0"
name="addFilters" nillable="true" type="q2:ArrayOfstring" />
                </xs:sequence>
            </xs:complexType>
        </xs:element>
<xs:element name="RemoveCategoryFilters">
    <xs:complexType>
        <xs:sequence>
            <xs:element
xmlns:q3="http://schemas.microsoft.com/2003/10/Serialization/Arrays" minOccurs="0"
name="removeFilters" nillable="true" type="q3:ArrayOfstring" />
                </xs:sequence>
            </xs:complexType>
        </xs:element>
<xs:element name="Disconnect">
    <xs:complexType>
        <xs:sequence />
    </xs:complexType>
</xs:element>
</xs:schema>

```

6.7 Addin Management Service WSDL

6.7.1 wsdl

```

<?xml version="1.0" encoding="utf-8"?>
<wsdl:definitions xmlns:wsap="http://schemas.xmlsoap.org/ws/2004/08/addressing/policy"
xmlns:wsa10="http://www.w3.org/2005/08/addressing" xmlns:tns="http://tempuri.org/"
xmlns:msc="http://schemas.microsoft.com/ws/2005/12/wsdl/contract"
xmlns:soapenc="http://schemas.xmlsoap.org/soap/encoding/"
xmlns:soap="http://schemas.xmlsoap.org/wsdl/soap/"
```

```

xmlns:wsp="http://schemas.xmlsoap.org/ws/2004/09/policy"
xmlns:wsam="http://www.w3.org/2007/05/addressing/metadata"
xmlns:wsa="http://schemas.xmlsoap.org/ws/2004/08/addressing"
xmlns:wsaw="http://www.w3.org/2006/05/addressing/wsdl"
xmlns:soap12="http://schemas.xmlsoap.org/wsdl/soap12/" xmlns:wsu="http://docs.oasis-open.org/wss/2004/01/oasis-200401-wss-wssecurity-utility-1.0.xsd"
xmlns:xsd="http://www.w3.org/2001/XMLSchema" name="AddInMetadataProvider"
targetNamespace="http://tempuri.org/" xmlns:wsdl="http://schemas.xmlsoap.org/wsdl/">
    <wsp:Policy wsu:Id="CustomBinding_IAddInMetadata_policy">
        <wsp:ExactlyOne>
            <wsp:All>
                <msb:BinaryEncoding
xmlns:msb="http://schemas.microsoft.com/ws/2004/06/2004/mspolicy/netbinary1" />
                <sp:TransportBinding
xmlns:sp="http://schemas.xmlsoap.org/ws/2005/07/securitypolicy">
                    <wsp:Policy>
                        <sp:TransportToken>
                            <wsp:Policy>
                                <msf:SslTransportSecurity
xmlns:msf="http://schemas.microsoft.com/ws/2006/05/framing/policy">
                                    <msf:RequireClientCertificate />
                                </msf:SslTransportSecurity>
                            </wsp:Policy>
                        </sp:TransportToken>
                        <sp:AlgorithmSuite>
                            <wsp:Policy>
                                <sp:Basic256 />
                            </wsp:Policy>
                        </sp:AlgorithmSuite>
                        <sp:Layout>
                            <wsp:Policy>
                                <sp:Strict />
                            </wsp:Policy>
                        </sp:Layout>
                    </wsp:Policy>
                </sp:TransportBinding>
                <wsaw:UsingAddressing />
            </wsp:All>
        </wsp:ExactlyOne>
    </wsp:Policy>
    <wsp:Policy wsu:Id="CustomBinding_IAddInMetadataInstall_policy">
        <wsp:ExactlyOne>
            <wsp:All>
                <msb:BinaryEncoding
xmlns:msb="http://schemas.microsoft.com/ws/2004/06/2004/mspolicy/netbinary1" />
                <sp:TransportBinding
xmlns:sp="http://schemas.xmlsoap.org/ws/2005/07/securitypolicy">
                    <wsp:Policy>
                        <sp:TransportToken>
                            <wsp:Policy>
                                <msf:WindowsTransportSecurity
xmlns:msf="http://schemas.microsoft.com/ws/2006/05/framing/policy">
                                    <msf:ProtectionLevel>EncryptAndSign</msf:ProtectionLevel>
                                </msf:WindowsTransportSecurity>
                            </wsp:Policy>
                        </sp:TransportToken>
                        <sp:AlgorithmSuite>
                            <wsp:Policy>
                                <sp:Basic256 />
                            </wsp:Policy>
                        </sp:AlgorithmSuite>
                        <sp:Layout>
                            <wsp:Policy>
                                <sp:Strict />
                            </wsp:Policy>
                        </sp:Layout>
                    </wsp:Policy>
                </sp:TransportBinding>
                <wsaw:UsingAddressing />
            </wsp:All>
        </wsp:ExactlyOne>
    </wsp:Policy>

```

```

        </wsp:ExactlyOne>
    </wsp:Policy>
<wsdl:types>
    <xsd:schema targetNamespace="http://tempuri.org/Imports">
        <xsd:import schemaLocation="" namespace="http://tempuri.org/" />
        <xsd:import schemaLocation="" namespace="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.AddinInfrastructure" />
            <xsd:import schemaLocation="" namespace="http://schemas.microsoft.com/2003/10/Serialization/" />
                <xsd:import schemaLocation="" namespace="http://schemas.datacontract.org/2004/07/System.Collections.ObjectModel" />
                    <xsd:import schemaLocation="" namespace="http://schemas.microsoft.com/2003/10/Serialization/Arrays" />
                        <xsd:import schemaLocation="" namespace="http://schemas.microsoft.com/WindowsServerSolutions/2010/03/Addins" />
                            <xsd:import schemaLocation="" namespace="http://schemas.datacontract.org/2004/07/System" />
                                </xsd:schema>
                            </wsdl:types>
                            <wsdl:message name="IAddInMetadata_GetPackagePath_InputMessage">
                                <wsdl:part name="parameters" element="tns:GetPackagePath" />
                            </wsdl:message>
                            <wsdl:message name="IAddInMetadata_GetPackagePath_OutputMessage">
                                <wsdl:part name="parameters" element="tns:GetPackagePathResponse" />
                            </wsdl:message>
                            <wsdl:message name="IAddInMetadata_GetPackagePath_AddInErrorFault_FaultMessage">
                                <wsdl:part
xmlns:q1="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.AddinInfrastructure" name="detail" element="q1:AddInError" />
                            </wsdl:message>
                            <wsdl:message name="IAddInMetadata_GetAddInIds_InputMessage">
                                <wsdl:part name="parameters" element="tns:GetAddInIds" />
                            </wsdl:message>
                            <wsdl:message name="IAddInMetadata_GetAddInIds_OutputMessage">
                                <wsdl:part name="parameters" element="tns:GetAddInIdsResponse" />
                            </wsdl:message>
                            <wsdl:message name="IAddInMetadata_GetAddInIds_AddInErrorFault_FaultMessage">
                                <wsdl:part
xmlns:q2="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.AddinInfrastructure" name="detail" element="q2:AddInError" />
                            </wsdl:message>
                            <wsdl:message name="IAddInMetadata_GetAddInInformation_InputMessage">
                                <wsdl:part name="parameters" element="tns:GetAddInInformation" />
                            </wsdl:message>
                            <wsdl:message name="IAddInMetadata_GetAddInInformation_OutputMessage">
                                <wsdl:part name="parameters" element="tns:GetAddInInformationResponse" />
                            </wsdl:message>
                            <wsdl:message
name="IAddInMetadata_GetAddInInformation_AddInErrorFault_FaultMessage">
                                <wsdl:part
xmlns:q3="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.AddinInfrastructure" name="detail" element="q3:AddInError" />
                            </wsdl:message>
                            <wsdl:message name="IAddInMetadata_RegisterForChanges_InputMessage">
                                <wsdl:part name="parameters" element="tns:RegisterForChanges" />
                            </wsdl:message>
                            <wsdl:message name="IAddInMetadata_RegisterForChanges_OutputMessage">
                                <wsdl:part name="parameters" element="tns:RegisterForChangesResponse" />
                            </wsdl:message>
                            <wsdl:message name="IAddInMetadata_OperationInProgress_InputMessage">
                                <wsdl:part name="parameters" element="tns:OperationInProgress" />
                            </wsdl:message>
                            <wsdl:message name="IAddInMetadata_OperationInProgress_OutputMessage">
                                <wsdl:part name="parameters" element="tns:OperationInProgressResponse" />
                            </wsdl:message>
                            <wsdl:message
name="IAddInMetadata_OperationInProgress_AddInErrorFault_FaultMessage">

```

```

<wsdl:part
xmlns:q4="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.AddinInfrastructure" name="detail" element="q4:AddInError" />
</wsdl:message>
<wsdl:message name="IAddInMetadata_ChangeOccured_OutputCallbackMessage">
<wsdl:part name="parameters" element="tns:ChangeOccured" />
</wsdl:message>
<wsdl:message name="IAddInMetadataInstall_CheckCredentials_InputMessage">
<wsdl:part name="parameters" element="tns:CheckCredentials" />
</wsdl:message>
<wsdl:message name="IAddInMetadataInstall_CheckCredentials_OutputMessage">
<wsdl:part name="parameters" element="tns:CheckCredentialsResponse" />
</wsdl:message>
<wsdl:message
name="IAddInMetadataInstall_CheckCredentials_ErrorFault_FaultMessage">
<wsdl:part
xmlns:q8="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.AddinInfrastructure" name="detail" element="q8:AddInError" />
</wsdl:message>
<wsdl:message name="IAddInMetadataInstall_InstallAddIn_InputMessage">
<wsdl:part name="parameters" element="tns:InstallAddIn" />
</wsdl:message>
<wsdl:message name="IAddInMetadataInstall_DownloadInstallAddIn_InputMessage">
<wsdl:part name="parameters" element="tns:DownloadInstallAddIn" />
</wsdl:message>
<wsdl:message name="IAddInMetadataInstall_UninstallAddIn_InputMessage">
<wsdl:part name="parameters" element="tns:UninstallAddIn" />
</wsdl:message>
<wsdl:message name="IAddInMetadataInstall_CancelOperation_InputMessage">
<wsdl:part name="parameters" element="tns:CancelOperation" />
</wsdl:message>
<wsdl:message name="IAddInMetadataInstall_StartUploadAddinFile_InputMessage">
<wsdl:part name="parameters" element="tns:StartUploadAddinFile" />
</wsdl:message>
<wsdl:message name="IAddInMetadataInstall_StartUploadAddinFile_ErrorFault_FaultMessage">
<wsdl:part
xmlns:q9="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.AddinInfrastructure" name="detail" element="q9:AddInError" />
</wsdl:message>
<wsdl:message name="IAddInMetadataInstall_UploadAddinFile_InputMessage">
<wsdl:part name="parameters" element="tns:UploadAddinFile" />
</wsdl:message>
<wsdl:message name="IAddInMetadataInstall_UploadAddinFile_ErrorFault_FaultMessage">
<wsdl:part
xmlns:q10="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.AddinInfrastructure" name="detail" element="q10:AddInError" />
</wsdl:message>
<wsdl:message name="IAddInMetadataInstall_EndUploadAddinFile_InputMessage">
<wsdl:part name="parameters" element="tns:EndUploadAddinFile" />
</wsdl:message>
<wsdl:message name="IAddInMetadataInstall_EndUploadAddinFile_ErrorFault_FaultMessage">
<wsdl:part
xmlns:q11="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.AddinInfrastructure" name="detail" element="q11:AddInError" />
</wsdl:message>
<wsdl:message name="IAddInMetadataInstall_ProgressChanged_OutputCallbackMessage">
<wsdl:part name="parameters" element="tns:ProgressChanged" />

```

```

</wsdl:message>
<wsdl:message name="IAddInMetadataInstall_ErrorOccured_OutputCallbackMessage">
    <wsdl:part name="parameters" element="tns:ErrorOccured" />
</wsdl:message>
<wsdl:message name="IAddInMetadataInstall_RebootRequired_OutputCallbackMessage">
    <wsdl:part name="parameters" element="tns:RebootRequired" />
</wsdl:message>
<wsdl:message name="IAddInMetadataInstall_RestartDashboardRequired_OutputCallbackMessage">
    <wsdl:part name="parameters" element="tns:RestartDashboardRequired" />
</wsdl:message>
<wsdl:portType name="IAddInMetadata">
    <wsdl:operation name="GetPackagePath">
        <wsdl:input wsaw:Action="http://tempuri.org/IAddInMetadata/GetPackagePath" message="tns:IAddInMetadata_GetPackagePath_InputMessage" />
        <wsdl:output wsaw:Action="http://tempuri.org/IAddInMetadata/GetPackagePathResponse" message="tns:IAddInMetadata_GetPackagePath_OutputMessage" />
        <wsdl:fault wsaw:Action="http://tempuri.org/IAddInMetadata/GetPackagePathAddInErrorFault" name="AddInErrorFault" message="tns:IAddInMetadata_GetPackagePath_AddInErrorFault_FaultMessage" />
    </wsdl:operation>
    <wsdl:operation name="GetAddInIds">
        <wsdl:input wsaw:Action="http://tempuri.org/IAddInMetadata/GetAddInIds" message="tns:IAddInMetadata_GetAddInIds_InputMessage" />
        <wsdl:output wsaw:Action="http://tempuri.org/IAddInMetadata/GetAddInIdsResponse" message="tns:IAddInMetadata_GetAddInIds_OutputMessage" />
        <wsdl:fault wsaw:Action="http://tempuri.org/IAddInMetadata/GetAddInIdsAddInErrorFault" name="AddInErrorFault" message="tns:IAddInMetadata_GetAddInIds_AddInErrorFault_FaultMessage" />
    </wsdl:operation>
    <wsdl:operation name="GetAddInInformation">
        <wsdl:input wsaw:Action="http://tempuri.org/IAddInMetadata/GetAddInInformation" message="tns:IAddInMetadata_GetAddInInformation_InputMessage" />
        <wsdl:output wsaw:Action="http://tempuri.org/IAddInMetadata/GetAddInInformationResponse" message="tns:IAddInMetadata_GetAddInInformation_OutputMessage" />
        <wsdl:fault wsaw:Action="http://tempuri.org/IAddInMetadata/GetAddInInformationAddInErrorFault" name="AddInErrorFault" message="tns:IAddInMetadata_GetAddInInformation_AddInErrorFault_FaultMessage" />
    </wsdl:operation>
    <wsdl:operation name="RegisterForChanges">
        <wsdl:input wsaw:Action="http://tempuri.org/IAddInMetadata/RegisterForChanges" message="tns:IAddInMetadata_RegisterForChanges_InputMessage" />
        <wsdl:output wsaw:Action="http://tempuri.org/IAddInMetadata/RegisterForChangesResponse" message="tns:IAddInMetadata_RegisterForChanges_OutputMessage" />
        <wsdl:fault wsaw:Action="http://tempuri.org/IAddInMetadata/OperationInProgress" name="AddInErrorFault" message="tns:IAddInMetadata_OperationInProgress_InputMessage" />
        <wsdl:output wsaw:Action="http://tempuri.org/IAddInMetadata/OperationInProgressResponse" message="tns:IAddInMetadata_OperationInProgress_OutputMessage" />
        <wsdl:fault wsaw:Action="http://tempuri.org/IAddInMetadata/OperationInProgressAddInErrorFault" name="AddInErrorFault" message="tns:IAddInMetadata_OperationInProgress_AddInErrorFault_FaultMessage" />
    </wsdl:operation>
    <wsdl:operation name="ChangeOccured">
        <wsdl:output wsaw:Action="http://tempuri.org/IAddInMetadata/ChangeOccured" message="tns:IAddInMetadata_ChangeOccured_OutputCallbackMessage" />
    </wsdl:operation>
</wsdl:portType>
<wsdl:portType name="IAddInMetadataInstall">
    <wsdl:operation name="CheckCredentials">

```

```

        <wsdl:input
wsaw:Action="http://tempuri.org/IAddInMetadataInstall/CheckCredentials"
message="tns:IAddInMetadataInstall_CheckCredentials_InputMessage" />
        <wsdl:output
wsaw:Action="http://tempuri.org/IAddInMetadataInstall/CheckCredentialsResponse"
message="tns:IAddInMetadataInstall CheckCredentials OutputMessage" />
        <wsdl:fault
wsaw:Action="http://tempuri.org/IAddInMetadataInstall/CheckCredentialsAddInErrorFault"
name="AddInErrorFault"
message="tns:IAddInMetadataInstall_CheckCredentials_AddInErrorFault_FaultMessage" />
    </wsdl:operation>
    <wsdl:operation name="InstallAddIn">
        <wsdl:input wsaw:Action="http://tempuri.org/IAddInMetadataInstall/InstallAddIn"
message="tns:IAddInMetadataInstall_InstallAddIn_InputMessage" />
    </wsdl:operation>
    <wsdl:operation name="DownloadInstallAddIn">
        <wsdl:input
wsaw:Action="http://tempuri.org/IAddInMetadataInstall/DownloadInstallAddIn"
message="tns:IAddInMetadataInstall DownloadInstallAddIn InputMessage" />
    </wsdl:operation>
    <wsdl:operation name="UninstallAddIn">
        <wsdl:input
wsaw:Action="http://tempuri.org/IAddInMetadataInstall/UninstallAddIn"
message="tns:IAddInMetadataInstall_UninstallAddIn_InputMessage" />
    </wsdl:operation>
    <wsdl:operation name="CancelOperation">
        <wsdl:input
wsaw:Action="http://tempuri.org/IAddInMetadataInstall/CancelOperation"
message="tns:IAddInMetadataInstall CancelOperation InputMessage" />
    </wsdl:operation>
    <wsdl:operation name="StartUploadAddinFile">
        <wsdl:input
wsaw:Action="http://tempuri.org/IAddInMetadataInstall/StartUploadAddinFile"
message="tns:IAddInMetadataInstall StartUploadAddinFile InputMessage" />
        <wsdl:output
wsaw:Action="http://tempuri.org/IAddInMetadataInstall/StartUploadAddinFileResponse"
message="tns:IAddInMetadataInstall_StartUploadAddinFile_OutputMessage" />
    <wsdl:fault
wsaw:Action="http://tempuri.org/IAddInMetadataInstall/StartUploadAddinFileAddInErrorFault"
name="AddInErrorFault"
message="tns:IAddInMetadataInstall_StartUploadAddinFile_AddInErrorFault_FaultMessage" />
    </wsdl:operation>
    <wsdl:operation name="UploadAddinFile">
        <wsdl:input
wsaw:Action="http://tempuri.org/IAddInMetadataInstall/UploadAddinFile"
message="tns:IAddInMetadataInstall UploadAddinFile InputMessage" />
        <wsdl:output
wsaw:Action="http://tempuri.org/IAddInMetadataInstall/UploadAddinFileResponse"
message="tns:IAddInMetadataInstall_UploadAddinFile_OutputMessage" />
    <wsdl:fault
wsaw:Action="http://tempuri.org/IAddInMetadataInstall/UploadAddinFileAddInErrorFault"
name="AddInErrorFault"
message="tns:IAddInMetadataInstall_UploadAddinFile_AddInErrorFault_FaultMessage" />
    </wsdl:operation>
    <wsdl:operation name="EndUploadAddinFile">
        <wsdl:input
wsaw:Action="http://tempuri.org/IAddInMetadataInstall/EndUploadAddinFile"
message="tns:IAddInMetadataInstall_EndUploadAddinFile_InputMessage" />
        <wsdl:output
wsaw:Action="http://tempuri.org/IAddInMetadataInstall/EndUploadAddinFileResponse"
message="tns:IAddInMetadataInstall_EndUploadAddinFile_OutputMessage" />
    <wsdl:fault
wsaw:Action="http://tempuri.org/IAddInMetadataInstall/EndUploadAddinFileAddInErrorFault"
name="AddInErrorFault"
message="tns:IAddInMetadataInstall_EndUploadAddinFile_AddInErrorFault_FaultMessage" />
    </wsdl:operation>
    <wsdl:operation name="ProgressChanged">

```

```

        <wsdl:output
wsaw:Action="http://tempuri.org/IAddInMetadataInstall/ProgressChanged"
message="tns:IAddInMetadataInstall_ProgressChanged_OutputCallbackMessage" />
    </wsdl:operation>
    <wsdl:operation name="ErrorOccured">
        <wsdl:output wsaw:Action="http://tempuri.org/IAddInMetadataInstall/ErrorOccured"
message="tns:IAddInMetadataInstall_ErrorOccured_OutputCallbackMessage" />
    </wsdl:operation>
    <wsdl:operation name="RebootRequired">
        <wsdl:output
wsaw:Action="http://tempuri.org/IAddInMetadataInstall/RebootRequired"
message="tns:IAddInMetadataInstall_RebootRequired_OutputCallbackMessage" />
        </wsdl:operation>
        <wsdl:operation name="RestartDashboardRequired">
            <wsdl:output
wsaw:Action="http://tempuri.org/IAddInMetadataInstall/RestartDashboardRequired"
message="tns:IAddInMetadataInstall_RestartDashboardRequired_OutputCallbackMessage" />
            </wsdl:operation>
        </wsdl:portType>
<wsdl:binding name="CustomBinding_IAddInMetadata" type="tns:IAddInMetadata">
    <wsp:PolicyReference URI="#CustomBinding_IAddInMetadata_policy" />
    <soap12:binding transport="http://schemas.microsoft.com/soap/tcp" />
    <wsdl:operation name="GetPackagePath">
        <soap12:operation soapAction="http://tempuri.org/IAddInMetadata/GetPackagePath"
style="document" />
        <wsdl:input>
            <soap12:body use="literal" />
        </wsdl:input>
        <wsdl:output>
            <soap12:body use="literal" />
        </wsdl:output>
        <wsdl:fault name="AddInErrorFault">
            <soap12:fault use="literal" name="AddInErrorFault" namespace="" />
        </wsdl:fault>
    </wsdl:operation>
    <wsdl:operation name="GetAddInIds">
        <soap12:operation soapAction="http://tempuri.org/IAddInMetadata/GetAddInIds"
style="document" />
        <wsdl:input>
            <soap12:body use="literal" />
        </wsdl:input>
        <wsdl:output>
            <soap12:body use="literal" />
        </wsdl:output>
        <wsdl:fault name="AddInErrorFault">
            <soap12:fault use="literal" name="AddInErrorFault" namespace="" />
        </wsdl:fault>
    </wsdl:operation>
    <wsdl:operation name="GetAddInInformation">
        <soap12:operation
soapAction="http://tempuri.org/IAddInMetadata/GetAddInInformation" style="document" />
        <wsdl:input>
            <soap12:body use="literal" />
        </wsdl:input>
        <wsdl:output>
            <soap12:body use="literal" />
        </wsdl:output>
        <wsdl:fault name="AddInErrorFault">
            <soap12:fault use="literal" name="AddInErrorFault" namespace="" />
        </wsdl:fault>
    </wsdl:operation>
    <wsdl:operation name="RegisterForChanges">
        <soap12:operation
soapAction="http://tempuri.org/IAddInMetadata/RegisterForChanges" style="document" />
        <wsdl:input>
            <soap12:body use="literal" />
        </wsdl:input>
        <wsdl:output>
            <soap12:body use="literal" />
        </wsdl:output>
    
```

```

        </wsdl:output>
    </wsdl:operation>
    <wsdl:operation name="OperationInProgress">
        <soap12:operation
            soapAction="http://tempuri.org/IAddInMetadata/OperationInProgress" style="document" />
            <wsdl:input>
                <soap12:body use="literal" />
            </wsdl:input>
            <wsdl:output>
                <soap12:body use="literal" />
            </wsdl:output>
            <wsdl:fault name="AddInErrorFault">
                <soap12:fault use="literal" name="AddInErrorFault" namespace="" />
            </wsdl:fault>
        </wsdl:operation>
        <wsdl:operation name="ChangeOccured">
            <soap12:operation soapAction="http://tempuri.org/IAddInMetadata/ChangeOccured" style="document" />
            <wsdl:output>
                <soap12:body use="literal" />
            </wsdl:output>
            </wsdl:operation>
        </wsdl:binding>
        <wsdl:binding name="CustomBinding_IAddInMetadataInstall"
type="tns:IAddInMetadataInstall">
            <wsp:PolicyReference URI="#CustomBinding_IAddInMetadataInstall_policy" />
            <soap12:binding transport="http://schemas.microsoft.com/soap/tcp" />
            <wsdl:operation name="CheckCredentials">
                <soap12:operation
                    soapAction="http://tempuri.org/IAddInMetadataInstall/CheckCredentials" style="document" />
                <wsdl:input>
                    <soap12:body use="literal" />
                </wsdl:input>
                <wsdl:output>
                    <soap12:body use="literal" />
                </wsdl:output>
                <wsdl:fault name="AddInErrorFault">
                    <soap12:fault use="literal" name="AddInErrorFault" namespace="" />
                </wsdl:fault>
            </wsdl:operation>
            <wsdl:operation name="InstallAddIn">
                <soap12:operation
                    soapAction="http://tempuri.org/IAddInMetadataInstall/InstallAddIn" style="document" />
                <wsdl:input>
                    <soap12:body use="literal" />
                </wsdl:input>
                </wsdl:operation>
                <wsdl:operation name="DownloadInstallAddIn">
                    <soap12:operation
                        soapAction="http://tempuri.org/IAddInMetadataInstall/DownloadInstallAddIn" style="document" />
                    <wsdl:input>
                        <soap12:body use="literal" />
                    </wsdl:input>
                    </wsdl:operation>
                    <wsdl:operation name="UninstallAddIn">
                        <soap12:operation
                            soapAction="http://tempuri.org/IAddInMetadataInstall/UninstallAddIn" style="document" />
                        <wsdl:input>
                            <soap12:body use="literal" />
                        </wsdl:input>
                    </wsdl:operation>
                    <wsdl:operation name="CancelOperation">
                        <soap12:operation
                            soapAction="http://tempuri.org/IAddInMetadataInstall/CancelOperation" style="document" />
                        <wsdl:input>
                            <soap12:body use="literal" />
                        </wsdl:input>
                    </wsdl:operation>
                </wsdl:operation>
            </wsdl:operation>
        </wsdl:binding>
    </wsdl:operation>

```

```

        <wsdl:operation name="StartUploadAddinFile">
            <soap12:operation
                soapAction="http://tempuri.org/IAddInMetadataInstall/StartUploadAddinFile" style="document"
            />
            <wsdl:input>
                <soap12:body use="literal" />
            </wsdl:input>
            <wsdl:output>
                <soap12:body use="literal" />
            </wsdl:output>
            <wsdl:fault name="AddInErrorFault">
                <soap12:fault use="literal" name="AddInErrorFault" namespace="" />
            </wsdl:fault>
        </wsdl:operation>
        <wsdl:operation name="UploadAddinFile">
            <soap12:operation
                soapAction="http://tempuri.org/IAddInMetadataInstall/UploadAddinFile" style="document" />
            <wsdl:input>
                <soap12:body use="literal" />
            </wsdl:input>
            <wsdl:output>
                <soap12:body use="literal" />
            </wsdl:output>
            <wsdl:fault name="AddInErrorFault">
                <soap12:fault use="literal" name="AddInErrorFault" namespace="" />
            </wsdl:fault>
        </wsdl:operation>
        <wsdl:operation name="EndUploadAddinFile">
            <soap12:operation
                soapAction="http://tempuri.org/IAddInMetadataInstall/EndUploadAddinFile" style="document"
            />
            <wsdl:input>
                <soap12:body use="literal" />
            </wsdl:input>
            <wsdl:output>
                <soap12:body use="literal" />
            </wsdl:output>
            <wsdl:fault name="AddInErrorFault">
                <soap12:fault use="literal" name="AddInErrorFault" namespace="" />
            </wsdl:fault>
        </wsdl:operation>
        <wsdl:operation name="ProgressChanged">
            <soap12:operation
                soapAction="http://tempuri.org/IAddInMetadataInstall/ProgressChanged" style="document" />
            <wsdl:output>
                <soap12:body use="literal" />
            </wsdl:output>
            <wsdl:fault name="AddInErrorFault">
                <soap12:fault use="literal" name="AddInErrorFault" namespace="" />
            </wsdl:fault>
        </wsdl:operation>
        <wsdl:operation name="ErrorOccured">
            <soap12:operation
                soapAction="http://tempuri.org/IAddInMetadataInstall/ErrorOccured" style="document" />
            <wsdl:output>
                <soap12:body use="literal" />
            </wsdl:output>
            <wsdl:fault name="AddInErrorFault">
                <soap12:fault use="literal" name="AddInErrorFault" namespace="" />
            </wsdl:fault>
        </wsdl:operation>
        <wsdl:operation name="RebootRequired">
            <soap12:operation
                soapAction="http://tempuri.org/IAddInMetadataInstall/RebootRequired" style="document" />
            <wsdl:output>
                <soap12:body use="literal" />
            </wsdl:output>
            <wsdl:fault name="AddInErrorFault">
                <soap12:fault use="literal" name="AddInErrorFault" namespace="" />
            </wsdl:fault>
        </wsdl:operation>
        <wsdl:operation name="RestartDashboardRequired">
            <soap12:operation
                soapAction="http://tempuri.org/IAddInMetadataInstall/RestartDashboardRequired" style="document" />
            <wsdl:output>
                <soap12:body use="literal" />
            </wsdl:output>
            <wsdl:fault name="AddInErrorFault">
                <soap12:fault use="literal" name="AddInErrorFault" namespace="" />
            </wsdl:fault>
        </wsdl:operation>
    </wsdl:service>

```

```

        </wsdl:operation>
    </wsdl:binding>
    <wsdl:service name="AddInMetadataProvider">
        <wsdl:port name="CustomBinding_IAddInMetadata"
binding="tns:CustomBinding_IAddInMetadata">
            <soap12:address
location="net.tcp://serverName:6602/Microsoft.WindowsServerSolutions.AddinInfrastructure.Ad
dInMetadataProvider/Microsoft.WindowsServerSolutions.AddinInfrastructure.IAddInMetadata" />
            <wsa10:EndpointReference>

<wsa10:Address>net.tcp://serverName:6602/Microsoft.WindowsServerSolutions.AddinInfrastructure.Ad
dInMetadataProvider/Microsoft.WindowsServerSolutions.AddinInfrastructure.IAddInMetadata
a</wsa10:Address>
            <Identity xmlns="http://schemas.xmlsoap.org/ws/2006/02/addressingidentity">
                <Dns>SERVERNAME</Dns>
            </Identity>
        </wsa10:EndpointReference>
    </wsdl:port>
    <wsdl:port name="CustomBinding_IAddInMetadataInstall"
binding="tns:CustomBinding_IAddInMetadataInstall">
            <soap12:address
location="net.tcp://serverName:6602/Microsoft.WindowsServerSolutions.AddinInfrastructure.Ad
dInMetadataProvider/Microsoft.WindowsServerSolutions.AddinInfrastructure.IAddInMetadataInst
all" />
            <wsa10:EndpointReference>

<wsa10:Address>net.tcp://serverName:6602/Microsoft.WindowsServerSolutions.AddinInfrastructure.Ad
dInMetadataProvider/Microsoft.WindowsServerSolutions.AddinInfrastructure.IAddInMetadata
aInstall</wsa10:Address>
            <Identity xmlns="http://schemas.xmlsoap.org/ws/2006/02/addressingidentity">
                <Spn>host/serverName.domain</Spn>
            </Identity>
        </wsa10:EndpointReference>
    </wsdl:port>
</wsdl:service>
</wsdl:definitions>

```

6.7.2 <http://tempuri.org>

```

<?xml version="1.0" encoding="utf-8"?>
<xsschema xmlns:tns="http://tempuri.org/" elementFormDefault="qualified"
targetNamespace="http://tempuri.org/" xmlns:xs="http://www.w3.org/2001/XMLSchema">
    <xs:import schemaLocation="" namespace="http://schemas.microsoft.com/2003/10/Serialization/" />
    <xs:import schemaLocation="" namespace="http://schemas.datacontract.org/2004/07/System.Collections.ObjectModel" />
    <xs:import schemaLocation="" namespace="http://schemas.microsoft.com/WindowsServerSolutions/2010/03/Addins" />
    <xs:import schemaLocation="" namespace="http://schemas.datacontract.org/2004/07/System" />
    <xs:import schemaLocation="" namespace="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.AddinIn
frastructure" />
    <xs:element name="GetPackagePath">
        <xs:complexType>
            <xs:sequence>
                <xs:element xmlns:q1="http://schemas.microsoft.com/2003/10/Serialization/" minOccurs="0" name="packageId" type="q1:guid" />
            </xs:sequence>
        </xs:complexType>
    </xs:element>
    <xs:element name="GetPackagePathResponse">
        <xs:complexType>
            <xs:sequence>
                <xs:element minOccurs="0" name="GetPackagePathResult" nillable="true" type="xs:string" />
            </xs:sequence>
        </xs:complexType>
    </xs:element>
</xsschema>

```

```

        </xs:complexType>
    </xs:element>
<xs:element name="GetAddInIds">
    <xs:complexType>
        <xs:sequence />
    </xs:complexType>
</xs:element>
<xs:element name="GetAddInIdsResponse">
    <xs:complexType>
        <xs:sequence>
            <xs:element
                xmlns:q2="http://schemas.datacontract.org/2004/07/System.Collections.ObjectModel"
                minOccurs="0" name="GetAddInIdsResult" nillable="true" type="q2:ReadOnlyCollectionOfguid"
            />
            </xs:sequence>
        </xs:complexType>
    </xs:element>
<xs:element name="GetAddInInformation">
    <xs:complexType>
        <xs:sequence>
            <xs:element
                xmlns:q3="http://schemas.microsoft.com/2003/10/Serialization/"
                minOccurs="0" name="packageId" type="q3:guid" />
        </xs:sequence>
    </xs:complexType>
</xs:element>
<xs:element name="GetAddInInformationResponse">
    <xs:complexType>
        <xs:sequence>
            <xs:element
                xmlns:q4="http://schemas.microsoft.com/WindowsServerSolutions/2010/03/Addins" minOccurs="0"
                name="GetAddInInformationResult" nillable="true" type="q4:PackageInfo" />
        </xs:sequence>
    </xs:complexType>
</xs:element>
<xs:element name="RegisterForChanges">
    <xs:complexType>
        <xs:sequence>
            <xs:element minOccurs="0" name="server" type="xs:boolean" />
        </xs:sequence>
    </xs:complexType>
</xs:element>
<xs:element name="RegisterForChangesResponse">
    <xs:complexType>
        <xs:sequence />
    </xs:complexType>
</xs:element>
<xs:element name="OperationInProgress">
    <xs:complexType>
        <xs:sequence />
    </xs:complexType>
</xs:element>
<xs:element name="OperationInProgressResponse">
    <xs:complexType>
        <xs:sequence>
            <xs:element minOccurs="0" name="OperationInProgressResult" type="xs:boolean" />
        </xs:sequence>
    </xs:complexType>
</xs:element>
<xs:element name="ChangeOccured">
    <xs:complexType>
        <xs:sequence />
    </xs:complexType>
</xs:element>
<xs:element name="RedeployAddInResponse">
    <xs:complexType>
        <xs:sequence />
    </xs:complexType>
</xs:element>

```

```

<xs:element name="NewAddInVersionResponse">
  <xs:complexType>
    <xs:sequence />
  </xs:complexType>
</xs:element>
<xs:element name="SetAddInExpirationDateResponse">
  <xs:complexType>
    <xs:sequence />
  </xs:complexType>
</xs:element>
<xs:element name="CheckCredentials">
  <xs:complexType>
    <xs:sequence />
  </xs:complexType>
</xs:element>
<xs:element name="CheckCredentialsResponse">
  <xs:complexType>
    <xs:sequence />
  </xs:complexType>
</xs:element>
<xs:element name="InstallAddIn">
  <xs:complexType>
    <xs:sequence>
      <xs:element
        xmlns:q10="http://schemas.microsoft.com/WindowsServerSolutions/2010/03/Addins"
        minOccurs="0" name="addin" nillable="true" type="q10:Package" />
      <xs:element
        xmlns:q11="http://schemas.microsoft.com/WindowsServerSolutions/2010/03/Addins"
        minOccurs="0" name="installOnClients" nillable="true" type="q11:ClientInstallFilter" />
    </xs:sequence>
  </xs:complexType>
</xs:element>
<xs:element name="DownloadInstallAddIn">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" name="address" nillable="true" type="xs:anyURI" />
      <xs:element minOccurs="0" name="certThumbprint" nillable="true"
        type="xs:string" />
      <xs:element xmlns:q12="http://schemas.microsoft.com/2003/10/Serialization/"
        minOccurs="0" name="expectedPackageId" type="q12:guid" />
      <xs:element
        xmlns:q13="http://schemas.microsoft.com/WindowsServerSolutions/2010/03/Addins"
        minOccurs="0" name="installOnClients" nillable="true" type="q13:ClientInstallFilter" />
    </xs:sequence>
  </xs:complexType>
</xs:element>
<xs:element name="UninstallAddIn">
  <xs:complexType>
    <xs:sequence>
      <xs:element xmlns:q14="http://schemas.microsoft.com/2003/10/Serialization/"
        minOccurs="0" name="id" type="q14:guid" />
    </xs:sequence>
  </xs:complexType>
</xs:element>
<xs:element name="CancelOperation">
  <xs:complexType>
    <xs:sequence />
  </xs:complexType>
</xs:element>
<xs:element name="StartUploadAddinFile">
  <xs:complexType>
    <xs:sequence>
      <xs:element xmlns:q15="http://schemas.microsoft.com/2003/10/Serialization/"
        minOccurs="0" name="addinId" type="q15:guid" />
    </xs:sequence>
  </xs:complexType>
</xs:element>
<xs:element name="StartUploadAddinFileResponse">
  <xs:complexType>

```

```

        <xs:sequence>
            <xs:element xmlns:q16="http://schemas.microsoft.com/2003/10/Serialization/" minOccurs="0" name="StartUploadAddinFileResult" type="q16:guid" />
        </xs:sequence>
    </xs:complexType>
</xs:element>
<xs:element name="UploadAddinFile">
    <xs:complexType>
        <xs:sequence>
            <xs:element xmlns:q17="http://schemas.microsoft.com/2003/10/Serialization/" minOccurs="0" name="sessionId" type="q17:guid" />
            <xs:element minOccurs="0" name="data" nillable="true" type="xs:base64Binary" />
        </xs:sequence>
    </xs:complexType>
</xs:element>
<xs:element name="UploadAddinFileResponse">
    <xs:complexType>
        <xs:sequence />
    </xs:complexType>
</xs:element>
<xs:element name="EndUploadAddinFile">
    <xs:complexType>
        <xs:sequence>
            <xs:element xmlns:q18="http://schemas.microsoft.com/2003/10/Serialization/" minOccurs="0" name="sessionId" type="q18:guid" />
        </xs:sequence>
    </xs:complexType>
</xs:element>
<xs:element name="EndUploadAddinFileResponse">
    <xs:complexType>
        <xs:sequence />
    </xs:complexType>
</xs:element>
<xs:element name="ProgressChanged">
    <xs:complexType>
        <xs:sequence>
            <xs:element minOccurs="0" name="p" type="xs:int" />
            <xs:element minOccurs="0" name="completed" type="xs:boolean" />
        </xs:sequence>
    </xs:complexType>
</xs:element>
<xs:element name="ErrorOccured">
    <xs:complexType>
        <xs:sequence>
            <xs:element
                xmlns:q19="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.AddinInfrastructure" minOccurs="0" name="messageId" type="q19:AddInError" />
        </xs:sequence>
    </xs:complexType>
</xs:element>
<xs:element name="RebootRequired">
    <xs:complexType>
        <xs:sequence />
    </xs:complexType>
</xs:element>
<xs:element name="RestartDashboardRequired">
    <xs:complexType>
        <xs:sequence />
    </xs:complexType>
</xs:element>
</xs:schema>

```

6.7.3 <http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.AddinInfrastructure>

```
<?xml version="1.0" encoding="utf-8"?>
```

```

<xs:schema
xmlns:tns="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.AddinInfrastructure" elementFormDefault="qualified"
targetNamespace="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.AddinInfrastructure" xmlns:xs="http://www.w3.org/2001/XMLSchema">
    <xs:import schemaLocation="" namespace="http://schemas.microsoft.com/2003/10/Serialization/" />
    <xs:simpleType name="AddInError">
        <xs:restriction base="xs:string">
            <xs:enumeration value="None" />
            <xs:enumeration value="OperationCancelled" />
            <xs:enumeration value="UnknownException" />
            <xs:enumeration value="FileNotFoundException" />
            <xs:enumeration value="InvalidSignature" />
            <xs:enumeration value="DownloadError" />
            <xs:enumeration value="PackageExtraction" />
            <xs:enumeration value="InstallError" />
            <xs:enumeration value="UpgradeError" />
            <xs:enumeration value="UnableToQueryServer" />
            <xs:enumeration value="InvalidDownloadRequest" />
            <xs:enumeration value="UninstallError" />
            <xs:enumeration value="AuthorizationError" />
            <xs:enumeration value="ProviderConnectionError" />
            <xs:enumeration value="PackageFileCopyError" />
            <xs:enumeration value="SettingsProviderError" />
            <xs:enumeration value="InvalidData" />
            <xs:enumeration value="UnknownAddIn" />
            <xs:enumeration value="OperationInProgress" />
        </xs:restriction>
    </xs:simpleType>
    <xs:element name="AddInError" nillable="true" type="tns:AddInError" />
    <xs:simpleType name="OSEditions">
        <xs:list>
            <xs:simpleType>
                <xs:restriction base="xs:string">
                    <xs:enumeration value="None" />
                    <xs:annotation>
                        <xs:appinfo>
                            <EnumerationValue
                                xmlns="http://schemas.microsoft.com/2003/10/Serialization/">0</EnumerationValue>
                        </xs:appinfo>
                    </xs:annotation>
                </xs:enumeration>
                <xs:enumeration value="NotSet" />
                <xs:annotation>
                    <xs:appinfo>
                        <EnumerationValue
                            xmlns="http://schemas.microsoft.com/2003/10/Serialization/">0</EnumerationValue>
                    </xs:appinfo>
                </xs:annotation>
            </xs:simpleType>
            <xs:enumeration value="Home" />
            <xs:annotation>
                <xs:appinfo>
                    <EnumerationValue
                        xmlns="http://schemas.microsoft.com/2003/10/Serialization/">1</EnumerationValue>
                </xs:appinfo>
            </xs:annotation>
            <xs:enumeration value="Pro" />
            <xs:annotation>
                <xs:appinfo>
                    <EnumerationValue
                        xmlns="http://schemas.microsoft.com/2003/10/Serialization/">2</EnumerationValue>
                </xs:appinfo>
            </xs:annotation>
            <xs:enumeration value="Starter" />
            <xs:annotation>

```

```

        <xs:appinfo>
            <EnumerationValue
                xmlns="http://schemas.microsoft.com/2003/10/Serialization/">4</EnumerationValue>
        </xs:appinfo>
    </xs:annotation>
</xs:enumeration>
<xs:enumeration value="MediaCenter">
    <xs:annotation>
        <xs:appinfo>
            <EnumerationValue
                xmlns="http://schemas.microsoft.com/2003/10/Serialization/">8</EnumerationValue>
        </xs:appinfo>
    </xs:annotation>
</xs:enumeration>
</xs:restriction>
</xs:simpleType>
</xs:list>
</xs:simpleType>
<xs:element name="OSEditions" nillable="true" type="tns:OSEditions" />
</xs:schema>

```

6.7.4 http://schemas.microsoft.com/2003/10/Serialization/Arrays

```

<?xml version="1.0" encoding="utf-8"?>
<xs:schema xmlns:ser="http://schemas.microsoft.com/2003/10/Serialization/"
xmlns:tns="http://schemas.microsoft.com/2003/10/Serialization/Arrays"
elementFormDefault="qualified"
targetNamespace="http://schemas.microsoft.com/2003/10/Serialization/Arrays"
xmlns:xs="http://www.w3.org/2001/XMLSchema">
    <xs:import schemaLocation="" namespace="http://schemas.microsoft.com/2003/10/Serialization/" />
    <xs:complexType name="ArrayOfguid">
        <xs:sequence>
            <xs:element minOccurs="0" maxOccurs="unbounded" name="guid" type="ser:guid" />
        </xs:sequence>
    </xs:complexType>
    <xs:element name="ArrayOfguid" nillable="true" type="tns:ArrayOfguid" />
    <xs:complexType name="ArrayOfstring">
        <xs:sequence>
            <xs:element minOccurs="0" maxOccurs="unbounded" name="string" nillable="true"
type="xs:string" />
        </xs:sequence>
    </xs:complexType>
    <xs:element name="ArrayOfstring" nillable="true" type="tns:ArrayOfstring" />
</xs:schema>

```

6.7.5 http://schemas.microsoft.com/2003/10/Serialization

```

<?xml version="1.0" encoding="utf-8"?>
<xs:schema xmlns:tns="http://schemas.microsoft.com/2003/10/Serialization/"
attributeFormDefault="qualified" elementFormDefault="qualified"
targetNamespace="http://schemas.microsoft.com/2003/10/Serialization/"
xmlns:xs="http://www.w3.org/2001/XMLSchema">
    <xs:element name="anyType" nillable="true" type="xs:anyType" />
    <xs:element name="anyURI" nillable="true" type="xs:anyURI" />
    <xs:element name="base64Binary" nillable="true" type="xs:base64Binary" />
    <xs:element name="boolean" nillable="true" type="xs:boolean" />
    <xs:element name="byte" nillable="true" type="xs:byte" />
    <xs:element name="dateTime" nillable="true" type="xs:dateTime" />
    <xs:element name="decimal" nillable="true" type="xs:decimal" />
    <xs:element name="double" nillable="true" type="xs:double" />
    <xs:element name="float" nillable="true" type="xs:float" />
    <xs:element name="int" nillable="true" type="xs:int" />
    <xs:element name="long" nillable="true" type="xs:long" />
    <xs:element name="QName" nillable="true" type="xs:QName" />

```

```

<xs:element name="short" nillable="true" type="xs:short" />
<xs:element name="string" nillable="true" type="xs:string" />
<xs:element name="unsignedByte" nillable="true" type="xs:unsignedByte" />
<xs:element name="unsignedInt" nillable="true" type="xs:unsignedInt" />
<xs:element name="unsignedLong" nillable="true" type="xs:unsignedLong" />
<xs:element name="unsignedShort" nillable="true" type="xs:unsignedShort" />
<xs:element name="char" nillable="true" type="tns:char" />
<xs:simpleType name="char">
    <xs:restriction base="xs:int" />
</xs:simpleType>
<xs:element name="duration" nillable="true" type="tns:duration" />
<xs:simpleType name="duration">
    <xs:restriction base="xs:duration">
        <xs:pattern value="-?P(\d*D)?(T(\d*H)?(\d*M)?(\d*(\.\d*)?S)?)?" />
        <xs:minInclusive value="-P10675199DT2H48M5.4775808S" />
        <xs:maxInclusive value="P10675199DT2H48M5.4775807S" />
    </xs:restriction>
</xs:simpleType>
<xs:element name="guid" nillable="true" type="tns:guid" />
<xs:simpleType name="guid">
    <xs:restriction base="xs:string">
        <xs:pattern value="[\da-fA-F]{8}-[\da-fA-F]{4}-[\da-fA-F]{4}-[\da-fA-F]{4}-[\da-fA-F]{12}" />
    </xs:restriction>
</xs:simpleType>
<xs:attribute name="FactoryType" type="xs:QName" />
<xs:attribute name="Id" type="xs:ID" />
<xs:attribute name="Ref" type="xs:IDREF" />
</xs:schema>

```

6.7.6 <http://schemas.microsoft.com/WindowsServerSolutions/2010/03/Addins>

```

<?xml version="1.0" encoding="utf-8"?>
<xs:schema xmlns:ser="http://schemas.microsoft.com/2003/10/Serialization/" 
xmlns:tns="http://schemas.microsoft.com/WindowsServerSolutions/2010/03/Addins"
elementFormDefault="qualified"
targetNamespace="http://schemas.microsoft.com/WindowsServerSolutions/2010/03/Addins"
xmlns:xs="http://www.w3.org/2001/XMLSchema">
    <xs:import schemaLocation="" namespace="http://schemas.datacontract.org/2004/07/System" />
    <xs:import schemaLocation="" namespace="http://schemas.microsoft.com/2003/10/Serialization/Arrays" />
    <xs:import schemaLocation="" namespace="http://schemas.microsoft.com/2003/10/Serialization/" />
    <xs:import schemaLocation="" namespace="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.AddinInfrastructure" />
    <xs:complexType name="PackageInfo">
        <xs:sequence>
            <xs:element minOccurs="0" name="Company" nillable="true" type="xs:string" />
            <xs:element minOccurs="0" name="ExpirationDateUtc" type="xs:dateTime" />
            <xs:element minOccurs="0" name="Filter" nillable="true" type="tns:ClientInstallFilter" />
                <xs:element minOccurs="0" name="Install" type="xs:boolean" />
                <xs:element minOccurs="0" name="InstallDateUtc" type="xs:dateTime" />
                <xs:element minOccurs="0" name="LastRedeployDate" type="xs:dateTime" />
                <xs:element minOccurs="0" name="Package" nillable="true" type="tns:Package" />
                <xs:element minOccurs="0" name="RenewalUri" nillable="true" type="xs:anyURI" />
                <xs:element minOccurs="0" name="UpdateType" type="tns:UpdateClassification" />
                <xs:element minOccurs="0" name="UpdateUri" nillable="true" type="xs:anyURI" />
                <xs:element xmlns:q1="http://schemas.datacontract.org/2004/07/System" minOccurs="0" name="UpdateVersion" nillable="true" type="q1:Version" />
                    <xs:element xmlns:q2="http://schemas.datacontract.org/2004/07/System" minOccurs="0" name="VersionOnServer" nillable="true" type="q2:Version" />
                </xs:sequence>
            </xs:complexType>
        <xs:element name="PackageInfo" nillable="true" type="tns:PackageInfo" />

```

```

<xs:complexType name="ClientInstallFilter">
    <xs:sequence>
        <xs:element xmlns:q3="http://schemas.microsoft.com/2003/10/Serialization/Arrays"
minOccurs="0" name="clientSidList" nillable="true" type="q3:ArrayOfstring" />
        <xs:element minOccurs="0" name="listIsMachinesToInclude" type="xs:boolean" />
    </xs:sequence>
</xs:complexType>
<xs:element name="ClientInstallFilter" nillable="true"
type="tns:ClientInstallFilter" />
<xs:complexType name="Package">
    <xs:sequence>
        <xs:element name="Id" type="ser:guid" />
        <xs:element name="Version" nillable="true" type="xs:string" />
        <xs:element name="Name" nillable="true" type="xs:string" />
        <xs:element minOccurs="0" name="Allow32BitOn64BitClients" type="xs:boolean" />
        <xs:element minOccurs="0" name="ServerBinary" nillable="true"
type="tns:BinaryCollection" />
            <xs:element minOccurs="0" name="ClientBinary32" nillable="true"
type="tns:BinaryCollection" />
                <xs:element minOccurs="0" name="ClientBinary64" nillable="true"
type="tns:BinaryCollection" />
                    <xs:element minOccurs="0" name="SupportedSkus" nillable="true"
type="tns:SkuCollection" />
                        <xs:element minOccurs="0" name="SupportUrl" nillable="true" type="xs:anyURI" />
                        <xs:element minOccurs="0" name="Location" nillable="true" type="xs:string" />
                        <xs:element minOccurs="0" name="PrivacyStatement" nillable="true"
type="xs:anyURI" />
                            <xs:element minOccurs="0" name="OtherBinaries" nillable="true"
type="tns:OtherBinariesMap" />
                                <xs:element minOccurs="0" name="Preinstall" nillable="true"
type="tns:Preinstall" />
                                    <xs:element minOccurs="0" name="UninstallConfirm" nillable="true"
type="tns:UninstallConfirm" />
                                        <xs:element minOccurs="0" name="ShowSupplementalNotice" type="xs:boolean" />
                                    </xs:sequence>
                                </xs:complexType>
<xs:element name="Package" nillable="true" type="tns:Package" />
<xs:complexType name="BinaryCollection">
    <xs:sequence>
        <xs:element minOccurs="0" maxOccurs="unbounded" name="File" nillable="true"
type="tns:BinaryReference" />
    </xs:sequence>
</xs:complexType>
<xs:element name="BinaryCollection" nillable="true" type="tns:BinaryCollection" />
<xs:complexType name="BinaryReference">
    <xs:sequence>
        <xs:element name="ProductCode" type="ser:guid" />
        <xs:element name="Version" nillable="true" type="xs:string" />
        <xs:element name="Name" nillable="true" type="xs:string" />
        <xs:element minOccurs="0" name="Arguments" nillable="true" type="xs:string" />
        <xs:element minOccurs="0" name="Filter" nillable="true" type="tns:Filter" />
    </xs:sequence>
</xs:complexType>
<xs:element name="BinaryReference" nillable="true" type="tns:BinaryReference" />
<xs:complexType name="Filter">
    <xs:sequence>
        <xs:element minOccurs="0" name="MinOSVersion" nillable="true" type="xs:string"
/>
        <xs:element minOccurs="0" name="MaxOSVersion" nillable="true" type="xs:string"
/>
        <xs:element
xmlns:q4="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.AddinInf
rastructure" minOccurs="0" name="OSEdition" type="q4:OSEditions" />
            <xs:element minOccurs="0" name="Language" nillable="true" type="xs:string" />
            <xs:element minOccurs="0" name="IsLanguageFallback" type="xs:boolean" />
    </xs:sequence>
</xs:complexType>
<xs:element name="Filter" nillable="true" type="tns:Filter" />
<xs:complexType name="SkuCollection">

```

```

<xs:sequence>
    <xs:element minOccurs="0" maxOccurs="unbounded" name="Sku" nillable="true"
type="xs:string" />
</xs:sequence>
</xs:complexType>
<xs:element name="SkuCollection" nillable="true" type="tns:SkuCollection" />
<xs:complexType name="OtherBinariesMap">
    <xs:annotation>
        <xs:appinfo>
            <IsDictionary
xmlns="http://schemas.microsoft.com/2003/10/Serialization/">true</IsDictionary>
        </xs:appinfo>
    </xs:annotation>
    <xs:sequence>
        <xs:element minOccurs="0" maxOccurs="unbounded" name="Item">
            <xs:complexType>
                <xs:sequence>
                    <xs:element name="Target" nillable="true" type="xs:string" />
                    <xs:element name="FileName" nillable="true" type="xs:string" />
                </xs:sequence>
            </xs:complexType>
        </xs:element>
    </xs:sequence>
</xs:complexType>
<xs:element name="OtherBinariesMap" nillable="true" type="tns:OtherBinariesMap" />
<xs:complexType name="Preinstall">
    <xs:sequence>
        <xs:element name="Executable" nillable="true" type="xs:string" />
        <xs:element minOccurs="0" name="NormalArgs" nillable="true" type="xs:string" />
        <xs:element minOccurs="0" name="SilentArgs" nillable="true" type="xs:string" />
        <xs:element minOccurs="0" name="IgnoreExitCode" type="xs:boolean" />
    </xs:sequence>
</xs:complexType>
<xs:element name="Preinstall" nillable="true" type="tns:Preinstall" />
<xs:complexType name="UninstallConfirm">
    <xs:sequence>
        <xs:element name="Executable" nillable="true" type="xs:string" />
        <xs:element minOccurs="0" name="Arguments" nillable="true" type="xs:string" />
    </xs:sequence>
</xs:complexType>
<xs:element name="UninstallConfirm" nillable="true" type="tns:UninstallConfirm" />
<xs:simpleType name="UpdateClassification">
    <xs:restriction base="xs:string">
        <xs:enumeration value="Unknown" />
        <xs:enumeration value="CriticalUpdate" />
        <xs:enumeration value="ImportantUpdate" />
        <xs:enumeration value="Update" />
    </xs:restriction>
</xs:simpleType>
    <xs:element name="UpdateClassification" nillable="true"
type="tns:UpdateClassification" />
</xs:schema>

```

6.7.7 <http://schemas.datacontract.org/2004/07/System.Collections.ObjectModel>

```

<?xml version="1.0" encoding="utf-8"?>
<xs:schema
xmlns:tns="http://schemas.datacontract.org/2004/07/System.Collections.ObjectModel"
elementFormDefault="qualified"
targetNamespace="http://schemas.datacontract.org/2004/07/System.Collections.ObjectModel"
xmlns:xs="http://www.w3.org/2001/XMLSchema">
    <xs:import schemaLocation="" namespace="http://schemas.microsoft.com/2003/10/Serialization/Arrays" />
    <xs:complexType name="ReadOnlyCollectionOfguid">
        <xs:annotation>
            <xs:appinfo>

```

```

        <GenericType Name="ReadOnlyCollectionOf{0}{#}">
Namespace="http://schemas.datacontract.org/2004/07/System.Collections.ObjectModel"
xmlns="http://schemas.microsoft.com/2003/10/Serialization/">
    <GenericParameter Name="guid">
Namespace="http://schemas.microsoft.com/2003/10/Serialization/" />
    </GenericType>
</xs:appinfo>
</xs:annotation>
<xs:sequence>
    <xs:element xmlns:q1="http://schemas.microsoft.com/2003/10/Serialization/Arrays"
name="list" nillable="true" type="q1:ArrayOfguid" />
</xs:sequence>
</xs:complexType>
<xs:element name="ReadOnlyCollectionOfguid" nillable="true"
type="tns:ReadOnlyCollectionOfguid" />
</xs:schema>

```

6.7.8 http://schemas.datacontract.org/2004/07/System

```

<?xml version="1.0" encoding="utf-8"?>
<xs:schema xmlns:tns="http://schemas.datacontract.org/2004/07/System"
elementFormDefault="qualified"
targetNamespace="http://schemas.datacontract.org/2004/07/System"
xmlns:xs="http://www.w3.org/2001/XMLSchema">
    <xs:complexType name="Version">
        <xs:sequence>
            <xs:element name="Build" type="xs:int" />
            <xs:element name="_Major" type="xs:int" />
            <xs:element name="_Minor" type="xs:int" />
            <xs:element name="_Revision" type="xs:int" />
        </xs:sequence>
    </xs:complexType>
    <xs:element name="Version" nillable="true" type="tns:Version" />
</xs:schema>

```

6.8 Network Service WSDL

6.8.1 wsdl

```

<?xml version="1.0" encoding="utf-8"?>
<wsdl:definitions xmlns:wsap="http://schemas.xmlsoap.org/ws/2004/08/addressing/policy"
xmlns:wsa10="http://www.w3.org/2005/08/addressing" xmlns:tns="http://tempuri.org/"
xmlns:msc="http://schemas.microsoft.com/ws/2005/12/wsdl/contract"
xmlns:soapenc="http://schemas.xmlsoap.org/soap/encoding/"
xmlns:soap="http://schemas.xmlsoap.org/wsdl/soap/"
xmlns:wsp="http://schemas.xmlsoap.org/ws/2004/09/policy"
xmlns:wsam="http://www.w3.org/2007/05/addressing/metadata"
xmlns:wsa="http://schemas.xmlsoap.org/ws/2004/08/addressing"
xmlns:wsaw="http://www.w3.org/2006/05/addressing/wsdl"
xmlns:soap12="http://schemas.xmlsoap.org/wsdl/soap12/" xmlns:wsu="http://docs.oasis-
open.org/wss/2004/01/oasis-200401-wss-wssecurity-utility-1.0.xsd"
xmlns:xsd="http://www.w3.org/2001/XMLSchema" name="NetworkingServiceWcfWrapper"
targetNamespace="http://tempuri.org/" xmlns:wsdl="http://schemas.xmlsoap.org/wsdl/">
    <wsp:Policy wsu:Id="CustomBinding_INetworkingService_policy">
        <wsp:ExactlyOne>
            <wsp:All>
                <msb:BinaryEncoding
xmlns:msb="http://schemas.microsoft.com/ws/2004/06/2004/mspolicy/netbinary1" />
                <sp:TransportBinding
xmlns:sp="http://schemas.xmlsoap.org/ws/2005/07/securitypolicy">
                    <wsp:Policy>
                        <sp:TransportToken>
                            <wsp:Policy>

```

```

        <msf:SslTransportSecurity
    xmlns:msf="http://schemas.microsoft.com/ws/2006/05/framing/policy">
        <msf:RequireClientCertificate />
        </msf:SslTransportSecurity>
    </wsp:Policy>
    </sp:TransportToken>
    <sp:AlgorithmSuite>
        <wsp:Policy>
            <sp:Basic256 />
        </wsp:Policy>
    </sp:AlgorithmSuite>
    <sp:Layout>
        <wsp:Policy>
            <sp:Strict />
        </wsp:Policy>
    </sp:Layout>
    </wsp:Policy>
    </sp:TransportBinding>
    <wsaw:UsingAddressing />
</wsp:All>
</wsp:ExactlyOne>
</wsp:Policy>
<wsdl:types>
    <xsd:schema targetNamespace="http://tempuri.org/Imports">
        <xsd:import schemaLocation="" namespace="http://tempuri.org/" />
        <xsd:import schemaLocation="" namespace="http://schemas.microsoft.com/2003/10/Serialization/" />
        <xsd:import schemaLocation="" namespace="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.RemoteAccess" />
        <xsd:import schemaLocation="" namespace="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.Networking" />
        <xsd:import schemaLocation="" namespace="http://schemas.datacontract.org/2004/07/System.Net" />
        <xsd:import schemaLocation="" namespace="http://schemas.datacontract.org/2004/07/System.Net.Sockets" />
        <xsd:import schemaLocation="" namespace="http://schemas.microsoft.com/2003/10/Serialization/Arrays" />
    </xsd:schema>
</wsdl:types>
<wsdl:message name="INetworkingService_Ping_InputMessage">
    <wsdl:part name="parameters" element="tns:Ping" />
</wsdl:message>
<wsdl:message name="INetworkingService_Ping_OutputMessage">
    <wsdl:part name="parameters" element="tns:PingResponse" />
</wsdl:message>
<wsdl:message name="INetworkingService_GetVPNServerSetting_InputMessage">
    <wsdl:part name="parameters" element="tns:GetVPNServerSetting" />
</wsdl:message>
<wsdl:message name="INetworkingService_GetVPNServerSetting_OutputMessage">
    <wsdl:part name="parameters" element="tns:GetVPNServerSettingResponse" />
</wsdl:message>
<wsdl:message name="INetworkingService_GetVirtualNetworkSettings_InputMessage">
    <wsdl:part name="parameters" element="tns:GetVirtualNetworkSettings" />
</wsdl:message>
<wsdl:message name="INetworkingService_GetVirtualNetworkSettings_OutputMessage">
    <wsdl:part name="parameters" element="tns:GetVirtualNetworkSettingsResponse" />
</wsdl:message>
<wsdl:portType name="INetworkingService">
    <wsdl:operation name="Ping">
        <wsdl:input wsaw:Action="http://tempuri.org/INetworkingService/Ping" message="tns:INetworkingService_Ping_InputMessage" />
        <wsdl:output wsaw:Action="http://tempuri.org/INetworkingService/PingResponse" message="tns:INetworkingService_Ping_OutputMessage" />
    </wsdl:operation>
    <wsdl:operation name="GetVPNServerSetting">

```

```

        <wsdl:input
wsaw:Action="http://tempuri.org/INetworkingService/GetVPNServerSetting"
message="tns:INetworkingService_GetVPNServerSetting_InputMessage" />
        <wsdl:output
wsaw:Action="http://tempuri.org/INetworkingService/GetVPNServerSettingResponse"
message="tns:INetworkingService GetVPNServerSetting OutputMessage" />
    </wsdl:operation>
    <wsdl:operation name="GetVirtualNetworkSettings">
        <wsdl:input
wsaw:Action="http://tempuri.org/INetworkingService/GetVirtualNetworkSettings"
message="tns:INetworkingService GetVirtualNetworkSettings InputMessage" />
        <wsdl:output
wsaw:Action="http://tempuri.org/INetworkingService/GetVirtualNetworkSettingsResponse"
message="tns:INetworkingService_GetVirtualNetworkSettings_OutputMessage" />
        </wsdl:operation>
    </wsdl:portType>
<wsdl:binding name="CustomBinding_INetworkingService" type="tns:INetworkingService">
    <wsp:PolicyReference URI="#CustomBinding_INetworkingService_policy" />
    <soap12:binding transport="http://schemas.microsoft.com/soap/tcp" />
    <wsdl:operation name="Ping">
        <soap12:operation soapAction="http://tempuri.org/INetworkingService/Ping"
style="document" />
            <wsdl:input>
                <soap12:body use="literal" />
            </wsdl:input>
            <wsdl:output>
                <soap12:body use="literal" />
            </wsdl:output>
        </wsdl:operation>
        <wsdl:operation name="GetVPNServerSetting">
            <soap12:operation
soapAction="http://tempuri.org/INetworkingService/GetVPNServerSetting" style="document" />
            <wsdl:input>
                <soap12:body use="literal" />
            </wsdl:input>
            <wsdl:output>
                <soap12:body use="literal" />
            </wsdl:output>
        </wsdl:operation>
        <wsdl:operation name="GetVirtualNetworkSettings">
            <soap12:operation
soapAction="http://tempuri.org/INetworkingService/GetVirtualNetworkSettings" style="document" />
            <wsdl:input>
                <soap12:body use="literal" />
            </wsdl:input>
            <wsdl:output>
                <soap12:body use="literal" />
            </wsdl:output>
        </wsdl:operation>
    </wsdl:binding>
    <wsdl:service name="NetworkingServiceWcfWrapper">
        <wsdl:port name="CustomBinding_INetworkingService"
binding="tns:CustomBinding_INetworkingService">
            <soap12:address
location="net.tcp://serverName:6602/Microsoft.WindowsServerSolutions.NetworkingProvider(INetworkingService)/Microsoft.WindowsServerSolutions.Networking.INetworkingService" />
            <wsa10:EndpointReference>
<wsa10:Address>net.tcp://serverName:6602/Microsoft.WindowsServerSolutions.NetworkingProvider(INetworkingService)/Microsoft.WindowsServerSolutions.Networking.INetworkingService</wsa10:Address>
                <Identity xmlns="http://schemas.xmlsoap.org/ws/2006/02/addressingidentity">
                    <Dns>SERVERNAME</Dns>
                </Identity>
            </wsa10:EndpointReference>
        </wsdl:port>
    </wsdl:service>

```

```
</wsdl:definitions>
```

6.8.2 http://tempuri.org

```
<?xml version="1.0" encoding="utf-8"?>
<xss:schema xmlns:tns="http://tempuri.org/" elementFormDefault="qualified"
targetNamespace="http://tempuri.org/" xmlns:xs="http://www.w3.org/2001/XMLSchema">
    <xss:import schemaLocation="" namespace="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.RemoteAccess" />
    <xss:import schemaLocation="" namespace="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.Networking" />
        <xss:element name="Ping">
            <xss:complexType>
                <xss:sequence />
            </xss:complexType>
        </xss:element>
        <xss:element name="PingResponse">
            <xss:complexType>
                <xss:sequence />
            </xss:complexType>
        </xss:element>
        <xss:element name="GetVPNServerSetting">
            <xss:complexType>
                <xss:sequence />
            </xss:complexType>
        </xss:element>
        <xss:element name="GetVPNServerSettingResponse">
            <xss:complexType>
                <xss:sequence>
                    <xss:element
xmlns:q1="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.RemoteAccess" minOccurs="0" name="GetVPNServerSettingResult" nillable="true" type="q1:VPNSetting" />
                </xss:sequence>
            </xss:complexType>
        </xss:element>
        <xss:element name="GetVirtualNetworkSettings">
            <xss:complexType>
                <xss:sequence />
            </xss:complexType>
        </xss:element>
        <xss:element name="GetVirtualNetworkSettingsResponse">
            <xss:complexType>
                <xss:sequence>
                    <xss:element
xmlns:q2="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.Networking" minOccurs="0" name="GetVirtualNetworkSettingsResult" nillable="true" type="q2:VirtualNetworkSettings" />
                </xss:sequence>
            </xss:complexType>
        </xss:element>
    </xss:schema>
```

6.8.3 http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.Networking

```
<?xml version="1.0" encoding="utf-8"?>
<xss:schema
xmlns:tns="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.Networking" elementFormDefault="qualified"
targetNamespace="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.Networking" xmlns:xs="http://www.w3.org/2001/XMLSchema">
```

```

<xs:import schemaLocation=""
namespace="http://schemas.datacontract.org/2004/07/System.Net" />
<xs:complexType name="VirtualNetworkSettings">
    <xs:sequence>
        <xs:element minOccurs="0" name="Enabled" type="xs:boolean" />
        <xs:element minOccurs="0" name="VirtualNetworkAddressPrefixes" nillable="true"
type="tns:ArrayOfAddressPrefix" />
            <xs:element minOccurs="0" name="VpnDeviceName" nillable="true" type="xs:string"
/>
    </xs:sequence>
</xs:complexType>
<xs:element name="VirtualNetworkSettings" nillable="true"
type="tns:VirtualNetworkSettings" />
<xs:complexType name="ArrayOfAddressPrefix">
    <xs:sequence>
        <xs:element minOccurs="0" maxOccurs="unbounded" name="AddressPrefix"
nillable="true" type="tns:AddressPrefix" />
    </xs:sequence>
</xs:complexType>
<xs:element name="ArrayOfAddressPrefix" nillable="true"
type="tns:ArrayOfAddressPrefix" />
<xs:complexType name="AddressPrefix">
    <xs:sequence>
        <xs:element xmlns:q1="http://schemas.datacontract.org/2004/07/System.Net"
minOccurs="0" name="Address" nillable="true" type="q1:IPAddress" />
            <xs:element minOccurs="0" name="PrefixLength" type="xs:int" />
        </xs:sequence>
</xs:complexType>
<xs:element name="AddressPrefix" nillable="true" type="tns:AddressPrefix" />
</xs:schema>

```

6.8.4 http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.RemoteAccess

```

<?xml version="1.0" encoding="utf-8"?>
<xs:schema
xmlns:tns="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.RemoteA
ccess" elementFormDefault="qualified"
targetNamespace="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.R
emoteAccess" xmlns:xs="http://www.w3.org/2001/XMLSchema">
    <xs:complexType name="VPNSetting">
        <xs:sequence>
            <xs:element minOccurs="0" name="ConnectionName" nillable="true" type="xs:string"
/>
            <xs:element minOccurs="0" name="InternetAddress" nillable="true"
type="xs:string" />
            <xs:element minOccurs="0" name="IntranetDnsSuffix" nillable="true"
type="xs:string" />
                <xs:element minOccurs="0" name="ServerPrepared" type="xs:boolean" />
            </xs:sequence>
        </xs:complexType>
        <xs:element name="VPNSetting" nillable="true" type="tns:VPNSetting" />
    </xs:schema>

```

6.8.5 http://schemas.microsoft.com/2003/10/Serialization/Arrays

```

<?xml version="1.0" encoding="utf-8"?>
<xs:schema xmlns:tns="http://schemas.microsoft.com/2003/10/Serialization/Arrays"
elementFormDefault="qualified"
targetNamespace="http://schemas.microsoft.com/2003/10/Serialization/Arrays"
xmlns:xs="http://www.w3.org/2001/XMLSchema">
    <xs:complexType name="ArrayOfunsignedShort">
        <xs:sequence>
            <xs:element minOccurs="0" maxOccurs="unbounded" name="unsignedShort"
type="xs:unsignedShort" />
        </xs:sequence>
    </xs:complexType>

```

```

</xs:sequence>
</xs:complexType>
<xs:element name="ArrayOfunsignedShort" nillable="true"
type="tns:ArrayOfunsignedShort" />
</xs:schema>

```

6.8.6 http://schemas.microsoft.com/2003/10/Serialization

```

<?xml version="1.0" encoding="utf-8"?>
<xs:schema xmlns:tns="http://schemas.microsoft.com/2003/10/Serialization/"
attributeFormDefault="qualified" elementFormDefault="qualified"
targetNamespace="http://schemas.microsoft.com/2003/10/Serialization/"
xmlns:xs="http://www.w3.org/2001/XMLSchema">
    <xs:element name="anyType" nillable="true" type="xs:anyType" />
    <xs:element name="anyURI" nillable="true" type="xs:anyURI" />
    <xs:element name="base64Binary" nillable="true" type="xs:base64Binary" />
    <xs:element name="boolean" nillable="true" type="xs:boolean" />
    <xs:element name="byte" nillable="true" type="xs:byte" />
    <xs:element name="dateTime" nillable="true" type="xs:dateTime" />
    <xs:element name="decimal" nillable="true" type="xs:decimal" />
    <xs:element name="double" nillable="true" type="xs:double" />
    <xs:element name="float" nillable="true" type="xs:float" />
    <xs:element name="int" nillable="true" type="xs:int" />
    <xs:element name="long" nillable="true" type="xs:long" />
    <xs:element name="QName" nillable="true" type="xs:QName" />
    <xs:element name="short" nillable="true" type="xs:short" />
    <xs:element name="string" nillable="true" type="xs:string" />
    <xs:element name="unsignedByte" nillable="true" type="xs:unsignedByte" />
    <xs:element name="unsignedInt" nillable="true" type="xs:unsignedInt" />
    <xs:element name="unsignedLong" nillable="true" type="xs:unsignedLong" />
    <xs:element name="unsignedShort" nillable="true" type="xs:unsignedShort" />
    <xs:element name="char" nillable="true" type="tns:char" />
    <xs:simpleType name="char">
        <xs:restriction base="xs:int" />
    </xs:simpleType>
    <xs:element name="duration" nillable="true" type="tns:duration" />
    <xs:simpleType name="duration">
        <xs:restriction base="xs:duration">
            <xs:pattern value="-?P{(\d*D)?(\d*H)?(\d*(\.\d*)?S)?)?" />
            <xs:minInclusive value="-P10675199DT2H48M5.4775808S" />
            <xs:maxInclusive value="P10675199DT2H48M5.4775807S" />
        </xs:restriction>
    </xs:simpleType>
    <xs:element name="guid" nillable="true" type="tns:guid" />
    <xs:simpleType name="guid">
        <xs:restriction base="xs:string">
            <xs:pattern value="[\da-fA-F]{8}-[\da-fA-F]{4}-[\da-fA-F]{4}-[\da-fA-F]{4}-[\da-fA-F]{12}" />
        </xs:restriction>
    </xs:simpleType>
    <xs:attribute name="FactoryType" type="xs:QName" />
    <xs:attribute name="Id" type="xs:ID" />
    <xs:attribute name="Ref" type="xs:IDREF" />
</xs:schema>

```

6.8.7 http://schemas.datacontract.org/2004/07/System.Net.Sockets

```

<?xml version="1.0" encoding="utf-8"?>
<xs:schema xmlns:tns="http://schemas.datacontract.org/2004/07/System.Net.Sockets"
elementFormDefault="qualified"
targetNamespace="http://schemas.datacontract.org/2004/07/System.Net.Sockets"
xmlns:xs="http://www.w3.org/2001/XMLSchema">
    <xs:import schemaLocation="" namespace="http://schemas.microsoft.com/2003/10/Serialization/" />
    <xs:simpleType name="AddressFamily">

```

```

<xs:restriction base="xs:string">
  <xs:enumeration value="Unknown">
    <xs:annotation>
      <xs:appinfo>
        <EnumerationValue
  xmlns="http://schemas.microsoft.com/2003/10/Serialization/">-1</EnumerationValue>
        </xs:appinfo>
      </xs:annotation>
    </xs:enumeration>
  <xs:enumeration value="Unspecified">
    <xs:annotation>
      <xs:appinfo>
        <EnumerationValue
  xmlns="http://schemas.microsoft.com/2003/10/Serialization/">0</EnumerationValue>
        </xs:appinfo>
      </xs:annotation>
    </xs:enumeration>
  <xs:enumeration value="Unix">
    <xs:annotation>
      <xs:appinfo>
        <EnumerationValue
  xmlns="http://schemas.microsoft.com/2003/10/Serialization/">1</EnumerationValue>
        </xs:appinfo>
      </xs:annotation>
    </xs:enumeration>
  <xs:enumeration value="InterNetwork">
    <xs:annotation>
      <xs:appinfo>
        <EnumerationValue
  xmlns="http://schemas.microsoft.com/2003/10/Serialization/">2</EnumerationValue>
        </xs:appinfo>
      </xs:annotation>
    </xs:enumeration>
  <xs:enumeration value="ImplLink">
    <xs:annotation>
      <xs:appinfo>
        <EnumerationValue
  xmlns="http://schemas.microsoft.com/2003/10/Serialization/">3</EnumerationValue>
        </xs:appinfo>
      </xs:annotation>
    </xs:enumeration>
  <xs:enumeration value="Pup">
    <xs:annotation>
      <xs:appinfo>
        <EnumerationValue
  xmlns="http://schemas.microsoft.com/2003/10/Serialization/">4</EnumerationValue>
        </xs:appinfo>
      </xs:annotation>
    </xs:enumeration>
  <xs:enumeration value="Chaos">
    <xs:annotation>
      <xs:appinfo>
        <EnumerationValue
  xmlns="http://schemas.microsoft.com/2003/10/Serialization/">5</EnumerationValue>
        </xs:appinfo>
      </xs:annotation>
    </xs:enumeration>
  <xs:enumeration value="NS">
    <xs:annotation>
      <xs:appinfo>
        <EnumerationValue
  xmlns="http://schemas.microsoft.com/2003/10/Serialization/">6</EnumerationValue>
        </xs:appinfo>
      </xs:annotation>
    </xs:enumeration>
  <xs:enumeration value="Ipx">
    <xs:annotation>
      <xs:appinfo>

```

```

        <EnumerationValue
xmlns="http://schemas.microsoft.com/2003/10/Serialization/">6</EnumerationValue>
        </xs:appinfo>
    </xs:annotation>
</xs:enumeration>
<xs:enumeration value="Iso">
    <xs:annotation>
        <xs:appinfo>
            <EnumerationValue
xmlns="http://schemas.microsoft.com/2003/10/Serialization/">7</EnumerationValue>
            </xs:appinfo>
        </xs:annotation>
    </xs:enumeration>
<xs:enumeration value="Osi">
    <xs:annotation>
        <xs:appinfo>
            <EnumerationValue
xmlns="http://schemas.microsoft.com/2003/10/Serialization/">7</EnumerationValue>
        </xs:appinfo>
    </xs:annotation>
    </xs:enumeration>
<xs:enumeration value="Ecma">
    <xs:annotation>
        <xs:appinfo>
            <EnumerationValue
xmlns="http://schemas.microsoft.com/2003/10/Serialization/">8</EnumerationValue>
        </xs:appinfo>
    </xs:annotation>
    </xs:enumeration>
<xs:enumeration value="DataKit">
    <xs:annotation>
        <xs:appinfo>
            <EnumerationValue
xmlns="http://schemas.microsoft.com/2003/10/Serialization/">9</EnumerationValue>
        </xs:appinfo>
    </xs:annotation>
    </xs:enumeration>
<xs:enumeration value="Ccitt">
    <xs:annotation>
        <xs:appinfo>
            <EnumerationValue
xmlns="http://schemas.microsoft.com/2003/10/Serialization/">10</EnumerationValue>
        </xs:appinfo>
    </xs:annotation>
    </xs:enumeration>
<xs:enumeration value="Sna">
    <xs:annotation>
        <xs:appinfo>
            <EnumerationValue
xmlns="http://schemas.microsoft.com/2003/10/Serialization/">11</EnumerationValue>
        </xs:appinfo>
    </xs:annotation>
    </xs:enumeration>
<xs:enumeration value="DecNet">
    <xs:annotation>
        <xs:appinfo>
            <EnumerationValue
xmlns="http://schemas.microsoft.com/2003/10/Serialization/">12</EnumerationValue>
        </xs:appinfo>
    </xs:annotation>
    </xs:enumeration>
<xs:enumeration value="DataLink">
    <xs:annotation>
        <xs:appinfo>
            <EnumerationValue
xmlns="http://schemas.microsoft.com/2003/10/Serialization/">13</EnumerationValue>
        </xs:appinfo>
    </xs:annotation>
    </xs:enumeration>

```

```

<xs:enumeration value="Lat">
  <xs:annotation>
    <xs:appinfo>
      <EnumerationValue
xmlns="http://schemas.microsoft.com/2003/10/Serialization/">14</EnumerationValue>
    </xs:appinfo>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="HyperChannel">
  <xs:annotation>
    <xs:appinfo>
      <EnumerationValue
xmlns="http://schemas.microsoft.com/2003/10/Serialization/">15</EnumerationValue>
    </xs:appinfo>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="AppleTalk">
  <xs:annotation>
    <xs:appinfo>
      <EnumerationValue
xmlns="http://schemas.microsoft.com/2003/10/Serialization/">16</EnumerationValue>
    </xs:appinfo>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="NetBios">
  <xs:annotation>
    <xs:appinfo>
      <EnumerationValue
xmlns="http://schemas.microsoft.com/2003/10/Serialization/">17</EnumerationValue>
    </xs:appinfo>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="VoiceView">
  <xs:annotation>
    <xs:appinfo>
      <EnumerationValue
xmlns="http://schemas.microsoft.com/2003/10/Serialization/">18</EnumerationValue>
    </xs:appinfo>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="FireFox">
  <xs:annotation>
    <xs:appinfo>
      <EnumerationValue
xmlns="http://schemas.microsoft.com/2003/10/Serialization/">19</EnumerationValue>
    </xs:appinfo>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="Banyan">
  <xs:annotation>
    <xs:appinfo>
      <EnumerationValue
xmlns="http://schemas.microsoft.com/2003/10/Serialization/">21</EnumerationValue>
    </xs:appinfo>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="Atm">
  <xs:annotation>
    <xs:appinfo>
      <EnumerationValue
xmlns="http://schemas.microsoft.com/2003/10/Serialization/">22</EnumerationValue>
    </xs:appinfo>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="InterNetworkV6">
  <xs:annotation>
    <xs:appinfo>
      <EnumerationValue
xmlns="http://schemas.microsoft.com/2003/10/Serialization/">23</EnumerationValue>

```

```

        </xs:appinfo>
    </xs:annotation>
</xs:enumeration>
<xs:enumeration value="Cluster">
    <xs:annotation>
        <xs:appinfo>
            <EnumerationValue
xmlns="http://schemas.microsoft.com/2003/10/Serialization/">24</EnumerationValue>
        </xs:appinfo>
    </xs:annotation>
</xs:enumeration>
<xs:enumeration value="Ieee12844">
    <xs:annotation>
        <xs:appinfo>
            <EnumerationValue
xmlns="http://schemas.microsoft.com/2003/10/Serialization/">25</EnumerationValue>
        </xs:appinfo>
    </xs:annotation>
</xs:enumeration>
<xs:enumeration value="Irda">
    <xs:annotation>
        <xs:appinfo>
            <EnumerationValue
xmlns="http://schemas.microsoft.com/2003/10/Serialization/">26</EnumerationValue>
        </xs:appinfo>
    </xs:annotation>
</xs:enumeration>
<xs:enumeration value="NetworkDesigners">
    <xs:annotation>
        <xs:appinfo>
            <EnumerationValue
xmlns="http://schemas.microsoft.com/2003/10/Serialization/">28</EnumerationValue>
        </xs:appinfo>
    </xs:annotation>
</xs:enumeration>
<xs:enumeration value="Max">
    <xs:annotation>
        <xs:appinfo>
            <EnumerationValue
xmlns="http://schemas.microsoft.com/2003/10/Serialization/">29</EnumerationValue>
        </xs:appinfo>
    </xs:annotation>
</xs:enumeration>
</xs:restriction>
</xs:simpleType>
<xs:element name="AddressFamily" nillable="true" type="tns:AddressFamily" />
</xs:schema>

```

6.8.8 <http://schemas.datacontract.org/2004/07/System.Net>

```

<?xml version="1.0" encoding="utf-8"?>
<xs:schema xmlns:tns="http://schemas.datacontract.org/2004/07/System.Net"
elementFormDefault="qualified"
targetNamespace="http://schemas.datacontract.org/2004/07/System.Net"
xmlns:xs="http://www.w3.org/2001/XMLSchema">
    <xs:import schemaLocation="" namespace="http://schemas.datacontract.org/2004/07/System.Net.Sockets" />
    <xs:import schemaLocation="" namespace="http://schemas.microsoft.com/2003/10/Serialization/Arrays" />
    <xs:complexType name="IPAddress">
        <xs:sequence>
            <xs:element name="m_Address" type="xs:long" />
            <xs:element
xmlns:q1="http://schemas.datacontract.org/2004/07/System.Net.Sockets" name="m_Family" type="q1:AddressFamily" />
            <xs:element name="m_HashCode" type="xs:int" />

```

```

<xs:element xmlns:q2="http://schemas.microsoft.com/2003/10/Serialization/Arrays"
name="m_Numbers" nillable="true" type="q2:ArrayOfunsignedShort" />
    <xs:element name="m_ScopeId" type="xs:long" />
</xs:sequence>
</xs:complexType>
<xs:element name="IPAddress" nillable="true" type="tns:IPAddress" />
</xs:schema>

```

6.9 Domain Infrastructure Service WSDL

6.9.1 wsdl

```

<?xml version="1.0" encoding="utf-8"?>
<wsdl:definitions xmlns:wsap="http://schemas.xmlsoap.org/ws/2004/08/addressing/policy"
xmlns:wsa10="http://www.w3.org/2005/08/addressing" xmlns:tns="http://tempuri.org/"
xmlns:msc="http://schemas.microsoft.com/ws/2005/12/wsdl/contract"
xmlns:soapenc="http://schemas.xmlsoap.org/soap/encoding/"
xmlns:soap="http://schemas.xmlsoap.org/wsdl/soap/"
xmlns:wsp="http://schemas.xmlsoap.org/ws/2004/09/policy"
xmlns:wsam="http://www.w3.org/2007/05/addressing/metadata"
xmlns:wsa="http://schemas.xmlsoap.org/ws/2004/08/addressing"
xmlns:wsaw="http://www.w3.org/2006/05/addressing/wsdl"
xmlns:soap12="http://schemas.xmlsoap.org/wsdl/soap12/" xmlns:wsu="http://docs.oasis-
open.org/wss/2004/01/oasis-200401-wss-wssecurity-utility-1.0.xsd"
xmlns:xsd="http://www.w3.org/2001/XMLSchema" name="DomainProviderManager"
targetNamespace="http://tempuri.org/" xmlns:wsdl="http://schemas.xmlsoap.org/wsdl/">
    <wsp:Policy wsu:Id="CustomBinding_IDomainMaintenanceManager_policy">
        <wsp:ExactlyOne>
            <wsp:All>
                <msb:BinaryEncoding
xmlns:msb="http://schemas.microsoft.com/ws/2004/04/mspolicy/netbinary1" />
                <sp:TransportBinding
xmlns:sp="http://schemas.xmlsoap.org/ws/2005/07/securitypolicy">
                    <wsp:Policy>
                        <sp:TransportToken>
                            <wsp:Policy>
                                <msf:WindowsTransportSecurity
xmlns:msf="http://schemas.microsoft.com/ws/2006/05/framing/policy">
                                    <msf:ProtectionLevel>EncryptAndSign</msf:ProtectionLevel>
                                    </msf:WindowsTransportSecurity>
                                </wsp:Policy>
                            </sp:TransportToken>
                            <sp:AlgorithmSuite>
                                <wsp:Policy>
                                    <sp:Basic256 />
                                </wsp:Policy>
                            </sp:AlgorithmSuite>
                            <sp:Layout>
                                <wsp:Policy>
                                    <sp:Strict />
                                </wsp:Policy>
                            </sp:Layout>
                        </wsp:Policy>
                    </sp:TransportBinding>
                    <wsaw:UsingAddressing />
                </wsp:All>
            </wsp:ExactlyOne>
        </wsp:Policy>
    <wsdl:types>
        <xsd:schema targetNamespace="http://tempuri.org/Imports">
            <xsd:import schemaLocation="" namespace="http://tempuri.org/" />
            <xsd:import schemaLocation="" namespace="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.RemoteA
ccess.Domains" />
            <xsd:import schemaLocation="" namespace="http://schemas.microsoft.com/2003/10/Serialization/" />

```

```

<xsd:import schemaLocation="" namespace="http://schemas.datacontract.org/2004/07/System" />
<xsd:import schemaLocation="" namespace="http://schemas.datacontract.org/2004/07/System.Net" />
<xsd:import schemaLocation="" namespace="http://schemas.datacontract.org/2004/07/System.Net.Sockets" />
<xsd:import schemaLocation="" namespace="http://schemas.microsoft.com/2003/10/Serialization/Arrays" />
<xsd:import schemaLocation="" namespace="http://schemas.datacontract.org/2004/07/System.Collections.ObjectModel" />
</xsd:schema>
</wsdl:types>
<wsdl:message name="IDomainMaintenanceManager_SetCredentials_InputMessage">
<wsdl:part name="parameters" element="tns:SetCredentials" />
</wsdl:message>
<wsdl:message name="IDomainMaintenanceManager_SetCredentials_OutputMessage">
<wsdl:part name="parameters" element="tns:SetCredentialsResponse" />
</wsdl:message>
<wsdl:message name="IDomainMaintenanceManager_SetCredentials_DomainManagerFault_FaultMessage">
<wsdl:part
xmlns:q1="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.RemoteAccess.Domains" name="detail" element="q1:DomainManagerFault" />
</wsdl:message>
<wsdl:message name="IDomainMaintenanceManager_ValidateCredentials_InputMessage">
<wsdl:part name="parameters" element="tns:ValidateCredentials" />
</wsdl:message>
<wsdl:message name="IDomainMaintenanceManager_ValidateCredentials_OutputMessage">
<wsdl:part name="parameters" element="tns:ValidateCredentialsResponse" />
</wsdl:message>
<wsdl:message name="IDomainMaintenanceManager_ValidateCredentials_DomainManagerFaultFault_FaultMessage">
<wsdl:part
xmlns:q2="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.RemoteAccess.Domains" name="detail" element="q2:DomainManagerFault" />
</wsdl:message>
<wsdl:message name="IDomainMaintenanceManager_UpdateDnsRecords_InputMessage">
<wsdl:part name="parameters" element="tns:UpdateDnsRecords" />
</wsdl:message>
<wsdl:message name="IDomainMaintenanceManager_UpdateDnsRecords_OutputMessage">
<wsdl:part name="parameters" element="tns:UpdateDnsRecordsResponse" />
</wsdl:message>
<wsdl:message name="IDomainMaintenanceManager_UpdateDnsRecords_ArgumentExceptionFault_FaultMessage">
<wsdl:part xmlns:q3="http://schemas.datacontract.org/2004/07/System" name="detail" element="q3:ArgumentException" />
</wsdl:message>
<wsdl:message name="IDomainMaintenanceManager_UpdateDnsRecords_DomainManagerFaultFault_FaultMessage">
<wsdl:part
xmlns:q4="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.RemoteAccess.Domains" name="detail" element="q4:DomainManagerFault" />
</wsdl:message>
<wsdl:message name="IDomainMaintenanceManager_QueryAddressFromDNS_InputMessage">
<wsdl:part name="parameters" element="tns:QueryAddressFromDNS" />
</wsdl:message>
<wsdl:message name="IDomainMaintenanceManager_QueryAddressFromDNS_OutputMessage">
<wsdl:part name="parameters" element="tns:QueryAddressFromDNSResponse" />
</wsdl:message>
<wsdl:message name="IDomainMaintenanceManager_QueryAddressFromDNS_DomainManagerFaultFault_FaultMessage">
<wsdl:part
xmlns:q5="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.RemoteAccess.Domains" name="detail" element="q5:DomainManagerFault" />
</wsdl:message>
<wsdl:message name="IDomainMaintenanceManager_QueryAddressFromProvider_InputMessage">
<wsdl:part name="parameters" element="tns:QueryAddressFromProvider" />
</wsdl:message>

```

```

<wsdl:message
name="IDomainMaintenanceManager_QueryAddressFromProvider_OutputMessage">
  <wsdl:part name="parameters" element="tns:QueryAddressFromProviderResponse" />
</wsdl:message>
<wsdl:message
name="IDomainMaintenanceManager QueryAddressFromProvider DomainManagerFaultFault FaultMessage">
  <wsdl:part
xmlns:q6="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.RemoteAccess.Domains" name="detail" element="q6:DomainManagerFault" />
</wsdl:message>
<wsdl:message name="IDomainMaintenanceManager_TestConnection_InputMessage">
  <wsdl:part name="parameters" element="tns:TestConnection" />
</wsdl:message>
<wsdl:message name="IDomainMaintenanceManager_TestConnection_OutputMessage">
  <wsdl:part name="parameters" element="tns:TestConnectionResponse" />
</wsdl:message>
<wsdl:message
name="IDomainMaintenanceManager TestConnection DomainManagerFaultFault FaultMessage">
  <wsdl:part
xmlns:q7="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.RemoteAccess.Domains" name="detail" element="q7:DomainManagerFault" />
</wsdl:message>
<wsdl:message name="IDomainMaintenanceManager_GetDomainState_InputMessage">
  <wsdl:part name="parameters" element="tns:GetDomainState" />
</wsdl:message>
<wsdl:message name="IDomainMaintenanceManager_GetDomainState_OutputMessage">
  <wsdl:part name="parameters" element="tns:GetDomainStateResponse" />
</wsdl:message>
<wsdl:message
name="IDomainMaintenanceManager GetDomainState DomainManagerFaultFault FaultMessage">
  <wsdl:part
xmlns:q8="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.RemoteAccess.Domains" name="detail" element="q8:DomainManagerFault" />
</wsdl:message>
<wsdl:message name="IDomainMaintenanceManager_GetCertificateState_InputMessage">
  <wsdl:part name="parameters" element="tns:GetCertificateState" />
</wsdl:message>
<wsdl:message name="IDomainMaintenanceManager_GetCertificateState_OutputMessage">
  <wsdl:part name="parameters" element="tns:GetCertificateStateResponse" />
</wsdl:message>
<wsdl:message
name="IDomainMaintenanceManager_GetCertificateState_DomainManagerFaultFault_FaultMessage">
  <wsdl:part
xmlns:q9="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.RemoteAccess.Domains" name="detail" element="q9:DomainManagerFault" />
</wsdl:message>
<wsdl:message
name="IDomainMaintenanceManager_GetDomainNameConfiguration_InputMessage">
  <wsdl:part name="parameters" element="tns:GetDomainNameConfiguration" />
</wsdl:message>
<wsdl:message
name="IDomainMaintenanceManager_GetDomainNameConfiguration_OutputMessage">
  <wsdl:part name="parameters" element="tns:GetDomainNameConfigurationResponse" />
</wsdl:message>
<wsdl:message name="IDomainMaintenanceManager_GetDynamicDNSInfo_InputMessage">
  <wsdl:part name="parameters" element="tns:GetDynamicDNSInfo" />
</wsdl:message>
<wsdl:message name="IDomainMaintenanceManager_GetDynamicDNSInfo_OutputMessage">
  <wsdl:part name="parameters" element="tns:GetDynamicDNSInfoResponse" />
</wsdl:message>
<wsdl:message name="IDomainMaintenanceManager_GetSettings_InputMessage">
  <wsdl:part name="parameters" element="tns:GetSettings" />
</wsdl:message>
<wsdl:message name="IDomainMaintenanceManager_GetSettings_OutputMessage">
  <wsdl:part name="parameters" element="tns:GetSettingsResponse" />
</wsdl:message>
<wsdl:portType name="IDomainMaintenanceManager">
  <wsdl:operation name="SetCredentials">
```

```

        <wsdl:input
wsaw:Action="http://tempuri.org/IDomainMaintenanceManager/SetCredentials"
message="tns:IDomainMaintenanceManager_SetCredentials_InputMessage" />
        <wsdl:output
wsaw:Action="http://tempuri.org/IDomainMaintenanceManager/SetCredentialsResponse"
message="tns:IDomainMaintenanceManager SetCredentials OutputMessage" />
        <wsdl:fault
wsaw:Action="http://tempuri.org/IDomainMaintenanceManager/SetCredentialsDomainManagerFaultF
ault" name="DomainManagerFaultFault"
message="tns:IDomainMaintenanceManager_SetCredentials_DomainManagerFaultFault_FaultMessage"
/>
        </wsdl:operation>
        <wsdl:operation name="ValidateCredentials">
            <wsdl:input
wsaw:Action="http://tempuri.org/IDomainMaintenanceManager/ValidateCredentials"
message="tns:IDomainMaintenanceManager_ValidateCredentials_InputMessage" />
            <wsdl:output
wsaw:Action="http://tempuri.org/IDomainMaintenanceManager/ValidateCredentialsResponse"
message="tns:IDomainMaintenanceManager ValidateCredentials OutputMessage" />
            <wsdl:fault
wsaw:Action="http://tempuri.org/IDomainMaintenanceManager/ValidateCredentialsDomainManagerF
aultFault" name="DomainManagerFaultFault"
message="tns:IDomainMaintenanceManager ValidateCredentials DomainManagerFaultFault FaultMes
sage" />
            </wsdl:operation>
            <wsdl:operation name="UpdateDnsRecords">
                <wsdl:input
wsaw:Action="http://tempuri.org/IDomainMaintenanceManager/UpdateDnsRecords"
message="tns:IDomainMaintenanceManager UpdateDnsRecords InputMessage" />
                <wsdl:output
wsaw:Action="http://tempuri.org/IDomainMaintenanceManager/UpdateDnsRecordsResponse"
message="tns:IDomainMaintenanceManager_UpdateDnsRecords_OutputMessage" />
                <wsdl:fault
wsaw:Action="http://tempuri.org/IDomainMaintenanceManager/UpdateDnsRecordsArgumentException
Fault" name="ArgumentExceptionFault"
message="tns:IDomainMaintenanceManager UpdateDnsRecords ArgumentExceptionFault FaultMessage
" />
                <wsdl:fault
wsaw:Action="http://tempuri.org/IDomainMaintenanceManager/UpdateDnsRecordsDomainManagerFau
tFault" name="DomainManagerFaultFault"
message="tns:IDomainMaintenanceManager_UpdateDnsRecords_DomainManagerFaultFault_FaultMessag
e" />
                </wsdl:operation>
                <wsdl:operation name="QueryAddressFromDNS">
                    <wsdl:input
wsaw:Action="http://tempuri.org/IDomainMaintenanceManager/QueryAddressFromDNS"
message="tns:IDomainMaintenanceManager_QueryAddressFromDNS_InputMessage" />
                    <wsdl:output
wsaw:Action="http://tempuri.org/IDomainMaintenanceManager/QueryAddressFromDNSResponse"
message="tns:IDomainMaintenanceManager_QueryAddressFromDNS_OutputMessage" />
                    <wsdl:fault
wsaw:Action="http://tempuri.org/IDomainMaintenanceManager/QueryAddressFromDNSDomainManagerF
aultFault" name="DomainManagerFaultFault"
message="tns:IDomainMaintenanceManager QueryAddressFromDNS DomainManagerFaultFault FaultMes
sage" />
                    </wsdl:operation>
                    <wsdl:operation name="QueryAddressFromProvider">
                        <wsdl:input
wsaw:Action="http://tempuri.org/IDomainMaintenanceManager/QueryAddressFromProvider"
message="tns:IDomainMaintenanceManager_QueryAddressFromProvider_InputMessage" />
                        <wsdl:output
wsaw:Action="http://tempuri.org/IDomainMaintenanceManager/QueryAddressFromProviderResponse"
message="tns:IDomainMaintenanceManager QueryAddressFromProvider OutputMessage" />
                        <wsdl:fault
wsaw:Action="http://tempuri.org/IDomainMaintenanceManager/QueryAddressFromProviderDomainMan
agerFaultFault" name="DomainManagerFaultFault"
message="tns:IDomainMaintenanceManager_QueryAddressFromProvider_DomainManagerFaultFault_Fau
ltMessage" />
                    </wsdl:operation>

```

```

        <wsdl:operation name="TestConnection">
            <wsdl:input
wsaw:Action="http://tempuri.org/IDomainMaintenanceManager/TestConnection"
message="tns:IDomainMaintenanceManager_TestConnection_InputMessage" />
            <wsdl:output
wsaw:Action="http://tempuri.org/IDomainMaintenanceManager/TestConnectionResponse"
message="tns:IDomainMaintenanceManager_TestConnection_OutputMessage" />
            <wsdl:fault
wsaw:Action="http://tempuri.org/IDomainMaintenanceManager/TestConnectionDomainManagerFaultF
ault" name="DomainManagerFaultFault"
message="tns:IDomainMaintenanceManager TestConnection DomainManagerFaultFault FaultMessage"
/>
        </wsdl:operation>
        <wsdl:operation name="GetDomainState">
            <wsdl:input
wsaw:Action="http://tempuri.org/IDomainMaintenanceManager/GetDomainState"
message="tns:IDomainMaintenanceManager GetDomainState InputMessage" />
            <wsdl:output
wsaw:Action="http://tempuri.org/IDomainMaintenanceManager/GetDomainStateResponse"
message="tns:IDomainMaintenanceManager_GetDomainState_OutputMessage" />
            <wsdl:fault
wsaw:Action="http://tempuri.org/IDomainMaintenanceManager/GetDomainStateDomainManagerFaultF
ault" name="DomainManagerFaultFault"
message="tns:IDomainMaintenanceManager_GetDomainState_DomainManagerFaultFault_FaultMessage"
/>
        </wsdl:operation>
        <wsdl:operation name="GetCertificateState">
            <wsdl:input
wsaw:Action="http://tempuri.org/IDomainMaintenanceManager/GetCertificateState"
message="tns:IDomainMaintenanceManager_GetCertificateState_InputMessage" />
            <wsdl:output
wsaw:Action="http://tempuri.org/IDomainMaintenanceManager/GetCertificateStateResponse"
message="tns:IDomainMaintenanceManager_GetCertificateState_OutputMessage" />
            <wsdl:fault
wsaw:Action="http://tempuri.org/IDomainMaintenanceManager/GetCertificateStateDomainManagerF
aultFault" name="DomainManagerFaultFault"
message="tns:IDomainMaintenanceManager_GetCertificateState_DomainManagerFaultFault_FaultMes
sage" />
        </wsdl:operation>
        <wsdl:operation name="GetDomainNameConfiguration">
            <wsdl:input
wsaw:Action="http://tempuri.org/IDomainMaintenanceManager/GetDomainNameConfiguration"
message="tns:IDomainMaintenanceManager_GetDomainNameConfiguration_InputMessage" />
            <wsdl:output
wsaw:Action="http://tempuri.org/IDomainMaintenanceManager/GetDomainNameConfigurationRespons
e" message="tns:IDomainMaintenanceManager GetDomainNameConfiguration OutputMessage" />
        </wsdl:operation>
        <wsdl:operation name="GetDynamicDNSInfo">
            <wsdl:input
wsaw:Action="http://tempuri.org/IDomainMaintenanceManager/GetDynamicDNSInfo"
message="tns:IDomainMaintenanceManager_GetDynamicDNSInfo_InputMessage" />
            <wsdl:output
wsaw:Action="http://tempuri.org/IDomainMaintenanceManager/GetDynamicDNSInfoResponse"
message="tns:IDomainMaintenanceManager GetDynamicDNSInfo_OutputMessage" />
        </wsdl:operation>
        <wsdl:operation name="GetSettings">
            <wsdl:input
wsaw:Action="http://tempuri.org/IDomainMaintenanceManager/GetSettings"
message="tns:IDomainMaintenanceManager GetSettings InputMessage" />
            <wsdl:output
wsaw:Action="http://tempuri.org/IDomainMaintenanceManager/GetSettingsResponse"
message="tns:IDomainMaintenanceManager_GetSettings_OutputMessage" />
        </wsdl:operation>
        </wsdl:portType>
        <wsdl:binding name="CustomBinding_IDomainMaintenanceManager"
type="tns:IDDomainMaintenanceManager">
            <wsp:PolicyReference URI="#CustomBinding_IDDomainMaintenanceManager_policy" />
            <soap12:binding transport="http://schemas.microsoft.com/soap/tcp" />
            <wsdl:operation name="SetCredentials">

```

```

        <soap12:operation
soapAction="http://tempuri.org/IDomainMaintenanceManager/SetCredentials" style="document"
/>
        <wsdl:input>
            <soap12:body use="literal" />
        </wsdl:input>
        <wsdl:output>
            <soap12:body use="literal" />
        </wsdl:output>
        <wsdl:fault name="DomainManagerFaultFault">
            <soap12:fault use="literal" name="DomainManagerFaultFault" namespace="" />
        </wsdl:fault>
    </wsdl:operation>
    <wsdl:operation name="ValidateCredentials">
        <soap12:operation
soapAction="http://tempuri.org/IDomainMaintenanceManager/ValidateCredentials" style="document" />
        <wsdl:input>
            <soap12:body use="literal" />
        </wsdl:input>
        <wsdl:output>
            <soap12:body use="literal" />
        </wsdl:output>
        <wsdl:fault name="DomainManagerFaultFault">
            <soap12:fault use="literal" name="DomainManagerFaultFault" namespace="" />
        </wsdl:fault>
    </wsdl:operation>
    <wsdl:operation name="UpdateDnsRecords">
        <soap12:operation
soapAction="http://tempuri.org/IDomainMaintenanceManager/UpdateDnsRecords" style="document" />
        <wsdl:input>
            <soap12:body use="literal" />
        </wsdl:input>
        <wsdl:output>
            <soap12:body use="literal" />
        </wsdl:output>
        <wsdl:fault name="ArgumentExceptionFault">
            <soap12:fault use="literal" name="ArgumentExceptionFault" namespace="" />
        </wsdl:fault>
        <wsdl:fault name="DomainManagerFaultFault">
            <soap12:fault use="literal" name="DomainManagerFaultFault" namespace="" />
        </wsdl:fault>
    </wsdl:operation>
    <wsdl:operation name="QueryAddressFromDNS">
        <soap12:operation
soapAction="http://tempuri.org/IDomainMaintenanceManager/QueryAddressFromDNS" style="document" />
        <wsdl:input>
            <soap12:body use="literal" />
        </wsdl:input>
        <wsdl:output>
            <soap12:body use="literal" />
        </wsdl:output>
        <wsdl:fault name="DomainManagerFaultFault">
            <soap12:fault use="literal" name="DomainManagerFaultFault" namespace="" />
        </wsdl:fault>
    </wsdl:operation>
    <wsdl:operation name="QueryAddressFromProvider">
        <soap12:operation
soapAction="http://tempuri.org/IDomainMaintenanceManager/QueryAddressFromProvider" style="document" />
        <wsdl:input>
            <soap12:body use="literal" />
        </wsdl:input>
        <wsdl:output>
            <soap12:body use="literal" />
        </wsdl:output>
        <wsdl:fault name="DomainManagerFaultFault">

```

```

        <soap12:fault use="literal" name="DomainManagerFaultFault" namespace="" />
    </wsdl:fault>
</wsdl:operation>
<wsdl:operation name="TestConnection">
    <soap12:operation
soapAction="http://tempuri.org/IDomainMaintenanceManager/TestConnection" style="document"
/>
    <wsdl:input>
        <soap12:body use="literal" />
    </wsdl:input>
    <wsdl:output>
        <soap12:body use="literal" />
    </wsdl:output>
    <wsdl:fault name="DomainManagerFaultFault">
        <soap12:fault use="literal" name="DomainManagerFaultFault" namespace="" />
    </wsdl:fault>
</wsdl:operation>
<wsdl:operation name="GetDomainState">
    <soap12:operation
soapAction="http://tempuri.org/IDomainMaintenanceManager/GetDomainState" style="document"
/>
    <wsdl:input>
        <soap12:body use="literal" />
    </wsdl:input>
    <wsdl:output>
        <soap12:body use="literal" />
    </wsdl:output>
    <wsdl:fault name="DomainManagerFaultFault">
        <soap12:fault use="literal" name="DomainManagerFaultFault" namespace="" />
    </wsdl:fault>
</wsdl:operation>
<wsdl:operation name="GetCertificateState">
    <soap12:operation
soapAction="http://tempuri.org/IDomainMaintenanceManager/GetCertificateState"
style="document" />
    <wsdl:input>
        <soap12:body use="literal" />
    </wsdl:input>
    <wsdl:output>
        <soap12:body use="literal" />
    </wsdl:output>
    <wsdl:fault name="DomainManagerFaultFault">
        <soap12:fault use="literal" name="DomainManagerFaultFault" namespace="" />
    </wsdl:fault>
</wsdl:operation>
<wsdl:operation name="GetDomainNameConfiguration">
    <soap12:operation
soapAction="http://tempuri.org/IDomainMaintenanceManager/GetDomainNameConfiguration"
style="document" />
    <wsdl:input>
        <soap12:body use="literal" />
    </wsdl:input>
    <wsdl:output>
        <soap12:body use="literal" />
    </wsdl:output>
    <wsdl:fault name="DomainManagerFaultFault">
        <soap12:fault use="literal" name="DomainManagerFaultFault" namespace="" />
    </wsdl:fault>
</wsdl:operation>
<wsdl:operation name="GetDynamicDNSInfo">
    <soap12:operation
soapAction="http://tempuri.org/IDomainMaintenanceManager/GetDynamicDNSInfo"
style="document" />
    <wsdl:input>
        <soap12:body use="literal" />
    </wsdl:input>
    <wsdl:output>
        <soap12:body use="literal" />
    </wsdl:output>
    <wsdl:fault name="DomainManagerFaultFault">
        <soap12:fault use="literal" name="DomainManagerFaultFault" namespace="" />
    </wsdl:fault>
</wsdl:operation>
<wsdl:operation name="GetSettings">

```

```

<soap12:operation
soapAction="http://tempuri.org/IDomainMaintenanceManager/GetSettings" style="document" />
<wsdl:input>
    <soap12:body use="literal" />
</wsdl:input>
<wsdl:output>
    <soap12:body use="literal" />
</wsdl:output>
</wsdl:operation>
</wsdl:binding>
<wsdl:service name="DomainProviderManager">
    <wsdl:port name="CustomBinding_IDomainMaintenanceManager"
binding="tns:CustomBinding_IDomainMaintenanceManager">
        <soap12:address
location="net.tcp://serverName:6602/Microsoft.WindowsServerSolutions.DomainProviderManager/
Microsoft.WindowsServerSolutions.RemoteAccess.Domains.IDomainMaintenanceManager" />
        <wsa10:EndpointReference>

<wsa10:Address>net.tcp://serverName:6602/Microsoft.WindowsServerSolutions.DomainProviderMan
ager/Microsoft.WindowsServerSolutions.RemoteAccess.Domains.IDDomainMaintenanceManager</wsa10
:Address>
        <Identity xmlns="http://schemas.xmlsoap.org/ws/2006/02/addressingidentity">
            <Spn>host/serverName.domain</Spn>
        </Identity>
        </wsa10:EndpointReference>
    </wsdl:port>
</wsdl:service>
</wsdl:definitions>

```

6.9.2 http://tempuri.org

```

<?xml version="1.0" encoding="utf-8"?>
<xsschema xmlns:tns="http://tempuri.org/" elementFormDefault="qualified"
targetNamespace="http://tempuri.org/" xmlns:xs="http://www.w3.org/2001/XMLSchema">
    <xss:import schemaLocation="" namespace="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.RemoteA
ccess.Domains" />
    <xss:import schemaLocation="" namespace="http://schemas.datacontract.org/2004/07/System.Net" />
<xss:element name="SetCredentials">
    <xss:complexType>
        <xss:sequence>
            <xss:element
xmlns:q1="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.RemoteAc
cess.Domains" minOccurs="0" name="credentials" nillable="true"
type="q1:DomainProviderCredentials" />
            </xss:sequence>
        </xss:complexType>
    </xss:element>
<xss:element name="SetCredentialsResponse">
    <xss:complexType>
        <xss:sequence>
            <xss:element minOccurs="0" name="SetCredentialsResult" type="xs:boolean" />
        </xss:sequence>
    </xss:complexType>
</xss:element>
<xss:element name="ValidateCredentials">
    <xss:complexType>
        <xss:sequence />
    </xss:complexType>
</xss:element>
<xss:element name="ValidateCredentialsResponse">
    <xss:complexType>
        <xss:sequence>
            <xss:element minOccurs="0" name="ValidateCredentialsResult" type="xs:boolean" />
        </xss:sequence>
    </xss:complexType>
</xss:element>
</xss:sequence>

```

```

        </xs:complexType>
    </xs:element>
    <xs:element name="UpdateDnsRecords">
        <xs:complexType>
            <xs:sequence>
                <xs:element
xmlns:q2="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.RemoteAccess.Domains" minOccurs="0" name="records" nillable="true" type="q2:ArrayOfDnsRecord" />
            </xs:sequence>
        </xs:complexType>
    </xs:element>
    <xs:element name="UpdateDnsRecordsResponse">
        <xs:complexType>
            <xs:sequence>
                <xs:element minOccurs="0" name="UpdateDnsRecordsResult" type="xs:boolean" />
            </xs:sequence>
        </xs:complexType>
    </xs:element>
    <xs:element name="QueryAddressFromDNS">
        <xs:complexType>
            <xs:sequence />
        </xs:complexType>
    </xs:element>
    <xs:element name="QueryAddressFromDNSResponse">
        <xs:complexType>
            <xs:sequence>
                <xs:element xmlns:q3="http://schemas.datacontract.org/2004/07/System.Net"
minOccurs="0" name="QueryAddressFromDNSResult" nillable="true" type="q3:IPAddress" />
            </xs:sequence>
        </xs:complexType>
    </xs:element>
    <xs:element name="QueryAddressFromProvider">
        <xs:complexType>
            <xs:sequence />
        </xs:complexType>
    </xs:element>
    <xs:element name="QueryAddressFromProviderResponse">
        <xs:complexType>
            <xs:sequence>
                <xs:element xmlns:q4="http://schemas.datacontract.org/2004/07/System.Net"
minOccurs="0" name="QueryAddressFromProviderResult" nillable="true" type="q4:IPAddress" />
            </xs:sequence>
        </xs:complexType>
    </xs:element>
    <xs:element name="TestConnection">
        <xs:complexType>
            <xs:sequence />
        </xs:complexType>
    </xs:element>
    <xs:element name="TestConnectionResponse">
        <xs:complexType>
            <xs:sequence>
                <xs:element minOccurs="0" name="TestConnectionResult" type="xs:boolean" />
            </xs:sequence>
        </xs:complexType>
    </xs:element>
    <xs:element name="GetDomainState">
        <xs:complexType>
            <xs:sequence />
        </xs:complexType>
    </xs:element>
    <xs:element name="GetDomainStateResponse">
        <xs:complexType>
            <xs:sequence>
                <xs:element
xmlns:q5="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.RemoteAccess.Domains" minOccurs="0" name="GetDomainStateResult" nillable="true"
type="q5:DomainState" />
            </xs:sequence>
        </xs:complexType>
    </xs:element>

```

```

        </xs:complexType>
    </xs:element>
<xs:element name="GetCertificateState">
    <xs:complexType>
        <xs:sequence />
    </xs:complexType>
</xs:element>
<xs:element name="GetCertificateStateResponse">
    <xs:complexType>
        <xs:sequence>
            <xs:element
                xmlns:q6="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.RemoteAccess.Domains" minOccurs="0" name="GetCertificateStateResult" nillable="true"
                type="q6:CertificateState" />
        </xs:sequence>
    </xs:complexType>
</xs:element>
<xs:element name="GetDomainNameConfiguration">
    <xs:complexType>
        <xs:sequence />
    </xs:complexType>
</xs:element>
<xs:element name="GetDomainNameConfigurationResponse">
    <xs:complexType>
        <xs:sequence>
            <xs:element
                xmlns:q7="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.RemoteAccess.Domains" minOccurs="0" name="GetDomainNameConfigurationResult" nillable="true"
                type="q7:DomainNameConfiguration" />
        </xs:sequence>
    </xs:complexType>
</xs:element>
<xs:element name="GetDynamicDNSInfo">
    <xs:complexType>
        <xs:sequence />
    </xs:complexType>
</xs:element>
<xs:element name="GetDynamicDNSInfoResponse">
    <xs:complexType>
        <xs:sequence>
            <xs:element
                xmlns:q8="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.RemoteAccess.Domains" minOccurs="0" name="GetDynamicDNSInfoResult" nillable="true"
                type="q8:DynamicDNSInfo" />
        </xs:sequence>
    </xs:complexType>
</xs:element>
<xs:element name="GetSettings">
    <xs:complexType>
        <xs:sequence />
    </xs:complexType>
</xs:element>
<xs:element name="GetSettingsResponse">
    <xs:complexType>
        <xs:sequence>
            <xs:element
                xmlns:q9="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.RemoteAccess.Domains" minOccurs="0" name="GetSettingsResult" nillable="true"
                type="q9:DomainProviderManagerSettings" />
        </xs:sequence>
    </xs:complexType>
</xs:element>
</xs:schema>

```

6.9.3 <http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.RemoteAccess.Domains>

```
<?xml version="1.0" encoding="utf-8"?>
<xs:schema xmlns:ser="http://schemas.microsoft.com/2003/10/Serialization/"
  xmlns:tns="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.RemoteA
  ccess.Domains" elementFormDefault="qualified"
  targetNamespace="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.R
  emoteAccess.Domains" xmlns:xs="http://www.w3.org/2001/XMLSchema">
    <xs:import schemaLocation="" namespace="http://schemas.microsoft.com/2003/10/Serialization/" />
    <xs:import schemaLocation="" namespace="http://schemas.datacontract.org/2004/07/System.Net" />
    <xs:import schemaLocation="" namespace="http://schemas.datacontract.org/2004/07/System.Collections.ObjectModel" />
    <xs:complexType name="DomainProviderCredentials">
      <xs:sequence>
        <xs:element minOccurs="0" name="AccessToken" nillable="true" type="xs:string" />
        <xs:element minOccurs="0" name="Password" nillable="true" type="xs:string" />
        <xs:element minOccurs="0" name="UserName" nillable="true" type="xs:string" />
      </xs:sequence>
    </xs:complexType>
    <xs:element name="DomainProviderCredentials" nillable="true" type="tns:DomainProviderCredentials" />
    <xs:complexType name="DomainManagerFault">
      <xs:sequence>
        <xs:element minOccurs="0" name="Detail" nillable="true" type="xs:string" />
        <xs:element minOccurs="0" name="Message" nillable="true" type="xs:string" />
        <xs:element minOccurs="0" name="Reason" type="tns:FailureReason" />
      </xs:sequence>
    </xs:complexType>
    <xs:element name="DomainManagerFault" nillable="true" type="tns:DomainManagerFault" />
  </>
  <xs:simpleType name="FailureReason">
    <xs:restriction base="xs:string">
      <xs:enumeration value="Unknown" />
      <xs:enumeration value="InvalidCredentials" />
      <xs:enumeration value="InvalidDomainName" />
      <xs:enumeration value="QuotaExceeded" />
      <xs:enumeration value="PurchaseNotStarted" />
      <xs:enumeration value="PurchaseFailed" />
      <xs:enumeration value="PendingCustomerInterventionRequired" />
      <xs:enumeration value="InRenewalCustomerInterventionRequired" />
      <xs:enumeration value="RenewalFailed" />
      <xs:enumeration value="RemoteProviderFailure" />
      <xs:enumeration value="CommunicationFailure" />
      <xs:enumeration value="LocalProviderFailure" />
      <xs:enumeration value="CertificateInstallFailure" />
      <xs:enumeration value="CertificateFileBroken" />
      <xs:enumeration value="CertificateNotTrusted" />
      <xs:enumeration value="CertificateBeforeValidPeriod" />
      <xs:enumeration value="CertificateNoPrivateKey" />
      <xs:enumeration value="CertificateFileBrokenOrPasswordWrong" />
    </xs:restriction>
  </xs:simpleType>
  <xs:element name="FailureReason" nillable="true" type="tns:FailureReason" />
  <xs:complexType name="ArrayOfDnsRecord">
    <xs:sequence>
      <xs:element minOccurs="0" maxOccurs="unbounded" name="DnsRecord" nillable="true" type="tns:DnsRecord" />
    </xs:sequence>
  </xs:complexType>
  <xs:element name="ArrayOfDnsRecord" nillable="true" type="tns:ArrayOfDnsRecord" />
  <xs:complexType name="DnsRecord">
    <xs:sequence>
      <xs:element minOccurs="0" name="Label" nillable="true" type="xs:string" />
      <xs:element minOccurs="0" name="TimeToLive" type="ser:duration" />
    </xs:sequence>
  </xs:complexType>
</xs:complexType>
```

```

<xs:element name="DnsRecord" nillable="true" type="tns:DnsRecord" />
<xs:complexType name="ARecord">
    <xs:complexContent mixed="false">
        <xs:extension base="tns:DnsRecord">
            <xs:sequence>
                <xs:element xmlns:q1="http://schemas.datacontract.org/2004/07/System.Net"
minOccurs="0" name="Address" nillable="true" type="q1:IPAddress" />
            </xs:sequence>
        </xs:extension>
    </xs:complexContent>
</xs:complexType>
<xs:element name="ARecord" nillable="true" type="tns:ARecord" />
<xs:complexType name="MXRecord">
    <xs:complexContent mixed="false">
        <xs:extension base="tns:DnsRecord">
            <xs:sequence>
                <xs:element minOccurs="0" name="MailExchange" nillable="true"
type="xs:string" />
                    <xs:element minOccurs="0" name="MailExchangePreference" type="xs:int" />
                </xs:sequence>
            </xs:extension>
        </xs:complexContent>
    </xs:complexType>
<xs:element name="MXRecord" nillable="true" type="tns:MXRecord" />
<xs:complexType name="SrvRecord">
    <xs:complexContent mixed="false">
        <xs:extension base="tns:DnsRecord">
            <xs:sequence>
                <xs:element minOccurs="0" name="Port" type="xs:int" />
                <xs:element minOccurs="0" name="Priority" type="xs:int" />
                <xs:element minOccurs="0" name="Protocol" nillable="true" type="xs:string"
/>
                <xs:element minOccurs="0" name="Service" nillable="true" type="xs:string" />
                <xs:element minOccurs="0" name="Target" nillable="true" type="xs:string" />
                <xs:element minOccurs="0" name="Weight" type="xs:int" />
            </xs:sequence>
        </xs:extension>
    </xs:complexContent>
</xs:complexType>
<xs:element name="SrvRecord" nillable="true" type="tns:SrvRecord" />
<xs:complexType name="TxtRecord">
    <xs:complexContent mixed="false">
        <xs:extension base="tns:DnsRecord">
            <xs:sequence>
                <xs:element minOccurs="0" name="Text" nillable="true" type="xs:string" />
            </xs:sequence>
        </xs:extension>
    </xs:complexContent>
</xs:complexType>
<xs:element name="TxtRecord" nillable="true" type="tns:TxtRecord" />
<xs:complexType name="CNameRecord">
    <xs:complexContent mixed="false">
        <xs:extension base="tns:DnsRecord">
            <xs:sequence>
                <xs:element minOccurs="0" name="CanonicalName" nillable="true"
type="xs:string" />
            </xs:sequence>
        </xs:extension>
    </xs:complexContent>
</xs:complexType>
<xs:element name="CNameRecord" nillable="true" type="tns:CNameRecord" />
<xs:complexType name="DomainState">
    <xs:sequence>
        <xs:element minOccurs="0" name="ExpirationDate" type="xs:dateTime" />
        <xs:element minOccurs="0" name="Status" type="tns:DomainStatus" />
        <xs:element minOccurs="0" name="StatusDescription" nillable="true"
type="xs:string" />
    </xs:sequence>
</xs:complexType>

```

```

<xs:element name="DomainState" nullable="true" type="tns:DomainState" />
<xs:simpleType name="DomainStatus">
    <xs:restriction base="xs:string">
        <xs:enumeration value="Unknown" />
        <xs:enumeration value="NotConfigured">
            <xs:annotation>
                <xs:appinfo>
                    <EnumerationValue
                        xmlns="http://schemas.microsoft.com/2003/10/Serialization/">0</EnumerationValue>
                </xs:appinfo>
            </xs:annotation>
        </xs:enumeration>
        <xs:enumeration value="Ready">
            <xs:annotation>
                <xs:appinfo>
                    <EnumerationValue
                        xmlns="http://schemas.microsoft.com/2003/10/Serialization/">1</EnumerationValue>
                </xs:appinfo>
            </xs:annotation>
        </xs:enumeration>
        <xs:enumeration value="Pending">
            <xs:annotation>
                <xs:appinfo>
                    <EnumerationValue
                        xmlns="http://schemas.microsoft.com/2003/10/Serialization/">2</EnumerationValue>
                </xs:appinfo>
            </xs:annotation>
        </xs:enumeration>
        <xs:enumeration value="PendingCustomerInterventionRequired">
            <xs:annotation>
                <xs:appinfo>
                    <EnumerationValue
                        xmlns="http://schemas.microsoft.com/2003/10/Serialization/">3</EnumerationValue>
                </xs:appinfo>
            </xs:annotation>
        </xs:enumeration>
        <xs:enumeration value="Failed">
            <xs:annotation>
                <xs:appinfo>
                    <EnumerationValue
                        xmlns="http://schemas.microsoft.com/2003/10/Serialization/">4</EnumerationValue>
                </xs:appinfo>
            </xs:annotation>
        </xs:enumeration>
        <xs:enumeration value="PurchaseFailed">
            <xs:annotation>
                <xs:appinfo>
                    <EnumerationValue
                        xmlns="http://schemas.microsoft.com/2003/10/Serialization/">5</EnumerationValue>
                </xs:appinfo>
            </xs:annotation>
        </xs:enumeration>
        <xs:enumeration value="DomainNotFound">
            <xs:annotation>
                <xs:appinfo>
                    <EnumerationValue
                        xmlns="http://schemas.microsoft.com/2003/10/Serialization/">6</EnumerationValue>
                </xs:appinfo>
            </xs:annotation>
        </xs:enumeration>
        <xs:enumeration value="InRenewal">
            <xs:annotation>
                <xs:appinfo>
                    <EnumerationValue
                        xmlns="http://schemas.microsoft.com/2003/10/Serialization/">7</EnumerationValue>
                </xs:appinfo>
            </xs:annotation>
        </xs:enumeration>
        <xs:enumeration value="InRenewalCustomerInterventionRequired">

```

```

<xs:annotation>
    <xs:appinfo>
        <EnumerationValue
xmlns="http://schemas.microsoft.com/2003/10/Serialization/">8</EnumerationValue>
    </xs:appinfo>
</xs:annotation>
</xs:enumeration>
<xs:enumeration value="RenewalFailed">
    <xs:annotation>
        <xs:appinfo>
            <EnumerationValue
xmlns="http://schemas.microsoft.com/2003/10/Serialization/">9</EnumerationValue>
        </xs:appinfo>
    </xs:annotation>
</xs:enumeration>
</xs:restriction>
</xs:simpleType>
<xs:element name="DomainStatus" nillable="true" type="tns:DomainStatus" />
<xs:complexType name="CertificateState">
    <xs:sequence>
        <xs:element minOccurs="0" name="Status" type="tns:CertificateStatus" />
        <xs:element minOccurs="0" name="StatusDescription" nillable="true"
type="xs:string" />
    </xs:sequence>
</xs:complexType>
<xs:element name="CertificateState" nillable="true" type="tns:CertificateState" />
<xs:simpleType name="CertificateStatus">
    <xs:restriction base="xs:string">
        <xs:enumeration value="Unknown" />
        <xs:enumeration value="Ready" />
        <xs:enumeration value="Failed" />
        <xs:enumeration value="CertificateRequestNotSubmitted" />
        <xs:enumeration value="Pending" />
        <xs:enumeration value="PendingCustomerInterventionRequired" />
    </xs:restriction>
</xs:simpleType>
<xs:element name="CertificateStatus" nillable="true" type="tns:CertificateStatus" />
<xs:complexType name="DomainNameConfiguration">
    <xs:sequence>
        <xs:element minOccurs="0" name="AccountName" nillable="true" type="xs:string" />
        <xs:element minOccurs="0" name="AutoConfiguredAnywhereAccessHostName"
type="tns:Idn" />
        <xs:element minOccurs="0" name="AutoConfiguredInternetDomainFullName"
type="tns:Idn" />
        <xs:element minOccurs="0" name="CertificateRenewInProgress" type="xs:boolean" />
        <xs:element minOccurs="0" name="CertificateRenewStatus"
type="tns:CertificateStatus" />
        <xs:element minOccurs="0" name="CertificateStatus" type="tns:CertificateStatus"
/>
        <xs:element minOccurs="0" name="CertificateStatusDescription" nillable="true"
type="xs:string" />
        <xs:element minOccurs="0" name="DomainStatus" type="tns:DomainStatus" />
        <xs:element minOccurs="0" name="DomainStatusDescription" nillable="true"
type="xs:string" />
        <xs:element minOccurs="0" name="ExpirationDate" type="xs:dateTime" />
        <xs:element minOccurs="0" name="ManualModeEnabled" type="xs:boolean" />
        <xs:element minOccurs="0" name="ManuallyConfiguredAnywhereAccessFullName"
type="tns:Idn" />
        <xs:element minOccurs="0" name="Offering" nillable="true" type="tns:Offering" />
        <xs:element minOccurs="0" name="ProviderID" type="ser:guid" />
    </xs:sequence>
</xs:complexType>
<xs:element name="DomainNameConfiguration" nillable="true"
type="tns:DomainNameConfiguration" />
<xs:complexType name="Idn">
    <xs:annotation>
        <xs:appinfo>
            <IsValueType
xmlns="http://schemas.microsoft.com/2003/10/Serialization/">true</IsValueType>

```

```

        </xs:appinfo>
    </xs:annotation>
    <xs:sequence>
        <xs:element minOccurs="0" name="_origin" nillable="true" type="xs:string" />
        <xs:element minOccurs="0" name="_punycode" nillable="true" type="xs:string" />
        <xs:element minOccurs="0" name="unicode" nillable="true" type="xs:string" />
    </xs:sequence>
</xs:complexType>
<xs:element name="Idn" nillable="true" type="tns:Idn" />
<xs:complexType name="Offering">
    <xs:sequence>
        <xs:element minOccurs="0" name="AccountManagementUrl" nillable="true"
type="xs:anyURI" />
        <xs:element
xmlns:q2="http://schemas.datacontract.org/2004/07/System.Collections.ObjectModel"
minOccurs="0" name="AdditionalSites" nillable="true" type="q2:ReadOnlyCollectionOfanyURI"
/>
        <xs:element minOccurs="0" name="Description" nillable="true" type="xs:string" />
        <xs:element minOccurs="0" name="EulaUrl" nillable="true" type="xs:anyURI" />
        <xs:element minOccurs="0" name="Icon" nillable="true" type="xs:base64Binary" />
        <xs:element minOccurs="0" name="MembershipServiceName" nillable="true"
type="xs:string" />
        <xs:element minOccurs="0" name="MembershipServiceSignupUrl" nillable="true"
type="xs:anyURI" />
        <xs:element minOccurs="0" name="MoreInfoUrl" nillable="true" type="xs:anyURI" />
        <xs:element minOccurs="0" name="Name" nillable="true" type="xs:string" />
        <xs:element minOccurs="0" name="ProviderID" type="ser:guid" />
        <xs:element minOccurs="0" name="SupportedDomainType" type="tns:DomainType" />
        <xs:element minOccurs="0" name="TroubleshootingUrl" nillable="true"
type="xs:anyURI" />
    </xs:sequence>
</xs:complexType>
<xs:element name="Offering" nillable="true" type="tns:Offering" />
<xs:simpleType name="DomainType">
    <xs:restriction base="xs:string">
        <xs:enumeration value="None" />
        <xs:enumeration value="Home" />
        <xs:enumeration value="Business" />
        <xs:enumeration value="All" />
    </xs:restriction>
</xs:simpleType>
<xs:element name="DomainType" nillable="true" type="tns:DomainType" />
<xs:complexType name="DynamicDNSInfo">
    <xs:sequence>
        <xs:element minOccurs="0" name="FailedDNSUpdateAttempts" type="xs:int" />
        <xs:element minOccurs="0" name="LastSuccessfulDNSUpdate" type="xs:dateTime" />
        <xs:element xmlns:q3="http://schemas.datacontract.org/2004/07/System.Net"
minOccurs="0" name="LastUpdatedIPAddress" nillable="true" type="q3:IPAddress" />
    </xs:sequence>
</xs:complexType>
<xs:element name="DynamicDNSInfo" nillable="true" type="tns:DynamicDNSInfo" />
<xs:complexType name="DomainProviderManagerSettings">
    <xs:sequence>
        <xs:element minOccurs="0" name="BypassProxyForLocalAddresses" type="xs:boolean"
/>
        <xs:element minOccurs="0" name="DNSUpdateInterval" type="ser:duration" />
        <xs:element minOccurs="0" name="DomainStatusQueryInterval" type="ser:duration"
/>
        <xs:element minOccurs="0" name="Environment"
type="tns:DomainProviderEnvironment" />
        <xs:element minOccurs="0" name="Proxy" nillable="true" type="xs:string" />
    </xs:sequence>
</xs:complexType>
<xs:element name="DomainProviderManagerSettings" nillable="true"
type="tns:DomainProviderManagerSettings" />
<xs:simpleType name="DomainProviderEnvironment">
    <xs:restriction base="xs:string">
        <xs:enumeration value="Testing" />
        <xs:enumeration value="Production" />
    </xs:restriction>
</xs:simpleType>

```

```

        </xs:restriction>
    </xs:simpleType>
    <xs:element name="DomainProviderEnvironment" nillable="true"
type="tns:DomainProviderEnvironment" />
</xs:schema>

```

6.9.4 <http://schemas.microsoft.com/2003/10/Serialization/Arrays>

```

<?xml version="1.0" encoding="utf-8"?>
<xs:schema xmlns:tns="http://schemas.microsoft.com/2003/10/Serialization/Arrays"
elementFormDefault="qualified"
targetNamespace="http://schemas.microsoft.com/2003/10/Serialization/Arrays"
xmlns:xs="http://www.w3.org/2001/XMLSchema">
    <xs:complexType name="ArrayOfunsignedShort">
        <xs:sequence>
            <xs:element minOccurs="0" maxOccurs="unbounded" name="unsignedShort"
type="xs:unsignedShort" />
        </xs:sequence>
    </xs:complexType>
    <xs:element name="ArrayOfunsignedShort" nillable="true"
type="tns:ArrayOfunsignedShort" />
    <xs:complexType name="ArrayOfanyURI">
        <xs:sequence>
            <xs:element minOccurs="0" maxOccurs="unbounded" name="anyURI" nillable="true"
type="xs:anyURI" />
        </xs:sequence>
    </xs:complexType>
    <xs:element name="ArrayOfanyURI" nillable="true" type="tns:ArrayOfanyURI" />
</xs:schema>

```

6.9.5 <http://schemas.microsoft.com/2003/10/Serialization>

```

<?xml version="1.0" encoding="utf-8"?>
<xs:schema xmlns:tns="http://schemas.microsoft.com/2003/10/Serialization/"
attributeFormDefault="qualified" elementFormDefault="qualified"
targetNamespace="http://schemas.microsoft.com/2003/10/Serialization/"
xmlns:xs="http://www.w3.org/2001/XMLSchema">
    <xs:element name="anyType" nillable="true" type="xs:anyType" />
    <xs:element name="anyURI" nillable="true" type="xs:anyURI" />
    <xs:element name="base64Binary" nillable="true" type="xs:base64Binary" />
    <xs:element name="boolean" nillable="true" type="xs:boolean" />
    <xs:element name="byte" nillable="true" type="xs:byte" />
    <xs:element name="dateTime" nillable="true" type="xs:dateTime" />
    <xs:element name="decimal" nillable="true" type="xs:decimal" />
    <xs:element name="double" nillable="true" type="xs:double" />
    <xs:element name="float" nillable="true" type="xs:float" />
    <xs:element name="int" nillable="true" type="xs:int" />
    <xs:element name="long" nillable="true" type="xs:long" />
    <xs:element name="QName" nillable="true" type="xs:QName" />
    <xs:element name="short" nillable="true" type="xs:short" />
    <xs:element name="string" nillable="true" type="xs:string" />
    <xs:element name="unsignedByte" nillable="true" type="xs:unsignedByte" />
    <xs:element name="unsignedInt" nillable="true" type="xs:unsignedInt" />
    <xs:element name="unsignedLong" nillable="true" type="xs:unsignedLong" />
    <xs:element name="unsignedShort" nillable="true" type="xs:unsignedShort" />
    <xs:element name="char" nillable="true" type="tns:char" />
    <xs:simpleType name="char">
        <xs:restriction base="xs:int" />
    </xs:simpleType>
    <xs:element name="duration" nillable="true" type="tns:duration" />
    <xs:simpleType name="duration">
        <xs:restriction base="xs:duration">
            <xs:pattern value="-?P(\d*D)?(T(\d*H)?(\d*M)?(\d*(\.\d*)?S)?)?" />
            <xs:minInclusive value="-P10675199DT2H48M5.4775808S" />
            <xs:maxInclusive value="P10675199DT2H48M5.4775807S" />

```

```

        </xs:restriction>
    </xs:simpleType>
    <xs:element name="guid" nillable="true" type="tns:guid" />
    <xs:simpleType name="guid">
        <xs:restriction base="xs:string">
            <xs:pattern value="[\da-fA-F]{8}-[\da-fA-F]{4}-[\da-fA-F]{4}-[\da-fA-F]{4}-[\da-fA-F]{12}" />
        </xs:restriction>
    </xs:simpleType>
    <xs:attribute name="FactoryType" type="xs:QName" />
    <xs:attribute name="Id" type="xs:ID" />
    <xs:attribute name="Ref" type="xs:IDREF" />
</xs:schema>

```

6.9.6 http://schemas.datacontract.org/2004/07/System.Collections.ObjectModel

```

<?xml version="1.0" encoding="utf-8"?>
<xs:schema
    xmlns:tns="http://schemas.datacontract.org/2004/07/System.Collections.ObjectModel"
    elementFormDefault="qualified"
    targetNamespace="http://schemas.datacontract.org/2004/07/System.Collections.ObjectModel"
    xmlns:xs="http://www.w3.org/2001/XMLSchema">
    <xs:import schemaLocation="" namespace="http://schemas.microsoft.com/2003/10/Serialization/Arrays" />
    <xs:complexType name="ReadOnlyCollectionOfanyURI">
        <xs:annotation>
            <xs:appinfo>
                <GenericType Name="ReadOnlyCollectionOf{0}{{#}}">
                    Namespace="http://schemas.datacontract.org/2004/07/System.Collections.ObjectModel"
                    xmlns="http://schemas.microsoft.com/2003/10/Serialization/">
                        <GenericParameter Name="anyURI" Namespace="http://www.w3.org/2001/XMLSchema" />
                </GenericType>
            </xs:appinfo>
        </xs:annotation>
        <xs:sequence>
            <xs:element xmlns:q1="http://schemas.microsoft.com/2003/10/Serialization/Arrays" name="list" nillable="true" type="q1:ArrayOfanyURI" />
        </xs:sequence>
    </xs:complexType>
    <xs:element name="ReadOnlyCollectionOfanyURI" nillable="true" type="tns:ReadOnlyCollectionOfanyURI" />
</xs:schema>

```

6.9.7 http://schemas.datacontract.org/2004/07/System.Net.Sockets

```

<?xml version="1.0" encoding="utf-8"?>
<xs:schema
    xmlns:tns="http://schemas.datacontract.org/2004/07/System.Net.Sockets"
    elementFormDefault="qualified"
    targetNamespace="http://schemas.datacontract.org/2004/07/System.Net.Sockets"
    xmlns:xs="http://www.w3.org/2001/XMLSchema">
    <xs:import schemaLocation="" namespace="http://schemas.microsoft.com/2003/10/Serialization/" />
    <xs:simpleType name="AddressFamily">
        <xs:restriction base="xs:string">
            <xs:enumeration value="Unknown">
                <xs:annotation>
                    <xs:appinfo>
                        <EnumerationValue
                            xmlns="http://schemas.microsoft.com/2003/10/Serialization/">-1</EnumerationValue>
                    </xs:appinfo>
                </xs:annotation>
            </xs:enumeration>
            <xs:enumeration value="Unspecified">
                <xs:annotation>

```

```

        <xs:appinfo>
            <EnumerationValue
        xmlns="http://schemas.microsoft.com/2003/10/Serialization/">0</EnumerationValue>
            </xs:appinfo>
        </xs:annotation>
    </xs:enumeration>
    <xs:enumeration value="Unix">
        <xs:annotation>
            <xs:appinfo>
                <EnumerationValue
        xmlns="http://schemas.microsoft.com/2003/10/Serialization/">1</EnumerationValue>
            </xs:appinfo>
        </xs:annotation>
    </xs:enumeration>
    <xs:enumeration value="InterNetwork">
        <xs:annotation>
            <xs:appinfo>
                <EnumerationValue
        xmlns="http://schemas.microsoft.com/2003/10/Serialization/">2</EnumerationValue>
            </xs:appinfo>
        </xs:annotation>
    </xs:enumeration>
    <xs:enumeration value="ImpLink">
        <xs:annotation>
            <xs:appinfo>
                <EnumerationValue
        xmlns="http://schemas.microsoft.com/2003/10/Serialization/">3</EnumerationValue>
            </xs:appinfo>
        </xs:annotation>
    </xs:enumeration>
    <xs:enumeration value="Pup">
        <xs:annotation>
            <xs:appinfo>
                <EnumerationValue
        xmlns="http://schemas.microsoft.com/2003/10/Serialization/">4</EnumerationValue>
            </xs:appinfo>
        </xs:annotation>
    </xs:enumeration>
    <xs:enumeration value="Chaos">
        <xs:annotation>
            <xs:appinfo>
                <EnumerationValue
        xmlns="http://schemas.microsoft.com/2003/10/Serialization/">5</EnumerationValue>
            </xs:appinfo>
        </xs:annotation>
    </xs:enumeration>
    <xs:enumeration value="NS">
        <xs:annotation>
            <xs:appinfo>
                <EnumerationValue
        xmlns="http://schemas.microsoft.com/2003/10/Serialization/">6</EnumerationValue>
            </xs:appinfo>
        </xs:annotation>
    </xs:enumeration>
    <xs:enumeration value="Ipx">
        <xs:annotation>
            <xs:appinfo>
                <EnumerationValue
        xmlns="http://schemas.microsoft.com/2003/10/Serialization/">6</EnumerationValue>
            </xs:appinfo>
        </xs:annotation>
    </xs:enumeration>
    <xs:enumeration value="Iso">
        <xs:annotation>
            <xs:appinfo>
                <EnumerationValue
        xmlns="http://schemas.microsoft.com/2003/10/Serialization/">7</EnumerationValue>
            </xs:appinfo>
        </xs:annotation>

```

```

    </xs:enumeration>
<xs:enumeration value="Osi">
    <xs:annotation>
        <xs:appinfo>
            <EnumerationValue
                xmlns="http://schemas.microsoft.com/2003/10/Serialization/">7</EnumerationValue>
            </xs:appinfo>
        </xs:annotation>
    </xs:enumeration>
<xs:enumeration value="Ecma">
    <xs:annotation>
        <xs:appinfo>
            <EnumerationValue
                xmlns="http://schemas.microsoft.com/2003/10/Serialization/">8</EnumerationValue>
            </xs:appinfo>
        </xs:annotation>
    </xs:enumeration>
<xs:enumeration value="DataKit">
    <xs:annotation>
        <xs:appinfo>
            <EnumerationValue
                xmlns="http://schemas.microsoft.com/2003/10/Serialization/">9</EnumerationValue>
            </xs:appinfo>
        </xs:annotation>
    </xs:enumeration>
<xs:enumeration value="Ccitt">
    <xs:annotation>
        <xs:appinfo>
            <EnumerationValue
                xmlns="http://schemas.microsoft.com/2003/10/Serialization/">10</EnumerationValue>
            </xs:appinfo>
        </xs:annotation>
    </xs:enumeration>
<xs:enumeration value="Sna">
    <xs:annotation>
        <xs:appinfo>
            <EnumerationValue
                xmlns="http://schemas.microsoft.com/2003/10/Serialization/">11</EnumerationValue>
            </xs:appinfo>
        </xs:annotation>
    </xs:enumeration>
<xs:enumeration value="DecNet">
    <xs:annotation>
        <xs:appinfo>
            <EnumerationValue
                xmlns="http://schemas.microsoft.com/2003/10/Serialization/">12</EnumerationValue>
            </xs:appinfo>
        </xs:annotation>
    </xs:enumeration>
<xs:enumeration value="DataLink">
    <xs:annotation>
        <xs:appinfo>
            <EnumerationValue
                xmlns="http://schemas.microsoft.com/2003/10/Serialization/">13</EnumerationValue>
            </xs:appinfo>
        </xs:annotation>
    </xs:enumeration>
<xs:enumeration value="Lat">
    <xs:annotation>
        <xs:appinfo>
            <EnumerationValue
                xmlns="http://schemas.microsoft.com/2003/10/Serialization/">14</EnumerationValue>
            </xs:appinfo>
        </xs:annotation>
    </xs:enumeration>
<xs:enumeration value="HyperChannel">
    <xs:annotation>
        <xs:appinfo>

```

```

        <EnumerationValue
xmlns="http://schemas.microsoft.com/2003/10/Serialization/">15</EnumerationValue>
        </xs:appinfo>
    </xs:annotation>
</xs:enumeration>
<xs:enumeration value="AppleTalk">
    <xs:annotation>
        <xs:appinfo>
            <EnumerationValue
xmlns="http://schemas.microsoft.com/2003/10/Serialization/">16</EnumerationValue>
        </xs:appinfo>
    </xs:annotation>
</xs:enumeration>
<xs:enumeration value="NetBios">
    <xs:annotation>
        <xs:appinfo>
            <EnumerationValue
xmlns="http://schemas.microsoft.com/2003/10/Serialization/">17</EnumerationValue>
        </xs:appinfo>
    </xs:annotation>
</xs:enumeration>
<xs:enumeration value="VoiceView">
    <xs:annotation>
        <xs:appinfo>
            <EnumerationValue
xmlns="http://schemas.microsoft.com/2003/10/Serialization/">18</EnumerationValue>
        </xs:appinfo>
    </xs:annotation>
</xs:enumeration>
<xs:enumeration value="FireFox">
    <xs:annotation>
        <xs:appinfo>
            <EnumerationValue
xmlns="http://schemas.microsoft.com/2003/10/Serialization/">19</EnumerationValue>
        </xs:appinfo>
    </xs:annotation>
</xs:enumeration>
<xs:enumeration value="Banyan">
    <xs:annotation>
        <xs:appinfo>
            <EnumerationValue
xmlns="http://schemas.microsoft.com/2003/10/Serialization/">21</EnumerationValue>
        </xs:appinfo>
    </xs:annotation>
</xs:enumeration>
<xs:enumeration value="Atm">
    <xs:annotation>
        <xs:appinfo>
            <EnumerationValue
xmlns="http://schemas.microsoft.com/2003/10/Serialization/">22</EnumerationValue>
        </xs:appinfo>
    </xs:annotation>
</xs:enumeration>
<xs:enumeration value="InterNetworkV6">
    <xs:annotation>
        <xs:appinfo>
            <EnumerationValue
xmlns="http://schemas.microsoft.com/2003/10/Serialization/">23</EnumerationValue>
        </xs:appinfo>
    </xs:annotation>
</xs:enumeration>
<xs:enumeration value="Cluster">
    <xs:annotation>
        <xs:appinfo>
            <EnumerationValue
xmlns="http://schemas.microsoft.com/2003/10/Serialization/">24</EnumerationValue>
        </xs:appinfo>
    </xs:annotation>
</xs:enumeration>

```

```

<xs:enumeration value="Ieee12844">
  <xs:annotation>
    <xs:appinfo>
      <EnumerationValue
xmlns="http://schemas.microsoft.com/2003/10/Serialization/">25</EnumerationValue>
    </xs:appinfo>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="Irda">
  <xs:annotation>
    <xs:appinfo>
      <EnumerationValue
xmlns="http://schemas.microsoft.com/2003/10/Serialization/">26</EnumerationValue>
    </xs:appinfo>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="NetworkDesigners">
  <xs:annotation>
    <xs:appinfo>
      <EnumerationValue
xmlns="http://schemas.microsoft.com/2003/10/Serialization/">28</EnumerationValue>
    </xs:appinfo>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="Max">
  <xs:annotation>
    <xs:appinfo>
      <EnumerationValue
xmlns="http://schemas.microsoft.com/2003/10/Serialization/">29</EnumerationValue>
    </xs:appinfo>
  </xs:annotation>
</xs:enumeration>
</xs:restriction>
</xs:simpleType>
<xs:element name="AddressFamily" nillable="true" type="tns:AddressFamily" />
</xs:schema>

```

6.9.8 <http://schemas.datacontract.org/2004/07/System.Net>

```

<?xml version="1.0" encoding="utf-8"?>
<xs:schema xmlns:tns="http://schemas.datacontract.org/2004/07/System.Net"
elementFormDefault="qualified"
targetNamespace="http://schemas.datacontract.org/2004/07/System.Net"
xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:import schemaLocation="" namespace="http://schemas.datacontract.org/2004/07/System.Net.Sockets" />
  <xs:import schemaLocation="" namespace="http://schemas.microsoft.com/2003/10/Serialization/Arrays" />
  <xs:complexType name="IPAddress">
    <xs:sequence>
      <xs:element name="m_Address" type="xs:long" />
    <xs:element
      xmlns:q1="http://schemas.datacontract.org/2004/07/System.Net.Sockets" name="m_Family"
      type="q1:AddressFamily" />
      <xs:element name="m_HashCode" type="xs:int" />
      <xs:element xmlns:q2="http://schemas.microsoft.com/2003/10/Serialization/Arrays" name="m_Numbers" nillable="true" type="q2:ArrayOfunsignedShort" />
        <xs:element name="m_ScopeId" type="xs:long" />
      </xs:sequence>
    </xs:complexType>
    <xs:element name="IPAddress" nillable="true" type="tns:IPAddress" />
</xs:schema>

```

6.9.9 http://schemas.datacontract.org/2004/07/System

```
<?xml version="1.0" encoding="utf-8"?>
<xs:schema xmlns:ser="http://schemas.microsoft.com/2003/10/Serialization/"
  xmlns:tns="http://schemas.datacontract.org/2004/07/System" elementFormDefault="qualified"
  targetNamespace="http://schemas.datacontract.org/2004/07/System"
  xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:import schemaLocation="" />
  namespace="http://schemas.microsoft.com/2003/10/Serialization/" />
  <xs:complexType name="ArgumentException">
    <xs:complexContent mixed="false">
      <xs:extension base="tns:SystemException" />
    </xs:complexContent>
  </xs:complexType>
  <xs:element name="ArgumentException" nillable="true" type="tns:ArgumentException" />
  <xs:complexType name="SystemException">
    <xs:complexContent mixed="false">
      <xs:extension base="tns:Exception" />
    </xs:complexContent>
  </xs:complexType>
  <xs:element name="SystemException" nillable="true" type="tns:SystemException" />
  <xs:complexType name="Exception">
    <xs:sequence>
      <xs:any minOccurs="0" maxOccurs="unbounded" namespace="###local"
        processContents="skip" />
    </xs:sequence>
    <xs:attribute ref="ser:FactoryType" />
  </xs:complexType>
  <xs:element name="Exception" nillable="true" type="tns:Exception" />
</xs:schema>
```

6.10 AzureAD and HostedEmail Integration Service WSDL

6.10.1 IPasswordSyncClientProvider

6.10.1.1 wsdl

```
<?xml version="1.0" encoding="utf-8"?>
<wsdl:definitions xmlns:wsap="http://schemas.xmlsoap.org/ws/2004/08/addressing/policy"
  xmlns:wsa10="http://www.w3.org/2005/08/addressing" xmlns:tns="http://tempuri.org/"
  xmlns:msc="http://schemas.microsoft.com/ws/2005/12/wsdl/contract"
  xmlns:soapenc="http://schemas.xmlsoap.org/soap/encoding/"
  xmlns:soap="http://schemas.xmlsoap.org/wsdl/soap/"
  xmlns:wsp="http://schemas.xmlsoap.org/ws/2004/09/policy"
  xmlns:wsam="http://www.w3.org/2007/05/addressing/metadata"
  xmlns:wsaa="http://schemas.xmlsoap.org/ws/2004/08/addressing"
  xmlns:wsaw="http://www.w3.org/2006/05/addressing/wsdl"
  xmlns:soap12="http://schemas.xmlsoap.org/wsdl/soap12/" xmlns:wsu="http://docs.oasis-
  open.org/wss/2004/01/oasis-200401-wss-wssecurity-utility-1.0.xsd"
  xmlns:xsd="http://www.w3.org/2001/XMLSchema" name="PasswordSyncClientProvider"
  targetNamespace="http://tempuri.org/" xmlns:wsdl="http://schemas.xmlsoap.org/wsdl/">
  <wsp:Policy wsu:Id="CustomBinding_IProvider_policy">
    <wsp:ExactlyOne>
      <wsp:All>
        <msb:BinaryEncoding
          xmlns:msb="http://schemas.microsoft.com/ws/06/2004/mspolicy/netbinary1" />
        <sp:TransportBinding
          xmlns:sp="http://schemas.xmlsoap.org/ws/2005/07/securitypolicy">
          <wsp:Policy>
            <sp:TransportToken>
              <wsp:Policy>
                <msf:SslTransportSecurity
                  xmlns:msf="http://schemas.microsoft.com/ws/2006/05/framing/policy" />
              </wsp:Policy>
            </sp:TransportToken>
          </wsp:Policy>
        </sp:TransportBinding>
      </wsp:All>
    </wsp:ExactlyOne>
  </wsp:Policy>
</wsdl:definitions>
```

```

        <sp:AlgorithmSuite>
            <wsp:Policy>
                <sp:Basic256 />
            </wsp:Policy>
        </sp:AlgorithmSuite>
        <sp:Layout>
            <wsp:Policy>
                <sp:Strict />
            </wsp:Policy>
        </sp:Layout>
    </wsp:Policy>
</sp:TransportBinding>
<wsaw:UsingAddressing />
</wsp:All>
</wsp:ExactlyOne>
</wsp:Policy>
<wsp:Policy wsu:Id="CustomBinding_IPasswordSyncClientProvider policy">
    <wsp:ExactlyOne>
        <wsp:All>
            <msb:BinaryEncoding
xmlns:msb="http://schemas.microsoft.com/ws/2004/06/2004/mspolicy/netbinary1" />
            <sp:TransportBinding
xmlns:sp="http://schemas.xmlsoap.org/ws/2005/07/securitypolicy">
                <wsp:Policy>
                    <sp:TransportToken>
                        <wsp:Policy>
                            <msf:SslTransportSecurity
xmlns:msf="http://schemas.microsoft.com/ws/2006/05/framing/policy" />
                        </wsp:Policy>
                    </sp:TransportToken>
                    <sp:AlgorithmSuite>
                        <wsp:Policy>
                            <sp:Basic256 />
                        </wsp:Policy>
                    </sp:AlgorithmSuite>
                    <sp:Layout>
                        <wsp:Policy>
                            <sp:Strict />
                        </wsp:Policy>
                    </sp:Layout>
                </wsp:Policy>
            </sp:TransportBinding>
            <wsaw:UsingAddressing />
        </wsp:All>
    </wsp:ExactlyOne>
</wsp:Policy>
<wsdl:types>
    <xsd:schema targetNamespace="http://tempuri.org/Imports">
        <xsd:import schemaLocation="" namespace="http://tempuri.org/" />
        <xsd:import schemaLocation="" namespace="http://schemas.microsoft.com/2003/10/Serialization/" />
        <xsd:import schemaLocation="" namespace="http://schemas.datacontract.org/2004/07/System" />
        <xsd:import schemaLocation="" namespace="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.PasswordSync" />
    </xsd:schema>
</wsdl:types>
<wsdl:message name="IProvider_Disconnect_InputMessage">
    <wsdl:part name="parameters" element="tns:Disconnect" />
</wsdl:message>
<wsdl:message name="IProvider_RaiseOperationInvokeEvent_OutputCallbackMessage">
    <wsdl:part name="parameters" element="tns:RaiseOperationInvokeEvent" />
</wsdl:message>
<wsdl:message name="IPasswordSyncClientProvider_GetPasswordChangeStatus_InputMessage">
    <wsdl:part name="parameters" element="tns:GetPasswordChangeStatus" />
</wsdl:message>

```

```

<wsdl:message
name="IPasswordSyncClientProvider_GetPasswordChangeStatus_OutputMessage">
    <wsdl:part name="parameters" element="tns:GetPasswordChangeStatusResponse" />
</wsdl:message>
<wsdl:message
name="IPasswordSyncClientProvider GetPasswordChangeStatus PwdSyncConfigurationExceptionFault_FaultMessage">
    <wsdl:part
xmlns:q1="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.PasswordSync" name="detail" element="q1:PwdSyncConfigurationException" />
    </wsdl:message>
<wsdl:message
name="IPasswordSyncClientProvider_MarkUserPasswordChangeFixed_InputMessage">
    <wsdl:part name="parameters" element="tns:MarkUserPasswordChangeFixed" />
</wsdl:message>
<wsdl:message
name="IPasswordSyncClientProvider MarkUserPasswordChangeFixed OutputMessage">
    <wsdl:part name="parameters" element="tns:MarkUserPasswordChangeFixedResponse" />
</wsdl:message>
<wsdl:message
name="IPasswordSyncClientProvider_MarkUserPasswordChangeFixed_PwdSyncConfigurationExceptionFault_FaultMessage">
    <wsdl:part
xmlns:q2="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.PasswordSync" name="detail" element="q2:PwdSyncConfigurationException" />
    </wsdl:message>
    <wsdl:portType msc:usingSession="true" name="IProvider">
        <wsdl:operation msc:isInitiating="true" msc:isTerminating="true"
name="Disconnect">
            <wsdl:input wsaw:Action="http://tempuri.org/IProvider/Disconnect"
message="tns:IProvider_Disconnect_InputMessage" />
            </wsdl:operation>
            <wsdl:operation msc:isInitiating="true" msc:isTerminating="false"
name="RaiseOperationInvokeEvent">
                <wsdl:output
wsaw:Action="http://tempuri.org/IProvider/RaiseOperationInvokeEvent"
message="tns:IProvider_RaiseOperationInvokeEvent_OutputCallbackMessage" />
                </wsdl:operation>
            </wsdl:portType>
            <wsdl:portType msc:usingSession="true" name="IPasswordSyncClientProvider">
                <wsdl:operation msc:isInitiating="true" msc:isTerminating="true"
name="Disconnect">
                    <wsdl:input wsaw:Action="http://tempuri.org/IProvider/Disconnect"
message="tns:IProvider_Disconnect_InputMessage" />
                    </wsdl:operation>
                    <wsdl:operation msc:isInitiating="true" msc:isTerminating="false"
name="RaiseOperationInvokeEvent">
                        <wsdl:output
wsaw:Action="http://tempuri.org/IProvider/RaiseOperationInvokeEvent"
message="tns:IProvider_RaiseOperationInvokeEvent_OutputCallbackMessage" />
                        </wsdl:operation>
                        <wsdl:operation msc:isInitiating="true" msc:isTerminating="false"
name="GetPasswordChangeStatus">
                            <wsdl:input
wsaw:Action="http://tempuri.org/IPasswordSyncClientProvider/GetPasswordChangeStatus"
message="tns:IPasswordSyncClientProvider_GetPasswordChangeStatus_InputMessage" />
                            </wsdl:output>
                        <wsdl:operation msc:isInitiating="true" msc:isTerminating="false"
" message="tns:IPasswordSyncClientProvider GetPasswordChangeStatus_OutputMessage" />
                            <wsdl:fault
wsaw:Action="http://tempuri.org/IPasswordSyncClientProvider/GetPasswordChangeStatusPwdSyncConfigurationExceptionFault" name="PwdSyncConfigurationExceptionFault"
message="tns:IPasswordSyncClientProvider GetPasswordChangeStatus_PwdSyncConfigurationExceptionFault_FaultMessage" />
                            </wsdl:operation>
                            <wsdl:operation msc:isInitiating="true" msc:isTerminating="false"
name="MarkUserPasswordChangeFixed">

```

```

        <wsdl:input
wsaw:Action="http://tempuri.org/IPasswordSyncClientProvider/MarkUserPasswordChangeFixed"
message="tns:IPasswordSyncClientProvider_MarkUserPasswordChangeFixed_InputMessage" />
        <wsdl:output
wsaw:Action="http://tempuri.org/IPasswordSyncClientProvider/MarkUserPasswordChangeFixedResp
onse" message="tns:IPasswordSyncClientProvider MarkUserPasswordChangeFixed OutputMessage"
/>
        <wsdl:fault
wsaw:Action="http://tempuri.org/IPasswordSyncClientProvider/MarkUserPasswordChangeFixedPwdS
yncConfigurationExceptionFault" name="PwdSyncConfigurationExceptionFault"
message="tns:IPasswordSyncClientProvider MarkUserPasswordChangeFixed PwdSyncConfigurationEx
ceptionFault_FaultMessage" />
        </wsdl:operation>
    </wsdl:portType>
    <wsdl:binding name="CustomBinding_IProvider" type="tns:IProvider">
        <wsp:PolicyReference URI="#CustomBinding_IProvider_policy" />
        <soap12:binding transport="http://schemas.microsoft.com/soap/tcp" />
        <wsdl:operation name="Disconnect">
            <soap12:operation soapAction="http://tempuri.org/IProvider/Disconnect"
style="document" />
            <wsdl:input>
                <soap12:body use="literal" />
            </wsdl:input>
        </wsdl:operation>
        <wsdl:operation name="RaiseOperationInvokeEvent">
            <soap12:operation
soapAction="http://tempuri.org/IProvider/RaiseOperationInvokeEvent" style="document" />
            <wsdl:output>
                <soap12:body use="literal" />
            </wsdl:output>
        </wsdl:operation>
    </wsdl:binding>
    <wsdl:binding name="CustomBinding_IPasswordSyncClientProvider"
type="tns:IPasswordSyncClientProvider">
        <wsp:PolicyReference URI="#CustomBinding_IPasswordSyncClientProvider_policy" />
        <soap12:binding transport="http://schemas.microsoft.com/soap/tcp" />
        <wsdl:operation name="Disconnect">
            <soap12:operation soapAction="http://tempuri.org/IProvider/Disconnect"
style="document" />
            <wsdl:input>
                <soap12:body use="literal" />
            </wsdl:input>
        </wsdl:operation>
        <wsdl:operation name="RaiseOperationInvokeEvent">
            <soap12:operation
soapAction="http://tempuri.org/IProvider/RaiseOperationInvokeEvent" style="document" />
            <wsdl:output>
                <soap12:body use="literal" />
            </wsdl:output>
        </wsdl:operation>
        <wsdl:operation name="GetPasswordChangeStatus">
            <soap12:operation
soapAction="http://tempuri.org/IPasswordSyncClientProvider/GetPasswordChangeStatus"
style="document" />
            <wsdl:input>
                <soap12:body use="literal" />
            </wsdl:input>
            <wsdl:output>
                <soap12:body use="literal" />
            </wsdl:output>
            <wsdl:fault name="PwdSyncConfigurationExceptionFault">
                <soap12:fault use="literal" name="PwdSyncConfigurationExceptionFault"
namespace="" />
                </wsdl:fault>
            </wsdl:operation>
            <wsdl:operation name="MarkUserPasswordChangeFixed">
                <soap12:operation
soapAction="http://tempuri.org/IPasswordSyncClientProvider/MarkUserPasswordChangeFixed"
style="document" />

```

```

<wsdl:input>
    <soap12:body use="literal" />
</wsdl:input>
<wsdl:output>
    <soap12:body use="literal" />
</wsdl:output>
<wsdl:fault name="PwdSyncConfigurationExceptionFault">
    <soap12:fault use="literal" name="PwdSyncConfigurationExceptionFault" />
</wsdl:fault>
</wsdl:operation>
</wsdl:binding>
<wsdl:service name="PasswordSyncClientProvider">
    <wsdl:port name="CustomBinding_IProvider" binding="tns:CustomBinding_IProvider">
        <soap12:address
location="net.tcp://localhost:65532/Microsoft.WindowsServerSolutions.PasswordSync.PasswordSyncClientProvider/Microsoft.WindowsServerSolutions.Common.ProviderFramework.IProvider" />
        <wsa10:EndpointReference>

<wsa10:Address>net.tcp://localhost:65532/Microsoft.WindowsServerSolutions.PasswordSync.PasswordSyncClientProvider/Microsoft.WindowsServerSolutions.Common.ProviderFramework.IProvider</wsa10:Address>
            <Identity xmlns="http://schemas.xmlsoap.org/ws/2006/02/addressingidentity">
                <Dns>SERVERNAME</Dns>
            </Identity>
        </wsa10:EndpointReference>
    </wsdl:port>
    <wsdl:port name="CustomBinding_IPasswordSyncClientProvider" binding="tns:CustomBinding_IPasswordSyncClientProvider">
        <soap12:address
location="net.tcp://serverName:6602/Microsoft.WindowsServerSolutions.PasswordSync.PasswordSyncClientProvider/Microsoft.WindowsServerSolutions.PasswordSync.IPasswordSyncClientProvider" />
        <wsa10:EndpointReference>

<wsa10:Address>net.tcp://serverName:6602/Microsoft.WindowsServerSolutions.PasswordSync.PasswordSyncClientProvider/Microsoft.WindowsServerSolutions.PasswordSync.IPasswordSyncClientProvider</wsa10:Address>
            <Identity xmlns="http://schemas.xmlsoap.org/ws/2006/02/addressingidentity">
                <Dns>SERVERNAME</Dns>
            </Identity>
        </wsa10:EndpointReference>
    </wsdl:port>
</wsdl:service>
</wsdl:definitions>

```

6.10.1.2 <http://tempuri.org>

```

<?xml version="1.0" encoding="utf-8"?>
<xsschema xmlns:tns="http://tempuri.org/" elementFormDefault="qualified"
targetNamespace="http://tempuri.org/" xmlns:xs="http://www.w3.org/2001/XMLSchema">
    <xss:import schemaLocation="" namespace="http://schemas.datacontract.org/2004/07/System" />
    <xss:import schemaLocation="" namespace="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.PasswordSync" />
    <xss:element name="Disconnect">
        <xss:complexType>
            <xss:sequence />
        </xss:complexType>
    </xss:element>
    <xss:element name="RaiseOperationInvokeEvent">
        <xss:complexType>
            <xss:sequence>
                <xss:element minOccurs="0" name="operationName" nillable="true" type="xs:string" />
                <xss:element minOccurs="0" name="result" nillable="true" type="xs:anyType" />

```

```

        <xs:element xmlns:q1="http://schemas.datacontract.org/2004/07/System"
minOccurs="0" name="errorException" nillable="true" type="q1:Exception" />
    </xs:sequence>
</xs:complexType>
</xs:element>
<xs:element name="GetPasswordChangeStatus">
    <xs:complexType>
        <xs:sequence>
            <xs:element
                xmlns:q2="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.PasswordSync"
minOccurs="0" name="type" type="q2>PasswordSyncType" />
                <xs:element minOccurs="0" name="localuser" nillable="true" type="xs:string" />
            </xs:sequence>
</xs:complexType>
</xs:element>
<xs:element name="GetPasswordChangeStatusResponse">
    <xs:complexType>
        <xs:sequence>
            <xs:element
                xmlns:q3="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.PasswordSync"
minOccurs="0" name="GetPasswordChangeStatusResult" type="q3:PasswordChangeStatus" />
                </xs:sequence>
</xs:complexType>
</xs:element>
<xs:element name="MarkUserPasswordChangeFixed">
    <xs:complexType>
        <xs:sequence>
            <xs:element
                xmlns:q4="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.PasswordSync"
minOccurs="0" name="type" type="q4>PasswordSyncType" />
                    <xs:element minOccurs="0" name="localuser" nillable="true" type="xs:string" />
                </xs:sequence>
</xs:complexType>
</xs:element>
<xs:element name="MarkUserPasswordChangeFixedResponse">
    <xs:complexType>
        <xs:sequence />
</xs:complexType>
</xs:element>
</xs:schema>

```

6.10.1.3 http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.PasswordSync

```

<?xml version="1.0" encoding="utf-8"?>
<xs:schema
xmlns:tns="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.PasswordSync" elementFormDefault="qualified"
targetNamespace="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.PasswordSync" xmlns:xs="http://www.w3.org/2001/XMLSchema">
    <xs:import schemaLocation="" namespace="http://schemas.datacontract.org/2004/07/System" />
    <xs:simpleType name="PasswordSyncType">
        <xs:restriction base="xs:string">
            <xs:enumeration value="AzureAD" />
            <xs:enumeration value="HostedEmail" />
        </xs:restriction>
    </xs:simpleType>
    <xs:element name="PasswordSyncType" nillable="true" type="tns:PasswordSyncType" />
    <xs:simpleType name="PasswordChangeStatus">
        <xs:restriction base="xs:string">
            <xs:enumeration value="Unknown" />
            <xs:enumeration value="Required" />
            <xs:enumeration value="UnSubmitted" />
            <xs:enumeration value="New" />
            <xs:enumeration value="InProcess" />
            <xs:enumeration value="Success" />

```

```

<xs:enumeration value="WaitForRetry" />
<xs:enumeration value="Failed" />
<xs:enumeration value="Fixed" />
<xs:enumeration value="InvalidPassword" />
</xs:restriction>
</xs:simpleType>
<xs:element name="PasswordChangeStatus" nillable="true"
type="tns:PasswordChangeStatus" />
<xs:complexType name="PwdSyncConfigurationException">
<xs:complexContent mixed="false">
<xs:extension xmlns:q1="http://schemas.datacontract.org/2004/07/System"
base="q1:Exception" />
</xs:complexContent>
</xs:complexType>
<xs:element name="PwdSyncConfigurationException" nillable="true"
type="tns:PwdSyncConfigurationException" />
</xs:schema>

```

6.10.1.4 http://schemas.microsoft.com/2003/10/Serialization

```

<?xml version="1.0" encoding="utf-8"?>
<xs:schema xmlns:tns="http://schemas.microsoft.com/2003/10/Serialization/"
attributeFormDefault="qualified" elementFormDefault="qualified"
targetNamespace="http://schemas.microsoft.com/2003/10/Serialization/"
xmlns:xs="http://www.w3.org/2001/XMLSchema">
<xs:element name="anyType" nillable="true" type="xs:anyType" />
<xs:element name="anyURI" nillable="true" type="xs:anyURI" />
<xs:element name="base64Binary" nillable="true" type="xs:base64Binary" />
<xs:element name="boolean" nillable="true" type="xs:boolean" />
<xs:element name="byte" nillable="true" type="xs:byte" />
<xs:element name="dateTime" nillable="true" type="xs:dateTime" />
<xs:element name="decimal" nillable="true" type="xs:decimal" />
<xs:element name="double" nillable="true" type="xs:double" />
<xs:element name="float" nillable="true" type="xs:float" />
<xs:element name="int" nillable="true" type="xs:int" />
<xs:element name="long" nillable="true" type="xs:long" />
<xs:element name="QName" nillable="true" type="xs:QName" />
<xs:element name="short" nillable="true" type="xs:short" />
<xs:element name="string" nillable="true" type="xs:string" />
<xs:element name="unsignedByte" nillable="true" type="xs:unsignedByte" />
<xs:element name="unsignedInt" nillable="true" type="xs:unsignedInt" />
<xs:element name="unsignedLong" nillable="true" type="xs:unsignedLong" />
<xs:element name="unsignedShort" nillable="true" type="xs:unsignedShort" />
<xs:element name="char" nillable="true" type="tns:char" />
<xs:simpleType name="char">
<xs:restriction base="xs:int" />
</xs:simpleType>
<xs:element name="duration" nillable="true" type="tns:duration" />
<xs:simpleType name="duration">
<xs:restriction base="xs:duration">
<xs:pattern value="\-?P(\d*D) ?(T(\d*H) ?(\d*M) ?(\d*(\.\d*)?S)?)?" />
<xs:minInclusive value="-P10675199DT2H48M5.4775808S" />
<xs:maxInclusive value="P10675199DT2H48M5.4775807S" />
</xs:restriction>
</xs:simpleType>
<xs:element name="guid" nillable="true" type="tns:guid" />
<xs:simpleType name="guid">
<xs:restriction base="xs:string">
<xs:pattern value="[\da-fA-F]{8}-[\da-fA-F]{4}-[\da-fA-F]{4}-[\da-fA-F]{4}-[\da-fA-F]{12}" />
</xs:restriction>
</xs:simpleType>
<xs:attribute name="FactoryType" type="xs:QName" />
<xs:attribute name="Id" type="xs:ID" />
<xs:attribute name="Ref" type="xs:IDREF" />
</xs:schema>

```

6.10.1.5 http://schemas.datacontract.org/2004/07/System

```
<?xml version="1.0" encoding="utf-8"?>
<xss:schema xmlns:ser="http://schemas.microsoft.com/2003/10/Serialization/"
  xmlns:tns="http://schemas.datacontract.org/2004/07/System" elementFormDefault="qualified"
  targetNamespace="http://schemas.datacontract.org/2004/07/System"
  xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xss:import schemaLocation="" />
  <xss:complexType name="Exception">
    <xss:sequence>
      <xss:any minOccurs="0" maxOccurs="unbounded" namespace="##local"
        processContents="skip" />
    </xss:sequence>
    <xss:attribute ref="ser:FactoryType" />
  </xss:complexType>
  <xss:element name="Exception" nillable="true" type="tns:Exception" />
</xss:schema>
```

6.10.2 IO365ClientProvider

6.10.2.1 wsdl

```
<?xml version="1.0" encoding="utf-8"?>
<wsdl:definitions xmlns:wsap="http://schemas.xmlsoap.org/ws/2004/08/addressing/policy"
  xmlns:wsa10="http://www.w3.org/2005/08/addressing" xmlns:tns="http://tempuri.org/"
  xmlns:msc="http://schemas.microsoft.com/ws/2005/12/wsdl/contract"
  xmlns:soapenc="http://schemas.xmlsoap.org/soap/encoding/"
  xmlns:soap="http://schemas.xmlsoap.org/wsdl/soap/"
  xmlns:wsp="http://schemas.xmlsoap.org/ws/2004/09/policy"
  xmlns:wsam="http://www.w3.org/2007/05/addressing/metadata"
  xmlns:wsa="http://schemas.xmlsoap.org/ws/2004/08/addressing"
  xmlns:wsaw="http://www.w3.org/2006/05/addressing/wsdl"
  xmlns:soap12="http://schemas.xmlsoap.org/wsdl/soap12/" xmlns:wsu="http://docs.oasis-
  open.org/wss/2004/01/oasis-200401-wss-wssecurity-utility-1.0.xsd"
  xmlns:xsd="http://www.w3.org/2001/XMLSchema" name="O365ManagementProvider"
  targetNamespace="http://tempuri.org/" xmlns:wsdl="http://schemas.xmlsoap.org/wsdl/">
  <wsp:Policy wsu:Id="CustomBinding_IProvider_policy">
    <wsp:ExactlyOne>
      <wsp:All>
        <msb:BinaryEncoding
          xmlns:msb="http://schemas.microsoft.com/ws/2004/06/2004/mspolicy/netbinary1" />
        <sp:TransportBinding
          xmlns:sp="http://schemas.xmlsoap.org/ws/2005/07/securitypolicy">
          <wsp:Policy>
            <sp:TransportToken>
              <wsp:Policy>
                <msf:SslTransportSecurity
                  xmlns:msf="http://schemas.microsoft.com/ws/2006/05/framing/policy" />
              </wsp:Policy>
            </sp:TransportToken>
            <sp:AlgorithmSuite>
              <wsp:Policy>
                <sp:Basic256 />
              </wsp:Policy>
            </sp:AlgorithmSuite>
            <sp:Layout>
              <wsp:Policy>
                <sp:Strict />
              </wsp:Policy>
            </sp:Layout>
          </wsp:Policy>
        </sp:TransportBinding>
        <wsaw:UsingAddressing />
      </wsp:All>
    </wsp:ExactlyOne>
```

```

</wsp:Policy>
<wsp:Policy wsu:Id="CustomBinding_IO365Provider_policy">
    <wsp:ExactlyOne>
        <wsp:All>
            <msb:BinaryEncoding
                xmlns:msb="http://schemas.microsoft.com/ws/2004/2004/mspolicy/netbinary1" />
            <sp:TransportBinding
                xmlns:sp="http://schemas.xmlsoap.org/ws/2005/07/securitypolicy">
                <wsp:Policy>
                    <sp:TransportToken>
                        <wsp:Policy>
                            <msf:WindowsTransportSecurity
                                xmlns:msf="http://schemas.microsoft.com/ws/2006/05/framing/policy">
                                    <msf:ProtectionLevel>EncryptAndSign</msf:ProtectionLevel>
                                    </msf:WindowsTransportSecurity>
                                </wsp:Policy>
                            </sp:TransportToken>
                            <sp:AlgorithmSuite>
                                <wsp:Policy>
                                    <sp:Basic256 />
                                </wsp:Policy>
                            </sp:AlgorithmSuite>
                            <sp:Layout>
                                <wsp:Policy>
                                    <sp:Strict />
                                </wsp:Policy>
                            </sp:Layout>
                        </wsp:Policy>
                    </sp:TransportBinding>
                    <wsaw:UsingAddressing />
                </wsp:All>
            </wsp:ExactlyOne>
        </wsp:Policy>
        <wsdl:types>
            <xsd:schema targetNamespace="http://tempuri.org/Imports">
                <xsd:import schemaLocation="" namespace="http://tempuri.org/" />
                <xsd:import schemaLocation="" namespace="http://schemas.microsoft.com/2003/10/Serialization/" />
                <xsd:import schemaLocation="" namespace="http://schemas.datacontract.org/2004/07/System" />
                <xsd:import schemaLocation="" namespace="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.O365Integration" />
                <xsd:import schemaLocation="" namespace="http://schemas.datacontract.org/2004/07/System.Collections.ObjectModel" />
                <xsd:import schemaLocation="" namespace="http://schemas.microsoft.com/2003/10/Serialization/Arrays" />
                <xsd:import schemaLocation="" namespace="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.RemoteAccess.Domains" />
                <xsd:import schemaLocation="" namespace="http://schemas.datacontract.org/2004/07/System.Net" />
                <xsd:import schemaLocation="" namespace="http://schemas.datacontract.org/2004/07/System.Net.Sockets" />
                <xsd:import schemaLocation="" namespace="http://schemas.datacontract.org/2004/07/System.ServiceModel.Security" />
                <xsd:import schemaLocation="" namespace="http://schemas.datacontract.org/2004/07/System.ServiceModel" />
            </xsd:schema>
        </wsdl:types>
        <wsdl:message name="IProvider_Disconnect_InputMessage">
            <wsdl:part name="parameters" element="tns:Disconnect" />
        </wsdl:message>
        <wsdl:message name="IProvider_RaiseOperationInvokeEvent_OutputCallbackMessage">
            <wsdl:part name="parameters" element="tns:RaiseOperationInvokeEvent" />
        </wsdl:message>
        <wsdl:message name="IO365Provider_Activate_InputMessage">
            <wsdl:part name="parameters" element="tns:Activate" />
        </wsdl:message>
    </wsp:Policy>
</wsp:Policy>

```

```

<wsdl:message name="IO365Provider_ActivateAAD_InputMessage">
  <wsdl:part name="parameters" element="tns:ActivateAAD" />
</wsdl:message>
<wsdl:message name="IO365Provider_ActivateService_InputMessage">
  <wsdl:part name="parameters" element="tns:ActivateService" />
</wsdl:message>
<wsdl:message name="IO365Provider_Deactivate_InputMessage">
  <wsdl:part name="parameters" element="tns:Deactivate" />
</wsdl:message>
<wsdl:message name="IO365Provider_DeactivateService_InputMessage">
  <wsdl:part name="parameters" element="tns:DeactivateService" />
</wsdl:message>
<wsdl:message name="IO365Provider_QueryMappedOnlineUserNumber_InputMessage">
  <wsdl:part name="parameters" element="tns:QueryMappedOnlineUserNumber" />
</wsdl:message>
<wsdl:message name="IO365Provider_QueryOnlineUser_InputMessage">
  <wsdl:part name="parameters" element="tns:QueryOnlineUser" />
</wsdl:message>
<wsdl:message name="IO365Provider_QueryAllOnlineUsers_InputMessage">
  <wsdl:part name="parameters" element="tns:QueryAllOnlineUsers" />
</wsdl:message>
<wsdl:message name="IO365Provider_QueryMappedOnlineUser_InputMessage">
  <wsdl:part name="parameters" element="tns:QueryMappedOnlineUser" />
</wsdl:message>
<wsdl:message name="IO365Provider_BulkMapOnlineUsers_InputMessage">
  <wsdl:part name="parameters" element="tns:BulkMapOnlineUsers" />
</wsdl:message>
<wsdl:message name="IO365Provider_MapOnlineUser_InputMessage">
  <wsdl:part name="parameters" element="tns:MapOnlineUser" />
</wsdl:message>
<wsdl:message name="IO365Provider_UnmapOnlineUser_InputMessage">
  <wsdl:part name="parameters" element="tns:UnmapOnlineUser" />
</wsdl:message>
<wsdl:message name="IO365Provider_RemoveOnlineUserFromLocalUserName_InputMessage">
  <wsdl:part name="parameters" element="tns:RemoveOnlineUserFromLocalUserName" />
</wsdl:message>
<wsdl:message name="IO365Provider_ActivateUser_InputMessage">
  <wsdl:part name="parameters" element="tns:ActivateUser" />
</wsdl:message>
<wsdl:message name="IO365Provider_DeactivateUser_InputMessage">
  <wsdl:part name="parameters" element="tns:DeactivateUser" />
</wsdl:message>
<wsdl:message name="IO365Provider_UpdateUserPrincipalName_InputMessage">
  <wsdl:part name="parameters" element="tns:UpdateUserPrincipalName" />
</wsdl:message>
<wsdl:message name="IO365Provider_ChangePassword_InputMessage">
  <wsdl:part name="parameters" element="tns:ChangePassword" />
</wsdl:message>
<wsdl:message name="IO365Provider_SetUserLicenses_InputMessage">
  <wsdl:part name="parameters" element="tns:SetUserLicenses" />
</wsdl:message>
<wsdl:message name="IO365Provider_QueryAllMSOSecurityGroups_InputMessage">
  <wsdl:part name="parameters" element="tns:QueryAllMSOSecurityGroups" />
</wsdl:message>
<wsdl:message name="IO365Provider_QueryMSOSecurityGroup_InputMessage">
  <wsdl:part name="parameters" element="tns:QueryMSOSecurityGroup" />
</wsdl:message>
<wsdl:message name="IO365Provider_QueryMappedMSOSecurityGroup_InputMessage">
  <wsdl:part name="parameters" element="tns:QueryMappedMSOSecurityGroup" />
</wsdl:message>
<wsdl:message name="IO365Provider_MapNewMSOSecurityGroup_InputMessage">
  <wsdl:part name="parameters" element="tns:MapNewMSOSecurityGroup" />
</wsdl:message>
<wsdl:message name="IO365Provider_MapExistingMSOSecurityGroup_InputMessage">
  <wsdl:part name="parameters" element="tns:MapExistingMSOSecurityGroup" />
</wsdl:message>
<wsdl:message name="IO365Provider_UnmapMSOSecurityGroup_InputMessage">
  <wsdl:part name="parameters" element="tns:UnmapMSOSecurityGroup" />
</wsdl:message>

```

```

<wsdl:message name="IO365Provider_RemoveMappedMSOSecurityGroup_InputMessage">
  <wsdl:part name="parameters" element="tns:RemoveMappedMSOSecurityGroup" />
</wsdl:message>
<wsdl:message name="IO365Provider_QueryO365Information_InputMessage">
  <wsdl:part name="parameters" element="tns:QueryO365Information" />
</wsdl:message>
<wsdl:message name="IO365Provider_UpdateIntegrationStatus_InputMessage">
  <wsdl:part name="parameters" element="tns:UpdateIntegrationStatus" />
</wsdl:message>
<wsdl:message name="IO365Provider_SetCustomDomain_InputMessage">
  <wsdl:part name="parameters" element="tns:SetCustomDomain" />
</wsdl:message>
<wsdl:message name="IO365Provider_SetManagedDomain_InputMessage">
  <wsdl:part name="parameters" element="tns:SetManagedDomain" />
</wsdl:message>
<wsdl:message name="IO365Provider_ResetDomain_InputMessage">
  <wsdl:part name="parameters" element="tns:ResetDomain" />
</wsdl:message>
<wsdl:message name="IO365Provider_QueryDnsRecords_InputMessage">
  <wsdl:part name="parameters" element="tns:QueryDnsRecords" />
</wsdl:message>
<wsdl:message name="IO365Provider_QueryDomainConfiguration_InputMessage">
  <wsdl:part name="parameters" element="tns:QueryDomainConfiguration" />
</wsdl:message>
<wsdl:message name="IO365Provider_UpdateCustomDomain_InputMessage">
  <wsdl:part name="parameters" element="tns:UpdateCustomDomain" />
</wsdl:message>
<wsdl:message name="IO365Provider_IsLocalUserMapped_InputMessage">
  <wsdl:part name="parameters" element="tns:IsLocalUserMapped" />
</wsdl:message>
<wsdl:message name="IO365Provider_IsLocalUserMapped_OutputMessage">
  <wsdl:part name="parameters" element="tns:IsLocalUserMappedResponse" />
</wsdl:message>
<wsdl:message
name="IO365Provider_IsLocalUserMapped_O365ConfigureExceptionFault_FaultMessage">
  <wsdl:part
xmlns:q1="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.O365Inte
gration" name="detail" element="q1:O365ConfigureException" />
</wsdl:message>
<wsdl:message
name="IO365Provider_IsLocalUserMapped_SecurityAccessDeniedExceptionFault_FaultMessage">
  <wsdl:part
xmlns:q2="http://schemas.datacontract.org/2004/07/System.ServiceModel.Security"
name="detail" element="q2:SecurityAccessDeniedException" />
</wsdl:message>
<wsdl:message name="IO365Provider_IsLocalGroupMapped_InputMessage">
  <wsdl:part name="parameters" element="tns:IsLocalGroupMapped" />
</wsdl:message>
<wsdl:message name="IO365Provider_IsLocalGroupMapped_OutputMessage">
  <wsdl:part name="parameters" element="tns:IsLocalGroupMappedResponse" />
</wsdl:message>
<wsdl:message
name="IO365Provider_IsLocalGroupMapped_O365ConfigureExceptionFault_FaultMessage">
  <wsdl:part
xmlns:q3="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.O365Inte
gration" name="detail" element="q3:O365ConfigureException" />
</wsdl:message>
<wsdl:message
name="IO365Provider_IsLocalGroupMapped_SecurityAccessDeniedExceptionFault_FaultMessage">
  <wsdl:part
xmlns:q4="http://schemas.datacontract.org/2004/07/System.ServiceModel.Security"
name="detail" element="q4:SecurityAccessDeniedException" />
</wsdl:message>
<wsdl:message name="IO365Provider_GetMappedOnlineUserFromAD_InputMessage">
  <wsdl:part name="parameters" element="tns:GetMappedOnlineUserFromAD" />
</wsdl:message>
<wsdl:message name="IO365Provider_GetMappedOnlineUserFromAD_OutputMessage">
  <wsdl:part name="parameters" element="tns:GetMappedOnlineUserFromADResponse" />
</wsdl:message>

```

```

<wsdl:message
name="IO365Provider_GetMappedOnlineUserFromAD_O365ConfigureExceptionFault_FaultMessage">
  <wsdl:part
  xmlns:q5="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.O365Inte
gration" name="detail" element="q5:O365ConfigureException" />
</wsdl:message>
<wsdl:message
name="IO365Provider_GetMappedOnlineUserFromAD_SecurityAccessDeniedExceptionFault_FaultMessa
ge">
  <wsdl:part
  xmlns:q6="http://schemas.datacontract.org/2004/07/System.ServiceModel.Security"
  name="detail" element="q6:SecurityAccessDeniedException" />
</wsdl:message>
<wsdl:message name="IO365Provider_QueryUserEmails_InputMessage">
  <wsdl:part name="parameters" element="tns:QueryUserEmails" />
</wsdl:message>
<wsdl:message name="IO365Provider_SetUserEmails_InputMessage">
  <wsdl:part name="parameters" element="tns:SetUserEmails" />
</wsdl:message>
<wsdl:message name="IO365Provider_QueryO365UserWithEmails_InputMessage">
  <wsdl:part name="parameters" element="tns:QueryO365UserWithEmails" />
</wsdl:message>
<wsdl:message name="IO365Provider_UpdateO365UserWithEmails_InputMessage">
  <wsdl:part name="parameters" element="tns:UpdateO365UserWithEmails" />
</wsdl:message>
<wsdl:message name="IO365Provider_QueryAllMailboxStatistics_InputMessage">
  <wsdl:part name="parameters" element="tns:QueryAllMailboxStatistics" />
</wsdl:message>
<wsdl:message name="IO365Provider_QueryMobileDevices_InputMessage">
  <wsdl:part name="parameters" element="tns:QueryMobileDevices" />
</wsdl:message>
<wsdl:message name="IO365Provider_AllowMobileDevices_InputMessage">
  <wsdl:part name="parameters" element="tns:AllowMobileDevices" />
</wsdl:message>
<wsdl:message name="IO365Provider_BlockMobileDevices_InputMessage">
  <wsdl:part name="parameters" element="tns:BlockMobileDevices" />
</wsdl:message>
<wsdl:message name="IO365Provider_RemoveMobileDevice_InputMessage">
  <wsdl:part name="parameters" element="tns:RemoveMobileDevice" />
</wsdl:message>
<wsdl:message name="IO365Provider_WipeMobileDevice_InputMessage">
  <wsdl:part name="parameters" element="tns:WipeMobileDevice" />
</wsdl:message>
<wsdl:message name="IO365Provider_QueryMobileDevicePolicy_InputMessage">
  <wsdl:part name="parameters" element="tns:QueryMobileDevicePolicy" />
</wsdl:message>
<wsdl:message name="IO365Provider_SetMobileDevicePolicy_InputMessage">
  <wsdl:part name="parameters" element="tns:SetMobileDevicePolicy" />
</wsdl:message>
<wsdl:message name="IO365Provider_CreateMobileDevicePolicy_InputMessage">
  <wsdl:part name="parameters" element="tns>CreateMobileDevicePolicy" />
</wsdl:message>
<wsdl:message name="IO365Provider_QueryMobileDeviceAccessRules_InputMessage">
  <wsdl:part name="parameters" element="tns:QueryMobileDeviceAccessRules" />
</wsdl:message>
<wsdl:message name="IO365Provider_RemoveMobileDeviceAccessRule_InputMessage">
  <wsdl:part name="parameters" element="tns:RemoveMobileDeviceAccessRule" />
</wsdl:message>
<wsdl:message name="IO365Provider_AddMobileDeviceAccessRule_InputMessage">
  <wsdl:part name="parameters" element="tns:AddMobileDeviceAccessRule" />
</wsdl:message>
<wsdl:message name="IO365Provider_ApplyMobileDeviceAccessRule_InputMessage">
  <wsdl:part name="parameters" element="tns:ApplyMobileDeviceAccessRule" />
</wsdl:message>
<wsdl:message name="IO365Provider_QueryMobileDeviceExtraInfo_InputMessage">
  <wsdl:part name="parameters" element="tns:QueryMobileDeviceExtraInfo" />
</wsdl:message>
<wsdl:message name="IO365Provider_QueryAllExchangeGroupUsers_InputMessage">
  <wsdl:part name="parameters" element="tns:QueryAllExchangeGroupUsers" />

```

```

</wsdl:message>
<wsdl:message name="IO365Provider_QueryAllExchangeDistrGroups_InputMessage">
  <wsdl:part name="parameters" element="tns:QueryAllExchangeDistrGroups" />
</wsdl:message>
<wsdl:message name="IO365Provider_AddExchangeDistrGroup_InputMessage">
  <wsdl:part name="parameters" element="tns:AddExchangeDistrGroup" />
</wsdl:message>
<wsdl:message name="IO365Provider_UpdateExchangeDistrGroup_InputMessage">
  <wsdl:part name="parameters" element="tns:UpdateExchangeDistrGroup" />
</wsdl:message>
<wsdl:message name="IO365Provider_UpdateExchangeDistrGroupMembers_InputMessage">
  <wsdl:part name="parameters" element="tns:UpdateExchangeDistrGroupMembers" />
</wsdl:message>
<wsdl:message name="IO365Provider_DeleteExchangeDistrGroup_InputMessage">
  <wsdl:part name="parameters" element="tns:DeleteExchangeDistrGroup" />
</wsdl:message>
<wsdl:message name="IO365Provider_UpdateUserExchangeDistrGroups_InputMessage">
  <wsdl:part name="parameters" element="tns:UpdateUserExchangeDistrGroups" />
</wsdl:message>
<wsdl:message name="IO365Provider_EnsureUser_InputMessage">
  <wsdl:part name="parameters" element="tns:EnsureUser" />
</wsdl:message>
<wsdl:message name="IO365Provider_GetSiteCollectionProperties_InputMessage">
  <wsdl:part name="parameters" element="tns:GetSiteCollectionProperties" />
</wsdl:message>
<wsdl:message name="IO365Provider_GetSiteProperties_InputMessage">
  <wsdl:part name="parameters" element="tns:GetSiteProperties" />
</wsdl:message>
<wsdl:message name="IO365Provider_UpdateSiteProperties_InputMessage">
  <wsdl:part name="parameters" element="tns:UpdateSiteProperties" />
</wsdl:message>
<wsdl:message name="IO365Provider_GetSiteLibraries_InputMessage">
  <wsdl:part name="parameters" element="tns:GetSiteLibraries" />
</wsdl:message>
<wsdl:message name="IO365Provider_UpdateLibraryProperties_InputMessage">
  <wsdl:part name="parameters" element="tns:UpdateLibraryProperties" />
</wsdl:message>
<wsdl:message name="IO365Provider_AddLibrary_InputMessage">
  <wsdl:part name="parameters" element="tns:AddLibrary" />
</wsdl:message>
<wsdl:message name="IO365Provider_DeleteLibrary_InputMessage">
  <wsdl:part name="parameters" element="tns:DeleteLibrary" />
</wsdl:message>
<wsdl:message name="IO365Provider_On0365UserUpdated_OutputCallbackMessage">
  <wsdl:part name="parameters" element="tns:On0365UserUpdated" />
</wsdl:message>
<wsdl:message name="IO365Provider_On0365InformationUpdated_OutputCallbackMessage">
  <wsdl:part name="parameters" element="tns:On0365InformationUpdated" />
</wsdl:message>
<wsdl:message name="IO365Provider_On0365DomainUpdated_OutputCallbackMessage">
  <wsdl:part name="parameters" element="tns:On0365DomainUpdated" />
</wsdl:message>
<wsdl:message name="IO365Provider_OnGroupInfoUpdated_OutputCallbackMessage">
  <wsdl:part name="parameters" element="tns:OnGroupInfoUpdated" />
</wsdl:message>
<wsdl:message name="IO365Provider_OnMSOSecurityGroupUpdated_OutputCallbackMessage">
  <wsdl:part name="parameters" element="tns:OnMSOSecurityGroupUpdated" />
</wsdl:message>
<wsdl:message name="IO365Provider_OnSharePointSiteUpdated_OutputCallbackMessage">
  <wsdl:part name="parameters" element="tns:OnSharePointSiteUpdated" />
</wsdl:message>
<wsdl:message name="IO365Provider_OnSharePointLibraryAdded_OutputCallbackMessage">
  <wsdl:part name="parameters" element="tns:OnSharePointLibraryAdded" />
</wsdl:message>
<wsdl:message name="IO365Provider_OnSharePointLibraryRemoved_OutputCallbackMessage">
  <wsdl:part name="parameters" element="tns:OnSharePointLibraryRemoved" />
</wsdl:message>
<wsdl:message name="IO365Provider_OnSharePointLibraryUpdated_OutputCallbackMessage">
  <wsdl:part name="parameters" element="tns:OnSharePointLibraryUpdated" />

```

```

</wsdl:message>
<wsdl:message name="IO365Provider_OnIntegrationStatusUpdated_OutputCallbackMessage">
    <wsdl:part name="parameters" element="tns:OnIntegrationStatusUpdated" />
</wsdl:message>
<wsdl:portType msc:usingSession="true" name="IProvider">
    <wsdl:operation msc:isInitiating="true" msc:isTerminating="true"
name="Disconnect">
        <wsdl:input wsaw:Action="http://tempuri.org/IProvider/Disconnect"
message="tns:IProvider_Disconnect_InputMessage" />
    </wsdl:operation>
    <wsdl:operation msc:isInitiating="true" msc:isTerminating="false"
name="RaiseOperationInvokeEvent">
        <wsdl:output
wsaw:Action="http://tempuri.org/IProvider/RaiseOperationInvokeEvent"
message="tns:IProvider_RaiseOperationInvokeEvent_OutputCallbackMessage" />
    </wsdl:operation>
</wsdl:portType>
<wsdl:portType msc:usingSession="true" name="IO365Provider">
    <wsdl:operation msc:isInitiating="true" msc:isTerminating="true"
name="Disconnect">
        <wsdl:input wsaw:Action="http://tempuri.org/IProvider/Disconnect"
message="tns:IProvider_Disconnect_InputMessage" />
    </wsdl:operation>
    <wsdl:operation msc:isInitiating="true" msc:isTerminating="false"
name="RaiseOperationInvokeEvent">
        <wsdl:output
wsaw:Action="http://tempuri.org/IProvider/RaiseOperationInvokeEvent"
message="tns:IProvider_RaiseOperationInvokeEvent_OutputCallbackMessage" />
    </wsdl:operation>
    <wsdl:operation msc:isInitiating="true" msc:isTerminating="false"
name="Activate">
        <wsdl:input wsaw:Action="http://tempuri.org/IO365Provider/Activate"
message="tns:IO365Provider_Activate_InputMessage" />
    </wsdl:operation>
    <wsdl:operation msc:isInitiating="true" msc:isTerminating="false"
name="ActivateAAD">
        <wsdl:input wsaw:Action="http://tempuri.org/IO365Provider/ActivateAAD"
message="tns:IO365Provider_ActivateAAD_InputMessage" />
    </wsdl:operation>
    <wsdl:operation msc:isInitiating="true" msc:isTerminating="false"
name="ActivateService">
        <wsdl:input wsaw:Action="http://tempuri.org/IO365Provider/ActivateService"
message="tns:IO365Provider_ActivateService_InputMessage" />
    </wsdl:operation>
    <wsdl:operation msc:isInitiating="true" msc:isTerminating="false"
name="Deactivate">
        <wsdl:input wsaw:Action="http://tempuri.org/IO365Provider/Deactivate"
message="tns:IO365Provider_Deactivate_InputMessage" />
    </wsdl:operation>
    <wsdl:operation msc:isInitiating="true" msc:isTerminating="false"
name="DeactivateService">
        <wsdl:input wsaw:Action="http://tempuri.org/IO365Provider/DeactivateService"
message="tns:IO365Provider_DeactivateService_InputMessage" />
    </wsdl:operation>
    <wsdl:operation msc:isInitiating="true" msc:isTerminating="false"
name="QueryMappedOnlineUserNumber">
        <wsdl:input
wsaw:Action="http://tempuri.org/IO365Provider/QueryMappedOnlineUserNumber"
message="tns:IO365Provider_QueryMappedOnlineUserNumber_InputMessage" />
    </wsdl:operation>
    <wsdl:operation msc:isInitiating="true" msc:isTerminating="false"
name="QueryOnlineUser">
        <wsdl:input wsaw:Action="http://tempuri.org/IO365Provider/QueryOnlineUser"
message="tns:IO365Provider_QueryOnlineUser_InputMessage" />
    </wsdl:operation>
    <wsdl:operation msc:isInitiating="true" msc:isTerminating="false"
name="QueryAllOnlineUsers">
        <wsdl:input wsaw:Action="http://tempuri.org/IO365Provider/QueryAllOnlineUsers"
message="tns:IO365Provider_QueryAllOnlineUsers_InputMessage" />
    </wsdl:operation>

```

```

<wsdl:operation msc:isInitiating="true" msc:isTerminating="false"
name="QueryMappedOnlineUser">
    <wsdl:input wsaw:Action="http://tempuri.org/IO365Provider/QueryMappedOnlineUser"
message="tns:IO365Provider_QueryMappedOnlineUser_InputMessage" />
</wsdl:operation>
<wsdl:operation msc:isInitiating="true" msc:isTerminating="false"
name="BulkMapOnlineUsers">
    <wsdl:input wsaw:Action="http://tempuri.org/IO365Provider/BulkMapOnlineUsers"
message="tns:IO365Provider_BulkMapOnlineUsers_InputMessage" />
</wsdl:operation>
<wsdl:operation msc:isInitiating="true" msc:isTerminating="false"
name="MapOnlineUser">
    <wsdl:input wsaw:Action="http://tempuri.org/IO365Provider/MapOnlineUser"
message="tns:IO365Provider_MapOnlineUser_InputMessage" />
</wsdl:operation>
<wsdl:operation msc:isInitiating="true" msc:isTerminating="false"
name="UnmapOnlineUser">
    <wsdl:input wsaw:Action="http://tempuri.org/IO365Provider/UnmapOnlineUser"
message="tns:IO365Provider UnmapOnlineUser InputMessage" />
</wsdl:operation>
<wsdl:operation msc:isInitiating="true" msc:isTerminating="false"
name="RemoveOnlineUserFromLocalUserName">
    <wsdl:input
wsaw:Action="http://tempuri.org/IO365Provider/RemoveOnlineUserFromLocalUserName"
message="tns:IO365Provider_RemoveOnlineUserFromLocalUserName_InputMessage" />
</wsdl:operation>
<wsdl:operation msc:isInitiating="true" msc:isTerminating="false"
name="ActivateUser">
    <wsdl:input wsaw:Action="http://tempuri.org/IO365Provider/ActivateUser"
message="tns:IO365Provider_ActivateUser_InputMessage" />
</wsdl:operation>
<wsdl:operation msc:isInitiating="true" msc:isTerminating="false"
name="DeactivateUser">
    <wsdl:input wsaw:Action="http://tempuri.org/IO365Provider/DeactivateUser"
message="tns:IO365Provider_DeactivateUser_InputMessage" />
</wsdl:operation>
<wsdl:operation msc:isInitiating="true" msc:isTerminating="false"
name="UpdateUserPrincipalName">
    <wsdl:input
wsaw:Action="http://tempuri.org/IO365Provider/UpdateUserPrincipalName"
message="tns:IO365Provider_UpdateUserPrincipalName_InputMessage" />
</wsdl:operation>
<wsdl:operation msc:isInitiating="true" msc:isTerminating="false"
name="ChangePassword">
    <wsdl:input wsaw:Action="http://tempuri.org/IO365Provider/ChangePassword"
message="tns:IO365Provider ChangePassword InputMessage" />
</wsdl:operation>
<wsdl:operation msc:isInitiating="true" msc:isTerminating="false"
name="SetUserLicenses">
    <wsdl:input wsaw:Action="http://tempuri.org/IO365Provider/SetUserLicenses"
message="tns:IO365Provider_SetUserLicenses_InputMessage" />
</wsdl:operation>
<wsdl:operation msc:isInitiating="true" msc:isTerminating="false"
name="QueryAllMSOSecurityGroups">
    <wsdl:input
wsaw:Action="http://tempuri.org/IO365Provider/QueryAllMSOSecurityGroups"
message="tns:IO365Provider_QueryAllMSOSecurityGroups_InputMessage" />
</wsdl:operation>
<wsdl:operation msc:isInitiating="true" msc:isTerminating="false"
name="QueryMSOSecurityGroup">
    <wsdl:input wsaw:Action="http://tempuri.org/IO365Provider/QueryMSOSecurityGroup"
message="tns:IO365Provider_QueryMSOSecurityGroup_InputMessage" />
</wsdl:operation>
<wsdl:operation msc:isInitiating="true" msc:isTerminating="false"
name="QueryMappedMSOSecurityGroup">
    <wsdl:input
wsaw:Action="http://tempuri.org/IO365Provider/QueryMappedMSOSecurityGroup"
message="tns:IO365Provider_QueryMappedMSOSecurityGroup_InputMessage" />
</wsdl:operation>

```

```

<wsdl:operation msc:isInitiating="true" msc:isTerminating="false"
name="MapNewMSOSecurityGroup">
    <wsdl:input
wsaw:Action="http://tempuri.org/IO365Provider/MapNewMSOSecurityGroup"
message="tns:IO365Provider_MapNewMSOSecurityGroup_InputMessage" />
    </wsdl:operation>
    <wsdl:operation msc:isInitiating="true" msc:isTerminating="false"
name="MapExistingMSOSecurityGroup">
    <wsdl:input
wsaw:Action="http://tempuri.org/IO365Provider/MapExistingMSOSecurityGroup"
message="tns:IO365Provider_MapExistingMSOSecurityGroup_InputMessage" />
    </wsdl:operation>
    <wsdl:operation msc:isInitiating="true" msc:isTerminating="false"
name="UnmapMSOSecurityGroup">
    <wsdl:input wsaw:Action="http://tempuri.org/IO365Provider/UnmapMSOSecurityGroup"
message="tns:IO365Provider_UnmapMSOSecurityGroup_InputMessage" />
    </wsdl:operation>
    <wsdl:operation msc:isInitiating="true" msc:isTerminating="false"
name="RemoveMappedMSOSecurityGroup">
    <wsdl:input
wsaw:Action="http://tempuri.org/IO365Provider/RemoveMappedMSOSecurityGroup"
message="tns:IO365Provider_RemoveMappedMSOSecurityGroup_InputMessage" />
    </wsdl:operation>
    <wsdl:operation msc:isInitiating="true" msc:isTerminating="false"
name="QueryO365Information">
    <wsdl:input wsaw:Action="http://tempuri.org/IO365Provider/QueryO365Information"
message="tns:IO365Provider_QueryO365Information_InputMessage" />
    </wsdl:operation>
    <wsdl:operation msc:isInitiating="true" msc:isTerminating="false"
name="UpdateIntegrationStatus">
    <wsdl:input
wsaw:Action="http://tempuri.org/IO365Provider/UpdateIntegrationStatus"
message="tns:IO365Provider_UpdateIntegrationStatus_InputMessage" />
    </wsdl:operation>
    <wsdl:operation msc:isInitiating="true" msc:isTerminating="false"
name="SetCustomDomain">
    <wsdl:input wsaw:Action="http://tempuri.org/IO365Provider/SetCustomDomain"
message="tns:IO365Provider_SetCustomDomain_InputMessage" />
    </wsdl:operation>
    <wsdl:operation msc:isInitiating="true" msc:isTerminating="false"
name="SetManagedDomain">
    <wsdl:input wsaw:Action="http://tempuri.org/IO365Provider/SetManagedDomain"
message="tns:IO365Provider_SetManagedDomain_InputMessage" />
    </wsdl:operation>
    <wsdl:operation msc:isInitiating="true" msc:isTerminating="false"
name="ResetDomain">
    <wsdl:input wsaw:Action="http://tempuri.org/IO365Provider/ResetDomain"
message="tns:IO365Provider_ResetDomain_InputMessage" />
    </wsdl:operation>
    <wsdl:operation msc:isInitiating="true" msc:isTerminating="false"
name="QueryDnsRecords">
    <wsdl:input wsaw:Action="http://tempuri.org/IO365Provider/QueryDnsRecords"
message="tns:IO365Provider_QueryDnsRecords_InputMessage" />
    </wsdl:operation>
    <wsdl:operation msc:isInitiating="true" msc:isTerminating="false"
name="QueryDomainConfiguration">
    <wsdl:input
wsaw:Action="http://tempuri.org/IO365Provider/QueryDomainConfiguration"
message="tns:IO365Provider_QueryDomainConfiguration_InputMessage" />
    </wsdl:operation>
    <wsdl:operation msc:isInitiating="true" msc:isTerminating="false"
name="UpdateCustomDomain">
    <wsdl:input wsaw:Action="http://tempuri.org/IO365Provider/UpdateCustomDomain"
message="tns:IO365Provider_UpdateCustomDomain_InputMessage" />
    </wsdl:operation>
    <wsdl:operation msc:isInitiating="true" msc:isTerminating="false"
name="IsLocalUserMapped">
    <wsdl:input wsaw:Action="http://tempuri.org/IO365Provider/IsLocalUserMapped"
message="tns:IO365Provider_IsLocalUserMapped_InputMessage" />

```

```

        <wsdl:output
wsaw:Action="http://tempuri.org/IO365Provider/IsLocalUserMappedResponse"
message="tns:IO365Provider_IsLocalUserMapped_OutputMessage" />
        <wsdl:fault
wsaw:Action="http://tempuri.org/IO365Provider/IsLocalUserMappedO365ConfigureExceptionFault"
name="O365ConfigureExceptionFault"
message="tns:IO365Provider_IsLocalUserMapped_O365ConfigureExceptionFault_FaultMessage" />
        <wsdl:fault
wsaw:Action="http://tempuri.org/IO365Provider/IsLocalUserMappedSecurityAccessDeniedExceptionFault"
name="SecurityAccessDeniedExceptionFault"
message="tns:IO365Provider_IsLocalUserMapped_SecurityAccessDeniedExceptionFault_FaultMessage" />
        </wsdl:operation>
        <wsdl:operation msc:isInitiating="true" msc:isTerminating="false"
name="IsLocalGroupMapped">
        <wsdl:input wsaw:Action="http://tempuri.org/IO365Provider/IsLocalGroupMapped"
message="tns:IO365Provider_IsLocalGroupMapped_InputMessage" />
        <wsdl:output
wsaw:Action="http://tempuri.org/IO365Provider/IsLocalGroupMappedResponse"
message="tns:IO365Provider_IsLocalGroupMapped_OutputMessage" />
        <wsdl:fault
wsaw:Action="http://tempuri.org/IO365Provider/IsLocalGroupMappedO365ConfigureExceptionFault"
name="O365ConfigureExceptionFault"
message="tns:IO365Provider_IsLocalGroupMapped_O365ConfigureExceptionFault_FaultMessage" />
        <wsdl:fault
wsaw:Action="http://tempuri.org/IO365Provider/IsLocalGroupMappedSecurityAccessDeniedExceptionFault"
name="SecurityAccessDeniedExceptionFault"
message="tns:IO365Provider_IsLocalGroupMapped_SecurityAccessDeniedExceptionFault_FaultMessage" />
        </wsdl:operation>
        <wsdl:operation msc:isInitiating="true" msc:isTerminating="false"
name="GetMappedOnlineUserFromAD">
        <wsdl:input
wsaw:Action="http://tempuri.org/IO365Provider/GetMappedOnlineUserFromAD"
message="tns:IO365Provider_GetMappedOnlineUserFromAD_InputMessage" />
        <wsdl:output
wsaw:Action="http://tempuri.org/IO365Provider/GetMappedOnlineUserFromADResponse"
message="tns:IO365Provider_GetMappedOnlineUserFromAD_OutputMessage" />
        <wsdl:fault
wsaw:Action="http://tempuri.org/IO365Provider/GetMappedOnlineUserFromADO365ConfigureExceptionFault"
name="O365ConfigureExceptionFault"
message="tns:IO365Provider_GetMappedOnlineUserFromAD_O365ConfigureExceptionFault_FaultMessage" />
        <wsdl:fault
wsaw:Action="http://tempuri.org/IO365Provider/GetMappedOnlineUserFromADSecurityAccessDeniedExceptionFault"
name="SecurityAccessDeniedExceptionFault"
message="tns:IO365Provider_GetMappedOnlineUserFromAD_SecurityAccessDeniedExceptionFault_FaultMessage" />
        </wsdl:operation>
        <wsdl:operation msc:isInitiating="true" msc:isTerminating="false"
name="QueryUserEmails">
        <wsdl:input wsaw:Action="http://tempuri.org/IO365Provider/QueryUserEmails"
message="tns:IO365Provider_QueryUserEmails_InputMessage" />
        </wsdl:operation>
        <wsdl:operation msc:isInitiating="true" msc:isTerminating="false"
name="SetUserEmails">
        <wsdl:input wsaw:Action="http://tempuri.org/IO365Provider/SetUserEmails"
message="tns:IO365Provider_SetUserEmails_InputMessage" />
        </wsdl:operation>
        <wsdl:operation msc:isInitiating="true" msc:isTerminating="false"
name="QueryO365UserWithEmails">
        <wsdl:input
wsaw:Action="http://tempuri.org/IO365Provider/QueryO365UserWithEmails"
message="tns:IO365Provider_QueryO365UserWithEmails_InputMessage" />
        </wsdl:operation>
        <wsdl:operation msc:isInitiating="true" msc:isTerminating="false"
name="UpdateO365UserWithEmails">

```

```

        <wsdl:input
wsaw:Action="http://tempuri.org/IO365Provider/UpdateO365UserWithEmails"
message="tns:IO365Provider_UpdateO365UserWithEmails_InputMessage" />
    </wsdl:operation>
    <wsdl:operation msc:isInitiating="true" msc:isTerminating="false"
name="QueryAllMailboxStatistics">
        <wsdl:input
wsaw:Action="http://tempuri.org/IO365Provider/QueryAllMailboxStatistics"
message="tns:IO365Provider_QueryAllMailboxStatistics_InputMessage" />
    </wsdl:operation>
    <wsdl:operation msc:isInitiating="true" msc:isTerminating="false"
name="QueryMobileDevices">
        <wsdl:input wsaw:Action="http://tempuri.org/IO365Provider/QueryMobileDevices"
message="tns:IO365Provider_QueryMobileDevices_InputMessage" />
    </wsdl:operation>
    <wsdl:operation msc:isInitiating="true" msc:isTerminating="false"
name="AllowMobileDevices">
        <wsdl:input wsaw:Action="http://tempuri.org/IO365Provider/AllowMobileDevices"
message="tns:IO365Provider.AllowMobileDevices_InputMessage" />
    </wsdl:operation>
    <wsdl:operation msc:isInitiating="true" msc:isTerminating="false"
name="BlockMobileDevices">
        <wsdl:input wsaw:Action="http://tempuri.org/IO365Provider/BlockMobileDevices"
message="tns:IO365Provider_BlockMobileDevices_InputMessage" />
    </wsdl:operation>
    <wsdl:operation msc:isInitiating="true" msc:isTerminating="false"
name="RemoveMobileDevice">
        <wsdl:input wsaw:Action="http://tempuri.org/IO365Provider/RemoveMobileDevice"
message="tns:IO365Provider.RemoveMobileDevice_InputMessage" />
    </wsdl:operation>
    <wsdl:operation msc:isInitiating="true" msc:isTerminating="false"
name="WipeMobileDevice">
        <wsdl:input wsaw:Action="http://tempuri.org/IO365Provider/WipeMobileDevice"
message="tns:IO365Provider.WipeMobileDevice_InputMessage" />
    </wsdl:operation>
    <wsdl:operation msc:isInitiating="true" msc:isTerminating="false"
name="QueryMobileDevicePolicy">
        <wsdl:input
wsaw:Action="http://tempuri.org/IO365Provider/QueryMobileDevicePolicy"
message="tns:IO365Provider.QueryMobileDevicePolicy_InputMessage" />
    </wsdl:operation>
    <wsdl:operation msc:isInitiating="true" msc:isTerminating="false"
name="SetMobileDevicePolicy">
        <wsdl:input wsaw:Action="http://tempuri.org/IO365Provider/SetMobileDevicePolicy"
message="tns:IO365Provider_SetMobileDevicePolicy_InputMessage" />
    </wsdl:operation>
    <wsdl:operation msc:isInitiating="true" msc:isTerminating="false"
name="CreateMobileDevicePolicy">
        <wsdl:input
wsaw:Action="http://tempuri.org/IO365Provider/CreateMobileDevicePolicy"
message="tns:IO365Provider_CreateMobileDevicePolicy_InputMessage" />
    </wsdl:operation>
    <wsdl:operation msc:isInitiating="true" msc:isTerminating="false"
name="QueryMobileDeviceAccessRules">
        <wsdl:input
wsaw:Action="http://tempuri.org/IO365Provider/QueryMobileDeviceAccessRules"
message="tns:IO365Provider.QueryMobileDeviceAccessRules_InputMessage" />
    </wsdl:operation>
    <wsdl:operation msc:isInitiating="true" msc:isTerminating="false"
name="RemoveMobileDeviceAccessRule">
        <wsdl:input
wsaw:Action="http://tempuri.org/IO365Provider/RemoveMobileDeviceAccessRule"
message="tns:IO365Provider.RemoveMobileDeviceAccessRule_InputMessage" />
    </wsdl:operation>
    <wsdl:operation msc:isInitiating="true" msc:isTerminating="false"
name="AddMobileDeviceAccessRule">
        <wsdl:input
wsaw:Action="http://tempuri.org/IO365Provider/AddMobileDeviceAccessRule"
message="tns:IO365Provider.AddMobileDeviceAccessRule_InputMessage" />

```

```

        </wsdl:operation>
        <wsdl:operation msc:isInitiating="true" msc:isTerminating="false"
name="ApplyMobileDeviceAccessRule">
            <wsdl:input
wsaw:Action="http://tempuri.org/IO365Provider/ApplyMobileDeviceAccessRule"
message="tns:IO365Provider_ApplyMobileDeviceAccessRule_InputMessage" />
        </wsdl:operation>
        <wsdl:operation msc:isInitiating="true" msc:isTerminating="false"
name="QueryMobileDeviceExtraInfo">
            <wsdl:input
wsaw:Action="http://tempuri.org/IO365Provider/QueryMobileDeviceExtraInfo"
message="tns:IO365Provider_QueryMobileDeviceExtraInfo_InputMessage" />
        </wsdl:operation>
        <wsdl:operation msc:isInitiating="true" msc:isTerminating="false"
name="QueryAllExchangeGroupUsers">
            <wsdl:input
wsaw:Action="http://tempuri.org/IO365Provider/QueryAllExchangeGroupUsers"
message="tns:IO365Provider_QueryAllExchangeGroupUsers_InputMessage" />
        </wsdl:operation>
        <wsdl:operation msc:isInitiating="true" msc:isTerminating="false"
name="QueryAllExchangeDistrGroups">
            <wsdl:input
wsaw:Action="http://tempuri.org/IO365Provider/QueryAllExchangeDistrGroups"
message="tns:IO365Provider_QueryAllExchangeDistrGroups_InputMessage" />
        </wsdl:operation>
        <wsdl:operation msc:isInitiating="true" msc:isTerminating="false"
name="AddExchangeDistrGroup">
            <wsdl:input wsaw:Action="http://tempuri.org/IO365Provider/AddExchangeDistrGroup"
message="tns:IO365Provider_AddExchangeDistrGroup_InputMessage" />
        </wsdl:operation>
        <wsdl:operation msc:isInitiating="true" msc:isTerminating="false"
name="UpdateExchangeDistrGroup">
            <wsdl:input
wsaw:Action="http://tempuri.org/IO365Provider/UpdateExchangeDistrGroup"
message="tns:IO365Provider_UpdateExchangeDistrGroup_InputMessage" />
        </wsdl:operation>
        <wsdl:operation msc:isInitiating="true" msc:isTerminating="false"
name="UpdateExchangeDistrGroupMembers">
            <wsdl:input
wsaw:Action="http://tempuri.org/IO365Provider/UpdateExchangeDistrGroupMembers"
message="tns:IO365Provider_UpdateExchangeDistrGroupMembers_InputMessage" />
        </wsdl:operation>
        <wsdl:operation msc:isInitiating="true" msc:isTerminating="false"
name="DeleteExchangeDistrGroup">
            <wsdl:input
wsaw:Action="http://tempuri.org/IO365Provider/DeleteExchangeDistrGroup"
message="tns:IO365Provider_DeleteExchangeDistrGroup_InputMessage" />
        </wsdl:operation>
        <wsdl:operation msc:isInitiating="true" msc:isTerminating="false"
name="UpdateUserExchangeDistrGroups">
            <wsdl:input
wsaw:Action="http://tempuri.org/IO365Provider/UpdateUserExchangeDistrGroups"
message="tns:IO365Provider_UpdateUserExchangeDistrGroups_InputMessage" />
        </wsdl:operation>
        <wsdl:operation msc:isInitiating="true" msc:isTerminating="false"
name="EnsureUser">
            <wsdl:input wsaw:Action="http://tempuri.org/IO365Provider/EnsureUser"
message="tns:IO365Provider_EnsureUser_InputMessage" />
        </wsdl:operation>
        <wsdl:operation msc:isInitiating="true" msc:isTerminating="false"
name="GetSiteCollectionProperties">
            <wsdl:input
wsaw:Action="http://tempuri.org/IO365Provider/GetSiteCollectionProperties"
message="tns:IO365Provider_GetSiteCollectionProperties_InputMessage" />
        </wsdl:operation>
        <wsdl:operation msc:isInitiating="true" msc:isTerminating="false"
name="GetSiteProperties">
            <wsdl:input wsaw:Action="http://tempuri.org/IO365Provider/GetSiteProperties"
message="tns:IO365Provider_GetSiteProperties_InputMessage" />

```

```

        </wsdl:operation>
        <wsdl:operation msc:isInitiating="true" msc:isTerminating="false"
name="UpdateSiteProperties">
            <wsdl:input wsaw:Action="http://tempuri.org/IO365Provider/UpdateSiteProperties"
message="tns:IO365Provider_UpdateSiteProperties_InputMessage" />
        </wsdl:operation>
        <wsdl:operation msc:isInitiating="true" msc:isTerminating="false"
name="GetSiteLibraries">
            <wsdl:input wsaw:Action="http://tempuri.org/IO365Provider/GetSiteLibraries"
message="tns:IO365Provider_GetSiteLibraries_InputMessage" />
        </wsdl:operation>
        <wsdl:operation msc:isInitiating="true" msc:isTerminating="false"
name="UpdateLibraryProperties">
            <wsdl:input
wsaw:Action="http://tempuri.org/IO365Provider/UpdateLibraryProperties"
message="tns:IO365Provider_UpdateLibraryProperties_InputMessage" />
        </wsdl:operation>
        <wsdl:operation msc:isInitiating="true" msc:isTerminating="false"
name="AddLibrary">
            <wsdl:input wsaw:Action="http://tempuri.org/IO365Provider/AddLibrary"
message="tns:IO365Provider_AddLibrary_InputMessage" />
        </wsdl:operation>
        <wsdl:operation msc:isInitiating="true" msc:isTerminating="false"
name="DeleteLibrary">
            <wsdl:input wsaw:Action="http://tempuri.org/IO365Provider/DeleteLibrary"
message="tns:IO365Provider_DeleteLibrary_InputMessage" />
        </wsdl:operation>
        <wsdl:operation msc:isInitiating="true" msc:isTerminating="false"
name="OnO365UserUpdated">
            <wsdl:output wsaw:Action="http://tempuri.org/IO365Provider/OnO365UserUpdated"
message="tns:IO365Provider_OnO365UserUpdated_OutputCallbackMessage" />
        </wsdl:operation>
        <wsdl:operation msc:isInitiating="true" msc:isTerminating="false"
name="OnO365InformationUpdated">
            <wsdl:output
wsaw:Action="http://tempuri.org/IO365Provider/OnO365InformationUpdated"
message="tns:IO365Provider_OnO365InformationUpdated_OutputCallbackMessage" />
        </wsdl:operation>
        <wsdl:operation msc:isInitiating="true" msc:isTerminating="false"
name="OnO365DomainUpdated">
            <wsdl:output wsaw:Action="http://tempuri.org/IO365Provider/OnO365DomainUpdated"
message="tns:IO365Provider_OnO365DomainUpdated_OutputCallbackMessage" />
        </wsdl:operation>
        <wsdl:operation msc:isInitiating="true" msc:isTerminating="false"
name="OnGroupInfoUpdated">
            <wsdl:output wsaw:Action="http://tempuri.org/IO365Provider/OnGroupInfoUpdated"
message="tns:IO365Provider_OnGroupInfoUpdated_OutputCallbackMessage" />
        </wsdl:operation>
        <wsdl:operation msc:isInitiating="true" msc:isTerminating="false"
name="OnMSOSecurityGroupUpdated">
            <wsdl:output
wsaw:Action="http://tempuri.org/IO365Provider/OnMSOSecurityGroupUpdated"
message="tns:IO365Provider_OnMSOSecurityGroupUpdated_OutputCallbackMessage" />
        </wsdl:operation>
        <wsdl:operation msc:isInitiating="true" msc:isTerminating="false"
name="OnSharePointSiteUpdated">
            <wsdl:output
wsaw:Action="http://tempuri.org/IO365Provider/OnSharePointSiteUpdated"
message="tns:IO365Provider_OnSharePointSiteUpdated_OutputCallbackMessage" />
        </wsdl:operation>
        <wsdl:operation msc:isInitiating="true" msc:isTerminating="false"
name="OnSharePointLibraryAdded">
            <wsdl:output
wsaw:Action="http://tempuri.org/IO365Provider/OnSharePointLibraryAdded"
message="tns:IO365Provider_OnSharePointLibraryAdded_OutputCallbackMessage" />
        </wsdl:operation>
        <wsdl:operation msc:isInitiating="true" msc:isTerminating="false"
name="OnSharePointLibraryRemoved">

```

```

        <wsdl:output
wsaw:Action="http://tempuri.org/IO365Provider/OnSharePointLibraryRemoved"
message="tns:IO365Provider_OnSharePointLibraryRemoved_OutputCallbackMessage" />
        </wsdl:operation>
        <wsdl:operation msc:isInitiating="true" msc:isTerminating="false"
name="OnSharePointLibraryUpdated">
        <wsdl:output
wsaw:Action="http://tempuri.org/IO365Provider/OnSharePointLibraryUpdated"
message="tns:IO365Provider_OnSharePointLibraryUpdated_OutputCallbackMessage" />
        </wsdl:operation>
        <wsdl:operation msc:isInitiating="true" msc:isTerminating="false"
name="OnIntegrationStatusUpdated">
        <wsdl:output
wsaw:Action="http://tempuri.org/IO365Provider/OnIntegrationStatusUpdated"
message="tns:IO365Provider_OnIntegrationStatusUpdated_OutputCallbackMessage" />
        </wsdl:operation>
</wsdl:portType>
<wsdl:binding name="CustomBinding_IProvider" type="tns:IProvider">
    <wsp:PolicyReference URI="#CustomBinding_IProvider_policy" />
    <soap12:binding transport="http://schemas.microsoft.com/soap/tcp" />
    <wsdl:operation name="Disconnect">
        <soap12:operation soapAction="http://tempuri.org/IProvider/Disconnect"
style="document" />
        <wsdl:input>
            <soap12:body use="literal" />
        </wsdl:input>
    </wsdl:operation>
    <wsdl:operation name="RaiseOperationInvokeEvent">
        <soap12:operation
soapAction="http://tempuri.org/IProvider/RaiseOperationInvokeEvent" style="document" />
        <wsdl:output>
            <soap12:body use="literal" />
        </wsdl:output>
    </wsdl:operation>
</wsdl:binding>
<wsdl:binding name="CustomBinding_IO365Provider" type="tns:IO365Provider">
    <wsp:PolicyReference URI="#CustomBinding_IO365Provider_policy" />
    <soap12:binding transport="http://schemas.microsoft.com/soap/tcp" />
    <wsdl:operation name="Disconnect">
        <soap12:operation soapAction="http://tempuri.org/IProvider/Disconnect"
style="document" />
        <wsdl:input>
            <soap12:body use="literal" />
        </wsdl:input>
    </wsdl:operation>
    <wsdl:operation name="RaiseOperationInvokeEvent">
        <soap12:operation
soapAction="http://tempuri.org/IProvider/RaiseOperationInvokeEvent" style="document" />
        <wsdl:output>
            <soap12:body use="literal" />
        </wsdl:output>
    </wsdl:operation>
    <wsdl:operation name="Activate">
        <soap12:operation soapAction="http://tempuri.org/IO365Provider/Activate"
style="document" />
        <wsdl:input>
            <soap12:body use="literal" />
        </wsdl:input>
    </wsdl:operation>
    <wsdl:operation name="ActivateAAD">
        <soap12:operation soapAction="http://tempuri.org/IO365Provider/ActivateAAD"
style="document" />
        <wsdl:input>
            <soap12:body use="literal" />
        </wsdl:input>
    </wsdl:operation>
    <wsdl:operation name="ActivateService">
        <soap12:operation soapAction="http://tempuri.org/IO365Provider/ActivateService"
style="document" />

```

```

        <wsdl:input>
            <soap12:body use="literal" />
        </wsdl:input>
    </wsdl:operation>
    <wsdl:operation name="Deactivate">
        <soap12:operation soapAction="http://tempuri.org/IO365Provider/Deactivate"
style="document" />
        <wsdl:input>
            <soap12:body use="literal" />
        </wsdl:input>
    </wsdl:operation>
    <wsdl:operation name="DeactivateService">
        <soap12:operation
soapAction="http://tempuri.org/IO365Provider/DeactivateService" style="document" />
        <wsdl:input>
            <soap12:body use="literal" />
        </wsdl:input>
    </wsdl:operation>
    <wsdl:operation name="QueryMappedOnlineUserNumber">
        <soap12:operation
soapAction="http://tempuri.org/IO365Provider/QueryMappedOnlineUserNumber" style="document"
/>
        <wsdl:input>
            <soap12:body use="literal" />
        </wsdl:input>
    </wsdl:operation>
    <wsdl:operation name="QueryOnlineUser">
        <soap12:operation soapAction="http://tempuri.org/IO365Provider/QueryOnlineUser"
style="document" />
        <wsdl:input>
            <soap12:body use="literal" />
        </wsdl:input>
    </wsdl:operation>
    <wsdl:operation name="QueryAllOnlineUsers">
        <soap12:operation
soapAction="http://tempuri.org/IO365Provider/QueryAllOnlineUsers" style="document" />
        <wsdl:input>
            <soap12:body use="literal" />
        </wsdl:input>
    </wsdl:operation>
    <wsdl:operation name="QueryMappedOnlineUser">
        <soap12:operation
soapAction="http://tempuri.org/IO365Provider/QueryMappedOnlineUser" style="document" />
        <wsdl:input>
            <soap12:body use="literal" />
        </wsdl:input>
    </wsdl:operation>
    <wsdl:operation name="BulkMapOnlineUsers">
        <soap12:operation
soapAction="http://tempuri.org/IO365Provider/BulkMapOnlineUsers" style="document" />
        <wsdl:input>
            <soap12:body use="literal" />
        </wsdl:input>
    </wsdl:operation>
    <wsdl:operation name="MapOnlineUser">
        <soap12:operation soapAction="http://tempuri.org/IO365Provider/MapOnlineUser"
style="document" />
        <wsdl:input>
            <soap12:body use="literal" />
        </wsdl:input>
    </wsdl:operation>
    <wsdl:operation name="UnmapOnlineUser">
        <soap12:operation soapAction="http://tempuri.org/IO365Provider/UnmapOnlineUser"
style="document" />
        <wsdl:input>
            <soap12:body use="literal" />
        </wsdl:input>
    </wsdl:operation>
    <wsdl:operation name="RemoveOnlineUserFromLocalUserName">

```

```

        <soap12:operation
soapAction="http://tempuri.org/IO365Provider/RemoveOnlineUserFromLocalUserName"
style="document" />
        <wsdl:input>
            <soap12:body use="literal" />
        </wsdl:input>
    </wsdl:operation>
    <wsdl:operation name="ActivateUser">
        <soap12:operation soapAction="http://tempuri.org/IO365Provider/ActivateUser"
style="document" />
        <wsdl:input>
            <soap12:body use="literal" />
        </wsdl:input>
    </wsdl:operation>
    <wsdl:operation name="DeactivateUser">
        <soap12:operation soapAction="http://tempuri.org/IO365Provider/DeactivateUser"
style="document" />
        <wsdl:input>
            <soap12:body use="literal" />
        </wsdl:input>
    </wsdl:operation>
    <wsdl:operation name="UpdateUserPrincipalName">
        <soap12:operation
soapAction="http://tempuri.org/IO365Provider/UpdateUserPrincipalName" style="document" />
        <wsdl:input>
            <soap12:body use="literal" />
        </wsdl:input>
    </wsdl:operation>
    <wsdl:operation name="ChangePassword">
        <soap12:operation soapAction="http://tempuri.org/IO365Provider/ChangePassword"
style="document" />
        <wsdl:input>
            <soap12:body use="literal" />
        </wsdl:input>
    </wsdl:operation>
    <wsdl:operation name="SetUserLicenses">
        <soap12:operation soapAction="http://tempuri.org/IO365Provider/SetUserLicenses"
style="document" />
        <wsdl:input>
            <soap12:body use="literal" />
        </wsdl:input>
    </wsdl:operation>
    <wsdl:operation name="QueryAllMSOSecurityGroups">
        <soap12:operation
soapAction="http://tempuri.org/IO365Provider/QueryAllMSOSecurityGroups" style="document" />
        <wsdl:input>
            <soap12:body use="literal" />
        </wsdl:input>
    </wsdl:operation>
    <wsdl:operation name="QueryMSOSecurityGroup">
        <soap12:operation
soapAction="http://tempuri.org/IO365Provider/QueryMSOSecurityGroup" style="document" />
        <wsdl:input>
            <soap12:body use="literal" />
        </wsdl:input>
    </wsdl:operation>
    <wsdl:operation name="QueryMappedMSOSecurityGroup">
        <soap12:operation
soapAction="http://tempuri.org/IO365Provider/QueryMappedMSOSecurityGroup" style="document" />
        <wsdl:input>
            <soap12:body use="literal" />
        </wsdl:input>
    </wsdl:operation>
    <wsdl:operation name="MapNewMSOSecurityGroup">
        <soap12:operation
soapAction="http://tempuri.org/IO365Provider/MapNewMSOSecurityGroup" style="document" />
        <wsdl:input>
            <soap12:body use="literal" />

```

```

        </wsdl:input>
    </wsdl:operation>
    <wsdl:operation name="MapExistingMSOSecurityGroup">
        <soap12:operation
soapAction="http://tempuri.org/IO365Provider/MapExistingMSOSecurityGroup" style="document"
/>
        <wsdl:input>
            <soap12:body use="literal" />
        </wsdl:input>
    </wsdl:operation>
    <wsdl:operation name="UnmapMSOSecurityGroup">
        <soap12:operation
soapAction="http://tempuri.org/IO365Provider/UnmapMSOSecurityGroup" style="document" />
        <wsdl:input>
            <soap12:body use="literal" />
        </wsdl:input>
    </wsdl:operation>
    <wsdl:operation name="RemoveMappedMSOSecurityGroup">
        <soap12:operation
soapAction="http://tempuri.org/IO365Provider/RemoveMappedMSOSecurityGroup" style="document"
/>
        <wsdl:input>
            <soap12:body use="literal" />
        </wsdl:input>
    </wsdl:operation>
    <wsdl:operation name="Query0365Information">
        <soap12:operation
soapAction="http://tempuri.org/IO365Provider/Query0365Information" style="document" />
        <wsdl:input>
            <soap12:body use="literal" />
        </wsdl:input>
    </wsdl:operation>
    <wsdl:operation name="UpdateIntegrationStatus">
        <soap12:operation
soapAction="http://tempuri.org/IO365Provider/UpdateIntegrationStatus" style="document" />
        <wsdl:input>
            <soap12:body use="literal" />
        </wsdl:input>
    </wsdl:operation>
    <wsdl:operation name="SetCustomDomain">
        <soap12:operation soapAction="http://tempuri.org/IO365Provider/SetCustomDomain"
style="document" />
        <wsdl:input>
            <soap12:body use="literal" />
        </wsdl:input>
    </wsdl:operation>
    <wsdl:operation name="SetManagedDomain">
        <soap12:operation soapAction="http://tempuri.org/IO365Provider/SetManagedDomain"
style="document" />
        <wsdl:input>
            <soap12:body use="literal" />
        </wsdl:input>
    </wsdl:operation>
    <wsdl:operation name="ResetDomain">
        <soap12:operation soapAction="http://tempuri.org/IO365Provider/ResetDomain"
style="document" />
        <wsdl:input>
            <soap12:body use="literal" />
        </wsdl:input>
    </wsdl:operation>
    <wsdl:operation name="QueryDnsRecords">
        <soap12:operation soapAction="http://tempuri.org/IO365Provider/QueryDnsRecords"
style="document" />
        <wsdl:input>
            <soap12:body use="literal" />
        </wsdl:input>
    </wsdl:operation>
    <wsdl:operation name="QueryDomainConfiguration">

```

```

<soap12:operation
soapAction="http://tempuri.org/IO365Provider/QueryDomainConfiguration" style="document" />
<wsdl:input>
    <soap12:body use="literal" />
</wsdl:input>
</wsdl:operation>
<wsdl:operation name="UpdateCustomDomain">
    <soap12:operation
soapAction="http://tempuri.org/IO365Provider/UpdateCustomDomain" style="document" />
<wsdl:input>
    <soap12:body use="literal" />
</wsdl:input>
</wsdl:operation>
<wsdl:operation name="IsLocalUserMapped">
    <soap12:operation
soapAction="http://tempuri.org/IO365Provider/IsLocalUserMapped" style="document" />
<wsdl:input>
    <soap12:body use="literal" />
</wsdl:input>
<wsdl:output>
    <soap12:body use="literal" />
</wsdl:output>
<wsdl:fault name="O365ConfigureExceptionFault">
    <soap12:fault use="literal" name="O365ConfigureExceptionFault" namespace="" />
</wsdl:fault>
<wsdl:fault name="SecurityAccessDeniedExceptionFault">
    <soap12:fault use="literal" name="SecurityAccessDeniedExceptionFault" namespace="" />
</wsdl:fault>
</wsdl:operation>
<wsdl:operation name="IsLocalGroupMapped">
    <soap12:operation
soapAction="http://tempuri.org/IO365Provider/IsLocalGroupMapped" style="document" />
<wsdl:input>
    <soap12:body use="literal" />
</wsdl:input>
<wsdl:output>
    <soap12:body use="literal" />
</wsdl:output>
<wsdl:fault name="O365ConfigureExceptionFault">
    <soap12:fault use="literal" name="O365ConfigureExceptionFault" namespace="" />
</wsdl:fault>
<wsdl:fault name="SecurityAccessDeniedExceptionFault">
    <soap12:fault use="literal" name="SecurityAccessDeniedExceptionFault" namespace="" />
</wsdl:fault>
</wsdl:operation>
<wsdl:operation name="GetMappedOnlineUserFromAD">
    <soap12:operation
soapAction="http://tempuri.org/IO365Provider/GetMappedOnlineUserFromAD" style="document" />
<wsdl:input>
    <soap12:body use="literal" />
</wsdl:input>
<wsdl:output>
    <soap12:body use="literal" />
</wsdl:output>
<wsdl:fault name="O365ConfigureExceptionFault">
    <soap12:fault use="literal" name="O365ConfigureExceptionFault" namespace="" />
</wsdl:fault>
<wsdl:fault name="SecurityAccessDeniedExceptionFault">
    <soap12:fault use="literal" name="SecurityAccessDeniedExceptionFault" namespace="" />
</wsdl:fault>
</wsdl:operation>
<wsdl:operation name="QueryUserEmails">
    <soap12:operation soapAction="http://tempuri.org/IO365Provider/QueryUserEmails" style="document" />
<wsdl:input>
    <soap12:body use="literal" />

```

```

        </wsdl:input>
    </wsdl:operation>
    <wsdl:operation name="SetUserEmails">
        <soap12:operation soapAction="http://tempuri.org/IO365Provider/SetUserEmails"
style="document" />
        <wsdl:input>
            <soap12:body use="literal" />
        </wsdl:input>
    </wsdl:operation>
    <wsdl:operation name="QueryO365UserWithEmails">
        <soap12:operation
soapAction="http://tempuri.org/IO365Provider/QueryO365UserWithEmails" style="document" />
        <wsdl:input>
            <soap12:body use="literal" />
        </wsdl:input>
    </wsdl:operation>
    <wsdl:operation name="UpdateO365UserWithEmails">
        <soap12:operation
soapAction="http://tempuri.org/IO365Provider/UpdateO365UserWithEmails" style="document" />
        <wsdl:input>
            <soap12:body use="literal" />
        </wsdl:input>
    </wsdl:operation>
    <wsdl:operation name="QueryAllMailboxStatistics">
        <soap12:operation
soapAction="http://tempuri.org/IO365Provider/QueryAllMailboxStatistics" style="document" />
        <wsdl:input>
            <soap12:body use="literal" />
        </wsdl:input>
    </wsdl:operation>
    <wsdl:operation name="QueryMobileDevices">
        <soap12:operation
soapAction="http://tempuri.org/IO365Provider/QueryMobileDevices" style="document" />
        <wsdl:input>
            <soap12:body use="literal" />
        </wsdl:input>
    </wsdl:operation>
    <wsdl:operation name="AllowMobileDevices">
        <soap12:operation
soapAction="http://tempuri.org/IO365Provider/AllowMobileDevices" style="document" />
        <wsdl:input>
            <soap12:body use="literal" />
        </wsdl:input>
    </wsdl:operation>
    <wsdl:operation name="BlockMobileDevices">
        <soap12:operation
soapAction="http://tempuri.org/IO365Provider/BlockMobileDevices" style="document" />
        <wsdl:input>
            <soap12:body use="literal" />
        </wsdl:input>
    </wsdl:operation>
    <wsdl:operation name="RemoveMobileDevice">
        <soap12:operation
soapAction="http://tempuri.org/IO365Provider/RemoveMobileDevice" style="document" />
        <wsdl:input>
            <soap12:body use="literal" />
        </wsdl:input>
    </wsdl:operation>
    <wsdl:operation name="WipeMobileDevice">
        <soap12:operation soapAction="http://tempuri.org/IO365Provider/WipeMobileDevice"
style="document" />
        <wsdl:input>
            <soap12:body use="literal" />
        </wsdl:input>
    </wsdl:operation>
    <wsdl:operation name="QueryMobileDevicePolicy">
        <soap12:operation
soapAction="http://tempuri.org/IO365Provider/QueryMobileDevicePolicy" style="document" />
        <wsdl:input>

```

```

        <soap12:body use="literal" />
    </wsdl:input>
</wsdl:operation>
<wsdl:operation name="SetMobileDevicePolicy">
    <soap12:operation
soapAction="http://tempuri.org/IO365Provider/SetMobileDevicePolicy" style="document" />
    <wsdl:input>
        <soap12:body use="literal" />
    </wsdl:input>
</wsdl:operation>
<wsdl:operation name="CreateMobileDevicePolicy">
    <soap12:operation
soapAction="http://tempuri.org/IO365Provider/CreateMobileDevicePolicy" style="document" />
    <wsdl:input>
        <soap12:body use="literal" />
    </wsdl:input>
</wsdl:operation>
<wsdl:operation name="QueryMobileDeviceAccessRules">
    <soap12:operation
soapAction="http://tempuri.org/IO365Provider/QueryMobileDeviceAccessRules" style="document" />
    <wsdl:input>
        <soap12:body use="literal" />
    </wsdl:input>
</wsdl:operation>
<wsdl:operation name="RemoveMobileDeviceAccessRule">
    <soap12:operation
soapAction="http://tempuri.org/IO365Provider/RemoveMobileDeviceAccessRule" style="document" />
    <wsdl:input>
        <soap12:body use="literal" />
    </wsdl:input>
</wsdl:operation>
<wsdl:operation name="AddMobileDeviceAccessRule">
    <soap12:operation
soapAction="http://tempuri.org/IO365Provider/AddMobileDeviceAccessRule" style="document" />
    <wsdl:input>
        <soap12:body use="literal" />
    </wsdl:input>
</wsdl:operation>
<wsdl:operation name="ApplyMobileDeviceAccessRule">
    <soap12:operation
soapAction="http://tempuri.org/IO365Provider/ApplyMobileDeviceAccessRule" style="document" />
    <wsdl:input>
        <soap12:body use="literal" />
    </wsdl:input>
</wsdl:operation>
<wsdl:operation name="QueryMobileDeviceExtraInfo">
    <soap12:operation
soapAction="http://tempuri.org/IO365Provider/QueryMobileDeviceExtraInfo" style="document" />
    <wsdl:input>
        <soap12:body use="literal" />
    </wsdl:input>
</wsdl:operation>
<wsdl:operation name="QueryAllExchangeGroupUsers">
    <soap12:operation
soapAction="http://tempuri.org/IO365Provider/QueryAllExchangeGroupUsers" style="document" />
    <wsdl:input>
        <soap12:body use="literal" />
    </wsdl:input>
</wsdl:operation>
<wsdl:operation name="QueryAllExchangeDistrGroups">
    <soap12:operation
soapAction="http://tempuri.org/IO365Provider/QueryAllExchangeDistrGroups" style="document" />
    <wsdl:input>

```

```

        <soap12:body use="literal" />
    </wsdl:input>
</wsdl:operation>
<wsdl:operation name="AddExchangeDistrGroup">
    <soap12:operation
soapAction="http://tempuri.org/IO365Provider/AddExchangeDistrGroup" style="document" />
    <wsdl:input>
        <soap12:body use="literal" />
    </wsdl:input>
</wsdl:operation>
<wsdl:operation name="UpdateExchangeDistrGroup">
    <soap12:operation
soapAction="http://tempuri.org/IO365Provider/UpdateExchangeDistrGroup" style="document" />
    <wsdl:input>
        <soap12:body use="literal" />
    </wsdl:input>
</wsdl:operation>
<wsdl:operation name="UpdateExchangeDistrGroupMembers">
    <soap12:operation
soapAction="http://tempuri.org/IO365Provider/UpdateExchangeDistrGroupMembers" style="document" />
    <wsdl:input>
        <soap12:body use="literal" />
    </wsdl:input>
</wsdl:operation>
<wsdl:operation name="DeleteExchangeDistrGroup">
    <soap12:operation
soapAction="http://tempuri.org/IO365Provider/DeleteExchangeDistrGroup" style="document" />
    <wsdl:input>
        <soap12:body use="literal" />
    </wsdl:input>
</wsdl:operation>
<wsdl:operation name="UpdateUserExchangeDistrGroups">
    <soap12:operation
soapAction="http://tempuri.org/IO365Provider/UpdateUserExchangeDistrGroups" style="document" />
    <wsdl:input>
        <soap12:body use="literal" />
    </wsdl:input>
</wsdl:operation>
<wsdl:operation name="EnsureUser">
    <soap12:operation soapAction="http://tempuri.org/IO365Provider/EnsureUser" style="document" />
    <wsdl:input>
        <soap12:body use="literal" />
    </wsdl:input>
</wsdl:operation>
<wsdl:operation name="GetSiteCollectionProperties">
    <soap12:operation
soapAction="http://tempuri.org/IO365Provider/GetSiteCollectionProperties" style="document" />
    <wsdl:input>
        <soap12:body use="literal" />
    </wsdl:input>
</wsdl:operation>
<wsdl:operation name="GetSiteProperties">
    <soap12:operation
soapAction="http://tempuri.org/IO365Provider/GetSiteProperties" style="document" />
    <wsdl:input>
        <soap12:body use="literal" />
    </wsdl:input>
</wsdl:operation>
<wsdl:operation name="UpdateSiteProperties">
    <soap12:operation
soapAction="http://tempuri.org/IO365Provider/UpdateSiteProperties" style="document" />
    <wsdl:input>
        <soap12:body use="literal" />
    </wsdl:input>
</wsdl:operation>

```

```

        <wsdl:operation name="GetSiteLibraries">
            <soap12:operation soapAction="http://tempuri.org/IO365Provider/GetSiteLibraries" style="document" />
                <wsdl:input>
                    <soap12:body use="literal" />
                </wsdl:input>
            </wsdl:operation>
        <wsdl:operation name="UpdateLibraryProperties">
            <soap12:operation soapAction="http://tempuri.org/IO365Provider/UpdateLibraryProperties" style="document" />
                <wsdl:input>
                    <soap12:body use="literal" />
                </wsdl:input>
            </wsdl:operation>
        <wsdl:operation name="AddLibrary">
            <soap12:operation soapAction="http://tempuri.org/IO365Provider/AddLibrary" style="document" />
                <wsdl:input>
                    <soap12:body use="literal" />
                </wsdl:input>
            </wsdl:operation>
        <wsdl:operation name="DeleteLibrary">
            <soap12:operation soapAction="http://tempuri.org/IO365Provider/DeleteLibrary" style="document" />
                <wsdl:input>
                    <soap12:body use="literal" />
                </wsdl:input>
            </wsdl:operation>
        <wsdl:operation name="OnO365UserUpdated">
            <soap12:operation soapAction="http://tempuri.org/IO365Provider/OnO365UserUpdated" style="document" />
                <wsdl:output>
                    <soap12:body use="literal" />
                </wsdl:output>
            </wsdl:operation>
        <wsdl:operation name="OnO365InformationUpdated">
            <soap12:operation soapAction="http://tempuri.org/IO365Provider/OnO365InformationUpdated" style="document" />
                <wsdl:output>
                    <soap12:body use="literal" />
                </wsdl:output>
            </wsdl:operation>
        <wsdl:operation name="OnO365DomainUpdated">
            <soap12:operation soapAction="http://tempuri.org/IO365Provider/OnO365DomainUpdated" style="document" />
                <wsdl:output>
                    <soap12:body use="literal" />
                </wsdl:output>
            </wsdl:operation>
        <wsdl:operation name="OnGroupInfoUpdated">
            <soap12:operation soapAction="http://tempuri.org/IO365Provider/OnGroupInfoUpdated" style="document" />
                <wsdl:output>
                    <soap12:body use="literal" />
                </wsdl:output>
            </wsdl:operation>
        <wsdl:operation name="OnMSOSecurityGroupUpdated">
            <soap12:operation soapAction="http://tempuri.org/IO365Provider/OnMSOSecurityGroupUpdated" style="document" />
                <wsdl:output>
                    <soap12:body use="literal" />
                </wsdl:output>
            </wsdl:operation>
        <wsdl:operation name="OnSharePointSiteUpdated">
            <soap12:operation soapAction="http://tempuri.org/IO365Provider/OnSharePointSiteUpdated" style="document" />
                <wsdl:output>
                    <soap12:body use="literal" />
                </wsdl:output>
            </wsdl:operation>

```

```

        </wsdl:operation>
        <wsdl:operation name="OnSharePointLibraryAdded">
            <soap12:operation
                soapAction="http://tempuri.org/IO365Provider/OnSharePointLibraryAdded" style="document" />
            <wsdl:output>
                <soap12:body use="literal" />
            </wsdl:output>
        </wsdl:operation>
        <wsdl:operation name="OnSharePointLibraryRemoved">
            <soap12:operation
                soapAction="http://tempuri.org/IO365Provider/OnSharePointLibraryRemoved" style="document" />
            <wsdl:output>
                <soap12:body use="literal" />
            </wsdl:output>
        </wsdl:operation>
        <wsdl:operation name="OnSharePointLibraryUpdated">
            <soap12:operation
                soapAction="http://tempuri.org/IO365Provider/OnSharePointLibraryUpdated" style="document" />
            <wsdl:output>
                <soap12:body use="literal" />
            </wsdl:output>
        </wsdl:operation>
        <wsdl:operation name="OnIntegrationStatusUpdated">
            <soap12:operation
                soapAction="http://tempuri.org/IO365Provider/OnIntegrationStatusUpdated" style="document" />
            <wsdl:output>
                <soap12:body use="literal" />
            </wsdl:output>
        </wsdl:operation>
    </wsdl:binding>
    <wsdl:service name="O365ManagementProvider">
        <wsdl:port name="CustomBinding_IProvider" binding="tns:CustomBinding_IProvider">
            <soap12:address
                location="net.tcp://localhost:65532/Microsoft.WindowsServerSolutions.O365Integration.O365Ma
                nagementProvider/Microsoft.WindowsServerSolutions.Common.ProviderFramework.IProvider" />
            <wsa10:EndpointReference>

<wsa10:Address>net.tcp://localhost:65532/Microsoft.WindowsServerSolutions.O365Integration.O
365ManagementProvider/Microsoft.WindowsServerSolutions.Common.ProviderFramework.IProvider</
wsa10:Address>
            <Identity xmlns="http://schemas.xmlsoap.org/ws/2006/02/addressingidentity">
                <Dns>SERVERNAME</Dns>
            </Identity>
        </wsa10:EndpointReference>
    </wsdl:port>
    <wsdl:port name="CustomBinding_IO365Provider"
        binding="tns:CustomBinding_IO365Provider">
        <soap12:address
            location="net.tcp://localhost:65532/Microsoft.WindowsServerSolutions.O365Integration.O365Ma
            nagementProvider/Microsoft.WindowsServerSolutions.O365Integration.IO365Provider" />
        <wsa10:EndpointReference>

<wsa10:Address>net.tcp://localhost:65532/Microsoft.WindowsServerSolutions.O365Integration.O
365ManagementProvider/Microsoft.WindowsServerSolutions.O365Integration.IO365Provider</wsa10
:Address>
            <Identity xmlns="http://schemas.xmlsoap.org/ws/2006/02/addressingidentity">
                <Spn>host/serverName.domain</Spn>
            </Identity>
        </wsa10:EndpointReference>
    </wsdl:port>
</wsdl:service>
</wsdl:definitions>

```

6.10.2.2 http://tempuri.org

```
<?xml version="1.0" encoding="utf-8"?>
<xs:schema xmlns:tns="http://tempuri.org/" elementFormDefault="qualified"
targetNamespace="http://tempuri.org/" xmlns:xs="http://www.w3.org/2001/XMLSchema">
    <xs:import schemaLocation="" namespace="http://schemas.datacontract.org/2004/07/System" />
    <xs:import schemaLocation="" namespace="http://schemas.microsoft.com/2003/10/Serialization/" />
    <xs:import schemaLocation="" namespace="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.O365Integration" />
    <xs:import schemaLocation="" namespace="http://schemas.microsoft.com/2003/10/Serialization/Arrays" />
    <xs:element name="Disconnect">
        <xs:complexType>
            <xs:sequence />
        </xs:complexType>
    </xs:element>
    <xs:element name="RaiseOperationInvokeEvent">
        <xs:complexType>
            <xs:sequence>
                <xs:element minOccurs="0" name="operationName" nillable="true" type="xs:string" />
                <xs:element minOccurs="0" name="result" nillable="true" type="xs:anyType" />
                <xs:element xmlns:q1="http://schemas.datacontract.org/2004/07/System" minOccurs="0" name="errorException" nillable="true" type="q1:Exception" />
            </xs:sequence>
        </xs:complexType>
    </xs:element>
    <xs:element name="Activate">
        <xs:complexType>
            <xs:sequence>
                <xs:element minOccurs="0" name="adminUserName" nillable="true" type="xs:string" />
                <xs:element minOccurs="0" name="adminPassword" nillable="true" type="xs:string" />
                <xs:element minOccurs="0" name="id" nillable="true" type="xs:string" />
            </xs:sequence>
        </xs:complexType>
    </xs:element>
    <xs:element name="ActivateAAD">
        <xs:complexType>
            <xs:sequence>
                <xs:element minOccurs="0" name="adminUserName" nillable="true" type="xs:string" />
                <xs:element minOccurs="0" name="adminPassword" nillable="true" type="xs:string" />
                <xs:element minOccurs="0" name="id" nillable="true" type="xs:string" />
            </xs:sequence>
        </xs:complexType>
    </xs:element>
    <xs:element name="ActivateService">
        <xs:complexType>
            <xs:sequence>
                <xs:element xmlns:q2="http://schemas.microsoft.com/2003/10/Serialization/" minOccurs="0" name="guid" type="q2:guid" />
                <xs:element minOccurs="0" name="id" nillable="true" type="xs:string" />
            </xs:sequence>
        </xs:complexType>
    </xs:element>
    <xs:element name="Deactivate">
        <xs:complexType>
            <xs:sequence>
                <xs:element minOccurs="0" name="id" nillable="true" type="xs:string" />
            </xs:sequence>
        </xs:complexType>
    </xs:element>
    <xs:element name="DeactivateService">
```

```

<xs:complexType>
    <xs:sequence>
        <xs:element xmlns:q3="http://schemas.microsoft.com/2003/10/Serialization/" minOccurs="0" name="guid" type="q3:guid" />
        <xs:element minOccurs="0" name="id" nillable="true" type="xs:string" />
    </xs:sequence>
</xs:complexType>
</xs:element>
<xs:element name="QueryMappedOnlineUserNumber">
    <xs:complexType>
        <xs:sequence>
            <xs:element minOccurs="0" name="id" nillable="true" type="xs:string" />
        </xs:sequence>
    </xs:complexType>
</xs:element>
<xs:element name="QueryOnlineUser">
    <xs:complexType>
        <xs:sequence>
            <xs:element minOccurs="0" name="userPrincipalName" nillable="true" type="xs:string" />
            <xs:element minOccurs="0" name="id" nillable="true" type="xs:string" />
        </xs:sequence>
    </xs:complexType>
</xs:element>
<xs:element name="QueryAllOnlineUsers">
    <xs:complexType>
        <xs:sequence>
            <xs:element minOccurs="0" name="id" nillable="true" type="xs:string" />
        </xs:sequence>
    </xs:complexType>
</xs:element>
<xs:element name="QueryMappedOnlineUser">
    <xs:complexType>
        <xs:sequence>
            <xs:element minOccurs="0" name="localUserName" nillable="true" type="xs:string" />
            <xs:element minOccurs="0" name="id" nillable="true" type="xs:string" />
        </xs:sequence>
    </xs:complexType>
</xs:element>
<xs:element name="BulkMapOnlineUsers">
    <xs:complexType>
        <xs:sequence>
            <xs:element
                xmlns:q4="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.O365Integration" minOccurs="0" name="users" nillable="true" type="q4:ArrayOfO365UserMap" />
            <xs:element
                xmlns:q5="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.O365Integration" minOccurs="0" name="licenses" nillable="true" type="q5:ArrayOfO365UserLicense" />
                <xs:element minOccurs="0" name="forceNew" type="xs:boolean" />
                <xs:element minOccurs="0" name="id" nillable="true" type="xs:string" />
            </xs:sequence>
        </xs:complexType>
</xs:element>
<xs:element name="MapOnlineUser">
    <xs:complexType>
        <xs:sequence>
            <xs:element minOccurs="0" name="localUserName" nillable="true" type="xs:string" />
            <xs:element minOccurs="0" name="onlineUserName" nillable="true" type="xs:string" />
            <xs:element minOccurs="0" name="password" nillable="true" type="xs:string" />
            <xs:element
                xmlns:q6="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.O365Integration" minOccurs="0" name="licenses" nillable="true" type="q6:ArrayOfO365UserLicense" />
                <xs:element minOccurs="0" name="forceNew" type="xs:boolean" />
                <xs:element minOccurs="0" name="id" nillable="true" type="xs:string" />
            </xs:sequence>
        </xs:complexType>
</xs:element>

```

```

</xs:element>
<xs:element name="UnmapOnlineUser">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" name="localUserName" nillable="true"
type="xs:string" />
      <xs:element minOccurs="0" name="id" nillable="true" type="xs:string" />
    </xs:sequence>
  </xs:complexType>
</xs:element>
<xs:element name="RemoveOnlineUserFromLocalUserName">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" name="localUserName" nillable="true"
type="xs:string" />
      <xs:element minOccurs="0" name="id" nillable="true" type="xs:string" />
    </xs:sequence>
  </xs:complexType>
</xs:element>
<xs:element name="ActivateUser">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" name="localUserName" nillable="true"
type="xs:string" />
      <xs:element minOccurs="0" name="id" nillable="true" type="xs:string" />
    </xs:sequence>
  </xs:complexType>
</xs:element>
<xs:element name="DeactivateUser">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" name="localUserName" nillable="true"
type="xs:string" />
      <xs:element minOccurs="0" name="id" nillable="true" type="xs:string" />
    </xs:sequence>
  </xs:complexType>
</xs:element>
<xs:element name="UpdateUserPrincipalName">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" name="localUserName" nillable="true"
type="xs:string" />
      <xs:element minOccurs="0" name="onlineUserPrincipalName" nillable="true"
type="xs:string" />
      <xs:element minOccurs="0" name="id" nillable="true" type="xs:string" />
    </xs:sequence>
  </xs:complexType>
</xs:element>
<xs:element name="ChangePassword">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" name="localUserName" nillable="true"
type="xs:string" />
      <xs:element minOccurs="0" name="password" nillable="true" type="xs:string" />
      <xs:element minOccurs="0" name="id" nillable="true" type="xs:string" />
    </xs:sequence>
  </xs:complexType>
</xs:element>
<xs:element name="SetUserLicenses">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" name="localUserName" nillable="true"
type="xs:string" />
      <xs:element minOccurs="0" name="licenses" nillable="true" type="q7:ArrayOfO365UserLicense" />
      <xs:element minOccurs="0" name="id" nillable="true" type="xs:string" />
    </xs:sequence>
  </xs:complexType>
</xs:element>

```

```

</xs:element>
<xs:element name="QueryAllMSOSecurityGroups">
    <xs:complexType>
        <xs:sequence>
            <xs:element minOccurs="0" name="id" nillable="true" type="xs:string" />
        </xs:sequence>
    </xs:complexType>
</xs:element>
<xs:element name="QueryMSOSecurityGroup">
    <xs:complexType>
        <xs:sequence>
            <xs:element xmlns:q8="http://schemas.microsoft.com/2003/10/Serialization/" minOccurs="0" name="groupId" type="q8:guid" />
            <xs:element minOccurs="0" name="id" nillable="true" type="xs:string" />
        </xs:sequence>
    </xs:complexType>
</xs:element>
<xs:element name="QueryMappedMSOSecurityGroup">
    <xs:complexType>
        <xs:sequence>
            <xs:element minOccurs="0" name="localGroupName" nillable="true" type="xs:string" />
            <xs:element minOccurs="0" name="id" nillable="true" type="xs:string" />
        </xs:sequence>
    </xs:complexType>
</xs:element>
<xs:element name="MapNewMSOSecurityGroup">
    <xs:complexType>
        <xs:sequence>
            <xs:element minOccurs="0" name="localGroupName" nillable="true" type="xs:string" />
            <xs:element minOccurs="0" name="onlineGroupName" nillable="true" type="xs:string" />
            <xs:element minOccurs="0" name="id" nillable="true" type="xs:string" />
        </xs:sequence>
    </xs:complexType>
</xs:element>
<xs:element name="MapExistingMSOSecurityGroup">
    <xs:complexType>
        <xs:sequence>
            <xs:element minOccurs="0" name="localGroupName" nillable="true" type="xs:string" />
            <xs:element xmlns:q9="http://schemas.microsoft.com/2003/10/Serialization/" minOccurs="0" name="onlineGroupId" type="q9:guid" />
            <xs:element minOccurs="0" name="id" nillable="true" type="xs:string" />
        </xs:sequence>
    </xs:complexType>
</xs:element>
<xs:element name="UnmapMSOSecurityGroup">
    <xs:complexType>
        <xs:sequence>
            <xs:element minOccurs="0" name="localGroupName" nillable="true" type="xs:string" />
            <xs:element minOccurs="0" name="id" nillable="true" type="xs:string" />
        </xs:sequence>
    </xs:complexType>
</xs:element>
<xs:element name="RemoveMappedMSOSecurityGroup">
    <xs:complexType>
        <xs:sequence>
            <xs:element minOccurs="0" name="localGroupName" nillable="true" type="xs:string" />
            <xs:element minOccurs="0" name="id" nillable="true" type="xs:string" />
        </xs:sequence>
    </xs:complexType>
</xs:element>
<xs:element name="QueryO365Information">
    <xs:complexType>
        <xs:sequence>

```

```

        <xs:element minOccurs="0" name="id" nillable="true" type="xs:string" />
    </xs:sequence>
</xs:complexType>
</xs:element>
<xs:element name="UpdateIntegrationStatus">
    <xs:complexType>
        <xs:sequence>
            <xs:element minOccurs="0" name="id" nillable="true" type="xs:string" />
        </xs:sequence>
    </xs:complexType>
</xs:element>
<xs:element name="SetCustomDomain">
    <xs:complexType>
        <xs:sequence>
            <xs:element minOccurs="0" name="domainName" nillable="true" type="xs:string"
/>
            <xs:element minOccurs="0" name="id" nillable="true" type="xs:string" />
        </xs:sequence>
    </xs:complexType>
</xs:element>
<xs:element name="SetManagedDomain">
    <xs:complexType>
        <xs:sequence>
            <xs:element minOccurs="0" name="id" nillable="true" type="xs:string" />
        </xs:sequence>
    </xs:complexType>
</xs:element>
<xs:element name="ResetDomain">
    <xs:complexType>
        <xs:sequence>
            <xs:element minOccurs="0" name="id" nillable="true" type="xs:string" />
        </xs:sequence>
    </xs:complexType>
</xs:element>
<xs:element name="QueryDnsRecords">
    <xs:complexType>
        <xs:sequence>
            <xs:element minOccurs="0" name="domainName" nillable="true" type="xs:string"
/>
            <xs:element minOccurs="0" name="id" nillable="true" type="xs:string" />
        </xs:sequence>
    </xs:complexType>
</xs:element>
<xs:element name="QueryDomainConfiguration">
    <xs:complexType>
        <xs:sequence>
            <xs:element minOccurs="0" name="id" nillable="true" type="xs:string" />
        </xs:sequence>
    </xs:complexType>
</xs:element>
<xs:element name="UpdateCustomDomain">
    <xs:complexType>
        <xs:sequence>
            <xs:element minOccurs="0" name="id" nillable="true" type="xs:string" />
        </xs:sequence>
    </xs:complexType>
</xs:element>
<xs:element name="IsLocalUserMapped">
    <xs:complexType>
        <xs:sequence>
            <xs:element minOccurs="0" name="localUserName" nillable="true"
type="xs:string" />
        </xs:sequence>
    </xs:complexType>
</xs:element>
<xs:element name="IsLocalUserMappedResponse">
    <xs:complexType>
        <xs:sequence>
            <xs:element minOccurs="0" name="IsLocalUserMappedResult" type="xs:boolean" />

```

```

        </xs:sequence>
    </xs:complexType>
</xs:element>
<xs:element name="IsLocalGroupMapped">
    <xs:complexType>
        <xs:sequence>
            <xs:element minOccurs="0" name="localGroupName" nillable="true"
type="xs:string" />
        </xs:sequence>
    </xs:complexType>
</xs:element>
<xs:element name="IsLocalGroupMappedResponse">
    <xs:complexType>
        <xs:sequence>
            <xs:element minOccurs="0" name="IsLocalGroupMappedResult" type="xs:boolean" />
        </xs:sequence>
    </xs:complexType>
</xs:element>
<xs:element name="GetMappedOnlineUserFromAD">
    <xs:complexType>
        <xs:sequence>
            <xs:element minOccurs="0" name="localUserName" nillable="true"
type="xs:string" />
        </xs:sequence>
    </xs:complexType>
</xs:element>
<xs:element name="GetMappedOnlineUserFromADResponse">
    <xs:complexType>
        <xs:sequence>
            <xs:element minOccurs="0" name="GetMappedOnlineUserFromADResult"
nillable="true" type="xs:string" />
        </xs:sequence>
    </xs:complexType>
</xs:element>
<xs:element name="QueryUserEmails">
    <xs:complexType>
        <xs:sequence>
            <xs:element minOccurs="0" name="localUserName" nillable="true"
type="xs:string" />
            <xs:element minOccurs="0" name="id" nillable="true" type="xs:string" />
        </xs:sequence>
    </xs:complexType>
</xs:element>
<xs:element name="SetUserEmails">
    <xs:complexType>
        <xs:sequence>
            <xs:element minOccurs="0" name="localUserName" nillable="true"
type="xs:string" />
            <xs:element
xmlns:q10="http://schemas.microsoft.com/2003/10/Serialization/Arrays" minOccurs="0"
name="emails" nillable="true" type="q10:ArrayOfstring" />
                <xs:element minOccurs="0" name="id" nillable="true" type="xs:string" />
            </xs:sequence>
        </xs:complexType>
</xs:element>
<xs:element name="QueryO365UserWithEmails">
    <xs:complexType>
        <xs:sequence>
            <xs:element minOccurs="0" name="localUserName" nillable="true"
type="xs:string" />
            <xs:element minOccurs="0" name="id" nillable="true" type="xs:string" />
        </xs:sequence>
    </xs:complexType>
</xs:element>
<xs:element name="UpdateO365UserWithEmails">
    <xs:complexType>
        <xs:sequence>
            <xs:element minOccurs="0" name="localUserName" nillable="true"
type="xs:string" />
        </xs:sequence>
    </xs:complexType>
</xs:element>

```

```

        <xs:element minOccurs="0" name="onlineUserPrincipalName" nillable="true"
type="xs:string" />
        <xs:element
xmlns:q11="http://schemas.microsoft.com/2003/10/Serialization/Arrays" minOccurs="0"
name="emails" nillable="true" type="q11:ArrayOfstring" />
            <xs:element minOccurs="0" name="id" nillable="true" type="xs:string" />
        </xs:sequence>
    </xs:complexType>
</xs:element>
<xs:element name="QueryAllMailboxStatistics">
    <xs:complexType>
        <xs:sequence>
            <xs:element minOccurs="0" name="id" nillable="true" type="xs:string" />
        </xs:sequence>
    </xs:complexType>
</xs:element>
<xs:element name="QueryMobileDevices">
    <xs:complexType>
        <xs:sequence>
            <xs:element minOccurs="0" name="id" nillable="true" type="xs:string" />
        </xs:sequence>
    </xs:complexType>
</xs:element>
<xs:element name="AllowMobileDevices">
    <xs:complexType>
        <xs:sequence>
            <xs:element minOccurs="0" name="mailbox" nillable="true" type="xs:string" />
            <xs:element
xmlns:q12="http://schemas.microsoft.com/2003/10/Serialization/Arrays" minOccurs="0"
name="deviceIds" nillable="true" type="q12:ArrayOfstring" />
                <xs:element minOccurs="0" name="id" nillable="true" type="xs:string" />
            </xs:sequence>
        </xs:complexType>
</xs:element>
<xs:element name="BlockMobileDevices">
    <xs:complexType>
        <xs:sequence>
            <xs:element minOccurs="0" name="mailbox" nillable="true" type="xs:string" />
            <xs:element
xmlns:q13="http://schemas.microsoft.com/2003/10/Serialization/Arrays" minOccurs="0"
name="deviceIds" nillable="true" type="q13:ArrayOfstring" />
                <xs:element minOccurs="0" name="id" nillable="true" type="xs:string" />
            </xs:sequence>
        </xs:complexType>
</xs:element>
<xs:element name="RemoveMobileDevice">
    <xs:complexType>
        <xs:sequence>
            <xs:element minOccurs="0" name="deviceId" nillable="true" type="xs:string" />
            <xs:element minOccurs="0" name="id" nillable="true" type="xs:string" />
        </xs:sequence>
    </xs:complexType>
</xs:element>
<xs:element name="WipeMobileDevice">
    <xs:complexType>
        <xs:sequence>
            <xs:element minOccurs="0" name="deviceId" nillable="true" type="xs:string" />
            <xs:element minOccurs="0" name="id" nillable="true" type="xs:string" />
        </xs:sequence>
    </xs:complexType>
</xs:element>
<xs:element name="QueryMobileDevicePolicy">
    <xs:complexType>
        <xs:sequence>
            <xs:element minOccurs="0" name="id" nillable="true" type="xs:string" />
        </xs:sequence>
    </xs:complexType>
</xs:element>
<xs:element name="SetMobileDevicePolicy">

```

```

<xs:complexType>
    <xs:sequence>
        <xs:element
            xmlns:q14="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.O365Integration" minOccurs="0" name="policy" nillable="true" type="q14:MobileDevicePolicy" />
            <xs:element minOccurs="0" name="id" nillable="true" type="xs:string" />
        </xs:sequence>
    </xs:complexType>
</xs:element>
<xs:element name="CreateMobileDevicePolicy">
    <xs:complexType>
        <xs:sequence>
            <xs:element
                xmlns:q15="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.O365Integration" minOccurs="0" name="policy" nillable="true" type="q15:MobileDevicePolicy" />
                    <xs:element minOccurs="0" name="id" nillable="true" type="xs:string" />
                </xs:sequence>
            </xs:complexType>
</xs:element>
<xs:element name="QueryMobileDeviceAccessRules">
    <xs:complexType>
        <xs:sequence>
            <xs:element minOccurs="0" name="id" nillable="true" type="xs:string" />
        </xs:sequence>
    </xs:complexType>
</xs:element>
<xs:element name="RemoveMobileDeviceAccessRule">
    <xs:complexType>
        <xs:sequence>
            <xs:element minOccurs="0" name="ruleId" nillable="true" type="xs:string" />
            <xs:element minOccurs="0" name="id" nillable="true" type="xs:string" />
        </xs:sequence>
    </xs:complexType>
</xs:element>
<xs:element name="AddMobileDeviceAccessRule">
    <xs:complexType>
        <xs:sequence>
            <xs:element
                xmlns:q16="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.O365Integration" minOccurs="0" name="rule" nillable="true" type="q16:MobileDeviceAccessRule" />
                    <xs:element minOccurs="0" name="id" nillable="true" type="xs:string" />
                </xs:sequence>
            </xs:complexType>
</xs:element>
<xs:element name="ApplyMobileDeviceAccessRule">
    <xs:complexType>
        <xs:sequence>
            <xs:element minOccurs="0" name="mailbox" nillable="true" type="xs:string" />
        <xs:element
            xmlns:q17="http://schemas.microsoft.com/2003/10/Serialization/Arrays" minOccurs="0" name="deviceIds" nillable="true" type="q17:ArrayOfstring" />
                <xs:element minOccurs="0" name="id" nillable="true" type="xs:string" />
            </xs:sequence>
        </xs:complexType>
</xs:element>
<xs:element name="QueryMobileDeviceExtraInfo">
    <xs:complexType>
        <xs:sequence>
            <xs:element
                xmlns:q18="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.O365Integration" minOccurs="0" name="infoType" type="q18:MobileDeviceExtraInfoType" />
                    <xs:element minOccurs="0" name="id" nillable="true" type="xs:string" />
                </xs:sequence>
            </xs:complexType>
</xs:element>
<xs:element name="QueryAllExchangeGroupUsers">
    <xs:complexType>
        <xs:sequence>
            <xs:element minOccurs="0" name="id" nillable="true" type="xs:string" />
        </xs:sequence>
    </xs:complexType>
</xs:element>

```

```

        </xs:sequence>
    </xs:complexType>
</xs:element>
<xs:element name="QueryAllExchangeDistrGroups">
    <xs:complexType>
        <xs:sequence>
            <xs:element minOccurs="0" name="id" nillable="true" type="xs:string" />
        </xs:sequence>
    </xs:complexType>
</xs:element>
<xs:element name="AddExchangeDistrGroup">
    <xs:complexType>
        <xs:sequence>
            <xs:element
xmlns:q19="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.O365Int
egration" minOccurs="0" name="group" nillable="true" type="q19:ExchangeDistrGroup" />
        <xs:element
xmlns:q20="http://schemas.microsoft.com/2003/10/Serialization/Arrays" minOccurs="0"
name="memberIds" nillable="true" type="q20:ArrayOfguid" />
            <xs:element minOccurs="0" name="id" nillable="true" type="xs:string" />
        </xs:sequence>
    </xs:complexType>
</xs:element>
<xs:element name="UpdateExchangeDistrGroup">
    <xs:complexType>
        <xs:sequence>
            <xs:element
xmlns:q21="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.O365Int
egration" minOccurs="0" name="group" nillable="true" type="q21:ExchangeDistrGroup" />
            <xs:element
xmlns:q22="http://schemas.microsoft.com/2003/10/Serialization/Arrays" minOccurs="0"
name="memberIds" nillable="true" type="q22:ArrayOfguid" />
            <xs:element minOccurs="0" name="id" nillable="true" type="xs:string" />
        </xs:sequence>
    </xs:complexType>
</xs:element>
<xs:element name="UpdateExchangeDistrGroupMembers">
    <xs:complexType>
        <xs:sequence>
            <xs:element xmlns:q23="http://schemas.microsoft.com/2003/10/Serialization/"
minOccurs="0" name="groupId" type="q23:guid" />
            <xs:element
xmlns:q24="http://schemas.microsoft.com/2003/10/Serialization/Arrays" minOccurs="0"
name="memberIds" nillable="true" type="q24:ArrayOfguid" />
            <xs:element minOccurs="0" name="id" nillable="true" type="xs:string" />
        </xs:sequence>
    </xs:complexType>
</xs:element>
<xs:element name="DeleteExchangeDistrGroup">
    <xs:complexType>
        <xs:sequence>
            <xs:element xmlns:q25="http://schemas.microsoft.com/2003/10/Serialization/"
minOccurs="0" name="groupId" type="q25:guid" />
            <xs:element minOccurs="0" name="id" nillable="true" type="xs:string" />
        </xs:sequence>
    </xs:complexType>
</xs:element>
<xs:element name="UpdateUserExchangeDistrGroups">
    <xs:complexType>
        <xs:sequence>
            <xs:element xmlns:q26="http://schemas.microsoft.com/2003/10/Serialization/"
minOccurs="0" name="userId" type="q26:guid" />
            <xs:element
xmlns:q27="http://schemas.microsoft.com/2003/10/Serialization/Arrays" minOccurs="0"
name="groupsToAdd" nillable="true" type="q27:ArrayOfguid" />
            <xs:element
xmlns:q28="http://schemas.microsoft.com/2003/10/Serialization/Arrays" minOccurs="0"
name="groupsToDelete" nillable="true" type="q28:ArrayOfguid" />
            <xs:element minOccurs="0" name="id" nillable="true" type="xs:string" />

```

```

        </xs:sequence>
    </xs:complexType>
</xs:element>
<xs:element name="EnsureUser">
    <xs:complexType>
        <xs:sequence>
            <xs:element minOccurs="0" name="siteCollectionUri" nillable="true"
type="xs:anyURI" />
            <xs:element minOccurs="0" name="logonName" nillable="true" type="xs:string" />
            <xs:element minOccurs="0" name="id" nillable="true" type="xs:string" />
        </xs:sequence>
    </xs:complexType>
</xs:element>
<xs:element name="GetSiteCollectionProperties">
    <xs:complexType>
        <xs:sequence>
            <xs:element minOccurs="0" name="siteCollectionUri" nillable="true"
type="xs:anyURI" />
            <xs:element minOccurs="0" name="id" nillable="true" type="xs:string" />
        </xs:sequence>
    </xs:complexType>
</xs:element>
<xs:element name="GetSiteProperties">
    <xs:complexType>
        <xs:sequence>
            <xs:element minOccurs="0" name="siteUri" nillable="true" type="xs:anyURI" />
            <xs:element minOccurs="0" name="id" nillable="true" type="xs:string" />
        </xs:sequence>
    </xs:complexType>
</xs:element>
<xs:element name="UpdateSiteProperties">
    <xs:complexType>
        <xs:sequence>
            <xs:element
xmlns:q29="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.O365Int
egration" minOccurs="0" name="site" nillable="true" type="q29:SharePointSite" />
            <xs:element minOccurs="0" name="id" nillable="true" type="xs:string" />
        </xs:sequence>
    </xs:complexType>
</xs:element>
<xs:element name="GetSiteLibraries">
    <xs:complexType>
        <xs:sequence>
            <xs:element minOccurs="0" name="siteUri" nillable="true" type="xs:anyURI" />
            <xs:element minOccurs="0" name="id" nillable="true" type="xs:string" />
        </xs:sequence>
    </xs:complexType>
</xs:element>
<xs:element name="UpdateLibraryProperties">
    <xs:complexType>
        <xs:sequence>
            <xs:element
xmlns:q30="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.O365Int
egration" minOccurs="0" name="library" nillable="true" type="q30:SharePointLibrary" />
            <xs:element minOccurs="0" name="id" nillable="true" type="xs:string" />
        </xs:sequence>
    </xs:complexType>
</xs:element>
<xs:element name="AddLibrary">
    <xs:complexType>
        <xs:sequence>
            <xs:element
xmlns:q31="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.O365Int
egration" minOccurs="0" name="library" nillable="true" type="q31:SharePointLibrary" />
            <xs:element minOccurs="0" name="id" nillable="true" type="xs:string" />
        </xs:sequence>
    </xs:complexType>
</xs:element>
<xs:element name="DeleteLibrary">

```

```

<xs:complexType>
    <xs:sequence>
        <xs:element
            xmlns:q32="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.O365Integration" minOccurs="0" name="library" nullable="true" type="q32:SharePointLibrary" />
            <xs:element minOccurs="0" name="id" nullable="true" type="xs:string" />
        </xs:sequence>
    </xs:complexType>
</xs:element>
<xs:element name="OnO365UserUpdated">
    <xs:complexType>
        <xs:sequence>
            <xs:element
                xmlns:q33="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.O365Integration" minOccurs="0" name="e" nullable="true" type="q33:O365UserEventArgs" />
        </xs:sequence>
    </xs:complexType>
</xs:element>
<xs:element name="OnO365InformationUpdated">
    <xs:complexType>
        <xs:sequence>
            <xs:element
                xmlns:q34="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.O365Integration" minOccurs="0" name="e" nullable="true" type="q34:O365InformationEventArgs" />
        </xs:sequence>
    </xs:complexType>
</xs:element>
<xs:element name="OnO365DomainUpdated">
    <xs:complexType>
        <xs:sequence>
            <xs:element
                xmlns:q35="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.O365Integration" minOccurs="0" name="e" nullable="true" type="q35:O365DomainConfigurationEventArgs" />
        </xs:sequence>
    </xs:complexType>
</xs:element>
<xs:element name="OnGroupInfoUpdated">
    <xs:complexType>
        <xs:sequence>
            <xs:element
                xmlns:q36="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.O365Integration" minOccurs="0" name="e" nullable="true" type="q36:ExchangeGroupEventArgs" />
        </xs:sequence>
    </xs:complexType>
</xs:element>
<xs:element name="OnMSOSecurityGroupUpdated">
    <xs:complexType>
        <xs:sequence>
            <xs:element
                xmlns:q37="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.O365Integration" minOccurs="0" name="e" nullable="true" type="q37:MSOSecurityGroupEventArgs" />
        </xs:sequence>
    </xs:complexType>
</xs:element>
<xs:element name="OnSharePointSiteUpdated">
    <xs:complexType>
        <xs:sequence>
            <xs:element
                xmlns:q38="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.O365Integration" minOccurs="0" name="e" nullable="true" type="q38:SharePointSiteEventArgs" />
        </xs:sequence>
    </xs:complexType>
</xs:element>
<xs:element name="OnSharePointLibraryAdded">

```

```

<xs:complexType>
  <xs:sequence>
    <xs:element
      xmlns:q39="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.O365Integration" minOccurs="0" name="e" nillable="true" type="q39:SharePointLibraryAddedEventArgs" />
    </xs:sequence>
  </xs:complexType>
</xs:element>
<xs:element name="OnSharePointLibraryRemoved">
  <xs:complexType>
    <xs:sequence>
      <xs:element
        xmlns:q40="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.O365Integration" minOccurs="0" name="e" nillable="true" type="q40:SharePointLibraryRemovedEventArgs" />
    </xs:sequence>
  </xs:complexType>
</xs:element>
<xs:element name="OnSharePointLibraryUpdated">
  <xs:complexType>
    <xs:sequence>
      <xs:element
        xmlns:q41="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.O365Integration" minOccurs="0" name="e" nillable="true" type="q41:SharePointLibraryUpdatedEventArgs" />
    </xs:sequence>
  </xs:complexType>
</xs:element>
<xs:element name="OnIntegrationStatusUpdated">
  <xs:complexType>
    <xs:sequence>
      <xs:element xmlns:q42="http://schemas.datacontract.org/2004/07/System" minOccurs="0" name="e" nillable="true" type="q42EventArgs" />
    </xs:sequence>
  </xs:complexType>
</xs:element>
</xs:schema>

```

6.10.2.3 <http://schemas.microsoft.com/2003/10/Serialization>

```

<?xml version="1.0" encoding="utf-8"?>
<xs:schema xmlns:tns="http://schemas.microsoft.com/2003/10/Serialization/" attributeFormDefault="qualified" elementFormDefault="qualified" targetNamespace="http://schemas.microsoft.com/2003/10/Serialization/" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:element name="anyType" nillable="true" type="xs:anyType" />
  <xs:element name="anyURI" nillable="true" type="xs:anyURI" />
  <xs:element name="base64Binary" nillable="true" type="xs:base64Binary" />
  <xs:element name="boolean" nillable="true" type="xs:boolean" />
  <xs:element name="byte" nillable="true" type="xs:byte" />
  <xs:element name="dateTime" nillable="true" type="xs:dateTime" />
  <xs:element name="decimal" nillable="true" type="xs:decimal" />
  <xs:element name="double" nillable="true" type="xs:double" />
  <xs:element name="float" nillable="true" type="xs:float" />
  <xs:element name="int" nillable="true" type="xs:int" />
  <xs:element name="long" nillable="true" type="xs:long" />
  <xs:element name="QName" nillable="true" type="xs:QName" />
  <xs:element name="short" nillable="true" type="xs:short" />
  <xs:element name="string" nillable="true" type="xs:string" />
  <xs:element name="unsignedByte" nillable="true" type="xs:unsignedByte" />
  <xs:element name="unsignedInt" nillable="true" type="xs:unsignedInt" />
  <xs:element name="unsignedLong" nillable="true" type="xs:unsignedLong" />
  <xs:element name="unsignedShort" nillable="true" type="xs:unsignedShort" />
  <xs:element name="char" nillable="true" type="tns:char" />
  <xs:simpleType name="char">
    <xs:restriction base="xs:int" />
  </xs:simpleType>

```

```

</xs:simpleType>
<xs:element name="duration" nillable="true" type="tns:duration" />
<xs:simpleType name="duration">
    <xs:restriction base="xs:duration">
        <xs:pattern value="-?P(\d*D)?(T(\d*M)?(\d*(\.\d*)?S)?)?" />
        <xs:minInclusive value="-P10675199DT2H48M5.4775808S" />
        <xs:maxInclusive value="P10675199DT2H48M5.4775807S" />
    </xs:restriction>
</xs:simpleType>
<xs:element name="guid" nillable="true" type="tns:guid" />
<xs:simpleType name="guid">
    <xs:restriction base="xs:string">
        <xs:pattern value="[\da-fA-F]{8}-[\da-fA-F]{4}-[\da-fA-F]{4}-[\da-fA-F]{4}-[\da-fA-F]{12}" />
    </xs:restriction>
</xs:simpleType>
<xs:attribute name="FactoryType" type="xs:QName" />
<xs:attribute name="Id" type="xs:ID" />
<xs:attribute name="Ref" type="xs:IDREF" />
</xs:schema>

```

6.10.2.4 http://schemas.datacontract.org/2004/07/System.Collections.ObjectModel

```

<?xml version="1.0" encoding="utf-8"?>
<xs:schema
    xmlns:tns="http://schemas.datacontract.org/2004/07/System.Collections.ObjectModel"
    elementFormDefault="qualified"
    targetNamespace="http://schemas.datacontract.org/2004/07/System.Collections.ObjectModel"
    xmlns:xs="http://www.w3.org/2001/XMLSchema">
    <xs:import schemaLocation="" namespace="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.O365Integration" />
    <xs:import schemaLocation="" namespace="http://schemas.microsoft.com/2003/10/Serialization/Arrays" />
    <xs:complexType name="ReadOnlyCollectionOfO365Skug8jlx19J">
        <xs:annotation>
            <xs:appinfo>
                <GenericType Name="ReadOnlyCollectionOf{0}{{#}}">
                    <GenericParameter Name="O365Sku">
                        <Namespace>http://schemas.datacontract.org/2004/07/System.Collections.ObjectModel</Namespace>
                    <Namespace>http://schemas.microsoft.com/2003/10/Serialization/</Namespace>
                    <GenericParameter Name="O365Sku">
                        <Namespace>http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.O365Integration</Namespace>
                    </GenericParameter>
                </GenericType>
            </xs:appinfo>
        </xs:annotation>
        <xs:sequence>
            <xs:element
                xmlns:q1="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.O365Integration" name="list" nillable="true" type="q1:ArrayOfO365Sku" />
        </xs:sequence>
    </xs:complexType>
    <xs:element name="ReadOnlyCollectionOfO365Skug8jlx19J" nillable="true" type="tns:ReadOnlyCollectionOfO365Skug8jlx19J" />
    <xs:complexType name="ReadOnlyCollectionOfO365Serviceeg8jlx19J">
        <xs:annotation>
            <xs:appinfo>
                <GenericType Name="ReadOnlyCollectionOf{0}{{#}}">
                    <GenericParameter Name="O365Service">
                        <Namespace>http://schemas.datacontract.org/2004/07/System.Collections.ObjectModel</Namespace>
                    <Namespace>http://schemas.microsoft.com/2003/10/Serialization/</Namespace>
                    <GenericParameter Name="O365Service">
                        <Namespace>http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.O365Integration</Namespace>
                    </GenericParameter>
                </GenericType>
            </xs:appinfo>
        </xs:annotation>
    </xs:complexType>
</xs:schema>

```

```

<xs:sequence>
    <xs:element
        xmlns:q2="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.O365Inte
        gration" name="list" nillable="true" type="q2:ArrayOfO365Service" />
    </xs:sequence>
</xs:complexType>
<xs:element name="ReadOnlyCollectionOfO365Serviceg8jlx19J" nillable="true"
    type="tns:ReadOnlyCollectionOfO365Serviceg8jlx19J" />
<xs:complexType name="ReadOnlyCollectionOfO365Subscriptiong8jlx19J">
    <xs:annotation>
        <xs:appinfo>
            <GenericType Name="ReadOnlyCollectionOf{0}{#}">
                Namespace="http://schemas.datacontract.org/2004/07/System.Collections.ObjectModel"
                xmlns="http://schemas.microsoft.com/2003/10/Serialization/">
                    <GenericParameter Name="O365Subscription">
                        Namespace="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.O365Int
                        egration" />
                    </GenericType>
                </GenericParameter>
            </GenericType>
        </xs:appinfo>
    </xs:annotation>
    <xs:sequence>
        <xs:element
            xmlns:q3="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.O365Inte
            gration" name="list" nillable="true" type="q3:ArrayOfO365Subscription" />
        </xs:sequence>
    </xs:complexType>
    <xs:element name="ReadOnlyCollectionOfO365Subscriptiong8jlx19J" nillable="true"
        type="tns:ReadOnlyCollectionOfO365Subscriptiong8jlx19J" />
    <xs:complexType name="ReadOnlyCollectionOfstring">
        <xs:annotation>
            <xs:appinfo>
                <GenericType Name="ReadOnlyCollectionOf{0}{#}">
                    Namespace="http://schemas.datacontract.org/2004/07/System.Collections.ObjectModel"
                    xmlns="http://schemas.microsoft.com/2003/10/Serialization/">
                        <GenericParameter Name="string" Namespace="http://www.w3.org/2001/XMLSchema">
                            />
                        </GenericParameter>
                    </GenericType>
                </GenericParameter>
            </GenericType>
        </xs:appinfo>
    </xs:annotation>
    <xs:sequence>
        <xs:element xmlns:q4="http://schemas.microsoft.com/2003/10/Serialization/Arrays"
            name="list" nillable="true" type="q4:ArrayOfstring" />
    </xs:sequence>
</xs:complexType>
<xs:element name="ReadOnlyCollectionOfstring" nillable="true"
    type="tns:ReadOnlyCollectionOfstring" />
<xs:complexType name="ReadOnlyCollectionOfO365UserLicenseg8jlx19J">
    <xs:annotation>
        <xs:appinfo>
            <GenericType Name="ReadOnlyCollectionOf{0}{#}">
                Namespace="http://schemas.datacontract.org/2004/07/System.Collections.ObjectModel"
                xmlns="http://schemas.microsoft.com/2003/10/Serialization/">
                    <GenericParameter Name="O365UserLicense">
                        Namespace="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.O365Int
                        egration" />
                    </GenericType>
                </GenericParameter>
            </GenericType>
        </xs:appinfo>
    </xs:annotation>
    <xs:sequence>
        <xs:element
            xmlns:q5="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.O365Inte
            gration" name="list" nillable="true" type="q5:ArrayOfO365UserLicense" />
        </xs:sequence>
    </xs:complexType>
    <xs:element name="ReadOnlyCollectionOfO365UserLicenseg8jlx19J" nillable="true"
        type="tns:ReadOnlyCollectionOfO365UserLicenseg8jlx19J" />
    <xs:complexType name="ReadOnlyCollectionOfO365Domaing8jlx19J">
        <xs:annotation>
            <xs:appinfo>

```

```

        <GenericType Name="ReadOnlyCollectionOf{0}{#}">
Namespace="http://schemas.datacontract.org/2004/07/System.Collections.ObjectModel"
xmlns="http://schemas.microsoft.com/2003/10/Serialization/">
    <GenericParameter Name="O365Domain">
Namespace="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.O365Int
egration" />
    </GenericType>
    </xs:appinfo>
</xs:annotation>
<xs:sequence>
    <xs:element
xmlns:q6="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.O365Int
egration" name="list" nillable="true" type="q6:ArrayOfO365Domain" />
    </xs:sequence>
</xs:complexType>
<xs:element name="ReadOnlyCollectionOfO365Domaing8jlx19J" nillable="true"
type="tns:ReadOnlyCollectionOfO365Domaing8jlx19J" />
<xs:complexType name="ReadOnlyCollectionOfint">
    <xs:annotation>
        <xs:appinfo>
            <GenericType Name="ReadOnlyCollectionOf{0}{#}">
Namespace="http://schemas.datacontract.org/2004/07/System.Collections.ObjectModel"
xmlns="http://schemas.microsoft.com/2003/10/Serialization/">
                <GenericParameter Name="int" Namespace="http://www.w3.org/2001/XMLSchema" />
            </GenericType>
        </xs:appinfo>
    </xs:annotation>
    <xs:sequence>
        <xs:element xmlns:q7="http://schemas.microsoft.com/2003/10/Serialization/Arrays"
name="list" nillable="true" type="q7:ArrayOfint" />
    </xs:sequence>
</xs:complexType>
<xs:element name="ReadOnlyCollectionOfint" nillable="true"
type="tns:ReadOnlyCollectionOfint" />
<xs:complexType name="ReadOnlyCollectionOfSharePointRoleDefinitiong8jlx19J">
    <xs:annotation>
        <xs:appinfo>
            <GenericType Name="ReadOnlyCollectionOf{0}{#}">
Namespace="http://schemas.datacontract.org/2004/07/System.Collections.ObjectModel"
xmlns="http://schemas.microsoft.com/2003/10/Serialization/">
                <GenericParameter Name="SharePointRoleDefinition">
Namespace="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.O365Int
egration" />
                </GenericParameter>
            </GenericType>
        </xs:appinfo>
    </xs:annotation>
    <xs:sequence>
        <xs:element
xmlns:q8="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.O365Int
egration" name="list" nillable="true" type="q8:ArrayOfSharePointRoleDefinition" />
    </xs:sequence>
</xs:complexType>
<xs:element name="ReadOnlyCollectionOfSharePointRoleDefinitiong8jlx19J"
nillable="true" type="tns:ReadOnlyCollectionOfSharePointRoleDefinitiong8jlx19J" />
<xs:complexType name="ReadOnlyCollectionOfSharePointGroupg8jlx19J">
    <xs:annotation>
        <xs:appinfo>
            <GenericType Name="ReadOnlyCollectionOf{0}{#}">
Namespace="http://schemas.datacontract.org/2004/07/System.Collections.ObjectModel"
xmlns="http://schemas.microsoft.com/2003/10/Serialization/">
                <GenericParameter Name="SharePointGroup">
Namespace="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.O365Int
egration" />
                </GenericParameter>
            </GenericType>
        </xs:appinfo>
    </xs:annotation>
    <xs:sequence>

```

```

<xs:element
  xmlns:q9="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.O365Inte
  gration" name="list" nillable="true" type="q9:ArrayOfSharePointGroup" />
  </xs:sequence>
</xs:complexType>
<xs:element name="ReadOnlyCollectionOfSharePointGroupg8jlx19J" nillable="true"
  type="tns:ReadOnlyCollectionOfSharePointGroupg8jlx19J" />
  <xs:complexType name="ReadOnlyCollectionOfSharePointUserg8jlx19J">
    <xs:annotation>
      <xs:appinfo>
        <GenericType Name="ReadOnlyCollectionOf{0}{{#}}"
          Namespace="http://schemas.datacontract.org/2004/07/System.Collections.ObjectModel"
          xmlns="http://schemas.microsoft.com/2003/10/Serialization/">
          <GenericParameter Name="SharePointUser" />
        Namespace="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.O365Int
        egration" />
        </GenericType>
      </xs:appinfo>
    </xs:annotation>
    <xs:sequence>
      <xs:element
        xmlns:q10="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.O365Int
        egration" name="list" nillable="true" type="q10:ArrayOfSharePointUser" />
      </xs:sequence>
    </xs:complexType>
    <xs:element name="ReadOnlyCollectionOfSharePointUserg8jlx19J" nillable="true"
      type="tns:ReadOnlyCollectionOfSharePointUserg8jlx19J" />
    <xs:complexType name="ReadOnlyCollectionOfSharePointRoleAssignmentg8jlx19J">
      <xs:annotation>
        <xs:appinfo>
          <GenericType Name="ReadOnlyCollectionOf{0}{{#}}"
            Namespace="http://schemas.datacontract.org/2004/07/System.Collections.ObjectModel"
            xmlns="http://schemas.microsoft.com/2003/10/Serialization/">
            <GenericParameter Name="SharePointRoleAssignment" />
          Namespace="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.O365Int
          egration" />
          </GenericType>
        </xs:appinfo>
      </xs:annotation>
      <xs:sequence>
        <xs:element
          xmlns:q11="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.O365Int
          egration" name="list" nillable="true" type="q11:ArrayOfSharePointRoleAssignment" />
        </xs:sequence>
      </xs:complexType>
      <xs:element name="ReadOnlyCollectionOfSharePointRoleAssignmentg8jlx19J"
        nillable="true" type="tns:ReadOnlyCollectionOfSharePointRoleAssignmentg8jlx19J" />
      <xs:complexType name="ReadOnlyCollectionOfanyURI">
        <xs:annotation>
          <xs:appinfo>
            <GenericType Name="ReadOnlyCollectionOf{0}{{#}}"
              Namespace="http://schemas.datacontract.org/2004/07/System.Collections.ObjectModel"
              xmlns="http://schemas.microsoft.com/2003/10/Serialization/">
              <GenericParameter Name="anyURI" Namespace="http://www.w3.org/2001/XMLSchema" />
            </GenericType>
          </xs:appinfo>
        </xs:annotation>
        <xs:sequence>
          <xs:element
            xmlns:q12="http://schemas.microsoft.com/2003/10/Serialization/Arrays" name="list"
            nillable="true" type="q12:ArrayOfanyURI" />
          </xs:sequence>
        </xs:complexType>
        <xs:element name="ReadOnlyCollectionOfanyURI" nillable="true"
          type="tns:ReadOnlyCollectionOfanyURI" />
      </xs:complexType>
    </xs:sequence>
  </xs:complexType>
</xs:schema>

```

6.10.2.5 <http://schemas.datacontract.org/2004/07/System.Net.Sockets>

```
<?xml version="1.0" encoding="utf-8"?>
<xs:schema xmlns:tns="http://schemas.datacontract.org/2004/07/System.Net.Sockets"
elementFormDefault="qualified"
targetNamespace="http://schemas.datacontract.org/2004/07/System.Net.Sockets"
xmlns:xs="http://www.w3.org/2001/XMLSchema">
    <xs:import schemaLocation="" />
    <xs:simpleType name="AddressFamily">
        <xs:restriction base="xs:string">
            <xs:enumeration value="Unknown">
                <xs:annotation>
                    <xs:appinfo>
                        <EnumerationValue
                            xmlns="http://schemas.microsoft.com/2003/10/Serialization/" />-1</EnumerationValue>
                    </xs:appinfo>
                </xs:annotation>
            </xs:enumeration>
            <xs:enumeration value="Unspecified">
                <xs:annotation>
                    <xs:appinfo>
                        <EnumerationValue
                            xmlns="http://schemas.microsoft.com/2003/10/Serialization/" />0</EnumerationValue>
                    </xs:appinfo>
                </xs:annotation>
            </xs:enumeration>
            <xs:enumeration value="Unix">
                <xs:annotation>
                    <xs:appinfo>
                        <EnumerationValue
                            xmlns="http://schemas.microsoft.com/2003/10/Serialization/" />1</EnumerationValue>
                    </xs:appinfo>
                </xs:annotation>
            </xs:enumeration>
            <xs:enumeration value="InterNetwork">
                <xs:annotation>
                    <xs:appinfo>
                        <EnumerationValue
                            xmlns="http://schemas.microsoft.com/2003/10/Serialization/" />2</EnumerationValue>
                    </xs:appinfo>
                </xs:annotation>
            </xs:enumeration>
            <xs:enumeration value="ImpLink">
                <xs:annotation>
                    <xs:appinfo>
                        <EnumerationValue
                            xmlns="http://schemas.microsoft.com/2003/10/Serialization/" />3</EnumerationValue>
                    </xs:appinfo>
                </xs:annotation>
            </xs:enumeration>
            <xs:enumeration value="Pup">
                <xs:annotation>
                    <xs:appinfo>
                        <EnumerationValue
                            xmlns="http://schemas.microsoft.com/2003/10/Serialization/" />4</EnumerationValue>
                    </xs:appinfo>
                </xs:annotation>
            </xs:enumeration>
            <xs:enumeration value="Chaos">
                <xs:annotation>
                    <xs:appinfo>
                        <EnumerationValue
                            xmlns="http://schemas.microsoft.com/2003/10/Serialization/" />5</EnumerationValue>
                    </xs:appinfo>
                </xs:annotation>
            </xs:enumeration>
            <xs:enumeration value="NS">
                <xs:annotation>
```

```

        <xs:appinfo>
            <EnumerationValue
        xmlns="http://schemas.microsoft.com/2003/10/Serialization/">6</EnumerationValue>
            </xs:appinfo>
        </xs:annotation>
    </xs:enumeration>
    <xs:enumeration value="Ipx">
        <xs:annotation>
            <xs:appinfo>
                <EnumerationValue
        xmlns="http://schemas.microsoft.com/2003/10/Serialization/">6</EnumerationValue>
            </xs:appinfo>
        </xs:annotation>
    </xs:enumeration>
    <xs:enumeration value="Iso">
        <xs:annotation>
            <xs:appinfo>
                <EnumerationValue
        xmlns="http://schemas.microsoft.com/2003/10/Serialization/">7</EnumerationValue>
            </xs:appinfo>
        </xs:annotation>
    </xs:enumeration>
    <xs:enumeration value="Osi">
        <xs:annotation>
            <xs:appinfo>
                <EnumerationValue
        xmlns="http://schemas.microsoft.com/2003/10/Serialization/">7</EnumerationValue>
            </xs:appinfo>
        </xs:annotation>
    </xs:enumeration>
    <xs:enumeration value="Ecma">
        <xs:annotation>
            <xs:appinfo>
                <EnumerationValue
        xmlns="http://schemas.microsoft.com/2003/10/Serialization/">8</EnumerationValue>
            </xs:appinfo>
        </xs:annotation>
    </xs:enumeration>
    <xs:enumeration value="DataKit">
        <xs:annotation>
            <xs:appinfo>
                <EnumerationValue
        xmlns="http://schemas.microsoft.com/2003/10/Serialization/">9</EnumerationValue>
            </xs:appinfo>
        </xs:annotation>
    </xs:enumeration>
    <xs:enumeration value="Ccitt">
        <xs:annotation>
            <xs:appinfo>
                <EnumerationValue
        xmlns="http://schemas.microsoft.com/2003/10/Serialization/">10</EnumerationValue>
            </xs:appinfo>
        </xs:annotation>
    </xs:enumeration>
    <xs:enumeration value="Sna">
        <xs:annotation>
            <xs:appinfo>
                <EnumerationValue
        xmlns="http://schemas.microsoft.com/2003/10/Serialization/">11</EnumerationValue>
            </xs:appinfo>
        </xs:annotation>
    </xs:enumeration>
    <xs:enumeration value="DecNet">
        <xs:annotation>
            <xs:appinfo>
                <EnumerationValue
        xmlns="http://schemas.microsoft.com/2003/10/Serialization/">12</EnumerationValue>
            </xs:appinfo>
        </xs:annotation>

```

```

    </xs:enumeration>
<xs:enumeration value="DataLink">
    <xs:annotation>
        <xs:appinfo>
            <EnumerationValue
                xmlns="http://schemas.microsoft.com/2003/10/Serialization/">13</EnumerationValue>
            </xs:appinfo>
        </xs:annotation>
    </xs:enumeration>
<xs:enumeration value="Lat">
    <xs:annotation>
        <xs:appinfo>
            <EnumerationValue
                xmlns="http://schemas.microsoft.com/2003/10/Serialization/">14</EnumerationValue>
            </xs:appinfo>
        </xs:annotation>
    </xs:enumeration>
<xs:enumeration value="HyperChannel">
    <xs:annotation>
        <xs:appinfo>
            <EnumerationValue
                xmlns="http://schemas.microsoft.com/2003/10/Serialization/">15</EnumerationValue>
            </xs:appinfo>
        </xs:annotation>
    </xs:enumeration>
<xs:enumeration value="AppleTalk">
    <xs:annotation>
        <xs:appinfo>
            <EnumerationValue
                xmlns="http://schemas.microsoft.com/2003/10/Serialization/">16</EnumerationValue>
            </xs:appinfo>
        </xs:annotation>
    </xs:enumeration>
<xs:enumeration value="NetBios">
    <xs:annotation>
        <xs:appinfo>
            <EnumerationValue
                xmlns="http://schemas.microsoft.com/2003/10/Serialization/">17</EnumerationValue>
            </xs:appinfo>
        </xs:annotation>
    </xs:enumeration>
<xs:enumeration value="VoiceView">
    <xs:annotation>
        <xs:appinfo>
            <EnumerationValue
                xmlns="http://schemas.microsoft.com/2003/10/Serialization/">18</EnumerationValue>
            </xs:appinfo>
        </xs:annotation>
    </xs:enumeration>
<xs:enumeration value="FireFox">
    <xs:annotation>
        <xs:appinfo>
            <EnumerationValue
                xmlns="http://schemas.microsoft.com/2003/10/Serialization/">19</EnumerationValue>
            </xs:appinfo>
        </xs:annotation>
    </xs:enumeration>
<xs:enumeration value="Banyan">
    <xs:annotation>
        <xs:appinfo>
            <EnumerationValue
                xmlns="http://schemas.microsoft.com/2003/10/Serialization/">21</EnumerationValue>
            </xs:appinfo>
        </xs:annotation>
    </xs:enumeration>
<xs:enumeration value="Atm">
    <xs:annotation>
        <xs:appinfo>

```

```

        <EnumerationValue
xmlns="http://schemas.microsoft.com/2003/10/Serialization/">22</EnumerationValue>
        </xs:appinfo>
    </xs:annotation>
</xs:enumeration>
<xs:enumeration value="InterNetworkV6">
    <xs:annotation>
        <xs:appinfo>
            <EnumerationValue
xmlns="http://schemas.microsoft.com/2003/10/Serialization/">23</EnumerationValue>
            </xs:appinfo>
        </xs:annotation>
    </xs:enumeration>
<xs:enumeration value="Cluster">
    <xs:annotation>
        <xs:appinfo>
            <EnumerationValue
xmlns="http://schemas.microsoft.com/2003/10/Serialization/">24</EnumerationValue>
            </xs:appinfo>
        </xs:annotation>
    </xs:enumeration>
<xs:enumeration value="Ieee12844">
    <xs:annotation>
        <xs:appinfo>
            <EnumerationValue
xmlns="http://schemas.microsoft.com/2003/10/Serialization/">25</EnumerationValue>
            </xs:appinfo>
        </xs:annotation>
    </xs:enumeration>
<xs:enumeration value="Irda">
    <xs:annotation>
        <xs:appinfo>
            <EnumerationValue
xmlns="http://schemas.microsoft.com/2003/10/Serialization/">26</EnumerationValue>
            </xs:appinfo>
        </xs:annotation>
    </xs:enumeration>
<xs:enumeration value="NetworkDesigners">
    <xs:annotation>
        <xs:appinfo>
            <EnumerationValue
xmlns="http://schemas.microsoft.com/2003/10/Serialization/">28</EnumerationValue>
            </xs:appinfo>
        </xs:annotation>
    </xs:enumeration>
<xs:enumeration value="Max">
    <xs:annotation>
        <xs:appinfo>
            <EnumerationValue
xmlns="http://schemas.microsoft.com/2003/10/Serialization/">29</EnumerationValue>
            </xs:appinfo>
        </xs:annotation>
    </xs:enumeration>
</xs:restriction>
</xs:simpleType>
<xs:element name="AddressFamily" nillable="true" type="tns:AddressFamily" />
</xs:schema>

```

6.10.2.6 http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.O365Integration

```

<?xml version="1.0" encoding="utf-8"?>
<xs:schema xmlns:ser="http://schemas.microsoft.com/2003/10/Serialization/"
xmlns:tns="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.O365Int
egration" elementFormDefault="qualified"
targetNamespace="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.O
365Integration" xmlns:xs="http://www.w3.org/2001/XMLSchema">

```

```

<xs:import schemaLocation=""
namespace="http://schemas.datacontract.org/2004/07/System.Collections.ObjectModel" />
<xs:import schemaLocation=""
namespace="http://schemas.microsoft.com/2003/10/Serialization/" />
<xs:import schemaLocation=""
namespace="http://schemas.datacontract.org/2004/07/System" />
<xs:import schemaLocation=""
namespace="http://schemas.microsoft.com/2003/10/Serialization/Arrays" />
<xs:complexType name="O365Information">
<xs:sequence>
<xs:element minOccurs="0" name="Activated" type="xs:boolean" />
<xs:element minOccurs="0" name="Address" nillable="true"
type="tns:CompanyAddress" />
<xs:element minOccurs="0" name="CompanyName" nillable="true" type="xs:string" />
<xs:element minOccurs="0" name="InitialDomain" nillable="true" type="xs:string"
/>
<xs:element
xmlns:q1="http://schemas.datacontract.org/2004/07/System.Collections.ObjectModel"
minOccurs="0" name="O365Skus" nillable="true" type="q1:ReadOnlyCollectionOfO365Skug8jlx19J"
/>
<xs:element minOccurs="0" name="PrimaryDomain" nillable="true" type="xs:string"
/>
<xs:element minOccurs="0" name="TechnicalContact" nillable="true"
type="xs:string" />
</xs:sequence>
</xs:complexType>
<xs:element name="O365Information" nillable="true" type="tns:O365Information" />
<xs:complexType name="CompanyAddress">
<xs:sequence>
<xs:element minOccurs="0" name="City" nillable="true" type="xs:string" />
<xs:element minOccurs="0" name="Country" nillable="true" type="xs:string" />
<xs:element minOccurs="0" name="PostalCode" nillable="true" type="xs:string" />
<xs:element minOccurs="0" name="State" nillable="true" type="xs:string" />
<xs:element minOccurs="0" name="Street" nillable="true" type="xs:string" />
<xs:element minOccurs="0" name="TelephoneNumber" nillable="true"
type="xs:string" />
</xs:sequence>
</xs:complexType>
<xs:element name="CompanyAddress" nillable="true" type="tns:CompanyAddress" />
<xs:complexType name="ArrayOfO365Sku">
<xs:sequence>
<xs:element minOccurs="0" maxOccurs="unbounded" name="O365Sku" nillable="true"
type="tns:O365Sku" />
</xs:sequence>
</xs:complexType>
<xs:element name="ArrayOfO365Sku" nillable="true" type="tns:ArrayOfO365Sku" />
<xs:complexType name="O365Sku">
<xs:sequence>
<xs:element minOccurs="0" name="AccountName" nillable="true" type="xs:string" />
<xs:element minOccurs="0" name="ConsumedLicenses" type="xs:int" />
<xs:element minOccurs="0" name="Description" nillable="true" type="xs:string" />
<xs:element
xmlns:q2="http://schemas.datacontract.org/2004/07/System.Collections.ObjectModel"
minOccurs="0" name="O365Services" nillable="true"
type="q2:ReadOnlyCollectionOfO365Serviceg8jlx19J" />
<xs:element
xmlns:q3="http://schemas.datacontract.org/2004/07/System.Collections.ObjectModel"
minOccurs="0" name="O365Subscriptions" nillable="true"
type="q3:ReadOnlyCollectionOfO365Subscriptiong8jlx19J" />
<xs:element minOccurs="0" name="Skuid" nillable="true" type="xs:string" />
<xs:element minOccurs="0" name="TotalLicenses" type="xs:int" />
</xs:sequence>
</xs:complexType>
<xs:element name="O365Sku" nillable="true" type="tns:O365Sku" />
<xs:complexType name="ArrayOfO365Service">
<xs:sequence>
<xs:element minOccurs="0" maxOccurs="unbounded" name="O365Service"
nillable="true" type="tns:O365Service" />
</xs:sequence>

```

```

    </xs:complexType>
  <xs:element name="ArrayOfO365Service" nillable="true" type="tns:ArrayOfO365Service"
/>
<xs:complexType name="O365Service">
  <xs:sequence>
    <xs:element minOccurs="0" name="Activated" type="xs:boolean" />
    <xs:element minOccurs="0" name="Description" nillable="true" type="xs:string" />
    <xs:element minOccurs="0" name="ServicePlan" nillable="true" type="xs:string" />
    <xs:element minOccurs="0" name="ServiceType" type="tns:O365ServiceTypes" />
  </xs:sequence>
</xs:complexType>
<xs:element name="O365Service" nillable="true" type="tns:O365Service" />
<xs:simpleType name="O365ServiceTypes">
  <xs:list>
    <xs:simpleType>
      <xs:restriction base="xs:string">
        <xs:enumeration value="None">
          <xs:annotation>
            <xs:appinfo>
              <EnumerationValue
                xmlns="http://schemas.microsoft.com/2003/10/Serialization/">0</EnumerationValue>
            </xs:appinfo>
          </xs:annotation>
        </xs:enumeration>
        <xs:enumeration value="Unknown">
          <xs:annotation>
            <xs:appinfo>
              <EnumerationValue
                xmlns="http://schemas.microsoft.com/2003/10/Serialization/">1</EnumerationValue>
            </xs:appinfo>
          </xs:annotation>
        </xs:enumeration>
        <xs:enumeration value="ExchangeOnline">
          <xs:annotation>
            <xs:appinfo>
              <EnumerationValue
                xmlns="http://schemas.microsoft.com/2003/10/Serialization/">2</EnumerationValue>
            </xs:appinfo>
          </xs:annotation>
        </xs:enumeration>
        <xs:enumeration value="SharePointOnline">
          <xs:annotation>
            <xs:appinfo>
              <EnumerationValue
                xmlns="http://schemas.microsoft.com/2003/10/Serialization/">4</EnumerationValue>
            </xs:appinfo>
          </xs:annotation>
        </xs:enumeration>
        <xs:enumeration value="LyncOnline">
          <xs:annotation>
            <xs:appinfo>
              <EnumerationValue
                xmlns="http://schemas.microsoft.com/2003/10/Serialization/">8</EnumerationValue>
            </xs:appinfo>
          </xs:annotation>
        </xs:enumeration>
        <xs:enumeration value="IntuneOnline">
          <xs:annotation>
            <xs:appinfo>
              <EnumerationValue
                xmlns="http://schemas.microsoft.com/2003/10/Serialization/">16</EnumerationValue>
            </xs:appinfo>
          </xs:annotation>
        </xs:enumeration>
      </xs:restriction>
    </xs:simpleType>
  </xs:list>
</xs:simpleType>
<xs:element name="O365ServiceTypes" nillable="true" type="tns:O365ServiceTypes" />

```

```

<xs:complexType name="ArrayOfO365Subscription">
    <xs:sequence>
        <xs:element minOccurs="0" maxOccurs="unbounded" name="O365Subscription"
nillable="true" type="tns:O365Subscription" />
    </xs:sequence>
</xs:complexType>
<xs:element name="ArrayOfO365Subscription" nillable="true"
type="tns:ArrayOfO365Subscription" />
<xs:complexType name="O365Subscription">
    <xs:sequence>
        <xs:element minOccurs="0" name="BillingExpirationTime" type="xs:dateTime" />
        <xs:element minOccurs="0" name="Expired" type="xs:boolean" />
    </xs:sequence>
</xs:complexType>
<xs:element name="O365Subscription" nillable="true" type="tns:O365Subscription" />
<xs:complexType name="O365User">
    <xs:sequence>
        <xs:element minOccurs="0" name="Activated" type="xs:boolean" />
        <xs:element
xmlns:q4="http://schemas.datacontract.org/2004/07/System.Collections.ObjectModel"
minOccurs="0" name="EmailAddresses" nillable="true" type="q4:ReadOnlyCollectionOfstring" />
            <xs:element minOccurs="0" name="LocalUserName" nillable="true" type="xs:string" />
        <xs:element minOccurs="0" name="ObjectId" type="ser:guid" />
        <xs:element
xmlns:q5="http://schemas.datacontract.org/2004/07/System.Collections.ObjectModel"
minOccurs="0" name="UserLicenses" nillable="true"
type="q5:ReadOnlyCollectionOfO365UserLicenseg8jlx19J" />
            <xs:element minOccurs="0" name="UserPrincipalName" nillable="true"
type="xs:string" />
        </xs:sequence>
    </xs:complexType>
<xs:element name="O365User" nillable="true" type="tns:O365User" />
<xs:complexType name="ArrayOfO365UserLicense">
    <xs:sequence>
        <xs:element minOccurs="0" maxOccurs="unbounded" name="O365UserLicense"
nillable="true" type="tns:O365UserLicense" />
    </xs:sequence>
</xs:complexType>
<xs:element name="ArrayOfO365UserLicense" nillable="true"
type="tns:ArrayOfO365UserLicense" />
<xs:complexType name="O365UserLicense">
    <xs:sequence>
        <xs:element minOccurs="0" name="AccountName" nillable="true" type="xs:string" />
        <xs:element
xmlns:q6="http://schemas.datacontract.org/2004/07/System.Collections.ObjectModel"
minOccurs="0" name="O365Services" nillable="true"
type="q6:ReadOnlyCollectionOfO365Serviceg8jlx19J" />
            <xs:element minOccurs="0" name="SkuId" nillable="true" type="xs:string" />
        </xs:sequence>
    </xs:complexType>
<xs:element name="O365UserLicense" nillable="true" type="tns:O365UserLicense" />
<xs:complexType name="O365ConfigureException">
    <xs:complexContent mixed="false">
        <xs:extension xmlns:q7="http://schemas.datacontract.org/2004/07/System"
base="q7:Exception" />
    </xs:complexContent>
</xs:complexType>
<xs:element name="O365ConfigureException" nillable="true"
type="tns:O365ConfigureException" />
<xs:complexType name="O365UserMap">
    <xs:sequence>
        <xs:element minOccurs="0" name="Error" nillable="true"
type="tns:O365ConfigureException" />
        <xs:element minOccurs="0" name="LocalUserName" nillable="true" type="xs:string" />
        <xs:element minOccurs="0" name="OnlineUserName" nillable="true" type="xs:string" />
    </xs:sequence>
</xs:complexType>

```

```

</xs:complexType>
<xs:element name="O365UserMap" nillable="true" type="tns:O365UserMap" />
<xs:complexType name="ArrayOfO365UserMap">
    <xs:sequence>
        <xs:element minOccurs="0" maxOccurs="unbounded" name="O365UserMap"
nillable="true" type="tns:O365UserMap" />
    </xs:sequence>
</xs:complexType>
<xs:element name="ArrayOfO365UserMap" nillable="true" type="tns:ArrayOfO365UserMap"
/>
<xs:simpleType name="O365ConfigureFault">
    <xs:restriction base="xs:string">
        <xs:enumeration value="Unexpected" />
        <xs:enumeration value="Communication" />
        <xs:enumeration value="IncorrectCredential" />
        <xs:enumeration value="AccessDenied" />
        <xs:enumeration value="OnlineUserNotExist" />
        <xs:enumeration value="OnlineUserAlreadyMapped" />
        <xs:enumeration value="LocalUserNotExist" />
        <xs:enumeration value="LocalUserNotMapped" />
        <xs:enumeration value="LocalUserAlreadyMapped" />
        <xs:enumeration value="DomainNotConfigured" />
        <xs:enumeration value="DomainVerifyFailed" />
        <xs:enumeration value="NotActivated" />
        <xs:enumeration value="NotAvailable" />
        <xs:enumeration value="NoSubscription" />
        <xs:enumeration value="NoAvailableLicense" />
        <xs:enumeration value="InvalidLicensesConfig" />
        <xs:enumeration value="LocalProviderIssue" />
        <xs:enumeration value="OnlineServiceIssue" />
        <xs:enumeration value="OnlineUserAlreadyExist" />
        <xs:enumeration value="InvalidPassword" />
        <xs:enumeration value="DeactivateServiceAdminAccount" />
        <xs:enumeration value="RemoveServiceAdminAccount" />
        <xs:enumeration value="RemoveReferencedDomain" />
        <xs:enumeration value="CredentialFromDifferentDomain" />
        <xs:enumeration value="DuplicateEmailAliasInInitialDomain" />
        <xs:enumeration value="EmailAddressAlreadyExist" />
        <xs:enumeration value="InvalidEmailAddress" />
        <xs:enumeration value="UserHasNoExLicense" />
        <xs:enumeration value="MobileDeviceNotFound" />
        <xs:enumeration value="MobileDevicePolicyNotFound" />
        <xs:enumeration value="MobileDevicePolicyConflict" />
        <xs:enumeration value="MobileDeviceAccessRuleNotFound" />
        <xs:enumeration value="MobileDeviceAccessRuleConflict" />
        <xs:enumeration value="MobileDeviceDeleteLimitationReached" />
        <xs:enumeration value="ExGroupIdentityNotFound" />
        <xs:enumeration value="ExAdminHasNoExLicense" />
        <xs:enumeration value="ExGroupNameAlreadyExists" />
        <xs:enumeration value="ExGroupEmailAddressInvalidDomain" />
        <xs:enumeration value="MSOSecurityGroupAlreadyExists" />
        <xs:enumeration value="MSOSecurityGroupNotFound" />
        <xs:enumeration value="MSOSecurityGroupMemberNotFound" />
        <xs:enumeration value="LocalGroupDoesNotExist" />
        <xs:enumeration value="LocalGroupAlreadyMapped" />
        <xs:enumeration value="MSOSecurityGroupAlreadyMapped" />
        <xs:enumeration value="LocalGroupNotMapped" />
        <xs:enumeration value="PwdSyncAccessDenied" />
        <xs:enumeration value="RebootPending" />
    </xs:restriction>
</xs:simpleType>
<xs:element name="O365ConfigureFault" nillable="true" type="tns:O365ConfigureFault"
/>
<xs:complexType name="O365DomainConfiguration">
    <xs:sequence>
        <xs:element
xmlns:q8="http://schemas.datacontract.org/2004/07/System.Collections.ObjectModel"
minOccurs="0" name="AvailableDomains" nillable="true"
type="q8:ReadOnlyCollectionOfO365Domaing8jlx19J" />

```

```

<xs:element minOccurs="0" name="CustomDomainName" nillable="true"
type="xs:string" />
    <xs:element minOccurs="0" name="CustomDomainStatus" type="tns:O365DomainStatus"
/>
        <xs:element minOccurs="0" name="PrimaryDomainName" nillable="true"
type="xs:string" />
    </xs:sequence>
</xs:complexType>
<xs:element name="O365DomainConfiguration" nillable="true"
type="tns:O365DomainConfiguration" />
    <xs:complexType name="ArrayOfO365Domain">
        <xs:sequence>
            <xs:element minOccurs="0" maxOccurs="unbounded" name="O365Domain"
nillable="true" type="tns:O365Domain" />
        </xs:sequence>
    </xs:complexType>
<xs:element name="ArrayOfO365Domain" nillable="true" type="tns:ArrayOfO365Domain" />
<xs:complexType name="O365Domain">
    <xs:sequence>
        <xs:element minOccurs="0" name="CapabilityType" type="tns:O365DomainType" />
        <xs:element minOccurs="0" name="IsPrimary" type="xs:boolean" />
        <xs:element minOccurs="0" name="IsVerified" type="xs:boolean" />
        <xs:element minOccurs="0" name="Name" nillable="true" type="xs:string" />
    </xs:sequence>
</xs:complexType>
<xs:element name="O365Domain" nillable="true" type="tns:O365Domain" />
<xs:simpleType name="O365DomainType">
    <xs:restriction base="xs:string">
        <xs:enumeration value="None" />
        <xs:enumeration value="Email" />
        <xs:enumeration value="Sharepoint" />
    </xs:restriction>
</xs:simpleType>
<xs:element name="O365DomainType" nillable="true" type="tns:O365DomainType" />
<xs:simpleType name="O365DomainStatus">
    <xs:restriction base="xs:string">
        <xs:enumeration value="NotConfigured" />
        <xs:enumeration value="Unverified" />
        <xs:enumeration value="Verified" />
        <xs:enumeration value="VerifyFailed" />
        <xs:enumeration value="FullyConfigured" />
    </xs:restriction>
</xs:simpleType>
<xs:element name="O365DomainStatus" nillable="true" type="tns:O365DomainStatus" />
<xs:complexType name="ArrayOfO365User">
    <xs:sequence>
        <xs:element minOccurs="0" maxOccurs="unbounded" name="O365User" nillable="true"
type="tns:O365User" />
    </xs:sequence>
</xs:complexType>
<xs:element name="ArrayOfO365User" nillable="true" type="tns:ArrayOfO365User" />
<xs:complexType name="O365InvalidEmailAddressException">
    <xs:complexContent mixed="false">
        <xs:extension base="tns:O365ConfigureException" />
    </xs:complexContent>
</xs:complexType>
<xs:element name="O365InvalidEmailAddressException" nillable="true"
type="tns:O365InvalidEmailAddressException" />
<xs:complexType name="O365DuplicateEmailAliasException">
    <xs:complexContent mixed="false">
        <xs:extension base="tns:O365ConfigureException" />
    </xs:complexContent>
</xs:complexType>
<xs:element name="O365DuplicateEmailAliasException" nillable="true"
type="tns:O365DuplicateEmailAliasException" />
<xs:complexType name="AADNoSubscriptionException">
    <xs:complexContent mixed="false">
        <xs:extension base="tns:O365ConfigureException" />
    </xs:complexContent>
</xs:complexType>

```

```

    </xs:complexType>
    <xs:element name="AADNoSubscriptionException" nillable="true"
type="tns:AADNoSubscriptionException" />
    <xs:complexType name="O365LicenseConfigurationException">
        <xs:complexContent mixed="false">
            <xs:extension base="tns:O365ConfigureException" />
        </xs:complexContent>
    </xs:complexType>
    <xs:element name="O365LicenseConfigurationException" nillable="true"
type="tns:O365LicenseConfigurationException" />
        <xs:complexType name="O365LicenseErrorDetail">
            <xs:sequence>
                <xs:element name="_x003C_DependsOnServices_x003E_k__BackingField"
nillable="true" type="tns:ArrayOfO365Service" />
                    <xs:element name="_x003C_ErrorType_x003E_k__BackingField"
type="tns:O365LicenseErrorType" />
                <xs:element name=" x003C Services x003E k BackingField" nillable="true"
type="tns:ArrayOfO365Service" />
            </xs:sequence>
        </xs:complexType>
        <xs:element name="O365LicenseErrorDetail" nillable="true"
type="tns:O365LicenseErrorDetail" />
            <xs:simpleType name="O365LicenseErrorType">
                <xs:restriction base="xs:string">
                    <xs:enumeration value="MutuallyExclusiveViolation" />
                    <xs:enumeration value="DependencyViolation" />
                    <xs:enumeration value="ProhibitedInUsageLocationViolation" />
                    <xs:enumeration value="RestrictedInUsageLocationViolation" />
                    <xs:enumeration value="OnPremiseMailboxViolation" />
                    <xs:enumeration value="Other" />
                </xs:restriction>
            </xs:simpleType>
            <xs:element name="O365LicenseErrorType" nillable="true"
type="tns:O365LicenseErrorType" />
                <xs:complexType name="ArrayOfO365LicenseErrorDetail">
                    <xs:sequence>
                        <xs:element minOccurs="0" maxOccurs="unbounded" name="O365LicenseErrorDetail"
nillable="true" type="tns:O365LicenseErrorDetail" />
                    </xs:sequence>
                </xs:complexType>
                <xs:element name="ArrayOfO365LicenseErrorDetail" nillable="true"
type="tns:ArrayOfO365LicenseErrorDetail" />
                    <xs:complexType name="O365EmailAddressAlreadyExistException">
                        <xs:complexContent mixed="false">
                            <xs:extension base="tns:O365ConfigureException" />
                        </xs:complexContent>
                    </xs:complexType>
                    <xs:element name="O365EmailAddressAlreadyExistException" nillable="true"
type="tns:O365EmailAddressAlreadyExistException" />
                        <xs:complexType name="O365MobileDeviceException">
                            <xs:complexContent mixed="false">
                                <xs:extension base="tns:O365ConfigureException" />
                            </xs:complexContent>
                        </xs:complexType>
                        <xs:element name="O365MobileDeviceException" nillable="true"
type="tns:O365MobileDeviceException" />
                            <xs:complexType name="ArrayOfO365MailboxStatisticsInfo">
                                <xs:sequence>
                                    <xs:element minOccurs="0" maxOccurs="unbounded" name="O365MailboxStatisticsInfo"
nillable="true" type="tns:O365MailboxStatisticsInfo" />
                                </xs:sequence>
                            </xs:complexType>
                            <xs:element name="ArrayOfO365MailboxStatisticsInfo" nillable="true"
type="tns:ArrayOfO365MailboxStatisticsInfo" />
                                <xs:complexType name="O365MailboxStatisticsInfo">
                                    <xs:sequence>
                                        <xs:element minOccurs="0" name="MailboxGUID" type="ser:guid" />
                                        <xs:element minOccurs="0" name="ProhibitSendReceiveQuota" nillable="true"
type="tns:QuotaProperty" />
                                    </xs:sequence>
                                </xs:complexType>
                            </xs:element>
                        </xs:complexType>
                    </xs:element>
                </xs:complexType>
            </xs:element>
        </xs:sequence>
    </xs:complexType>

```

```

<xs:element minOccurs="0" name="TotalItemSize" nillable="true"
type="tns:QuotaProperty" />
    <xs:element minOccurs="0" name="UserPrincipalName" nillable="true"
type="xs:string" />
        </xs:sequence>
    </xs:complexType>
    <xs:element name="O365MailboxStatisticsInfo" nillable="true"
type="tns:O365MailboxStatisticsInfo" />
        <xs:complexType name="QuotaProperty">
            <xs:sequence>
                <xs:element minOccurs="0" name="Quota" type="xs:unsignedLong" />
                <xs:element minOccurs="0" name="unlimited" type="xs:boolean" />
            </xs:sequence>
        </xs:complexType>
    <xs:element name="QuotaProperty" nillable="true" type="tns:QuotaProperty" />
    <xs:complexType name="ExchangeDistrGroup">
        <xs:complexContent mixed="false">
            <xs:extension base="tns:ExchangeGroupIdentity">
                <xs:sequence>
                    <xs:element
xmlns:q9="http://schemas.microsoft.com/2003/10/Serialization/Arrays" minOccurs="0"
name="MemberNames" nillable="true" type="q9:ArrayOfstring" />
                        <xs:element minOccurs="0" name="RequireSenderAuthentication"
type="xs:boolean" />
                            </xs:sequence>
                        </xs:extension>
                    </xs:complexContent>
                </xs:complexType>
            <xs:element name="ExchangeDistrGroup" nillable="true" type="tns:ExchangeDistrGroup"
/>
            <xs:complexType name="ExchangeGroupIdentity">
                <xs:sequence>
                    <xs:element minOccurs="0" name="Description" nillable="true" type="xs:string" />
                    <xs:element minOccurs="0" name="DisplayName" nillable="true" type="xs:string" />
                    <xs:element minOccurs="0" name="EmailAddress" nillable="true" type="xs:string"
/>
                    <xs:element minOccurs="0" name="Name" nillable="true" type="xs:string" />
                    <xs:element minOccurs="0" name="ObjectId" type="ser:guid" />
                </xs:sequence>
            </xs:complexType>
            <xs:element name="ExchangeGroupIdentity" nillable="true"
type="tns:ExchangeGroupIdentity" />
            <xs:complexType name="ExchangeGroupUser">
                <xs:complexContent mixed="false">
                    <xs:extension base="tns:ExchangeGroupIdentity">
                        <xs:sequence>
                            <xs:element minOccurs="0" name="LocalUserName" nillable="true"
type="xs:string" />
                        </xs:sequence>
                    </xs:extension>
                </xs:complexContent>
            </xs:complexType>
            <xs:element name="ExchangeGroupUser" nillable="true" type="tns:ExchangeGroupUser" />
            <xs:complexType name="ArrayOfExchangeDistrGroup">
                <xs:sequence>
                    <xs:element minOccurs="0" maxOccurs="unbounded" name="ExchangeDistrGroup"
nillable="true" type="tns:ExchangeDistrGroup" />
                </xs:sequence>
            </xs:complexType>
            <xs:element name="ArrayOfExchangeDistrGroup" nillable="true"
type="tns:ArrayOfExchangeDistrGroup" />
            <xs:complexType name="ArrayOfExchangeGroupUser">
                <xs:sequence>
                    <xs:element minOccurs="0" maxOccurs="unbounded" name="ExchangeGroupUser"
nillable="true" type="tns:ExchangeGroupUser" />
                </xs:sequence>
            </xs:complexType>
            <xs:element name="ArrayOfExchangeGroupUser" nillable="true"
type="tns:ArrayOfExchangeGroupUser" />
        </xs:sequence>
    </xs:complexType>

```

```

<xs:complexType name="ArrayOfExchangeGroupIdentity">
    <xs:sequence>
        <xs:element minOccurs="0" maxOccurs="unbounded" name="ExchangeGroupIdentity"
nillable="true" type="tns:ExchangeGroupIdentity" />
    </xs:sequence>
</xs:complexType>
<xs:element name="ArrayOfExchangeGroupIdentity" nillable="true"
type="tns:ArrayOfExchangeGroupIdentity" />
    <xs:complexType name="ExIdentityNotFoundException">
        <xs:complexContent mixed="false">
            <xs:extension base="tns:O365ConfigureException" />
        </xs:complexContent>
    </xs:complexType>
    <xs:element name="ExIdentityNotFoundException" nillable="true"
type="tns:ExIdentityNotFoundException" />
        <xs:complexType name="ExGroupNameAlreadyExistsException">
            <xs:complexContent mixed="false">
                <xs:extension base="tns:O365ConfigureException" />
            </xs:complexContent>
        </xs:complexType>
        <xs:element name="ExGroupNameAlreadyExistsException" nillable="true"
type="tns:ExGroupNameAlreadyExistsException" />
            <xs:complexType name="ExEmailAddressInvalidDomainException">
                <xs:complexContent mixed="false">
                    <xs:extension base="tns:O365ConfigureException" />
                </xs:complexContent>
            </xs:complexType>
            <xs:element name="ExEmailAddressInvalidDomainException" nillable="true"
type="tns:ExEmailAddressInvalidDomainException" />
                <xs:complexType name="MobileDeviceInfo">
                    <xs:sequence>
                        <xs:element minOccurs="0" name="DeviceFriendlyName" nillable="true"
type="xs:string" />
                        <xs:element minOccurs="0" name="DeviceID" nillable="true" type="xs:string" />
                        <xs:element minOccurs="0" name="DeviceMobileOperator" nillable="true"
type="xs:string" />
                        <xs:element minOccurs="0" name="DeviceModel" nillable="true" type="xs:string" />
                        <xs:element minOccurs="0" name="DeviceOS" nillable="true" type="xs:string" />
                        <xs:element minOccurs="0" name="DevicePhoneNumber" nillable="true"
type="xs:string" />
                        <xs:element minOccurs="0" name="DeviceState" type="tns:DeviceStateType" />
                        <xs:element minOccurs="0" name="DeviceType" nillable="true" type="xs:string" />
                        <xs:element minOccurs="0" name="DisplayName" nillable="true" type="xs:string" />
                        <xs:element minOccurs="0" name="FirstSuccessSync" nillable="true"
type="xs:string" />
                        <xs:element minOccurs="0" name="Identity" type="ser:guid" />
                        <xs:element minOccurs="0" name="IsRemoteWipeSupported" type="xs:boolean" />
                        <xs:element minOccurs="0" name="LastSuccessSync" nillable="true"
type="xs:string" />
                        <xs:element minOccurs="0" name="Mailbox" nillable="true" type="xs:string" />
                    </xs:sequence>
                </xs:complexType>
<xs:element name="MobileDeviceInfo" nillable="true" type="tns:MobileDeviceInfo" />
<xs:simpleType name="DeviceStateType">
    <xs:restriction base="xs:string">
        <xs:enumeration value="Allowed" />
        <xs:enumeration value="Blocked" />
        <xs:enumeration value="DeviceWipePending" />
        <xs:enumeration value="DeviceWipeSucceeded" />
        <xs:enumeration value="Unknown" />
    </xs:restriction>
</xs:simpleType>
<xs:element name="DeviceStateType" nillable="true" type="tns:DeviceStateType" />
<xs:complexType name="ArrayOfMobileDeviceInfo">
    <xs:sequence>
        <xs:element minOccurs="0" maxOccurs="unbounded" name="MobileDeviceInfo"
nillable="true" type="tns:MobileDeviceInfo" />
    </xs:sequence>
</xs:complexType>

```

```

<xs:element name="ArrayOfMobileDeviceInfo" nillable="true"
type="tns:ArrayOfMobileDeviceInfo" />
<xs:complexType name="MobileDeviceAccessRule">
<xs:sequence>
<xs:element minOccurs="0" name="Characteristic" nillable="true" type="xs:string"
/>
<xs:element minOccurs="0" name="Identity" type="ser:guid" />
<xs:element minOccurs="0" name="Name" nillable="true" type="xs:string" />
<xs:element minOccurs="0" name="QueryStr" nillable="true" type="xs:string" />
</xs:sequence>
</xs:complexType>
<xs:element name="MobileDeviceAccessRule" nillable="true"
type="tns:MobileDeviceAccessRule" />
<xs:complexType name="ArrayOfMobileDeviceAccessRule">
<xs:sequence>
<xs:element minOccurs="0" maxOccurs="unbounded" name="MobileDeviceAccessRule"
nillable="true" type="tns:MobileDeviceAccessRule" />
</xs:sequence>
</xs:complexType>
<xs:element name="ArrayOfMobileDeviceAccessRule" nillable="true"
type="tns:ArrayOfMobileDeviceAccessRule" />
<xs:complexType name="MobileDevicePolicy">
<xs:sequence>
<xs:element minOccurs="0" name="AllowSimpleDevicePassword" type="xs:boolean" />
<xs:element minOccurs="0" name="AlphanumericDevicePasswordRequired"
type="xs:boolean" />
<xs:element minOccurs="0" name="DeviceEncryptionEnabled" type="xs:boolean" />
<xs:element minOccurs="0" name="DevicePasswordEnabled" type="xs:boolean" />
<xs:element minOccurs="0" name="DevicePasswordExpiration" type="xs:int" />
<xs:element minOccurs="0" name="DevicePasswordHistory" type="xs:int" />
<xs:element minOccurs="0" name="Identity" type="ser:guid" />
<xs:element minOccurs="0" name="IsDefault" type="xs:boolean" />
<xs:element minOccurs="0" name="MaxDevicePasswordFailedAttempts" type="xs:int"
/>
<xs:element minOccurs="0" name="MaxInactivityTimeDeviceLock" type="xs:int" />
<xs:element minOccurs="0" name="MinDevicePasswordComplexCharacters"
type="xs:int" />
<xs:element minOccurs="0" name="MinDevicePasswordLength" type="xs:int" />
</xs:sequence>
</xs:complexType>
<xs:element name="MobileDevicePolicy" nillable="true" type="tns:MobileDevicePolicy"
/>
<xs:complexType name="SharePointUser">
<xs:complexContent mixed="false">
<xs:extension base="tns:SharePointPrincipal">
<xs:sequence>
<xs:element minOccurs="0" name="Email" nillable="true" type="xs:string" />
<xs:element
xmlns:q10="http://schemas.datacontract.org/2004/07/System.Collections.ObjectModel"
minOccurs="0" name="GroupIds" nillable="true" type="q10:ReadOnlyCollectionOfint" />
</xs:sequence>
</xs:extension>
</xs:complexContent>
</xs:complexType>
<xs:element name="SharePointUser" nillable="true" type="tns:SharePointUser" />
<xs:complexType name="SharePointPrincipal">
<xs:sequence>
<xs:element minOccurs="0" name="Id" type="xs:int" />
<xs:element minOccurs="0" name="LoginName" nillable="true" type="xs:string" />
<xs:element minOccurs="0" name="PrincipalType"
type="tns:SharePointPrincipalType" />
<xs:element minOccurs="0" name="Title" nillable="true" type="xs:string" />
</xs:sequence>
</xs:complexType>
<xs:element name="SharePointPrincipal" nillable="true"
type="tns:SharePointPrincipal" />
<xs:simpleType name="SharePointPrincipalType">
<xs:list>
<xs:simpleType>

```

```

<xs:restriction base="xs:string">
    <xs:enumeration value="None">
        <xs:annotation>
            <xs:appinfo>
                <EnumerationValue
                    xmlns="http://schemas.microsoft.com/2003/10/Serialization/">0</EnumerationValue>
            </xs:appinfo>
        </xs:annotation>
    </xs:enumeration>
    <xs:enumeration value="User">
        <xs:annotation>
            <xs:appinfo>
                <EnumerationValue
                    xmlns="http://schemas.microsoft.com/2003/10/Serialization/">1</EnumerationValue>
            </xs:appinfo>
        </xs:annotation>
    </xs:enumeration>
    <xs:enumeration value="DistributionList">
        <xs:annotation>
            <xs:appinfo>
                <EnumerationValue
                    xmlns="http://schemas.microsoft.com/2003/10/Serialization/">2</EnumerationValue>
            </xs:appinfo>
        </xs:annotation>
    </xs:enumeration>
    <xs:enumeration value="SecurityGroup">
        <xs:annotation>
            <xs:appinfo>
                <EnumerationValue
                    xmlns="http://schemas.microsoft.com/2003/10/Serialization/">4</EnumerationValue>
            </xs:appinfo>
        </xs:annotation>
    </xs:enumeration>
    <xs:enumeration value="SharePointGroup">
        <xs:annotation>
            <xs:appinfo>
                <EnumerationValue
                    xmlns="http://schemas.microsoft.com/2003/10/Serialization/">8</EnumerationValue>
            </xs:appinfo>
        </xs:annotation>
    </xs:enumeration>
    </xs:restriction>
</xs:simpleType>
</xs:list>
</xs:simpleType>
<xs:element name="SharePointPrincipalType" nillable="true"
type="tns:SharePointPrincipalType" />
<xs:complexType name="SharePointSiteCollection">
    <xs:sequence>
        <xs:element minOccurs="0" name="Id" type="ser:guid" />
        <xs:element
            xmlns:q11="http://schemas.datacontract.org/2004/07/System.Collections.ObjectModel"
minOccurs="0" name="RoleDefinitions" nillable="true"
type="q11:ReadOnlyCollectionOfSharePointRoleDefinitiong8jlx19J" />
            <xs:element minOccurs="0" name="RootSiteUri" nillable="true" type="xs:anyURI" />
            <xs:element
                xmlns:q12="http://schemas.datacontract.org/2004/07/System.Collections.ObjectModel"
minOccurs="0" name="SiteGroups" nillable="true"
type="q12:ReadOnlyCollectionOfSharePointGroupg8jlx19J" />
                <xs:element
                    xmlns:q13="http://schemas.datacontract.org/2004/07/System.Collections.ObjectModel"
minOccurs="0" name="SiteUsers" nillable="true"
type="q13:ReadOnlyCollectionOfSharePointUserg8jlx19J" />
                    <xs:element minOccurs="0" name="Storage" type="xs:long" />
                    <xs:element minOccurs="0" name="StoragePercentageUsed" type="xs:double" />
                </xs:sequence>
            </xs:complexType>
        <xs:element name="SharePointSiteCollection" nillable="true"
type="tns:SharePointSiteCollection" />

```

```

<xs:complexType name="ArrayOfSharePointRoleDefinition">
    <xs:sequence>
        <xs:element minOccurs="0" maxOccurs="unbounded" name="SharePointRoleDefinition"
nillable="true" type="tns:SharePointRoleDefinition" />
    </xs:sequence>
</xs:complexType>
<xs:element name="ArrayOfSharePointRoleDefinition" nillable="true"
type="tns:ArrayOfSharePointRoleDefinition" />
    <xs:complexType name="SharePointRoleDefinition">
        <xs:sequence>
            <xs:element minOccurs="0" name="Id" type="xs:int" />
            <xs:element minOccurs="0" name="Name" nillable="true" type="xs:string" />
            <xs:element minOccurs="0" name="RoleTypeKind" type="tns:SharePointRoleType" />
        </xs:sequence>
</xs:complexType>
<xs:element name="SharePointRoleDefinition" nillable="true"
type="tns:SharePointRoleDefinition" />
    <xs:simpleType name="SharePointRoleType">
        <xs:restriction base="xs:string">
            <xs:enumeration value="None" />
            <xs:enumeration value="Guest" />
            <xs:enumeration value="Reader" />
            <xs:enumeration value="Contributor" />
            <xs:enumeration value="WebDesigner" />
            <xs:enumeration value="Administrator" />
            <xs:enumeration value="Editor" />
        </xs:restriction>
    </xs:simpleType>
<xs:element name="SharePointRoleType" nillable="true" type="tns:SharePointRoleType"
/>
<xs:complexType name="ArrayOfSharePointGroup">
    <xs:sequence>
        <xs:element minOccurs="0" maxOccurs="unbounded" name="SharePointGroup"
nillable="true" type="tns:SharePointGroup" />
    </xs:sequence>
</xs:complexType>
<xs:element name="ArrayOfSharePointGroup" nillable="true"
type="tns:ArrayOfSharePointGroup" />
    <xs:complexType name="SharePointGroup">
        <xs:complexContent mixed="false">
            <xs:extension base="tns:SharePointPrincipal">
                <xs:sequence>
                    <xs:element
xmlns:q14="http://schemas.datacontract.org/2004/07/System.Collections.ObjectModel"
minOccurs="0" name="UserIds" nillable="true" type="q14:ReadOnlyCollectionofint" />
                </xs:sequence>
            </xs:extension>
        </xs:complexContent>
    </xs:complexType>
<xs:element name="SharePointGroup" nillable="true" type="tns:SharePointGroup" />
<xs:complexType name="ArrayOfSharePointUser">
    <xs:sequence>
        <xs:element minOccurs="0" maxOccurs="unbounded" name="SharePointUser"
nillable="true" type="tns:SharePointUser" />
    </xs:sequence>
</xs:complexType>
<xs:element name="ArrayOfSharePointUser" nillable="true"
type="tns:ArrayOfSharePointUser" />
    <xs:complexType name="SharePointSite">
        <xs:complexContent mixed="false">
            <xs:extension base="tns:SharePointSecurableObject">
                <xs:sequence>
                    <xs:element minOccurs="0" name="Description" nillable="true"
type="xs:string" />
                    <xs:element minOccurs="0" name="Id" type="ser:guid" />
                    <xs:element
xmlns:q15="http://schemas.datacontract.org/2004/07/System.Collections.ObjectModel"
minOccurs="0" name="SubSitesRelativeUri" nillable="true"
type="q15:ReadOnlyCollectionofanyURI" />
                </xs:sequence>
            </xs:extension>
        </xs:complexContent>
    </xs:complexType>

```

```

        <xs:element minOccurs="0" name="Title" nillable="true" type="xs:string" />
        <xs:element minOccurs="0" name="Uri" nillable="true" type="xs:anyURI" />
    </xs:sequence>
</xs:extension>
</xs:complexContent>
</xs:complexType>
<xs:element name="SharePointSite" nillable="true" type="tns:SharePointSite" />
<xs:complexType name="SharePointSecurableObject">
    <xs:sequence>
        <xs:element minOccurs="0" name="HasUniqueRoleAssignments" type="xs:boolean" />
        <xs:element
xmlns:q16="http://schemas.datacontract.org/2004/07/System.Collections.ObjectModel"
minOccurs="0" name="RoleAssignments" nillable="true"
type="q16:ReadOnlyCollectionOfSharePointRoleAssignmentg8jlx19J" />
    </xs:sequence>
</xs:complexType>
<xs:element name="SharePointSecurableObject" nillable="true"
type="tns:SharePointSecurableObject" />
<xs:complexType name="ArrayOfSharePointRoleAssignment">
    <xs:sequence>
        <xs:element minOccurs="0" maxOccurs="unbounded" name="SharePointRoleAssignment"
nillable="true" type="tns:SharePointRoleAssignment" />
    </xs:sequence>
</xs:complexType>
<xs:element name="ArrayOfSharePointRoleAssignment" nillable="true"
type="tns:ArrayOfSharePointRoleAssignment" />
<xs:complexType name="SharePointRoleAssignment">
    <xs:sequence>
        <xs:element minOccurs="0" name="MemberId" type="xs:int" />
        <xs:element minOccurs="0" name="MemberType" type="tns:SharePointPrincipalType" />
    </xs:sequence>
<xs:element
xmlns:q17="http://schemas.datacontract.org/2004/07/System.Collections.ObjectModel"
minOccurs="0" name="RoleDefinitionBindings" nillable="true"
type="q17:ReadOnlyCollectionOfSharePointRoleDefinitiong8jlx19J" />
    </xs:sequence>
</xs:complexType>
<xs:element name="SharePointRoleAssignment" nillable="true"
type="tns:SharePointRoleAssignment" />
<xs:complexType name="SharePointLibrary">
    <xs:complexContent mixed="false">
        <xs:extension base="tns:SharePointSecurableObject">
            <xs:sequence>
                <xs:element minOccurs="0" name="Description" nillable="true"
type="xs:string" />
                <xs:element minOccurs="0" name="EnableVersioning" type="xs:boolean" />
                <xs:element minOccurs="0" name="ForceCheckout" type="xs:boolean" />
                <xs:element minOccurs="0" name="Id" type="ser:guid" />
                <xs:element minOccurs="0" name="LibraryType"
type="tns:SharePointLibraryType" />
                <xs:element minOccurs="0" name="ParentSiteUri" nillable="true"
type="xs:anyURI" />
                <xs:element minOccurs="0" name="RelativeUri" nillable="true"
type="xs:anyURI" />
                <xs:element minOccurs="0" name="Title" nillable="true" type="xs:string" />
            </xs:sequence>
        </xs:extension>
    </xs:complexContent>
</xs:complexType>
<xs:element name="SharePointLibrary" nillable="true" type="tns:SharePointLibrary" />
<xs:simpleType name="SharePointLibraryType">
    <xs:restriction base="xs:string">
        <xs:enumeration value="InvalidType">
            <xs:annotation>
                <xs:appinfo>
                    <EnumerationValue
xmlns="http://schemas.microsoft.com/2003/10/Serialization/">-1</EnumerationValue>
                </xs:appinfo>
            </xs:annotation>

```

```

        </xs:enumeration>
    <xs:enumeration value="NoListTemplate">
        <xs:annotation>
            <xs:appinfo>
                <EnumerationValue
        xmlns="http://schemas.microsoft.com/2003/10/Serialization/">0</EnumerationValue>
            </xs:appinfo>
        </xs:annotation>
    </xs:enumeration>
    <xs:enumeration value="DocumentLibrary">
        <xs:annotation>
            <xs:appinfo>
                <EnumerationValue
        xmlns="http://schemas.microsoft.com/2003/10/Serialization/">101</EnumerationValue>
            </xs:appinfo>
        </xs:annotation>
    </xs:enumeration>
    <xs:enumeration value="PictureLibrary">
        <xs:annotation>
            <xs:appinfo>
                <EnumerationValue
        xmlns="http://schemas.microsoft.com/2003/10/Serialization/">109</EnumerationValue>
            </xs:appinfo>
        </xs:annotation>
    </xs:enumeration>
    <xs:enumeration value="WebPageLibrary">
        <xs:annotation>
            <xs:appinfo>
                <EnumerationValue
        xmlns="http://schemas.microsoft.com/2003/10/Serialization/">119</EnumerationValue>
            </xs:appinfo>
        </xs:annotation>
    </xs:enumeration>
    </xs:restriction>
</xs:simpleType>
<xs:element name="SharePointLibraryType" nillable="true"
type="tns:SharePointLibraryType" />
<xs:complexType name="ArrayOfSharePointLibrary">
    <xs:sequence>
        <xs:element minOccurs="0" maxOccurs="unbounded" name="SharePointLibrary"
nillable="true" type="tns:SharePointLibrary" />
    </xs:sequence>
</xs:complexType>
<xs:element name="ArrayOfSharePointLibrary" nillable="true"
type="tns:ArrayOfSharePointLibrary" />
<xs:complexType name="SharePointException">
    <xs:complexContent mixed="false">
        <xs:extension xmlns:q18="http://schemas.datacontract.org/2004/07/System"
base="q18:Exception" />
    </xs:complexContent>
</xs:complexType>
<xs:element name="SharePointException" nillable="true"
type="tns:SharePointException" />
<xs:simpleType name="SharePointFault">
    <xs:restriction base="xs:string">
        <xs:enumeration value="Unexpected" />
        <xs:enumeration value="SPOServerNotFound" />
        <xs:enumeration value="SPOUnauthorized" />
        <xs:enumeration value="SPOClientRequestFailed" />
        <xs:enumeration value="SPOInvalidQuery" />
        <xs:enumeration value="SPOServerOperationFailed" />
    </xs:restriction>
</xs:simpleType>
<xs:element name="SharePointFault" nillable="true" type="tns:SharePointFault" />
<xs:complexType name="MSOSecurityGroup">
    <xs:complexContent mixed="false">
        <xs:extension base="tns:MSOSecurityIdentity">
            <xs:sequence>

```

```

            <xs:element minOccurs="0" name="Description" nillable="true"
type="xs:string" />
            <xs:element minOccurs="0" name="LocalGroupName" nillable="true"
type="xs:string" />
        </xs:sequence>
    </xs:extension>
</xs:complexContent>
</xs:complexType>
<xs:element name="MSOSecurityGroup" nillable="true" type="tns:MSOSecurityGroup" />
<xs:complexType name="MSOSecurityIdentity">
    <xs:sequence>
        <xs:element minOccurs="0" name="DisplayName" nillable="true" type="xs:string" />
        <xs:element minOccurs="0" name="ObjectId" type="ser:guid" />
        <xs:element minOccurs="0" name="PrincipleName" nillable="true" type="xs:string"
/>
    </xs:sequence>
</xs:complexType>
<xs:element name="MSOSecurityIdentity" nillable="true"
type="tns:MSOSecurityIdentity" />
<xs:complexType name="ArrayOfMSOSecurityGroup">
    <xs:sequence>
        <xs:element minOccurs="0" maxOccurs="unbounded" name="MSOSecurityGroup"
nillable="true" type="tns:MSOSecurityGroup" />
    </xs:sequence>
</xs:complexType>
<xs:element name="ArrayOfMSOSecurityGroup" nillable="true"
type="tns:ArrayOfMSOSecurityGroup" />
<xs:complexType name="SharePointSiteAddressCollection">
    <xs:sequence>
        <xs:element minOccurs="0" name="MySiteAddress" nillable="true" type="xs:string"
/>
        <xs:element minOccurs="0" name="TeamSiteAddress" nillable="true"
type="xs:string" />
    </xs:sequence>
</xs:complexType>
<xs:element name="SharePointSiteAddressCollection" nillable="true"
type="tns:SharePointSiteAddressCollection" />
<xs:simpleType name="MobileDeviceExtraInfoType">
    <xs:restriction base="xs:string">
        <xs:enumeration value="DeviceFamily" />
        <xs:enumeration value="DeviceModel" />
    </xs:restriction>
</xs:simpleType>
<xs:element name="MobileDeviceExtraInfoType" nillable="true"
type="tns:MobileDeviceExtraInfoType" />
<xs:complexType name="O365UserUpdatedEventArgs">
    <xs:complexContent mixed="false">
        <xs:extension xmlns:q19="http://schemas.datacontract.org/2004/07/System"
base="q19EventArgs">
            <xs:sequence>
                <xs:element minOccurs="0" name="IsMappingChanged" type="xs:boolean" />
                <xs:element minOccurs="0" name="User" nillable="true" type="tns:O365User" />
            </xs:sequence>
        </xs:extension>
    </xs:complexContent>
</xs:complexType>
<xs:element name="O365UserUpdatedEventArgs" nillable="true"
type="tns:O365UserUpdatedEventArgs" />
<xs:complexType name="O365InformationUpdatedEventArgs">
    <xs:complexContent mixed="false">
        <xs:extension xmlns:q20="http://schemas.datacontract.org/2004/07/System"
base="q20EventArgs">
            <xs:sequence>
                <xs:element minOccurs="0" name="Information" nillable="true"
type="tns:O365Information" />
            </xs:sequence>
        </xs:extension>
    </xs:complexContent>
</xs:complexType>
</xs:complexType>

```

```

<xs:element name="O365InformationUpdatedEventArgs" nillable="true"
type="tns:O365InformationUpdatedEventArgs" />
<xs:complexType name="O365DomainConfigurationUpdateEventArgs">
<xs:complexContent mixed="false">
<xs:extension xmlns:q21="http://schemas.datacontract.org/2004/07/System"
base="q21EventArgs">
<xs:sequence>
<xs:element minOccurs="0" name="DomainConfiguration" nillable="true"
type="tns:O365DomainConfiguration" />
</xs:sequence>
</xs:extension>
</xs:complexContent>
</xs:complexType>
<xs:element name="O365DomainConfigurationUpdateEventArgs" nillable="true"
type="tns:O365DomainConfigurationUpdateEventArgs" />
<xs:complexType name="ExchangeGroupInfoUpdatedEventArgs">
<xs:complexContent mixed="false">
<xs:extension xmlns:q22="http://schemas.datacontract.org/2004/07/System"
base="q22EventArgs">
<xs:sequence>
<xs:element minOccurs="0" name="DistrGroups" nillable="true"
type="tns:ArrayOfExchangeDistrGroup" />
<xs:element minOccurs="0" name="GroupUsers" nillable="true"
type="tns:ArrayOfExchangeGroupUser" />
<xs:element minOccurs="0" name="O365Users" nillable="true"
type="tns:ArrayOfO365User" />
</xs:sequence>
</xs:extension>
</xs:complexContent>
</xs:complexType>
<xs:element name="ExchangeGroupInfoUpdatedEventArgs" nillable="true"
type="tns:ExchangeGroupInfoUpdatedEventArgs" />
<xs:complexType name="MSOSecurityGroupUpdatedEventArgs">
<xs:complexContent mixed="false">
<xs:extension xmlns:q23="http://schemas.datacontract.org/2004/07/System"
base="q23EventArgs">
<xs:sequence>
<xs:element minOccurs="0" name="Group" nillable="true"
type="tns:MSOSecurityGroup" />
</xs:sequence>
</xs:extension>
</xs:complexContent>
</xs:complexType>
<xs:element name="MSOSecurityGroupUpdatedEventArgs" nillable="true"
type="tns:MSOSecurityGroupUpdatedEventArgs" />
<xs:complexType name="SharePointSiteUpdatedEventArgs">
<xs:complexContent mixed="false">
<xs:extension xmlns:q24="http://schemas.datacontract.org/2004/07/System"
base="q24EventArgs">
<xs:sequence>
<xs:element minOccurs="0" name="Site" nillable="true"
type="tns:SharePointSite" />
</xs:sequence>
</xs:extension>
</xs:complexContent>
</xs:complexType>
<xs:element name="SharePointSiteUpdatedEventArgs" nillable="true"
type="tns:SharePointSiteUpdatedEventArgs" />
<xs:complexType name="SharePointLibraryAddedEventArgs">
<xs:complexContent mixed="false">
<xs:extension xmlns:q25="http://schemas.datacontract.org/2004/07/System"
base="q25EventArgs">
<xs:sequence>
<xs:element minOccurs="0" name="Library" nillable="true"
type="tns:SharePointLibrary" />
</xs:sequence>
</xs:extension>
</xs:complexContent>
</xs:complexType>

```

```

<xs:element name="SharePointLibraryAddedEventArgs" nillable="true"
type="tns:SharePointLibraryAddedEventArgs" />
<xs:complexType name="SharePointLibraryRemovedEventArgs">
<xs:complexContent mixed="false">
<xs:extension xmlns:q26="http://schemas.datacontract.org/2004/07/System"
base="q26EventArgs">
<xs:sequence>
<xs:element minOccurs="0" name="Library" nillable="true"
type="tns:SharePointLibrary" />
</xs:sequence>
</xs:extension>
</xs:complexContent>
</xs:complexType>
<xs:element name="SharePointLibraryRemovedEventArgs" nillable="true"
type="tns:SharePointLibraryRemovedEventArgs" />
<xs:complexType name="SharePointLibraryUpdatedEventArgs">
<xs:complexContent mixed="false">
<xs:extension xmlns:q27="http://schemas.datacontract.org/2004/07/System"
base="q27EventArgs">
<xs:sequence>
<xs:element minOccurs="0" name="Library" nillable="true"
type="tns:SharePointLibrary" />
</xs:sequence>
</xs:extension>
</xs:complexContent>
</xs:complexType>
<xs:element name="SharePointLibraryUpdatedEventArgs" nillable="true"
type="tns:SharePointLibraryUpdatedEventArgs" />
</xs:schema>

```

6.10.2.7 http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.RemoteAccess.Domains

```

<?xml version="1.0" encoding="utf-8"?>
<xs:schema xmlns:ser="http://schemas.microsoft.com/2003/10/Serialization/"
xmlns:tns="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.RemoteA
ccess.Domains" elementFormDefault="qualified"
targetNamespace="http://schemas.datacontract.org/2004/07/Microsoft.WindowsServerSolutions.R
emoteAccess.Domains" xmlns:xs="http://www.w3.org/2001/XMLSchema">
<xs:import schemaLocation="" namespace="http://schemas.microsoft.com/2003/10/Serialization/" />
<xs:import schemaLocation="" namespace="http://schemas.datacontract.org/2004/07/System.Net" />
<xs:complexType name="DnsRecord">
<xs:sequence>
<xs:element minOccurs="0" name="Label" nillable="true" type="xs:string" />
<xs:element minOccurs="0" name="TimeToLive" type="ser:duration" />
</xs:sequence>
</xs:complexType>
<xs:element name="DnsRecord" nillable="true" type="tns:DnsRecord" />
<xs:complexType name="ARecord">
<xs:complexContent mixed="false">
<xs:extension base="tns:DnsRecord">
<xs:sequence>
<xs:element xmlns:q1="http://schemas.datacontract.org/2004/07/System.Net"
minOccurs="0" name="Address" nillable="true" type="q1:IPAddress" />
</xs:sequence>
</xs:extension>
</xs:complexContent>
</xs:complexType>
<xs:element name="ARecord" nillable="true" type="tns:ARecord" />
<xs:complexType name="MXRecord">
<xs:complexContent mixed="false">
<xs:extension base="tns:DnsRecord">
<xs:sequence>
<xs:element minOccurs="0" name="MailExchange" nillable="true"
type="xs:string" />

```

```

        <xs:element minOccurs="0" name="MailExchangePreference" type="xs:int" />
    </xs:sequence>
</xs:extension>
</xs:complexContent>
</xs:complexType>
<xs:element name="MXRecord" nillable="true" type="tns:MXRecord" />
<xs:complexType name="SrvRecord">
<xs:complexContent mixed="false">
    <xs:extension base="tns:DnsRecord">
        <xs:sequence>
            <xs:element minOccurs="0" name="Port" type="xs:int" />
            <xs:element minOccurs="0" name="Priority" type="xs:int" />
            <xs:element minOccurs="0" name="Protocol" nillable="true" type="xs:string"
/>
            <xs:element minOccurs="0" name="Service" nillable="true" type="xs:string" />
            <xs:element minOccurs="0" name="Target" nillable="true" type="xs:string" />
            <xs:element minOccurs="0" name="Weight" type="xs:int" />
        </xs:sequence>
    </xs:extension>
</xs:complexContent>
</xs:complexType>
<xs:element name="SrvRecord" nillable="true" type="tns:SrvRecord" />
<xs:complexType name="TxtRecord">
<xs:complexContent mixed="false">
    <xs:extension base="tns:DnsRecord">
        <xs:sequence>
            <xs:element minOccurs="0" name="Text" nillable="true" type="xs:string" />
        </xs:sequence>
    </xs:extension>
</xs:complexContent>
</xs:complexType>
<xs:element name="TxtRecord" nillable="true" type="tns:TxtRecord" />
<xs:complexType name="CNameRecord">
<xs:complexContent mixed="false">
    <xs:extension base="tns:DnsRecord">
        <xs:sequence>
            <xs:element minOccurs="0" name="CanonicalName" nillable="true"
type="xs:string" />
        </xs:sequence>
    </xs:extension>
</xs:complexContent>
</xs:complexType>
<xs:element name="CNameRecord" nillable="true" type="tns:CNameRecord" />
<xs:complexType name="ArrayOfDnsRecord">
<xs:sequence>
    <xs:element minOccurs="0" maxOccurs="unbounded" name="DnsRecord" nillable="true"
type="tns:DnsRecord" />
</xs:sequence>
</xs:complexType>
<xs:element name="ArrayOfDnsRecord" nillable="true" type="tns:ArrayOfDnsRecord" />
</xs:schema>

```

6.10.2.8 <http://schemas.microsoft.com/2003/10/Serialization/Arrays>

```

<?xml version="1.0" encoding="utf-8"?>
<xs:schema xmlns:ser="http://schemas.microsoft.com/2003/10/Serialization/"
xmlns:tns="http://schemas.microsoft.com/2003/10/Serialization/Arrays"
elementFormDefault="qualified"
targetNamespace="http://schemas.microsoft.com/2003/10/Serialization/Arrays"
xmlns:xs="http://www.w3.org/2001/XMLSchema">
    <xs:import schemaLocation=""
namespace="http://schemas.microsoft.com/2003/10/Serialization/" />
    <xs:complexType name="ArrayOfstring">
        <xs:sequence>
            <xs:element minOccurs="0" maxOccurs="unbounded" name="string" nillable="true"
type="xs:string" />
        </xs:sequence>
    </xs:complexType>
</xs:schema>

```

```

</xs:complexType>
<xs:element name="ArrayOfstring" nillable="true" type="tns:ArrayOfstring" />
<xs:complexType name="ArrayOfunsignedShort">
    <xs:sequence>
        <xs:element minOccurs="0" maxOccurs="unbounded" name="unsignedShort"
type="xs:unsignedShort" />
    </xs:sequence>
</xs:complexType>
<xs:element name="ArrayOfunsignedShort" nillable="true"
type="tns:ArrayOfunsignedShort" />
<xs:complexType name="ArrayOfguid">
    <xs:sequence>
        <xs:element minOccurs="0" maxOccurs="unbounded" name="guid" type="ser:guid" />
    </xs:sequence>
</xs:complexType>
<xs:element name="ArrayOfguid" nillable="true" type="tns:ArrayOfguid" />
<xs:complexType name="ArrayOfint">
    <xs:sequence>
        <xs:element minOccurs="0" maxOccurs="unbounded" name="int" type="xs:int" />
    </xs:sequence>
</xs:complexType>
<xs:element name="ArrayOfint" nillable="true" type="tns:ArrayOfint" />
<xs:complexType name="ArrayOfanyURI">
    <xs:sequence>
        <xs:element minOccurs="0" maxOccurs="unbounded" name="anyURI" nillable="true"
type="xs:anyURI" />
    </xs:sequence>
</xs:complexType>
<xs:element name="ArrayOfanyURI" nillable="true" type="tns:ArrayOfanyURI" />
</xs:schema>

```

6.10.2.9 <http://schemas.datacontract.org/2004/07/System.Net>

```

<?xml version="1.0" encoding="utf-8"?>
<xs:schema xmlns:tns="http://schemas.datacontract.org/2004/07/System.Net"
elementFormDefault="qualified"
targetNamespace="http://schemas.datacontract.org/2004/07/System.Net"
xmlns:xs="http://www.w3.org/2001/XMLSchema">
    <xs:import schemaLocation="" namespace="http://schemas.datacontract.org/2004/07/System.Net.Sockets" />
    <xs:import schemaLocation="" namespace="http://schemas.microsoft.com/2003/10/Serialization/Arrays" />
    <xs:complexType name="IPAddress">
        <xs:sequence>
            <xs:element name="m_Address" type="xs:long" />
            <xs:element
type="q1:AddressFamily" name="m_Family" />
            <xs:element name="m_HashCode" type="xs:int" />
            <xs:element
name="m_Numbers" nillable="true" type="q2:ArrayOfunsignedShort" />
            <xs:element name="m_ScopeId" type="xs:long" />
        </xs:sequence>
    </xs:complexType>
    <xs:element name="IPAddress" nillable="true" type="tns:IPAddress" />
</xs:schema>

```

6.10.2.10 <http://schemas.datacontract.org/2004/07/System.ServiceModel.Security>

```

<?xml version="1.0" encoding="utf-8"?>
<xs:schema
xmlns:tns="http://schemas.datacontract.org/2004/07/System.ServiceModel.Security"
elementFormDefault="qualified"

```

```

targetNamespace="http://schemas.datacontract.org/2004/07/System.ServiceModel.Security"
xmlns:xs="http://www.w3.org/2001/XMLSchema">
    <xs:import schemaLocation="" namespace="http://schemas.datacontract.org/2004/07/System.ServiceModel" />
        <xs:complexType name="SecurityAccessDeniedException">
            <xs:complexContent mixed="false">
                <xs:extension
        xmlns:q1="http://schemas.datacontract.org/2004/07/System.ServiceModel"
        base="q1:CommunicationException" />
            </xs:complexContent>
        </xs:complexType>
        <xs:element name="SecurityAccessDeniedException" nillable="true" type="tns:SecurityAccessDeniedException" />
</xs:schema>

```

6.10.2.11 http://schemas.datacontract.org/2004/07/System.ServiceModel

```

<?xml version="1.0" encoding="utf-8"?>
<xs:schema xmlns:tns="http://schemas.datacontract.org/2004/07/System.ServiceModel" elementFormDefault="qualified"
targetNamespace="http://schemas.datacontract.org/2004/07/System.ServiceModel"
xmlns:xs="http://www.w3.org/2001/XMLSchema">
    <xs:import schemaLocation="" namespace="http://schemas.datacontract.org/2004/07/System" />
        <xs:complexType name="CommunicationException">
            <xs:complexContent mixed="false">
                <xs:extension xmlns:q1="http://schemas.datacontract.org/2004/07/System"
        base="q1:SystemException" />
            </xs:complexContent>
        </xs:complexType>
        <xs:element name="CommunicationException" nillable="true" type="tns:CommunicationException" />
</xs:schema>

```

6.10.2.12 http://schemas.datacontract.org/2004/07/System

```

<?xml version="1.0" encoding="utf-8"?>
<xs:schema xmlns:ser="http://schemas.microsoft.com/2003/10/Serialization/" xmlns:tns="http://schemas.datacontract.org/2004/07/System" elementFormDefault="qualified"
targetNamespace="http://schemas.datacontract.org/2004/07/System"
xmlns:xs="http://www.w3.org/2001/XMLSchema">
    <xs:import schemaLocation="" namespace="http://schemas.microsoft.com/2003/10/Serialization/" />
        <xs:complexType name="Exception">
            <xs:sequence>
                <xs:any minOccurs="0" maxOccurs="unbounded" namespace="##local" processContents="skip" />
            </xs:sequence>
            <xs:attribute ref="ser:FactoryType" />
        </xs:complexType>
        <xs:element name="Exception" nillable="true" type="tns:Exception" />
        <xs:complexType name="SystemException">
            <xs:complexContent mixed="false">
                <xs:extension base="tns:Exception" />
            </xs:complexContent>
        </xs:complexType>
        <xs:element name="SystemException" nillable="true" type="tns:SystemException" />
        <xs:complexType name="EventArgs">
            <xs:sequence />
        </xs:complexType>
        <xs:element name="EventArgs" nillable="true" type="tns:EventArgs" />
</xs:schema>

```

6.11 Client Notification Service WSDL

6.11.1 wsdl

```
<?xml version="1.0" encoding="utf-8"?>
<wsdl:definitions xmlns:wsap="http://schemas.xmlsoap.org/ws/2004/08/addressing/policy"
xmlns:wsa10="http://www.w3.org/2005/08/addressing" xmlns:tns="http://tempuri.org/"
xmlns:msc="http://schemas.microsoft.com/ws/2005/12/wsdl/contract"
xmlns:soapenc="http://schemas.xmlsoap.org/soap/encoding/"
xmlns:soap="http://schemas.xmlsoap.org/wsdl/soap/"
xmlns:wsp="http://schemas.xmlsoap.org/ws/2004/09/policy"
xmlns:wsam="http://www.w3.org/2007/05/addressing/metadata"
xmlns:wsaa="http://schemas.xmlsoap.org/ws/2004/08/addressing"
xmlns:wsaw="http://www.w3.org/2006/05/addressing/wsdl"
xmlns:soap12="http://schemas.xmlsoap.org/wsdl/soap12/" xmlns:wsu="http://docs.oasis-
open.org/wss/2004/01/oasis-200401-wss-wssecurity-utility-1.0.xsd"
xmlns:xsd="http://www.w3.org/2001/XMLSchema" name="ClientNotificationProvider"
targetNamespace="http://tempuri.org/" xmlns:wsdl="http://schemas.xmlsoap.org/wsdl/">
    <wsp:Policy wsu:Id="CustomBinding_IClientNotificationProvider_policy">
        <wsp:ExactlyOne>
            <wsp:All>
                <msb:BinaryEncoding
xmlns:msb="http://schemas.microsoft.com/ws/2004/mspolicy/netbinary1" />
                <sp:TransportBinding
xmlns:sp="http://schemas.xmlsoap.org/ws/2005/07/securitypolicy">
                    <wsp:Policy>
                        <sp:TransportToken>
                            <wsp:Policy>
                                <msf:WindowsTransportSecurity
xmlns:msf="http://schemas.microsoft.com/ws/2006/05/framing/policy">
                                    <msf:ProtectionLevel>EncryptAndSign</msf:ProtectionLevel>
                                    </msf:WindowsTransportSecurity>
                                </wsp:Policy>
                            </sp:TransportToken>
                            <sp:AlgorithmSuite>
                                <wsp:Policy>
                                    <sp:Basic256 />
                                </wsp:Policy>
                            </sp:AlgorithmSuite>
                            <sp:Layout>
                                <wsp:Policy>
                                    <sp:Strict />
                                </wsp:Policy>
                            </sp:Layout>
                            <wsp:Policy>
                                <sp:TransportBinding>
                                    <wsaw:UsingAddressing />
                                </wsp:All>
                            </wsp:ExactlyOne>
                        </wsp:Policy>
                    </wsp:types>
                    <xsd:schema targetNamespace="http://tempuri.org/Imports">
                        <xsd:import schemaLocation="" namespace="http://tempuri.org/" />
                        <xsd:import schemaLocation="" namespace="http://schemas.datacontract.org/2004/07/System" />
                        <xsd:import schemaLocation="" namespace="http://schemas.microsoft.com/2003/10/Serialization/" />
                    </xsd:schema>
                </wsdl:types>
                <wsdl:message name="IClientNotificationProvider_NotifyClientByName_InputMessage">
                    <wsdl:part name="parameters" element="tns:NotifyClientByName" />
                </wsdl:message>
                <wsdl:message name="IClientNotificationProvider_NotifyClientByName_OutputMessage">
                    <wsdl:part name="parameters" element="tns:NotifyClientByNameResponse" />
                </wsdl:message>
                <wsdl:message name="IClientNotificationProvider_NotifyClientByName_InvalidOperationExceptionFault_FaultMe-
ssage">
```

```

        <wsdl:part xmlns:q1="http://schemas.datacontract.org/2004/07/System" name="detail"
element="q1:InvalidOperationException" />
    </wsdl:message>
    <wsdl:message name="IClientNotificationProvider_NotifyClientById_InputMessage">
        <wsdl:part name="parameters" element="tns:NotifyClientById" />
    </wsdl:message>
    <wsdl:message name="IClientNotificationProvider_NotifyClientById_OutputMessage">
        <wsdl:part name="parameters" element="tns:NotifyClientByIdResponse" />
    </wsdl:message>
    <wsdl:message name="IClientNotificationProvider_NotifyAllClients_InputMessage">
        <wsdl:part name="parameters" element="tns:NotifyAllClients" />
    </wsdl:message>
    <wsdl:message name="IClientNotificationProvider_NotifyAllClients_OutputMessage">
        <wsdl:part name="parameters" element="tns:NotifyAllClientsResponse" />
    </wsdl:message>
<wsdl:portType name="IClientNotificationProvider">
    <wsdl:operation name="NotifyClientByName">
        <wsdl:input
wsaw:Action="http://tempuri.org/IClientNotificationProvider/NotifyClientByName"
message="tns:IClientNotificationProvider_NotifyClientByName_InputMessage" />
        <wsdl:output
wsaw:Action="http://tempuri.org/IClientNotificationProvider/NotifyClientByNameResponse"
message="tns:IClientNotificationProvider_NotifyClientByName_OutputMessage" />
        <wsdl:fault
wsaw:Action="http://tempuri.org/IClientNotificationProvider/NotifyClientByNameInvalidOperationFault"
name="InvalidOperationExceptionFault"
message="tns:IClientNotificationProvider_NotifyClientByName_InvalidOperationExceptionFault_FaultMessage" />
    </wsdl:operation>
    <wsdl:operation name="NotifyClientById">
        <wsdl:input
wsaw:Action="http://tempuri.org/IClientNotificationProvider/NotifyClientById"
message="tns:IClientNotificationProvider_NotifyClientById_InputMessage" />
        <wsdl:output
wsaw:Action="http://tempuri.org/IClientNotificationProvider/NotifyClientByIdResponse"
message="tns:IClientNotificationProvider_NotifyClientById_OutputMessage" />
        <wsdl:operation name="NotifyAllClients">
            <wsdl:input
wsaw:Action="http://tempuri.org/IClientNotificationProvider/NotifyAllClients"
message="tns:IClientNotificationProvider_NotifyAllClients_InputMessage" />
            <wsdl:output
wsaw:Action="http://tempuri.org/IClientNotificationProvider/NotifyAllClientsResponse"
message="tns:IClientNotificationProvider_NotifyAllClients_OutputMessage" />
            <wsdl:fault
wsaw:Action="http://tempuri.org/IClientNotificationProvider/NotifyAllClientsFault"
name="InvalidOperationExceptionFault"
message="tns:IClientNotificationProvider_NotifyAllClients_InvalidOperationExceptionFault_FaultMessage" />
        </wsdl:operation>
    </wsdl:portType>
    <wsdl:binding name="CustomBinding_IClientNotificationProvider"
type="tns:IClientNotificationProvider">
        <wsp:PolicyReference URI="#CustomBinding_IClientNotificationProvider_policy" />
        <soap12:binding transport="http://schemas.microsoft.com/soap/tcp" />
        <wsdl:operation name="NotifyClientByName">
            <soap12:operation
soapAction="http://tempuri.org/IClientNotificationProvider/NotifyClientByName"
style="document" />
            <wsdl:input>
                <soap12:body use="literal" />
            </wsdl:input>
            <wsdl:output>
                <soap12:body use="literal" />
            </wsdl:output>
            <wsdl:fault name="InvalidOperationExceptionFault">
                <soap12:fault use="literal" name="InvalidOperationExceptionFault" namespace="" />
            </wsdl:fault>
        </wsdl:operation>
        <wsdl:operation name="NotifyClientById">
            <soap12:operation
soapAction="http://tempuri.org/IClientNotificationProvider/NotifyClientById"
style="document" />

```

```

<wsdl:input>
    <soap12:body use="literal" />
</wsdl:input>
<wsdl:output>
    <soap12:body use="literal" />
</wsdl:output>
</wsdl:operation>
<wsdl:operation name="NotifyAllClients">
    <soap12:operation
        soapAction="http://tempuri.org/IClientNotificationProvider/NotifyAllClients"
        style="document" />
    <wsdl:input>
        <soap12:body use="literal" />
    </wsdl:input>
    <wsdl:output>
        <soap12:body use="literal" />
    </wsdl:output>
    </wsdl:operation>
</wsdl:binding>
<wsdl:service name="ClientNotificationProvider">
    <wsdl:port name="CustomBinding_IClientNotificationProvider"
        binding="tns:CustomBinding_IClientNotificationProvider">
        <soap12:address
            location="net.tcp://localhost:65532/Microsoft.WindowsServerSolutions.ClientNotificationProvider/Microsoft.WindowsServerSolutions.Client.Notification.IClientNotificationProvider" />
        <wsa10:EndpointReference>

<wsa10:Address>net.tcp://localhost:65532/Microsoft.WindowsServerSolutions.ClientNotificationProvider/Microsoft.WindowsServerSolutions.Client.Notification.IClientNotificationProvider</wsa10:Address>
        <Identity xmlns="http://schemas.xmlsoap.org/ws/2006/02/addressingidentity">
            <Spn>host/serverName.domain</Spn>
        </Identity>
    </wsa10:EndpointReference>
</wsdl:port>
</wsdl:service>
</wsdl:definitions>

```

6.11.2 http://tempuri.org

```

<?xml version="1.0" encoding="utf-8"?>
<xss:schema xmlns:tns="http://tempuri.org/" elementFormDefault="qualified"
targetNamespace="http://tempuri.org/" xmlns:xs="http://www.w3.org/2001/XMLSchema">
    <xss:import schemaLocation="" />
    <xs:namespace="http://schemas.datacontract.org/2004/07/System" />
    <xs:element name="NotifyClientByName">
        <xs:complexType>
            <xs:sequence>
                <xs:element minOccurs="0" name="name" nillable="true" type="xs:string" />
                <xs:element minOccurs="0" name="messageId" type="xs:unsignedInt" />
                <xs:element minOccurs="0" name="message" nillable="true" type="xs:string" />
            </xs:sequence>
        </xs:complexType>
    </xs:element>
    <xs:element name="NotifyClientByNameResponse">
        <xs:complexType>
            <xs:sequence>
                <xs:element minOccurs="0" name="NotifyClientByNameResult" type="xs:boolean" />
            </xs:sequence>
        </xs:complexType>
    </xs:element>
    <xs:element name="NotifyClientById">
        <xs:complexType>
            <xs:sequence>
                <xs:element minOccurs="0" name="id" nillable="true" type="xs:string" />
                <xs:element minOccurs="0" name="messageId" type="xs:unsignedInt" />
                <xs:element minOccurs="0" name="message" nillable="true" type="xs:string" />
            </xs:sequence>
        </xs:complexType>
    </xs:element>

```

```

        </xs:sequence>
    </xs:complexType>
</xs:element>
<xs:element name="NotifyClientByIdResponse">
    <xs:complexType>
        <xs:sequence>
            <xs:element minOccurs="0" name="NotifyClientByIdResult" type="xs:boolean" />
        </xs:sequence>
    </xs:complexType>
</xs:element>
<xs:element name="NotifyAllClients">
    <xs:complexType>
        <xs:sequence>
            <xs:element minOccurs="0" name="messageId" type="xs:unsignedInt" />
            <xs:element minOccurs="0" name="message" nillable="true" type="xs:string" />
        </xs:sequence>
    </xs:complexType>
</xs:element>
<xs:element name="NotifyAllClientsResponse">
    <xs:complexType>
        <xs:sequence>
            <xs:element xmlns:q1="http://schemas.datacontract.org/2004/07/System"
minOccurs="0" name="NotifyAllClientsResult" nillable="true"
type="q1:ArrayOfTupleOfstringboolean" />
        </xs:sequence>
    </xs:complexType>
</xs:element>
</xs:schema>

```

6.11.3 http://schemas.microsoft.com/2003/10/Serialization

```

<?xml version="1.0" encoding="utf-8"?>
<xs:schema xmlns:tns="http://schemas.microsoft.com/2003/10/Serialization/"
attributeFormDefault="qualified" elementFormDefault="qualified"
targetNamespace="http://schemas.microsoft.com/2003/10/Serialization/"
xmlns:xs="http://www.w3.org/2001/XMLSchema">
    <xs:element name="anyType" nillable="true" type="xs:anyType" />
    <xs:element name="anyURI" nillable="true" type="xs:anyURI" />
    <xs:element name="base64Binary" nillable="true" type="xs:base64Binary" />
    <xs:element name="boolean" nillable="true" type="xs:boolean" />
    <xs:element name="byte" nillable="true" type="xs:byte" />
    <xs:element name="dateTime" nillable="true" type="xs:dateTime" />
    <xs:element name="decimal" nillable="true" type="xs:decimal" />
    <xs:element name="double" nillable="true" type="xs:double" />
    <xs:element name="float" nillable="true" type="xs:float" />
    <xs:element name="int" nillable="true" type="xs:int" />
    <xs:element name="long" nillable="true" type="xs:long" />
    <xs:element name="QName" nillable="true" type="xs:QName" />
    <xs:element name="short" nillable="true" type="xs:short" />
    <xs:element name="string" nillable="true" type="xs:string" />
    <xs:element name="unsignedByte" nillable="true" type="xs:unsignedByte" />
    <xs:element name="unsignedInt" nillable="true" type="xs:unsignedInt" />
    <xs:element name="unsignedLong" nillable="true" type="xs:unsignedLong" />
    <xs:element name="unsignedShort" nillable="true" type="xs:unsignedShort" />
    <xs:element name="char" nillable="true" type="tns:char" />
    <xs:simpleType name="char">
        <xs:restriction base="xs:int" />
    </xs:simpleType>
    <xs:element name="duration" nillable="true" type="tns:duration" />
    <xs:simpleType name="duration">
        <xs:restriction base="xs:duration">
            <xs:pattern value="-?P(\d*D)?(T(\d*H)?(\d*M)?(\d*(\.\d*)?S)?)?" />
            <xs:minInclusive value="-P10675199DT2H48M5.4775808S" />
            <xs:maxInclusive value="P10675199DT2H48M5.4775807S" />
        </xs:restriction>
    </xs:simpleType>
    <xs:element name="guid" nillable="true" type="tns:guid" />

```

```

<xs:simpleType name="guid">
    <xs:restriction base="xs:string">
        <xs:pattern value="[\da-fA-F]{8}-[\da-fA-F]{4}-[\da-fA-F]{4}-[\da-fA-F]{4}-[\da-fA-F]{12}" />
    </xs:restriction>
</xs:simpleType>
<xs:attribute name="FactoryType" type="xs:QName" />
<xs:attribute name="Id" type="xs:ID" />
<xs:attribute name="Ref" type="xs:IDREF" />
</xs:schema>

```

6.11.4 http://schemas.datacontract.org/2004/07/System

```

<?xml version="1.0" encoding="utf-8"?>
<xs:schema xmlns:ser="http://schemas.microsoft.com/2003/10/Serialization/" targetNamespace="http://schemas.datacontract.org/2004/07/System" elementFormDefault="qualified" xmlns:xs="http://www.w3.org/2001/XMLSchema">
    <xs:import schemaLocation="" namespace="http://schemas.microsoft.com/2003/10/Serialization/" />
    <xs:complexType name="InvalidOperationException">
        <xs:complexContent mixed="false">
            <xs:extension base="tns:SystemException" />
        </xs:complexContent>
    </xs:complexType>
    <xs:element name="InvalidOperationException" nillable="true" type="tns:InvalidOperationException" />
    <xs:complexType name="SystemException">
        <xs:complexContent mixed="false">
            <xs:extension base="tns:Exception" />
        </xs:complexContent>
    </xs:complexType>
    <xs:element name="SystemException" nillable="true" type="tns:SystemException" />
    <xs:complexType name="Exception">
        <xs:sequence>
            <xs:any minOccurs="0" maxOccurs="unbounded" namespace="##local" processContents="skip" />
        </xs:sequence>
        <xs:attribute ref="ser:FactoryType" />
    </xs:complexType>
    <xs:element name="Exception" nillable="true" type="tns:Exception" />
    <xs:complexType name="ArrayOfTupleOfstringboolean">
        <xs:sequence>
            <xs:element minOccurs="0" maxOccurs="unbounded" name="TupleOfstringboolean" nillable="true" type="tns:TupleOfstringboolean" />
        </xs:sequence>
    </xs:complexType>
    <xs:element name="ArrayOfTupleOfstringboolean" nillable="true" type="tns:ArrayOfTupleOfstringboolean" />
    <xs:complexType name="TupleOfstringboolean">
        <xs:annotation>
            <xs:appinfo>
                <GenericType Name="TupleOf{0}{1}{#}" Namespace="http://schemas.datacontract.org/2004/07/System" xmlns="http://schemas.microsoft.com/2003/10/Serialization/">
                    <GenericParameter Name="string" Namespace="http://www.w3.org/2001/XMLSchema" />
                </GenericType>
                <GenericParameter Name="boolean" Namespace="http://www.w3.org/2001/XMLSchema" />
            </xs:appinfo>
        </xs:annotation>
        <xs:sequence>
            <xs:element name="m_Item1" nillable="true" type="xs:string" />
            <xs:element name="m_Item2" type="xs:boolean" />
        </xs:sequence>
    </xs:complexType>

```

```
<xs:element name="TupleOfstringboolean" nillable="true"
type="tns:TupleOfstringboolean" />
</xs:schema>
```

7 Appendix B: Product Behavior

The information in this specification is applicable to the following Microsoft products or supplemental software. References to product versions include updates to those products.

The terms "earlier" and "later", when used with a product version, refer to either all preceding versions or all subsequent versions, respectively. The term "through" refers to the inclusive range of versions. Applicable Microsoft products are listed chronologically in this section.

Windows Client

- Windows 7 operating system with Service Pack 1 (SP1)
- Windows 8 operating system

Windows Server

- Windows Server 2008 R2 operating system with Service Pack 1 (SP1)
- Windows Server 2012 operating system
- Windows Server 2012 R2 operating system
- Windows Server 2016 operating system
- Windows Server 2019 operating system
- Windows Server 2022 operating system

Exceptions, if any, are noted in this section. If an update version, service pack or Knowledge Base (KB) number appears with a product name, the behavior changed in that update. The new behavior also applies to subsequent updates unless otherwise specified. If a product edition appears with the product version, behavior is different in that product edition.

Unless otherwise specified, any statement of optional behavior in this specification that is prescribed using the terms "SHOULD" or "SHOULD NOT" implies product behavior in accordance with the SHOULD or SHOULD NOT prescription. Unless otherwise specified, the term "MAY" implies that the product does not follow the prescription.

[<1> Section 2.2.4](#): Windows uses this for non-Windows client platforms.

[<2> Section 2.2.4.5.2](#): Windows uses this as the Windows SID of this user.

[<3> Section 2.2.4.5.2](#): Windows uses this as the Windows account of this user.

[<4> Section 2.2.4.7.3](#): In Windows, this contains non-Windows client binaries.

[<5> Section 2.2.4.7.6](#): Windows uses this for non-Windows client platforms.

[<6> Section 2.2.4.8.2](#): The VirtualNetworkSettings type is not available in Windows 7 SP1, Windows Server 2008 R2 SP1, Windows 8, Windows Server 2012, and Windows Server 2012 R2.

[<7> Section 2.2.4.8.3](#): The AddressPrefix type is not available in Windows 7 SP1, Windows Server 2008 R2 SP1, Windows 8, Windows Server 2012, and Windows Server 2012 R2.

[<8> Section 2.2.5.6.1](#): The implementation is defined by the platform, but could be (as an example) Windows identity.

[<9> Section 2.2.5.6.1](#): The implementation is defined by the platform, but could be (as an example) **Active Directory** (AD) machine accounts or certificates.

[<10> Section 2.2.5.10](#): AzureAD and HostedEmail Integration are not available in Windows 7 SP1, Windows Server 2008 R2 SP1, Windows 8, and Windows Server 2012.

[<11> Section 2.2.5.10.2](#): InvalidPassword is not available in Windows 7 SP1, Windows Server 2008 R2 SP1, Windows 8, and Windows Server 2012. Support for this type in Windows Server 2012 R2 requires [\[MSKB-2975719\]](#).

[<12> Section 3.2.1.2](#): In Windows, the schedule can be saved in the Windows task scheduler.

[<13> Section 3.4.5.5](#): IMachineIdentityProvider.ReturnRemoveMachine is available in Windows 7 SP1, Windows Server 2008 R2 SP1, Windows 8, and Windows Server 2012 only.

[<14> Section 3.4.5.8](#): IMachineIdentityProvider.RemoveMachine is available in Windows 7 SP1, Windows Server 2008 R2 SP1, Windows 8, and Windows Server 2012 only.

[<15> Section 3.5.1.1.1.1](#): Windows uses this as the Windows account of this user.

[<16> Section 3.5.1.1.1.1](#): Windows uses this as the Windows SID of this user.

[<17> Section 3.5.5.1](#): IUserLogonProvider.LogonUser is not available in Windows 7 SP1, Windows Server 2008 R2 SP1, Windows 8, and Windows Server 2012.

[<18> Section 3.5.5.2](#): IUserChangePasswordProvider.ChangePassword is not available in Windows 7 SP1, Windows Server 2008 R2 SP1, Windows 8, and Windows Server 2012.

[<19> Section 3.10.5](#): In Windows Server 2012 R2 and later, the IO365ClientProvider functionality is replaced by IPasswordSyncClientProvider.

[<20> Section 3.10.5.2](#): The IPasswordSyncClientProvider.RaiseOperationInvokeEvent operation is named Provider.RaiseOperationInvokeEvent in Windows Server 2012.

[<21> Section 3.10.5.3](#): In Windows Server 2012 R2 and later, IO365ClientProvider.GetSharePointAddress functionality is replaced by IPasswordSyncClientProvider.

[<22> Section 3.10.5.4](#): IO365ClientProvider.IsActivated is available in Windows 7 SP1, Windows Server 2008 R2 SP1, Windows 8, and Windows Server 2012 only.

[<23> Section 3.10.5.7](#): IO365ClientProvider.GetEmailAddress is available in Windows 7 SP1, Windows Server 2008 R2 SP1, Windows 8, and Windows Server 2012 only.

[<24> Section 3.11.1](#): Client Notification Service Contract is not available in Windows 7 SP1, Windows Server 2008 R2 SP1, Windows 8, and Windows Server 2012.

[<25> Section 5.1.2](#): In Windows, the certificate can be retrieved using Microsoft.WindowsServerSolutions.Devices.Identity.MachineIdentityManager.GetLocalMachineCert method in the Windows Server Solutions SDK. See [\[MSDN-GetLocMachCert\]](#).

8 Change Tracking

This section identifies changes that were made to this document since the last release. Changes are classified as Major, Minor, or None.

The revision class **Major** means that the technical content in the document was significantly revised. Major changes affect protocol interoperability or implementation. Examples of major changes are:

- A document revision that incorporates changes to interoperability requirements.
- A document revision that captures changes to protocol functionality.

The revision class **Minor** means that the meaning of the technical content was clarified. Minor changes do not affect protocol interoperability or implementation. Examples of minor changes are updates to clarify ambiguity at the sentence, paragraph, or table level.

The revision class **None** means that no new technical changes were introduced. Minor editorial and formatting changes may have been made, but the relevant technical content is identical to the last released version.

The changes made to this document are listed in the following table. For more information, please contact dochelp@microsoft.com.

Section	Description	Revision class
7 Appendix B: Product Behavior	Updated for this version of Windows Server.	Major

9 Index

A

Abstract data model
 [Addin management](#) 258
 [AzureAD and HostedEmail integration](#) 306
 [client backup provider](#) 109
 [client file backup provider](#) 104
 [client notification](#) 316
 [domain infrastructure](#) 288
 [health provider](#) 188
 [machine identity provider](#) 217
 [network](#) 280
 [provider registry](#) 242
 [user identity provider](#) 231
Addin management
 [abstract data model](#) 258
 [higher-layer triggered events](#) 258
 [initialization](#) 258
 [local events](#) 280
 [message processing](#) 259
 [sequencing rules](#) 259
 [timer events](#) 280
 [timers](#) 258
Applicability 33
AzureAD and HostedEmail integration
 [abstract data model](#) 306
 [higher-layer triggered events](#) 306
 [initialization](#) 306
 [local events](#) 316
 [message processing](#) 306
 [sequencing rules](#) 306
 [timer events](#) 316
 [timers](#) 306

C

Capability negotiation 33
Change tracking 577
Client backup provider
 [abstract data model](#) 109
 [higher-layer triggered events](#) 110
 [initialization](#) 110
 [local events](#) 188
 [message processing](#) 110
 [sequencing rules](#) 110
 [timer events](#) 188
 [timers](#) 110
Client file backup provider
 [abstract data model](#) 104
 [higher-layer triggered events](#) 104
 [initialization](#) 104
 [local events](#) 109
 [message processing](#) 104
 [sequencing rules](#) 104
 [timer events](#) 109
 [timers](#) 104
Client notification
 [abstract data model](#) 316
 [higher-layer triggered events](#) 316
 [initialization](#) 316
 [message processing](#) 317

[sequencing rules](#) 317
 [timers](#) 316
Complex types 37

D

Data model – abstract
 [Addin management](#) 258
 [AzureAD and HostedEmail integration](#) 306
 [client backup provider](#) 109
 [client file backup provider](#) 104
 [client notification](#) 316
 [domain infrastructure](#) 288
 [health provider](#) 188
 [machine identity provider](#) 217
 [network](#) 280
 [provider registry](#) 242
 [user identity provider](#) 231
Domain infrastructure
 [abstract data model](#) 288
 [higher-layer triggered events](#) 288
 [initialization](#) 288
 [local events](#) 306
 [message processing](#) 288
 [sequencing rules](#) 288
 [timer events](#) 306
 [timers](#) 288

E

Events
 [local - client file backup provider](#) 109
 [timer - client file backup provider](#) 109

Example
 [Get the computer backup service status](#) 324

F

Fields - vendor-extensible 34

G

Get the computer backup service status example 324
Glossary 30

H

Health provider
 [abstract data model](#) 188
 [higher-layer triggered events](#) 189
 [initialization](#) 189
 [local events](#) 217
 [message processing](#) 189
 [sequencing rules](#) 189
 [timer events](#) 216
 [timers](#) 189

Higher-layer triggered events
 [Addin management](#) 258
 [AzureAD and HostedEmail integration](#) 306
 [client backup provider](#) 110
 [client file backup provider](#) 104

[client notification](#) 316
[domain infrastructure](#) 288
[health provider](#) 189
[machine identity provider](#) 217
[network](#) 281
[provider registry](#) 242
[user identity provider](#) 232

I

[Implementer - security considerations](#) 325
[Index of security parameters](#) 325
[Informative references](#) 32
Initialization
 [Addin management](#) 258
 [AzureAD and HostedEmail integration](#) 306
 [client backup provider](#) 110
 [client file backup provider](#) 104
 [client notification](#) 316
 [domain infrastructure](#) 288
 [health provider](#) 189
 [machine identity provider](#) 217
 [network](#) 280
 [provider registry](#) 242
 [user identity provider](#) 232
[Introduction](#) 30

L

Local events
 [Addin management](#) 280
 [AzureAD and HostedEmail integration](#) 316
 [client backup provider](#) 188
 [client file backup provider](#) 109
 [domain infrastructure](#) 306
 [health provider](#) 217
 [machine identity provider](#) 231
 [network](#) 288
 [provider registry](#) 258
 [user identity provider](#) 242

M

Machine identity provider
 [abstract data model](#) 217
 [higher-layer triggered events](#) 217
 [initialization](#) 217
 [local events](#) 231
 [message processing](#) 217
 [sequencing rules](#) 217
 [timer events](#) 230
 [timers](#) 217
Message processing
 [Addin management](#) 259
 [AzureAD and HostedEmail integration](#) 306
 [client backup provider](#) 110
 [client file backup provider](#) 104
 [client notification](#) 317
 [domain infrastructure](#) 288
 [health provider](#) 189
 [machine identity provider](#) 217
 [network](#) 281
 [provider registry](#) 242
 [user identity provider](#) 232
[Message syntax](#) 35

Messages

[complex types](#) 37
[elements](#) 36
[enumerated](#) 36
[message syntax](#) 35
[namespaces](#) 35
[simple types](#) 70
[transport](#) 35

N

[Namespaces](#) 35
Network
 [abstract data model](#) 280
 [higher-layer triggered events](#) 281
 [initialization](#) 280
 [local events](#) 288
 [message processing](#) 281
 [sequencing rules](#) 281
 [timer events](#) 288
 [timers](#) 280
[Normative references](#) 31

O

[Overview \(synopsis\)](#) 32

P

[Parameters - security index](#) 325
[Preconditions](#) 33
[Prerequisites](#) 33
[Product behavior](#) 575
Provider registry
 [abstract data model](#) 242
 [higher-layer triggered events](#) 242
 [initialization](#) 242
 [local events](#) 258
 [message processing](#) 242
 [sequencing rules](#) 242
 [timer events](#) 258
 [timers](#) 242

R

[References](#) 31
 [informative](#) 32
 [normative](#) 31
[Relationship to other protocols](#) 33

S

Security
 [implementer considerations](#) 325
 [parameter index](#) 325
Sequencing rules
 [Addin management](#) 259
 [AzureAD and HostedEmail integration](#) 306
 [client backup provider](#) 110
 [client file backup provider](#) 104
 [client notification](#) 317
 [domain infrastructure](#) 288
 [health provider](#) 189
 [machine identity provider](#) 217

[network](#) 281
[provider registry](#) 242
[user identity provider](#) 232
Service contracts
 [Addin management](#) 258
 [AzureAD and HostedEmail integration](#) 306
 [client backup provider](#) 109
 [client file backup provider](#) 104
 [client notification](#) 316
 [domain infrastructure](#) 288
 [health provider](#) 188
 [machine identity provider](#) 217
 [network](#) 280
 [provider registry](#) 242
 [user identity provider](#) 231
[Simple types](#) 70
[Standards assignments](#) 34

T

Timer events
 [Addin management](#) 280
 [AzureAD and HostedEmail integration](#) 316
 [client backup provider](#) 188
 [client file backup provider](#) 109
 [domain infrastructure](#) 306
 [health provider](#) 216
 [machine identity provider](#) 230
 [network](#) 288
 [provider registry](#) 258
 [user identity provider](#) 242
Timers
 [Addin management](#) 258
 [AzureAD and HostedEmail integration](#) 306
 [client backup provider](#) 110
 [client file backup provider](#) 104
 [client notification](#) 316
 [domain infrastructure](#) 288
 [health provider](#) 189
 [machine identity provider](#) 217
 [network](#) 280
 [provider registry](#) 242
 [user identity provider](#) 232
[Tracking changes](#) 577
[Transport](#) 35
Triggered events
 [Addin management](#) 258
 [AzureAD and HostedEmail integration](#) 306
 [client backup provider](#) 110
 [client file backup provider](#) 104
 [client notification](#) 316
 [domain infrastructure](#) 288
 [health provider](#) 189
 [machine identity provider](#) 217
 [network](#) 281
 [provider registry](#) 242
 [user identity provider](#) 232
Types
 [complex](#) 37
 [simple](#) 70

U

User identity provider
 [abstract data model](#) 231

[higher-layer triggered events](#) 232
[initialization](#) 232
[local events](#) 242
[message processing](#) 232
[sequencing rules](#) 232
[timer events](#) 242
[timers](#) 232

V

[Vendor-extensible fields](#) 34
[Versioning](#) 33