

[MS-DPWSRP]:

Devices Profile for Web Services (DPWS): Shared Resource Publishing Data Structure

Intellectual Property Rights Notice for Open Specifications Documentation

- **Technical Documentation.** Microsoft publishes Open Specifications documentation ("this documentation") for protocols, file formats, data portability, computer languages, and standards support. Additionally, overview documents cover inter-protocol relationships and interactions.
- **Copyrights.** This documentation is covered by Microsoft copyrights. Regardless of any other terms that are contained in the terms of use for the Microsoft website that hosts this documentation, you can make copies of it in order to develop implementations of the technologies that are described in this documentation and can distribute portions of it in your implementations that use these technologies or in your documentation as necessary to properly document the implementation. You can also distribute in your implementation, with or without modification, any schemas, IDLs, or code samples that are included in the documentation. This permission also applies to any documents that are referenced in the Open Specifications documentation.
- **No Trade Secrets.** Microsoft does not claim any trade secret rights in this documentation.
- **Patents.** Microsoft has patents that might cover your implementations of the technologies described in the Open Specifications documentation. Neither this notice nor Microsoft's delivery of this documentation grants any licenses under those patents or any other Microsoft patents. However, a given Open Specifications document might be covered by the Microsoft [Open Specifications Promise](#) or the [Microsoft Community Promise](#). If you would prefer a written license, or if the technologies described in this documentation are not covered by the Open Specifications Promise or Community Promise, as applicable, patent licenses are available by contacting iplg@microsoft.com.
- **License Programs.** To see all of the protocols in scope under a specific license program and the associated patents, visit the [Patent Map](#).
- **Trademarks.** The names of companies and products contained in this documentation might be covered by trademarks or similar intellectual property rights. This notice does not grant any licenses under those rights. For a list of Microsoft trademarks, visit www.microsoft.com/trademarks.
- **Fictitious Names.** The example companies, organizations, products, domain names, email addresses, logos, people, places, and events that are depicted in this documentation are fictitious. No association with any real company, organization, product, domain name, email address, logo, person, place, or event is intended or should be inferred.

Reservation of Rights. All other rights are reserved, and this notice does not grant any rights other than as specifically described above, whether by implication, estoppel, or otherwise.

Tools. The Open Specifications documentation does not require the use of Microsoft programming tools or programming environments in order for you to develop an implementation. If you have access to Microsoft programming tools and environments, you are free to take advantage of them. Certain Open Specifications documents are intended for use in conjunction with publicly available standards specifications and network programming art and, as such, assume that the reader either is familiar with the aforementioned material or has immediate access to it.

Support. For questions and support, please contact dochelp@microsoft.com.

Revision Summary

Date	Revision History	Revision Class	Comments
1/29/2010	0.1	Major	First Release.
3/12/2010	0.1.1	Editorial	Changed language and formatting in the technical content.
4/23/2010	0.1.2	Editorial	Changed language and formatting in the technical content.
6/4/2010	1.0	Major	Updated and revised the technical content.
7/16/2010	1.0	None	No changes to the meaning, language, or formatting of the technical content.
8/27/2010	1.0	None	No changes to the meaning, language, or formatting of the technical content.
10/8/2010	1.0	None	No changes to the meaning, language, or formatting of the technical content.
11/19/2010	1.0	None	No changes to the meaning, language, or formatting of the technical content.
1/7/2011	1.0	None	No changes to the meaning, language, or formatting of the technical content.
2/11/2011	1.0	None	No changes to the meaning, language, or formatting of the technical content.
3/25/2011	1.0	None	No changes to the meaning, language, or formatting of the technical content.
5/6/2011	1.0	None	No changes to the meaning, language, or formatting of the technical content.
6/17/2011	1.1	Minor	Clarified the meaning of the technical content.
9/23/2011	1.1	None	No changes to the meaning, language, or formatting of the technical content.
12/16/2011	2.0	Major	Updated and revised the technical content.
3/30/2012	2.0	None	No changes to the meaning, language, or formatting of the technical content.
7/12/2012	2.0	None	No changes to the meaning, language, or formatting of the technical content.
10/25/2012	2.1	Minor	Clarified the meaning of the technical content.
1/31/2013	2.1	None	No changes to the meaning, language, or formatting of the technical content.
8/8/2013	3.0	Major	Updated and revised the technical content.
11/14/2013	3.0	None	No changes to the meaning, language, or formatting of the technical content.
2/13/2014	3.0	None	No changes to the meaning, language, or formatting of the technical content.
5/15/2014	3.0	None	No changes to the meaning, language, or formatting of the

Date	Revision History	Revision Class	Comments
			technical content.
6/30/2015	4.0	Major	Significantly changed the technical content.
10/16/2015	4.0	None	No changes to the meaning, language, or formatting of the technical content.
7/14/2016	4.0	None	No changes to the meaning, language, or formatting of the technical content.
6/1/2017	4.0	None	No changes to the meaning, language, or formatting of the technical content.
3/16/2018	5.0	Major	Significantly changed the technical content.
9/12/2018	5.0	None	No changes to the meaning, language, or formatting of the technical content.

Table of Contents

1	Introduction	5
1.1	Glossary	5
1.2	References	5
1.2.1	Normative References	6
1.2.2	Informative References	6
1.3	Overview	6
1.4	Relationship to Protocols and Other Structures	6
1.5	Applicability Statement	6
1.6	Versioning and Localization	6
1.7	Vendor-Extensible Fields	7
2	Structures	8
2.1	The Shell Publishing Data Structure.....	8
2.1.1	Namespaces	8
2.1.2	Complex Types.....	8
2.1.2.1	pi.....	9
2.1.2.2	usersFilesDescription	9
2.1.2.3	o.....	9
2.1.2.4	il.....	10
2.1.2.5	dil	10
2.1.2.6	i.....	11
2.1.2.7	ul	11
2.1.3	Simple Types	12
2.1.3.1	serializedType	12
2.1.4	Encryption Rules.....	12
2.1.4.1	Data Signing	12
2.1.4.2	Data Encoding	12
2.1.4.2.1	Alphabet	13
2.1.4.2.2	Encoding	13
3	Structure Examples	15
3.1	Shell Publishing Data Structure Example	15
3.2	Signed XML Data.....	16
3.3	Base-64-Encoded Shell Publishing Data Structure Example	17
4	Security	20
4.1	Security Considerations for Implementers	20
4.2	Index of Security Fields	20
5	Appendix A: Product Behavior	21
6	Change Tracking.....	22
7	Index.....	23

1 Introduction

The Devices Profile for Web Services (DPWS): Shared Resource Publishing Data Structure describes the Shell Publishing data structure. This data structure is used by the HomeGroup Protocol to advertise shared files and folders in a HomeGroup peer-to-peer network environment.

Sections 1.7 and 2 of this specification are normative. All other sections and examples in this specification are informative.

1.1 Glossary

This document uses the following terms:

homegroup: A group of one or more computers that are AES joined together by using Advanced Encryption Standard (AES) through the HomeGroup Protocol, which are able to share resources (files, printers, and so on) with each other.

HomeGroup machine: The machine where files are being shared, and that creates the Shell Publishing data structure.

HomeGroup user: A user account on the **HomeGroup machine** where files are being shared.

Internet SID: A user **SID** that represents an online identity. The **SID** is unique across all providers and all machines. The **SID** is a hash of the identity's unique ID and the provider GUID.

item ID list (IDList): A data structure that refers to a location. An item ID list is a multi-segment data structure where each segment's content is defined by a data source that is responsible for the location in the namespace referred to by the preceding segments.

security identifier (SID): An identifier for security principals that is used to identify an account or a group. Conceptually, the **SID** is composed of an account authority portion (typically a domain) and a smaller integer representing an identity relative to the account authority, termed the relative identifier (RID). The **SID** format is specified in [\[MS-DTYP\]](#) section 2.4.2; a string representation of **SIDs** is specified in [\[MS-DTYP\]](#) section 2.4.2 and [\[MS-AZOD\]](#) section 1.1.1.2.

Web Services on Devices (WSD): A function-discovery protocol used to discover and communicate certain data structures in a HomeGroup network environment. Implementation details are specified in [\[DPWS\]](#).

XML schema: A description of a type of XML document that is typically expressed in terms of constraints on the structure and content of documents of that type, in addition to the basic syntax constraints that are imposed by XML itself. An XML schema provides a view of a document type at a relatively high level of abstraction.

MAY, SHOULD, MUST, SHOULD NOT, MUST NOT: These terms (in all caps) are used as defined in [\[RFC2119\]](#). All statements of optional behavior use either MAY, SHOULD, or SHOULD NOT.

1.2 References

Links to a document in the Microsoft Open Specifications library point to the correct section in the most recently published version of the referenced document. However, because individual documents in the library are not updated at the same time, the section numbers in the documents may not match. You can confirm the correct section numbering by checking the [Errata](#).

1.2.1 Normative References

We conduct frequent surveys of the normative references to assure their continued availability. If you have any issue with finding a normative reference, please contact dochelp@microsoft.com. We will assist you in finding the relevant information.

[DPWS] Chans, S., Conti, D., Schlimmer, J., et al., "Devices Profile for Web Services", February 2006, <http://specs.xmlsoap.org/ws/2006/02/devprof/devicesprofile.pdf>

[MS-DTYP] Microsoft Corporation, "[Windows Data Types](#)".

[MS-HGRP] Microsoft Corporation, "[HomeGroup Protocol](#)".

[MS-SHLLINK] Microsoft Corporation, "[Shell Link \(.LNK\) Binary File Format](#)".

[RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", BCP 14, RFC 2119, March 1997, <https://www.rfc-editor.org/rfc/rfc2119.html>

[RFC3548] Josefsson, S., Ed., "The Base16, Base32, and Base64 Data Encodings", RFC 3548, July 2003, <http://www.rfc-editor.org/rfc/rfc3548.txt>

1.2.2 Informative References

[XMLNS] Bray, T., Hollander, D., Layman, A., et al., Eds., "Namespaces in XML 1.0 (Third Edition)", W3C Recommendation, December 2009, <https://www.w3.org/TR/2009/REC-xml-names-20091208/>

1.3 Overview

This specification extends DPWS [\[DPWS\]](#) by adding the Shell Publishing data structure. The Shell Publishing data structure describes shared files and folders by each **HomeGroup user** on each **HomeGroup machine** in a **HomeGroup** network environment. [<1>](#)

1.4 Relationship to Protocols and Other Structures

The Shell Publishing data structure is a data structure format made available to **HomeGroup** networked environment by a DPWS provider.

Shell Publishing Extension	This extension
DPWS	Industry standard
SOAP	Industry standard

1.5 Applicability Statement

Use of the Shell Publishing data structure is suitable when machines in a **HomeGroup** network environment share files and folders among HomeGroup members.

1.6 Versioning and Localization

This document covers versioning issues in the following areas:

- **Supported Transports:** This data structure uses the DPWS provider as the only transport.
- **Protocol Versions:** This data structure is not versioned.

- **Security and Authentication Methods:** This data structure does not support authentication. The data structure is signed using a **HomeGroup** public key (see [\[MS-HGRP\]](#) section 3.1.4.5).
- **Localization:** This data structure does not support localization.
- **Capability Negotiation:** This data structure does not support explicit capability negotiation.

1.7 Vendor-Extensible Fields

There are no vendor-extensible fields. The **XML schema** of the data structure is not validated, making it possible for vendors to extend the Shell Publishing data structure by adding additional elements and/or attributes. The extended data will not be interpreted unless consumed by the vendor who added it.

2 Structures

2.1 The Shell Publishing Data Structure

The Shell Publishing data structure describes a method of publishing and discovering shared files and folders in a **HomeGroup** configured network environment.

The Shell Publishing data structure MUST be transported using **WSD**. The WSD type MUST be ShellPublishing.

This structure uses SID structures as specified in [\[MS-DTYP\]](#) section 2.4.2.

An individual HomeGroup member MUST publish certain data about his or her shared files and folders as specified in section [2.1.2.1](#), in order to participate in the HomeGroup sharing.

The Shell Publishing XML data structure is defined as follows:

```
<?xml version="1.0" encoding="UTF-8"?>
<xs:schema xmlns:xs="http://www.w3.org/2001/XMLSchema" elementFormDefault="qualified"
attributeFormDefault="unqualified">
  <xs:simpleType name="serializedType">
    <xs:restriction base="xs:string">
      <xs:pattern value="\{[A-Za-z0-9+/*\}]" />
    </xs:restriction>
  </xs:simpleType>
  <xs:element name="pi" type="pi" />
</xs:schema>
```

pi: A **pi** complex type, as specified in section 2.1.2.1. Published items. Serves as an envelope for descriptions of a **HomeGroup user's** shared files.

2.1.1 Namespaces

XML Namespace	Reference
http://www.w3.org/2001/XMLSchema	[XMLNS]

2.1.2 Complex Types

The following table summarizes the set of common **XML schema** complex types defined by this specification.

Complex Type	Description
pi	Published items. The envelope for the description of shared files and folders.
usersFilesDescription	Describes shared files and folders per HomeGroup user , per HomeGroup machine in the HomeGroup .
o	Owner. Describes a HomeGroup user in the HomeGroup machine that is sharing the files and folders on the HomeGroup.
il	Items list. Describes a list of items that are being shared by a HomeGroup user in a HomeGroup machine on the HomeGroup.
dil	Discretionary access items list. Describes a list of items that have their security set so that only a specific set of HomeGroup users has access to them.

Complex Type	Description
i	Item. Describes a file or folder that is being shared by a HomeGroup user in a HomeGroup machine on the HomeGroup.
ul	User list. Describes a list of SIDs that identifies the users the particular item is shared with.

2.1.2.1 pi

The pi (published items) complex type is an envelope that contains the description of shared files and folders.

```
<xs:element name="pi">
  <xs:complexType>
    <xs:element name="usersFilesDescription" type="usersFilesDescription" />
    <xs:complexType>
  </xs:element>
```

usersFilesDescription: A description of the **HomeGroup user's** files. Defines the resources shared by a HomeGroup user on a **HomeGroup machine**.

2.1.2.2 usersFilesDescription

The usersFilesDescription complex type describes shared files and folders per **HomeGroup user**, per **HomeGroup machine** in the **HomeGroup**.

```
<xs:element name="usersFilesDescription">
  <xs:complexType>
    <xs:all>
      <xs:element name="o" type="o" />
      <xs:element name="il" type="il" minOccurs="0" />
      <xs:element name="dil" type="dil" minOccurs="0" />
    </xs:all>
  </xs:complexType>
</xs:element>
```

o: The owner of the shared resource. The owner is typically the HomeGroup user who designates a resource for sharing.

il: Optional element. When present, contains a sequence of one or more items (the item list).

dil: Optional element. When present, contains a sequence of one or more items (the item list), which are shared with specific other members of the HomeGroup using discretionary access.

The **usersFilesDescription** MUST contain at least an **il** or a **dil** element. If both the **il** and **dil** elements are missing, the message will be discarded.

2.1.2.3 o

The o (owner) complex type describes a **HomeGroup user** in the **HomeGroup machine** that is sharing the files and folders on the **HomeGroup**.

```
<xs:element name="o">
  <xs:complexType>
    <xs:annotation>
```

```

        <xs:documentation>owner information, attributes are user name, alias and
        SID</xs:documentation>
      </xs:annotation>
      <xs:complexType>
        <xs:attribute name="un" type="xs:string" />
        <xs:attribute name="a" type="xs:string" />
        <xs:attribute name="s" type="xs:string" />
      </xs:complexType>
    </xs:element>

```

- un:** The owner's user name (display name). This is the display name for the HomeGroup user on the HomeGroup machine sharing the files and folders on the HomeGroup.
- a:** The owner's alias. Describes the **alias object** of the HomeGroup user on the HomeGroup machine sharing the files and folders on the HomeGroup. This value MAY be used by the implementation as a hint for the HomeGroup user identity.
- s:** Concatenation of the HomeGroup GUID and the SID (security identifier) of the account sharing the files on the HomeGroup machine. This is the unique identifier for the HomeGroup and the security identifier for the HomeGroup user on the HomeGroup machine that is sharing the files and folders on the HomeGroup.

2.1.2.4 il

The il (items list) complex type describes a list of items that are being shared by a **HomeGroup user** in a **HomeGroup machine** on the **HomeGroup**.

```

<xs:element name="il">
  <xs:complexType>
    <xs:annotation>
      <xs:documentation>item list</xs:documentation>
    </xs:annotation>
    <xs:all>
      <xs:element name="i" minOccurs="1" maxOccurs="unbounded" type="i" />
    </xs:all>
  </xs:complexType>
</xs:element>

```

- i:** An item in the item list. Contains a description of shared files and folders for the HomeGroup user on the HomeGroup machine.

2.1.2.5 dil

The dil (discretionary access items list) complex type describes a list of items that have their security set so that only a specific set of **HomeGroup users** has access to them. Clients of the information SHOULD only present these items to the user if the user's **security identifier (SID)** values match one of the user identities in the **ul** (user list) complex type. Items that are shared by using discretionary access can be shared only with users represented by **Internet SIDs**.

```

<xs:element name="dil">
  <xs:complexType>
    <xs:annotation>
      <xs:documentation>discretionary access item list</xs:documentation>
    </xs:annotation>
    <xs:all>
      <xs:element name="i" minOccurs="1" maxOccurs="unbounded" type="i" />
    </xs:all>
  </xs:complexType>
</xs:element>

```

```

    </xs:complexType>
  </xs:element>

```

i: An item in the item list. Contains a description of shared files and folders for the HomeGroup user on the **HomeGroup machine**.

2.1.2.6 i

The i (item) complex type describes a file or folder that is being shared by a **HomeGroup user** in a **HomeGroup machine** on the **HomeGroup**.

```

<xs:element name="i" minOccurs="1"
maxOccurs="unbounded">
  <xs:complexType>
    <xs:annotation>
      <xs:documentation>item, sub elements are path (absolute UNC or machine relative),
display name and BASE-64 encoded serialized shell link</xs:documentation>
    </xs:annotation>
    <xs:all>
      <xs:element name="p" type="xs:anyURI"/>
      <xs:element name="dn" type="xs:string" minOccurs="0" />
      <xs:element name="sl" type="serializedType"/>
      <xs:element name="ul" type="ul" minOccurs="0" />
    </xs:all>
  </xs:complexType>
</xs:element>

```

p: An absolute **UNC** path or a relative machine path to the shared file or folder. If the path begins with a "\" then it is a machine-relative path. Relative paths are related to the HomeGroup machine where the message originated. The machine name is taken from the **WSD** Shell Publishing message that is transporting this data structure.

This element is used to access the shared resource if the shell link element **pi.usersFilesDescription.il.i.sl** is not present or if the HomeGroup machine originating the message has changed since the link was created.

dn: Optional element. When present, contains the display name of the item. The display name is sent so that if the message client implementation uses the display name, it is unnecessary to use additional protocols to retrieve the display name.

sl: A base-64-encoded binary stream representing a serialized shell link. The shell link references a file or folder shared by the HomeGroup user on the machine and contains the associated **item ID list**. This information is sent so that if the implementation uses the item ID list, it is unnecessary to use additional protocols to retrieve the ID list. Shell Links are specified in [\[MS-SHLLINK\]](#).

This field uses nonstandard base-64 encoding as specified in section [2.1.4.2](#).

ul: Optional element. When present, contains the users list. This is a list of **Internet SIDs** (security identifiers) that identifies the users that have discretionary access to a shared item. This list SHOULD only be included if the user is sharing out items by using discretionary access.

2.1.2.7 ul

The ul (user list) complex type describes a list of **SIDs** that identifies the users the particular item is shared with. Because sharing based on discretionary access is only possible using **Internet SIDs**, this list MUST contain only Internet SIDs.

```

<xs:element name="ul">

```

```

<xs:complexType>
  <xs:annotation>
    <xs:documentation>user list</xs:documentation>
  </xs:annotation>
  <xs:all>
    <xs:element name="u" minOccurs="1">
      <xs:complexType>
        <xs:sequence>
          <xs:element name="s" type="xs:string" minOccurs="1" maxOccurs="1" />
        </xs:sequence>
      </xs:complexType>
    </xs:element>
  </xs:all>
</xs:complexType>
</xs:element>

```

u.s: The SID of the account sharing the files on the **HomeGroup machine**. Describes the security identifier for the **HomeGroup user** on the HomeGroup machine that is sharing the files and folders on the **HomeGroup**.

2.1.3 Simple Types

The following table summarizes the set of common **XML schema** simple type definitions defined by this specification.

Simple type	Description
serializedType	A base-64-encoded binary stream

2.1.3.1 serializedType

The serializedType simple type contains a base-64-encoded binary stream.

```

<xs:simpleType name="serializedType">
  <xs:restriction base="xs:string">
    <xs:pattern value="\{ [A-Za-z0-9+/\]*\}" />
  </xs:restriction>
</xs:simpleType>

```

pattern: This value describes base-64 encoding using the following pattern: `[A-Za-z0-9+/\]*`

This field uses non-standard base-64 encoding as specified in section [2.1.4.2](#).

2.1.4 Encryption Rules

2.1.4.1 Data Signing

The Shell Publishing data structure MUST be signed using a **HomeGroup** public key ([\[MS-HGRP\]](#) section 3.1.4.5) prior to being encoded. To create the signature, the data structure is hashed and the hash value is encrypted using HomeGroup public key. This signature is then appended to the data structure.

2.1.4.2 Data Encoding

This data structure MUST be base-64 encoded after being signed and before being transported in a **WSD** message. The base-64 encoding used by this data structure is a modification on the standard

encoding specified by [\[RFC3548\]](#). The alphabet used is the same, but the encoding algorithm is different (see [2.1.4.2.2](#)).

2.1.4.2.1 Alphabet

The base-64 alphabet used by this data structure is the following:

Value	Encoding	Value	Encoding	Value	Encoding	Value	Encoding
0	A	17	R	34	i	51	z
1	B	18	S	35	j	52	0
2	C	19	T	36	k	53	1
3	D	20	U	37	l	54	2
4	E	21	V	38	m	55	3
5	F	22	W	39	n	56	4
6	G	23	X	40	o	57	5
7	H	24	Y	41	p	58	6
8	I	25	Z	42	q	59	7
9	J	26	a	43	r	60	8
10	K	27	b	44	s	61	9
11	L	28	c	45	t	62	+
12	M	29	d	46	u	63	/
13	N	30	e	47	v		
14	O	31	f	48	w		
15	P	32	g	49	x		
16	Q	33	h	50	y		

2.1.4.2.2 Encoding

The data being encoded is manipulated at the 8-bit chunk (octet) borders. The lowest 6 bits are converted to an appropriate alphabet character. (The value represented by these 6 bits is converted to a corresponding character, shown in the table in section [2.1.4.2.1](#)). The remaining 2 bits are combined with the next octet by making them the lowest 2 bits. And the process is repeated, with each step having 2 more extra bits until 6 bits remain, which are then converted to a character without the use of the next octet. The following diagram illustrates this process:

First Octet								Second Octet								Third Octet									
07	06	05	04	03	02	01	00	17	16	15	14	13	12	11	10	27	26	25	24	23	22	21	20		
		05	04	03	02	01	00																		
First Encoded Character																									
								17	16	15	14	13	12	11	10	07	06	27	26	25	24	23	22	21	20

Figure 1: Data encoding at the 8-bit (octet) level

The lowest 6 bits of the second octet are converted to the next character, and the remaining 4 bits are moved to be the lowest 4 bits of the next octet.

First Octet								Second Octet								Third Octet									
						17	16	15	14	13	12	11	10	07	06	27	26	25	24	23	22	21	20		
										13	12	11	10	07	06										
								Second Encoded Character																	
												27	26	25	24	23	22	21	20	17	16	15	14		
																		Third Encoded Character							
																		27	26	25	24	23	22		
																		Fourth Encoded Character							

Figure 2: Data encoding of the lowest 6 bits and remaining 4 bits


```

1330011019-2935621724</s>                </u>                </ul>                </i>                <i>
<p>\Users\HomeGroupUser\AppData\Roaming\Microsoft\Windows\Libraries\Documents.library-ms</p>
<sl>MBAAAEAFCAAAAAAAAAADAAAAAAAAAYkgAADBgAAAAUptMb6+wucAs2YKL2PsLHArNmyi9D7yBMjDAAAAAAAAABAAAAAAAA
AAAAAAAAAAAAAgIAAAAHAAAAACAAAAAAAAAAAAAAcAAAAEEAAQJAAACAAAAQBAAAAAAAAAAAAAgAAwFXSFUTB5UQSNDXVN
VRSNFVAVNXZyNDXBHCEFGdhx1UvFWbp52Zc1UajJ3bz9mZ0x1Vp5GZvd3ccxUaiJXYy1WZzxFRvNWdtVmb0NnLslmYyFm
c51SbzBAiDAAAMAAAgSBAfGvDawC8h4LUDhIszdg/W+OPzCAAA0KA7+6k78JAEAAAAAAAAAtAAAAEzUQN1cDVuC+OUrPVI5
pxthzgpBRAAAAsAAAAALAAA8//AAAAAAAAABBAAEzUQNFMxYtVfKGQuA8CAGjeuOrlAAAAoAAAAAfAAAAKAAAAGUA
EEANBQQA4EABBgUAMDAAAAAAAAAAQLAAAAxMFUTpDp969s3M4QReORYqdKVuaEAAAADAAAAAwEAAAAAAAAAAAAAAAAA
AAAAwKAMcAFzFXSFUTB5UQSNDXVNXYNHAN12Yy92cvZGdg4UZ0d3bytGAAIAAMBQMAAAAAAgK+AsmQAQVzVmczAAOAgA
AEAw7+qiP5qpK+AsmqAAAAwIAAAAAA8DAAAAAAAAAAAAAAAAAAAAAQVAMHAlBgcAMDAAAAFAIFAxAAAAAAAg4juaKBABHc
EFGdhBAPAgAAEAW7+qiP5qpK+ormqAAAAUWBAAAAwBAAAAAAAAAAAAAAAAAAAAQAAHAWBARAEGA0BQYAAAAWAGUAEADA
AAAAoiPlsIEAI1bh1WaudGA8AACQAav7rK+krmq4TuaqCAAAAgZFAAAAAATAAAAAAAAAAAAAAAAAASBwbAEGAtBQaA4
GAnBAAAYBAYBQMAAAAAAgK+0+mUAQTJNkUPN1fxAAAAABACAQAav7rK+krmq4T7bqCAAAwZFAAAAwKAAAAAAAAAAAA
AAAAANBQAAMGyBwBAMHAvBgZAHAAAGAIFAxAAAAAAAg4z6aCBAXlmbk92dzBAPAgAAEAW7+qiP5qpK+sumqAAABAGWB
AAAAA4CAAAAAAAAAAAAAAAAAAAwVakGAuBAZA8GA3BwcAAAAWAWAEDAAAAAAoiPxxZEAWScJVS5XMAAAQAgAAEAW7+
qiPArpK+EHnqAAAGjBAAAAA0BAAAAAAAAAAAAAAAAAAATAKGAIbGcAEGAYBQaAUGAzBAAAgBaaCgMAMjDAAGK+AHngA
ARPNUVNVkfX4CTJJEAA4HAIABA8uvq4DwaqiPwxpKAAAAIdAAAAAUAAAAAAAAAAAAAFAAAAAQEAwBwYAUHATBQZA4G
A0Bwc4CAsBQAIGAYBQYAIHA5BQLA0GAzBAAAAEAzBaaAUGAsBabAMDAyAgLAQGAsBabAwCatAwMAQDA1AwNAUDAAAAH
AAAAGOAaAKAAAAqeDAAXMFUTJuiYZEvMhzQ7y/ETaCmt5cHAAAACAAAAASAAAAJY0GRu36U3ktVZztUcD1tG0AAwAA
AAAAEBEAALDAAAUAWHQB+TQDi66kGEiINcAsCmW0ZGA8yQ6wFAAAAAAAAAAAAAAAAAAAAAAA0BQMAAAAAAgK+krmRA
QVzVmczBAYAgAAEAW7+qiPG3jK+krmqAAAAshLAAAAA4AAAAAAAAAAAAAGNAAAAAQVAMHAlBgcAMHAAAAQAMHA0BQZAwG
AsBwMANIDAuAAZAGAsBALA0CayAQMAgDaxAwMAAAUAAATAEDAAAAAAoiPArJEAU1clJ3MAGDAIABA8uvq4TuaqiPArpK
AAAAIAAAAA/AAAAAAAAAAAAAAAAAAUFAzBQZAIHAzAAAAQBASBQMAAAAAAgK+ormSAQQwBHRhRXYAWDAIABA8uvq
4TuaqiP6qpKAAALVAAAAACAAAAAAAAAAAAAAAAAAAAEEAwBacAQEAhBAAdAEGAAAGFAIFAxAAAAAAAg4TJLCBAS9WYt1
mbnBAPAgAAEAW7+qiP5qpK+krmqAAAAyWBAAAAwEAAAAAAAAAAAAAAAAAAAGUA8GAhBQbAkGAuBwZAAAAWAAWEDAAAA
AAoiPtvJFAU0USDJ1TT5XMAAAQAgAAEAW7+qiP5qpK+0+mqAAAAcWBAAAAAsCAAAAAAAAAAAAAAAAAAAQTAKGAjBgC8GA
zBwbAYGA0BAAAgBASBQMAAAAAAgK+sumQAQwVp5GZvd3cAwDAIABA8uvq4TuaqiPrrpKAAAAVAAAAAAuAAAAAAAAAAAA
AAAAAAAAAcFAPBgBAQGAvBwdAMHAAAGFAgFAxAAAAAAAg4TccGBAM1kQSFkU+FDAAAEIAABA8uvq4DwaqiPxxpKAAAA4Y
AAAAAADAAAAAAAAAAAAAAAAAAwEApBgYAIHahBgCAkGAlBwcAAAAAYAgMAIDAz4AAAoiPwxJIAQ0TDVVTf5XMuwUSCBA
A+BACAQAav7rK+Asmq4DccqCAAAASHAAAAAFAAAAAAAAAAAAAUUBAAAAAEEBwBAMGA1BQbAUGAuBAdAMHAuAAbAkGaiBgc
AEGAYBQeA0CatBwcAAAAABwcAgGAlBAbAwGAzAgMA4CAkBAwAwGAsAQLAMDA0AQNAcDA1AAAwBAAAAAAAAAAAAAAAAAY
AADAAAGiFAAAAAAAAYFWbh5WYyNDAAAAAAAAAAAYBUMPRBhc/Sy2G3HIG2MWWpd2MuuzB4R04FAQHIX54YWAFzT02B3v
kstx9BihNj1VanNjr7cAeEneBAUIyVOOGAAAAA</sl>                </ul>                <u>                <s>S-1-11-96-
3623454863-58364-18864-2661722203-1597581903-1555942514-2007325574-4116307836-2518318601-
3450682263</s>                </u>                <u>                <s>S-1-11-96-3623454863-58364-18864-
2661722203-1597581903-1847293483-3855340794-256571992-1330011019-2935621724</s>                </u>
</ul>                </i>                </dil>
</usersFilesDescription>
</pi>

```

3.2 Signed XML Data

The following signature has been created based on the Shell Publishing data structure example in section 3.1. This signature has been created by hashing the data using the **HomeGroup** public key (see section 2.1.4.1). This signature can be appended to the Shell Publishing data structure example before base-64 encoding in order to create an authentic message.

```

0x0000: 01 00 00 9d 21 49 20 76
0x0008: ff 72 31 7f 31 5f 57 ef-22 ae 08 92 8e 08 29 5d
0x0028: cd 54 ab 8f 7e 9a 42 ea-a4 c1 03 07 41 38 62 77
0x0048: de 33 cb 83 c2 4f eb b2-cb 10 84 02 8b 22 4f d0
0x0068: 74 e2 04 c6 af 3c 23 8a-5d e3 7c c0 5b b1 84 c2
0x0088: 2c 95 67 aa ff 17 08 7a-48 52 0f 30 2b 6c cd 3d
0x00A8: 3a 24 97 67 0a 68 5d b2-8c 3c a9 d6 90 cf 18 3b
0x00C8: 69 c8 58 de 94 57 e8 39-30 98 0a 79 ac 44 85 02
0x00E8: 21 5e 5e cf 96 24 64 27-59 0a 98 cb 88 68 a5 66
0x0108: 14 1e e6 4a 7d ab e0 15-8e 5b 57 08 3d 7f 0c c3
0x0128: f3 d9 dc 68 95 48 8d 5d-e3 1d 42 3b d0 a1 33 ed
0x0148: f0 30 ea 0e 5c de ca 93-a5 c2 fe a5 72 0c c6 3b
0x0168: c6 aa dd 38 99 dd 44 22-f5 e0 d4 df 74 2a f3 4b
0x0188: 32 c5 55 59 c4 a1 a6 52-3f 9f a2 39 24 33 38 c5
0x01A8: 45 3b 9c f1 24 de be af-41 c0 6d 28 0e 5a 75 4c
0x01C8: 4a 64 5d b0 b0 6d d1 d2-39 2f 1c f3 64 f3 0c 3a
0x01E8: df 9f 00 ec 48 37 01 24-f7 a4 9a

```


This section contains a signed, base-64-encoded version of the Shell Publishing data structure example provided in section [3.1](#). The base-64 encoding has been applied to the structure after appending the signature given in section [3.2](#).

17 / 24

[MS-DPWSRP] - v20180912
Devices Profile for Web Services (DPWS): Shared Resource Publishing Data Structure
Copyright © 2018 Microsoft Corporation
Release: September 12, 2018

0x1020: 88yCS5TDKACIgACIgwzLp5TDKACIgACP
0x1040: vkGb+0gCgACPvU3clJ3cG1GblNHR1N3Y
0x1060: y1Gc012bu5TDKwzLwlmPAEAAA0ZIJBid
0x1080: /LXM/FzXX9uIuigkOiQKd1Mvr+ofaKk6
0x10A0: kG8AHEEOidn3zs8gC/06yuMEEKwii8E0
0x10C0: 0JOBG/KPjoYXjzHwbFLhCzS1np6/Xgge
0x10E0: IJ1DwsCbN3jOkc5ZKgWXyyIPpaNkPjxO
0x1100: phMWeT5VonDMYqQesSUhCEiXe9slkQ2J
0x1120: ZpAmLjIalaGFeYuS9tK4V44WXhQP/xww
0x1140: znN3oVJSN214dI00QH6MtDPMq7AXer8k
0x1160: lKs/lKHDGvjxq2NOZ2NRiUP4U/NdqM/S
0x1180: yUcVZRcomK1PfKaOkMDOFX0OcGPJe77r
0x11A0: BBcbo4gW1xkSk1Fsw2W0SnzLcMPZzzgO
0x11C0: f/JAsj0NBQy9kqJ

4 Security

4.1 Security Considerations for Implementers

The Shell Publishing data structure relies on **HomeGroup** key signing to validate authenticity of the data.

4.2 Index of Security Fields

Security parameter	Section
HomeGroup public key	2.1.4.1

5 Appendix A: Product Behavior

The information in this specification is applicable to the following Microsoft products or supplemental software. References to product versions include updates to those products.

- Windows 7 operating system
- Windows Home Server 2011 server software
- Windows 8 operating system
- Windows 8.1 operating system
- Windows 10 operating system

Exceptions, if any, are noted in this section. If an update version, service pack or Knowledge Base (KB) number appears with a product name, the behavior changed in that update. The new behavior also applies to subsequent updates unless otherwise specified. If a product edition appears with the product version, behavior is different in that product edition.

Unless otherwise specified, any statement of optional behavior in this specification that is prescribed using the terms "SHOULD" or "SHOULD NOT" implies product behavior in accordance with the SHOULD or SHOULD NOT prescription. Unless otherwise specified, the term "MAY" implies that the product does not follow the prescription.

[<1> Section 1.3](#): This protocol is disabled in Windows 10 v1803 operating system and subsequent updates.

6 Change Tracking

No table of changes is available. The document is either new or has had no changes since its last release.

7 Index

A

[Applicability](#) 6

B

[Base-64-encoded shell publishing data structure example](#) 17

[Base-64-Encoded Shell Publishing Data Structure Example example](#) 17

C

[Change tracking](#) 22

Complex types

[dil](#) 10

[i](#) 11

[il](#) 10

[o](#) 9

[overview](#) 8

[pi](#) 9

[ul](#) 11

[usersFilesDescription](#) 9

D

Data

[encoding encryption rules](#) 12

[signing encryption rules](#) 12

[structures - Shell Publishing](#) 8

Details

[complex types](#) 8

data

[encoding encryption rules](#) 12

[signing encryption rules](#) 12

[dil complex type](#) 10

[i complex type](#) 11

[il complex type](#) 10

[namespaces](#) 8

[o complex type](#) 9

[pi complex type](#) 9

[serializedType simple type](#) 12

[Shell Publishing data structure](#) 8

[simple types](#) 12

[ul complex type](#) 11

[usersFilesDescription complex type](#) 9

[dil complex type](#) 10

E

Encryption rules - data

[encoding](#) 12

[signing](#) 12

Examples

[base-64-encoded shell publishing data structure](#) 17

[Base-64-Encoded Shell Publishing Data Structure Example](#) 17

[shell publishing data structure](#) 15

[Shell Publishing Data Structure Example](#) 15

[Signed XML Data](#) 16

F

Fields

[security index](#) 20

[vendor-extensible](#) 7

[Fields - security index](#) 20

[Fields - vendor-extensible](#) 7

G

[Glossary](#) 5

I

[i complex type](#) 11

[il complex type](#) 10

[Implementer - security considerations](#) 20

[Index of security fields](#) 20

[Informative references](#) 6

[Introduction](#) 5

L

[Localization](#) 6

N

[Namespaces](#) 8

[Normative references](#) 6

O

[o complex type](#) 9

[Overview \(synopsis\)](#) 6

P

[pi complex type](#) 9

[Product behavior](#) 21

R

[References](#) 5

[informative](#) 6

[normative](#) 6

[Relationship to protocols and other structures](#) 6

S

Security

[field index](#) 20

[implementer considerations](#) 20

[serializedType simple type](#) 12

Shell Publishing data

[structure](#) 8

[structure example](#) 15

[Shell Publishing Data Structure Example example](#) 15

[Signed XML Data example](#) 16

Simple types

[overview](#) 12

[serializedType](#) 12

Structures

[Shell Publishing](#) 8

[simple types](#) 12

T

[Tracking changes](#) 22

Types

[complex](#) 8

[simple](#) 12

U

[ul complex type](#) 11

[usersFilesDescription complex type](#) 9

V

[Vendor-extensible fields](#) 7

[Versioning](#) 6