16bit add

==========

```
assume cs:code,ds:data
data segment
        opr1 dw 1144h
    opr2 dw 4477h
    result dw ?

data ends
code segment
    org 0100h
start:  mov ax,data
    mov ds,ax

    mov ax,opr1
    mov bx,opr2
    add ax,bx
    mov result,ax


        mov ah,4ch
    int 21h
        code ends
end start
```

Case conversion

==========

```
ASSUME CS:CODE,DS:data
data SEGMENT
COUNT equ 10h
data ends
CODE SEGMENT
START:MOV AX,data
        MOV DS,AX
        MOV CX,COUNT ; LOOP COUNTER
L1:MOV AH,1 ; INPUT CHARACTER,
        INT 21H ; AL = CHARACTER
        CMP AL,60H
        JNC UPPER
        ADD AL,20H
        JMP SKIP
UPPER:SUB AL,20H ; CONVERT TO UPPER CASE
SKIP:MOV AH,2 ; CHARACTER OUTPUT FUNCTION
        MOV DL,AL ; CHARACTER MUST BE IN DL
```

```
        INT 21H ; DISPLAY THE CHARACTER
        LOOP L1 ; REPEAT LOOP
        MOV Ah,4CH
        INT 21H
CODE ENDS
end start
```

Float Add

```
=========
ASSUME      CS:CODESEG, DS:DATASEG
; -------------------------------------------------------------
DATASEG     SEGMENT                     ; start of data segment
        ORG     00H             ; directive to assign an offset address for a variable
X       DD      20.4375
        ORG     10H
Y       DD      20.4375
        ORG     20H
SUM     DD      ?
DATASEG     ENDS                    ; end of data segment
```

```
; ------------------------------------------------------------

CODESEG     SEGMENT                     ; start of code segment

start:  MOV     AX,DATASEG      ; load the data segment address
        MOV     DS,AX           ; assign value to DS

        FINIT                   ; initialize 8087 stack
        FLD     X               ; load X into ST(0)
        FLD     Y               ; load Y into ST(0)

        FADD    ST(0),ST(1)     ; ST(0) = X+Y

        FST     SUM             ; store ST(0) in sum

        MOV     AH,4CH          ; setup function-4C of the int21
        INT     21H             ; call BIOS int21 to return to DOS



CODESEG     ENDS                    ; end of code segment
        END START
```

F

loat sub

=========

```
ASSUME          CS:CODESEG, DS:DATASEG
; ---------------------------------------------------------------
DATASEG         SEGMENT                         ; start of data segment
        ORG     00H             ; directive to assign an offset address for a variable
X       DD      20.4375
        ORG     10H
Y       DD      0.125
        ORG     20H
SUM     DD      ?
DATASEG         ENDS                    ; end of data segment

; ---------------------------------------------------------------

CODESEG         SEGMENT                         ; start of code segment

start:  MOV     AX,DATASEG      ; load the data segment address
        MOV     DS,AX           ; assign value to DS
```

```
        FINIT                   ; initialize 8087 stack
        FLD     Y               ; load X into ST(0)
        FLD     X               ; load Y into ST(0)

        FSUB    ST(0),ST(1)     ; ST(0) = X+Y

        FST     SUM             ; store ST(0) in sum

        MOV     AH,4CH          ; setup function-4C of the int21
        INT     21H             ; call BIOS int21 to return to DOS



CODESEG ENDS                    ; end of code segment
        END START
```

Largest

=========

```
assume cs:code,ds:data
data segment
        count db 00h
        numbers db 10 dup(0)
        result db 00h
data ends
code segment
    org 1000h
start:  mov ax,data
    mov ds,ax

        mov si,offset numbers
        mov cl,count

carry: mov al,[si]
other: inc si
        dec cl
        jz finish
nonzero:cmp al,[si]
        jc carry
        jmp other
finish: mov si,offset result
        mov [si],al
```

```
        mov ah,4ch
    int 21h
        code ends
end start
```

SUM of N

=========

```
assume cs:code,ds:data
data segment
        count db 00h
        numbers db 10 dup(?)
        carry db 00h
        result db 00h
data ends
code segment
    org 1000h
start:  mov ax,data
    mov ds,ax
```

```
        mov cl,00h
        mov ax,0000h
        mov dl,count
        mov si,offset numbers
nozero:add al,[si]
        jnc nocarry
        inc cl
nocarry:inc si
        dec dl
        jnz nozero
        mov si,offset result
        mov [si],al
        mov si,offset carry
        mov [si],cl


        mov ah,4ch
    int 21h
        code ends
end start
```

ODD EVEN

=========

```
assume cs:code,ds:data
data segment
        count db 00h
        numbers db 10 dup(0)
        oddcount db 00h
        evencount db 00h
data ends
code segment
    org 1000h
start:  mov ax,data
    mov ds,ax

        mov si,offset numbers
        mov cl,count
        mov ax,0000h
        mov bl,00h
        mov bh,02h
        mov dl,00h
        inc cl
scanlist:mov al,[si]
```

```
        inc si
        dec cl
        jz store
        div bh
        or ah,00h
        jnz odd
        inc bl
        jmp scanlist
odd:    inc dl
        jmp scanlist
store:  mov si,offset evencount
        mov [si],bl
        mov si,offset oddcount
        mov [si],dl

        mov ah,4ch
    int 21h
        code ends
end start
```

Pass

====

```
assume cs:code,ds:data


data segment
    pass db "392001$"
    mes1 db "Password is correct!$"
    mes2 db "Password is incorrect!$"
    disp db "Password : $"
data ends


code segment
   org 0100H
start:
   MOV AX,data
   MOV DS,AX


   MOV AH,09H
   MOV DX,OFFSET disp
   INT 21H


   MOV BX,OFFSET pass
   MOV DI,0006H
```

```
L1: MOV AH,01H
    INT 21H
    MOV DH,AL
    MOV SI,000FH
  L3:
     MOV CX,9FFFH
     L2: LOOP L2
     DEC SI
     JNZ L3

    MOV AH,2
    MOV DL,08H
    INT 21H

    MOV AH,2
    MOV DL,2AH
    INT 21H

    CMP DH,[BX]
    JNE fail
    INC BX
    DEC DI
    JNZ L1

    CMP CX,0000H
```

```
    JNE fail
    MOV AH,2
    MOV DL,0AH
    INT 21H
    MOV AH,09H
    MOV DX,OFFSET mes1
    INT 21H
    JMP exit

fail: MOV AH,2
      MOV DL,0AH
      INT 21H
      MOV AH,09H
      MOV DX,OFFSET mes2
      INT 21H

exit: MOV AH,4CH
      INT 21H

      code ends
end start
```

String

======

```
DATA SEGMENT
MESSAGE DB "THIS IS THE STRING$"
DATA ENDS
CODE SEGMENT
ASSUME CS:CODE,DS:DATA
START:MOV AX,DATA
MOV DS,AX
MOV AH,9 ; DOS FUNCTION #9
MOV DX,OFFSET MESSAGE ; OFFSET OF THE STRING
INT 21H ; DISPLAY IT
MOV Ah,4CH
INT 21H
CODE ENDS
END START
```

SYSDATE

=======

```
assume cs:code,ds:data
data segment
```

```
        day db 01 dup(?)
        month db 01 dup(?)
        year db 02 dup(?)
data ends
code segment
      org 0100h
start:  mov ax,data
      mov ds,ax


   ;system date
;INT 21h /AH=2Ah - get system date;
;return:CX= year (1980-2099).DH= month. DL= day.AL= day of week (00h=Sunday)

        mov ah,2ah
      int 21h

mov si,offset day
      mov [si],dl

mov si,offset month
      mov [si],dh

mov si,offset year
      mov [si],cx
```

```
        mov ah,4ch
    int 21h
        code ends
end start
```

SYStime

=======

```
assume cs:code,ds:data
data segment
        hour db 01 dup(?)
        minute db 01 dup(?)
        second db 02 dup(?)
data ends
code segment
    org 0100h
start:  mov ax,data
    mov ds,ax

;  INT 21h/AH=2Ch- get system time;
```

```
;return:CH= hour.CL= minute.DH= second



        mov ah,2ch
    int 21h


mov si,offset hour
    mov [si],ch


mov si,offset minute
    mov [si],cl


mov si,offset second
    mov [si],dh


        mov ah,4ch
    int 21h
        code ends
end start
```