

Python: Recap IV

This notebook was generated in **pseudocode** mode.

Exercise 1: ASCII sum substring

Exercise Description

You are given a number N and a string S . In Python, a character can be converted to a numeric code (its ASCII representation) using the function `ord()`. For example, `ord('A')` is 65, `ord('B')` is 66, `ord('a')` is 97, `ord('1')` is 49, and so on.

Write a function `ascii_sum(N, S)` that returns `True` if S contains a substring whose **sum of ASCII codes** is exactly N , and `False` otherwise.

Example: if $N = 180$ and $S = \text{'CAB19'}$, the function must return `True` because there exists the substring `'AB1'` such that $\text{ord('A')} + \text{ord('B')} + \text{ord('1')} = 65 + 66 + 49 = 180$.

Your solution

```
def ascii_sum(N, S):  
    # iterate over all possible starting indices i in S  
    #   for each i, iterate over all possible ending indices j > i  
    #   take the substring S[i:j]  
    #   compute the sum of ord(letter) for each letter in the substring  
    #   if the sum is equal to N, return True  
    # if no substring has sum equal to N, return False  
pass
```

Test your solution

```
# Test case 1 (Example)  
N = 180  
S = 'CAB19'  
assert ascii_sum(N, S) is True  
  
# Test case 2  
N = 180  
S = 'CAB91'  
assert ascii_sum(N, S) is False  
  
# Test case 3  
N = 200  
S = 'Hello, World!'  
assert ascii_sum(N, S) is False  
  
# Test case 4  
N = 65 # ASCII code for 'A'  
S = 'ABCDEF'  
assert ascii_sum(N, S) is True
```

Debug your solution

The following cells contain code to generate links to Python Tutor for debugging your code when running the tests. **You need to first run the cell containing your solution code before running the cell containing the Python Tutor link.**

```
from IPython.display import HTML;import urllib.parse as u;HTML('<a href="https://pyth
```

Exercise 2: Flip if upper

Exercise Description

Write a function `my_function(s)` that receives a string `s` (a sentence where words are separated by whitespaces) and returns a new string built according to the following rule: if a word in `s` begins with an uppercase letter, then the word must be **reversed** in the new string; otherwise it must be left intact.

The order of the words between the input and the output string must not change. If the input string is empty, the function must return `None`.

Note: the examples include a trailing space at the end of the returned string.

Your solution

```
def my_function(s):  
    # if s is empty, return None  
    # otherwise, split s into words  
    # initialize an empty result string s_new  
    # for each word in the list:  
        # if the first character of the word is uppercase:  
            # append the reversed word plus a space to s_new  
        # else:  
            # append the word plus a space to s_new  
    # return s_new  
pass
```

Test your solution

```
# Test case 1 (Example)  
s = 'hello World'  
t = my_function(s)  
assert t == 'hello dlrow '  
  
# Test case 2  
s = ''  
t = my_function(s)  
assert t is None  
  
# Test case 3  
s = 'Python is AWESOME'  
t = my_function(s)  
assert t == 'nohtyP is EMOSEWA '  
  
# Test case 4
```

```
s = 'viva david parenzo'
t = my_function(s)
assert t == 'viva david parenzo '
```

Debug your solution

The following cells contain code to generate links to Python Tutor for debugging your code when running the tests. **You need to first run the cell containing your solution code before running the cell containing the Python Tutor link.**

```
from IPython.display import HTML;import urllib.parse as u;HTML('<a href="https://pyth
```

Exercise 3: Longest word in string

Exercise Description

Write a function `my_function(s)` that receives a string `s` (representing a sentence where words are separated by whitespaces) and returns the **longest word** in `s`.

If the input string is empty, the function must return `None`. If there are more than one longest words, the function must return the **first** one.

Your solution

```
def my_function(s):
    # if s is empty, return None
```

```
# split s into words
# initialize a variable to store the maximum length and longest word
# iterate over words:
    # if len(word) is greater than current max_length, update longest_word and max_length
# return longest_word
pass
```

Test your solution

```
# Test case 1 (Example)
s = 'This is an example sentence with some long words.'
assert my_function(s) == 'sentence'

# Test case 2
s = 'The quick brown fox jumps over the lazy dog.'
assert my_function(s) == 'quick'

# Test case 3
s = ''
assert my_function(s) is None

# Test case 4
s = 'Ragazzi ma se po senti Parento su lasette che fa il grande storico'
assert my_function(s) == 'Ragazzi'
```

Debug your solution

The following cells contain code to generate links to Python Tutor for debugging your code when running the tests. **You need to first run the cell containing your solution code before running the cell containing the Python Tutor link.**

```
from IPython.display import HTML;import urllib.parse as u;HTML('<a href="https://pyth
```

Exercise 4: Periodic String Group

Exercise Description

Write a function `my_function(X, Y, S)` that, given two integer values `X` and `Y` and a string `S` of length 1 (a character), returns a string with `Y` **groups** of characters. Each group consists of `X` copies of `S`. Groups are separated by `' - '`.

You can assume that `X` and `Y` are greater than or equal to 0. If `X == 0`, groups are empty and no `' - '` separators should be used (the function should return the empty string).

Hint: you can use the `*` operator to obtain sequences of equal characters, e.g., `'x' * 7 == 'xxxxxxx'`.

Your solution

```
def my_function(X, Y, S):  
    # initialize an empty string new_s  
    # if X == 0, return the empty string immediately  
    # for i from 0 to Y-2:  
        # append X * S and then '-' to new_s  
    # after the loop, append X * S one last time (without '-')  
    # return new_s  
    pass
```

Test your solution

```
# Test case 1 (Example)  
s1 = my_function(4, 2, 'A')  
assert s1 == 'AAAA-AAAA'  
  
# Test case 2  
s1 = my_function(1, 10, 'A')  
assert s1 == 'A-A-A-A-A-A-A-A-A-A'  
  
# Test case 3  
s1 = my_function(0, 5, 'A')  
assert s1 == ''  
  
# Test case 4  
s1 = my_function(3, 5, 'A')  
assert s1 == 'AAA-AAA-AAA-AAA-AAA'
```

Debug your solution

The following cells contain code to generate links to Python Tutor for debugging your code when running the tests. **You need to first run the cell containing your solution code before running the cell containing the Python Tutor link.**

```
from IPython.display import HTML;import urllib.parse as u;HTML('<a href="https://pyth
```

Exercise 5: Periodic String

Exercise Description

Write a function `my_function(X, Y, S)` that, given two integer values `X` and `Y` and a string `S` of length 1 (a character), returns a string with `X` characters `S` separated by `Y` characters `' - '`. You can assume that `X` and `Y` are greater than or equal to 0.

If `X == 1` no `' - '` characters should be added, independently of the value of `Y`.

Hint: you can use the `*` operator to obtain sequences of equal characters (e.g., `'x' * 7 == 'xxxxxxx'`).

Your solution

```
def my_function(X, Y, S):  
    # initialize an empty string new_s  
    # if X is not zero:  
        # for i from 0 to X-2:  
            # append S and then Y copies of ' - ' to new_s
```

```
        # append S one last time (without '-')
    # return new_s
    pass
```

Test your solution

```
# Test case 1 (Example)
s1 = my_function(3, 2, 'A')
assert s1 == 'A--A--A'

# Test case 2
s1 = my_function(1, 10, 'A')
assert s1 == 'A'

# Test case 3
s1 = my_function(0, 5, 'A')
assert s1 == ''

# Test case 4
s1 = my_function(4, 5, 'A')
assert s1 == 'A-----A-----A-----A'
```

Debug your solution

The following cells contain code to generate links to Python Tutor for debugging your code when running the tests. **You need to first run the cell containing your solution code before running the cell containing the Python Tutor link.**

```
from IPython.display import HTML;import urllib.parse as u;HTML('<a href="https://pyth
```

Exercise 6: Remove Char

Exercise Description

Write a function `my_function(S, C)` that, given as parameters a string `S` and another string `C` of length 1 (a character), returns a string `T` that is equal to `S` except that it contains **no occurrence** of character `C`.

Your solution

```
def my_function(S, C):  
    # initialize an empty string new_s  
    # for each letter in S:  
        # if the letter is not equal to C, append it to new_s  
    # return new_s  
    pass
```

Test your solution

```
# Test case 1 (Example)  
s = 'I study at Luiss'  
c = 's'  
t = my_function(s, c)  
assert t == 'I tudy at Lui'  
  
# Test case 2
```

```

s = 'xxxxxxo'
c = 'x'
t = my_function(s, c)
assert t == 'o'

# Test case 3
s = 'xxxxxxxx 000'
c = 'x'
t = my_function(s, c)
assert t == 'o 000'

# Test case 4
s = 'xxxxxxxxo'
c = 's'
t = my_function(s, c)
assert t == 'xxxxxxxxo'

```

Debug your solution

The following cells contain code to generate links to Python Tutor for debugging your code when running the tests. **You need to first run the cell containing your solution code before running the cell containing the Python Tutor link.**

```

from IPython.display import HTML;import urllib.parse as u;HTML('<a href="https://pyth

```

Exercise 7: Replace Substring

Exercise Description

Write a function `my_function(S, R, C)` that, given as parameters a string `S`, a string `R` and another string `C` of length 1 (a character), returns a string `T` that is equal to `S` except that each occurrence of character `C` is **replaced** by string `R`.

Your solution

```
def my_function(S, R, C):  
    # initialize an empty string new_s  
    # for each letter in S:  
        # if the letter is equal to C, append R to new_s  
        # otherwise, append the original letter to new_s  
    # return new_s  
    pass
```

Test your solution

```
# Test case 1 (Example)  
s = 'I study at Luiss'  
r = 'REPLACE'  
c = 's'  
t = my_function(s, r, c)  
assert t == 'I REPLACetudy at LuiREPLACEREPLACE'  
  
# Test case 2  
s = 'I REPLACEddd'  
r = 'REPLACE'  
c = 'D'
```

```

t = my_function(s, r, c)
assert t == 'I REPLACEddd'

# Test case 3
s = 'D'
r = 'REPLACE'
c = 'D'
t = my_function(s, r, c)
assert t == 'REPLACE'

# Test case 4
s = ''
r = 'REPLACE'
c = 'D'
t = my_function(s, r, c)
assert t == ''

```

Debug your solution

The following cells contain code to generate links to Python Tutor for debugging your code when running the tests. **You need to first run the cell containing your solution code before running the cell containing the Python Tutor link.**

```

from IPython.display import HTML;import urllib.parse as u;HTML('<a href="https://pyth

```

Exercise 8: Driving License

Exercise Description

Write a function `my_function(license_plate)` that validates a driving license plate format.

The function should return `True` if the license plate follows the correct format, and `False` otherwise.

A valid license plate must:

- Be exactly 7 characters long
- Have exactly 4 letters followed by exactly 3 digits
- All letters must be uppercase

For example: "ABCD123" is valid, but "ABC123", "ABCDE123", or "ABCD12" are not valid.

Your solution

```
# Write your solution here
```

Test your solution

```
# Test case 1 (Example)  
result = my_function("ABCD123")  
assert result == True  
  
# Test case 2  
result = my_function("ABC123")  
assert result == False
```

```
# Test case 3
result = my_function("ABCDE123")
assert result == False

# Test case 4
result = my_function("ABCD12")
assert result == False
```

Debug your solution

The following cells contain code to generate links to Python Tutor for debugging your code when running the tests. **You need to first run the cell containing your solution code before running the cell containing the Python Tutor link.**

```
from IPython.display import HTML;import urllib.parse as u;HTML('<a href="https://pyth
```

Exercise 9: Reverse Order

Exercise Description

Write a Python function `my_function(s)` that takes a string `s` as an argument and returns a new **list of words** that contains the words in `s` in reverse order.

For example, if `s = 'I love you'`, then `my_function(s)` should return `['you', 'love', 'I']`.

Hint: you can use the `split()` method to split the string into a list of words.

Your solution

```
def my_function(s):  
    # split the string into a list of words  
    # return the list of words in reverse order  
    pass
```

Test your solution

```
# Test case 1 (Example)  
s1 = 'I love you'  
assert my_function(s1) == ['you', 'love', 'I']  
  
# Test case 2  
s2 = 'The quick brown fox'  
assert my_function(s2) == ['fox', 'brown', 'quick', 'The']  
  
# Test case 3  
s3 = 'Hello World'  
assert my_function(s3) == ['World', 'Hello']  
  
# Test case 4  
s4 = 'Python is fun'  
assert my_function(s4) == ['fun', 'is', 'Python']
```

Debug your solution

The following cells contain code to generate links to Python Tutor for debugging your code when running the tests. **You need to first run the cell containing your solution code before running the cell containing the Python Tutor link.**

```
from IPython.display import HTML;import urllib.parse as u;HTML('<a href="https://pyth
```

Exercise 10: Alien race

Exercise Description

It's 2027. Earth has been invaded by three alien races: the Greys, the Reptilians, and the Annunaki. A running race is organized to decide which race will dominate. At the end of the race, a list is provided with the order in which the participants finished. Each element of the list is in the format participant- race.

The score of a race is determined by **adding the positions** of all its participants, and the race with the **lowest score** wins.

Write a function `my_function(order_of_arrival, race)` that calculates the score obtained by a specific race. Positions are 1-based (the first element has position 1). If the list does not include that race among the participants, the result should be 0.

Your solution

```
def my_function(order_of_arrival, race):  
    # initialize score to 0
```

```
# initialize position counter i to 0
# for each element in order_of_arrival:
    # increase i by 1 (this is the position)
    # split the element on '-' to extract the race
    # if the extracted race is equal to the given race:
        # add i to score
# return the final score (0 if race never appears)
pass
```

Test your solution

```
# Test case 1
order_of_arrival = ['Gix-Annunaki', 'Tom-Grey', 'XYZ-Reptilian', 'Alex-Annunaki', 'Ar
race = 'Annunaki'
assert my_function(order_of_arrival, race) == 22

# Test case 2
race = 'Grey'
assert my_function(order_of_arrival, race) == 26

# Test case 3
order_of_arrival = ['Gix-Annunaki', 'Tom-Grey', 'Alex-Annunaki', 'AngelFab-Grey', 'Mi
race = 'Reptilian'
assert my_function(order_of_arrival, race) == 0

# Test case 4
order_of_arrival = ['Gix-Annunaki', 'Tom-Grey', 'XYZ-Reptilian', 'Alex-Annunaki', 'Ar
race = 'Humans'
assert my_function(order_of_arrival, race) == 0
```

Debug your solution

The following cells contain code to generate links to Python Tutor for debugging your code when running the tests. **You need to first run the cell containing your solution code before running the cell containing the Python Tutor link.**

```
from IPython.display import HTML;import urllib.parse as u;HTML('<a href="https://pyth
```

Exercise 11: Remove numeric duplicates and sort

Exercise Description

Write a function `my_function(L)` that, given a list of numbers `L`, returns a new list containing the same numbers **without duplicates**.

The numbers in the output list must be sorted from the smallest to the largest. If the input list is empty, the function should return an empty list.

Your solution

```
def my_function(L):  
    # create an empty list to store unique numbers  
    # for each item in L:  
        # if the item is not already in the new list, append it  
    # sort the new list in ascending order
```

```
# return the new list
pass
```

Test your solution

```
# Test case 1 (Example)
assert my_function([10, 2, 3, 5, 2, 10, 3]) == [2, 3, 5, 10]

# Test case 2
assert my_function([]) == []

# Test case 3
assert my_function([1, 1, 1, 1, 1, 1]) == [1]

# Test case 4
assert my_function([1, -2, 3, -4, 5, -6, 7, -8, 9, -10] * 1000) == [-10, -8, -6, -4,
```

Debug your solution

The following cells contain code to generate links to Python Tutor for debugging your code when running the tests. **You need to first run the cell containing your solution code before running the cell containing the Python Tutor link.**

```
from IPython.display import HTML;import urllib.parse as u;HTML('<a href="https://pyth
```

Exercise 12: Euro To Dollars

Exercise Description

Write a function `my_function(L)` that is given a list `L` of numbers representing coins in euro. The function should return the **sum of the coins converted to dollars**, where 1 euro corresponds to 1.22 dollars.

If there are no items in the list, the function should return `0.0` (a float).

Your solution

```
def my_function(L):  
    # initialize a sum variable s to 0  
    # for each number n in L:  
        # convert n euros to dollars by multiplying by 1.22 and add to s  
    # return s (0.0 if the list is empty)  
    pass
```

Test your solution

```
# Test case 1 (Example)  
assert my_function([3, 2, 4]) == 10.98  
  
# Test case 2  
assert my_function([0, 0, 1]) == 1.22  
  
# Test case 3  
assert my_function([2, 5, 12]) == 23.18
```

```
# Test case 4
assert float(my_function([])) == 0.0
```

Debug your solution

The following cells contain code to generate links to Python Tutor for debugging your code when running the tests. **You need to first run the cell containing your solution code before running the cell containing the Python Tutor link.**

```
from IPython.display import HTML;import urllib.parse as u;HTML('<a href="https://pyth
```

Exercise 13: H-index

Exercise Description

The h -index is a common index to quantify the scientific impact of a researcher. For a given researcher, you are given a list papers of n integer numbers, where n is the number of papers. In position i you have the number of citations of the i -th paper.

The h -index is defined as the largest number h such that there are **at least h papers with at least h citations**.

Write a function `my_function(papers)` that returns the h -index of the researcher. You can assume the list contains only integers. If the input list is empty, the function must return `None`.

Your solution

```
def my_function(citations):  
    # get the number of papers n  
    # if n is 0, return None  
    # sort the citation list in descending order  
    # initialize h to 0  
    # for each index i from 0 to n-1:  
        # if citations_srt[i] is greater than or equal to i+1:  
            # increase h by 1  
    # return h  
    pass
```

Test your solution

```
# Test case 1 (Example)  
assert my_function([24, 2, 36, 2, 3]) == 3  
  
# Test case 2  
assert my_function([3, 0, 6, 1, 5]) == 3  
  
# Test case 3  
assert my_function([]) is None  
  
# Test case 4  
assert my_function([24, 6, 12, 36, 2, 2]) == 4
```

Debug your solution

The following cells contain code to generate links to Python Tutor for debugging your code when running the tests. **You need to first run the cell containing your solution code before running the cell containing the Python Tutor link.**

```
from IPython.display import HTML;import urllib.parse as u;HTML('<a href="https://pyth
```

Exercise 14: Km To Miles

Exercise Description

Write a function `my_function(L)` that is given a list `L` of numbers representing distances in kilometers. The function should return the **sum of the distances converted to miles**, where 1 kilometer corresponds to 0.62 miles.

If there are no items in the list, the function should return 0.

Your solution

```
def my_function(L):  
    # compute the sum over all items in L of item * 0.62  
    # return this sum (0 if the list is empty)  
    pass
```

Test your solution

```
# Test case 1 (Example)
assert my_function([3, 2, 4]) == 5.58

# Test case 2
assert my_function([3]) == 1.8599999999999999

# Test case 3
assert float(my_function([0])) == 0.0

# Test case 4
assert float(my_function([])) == 0.0
```

Debug your solution

The following cells contain code to generate links to Python Tutor for debugging your code when running the tests. **You need to first run the cell containing your solution code before running the cell containing the Python Tutor link.**

```
from IPython.display import HTML;import urllib.parse as u;HTML('<a href="https://pyth
```

Exercise 15: Name Ends With

Exercise Description

Write a function `my_function(L1, L2)` that takes two lists as parameters:

- each element in L1 is the name of a person,
- each element in L2 is a character (a string of length 1).

The function shall return a list L3 containing the persons whose name **ends with** a letter in L2. Elements in L3 should appear in the same order in which they appear in L1.

If L1 is empty or does not contain any person whose name ends with a letter in L2, then L3 must be an empty list.

Your solution

```
def my_function(L1, L2):  
    # create an empty list L3  
    # for each name in L1:  
        # for each letter in L2:  
            # if the name ends with that letter:  
                # append the name to L3  
                # break the inner loop to avoid duplicates  
    # return L3  
    pass
```

Test your solution

```
# Test case 1 (Example)  
assert my_function(["Giorgio", "Irene", "Antonio", "Carla"], ["o", "e"]) == ["Giorgio", "Irene"]  
  
# Test case 2  
assert my_function(["Giorgio", "Irene", "Antonio", "Carla"], ["e", "x"]) == ["Irene"]
```

```
# Test case 3
assert my_function(["Giorgio", "Irene", "Antonio", "Carlx"], ["e", "x"]) == ["Irene",

# Test case 4
assert my_function(["Giorgio", "Irene", "Antonio", "Carlx"], ["v", "z"]) == []
```

Debug your solution

The following cells contain code to generate links to Python Tutor for debugging your code when running the tests. **You need to first run the cell containing your solution code before running the cell containing the Python Tutor link.**

```
from IPython.display import HTML;import urllib.parse as u;HTML('<a href="https://pyth
```

Exercise 16: Nevio the Ironed

Exercise Description

"Nevio the Ironed" is a fervent gambler who has accumulated a series of debts with banks. He is ordered to repay the amounts owed. Nevio currently has in his pocket a winning_sum of money he just won by betting on a horse.

You are given a list debts where each element has the format 'amount-repaid':

- amount is an integer amount of money,
- repaid is 0 if the amount has **not** yet been settled and 1 if it has already been repaid.

Write a function `my_function(debts, winning_sum)` that returns `True` if Nevio can settle **all unpaid debts** using `winning_sum`, and `False` otherwise.

Your solution

```
def my_function(debts, winning_sum):  
    # iterate over each debt in debts  
    # if the last character is '0' (not repaid):  
        # subtract the numeric amount (everything except the last 2 characters) i  
    # after processing all debts, return True if winning_sum is >= 0, else False  
    pass
```

Test your solution

```
# Test case 1  
debts = ['300-1', '200-0', '100-0']  
winning_sum = 500  
assert my_function(debts, winning_sum) is True  
  
# Test case 2  
debts = ['500-0', '200-0', '100-1']  
winning_sum = 500  
assert my_function(debts, winning_sum) is False  
  
# Test case 3  
debts = ['500-0', '200-0', '100-1']  
winning_sum = 400  
assert my_function(debts, winning_sum) is False
```

```
# Test case 4
debts = ['500-0', '200-0', '100-1']
winning_sum = 300
assert my_function(debts, winning_sum) is False
```

Debug your solution

The following cells contain code to generate links to Python Tutor for debugging your code when running the tests. **You need to first run the cell containing your solution code before running the cell containing the Python Tutor link.**

```
from IPython.display import HTML;import urllib.parse as u;HTML('<a href="https://pyth
```

Exercise 17: No escape for Earth

Exercise Description

Some theories suggest the existence of a planet called Nibiru or Planet X. Scientists have identified a series of meteors approaching Earth. For each meteor, they recorded its radius and whether its trajectory is directed towards Earth.

Data are given in a list `data`, where each element has the format `'radius-trajectory'`:

- `radius` is a number,
- `trajectory` is `0` if it is **not** directed towards Earth, and `1` otherwise.

You are also given:

- circumference: the **maximum acceptable circumference** for a meteor,
- limit: the **maximum number of meteors** directed towards Earth that we can withstand.

Write a function `my_function(data, circumference, limit)` that returns:

- False if **any** meteor has circumference greater than `circumference`, or if the number of meteors with trajectory 1 is greater than `limit`,
- True otherwise.

You can use `math.pi` and the formula `circ = radius * radius * pi`.

Your solution

```
import math

def my_function(data, circumference, limit):
    # initialize a counter for meteors directed towards Earth to 0
    # for each entry in data:
        # split the string on '-' to get radius and trajectory
        # compute the circumference as radius * radius * math.pi
        # if this circumference is greater than the given circumference, return False
        # if trajectory is '1', increment the counter
    # after the loop, if the counter is greater than limit, return False
    # otherwise, return True
    pass
```

Test your solution

```
# Test case 1
data = ['100-1', '200-1', '300-0', '400-1', '500-0']
circumference = 400
limit = 2
assert my_function(data, circumference, limit) is False

# Test case 2
limit = 1
assert my_function(data, circumference, limit) is False

# Test case 3
limit = 3
assert my_function(data, circumference, limit) is False

# Test case 4
circumference = 3000000
limit = 4
assert my_function(data, circumference, limit) is True
```

Debug your solution

The following cells contain code to generate links to Python Tutor for debugging your code when running the tests. **You need to first run the cell containing your solution code before running the cell containing the Python Tutor link.**

```
from IPython.display import HTML; import urllib.parse as u; HTML('<a href="https://pyth
```

Exercise 18: Person and first letter

Exercise Description

Write a function `my_function(L1, L2)` that takes two lists as parameters:

- each element in list `L1` is the name of a person,
- each element in list `L2` is a character (a string of length 1).

The function shall return a list `L3` containing the persons whose name **begins with** a letter in `L2`. Elements in `L3` should appear in the same order in which they appear in `L1`.

If `L1` is empty or does not contain persons whose name begins with a letter in `L2`, then `L3` must be an empty list.

Your solution

```
def my_function(L1, L2):  
    # create an empty result list L3  
    # for each name in L1:  
        # take the first character of the name  
        # if this character is in L2, append the name to L3  
    # return L3  
    pass
```

Test your solution

```
# Test case 1 (Example)
assert my_function(['Giorgio', 'Irene', 'Antonio', 'Giuseppe'], ['I', 'G']) == ['Gior

# Test case 2
assert my_function(['Giorgio', 'Mino', 'Antonio', 'Marco'], ['I', 'M']) == ['Mino', '

# Test case 3
assert my_function(['Giorgio', 'Mino', 'Antonio', 'Marco'], ['I', 'S']) == []

# Test case 4
assert my_function([], ['I', 'M']) == []
```

Debug your solution

The following cells contain code to generate links to Python Tutor for debugging your code when running the tests. **You need to first run the cell containing your solution code before running the cell containing the Python Tutor link.**

```
from IPython.display import HTML; import urllib.parse as u; HTML('<a href="https://pyth
```

Exercise 19: Products of Elements

Exercise Description

Write a function `my_function(L1, L2)` that takes as parameters two lists of integer numbers.

The function shall return an empty list if `L1` and `L2` are empty **or** do not have the same length. Otherwise, it shall return a list `L3` containing the products of elements in the same position in `L1` and `L2`.

Your solution

```
def my_function(L1, L2):  
    # create an empty list L3  
    # if both lists are empty, return L3  
    # if the two lists have different lengths, return L3  
    # otherwise, for each index i in the range of the list length:  
        # compute L1[i] * L2[i] and append it to L3  
    # return L3  
    pass
```

Test your solution

```
# Test case 1 (Example)  
assert my_function([10, 20, 30], [100, 200, 300]) == [1000, 4000, 9000]  
  
# Test case 2  
assert my_function([10, 30], [100, 300]) == [1000, 9000]  
  
# Test case 3  
assert my_function([10, 30, 15], [100, 300]) == []
```

```
# Test case 4
assert my_function([], []) == []
```

Debug your solution

The following cells contain code to generate links to Python Tutor for debugging your code when running the tests. **You need to first run the cell containing your solution code before running the cell containing the Python Tutor link.**

```
from IPython.display import HTML;import urllib.parse as u;HTML('<a href="https://pyth
```

Exercise 20: Remove duplicates (strings)

Exercise Description

Define a function `my_function(lst)` that takes a list of strings `lst` as input.

The function shall return a list containing the same elements of `lst`, but **without duplicates**: if a string `s` appears more than once in `lst`, only the **first** occurrence of `s` should be copied to the output list.

If the input list `lst` is empty, the function should return an empty list.

Your solution

```
def my_function(lst):  
    # create an empty output list  
    # for each item in lst:  
        # if the item is not already in output, append it  
    # return the output list  
    pass
```

Test your solution

```
# Test case 1 (Example)  
a = ['a', 'good', 'day', 'is', 'good', 'a', 'bad', 'day', 'is', 'not', 'good']  
assert my_function(a) == ['a', 'good', 'day', 'is', 'bad', 'not']  
  
# Test case 2  
a = ['test', 'test', 'test', 'test', 'test', 'test', 'test', 'test']  
assert my_function(a) == ['test']  
  
# Test case 3  
a = ['test', 'test', 'hello', 'test', 'hello', 'test', 'hello', 'test']  
assert my_function(a) == ['test', 'hello']  
  
# Test case 4  
a = []  
assert my_function(a) == []
```

Debug your solution

The following cells contain code to generate links to Python Tutor for debugging your code when running the tests. **You need to first run the cell containing your solution code**

before running the cell containing the Python Tutor link.

```
from IPython.display import HTML;import urllib.parse as u;HTML('<a href="https://pyth
```

Exercise 21: Reptilians

Exercise Description

The Reptilians are among us! An intelligence agency has revealed that many presidents of the world's nations are actually clones controlled by the Reptilians. The clones have specific characteristics:

- They have odd-length names.
- They have light-colored eyes.
- They are over 40 years old.

Each president is represented as a string in the format 'name-eyes-age', where eyes can be either 'light' or 'dark'.

Write a function `my_function(presidents)` that returns the number of presidents that are clones according to the rules above.

Your solution

```
def my_function(presidents):  
    # initialize a counter to 0  
    # for each president in the list:  
        # split the string on '-' to get name, eyes, and age  
        # check if the length of the name is odd  
        # check if eyes == 'light'  
        # check if age converted to int is greater than 40  
        # if all conditions are satisfied, increment the counter  
    # return the counter  
pass
```

Test your solution

```
# Test cases 1  
presidents = ['John-light-45', 'George-dark-54', 'Barack-dark-55', 'Bill-light-68', 'F  
assert my_function(presidents) == 1  
  
# Test cases 2  
presidents = ['John-light-45', 'George-dark-54', 'Barack-dark-55', 'Bill-light-68', 'F  
assert my_function(presidents) == 2  
  
# Test cases 3  
presidents = ['John-light-40', 'George-dark-54', 'Barack-dark-55', 'Bill-dark-68', 'F  
assert my_function(presidents) == 0  
  
# Test cases 4  
presidents = []  
assert my_function(presidents) == 0
```

Debug your solution

The following cells contain code to generate links to Python Tutor for debugging your code when running the tests. **You need to first run the cell containing your solution code before running the cell containing the Python Tutor link.**

```
from IPython.display import HTML;import urllib.parse as u;HTML('<a href="https://pyth
```

Exercise 22: Rugby betting scandal

Exercise Description

In New Zealand, a rugby betting scandal has erupted. Some players have placed bets on certain matches despite the rules prohibiting it. The rules forbid betting from any **illegal** platform, and there is also a maximum amount of money that can be spent on legal platforms.

The federation has gathered a list `bets` of bets placed by players, where each element has the format `'name-bet-illegal'`:

- `name` is the name of the rugby player,
- `bet` is the amount wagered (a float),
- `illegal` is 0 if the site was legal, and 1 otherwise.

Write a function `my_function(bets, player)` that returns `True` if the player should be **disqualified**, and `False` otherwise.

A player is disqualified if:

- they placed **any** bet on an illegal platform, or
- the **total** amount they bet on legal platforms exceeds 500.

Your solution

```
def my_function(bets, player):  
    # initialize total to 0  
    # for each bet in bets:  
        # split the string on '-'  
        # if the name matches the given player:  
            # if illegal flag is '1', return True immediately  
            # otherwise, add the bet amount to total  
    # after the loop, if total > 500, return True  
    # otherwise, return False  
    pass
```

Test your solution

```
# Test case 1  
bets = ['Beans-30.5-0', 'Beans-20.4-1', 'Tonal-50.5-1', 'Tonal-100.5-0', 'TheShara-21  
player = 'Beans'  
assert my_function(bets, player) is True  
  
# Test case 2  
player = 'Tonal'  
assert my_function(bets, player) is True  
  
# Test case 3
```

```
player = 'TheShara'
assert my_function(bets, player) is False

# Test case 4
player = 'Mikasa'
assert my_function(bets, player) is False
```

Debug your solution

The following cells contain code to generate links to Python Tutor for debugging your code when running the tests. **You need to first run the cell containing your solution code before running the cell containing the Python Tutor link.**

```
from IPython.display import HTML;import urllib.parse as u;HTML('<a href="https://pyth
```

Exercise 23: Subtract digit sum

Exercise Description

Write a function `subtract_digits(n)` that, given an integer number `n`, returns the number `d` obtained by **subtracting from `n` the sum of its digits**.

Hint: convert `n` into a string and work on each character, which corresponds to a digit.

Example: if `n = 12`, the function should return 9 because $12 - 1 - 2 = 9$.

Your solution

```
def subtract_digits(n):  
    # convert n to a string  
    # for each character (digit) in the string:  
        # convert the digit back to int and subtract it from n  
    # return the final value of n  
    pass
```

Test your solution

```
# Test case 1 (Example)  
assert subtract_digits(12) == 9  
  
# Test case 2  
assert subtract_digits(1038) == 1026  
  
# Test case 3  
assert subtract_digits(0) == 0  
  
# Test case 4  
assert subtract_digits(1199) == 1179
```

Debug your solution

The following cells contain code to generate links to Python Tutor for debugging your code when running the tests. **You need to first run the cell containing your solution code before running the cell containing the Python Tutor link.**

```
from IPython.display import HTML;import urllib.parse as u;HTML('<a href="https://pyth
```

Exercise 24: Sum larger or equal 3

Exercise Description

Write a function `my_function(L)` that, given a list `L` of strings, returns the **sum of the lengths** of the strings whose length is **greater than or equal to 3**.

If there are no items in the list or no strings of length ≥ 3 , the function should return 0.

Your solution

```
def my_function(L):  
    # initialize a sum s to 0  
    # for each string in L:  
        # if the length of the string is >= 3:  
            # add its length to s  
    # return s  
    pass
```

Test your solution

```
# Test case 1 (Example)  
assert my_function(['luiss', 'row', 'a', 'bx']) == 8
```

```
# Test case 2
assert my_function(['a', 'a', 'a', 'a']) == 0

# Test case 3
assert my_function(['aa', 'aaaa', 'aaa', 'aaa']) == 10

# Test case 4
assert my_function([]) == 0
```

Debug your solution

The following cells contain code to generate links to Python Tutor for debugging your code when running the tests. **You need to first run the cell containing your solution code before running the cell containing the Python Tutor link.**

```
from IPython.display import HTML;import urllib.parse as u;HTML('<a href="https://pyth
```

Exercise 25: Sum of Even Squares

Exercise Description

Write a function `my_function(L)` that, given a list `L` of numbers, returns the **sum of the squares of the even numbers** contained in `L`.

If there are no items or no even numbers in the list, the function should return `0`.

Your solution

```
def my_function(L):  
    # if the list is empty, return 0  
    # build a list of even numbers from L  
    # if there are no even numbers, return 0  
    # otherwise, compute and return the sum of squares of the even numbers  
    pass
```

Test your solution

```
# Test case 1 (Example)  
assert my_function([2, 13, 8, 5]) == 68  
  
# Test case 2  
assert my_function([1, 3, 5, 7]) == 0  
  
# Test case 3  
assert my_function([3, 101, 9, 7, 4]) == 16  
  
# Test case 4  
assert my_function([]) == 0
```

Debug your solution

The following cells contain code to generate links to Python Tutor for debugging your code when running the tests. **You need to first run the cell containing your solution code before running the cell containing the Python Tutor link.**

```
from IPython.display import HTML;import urllib.parse as u;HTML('<a href="https://pyth
```

Exercise 26: Sum of all the odd

Exercise Description

You have an integer number n as input. Define a function `all_odd(n)` that returns the **sum of all odd integer numbers between 1 and n** , n included.

Your solution

```
def all_odd(n):  
    # initialize a counter c to 0  
    # loop i from 1 to n (inclusive)  
        # if i is even, skip it  
        # otherwise, add i to c  
    # return c  
    pass
```

Test your solution

```
# Test case 1 (Example)  
assert all_odd(7) == 16  
  
# Test case 2  
assert all_odd(6) == 9
```

```
# Test case 3
assert all_odd(100) == 2500

# Test case 4
assert all_odd(1000 * 1000) == 2500000000000
```

Debug your solution

The following cells contain code to generate links to Python Tutor for debugging your code when running the tests. **You need to first run the cell containing your solution code before running the cell containing the Python Tutor link.**

```
from IPython.display import HTML;import urllib.parse as u;HTML('<a href="https://pyth
```

Exercise 27: Valid votes

Exercise Description

You are given a list of votes `votes` and a candidate name `candidate`. Each vote is represented as a string in the format `'candidate-valid_vote'`, where `valid_vote` is either 0 or 1 (1 means the vote is valid).

Write a function `my_function(votes, candidate)` that **counts how many valid votes** (with `valid_vote == '1'`) the given candidate received and returns that count. The candidate may have received 0 votes.

Your solution

```
def my_function(votes, candidate):  
    # initialize valid_votes to 0  
    # for each vote in votes:  
        # split the vote on '-' to get candidate name and valid flag  
        # if the candidate name matches the given candidate and the flag is '1':  
            # increment valid_votes  
    # return valid_votes  
    pass
```

Test your solution

```
# Test case 1  
votes = ['A-1', 'A-0', 'B-1', 'B-1', 'C-0', 'A-1', 'C-1', 'D-0']  
assert my_function(votes, 'A') == 2  
  
# Test case 2  
votes = ['A-0', 'B-1', 'C-1', 'D-1', 'E-0', 'F-1', 'G-1', 'H-0']  
assert my_function(votes, 'H') == 0
```

```
# Test case 3
votes = ['A-1', 'B-1', 'C-1', 'D-1', 'E-1', 'F-1', 'G-1', 'H-1']
assert my_function(votes, 'A') == 1

# Test case 4
votes = ['A-0', 'B-0', 'C-0', 'D-0', 'E-0', 'F-0', 'G-0', 'H-0']
assert my_function(votes, 'A') == 0
```

Debug your solution

The following cells contain code to generate links to Python Tutor for debugging your code when running the tests. **You need to first run the cell containing your solution code before running the cell containing the Python Tutor link.**

```
from IPython.display import HTML;import urllib.parse as u;HTML('<a href="https://pyth
```

Exercise 28: Vowels

Exercise Description

You have a string `a` as input, along with two integer numbers `s` and `e`. Define a function `my_function(a, s, e)` that returns **how many vowels** are in the substring starting at position `s` and ending at position `e` (both included).

Consider the vowels `a, e, i, o, u` in both lowercase and uppercase.

Your solution

```
def my_function(a, s, e):  
    # take the substring from index s to e (inclusive)  
    # convert the substring to lowercase  
    # initialize a counter c to 0  
    # for each letter in the substring:  
        # if the letter is one of 'a', 'e', 'i', 'o', 'u', increment c  
    # return c  
    pass
```

Test your solution

```
# Test case 1 (Example)  
a = 'I study at Luiss'  
assert my_function(a, 0, 15) == 5  
  
# Test case 2  
a = 'aaccocoa'  
assert my_function(a, 0, 7) == 4  
  
# Test case 3  
a = 'AAAAmmm'  
assert my_function(a, 4, 6) == 0  
  
# Test case 4  
a = 'xyz rtw lpq'  
assert my_function(a, 1, 7) == 0
```

Debug your solution

The following cells contain code to generate links to Python Tutor for debugging your code when running the tests. **You need to first run the cell containing your solution code before running the cell containing the Python Tutor link.**

```
from IPython.display import HTML;import urllib.parse as u;HTML('<a href="https://pyth
```

Exercise 29: Aggregate Address

Exercise Description

Write a function `my_function(addresses)` that aggregates addresses by town.

`addresses` is a list of tuples, where each tuple has two string elements: `(town, street_name)`. For example, it could be `addresses = [('Roma', 'Via Panama'), ('Roma', 'Viale Romania'), ('Milano', 'Corso Sempione')]`.

The function shall return a dictionary that maps each town to the number of addresses in that town from the input list. If the input list is empty, the function should return an empty dictionary.

Your solution

```
# Define function my_function that takes parameters: addresses    # Initialize aggreg
```

Test your solution

```
# Test case 1 (Example)
a = my_function([('Roma', 'Via Panama'), ('Roma', 'Viale Romania'), ('Milano', 'Corso')])
assert a == {'Roma': 2, 'Milano': 1}

# Test case 2
a = my_function([('Londra', 'Via Panama'), ('Milano', 'Viale Romania'), ('Milano', 'Corso')])
assert a == {'Londra': 1, 'Milano': 2}

# Test case 3
a = my_function([])
assert a == {}

# Test case 4
a = my_function([('Firenze', 'Via Panama'), ('Como', 'Viale Romania'), ('Napoli', 'Corso')])
assert a == {'Firenze': 1, 'Como': 1, 'Napoli': 1}
```

Debug your solution

The following cells contain code to generate links to Python Tutor for debugging your code when running the tests. **You need to first run the cell containing your solution code before running the cell containing the Python Tutor link.**

```
from IPython.display import HTML;import urllib.parse as u;HTML('<a href="https://pyth
```

Exercise 30: Deck

Exercise Description

Write a function `my_function(deck)` that processes a deck of cards represented as a dictionary.

The `deck` parameter is a dictionary where keys are card names (strings) and values are the number of cards of that type. The function should return a new dictionary containing only the cards that appear more than once in the deck.

If no cards appear more than once, return an empty dictionary.

Your solution

```
# Define function my_function that takes parameters: deck, points    # # do not iterate
```

Test your solution

```
# Test case 1 (Example)  
a = my_function(['Q', '6', 'A', '8'], {'A': 1, '8': 8, 'J': 11, 'Q': 12, 'K': 13})  
# assert a == expected_result # TODO: Add expected result  
  
# Test case 2  
a = my_function(['Q', '6', 'A'], {'8': 8, 'J': 11, 'Q': 12, 'K': 13})  
# assert a == expected_result # TODO: Add expected result  
  
# Test case 3
```

```
a = my_function([], {'A': 1, '8': 8, 'J': 11, 'Q': 12, 'K': 13})
# assert a == expected_result # TODO: Add expected result

# Test case 4
a = my_function(['Q', '6', 'A', '8'], {'K': 1, 'J': 11, '3': 3, '2': 13})
# assert a == expected_result # TODO: Add expected result
```

Debug your solution

The following cells contain code to generate links to Python Tutor for debugging your code when running the tests. **You need to first run the cell containing your solution code before running the cell containing the Python Tutor link.**

```
from IPython.display import HTML;import urllib.parse as u;HTML('<a href="https://pyth
```

Exercise 31: Dict Game 1

Exercise Description

Let D be a dictionary whose keys are words (strings) and whose corresponding values are integer numbers. Further, let L be a list of words.

Write a function `my_function(D, L)` that, given as input a dictionary D and a list L , returns the sum of the lengths of the words in the dictionary that satisfy the following requirements:

- The word must be present in the list
- The word must contain at least 1 uppercase character
- The value associated with the word must be an even number

If the input list is empty, the function must return 0.

Your solution

```
# Define function checkUppercase that takes parameters: word      # Set uppercase to t
```

Test your solution

```
# Test case 1 (Example)
D = {"Sara" : 8, "Mara" : 3}
L = ["Alessio", "Sara", "Giorgio", "Mara"]
result = my_function(D, L)
assert result == 4

# Test case 2
D = {"Sara" : 8, "ilaria" : 4}
L = ["Alessio", "Sara", "Giorgio", "Mara", "ilaria"]
result = my_function(D, L)
assert result == 4

# Test case 3
D = {"Sara" : 8, "Ilaria" : 4}
L = ["Alessio", "Sara", "Giorgio", "Mara", "Ilaria"]
result = my_function(D, L)
assert result == 10
```



```
# Test case 4
D = {"Sara" : 8, "Ilaria" : 7}
L = []
result = my_function(D, L)
assert result == 0
```

Debug your solution

The following cells contain code to generate links to Python Tutor for debugging your code when running the tests. **You need to first run the cell containing your solution code before running the cell containing the Python Tutor link.**

```
from IPython.display import HTML;import urllib.parse as u;HTML('<a href="https://pyth
```

Exercise 32: Dict Game 2

Exercise Description

Let D be a dictionary whose keys are words (strings) and whose corresponding values are integer numbers. Further, let L be a list of words.

Write a function `my_function(D, L)` that, given as input a dictionary D and a list L , returns the sum of the lengths of the words in the dictionary that satisfy the following requirements:

- The word must be present in the list
- The word must contain at least 1 uppercase character
- The value associated with the word must be an even number

If the input list is empty, the function must return 0.

Your solution

```
# Define function my_function that takes parameters: D,L    # Initialize count to zero
```

Test your solution

```
# Test case 1 (Example)
D = {"Sara" : 8, "Mara" : 3}
L = ["Alessio", "Sara", "Giorgio", "Mara"]
result = my_function(D, L)
assert result == 4

# Test case 2
D = {"Sara" : 8, "ilaria" : 4}
L = ["Alessio", "Sara", "Giorgio", "Mara", "ilaria"]
result = my_function(D, L)
assert result == 4

# Test case 3
D = {"Sara" : 8, "Ilaria" : 4}
L = ["Alessio", "Sara", "Giorgio", "Mara", "Ilaria"]
result = my_function(D, L)
assert result == 10
```

```
# Test case 4
D = {"Sara" : 8, "Ilaria" : 7}
L = []
result = my_function(D, L)
assert result == 0
```

Debug your solution

The following cells contain code to generate links to Python Tutor for debugging your code when running the tests. **You need to first run the cell containing your solution code before running the cell containing the Python Tutor link.**

```
from IPython.display import HTML;import urllib.parse as u;HTML('<a href="https://pyth
```

Exercise 33: Dict Game 3

Exercise Description

Let D be a dictionary whose keys are words (strings) and whose corresponding values are dates. Further, let L be a list of words and let A and B be two `datetime.date` objects where $A < B$ (or A comes before B).

Write a function `my_function(D, L, A, B)` that, given as input a dictionary D , a list L and the two date objects A and B , returns the number of words (keys) in the dictionary that satisfy the following requirements:

- The word must be present in the list
- The word must contain at least one uppercase letter
- The date associated with the word must be between A and B

If the input list is empty, the function must return 0.

Hint: Remember that it is possible to use the common operators for comparison (e.g., <, >, ==) on date objects.

Recall: To use the datetime module in your code, please make sure to import it before the def of your function.

Your solution

```
# Execute: import datetime# Define function checkUppercase that takes parameters: word
```

Test your solution

```
# Test case 1 (Example)
import datetime
D = {
    "apple": datetime.date(2023, 3, 15),
    "Banana": datetime.date(2023, 4, 10),
    "Orange": datetime.date(2022, 12, 5),
    "Grapes": datetime.date(2023, 5, 20),
}
L = ["apple", "Banana", "Cherry", "Grapes"]
A = datetime.date(2023, 1, 1)
```

```
B = datetime.date(2023, 6, 30)
result = my_function(D, L, A, B)
assert result == 2
```

Test case 2

```
D = {
    "Hello": datetime.date(2023, 3, 15),
    "World": datetime.date(2023, 4, 10),
    "Python": datetime.date(2022, 12, 5),
    "Programming": datetime.date(2023, 5, 20),
}
L = ["Hello", "Programming", "AI", "MachineLearning"]
A = datetime.date(2023, 1, 1)
B = datetime.date(2023, 6, 30)
result = my_function(D, L, A, B)
assert result == 2
```

Test case 3

```
D = {
    "Car": datetime.date(2023, 3, 15),
    "Bus": datetime.date(2023, 4, 10),
    "Bicycle": datetime.date(2022, 12, 5),
    "Train": datetime.date(2023, 5, 20),
}
L = ["Car", "Bus", "Bicycle", "Train"]
A = datetime.date(2023, 3, 1)
B = datetime.date(2023, 4, 30)
result = my_function(D, L, A, B)
assert result == 2
```

Test case 4

```
D = {
    "Sun": datetime.date(2023, 3, 15),
    "Moon": datetime.date(2023, 4, 10),
    "Stars": datetime.date(2022, 12, 5),
    "Planets": datetime.date(2023, 5, 20),
}
L = ["Sun", "Moon", "Stars", "Planets"]
A = datetime.date(2024, 1, 1)
B = datetime.date(2024, 6, 30)
result = my_function(D, L, A, B)
assert result == 0
```

Debug your solution

The following cells contain code to generate links to Python Tutor for debugging your code when running the tests. **You need to first run the cell containing your solution code before running the cell containing the Python Tutor link.**

```
from IPython.display import HTML;import urllib.parse as u;HTML('<a href="https://pyth
```

Exercise 34: Dict Game 4

Exercise Description

Let D be a dictionary whose keys are words (strings) and whose corresponding values are integer numbers. Further, let L be a list of words.

Write a function `my_function(D, L)` that, given as input a dictionary `D` and a list `L`, returns the sum of the lengths of the words in the dictionary that satisfy the following requirements:

- The word must be present in the list
- The word must contain at least 1 uppercase character
- The value associated with the word must be an even number

If the input list is empty, the function must return 0.

Your solution

```
# Define function my_function that takes parameters: D, L      # Initialize count to zero
```

Test your solution

```
# Test case 1 (Example)
D = {"Sara" : 8, "Mara" : 3}
L = ["Alessio", "Sara", "Giorgio", "Mara"]
result = my_function(D, L)
assert result == 4

# Test case 2
D = {"Sara" : 8, "ilaria" : 4}
L = ["Alessio", "Sara", "Giorgio", "Mara", "ilaria"]
result = my_function(D, L)
assert result == 4

# Test case 3
D = {"Sara" : 8, "Ilaria" : 4}
```

```
L = ["Alessio", "Sara", "Giorgio", "Mara", "Ilaria"]
result = my_function(D, L)
assert result == 10

# Test case 4
D = {"Sara" : 8, "Ilaria" : 7}
L = []
result = my_function(D, L)
assert result == 0
```

Debug your solution

The following cells contain code to generate links to Python Tutor for debugging your code when running the tests. **You need to first run the cell containing your solution code before running the cell containing the Python Tutor link.**

```
from IPython.display import HTML;import urllib.parse as u;HTML('<a href="https://pyth
```

Exercise 35: Dict Game 5

Exercise Description

Let D be a dictionary whose keys are words (strings) and whose corresponding values are integer numbers. Further, let L be a list of words.

Write a function `my_function(D, L)` that, given as input a dictionary `D` and a list `L`, returns the sum of the lengths of the words in the dictionary that satisfy the following requirements:

- The word must be present in the list
- The word must contain at least 1 uppercase character
- The value associated with the word must be an even number

If the input list is empty, the function must return 0.

Your solution

```
# Define function my_function that takes parameters: D, L      # Initialize s to zero
```

Test your solution

```
# Test case 1 (Example)
D = {"Sara" : 8, "Mara" : 3}
L = ["Alessio", "Sara", "Giorgio", "Mara"]
result = my_function(D, L)
assert result == 4

# Test case 2
D = {"Sara" : 8, "ilaria" : 4}
L = ["Alessio", "Sara", "Giorgio", "Mara", "ilaria"]
result = my_function(D, L)
assert result == 4

# Test case 3
D = {"Sara" : 8, "Ilarla" : 4}
```

```
L = ["Alessio", "Sara", "Giorgio", "Mara", "Ilenia"]
result = my_function(D, L)
assert result == 10

# Test case 4
D = {"Sara" : 8, "Ilenia" : 7}
L = []
result = my_function(D, L)
assert result == 0
```

Debug your solution

The following cells contain code to generate links to Python Tutor for debugging your code when running the tests. **You need to first run the cell containing your solution code before running the cell containing the Python Tutor link.**

```
from IPython.display import HTML;import urllib.parse as u;HTML('<a href="https://pyth
```

Exercise 36: Encrypt

Exercise Description

Write a function `my_function(text, key)` that encrypts `text` using a simple substitution cipher.

The key parameter is a dictionary that maps each character to its encrypted replacement. The function should return the encrypted version of the input text.

If a character in the text is not found in the key dictionary, it should remain unchanged in the output.

Your solution

```
# Define function my_function that takes parameters: S,D
    # Set result to ''
    # For each el in S:
        # If el is in D:
            # Add the value to result +
        # Otherwise:
            # Add the value to result +
    # Return result
```

Test your solution

```
# Test case 1 (Example)
a = my_function("hvssm", {"v": "e", "t": "w", "s": "l", "m": "o"})
assert a == "hello"

# Test case 2
a = my_function("vtmx", {"v": "e", "t": "w", "s": "l", "m": "o"})
assert a == "ewox"

# Test case 3
a = my_function("xxxxqqqq", {"v": "e", "t": "w", "s": "l", "m": "o"})
assert a == "xxxxqqqq"
```

```
# Test case 4
a = my_function("", {"v": "e", "t": "w", "s": "l", "m": "o"})
assert a == ""
```

Debug your solution

The following cells contain code to generate links to Python Tutor for debugging your code when running the tests. **You need to first run the cell containing your solution code before running the cell containing the Python Tutor link.**

```
from IPython.display import HTML;import urllib.parse as u;HTML('<a href="https://pyth
```

Exercise 37: Football League

Exercise Description

Write a function `my_function(teams, results)` that calculates the points for each team in a football league.

Parameters:

- `teams`: A list of team names (strings)
- `results`: A list of tuples, where each tuple represents a match result: `(team1, team2, goals1, goals2)`

Scoring rules:

- Win: 3 points
- Draw: 1 point
- Loss: 0 points

The function should return a dictionary mapping each team name to their total points.

Your solution

```
# Define function my_function that takes parameters: matches    # Initialize teams as
```

Test your solution

```
# Test case 1 (Example)
teams = ["Team A", "Team B", "Team C"]
results = [("Team A", "Team B", 2, 1), ("Team B", "Team C", 0, 3), ("Team A", "Team C", 1, 1)]
result = my_function(teams, results)
assert result == {"Team A": 4, "Team B": 0, "Team C": 4}

# Test case 2
teams = ["Team X", "Team Y"]
results = [("Team X", "Team Y", 3, 0)]
result = my_function(teams, results)
assert result == {"Team X": 3, "Team Y": 0}

# Test case 3
teams = ["Team P", "Team Q", "Team R"]
results = [("Team P", "Team Q", 1, 1), ("Team Q", "Team R", 2, 0), ("Team P", "Team R", 1, 1)]
result = my_function(teams, results)
assert result == {"Team P": 3, "Team Q": 0, "Team R": 0}
```

```
result = my_function(teams, results)
assert result == {"Team P": 1, "Team Q": 1, "Team R": 3}

# Test case 4
teams = []
results = []
result = my_function(teams, results)
assert result == {}
```

Debug your solution

The following cells contain code to generate links to Python Tutor for debugging your code when running the tests. **You need to first run the cell containing your solution code before running the cell containing the Python Tutor link.**

```
from IPython.display import HTML;import urllib.parse as u;HTML('<a href="https://pyth
```

Exercise 38: Morse Code

Exercise Description

Write a function `my_function(text)` that converts text to Morse code.

The function should convert each letter in the input text to its corresponding Morse code representation and return the result as a string with Morse code symbols separated by spaces.

Use the standard International Morse Code alphabet. If the input is empty, return an empty string.

Your solution

```
# Define function my_function that takes parameters: s, morse_dict    # Execute: ""
```

Test your solution

```
# Test case 1 (Example)  
result = my_function("HELLO")  
assert result == ". . . . . . - . . . - - -"  
  
# Test case 2  
result = my_function("SOS")  
assert result == "... - - - ..."  
  
# Test case 3  
result = my_function("A")  
assert result == ". -"  
  
# Test case 4  
result = my_function("")  
assert result == ""
```

Debug your solution

The following cells contain code to generate links to Python Tutor for debugging your code when running the tests. **You need to first run the cell containing your solution code**

before running the cell containing the Python Tutor link.

```
from IPython.display import HTML;import urllib.parse as u;HTML('<a href="https://pyth
```

Exercise 39: Musical Albums

Exercise Description

Write a function `my_function(albums, year)` that filters musical albums by release year.

The `albums` parameter is a list of tuples, where each tuple represents an album: `(title, artist, year, tracks)`.

The function should return a list containing only the albums that were released in the specified year, maintaining the original order.

Your solution

```
# Define function my_function that takes parameters: L, S    # # check if L is empty,
```

Test your solution

```
# Test case 1 (Example)  
albums = [("Album A", "Artist 1", 2020, 10), ("Album B", "Artist 2", 2019, 8)]  
result = my_function(albums, 2019)  
assert result == [("Album B", "Artist 2", 2019, 8)]
```



```
# Test case 2
albums = [("Album X", "Artist X", 2021, 12), ("Album Y", "Artist Y", 2021, 9)]
result = my_function(albums, 2021)
assert result == [("Album X", "Artist X", 2021, 12), ("Album Y", "Artist Y", 2021, 9)]

# Test case 3
albums = [("Album P", "Artist P", 2018, 7)]
result = my_function(albums, 2020)
assert result == []

# Test case 4
albums = []
result = my_function(albums, 2022)
assert result == []
```

Debug your solution

The following cells contain code to generate links to Python Tutor for debugging your code when running the tests. **You need to first run the cell containing your solution code before running the cell containing the Python Tutor link.**

```
from IPython.display import HTML;import urllib.parse as u;HTML('<a href="https://pyth
```

Exercise 40: Planet 4z Mission Cost

Exercise Description

Write a function `my_function(supplies, costs)` that calculates the total cost of supplies for a mission to Planet 4z.

Parameters:

- `supplies`: A dictionary mapping supply names to quantities needed
- `costs`: A dictionary mapping supply names to cost per unit

The function should return the total cost by multiplying the quantity of each supply by its unit cost and summing all costs.

If a supply is needed but has no cost information, or if a cost is given for a supply that's not needed, ignore it in the calculation.

Your solution

```
# Define function my_function that takes parameters: humans    # Initialize cost to 0
```

Test your solution

```
# Test case 1 (Example)
supplies = {"water": 100, "food": 50, "fuel": 200}
costs = {"water": 10, "food": 20, "fuel": 5}
result = my_function(supplies, costs)
assert result == 3000

# Test case 2
supplies = {"oxygen": 150, "tools": 25}
```

```
costs = {"oxygen": 8, "tools": 40}
result = my_function(supplies, costs)
assert result == 2200

# Test case 3
supplies = {}
costs = {"item": 10}
result = my_function(supplies, costs)
assert result == 0

# Test case 4
supplies = {"item1": 10, "item2": 20}
costs = {}
result = my_function(supplies, costs)
assert result == 0
```

Debug your solution

The following cells contain code to generate links to Python Tutor for debugging your code when running the tests. **You need to first run the cell containing your solution code before running the cell containing the Python Tutor link.**

```
from IPython.display import HTML;import urllib.parse as u;HTML('<a href="https://pyth
```

Exercise 41: Shopping By Quantity

Exercise Description

Shopping by Quantity

Write a function `my_function(cart, inventory)` that processes a shopping cart based on available inventory quantities.

Parameters:

- `cart`: A dictionary mapping item names to desired quantities
- `inventory`: A dictionary mapping item names to available quantities

The function should return a dictionary showing the actual quantities that can be purchased (limited by inventory availability).

Your solution

```
# Define function my_function that takes parameters: prices, cart    # If len(cart) =
```

Test your solution

```
# Test case 1 (Example)  
a = my_function([('cookies', 4.2), ('pasta', 3.0), ('eggs', 3.2), ('milk', 2.3)], {'p  
# assert a == expected_result # TODO: Add expected result  
  
# Test case 2  
a = my_function([('cookies', 4.2), ('orange', 1.0), ('eggs', 3.2), ('milk', 2.3)], {'  
# assert a == expected_result # TODO: Add expected result
```

```
# Test case 3
a = my_function([('cookies', 4.2), ('orange', 1.0), ('bacon', 3.2), ('milk', 2.3)], {
# assert a == expected_result # TODO: Add expected result

# Test case 4
a = my_function([('cookies', 4.2), ('orange', 1.0), ('bacon', 3.2), ('milk', 2.3)], {
```

Debug your solution

The following cells contain code to generate links to Python Tutor for debugging your code when running the tests. **You need to first run the cell containing your solution code before running the cell containing the Python Tutor link.**

```
from IPython.display import HTML;import urllib.parse as u;HTML('<a href="https://pyth
```

Exercise 42: Shopping By Prices

Exercise Description

Shopping by Prices

Write a function `my_function(cart, prices)` that calculates the total cost of items in a shopping cart.

Parameters:

- cart: A dictionary mapping item names to quantities
- prices: A dictionary mapping item names to unit prices

The function should return the total cost by multiplying the quantity of each item by its unit price and summing all costs.

Your solution

```
# Define function my_function that takes parameters: shopping_cart, prices    # Init:
```

Test your solution

```
# Test case 1 (Example)
a = my_function([('pasta', 3), ('milk', 2), ('cookies', 4)], {'pasta': 0.69, 'milk':
# assert a == expected_result # TODO: Add expected result

# Test case 2
a = my_function([('orange', 1), ('cookies', 10)], {'cookies': 0.69, 'milk': 1.19, 'eg
# assert a == expected_result # TODO: Add expected result

# Test case 3
a = my_function([('orange', 1)], {'cookies': 0.69, 'milk': 1.19, 'eggs': 0.79, 'brea
# assert a == expected_result # TODO: Add expected result

# Test case 4
a = my_function([], {'cookies': 0.69, 'milk': 1.19, 'eggs': 0.79, 'bread': 1.99, 'ora
```

Debug your solution

The following cells contain code to generate links to Python Tutor for debugging your code when running the tests. **You need to first run the cell containing your solution code before running the cell containing the Python Tutor link.**

```
from IPython.display import HTML;import urllib.parse as u;HTML('<a href="https://pyth
```

Exercise 43: Wallet

Exercise Description

Write a function `my_function(wallet, price)` that computes the total value inside the wallet in Euro.

Parameter `wallet` is a list of tuples `(currency, quantity)`, where `currency` is a string and `quantity` is a number: for example, `wallet` could be `[("gbp", 3), ("dollar", 2), ("gbp", 4)]`.

Parameter `price` is a dictionary that maps the conversion of different currencies in euro (1 euro), for example `{"krona": 7.44, "dollar": 1.22, "gbp": 0.89, "real": 6.65}`.

You can assume that the currency in each item in the wallet appears as a key in the price dictionary.

The function shall return the total value in euro inside the wallet. If there are no items in the wallet, the function should return 0.

Back-of-the-envelope example: `my_function([("gbp", 2), ("dollar", 2)], {"krona": 7.44, "dollar": 1.22, "gbp": 0.89, "real": 6.65})` should return $4.22 = 2 \cdot 0.89 + 2 \cdot 1.22$.

Your solution

```
# Define function my_function that takes parameters: wallet, price  
# If wallet == []:  
    # Return 0  
# Otherwise:  
    # Initialize s to zero  
    # Execute: for currency, quantity in wallet:  
        # Add the value to s +  
    # Return s
```

Test your solution

```
# Test case 1 (Example)  
a = my_function([("gbp", 2), ("dollar", 2)], {"krona": 7.44, "dollar": 1.22, "gbp": 0.89, "real": 6.65})  
# assert a == expected_result # TODO: Add expected result  
  
# Test case 2  
a = my_function([("dollar", 2)], {"krona": 7.44, "dollar": 1.22, "gbp": 0.89, "real": 6.65})  
# assert a == expected_result # TODO: Add expected result  
  
# Test case 3  
a = my_function([("krona", 1), ("dollar", 2)], {"krona": 7.44, "dollar": 1.22, "gbp": 0.89, "real": 6.65})  
# assert a == expected_result # TODO: Add expected result
```



```
# Test case 4
a = my_function([], {"krona": 7.44, "dollar": 1.22, "gbp": 0.89, "real": 6.65})
# assert a == expected_result # TODO: Add expected result
```

Debug your solution

The following cells contain code to generate links to Python Tutor for debugging your code when running the tests. **You need to first run the cell containing your solution code before running the cell containing the Python Tutor link.**

```
from IPython.display import HTML;import urllib.parse as u;HTML('<a href="https://pyth
```

Exercise 44: Automatic writing

Exercise Description

Write a function `my_function(a, b)` that takes two lists:

- `a` is a list of characters, for example `['b', 'e', 'l', 'a']`
- `b` is a list of integers, for example `[1, 1, 2, 1]`

The function should behave as follows:

- If the two lists a and b have different lengths, the function returns -1.
- If there is at least one negative value in b, the function returns -1.
- Otherwise, the function returns a string containing the characters in a repeated as many times as the number specified in the corresponding position in b.

For example, `my_function(['b','e','l','a'], [1,1,2,1])` should return 'bella'.

Your solution

```
def my_function(a, b):  
    # check whether the two lists have different length: if so, return -1  
    # check whether there are some negative elements in b: if so, return -1  
    # if no returns have been triggered so far, then create the proper string  
    # initialize an empty string to accumulate the result  
    # iterate over the indices of the lists  
        # for each index, repeat the character in a[i] b[i] times and append to the result  
    # return the result string  
    pass
```

Test your solution

```
# Test case 1 (Example)  
assert my_function(['b','e','l','a'], [1,1,2,1]) == 'bella'  
  
# Test case 2  
assert my_function(['a','b','c'], [3,2,0]) == 'aaabb'  
  
# Test case 3  
assert my_function(['a','b','c'], [3,2,-1]) == -1
```

```
# Test case 4
assert my_function(['a', 'b', 'c'], [3,2,2,2]) == -1
```

Debug your solution

The following cells contain code to generate links to Python Tutor for debugging your code when running the tests. **You need to first run the cell containing your solution code before running the cell containing the Python Tutor link.**

```
from IPython.display import HTML;import urllib.parse as u;HTML('<a href="https://pyth
```

Exercise 45: List concatenations even n

Exercise Description

Write a function `my_function(lst, n)` which, given as input a list of strings `lst` and a number `n`, returns a string that concatenates all the strings in the list that:

- have length strictly greater than `n`, and
- have an even length.

If none of the strings satisfy the requirements, the function must return the string `'no'`.

If the input list is empty, the function must return `-1`.

Your solution

```
def my_function(lst, n):  
    # if the list is empty, return -1  
    # initialize an empty string to store the result  
    # iterate over each string in the list  
        # if the length of the string is greater than n and even  
            # append the string to the result  
    # after the loop, if the result string is still empty  
        # return 'no'  
    # otherwise, return the result string  
    pass
```

Test your solution

```
# Test case 1 (Example)  
assert my_function(["chirus", "sam", "z", "alessio martino"], 4) == "chirus"  
  
# Test case 2  
assert my_function(["chirus", "samo", "zo", "alessio martino", "time"], 2) == "chirus"  
  
# Test case 3  
assert my_function(["chirus", "samo", "zo", "alessio martino", "time"], 22) == "no"  
  
# Test case 4  
assert my_function([], 4) == -1
```

Debug your solution

The following cells contain code to generate links to Python Tutor for debugging your code when running the tests. **You need to first run the cell containing your solution code before running the cell containing the Python Tutor link.**

```
from IPython.display import HTML;import urllib.parse as u;HTML('<a href="https://pyth
```

Exercise 46: Loop Game 1: prime-weighted sum

Exercise Description

Write a function `my_function(lst)` which takes as input a list of numbers `lst` and returns the sum of the numbers in the list, with the following rules:

- Prime numbers are worth double (for example, 7 is worth 14).
- If a 0 is encountered, the current sum is reset to 0.
- If the number -1 is encountered, the loop is interrupted and the function returns the sum obtained up to that point.

If the list is empty, the function should return 0.

Your solution

```
def is_prime(n):  
    # iterate from 2 to n-1  
    # if n is divisible by any of these numbers, it is not prime
```

```
    # if no divisors are found, return True
    pass

def my_function(lst):
    # initialize result to 0
    # iterate over each element in the list
    # if element is -1, break the loop
    # elif element is 0, reset result to 0
    # elif element is prime, add double its value to result
    # otherwise, add its value normally
    # return result
    pass
```

Test your solution

```
# Test case 1 (Example)
assert my_function([4, 6, 8]) == 18

# Test case 2
assert my_function([99, 45, 18, 0, 7]) == 14

# Test case 3
assert my_function([40, 40, -1, 100, 7, 0, 12]) == 80

# Test case 4
assert my_function([]) == 0
```

Debug your solution

The following cells contain code to generate links to Python Tutor for debugging your code when running the tests. **You need to first run the cell containing your solution code before running the cell containing the Python Tutor link.**

```
from IPython.display import HTML;import urllib.parse as u;HTML('<a href="https://pyth
```

Exercise 47: Loop Game 2: character counter

Exercise Description

Write a function `my_function(lst)` which takes as input a list of strings `lst` and returns the total "value" of all the characters in the list. The rules are:

- Lowercase letters are worth 1 point each.
- Uppercase letters are worth 2 points each.
- If the character '0' is encountered, the current total is doubled (the character '0' itself does not add points).
- If the lowercase character 'z' is encountered, the loop stops immediately and the function returns -1.

The function returns the final value according to these rules.

Your solution

```
def my_function(lst):  
    # define a string with all uppercase letters  
    # initialize result to 0  
    # for each string in the list  
        # for each character in the string  
            # if character is uppercase, add 2 to result  
            # elif character is '0', double the current result  
            # elif character is 'z', return -1 immediately  
            # else, add 1 to result  
    # return the final result  
pass
```

Test your solution

```
# Test case 1 (Example)  
assert my_function(["hello", "test", "hi"]) == 11  
  
# Test case 2  
assert my_function(["hEllo", "teSt", "hi"]) == 13  
  
# Test case 3  
assert my_function(["hEllo", "teSt", "0i"]) == 23  
  
# Test case 4  
assert my_function(["hEllz", "teSt", "0i"]) == -1
```

Debug your solution

The following cells contain code to generate links to Python Tutor for debugging your code when running the tests. **You need to first run the cell containing your solution code before running the cell containing the Python Tutor link.**

```
from IPython.display import HTML;import urllib.parse as u;HTML('<a href="https://pyth
```

Exercise 48: Loop Game 3: even numbers and powers

Exercise Description

Write a function `my_function(lst)` which takes as input a list of numbers `lst` and returns the sum of the numbers in the list, with the following rules:

- Even numbers less than 100 are worth double (for example, 50 is worth 100).
- If a 0 is encountered, the current sum is doubled.
- If the number -1 is encountered, the loop is interrupted and the function returns the square of the current sum (`sum ** 2`).

If the list is empty, the function should return 0.

Your solution

```
def my_function(lst):  
    # import the math module if needed  
    # initialize result to 0
```

```
# iterate over each element in the list
    # if the element is even and less than 100, add double its value to result
    # elif the element is 0, double the current result
    # elif the element is -1, return the square of result
    # otherwise, add the element normally
# return result
pass
```

Test your solution

```
# Test case 1 (Example)
assert int(my_function([1, 1, 1, 102])) == 105

# Test case 2
assert int(my_function([2, 2, 2, 102])) == 114

# Test case 3
assert int(my_function([])) == 0

# Test case 4
assert int(my_function([2, 2, -1, 102])) == 64
```

Debug your solution

The following cells contain code to generate links to Python Tutor for debugging your code when running the tests. **You need to first run the cell containing your solution code before running the cell containing the Python Tutor link.**

```
from IPython.display import HTML;import urllib.parse as u;HTML('<a href="https://pyth
```

Exercise 49: Loop Game 4: filtered strings count

Exercise Description

Write a function `my_function(lst, n)` which takes as inputs a list of strings `lst` and an integer `n` and returns the number of elements in the list that satisfy all the following conditions:

- the string length is **less than or equal to** `n`, and
- the string does **not** contain any uppercase characters.

If an empty string `" "` is encountered in the list, the function must stop and return the count obtained up to that point.

Your solution

```
def checkUpper(w):  
    # define a string of uppercase letters  
    # iterate over the characters in w  
    # if any character is uppercase, return True  
    # otherwise, return False  
    pass  
  
def my_function(lst, n):  
    # initialize count to 0  
    # iterate over each string in the list
```

```
        # if the string is empty, return the current count
        # if the string has no uppercase letters and length <= n
            # increase the count
    # return the final count
pass
```

Test your solution

```
# Test case 1 (Example)
assert my_function(["a", "ab", "abc"], 3) == 3

# Test case 2
assert my_function(["a", "ab", "abc"], 2) == 2

# Test case 3
assert my_function(["A", "aB", "abc"], 3) == 1

# Test case 4
assert my_function(["abcd", "ab", "A", "", "abc"], 3) == 1
```

Debug your solution

The following cells contain code to generate links to Python Tutor for debugging your code when running the tests. **You need to first run the cell containing your solution code before running the cell containing the Python Tutor link.**

```
from IPython.display import HTML;import urllib.parse as u;HTML('<a href="https://pyth
```

Exercise 50: Merge words

Exercise Description

Write a function `my_function(a, b)` that adds two lists index-wise.

- `a` and `b` are lists whose elements are strings (or characters).
- The function returns a new list where each element is the concatenation of the elements from `a` and `b` in the same position.

If the lists do not have the same length, the function should return `-1`.

Your solution

```
def my_function(a, b):  
    # if the two lists have different lengths, return -1  
    # otherwise, create an empty result list  
    # iterate over the elements of the two lists at the same time  
        # for each pair, concatenate the two strings and append to the result list  
    # return the result list  
    pass
```

Test your solution

```
# Test case 1 (Example)  
assert my_function(['Pro', 'Ale', 'Mar'], ['f', 'ssio', 'tino']) == ['Prof', 'Alessio', 'Marino']
```

```

# Test case 2
assert my_function(['Pro', 'Ale', 'Mar'], ['f', 'ssio']) == -1

# Test case 3
assert my_function(['Ta', 'va', 'gat'], ['nto', ' la', 'ta']) == ['Tanto', 'va la', 'gatt

# Test case 4
assert my_function(['Pro', 'Ale'], ['nto', 'ssandro']) == ['Pronto', 'Alessandro']

```

Debug your solution

The following cells contain code to generate links to Python Tutor for debugging your code when running the tests. **You need to first run the cell containing your solution code before running the cell containing the Python Tutor link.**

```

from IPython.display import HTML;import urllib.parse as u;HTML('<a href="https://pyth

```

Exercise 51: Password Encoder

Exercise Description

Write a function `my_function(s, letter)` that helps to build a password.

- `s` is a string.
- `letter` is a character and must be one of `['i', 'a', 's']`.

The function converts the string into a password with the following rules:

- If there are **no capital letters** in `s`, the function returns `-1`.
- If letter is **not** one of `'i'`, `'a'`, `'s'`, the function returns `-1`.
- If letter does not appear in `s`, the function returns `-1`.
- Otherwise, it returns a new string where every occurrence of letter is replaced by a special character according to this mapping:
 - `'i'` becomes `'!'`
 - `'a'` becomes `'@'`
 - `'s'` becomes `'$'`

All other characters remain unchanged.

Your solution

```
def my_function(s, letter):  
    # define a string containing all capital letters  
    # check if there is at least one capital letter in s  
    # if not, return -1  
    # check if letter is one of 'i', 'a', 's'  
    # if not, return -1  
    # check if letter appears in s  
    # if not, return -1  
    # create an empty result string  
    # iterate over the characters of s  
    # if the current character is equal to letter  
    # append the corresponding special character to the result  
    # otherwise, append the original character
```

```
# return the result string  
pass
```

Test your solution

```
# Test case 1 (Example)  
assert my_function("Mammabuttalapasta", "a") == "M@mm@butt@l@p@st@"  
  
# Test case 2  
assert my_function("SerpentiSuonatoridiSonagli", "s") == -1  
  
# Test case 3  
assert my_function("CaniCattivi", "i") == "Can!Catt!v!"  
  
# Test case 4  
assert my_function("CaniCattivi", "q") == -1
```

Debug your solution

The following cells contain code to generate links to Python Tutor for debugging your code when running the tests. **You need to first run the cell containing your solution code before running the cell containing the Python Tutor link.**

```
from IPython.display import HTML;import urllib.parse as u;HTML('<a href="https://pyth
```

Exercise 52: Planet 4z

Exercise Description

It is the year 2222 and the Earth is nearing its end. The inhabitants of planet 4z have decided to help the earthlings by sending escape ships. Each spacecraft can hold only one person.

On planet 4z there is an inviolable rule: the name of all its inhabitants must **contain the letter 'z'** or be **at most 4 characters long**. Any humans who fail to meet these requirements will not be saved.

Write a function `my_function(inhabitants)` that, given as input a list of names of earthlings, returns the number of ships to be sent to planet Earth (i.e., the number of humans that satisfy the rule).

If none of the names meet the requirements, the function must return `-1`.

Your solution

```
def my_function(inhabitants):  
    # initialize a counter for ships to 0  
    # iterate over each name in the list  
        # if the name length is <= 4 or the name contains 'z'  
            # increment the counter  
    # after the loop, if the counter is 0, return -1  
    # otherwise, return the counter  
    pass
```

Test your solution

```
# Test case 1 (Example)
assert my_function(["chirus", "zzzzzzz"]) == 1

# Test case 2
assert my_function(["chirus"]) == -1

# Test case 3
assert my_function(["chirus", "sam", "z", "alessio martino"]) == 2

# Test case 4
assert my_function([]) == -1
```

Debug your solution

The following cells contain code to generate links to Python Tutor for debugging your code when running the tests. **You need to first run the cell containing your solution code before running the cell containing the Python Tutor link.**

```
from IPython.display import HTML;import urllib.parse as u;HTML('<a href="https://pyth
```

Exercise 53: Repeat

Exercise Description

Write a function `my_function(lst)` that takes a list of integers as input and returns a new list of integers.

The new list is built as follows:

- the element in position 0 is repeated 1 time,
- the element in position 1 is repeated 2 times,
- the element in position 2 is repeated 3 times, and so on.

However, you do **not** like the number 4, therefore:

- you must **ignore** any element whose value is 4 in the output list, and
- you must **never** repeat an element **4 times** (i.e., when the position index + 1 is 4, skip that element).

Your solution

```
def my_function(lst):  
    # create an empty result list  
    # iterate over the index and value of each element in lst  
        # compute the repetition count as index + 1  
        # if the repetition count is 4 or the value is 4, skip this element  
        # otherwise, append the value to the result list repetition-count times  
    # return the result list  
    pass
```

Test your solution

```
# Test case 1 (Example)  
assert my_function([1, 2, 3, 4]) == [1, 2, 2, 3, 3, 3]
```

```
# Test case 2
assert my_function([9, 8, 7, 6, 5]) == [9, 8, 8, 7, 7, 7, 5, 5, 5, 5, 5]

# Test case 3
assert my_function([4, 4, 4, 2, 1]) == [1, 1, 1, 1, 1]

# Test case 4
assert my_function([4, 4, 4, 4, 4, 4, 4]) == []
```

Debug your solution

The following cells contain code to generate links to Python Tutor for debugging your code when running the tests. **You need to first run the cell containing your solution code before running the cell containing the Python Tutor link.**

```
from IPython.display import HTML;import urllib.parse as u;HTML('<a href="https://pyth
```

Exercise 54: Reverse (almost) everything

Exercise Description

Write a function `my_function(lst, key)` that takes as input a list of words `lst` and a word `key`.

- If key is **not** in the list, the function should return -1.
- Otherwise, it should return a new list where **all words are reversed**, except for key, which remains unchanged (but stays in its original position).

Your solution

```
def my_function(lst, key):  
    # if key is not in the list, return -1  
    # create an empty result list  
    # iterate over each word in the list  
        # if the current word is not key, append the reversed word to the result list  
        # otherwise, append the word as it is  
    # return the result list  
    pass
```

Test your solution

```
# Test case 1 (Example)  
assert my_function(['hello', 'world', 'python'], 'world') == ['olleh', 'world', 'noht']  
  
# Test case 2: key not present  
assert my_function(['a', 'b', 'c'], 'x') == -1  
  
# Test case 3: key at the beginning  
assert my_function(['key', 'abc', 'def'], 'key') == ['key', 'cba', 'fed']  
  
# Test case 4: key at the end  
assert my_function(['abc', 'def', 'key'], 'key') == ['cba', 'fed', 'key']
```

Debug your solution

The following cells contain code to generate links to Python Tutor for debugging your code when running the tests. **You need to first run the cell containing your solution code before running the cell containing the Python Tutor link.**

```
from IPython.display import HTML;import urllib.parse as u;HTML('<a href="https://pyth
```

Exercise 55: Sandwich

Exercise Description

Write a function `my_function(lst, k)` that returns a list of all the elements in `lst` that are **between two values** `k`.

That is, for each element in the list, you check whether the element before it and the element after it are both equal to `k`. If so, this element is included in the output.

Additional rules:

- If there are multiple occurrences of the same value that satisfy the condition, the output list should contain each such value **only once** (no duplicates).
- If `k` is not in `lst`, the function should return `-1`.

Your solution

```
def my_function(lst, k):  
    # if k is not in the list, return -1  
    # create an empty result list  
    # iterate over the indices and values of the list, stopping before the last element  
        # skip index 0 (cannot have an element before it)  
        # if the current value is already in result, skip it (to avoid duplicates)  
        # if the previous element and the next element are both equal to k  
            # append the current value to result  
    # return result  
    pass
```

Test your solution

```
# Test case 1 (Example)  
assert my_function([2, 1, 2, 3, 4, 5, 2, 4, 2, 4, 2], 2) == [1, 4]  
  
# Test case 2: k not present  
assert my_function([2, 1, 2, 3, 4, 5, 2, 4, 2, 4, 2], 7) == -1  
  
# Test case 3: repeated values  
assert my_function([2, 2, 2, 3, 4, 5, 2, 4, 2, 4, 2], 2) == [2, 4]  
  
# Test case 4  
assert my_function([2, 2, 2, 2, 2, 2, 2, 3, 4, 3, 4, 3, 2, 3, 2], 2) == [2, 3]
```

Debug your solution

The following cells contain code to generate links to Python Tutor for debugging your code when running the tests. **You need to first run the cell containing your solution code before running the cell containing the Python Tutor link.**

```
from IPython.display import HTML;import urllib.parse as u;HTML('<a href="https://pyth
```

Exercise 56: Converting Time 1

Exercise Description

Write a function `my_function(K, L)` that is given an integer number `K` and a list of tuples `L`. Each tuple is a pair consisting of an integer number and a character `'m'` (minutes), `'h'` (hours), or `'s'` (seconds).

After converting hours and minutes to seconds, the function should return the position `i` of the tuple in list `L` such that the sum of seconds up to position `i` is **smaller than or equal to** `K`. Positions start from 0.

If the input list is empty or the number of seconds specified by the tuple in position 0 is larger than `K`, the function should return `-1`.

Example: `my_function(1000, [(2, 'm'), (25, 's'), (1, 'h'), (1, 's')])` should return 1, because 2 minutes = 120 seconds, 1 hour = 3600 seconds, and $120 + 25 = 145 < 1000$, while $120 + 25 + 3600 = 3745 > 1000$.

Your solution

```
def my_function(K, L):  
    # create an empty list L_sec to store all values in seconds  
    # for each (value, unit) in L:  
        # if unit is 's', append value  
        # if unit is 'm', convert value to seconds and append  
        # if unit is 'h', convert value to seconds and append  
    # if L is empty or the first element in L_sec is greater than K, return -1  
    # create a list cumsum to store cumulative sums  
    # for each index i, compute the sum of L_sec up to i and store in cumsum[i]  
    # build a list TF of booleans indicating whether each cumulative sum is <= K  
    # if there is any False in TF, return the index of the first False minus 1  
    # otherwise, return the last index (len(L) - 1)  
    pass
```

Test your solution

```
# Test case 1 (Example)  
assert my_function(1000, [(2, 'm'), (25, 's'), (1, 'h'), (1, 's')]) == 1  
  
# Test case 2  
assert my_function(121, [(2, 'm'), (25, 's'), (1, 'h'), (1, 's')]) == 0  
  
# Test case 3  
assert my_function(1, [(1, 'm'), (25, 's'), (1, 'h'), (1, 's')]) == -1  
  
# Test case 4  
assert my_function(1, []) == -1
```

Debug your solution

The following cells contain code to generate links to Python Tutor for debugging your code when running the tests. **You need to first run the cell containing your solution code before running the cell containing the Python Tutor link.**

```
from IPython.display import HTML;import urllib.parse as u;HTML('<a href="https://pyth
```

Exercise 57: Converting Time 2

Exercise Description

Write a function `my_function(K, L)` that is given an integer number `K` and a list of tuples `L`. Each tuple is a triple consisting of three integer numbers, corresponding to **hours, minutes, and seconds**.

After computing the total number of seconds given by each tuple, the function should return the position `i` of the tuple in list `L` such that the sum of seconds up to position `i` is **smaller than or equal to** `K`. Positions start from 0.

If the input list is empty or the number of seconds specified by the tuple in position 0 is larger than `K`, the function should return `-1`.

Example: `my_function(4000, [(0, 2, 3), (1, 3, 5), (2, 0, 32)])` should return 1.

Your solution

```
def my_function(K, L):  
    # create an empty list L_sec  
    # for each (h, m, s) in L:  
        # convert to seconds as s + m * 60 + h * 3600 and append to L_sec  
    # if L is empty or the first element in L_sec is greater than K, return -1  
    # create a cumulative sum list cumsum  
    # for each index i, compute the sum of L_sec up to i  
    # build a boolean list TF with entries (cumsum[i] <= K)  
    # if any value in TF is False, return the index of the first False minus 1  
    # otherwise, return the last index  
    pass
```

Test your solution

```
# Test case 1 (Example)  
assert my_function(4000, [(0, 2, 3), (1, 3, 5), (2, 0, 32)]) == 1  
  
# Test case 2  
assert my_function(344000, [(0, 0, 3), (0, 0, 5), (2, 0, 32)]) == 2  
  
# Test case 3  
assert my_function(2, [(0, 0, 3), (1, 0, 5), (2, 0, 32)]) == -1  
  
# Test case 4  
assert my_function(2, []) == -1
```

Debug your solution

The following cells contain code to generate links to Python Tutor for debugging your code when running the tests. **You need to first run the cell containing your solution code before running the cell containing the Python Tutor link.**

```
from IPython.display import HTML;import urllib.parse as u;HTML('<a href="https://pyth
```

Exercise 58: Divisible by 4

Exercise Description

You have to compute how many numbers divisible by 4 with remainder 1 or 2 you have to sum up until the value of the sum becomes **larger than or equal** to n .

The series of numbers divisible by 4 with remainder 1 or 2 starts with 1, 2, 5, 6, 9, 10, ... (since dividing 1 by 4 gives remainder 1, 2 gives remainder 2, 5 gives remainder 1, and so on).

Write a function `my_function(n)` that gets an integer value n as input and returns the **number of terms** in the smallest sum whose value is $\geq n$. The sum of 0 terms is equal to 0.

Example: if the input is 25, the output is 6 because $1 + 2 + 5 + 6 + 9 = 23 < 25$ but $1 + 2 + 5 + 6 + 9 + 10 = 33 \geq 25$.

Your solution

```
def my_function(n):  
    # start from x = 1, mySum = 0, count i = 0  
    # while mySum < n:  
        # if x % 4 is 1 or 2:  
            # add x to mySum  
            # increment i  
        # increment x  
    # return i  
    pass
```

Test your solution

```
# Test case 1 (Example)  
assert my_function(25) == 6  
  
# Test case 2  
assert my_function(8) == 3  
  
# Test case 3  
assert my_function(75) == 9  
  
# Test case 4  
assert my_function(0) == 0
```

Debug your solution

The following cells contain code to generate links to Python Tutor for debugging your code when running the tests. **You need to first run the cell containing your solution code before running the cell containing the Python Tutor link.**

```
from IPython.display import HTML;import urllib.parse as u;HTML('<a href="https://pyth
```

Exercise 59: Fitting sum

Exercise Description

You are given an integer number n as input, representing the maximum amount available. Sum all the natural numbers (1, 2, 3, ...) that fit in n , i.e., all natural numbers whose cumulative sum is smaller than or equal to n .

Define a function `last_fit(n)` that returns the **last number** that fits in this sum.

Example: if $n = 12$, the output is 4 because $1 + 2 + 3 + 4 \leq 12$ but $1 + 2 + 3 + 4 + 5 > 12$.

Your solution

```
def last_fit(n):  
    # initialize mySum to 0 and toBeAdded to 0  
    # while mySum is less than or equal to n:  
        # increase toBeAdded by 1  
        # add toBeAdded to mySum  
    # when the loop ends, the last value that fit was toBeAdded - 1  
    # return toBeAdded - 1  
    pass
```

Test your solution

```
# Test case 1 (Example)
assert last_fit(12) == 4

# Test case 2
assert last_fit(8) == 3

# Test case 3
assert last_fit(10) == 4

# Test case 4
assert last_fit(100) == 13
```

Debug your solution

The following cells contain code to generate links to Python Tutor for debugging your code when running the tests. **You need to first run the cell containing your solution code before running the cell containing the Python Tutor link.**

```
from IPython.display import HTML;import urllib.parse as u;HTML('<a href="https://pyth
```

Exercise 60: KM CM to M

Exercise Description

Write a function `my_function(S, L)` that is given an integer number `S` and a list of tuples `L`. Each tuple is a pair consisting of an integer number and a character `'k'` (kilometers), `'c'` (centimeters), or `'m'` (meters).

After converting kilometers and centimeters to meters, the function should return the position `i` of the tuple in list `L` such that the sum of meters up to position `i` is **smaller than or equal to** `S`. Positions start from 0.

If the input list is empty or the number of meters specified by the tuple in position 0 is larger than `S`, the function should return `-1`.

Example: `my_function(1000, [(2, 'm'), (30000, 'c'), (5, 'k')])` should return 1, because $30000\text{ cm} = 300\text{ m}$, $5\text{ km} = 5000\text{ m}$, and $2 + 300 = 302 \leq 1000$, while $2 + 300 + 5000 = 5302 > 1000$.

Your solution

```
def my_function(S, L):  
    # if L is empty, return -1  
    # convert each (value, unit) to meters and accumulate into a list or running sum  
    # if the first converted value is greater than S, return -1  
    # iterate over the list with a running total in meters  
        # for each element, convert to meters and add to the running total  
        # if the running total becomes greater than S, return the previous index  
    # if the loop finishes without exceeding S, return the last index  
    pass
```

Test your solution


```
# Test case 1 (Example)
assert my_function(1000, [(2, 'm'), (30000, 'c'), (5, 'k')]) == 1

# Test case 2
assert my_function(1000, [(2, 'm'), (30000, 'c'), (5, 'c')]) == 2

# Test case 3
assert my_function(1, [(20, 'k'), (30000, 'c'), (5, 'k')]) == -1

# Test case 4
assert my_function(1000, []) == -1
```

Debug your solution

The following cells contain code to generate links to Python Tutor for debugging your code when running the tests. **You need to first run the cell containing your solution code before running the cell containing the Python Tutor link.**

```
from IPython.display import HTML; import urllib.parse as u; HTML('<a href="https://pyth
```

Exercise 61: Larger in a sequence

Exercise Description

Write a function `first_larger(a, b, n)` that receives three natural numbers `a`, `b`, and `n`.

Starting from a and b, the function generates a sequence where each element is equal to the sum of the previous two elements. It then returns the **first element in the sequence that is strictly larger than n**.

Example: if a = 1, b = 2, and n = 50, the sequence is 1, 2, 3, 5, 8, 13, 21, 34, 55, ... and the function should return 55.

Your solution

```
def first_larger(a, b, n):  
    # set second_to_last to a and last to b  
    # while last is less than n:  
        # compute new as last + second_to_last  
        # update second_to_last to last  
        # update last to new  
    # when the loop ends, last is the first element > n  
    # return last  
    pass
```

Test your solution

```
# Test case 1 (Example)  
assert first_larger(1, 2, 50) == 55  
  
# Test case 2  
assert first_larger(1, 2, 15) == 21  
  
# Test case 3  
a = 2; b = 3; n = 8  
assert first_larger(a, b, n) == 8
```

```
# Test case 4
a = 1; b = 1; n = 1000
assert first_larger(a, b, n) == 1597
```

Debug your solution

The following cells contain code to generate links to Python Tutor for debugging your code when running the tests. **You need to first run the cell containing your solution code before running the cell containing the Python Tutor link.**

```
from IPython.display import HTML;import urllib.parse as u;HTML('<a href="https://pyth
```

Exercise 62: Sum 2 Series

Exercise Description

You have to compute the sum of a series of numbers 2, 22, 222, 2222, and so on, until the value of the sum becomes larger than or equal to n .

Write a function `my_function(n)` that gets an integer value n as input parameter and returns the **number of terms** in the smallest sum whose value is $\geq n$. The sum of 0 terms is equal to 0.

Hint: each number can be obtained from the previous one in the series by multiplying it by 10 and adding 2 (e.g., $2222 = 222 * 10 + 2$).

Example: if the input is 25, the output is 3 because $2 + 22 = 24 < 25$ but $2 + 22 + 222 = 246 \geq 25$.

Your solution

```
def my_function(n):  
    # start with twos = 2, mySum = 0, i = 1  
    # while mySum is less than n:  
        # add twos to mySum  
        # update twos to twos * 10 + 2  
        # increment i  
    # when the loop ends, we have added one term too many  
    # return i - 1  
    pass
```

Test your solution

```
# Test case 1 (Example)  
assert my_function(25) == 3  
  
# Test case 2  
assert my_function(1000) == 4  
  
# Test case 3  
assert my_function(2468) == 4  
  
# Test case 4  
assert my_function(1) == 1
```

Debug your solution

The following cells contain code to generate links to Python Tutor for debugging your code when running the tests. **You need to first run the cell containing your solution code before running the cell containing the Python Tutor link.**

```
from IPython.display import HTML;import urllib.parse as u;HTML('<a href="https://pyth
```

Exercise 63: Sum Fermat

Exercise Description

You have to compute the sum of numbers 11, 101, 1001, 10001, 100001, and so on, until the value of the sum becomes larger than or equal to n .

Write a function `my_function(n)` that gets an integer value n as input parameter and returns the **number of terms** in the smallest sum whose value is $\geq n$. The sum of 0 terms is equal to 0.

Hint: each number in the series is a power of 10 plus 1 (e.g., $10001 = 10^4 + 1$).

Example: if the input is 250, then the output is 3 because $11 + 101 = 112 < 250$ but $11 + 101 + 1001 = 1113 \geq 250$.

Your solution

```
def my_function(n):  
    # start with howMany0 = 0 and mySum = 0  
    # while mySum is less than n:  
        # build the current term as '1' + howMany0 * '0' + '1' and convert to int  
        # add this term to mySum  
        # increase howMany0 by 1  
    # when the loop ends, howMany0 is the number of terms  
    # return howMany0  
pass
```

Test your solution

```
# Test case 1 (Example)  
assert my_function(250) == 3  
  
# Test case 2  
assert my_function(11114) == 4  
  
# Test case 3  
assert my_function(3000) == 4  
  
# Test case 4  
assert my_function(1) == 1
```

Debug your solution

The following cells contain code to generate links to Python Tutor for debugging your code when running the tests. **You need to first run the cell containing your solution code before running the cell containing the Python Tutor link.**

```
from IPython.display import HTML;import urllib.parse as u;HTML('<a href="https://pyth
```

Exercise 64: Sum Km and Cm to M

Exercise Description

Write a function `my_function(S, L)` that is given an integer number `S` and a list of tuples `L`. Each tuple is a pair consisting of an integer number and a character `'k'` (kilometers), `'c'` (centimeters), or `'m'` (meters).

After converting kilometers and centimeters to meters, the function should return the **largest sum** `s` of meters such that $s \leq S$. The sum must be computed starting from position 0 and using elements in consecutive positions in the list.

If the input list is empty or the number of meters specified by the tuple in position 0 is larger than `S`, the function should return `-1`.

Example: `my_function(1000, [(2, 'm'), (30000, 'c'), (5, 'k')])` should return 302, because $30000 \text{ cm} = 300 \text{ m}$, $5 \text{ km} = 5000 \text{ m}$, and $2 + 300 = 302 \leq 1000$, while $2 + 300 + 5000 = 5302 > 1000$.

Your solution

```
def my_function(S, L):  
    # if L is empty, return -1  
    # check the first tuple converted to meters; if it is greater than S, return -1
```

```
# initialize sum_meters and max_sum to 0
# for each (distance, unit) in L, in order:
    # convert distance to meters depending on unit ('k', 'c', 'm')
    # add the converted distance to sum_meters
    # if sum_meters is greater than S, break the loop
    # otherwise, update max_sum to sum_meters
# return max_sum (or -1 if we never added anything)
pass
```

Test your solution

```
# Test case 1 (Example)
assert int(my_function(1000, [(2, 'm'), (30000, 'c'), (5, 'k')])) == 302

# Test case 2
assert int(my_function(1000, [(2, 'm'), (3, 'm'), (5, 'm')])) == 10

# Test case 3
assert int(my_function(1, [(2, 'm'), (30000, 'c'), (5, 'k')])) == -1

# Test case 4
assert int(my_function(1000, [])) == -1
```

Debug your solution

The following cells contain code to generate links to Python Tutor for debugging your code when running the tests. **You need to first run the cell containing your solution code before running the cell containing the Python Tutor link.**


```
from IPython.display import HTML;import urllib.parse as u;HTML('<a href="https://pyth
```

Exercise 65: Sum of Triangular

Exercise Description

You have to compute the sum of triangular numbers 1, 3, 6, 10, 15, 21, ... until the value of the sum becomes larger than or equal to n .

Write a function `my_function(n)` that gets an integer value n as input parameter and returns the **number of terms** in the smallest sum whose value is $\geq n$. The sum of 0 terms is equal to 0.

Hint: the first triangular number in the sequence (position 1) is 1. For $x > 1$, the triangular number at position x is equal to the triangular number at position $x-1$ plus x .

Example: if the input is 25, then the output is 5 because $1 + 3 + 6 + 10 = 20 < 25$ but $1 + 3 + 6 + 10 + 15 = 35 \geq 25$.

Your solution

```
def my_function(n):  
    # initialize i = 1, last_x = 0, mySum = 0  
    # while mySum is less than n:  
        # compute current triangular x as last_x + i  
        # update last_x to x
```

```
        # increment i
        # add x to mySum
    # when the loop ends, we have added one term too many
    # return i - 1
pass
```

Test your solution

```
# Test case 1 (Example)
assert my_function(25) == 5

# Test case 2
assert my_function(56) == 6

# Test case 3
assert my_function(60) == 7

# Test case 4
assert my_function(1) == 1
```

Debug your solution

The following cells contain code to generate links to Python Tutor for debugging your code when running the tests. **You need to first run the cell containing your solution code before running the cell containing the Python Tutor link.**

```
from IPython.display import HTML;import urllib.parse as u;HTML('<a href="https://pyth
```

Exercise 66: Classroom Attendance Tracker

Exercise Description

Imagine you're helping a school modernize its attendance system. Each classroom has a unique ID and a roster of students. The school wants to track attendance daily, marking students as present or absent.

Write a function `update_attendance(current_attendance, attendance_updates)` that:

- `current_attendance` is a dictionary where keys are classroom IDs and values are dictionaries mapping student names to their attendance status ('Present' or 'Absent').
- `attendance_updates` is a list of tuples (`class_id`, `student_name`, `status`) with the updated status.

The function should apply all updates and return the updated dictionary. If a classroom or student does not exist yet, add them.

Your solution

```
def update_attendance(current_attendance, attendance_updates):  
    # iterate over each tuple in attendance_updates  
    # unpack tuple into classID, studentName, attendanceStatus  
    # if classID is already a key in current_attendance:  
        # set current_attendance[classID][studentName] = attendanceStatus  
    # (this also adds the student if they do not exist)
```

```
# otherwise:  
    # create a new inner dict for this classID with the single student entry  
    # return current_attendance  
pass
```

Test your solution

```
# Test case 1 (Example)  
current_attendance = {  
    'Class 1A': {'Alice': 'Present', 'Bob': 'Absent'},  
    'Class 2B': {'Charlie': 'Present', 'Daisy': 'Present'},  
}  
  
attendance_updates = [  
    ('Class 1A', 'Alice', 'Absent'),  
    ('Class 2B', 'Eva', 'Present'),  
    ('Class 3C', 'Frank', 'Present'),  
]  
  
updated_attendance = update_attendance(current_attendance, attendance_updates)  
assert updated_attendance == {  
    'Class 1A': {'Alice': 'Absent', 'Bob': 'Absent'},  
    'Class 2B': {'Charlie': 'Present', 'Daisy': 'Present', 'Eva': 'Present'},  
    'Class 3C': {'Frank': 'Present'},  
}  
  
# Test case 2  
current_attendance = {  
    'Class 3A': {'John': 'Present', 'Sarah': 'Absent'},  
    'Class 4B': {'Mike': 'Absent', 'Emily': 'Present'},  
}
```

```
attendance_updates = [
    ('Class 3A', 'Sarah', 'Present'),
    ('Class 4B', 'Mike', 'Present'),
    ('Class 5C', 'Anna', 'Present'),
]

updated_attendance = update_attendance(current_attendance, attendance_updates)
assert updated_attendance == {
    'Class 3A': {'John': 'Present', 'Sarah': 'Present'},
    'Class 4B': {'Mike': 'Present', 'Emily': 'Present'},
    'Class 5C': {'Anna': 'Present'},
}

# Additional tests adapted from the import notebook follow the same pattern
```

Debug your solution

The following cells contain code to generate links to Python Tutor for debugging your code when running the tests. **You need to first run the cell containing your solution code before running the cell containing the Python Tutor link.**

```
from IPython.display import HTML;import urllib.parse as u;HTML('<a href="https://pyth
```

Exercise 67: Employee Skillset Tracker

Exercise Description

You are assisting the HR department of TechGiant Inc. to manage employees' skillsets.

Write a function `update_employee_skills(current_skills, skill_updates)` that:

- `current_skills` is a dictionary where keys are employee IDs and values are lists of skills.
- `skill_updates` is a list of tuples (`employee_id`, `list_of_skills`, `action`) where `action` is either 'add' or 'remove'.

The function should:

- If `action == 'add'`, **add** all skills in the list to that employee's skills (without removing existing ones).
- If `action == 'remove'`, **remove** each listed skill from the employee's skills (if present).
- If an employee ID is not present in `current_skills`, add it.
- If removing skills leaves an employee with no skills, remove that employee from the dictionary.

The function must return the updated dictionary.

Your solution

```
def update_employee_skills(current_skills, skill_updates):  
    # iterate over each tuple in skill_updates
```

```

# unpack employeeID, listOfSkills, action
# if employeeID exists in current_skills:
    # if action is 'add': extend the list with new skills
    # if action is 'remove': for each skill in listOfSkills, remove it if present
# otherwise (employeeID not present): add it with listOfSkills
# after updates, iterate over employees and remove those with an empty skills list
# return current_skills
pass

```

Test your solution

```

# Test case 1 (Example)
current_skills = {
    101: ['Python', 'SQL'],
    102: ['Java', 'C++', 'Python'],
    103: ['HTML', 'CSS'],
}

skill_updates = [
    (101, ['Java'], 'add'),
    (104, ['Python', 'JavaScript'], 'add'),
    (102, ['C++'], 'remove'),
    (103, ['HTML'], 'remove'),
]

updated_skills = update_employee_skills(current_skills, skill_updates)
assert updated_skills == {
    101: ['Python', 'SQL', 'Java'],
    102: ['Java', 'Python'],
    103: ['CSS'],
    104: ['Python', 'JavaScript'],
}

```

```
}
```

Additional tests follow the same structure as in the import notebook

Debug your solution

The following cells contain code to generate links to Python Tutor for debugging your code when running the tests. **You need to first run the cell containing your solution code before running the cell containing the Python Tutor link.**

```
from IPython.display import HTML;import urllib.parse as u;HTML('<a href="https://pyth
```

Exercise 68: Inventory Management in Gridmart

Exercise Description

Gridmart is organized as a grid where each cell stores the quantity of a product category.

Write a function `update_inventory(current_inventory, updates)` that:

- `current_inventory` is a 2D list (list of lists) where each sublist is a row and each element is the quantity of a product category.
- `updates` is a list of tuples (row, column, delta) describing how many products to add (positive) or subtract (negative).

The function should:

- For each update, check if (row, column) is inside the grid. If any update refers to an invalid position, return None.
- Otherwise, apply all updates in order, modifying current_inventory.
- If after an update any quantity becomes negative, return -1.
- If all updates are valid and no quantity goes negative, return the updated 2D list.

Your solution

```
def update_inventory(current_inventory, updates):  
    # compute number of rows nRows and columns nCols (assume rectangular grid)  
    # for each (row, column, quantity) in updates:  
        # if row is outside [0, nRows-1] return None  
        # if column is outside [0, nCols-1] return None  
        # add quantity to current_inventory[row][column]  
        # if the updated value is negative, return -1  
    # if all updates are applied successfully, return current_inventory  
    pass
```

Test your solution

```
# Test case 1 (Example)  
current_inventory = [[20, 15, 10], [30, 25, 5], [12, 8, 3]]  
updates = [(0, 1, -5), (1, 0, 10), (2, 2, -2)]  
assert update_inventory(current_inventory, updates) == [[20, 10, 10], [40, 25, 5], [12, 8, 3]]  
  
# Test case 2: invalid column index
```

```

current_inventory = [[40, 30, 20], [25, 35, 45], [15, 10, 5]]
updates = [(0, 2, 5), (1, 3, -15), (2, 0, 10)]
assert update_inventory(current_inventory, updates) is None

# Test case 3: negative quantity after update
current_inventory = [[50, 60], [20, 30], [70, 80]]
updates = [(0, 0, -100), (1, 1, 20), (2, 0, -15)]
assert update_inventory(current_inventory, updates) == -1

# Test case 4
current_inventory = [[100, 200, 300], [400, 500, 600]]
updates = [(0, 1, -50), (1, 2, 25), (1, 0, -40)]
assert update_inventory(current_inventory, updates) == [[100, 150, 300], [360, 500, 600]]

# Test case 5
current_inventory = [[5, 10, 15], [20, 25, 30], [35, 40, 45], [50, 55, 60]]
updates = [(3, 2, -10), (2, 1, 20), (0, 0, 5)]
assert update_inventory(current_inventory, updates) == [[10, 10, 15], [20, 25, 30], [35, 40, 45], [50, 55, 60]]

```

Debug your solution

The following cells contain code to generate links to Python Tutor for debugging your code when running the tests. **You need to first run the cell containing your solution code before running the cell containing the Python Tutor link.**

```

from IPython.display import HTML;import urllib.parse as u;HTML('<a href="https://pyth

```

Exercise 69: Library Book Tracker

Exercise Description

A library wants to track whether books are currently 'in' or 'out'.

Write a function `update_library(current_status, transactions)` that:

- `current_status` is a dictionary mapping book titles to their status ('in' or 'out').
- `transactions` is a list of tuples (title, status) where status is 'in' or 'out'.

The function should apply each transaction in order, updating or inserting entries in the dictionary, and then return the updated dictionary. If a title does not exist yet, add it.

Your solution

```
def update_library(current_status, transactions):  
    # for each (book, status) in transactions:  
        # set current_status[book] = status (this both updates and inserts)  
    # return current_status  
    pass
```

Test your solution

```
# Test case 1 (Example)  
current_status = {  
    'The Great Gatsby': 'in',  
    'To Kill a Mockingbird': 'out',
```

```
        '1984': 'in',
    }

    transactions = [
        ('To Kill a Mockingbird', 'in'),
        ('The Catcher in the Rye', 'out'),
        ('1984', 'out'),
    ]

    updated_status = update_library(current_status, transactions)
    assert updated_status == {
        'The Great Gatsby': 'in',
        'To Kill a Mockingbird': 'in',
        '1984': 'out',
        'The Catcher in the Rye': 'out',
    }

# Additional tests mirror the import notebook cases
```

Debug your solution

The following cells contain code to generate links to Python Tutor for debugging your code when running the tests. **You need to first run the cell containing your solution code before running the cell containing the Python Tutor link.**

```
from IPython.display import HTML;import urllib.parse as u;HTML('<a href="https://pyth
```

Exercise 70: The Classroom Gradebook

Exercise Description

Mr. Alan maintains a gradebook where each student's test scores are stored in a row.

Write a function `calculate_student_averages(gradebook)` that:

- Receives a 2D list `gradebook`, where each inner list contains the scores of one student.
- Returns a list of tuples `(student_index, average_score)` where `student_index` is the index of the student in `gradebook` and `average_score` is their average rounded to 2 decimal places.

Caveats:

- Students with no scores are represented by an empty inner list: their average is defined to be 0.

Your solution

```
def calculate_student_averages(gradebook):  
    # create an empty output list  
    # for each index i in gradebook:  
        # compute sumOfGrades and numOfGrades for gradebook[i]  
        # if numOfGrades is 0, append (i, 0) to output  
        # otherwise append (i, round(sumOfGrades / numOfGrades, 2))
```

```
# return output  
pass
```

Test your solution

```
# Test case 1 (Example)  
gradebook = [[78, 82, 85], [92, 88, 91], [83, 76, 79], [95, 92]]  
assert calculate_student_averages(gradebook) == [(0, 81.67), (1, 90.33), (2, 79.33),  
  
# Further tests follow the patterns in the import notebook
```

Debug your solution

The following cells contain code to generate links to Python Tutor for debugging your code when running the tests. **You need to first run the cell containing your solution code before running the cell containing the Python Tutor link.**

```
from IPython.display import HTML;import urllib.parse as u;HTML('<a href="https://pyth
```

Exercise 71: The Seating Arrangement Puzzle

Exercise Description

The community hall seating is organized as a 2D grid of 'Occupied' / 'Available' seats.

Write a function `update_seating_arrangement(current_seating, updates)` that:

- `current_seating` is a 2D list where each inner list is a row of seats.
- `updates` is a list of tuples `(row, col, new_status)` where `new_status` is `'Occupied'` or `'Available'`.

The function should:

- First check that the grid is regular (all rows have the same length). If not, return `-1`.
- For each update, if `(row, col)` is inside the grid, update that seat's status. If `(row, col)` is outside the grid, ignore that update.
- Return the updated 2D list.

Your solution

```
def update_seating_arrangement(current_seating, updates):  
    # compute number of rows n and list m of row lengths  
    # if not all row lengths are equal, return -1  
    # otherwise, let m be the common number of columns  
    # for each (row, col, new_value) in updates:  
        # if row and col are within valid bounds, update current_seating[row][col]  
    # return current_seating  
    pass
```

Test your solution

```
# Test case 1 (Example)  
current_seating = [  
    ['Available', 'Occupied', 'Available'],
```

```

    ['Occupied', 'Occupied', 'Available'],
    ['Available', 'Available', 'Available'],
]

updates = [(0, 0, 'Occupied'), (1, 2, 'Occupied'), (2, 1, 'Occupied')]
assert update_seating_arrangement(current_seating, updates) == [
    ['Occupied', 'Occupied', 'Available'],
    ['Occupied', 'Occupied', 'Occupied'],
    ['Available', 'Occupied', 'Available'],
]

# Additional tests mirror the import notebook behaviour

```

Debug your solution

The following cells contain code to generate links to Python Tutor for debugging your code when running the tests. **You need to first run the cell containing your solution code before running the cell containing the Python Tutor link.**

```

from IPython.display import HTML; import urllib.parse as u; HTML('<a href="https://pyth

```

Exercise 72: Count Pairs

Exercise Description

Write a function `my_function(n, a, b, k)` that returns the **number of pairs** (x, y) such that:

1. x is a multiple of 3, strictly larger than 0 and smaller than or equal to n .
2. y is a number strictly larger than a and strictly smaller than b .
3. The difference between x and y is at most k (included), i.e. $x - y \leq k$.

Your solution

```
def my_function(n, a, b, k):  
    # initialize counter numPairs to 0  
    # for x from 3 to n included, stepping by 3 (multiples of 3):  
        # for y from a+1 to b-1 included:  
            # if x - y <= k:  
                # increment numPairs  
    # return numPairs  
    pass
```

Test your solution

```
# Test case 1 (Example)  
assert my_function(32, 9, 21, 12) == 95  
  
# Test case 2  
assert my_function(32, 3, 21, 12) == 130  
  
# Test case 3  
assert my_function(32, 3, 21, 3) == 79
```

```
# Test case 4
assert my_function(2, 3, 21, 3) == 0
```

Debug your solution

The following cells contain code to generate links to Python Tutor for debugging your code when running the tests. **You need to first run the cell containing your solution code before running the cell containing the Python Tutor link.**

```
from IPython.display import HTML;import urllib.parse as u;HTML('<a href="https://pyth
```

Exercise 73: Count Pairs Between

Exercise Description

Write a function `my_function(n, a, b, k)` that returns the **number of pairs** (x, y) such that:

1. y is an even number strictly larger than 0 and smaller than or equal to n .
2. x is a number strictly larger than a and strictly smaller than b .
3. The product $x * y$ is at most k (included).

Your solution

```
def my_function(n, a, b, k):  
    # initialize counter numPairs to 0  
    # for y from 2 to n included, stepping by 2 (even numbers):  
        # for x from a+1 to b-1 included:  
            # if x * y <= k:  
                # increment numPairs  
    # return numPairs  
pass
```

Test your solution

```
# Test case 1 (Example)  
assert my_function(2, 1, 6, 10) == 4  
  
# Test case 2  
assert my_function(2, 10, 60, 100) == 40  
  
# Test case 3  
assert my_function(6, 2, 6, 100) == 9  
  
# Test case 4  
assert my_function(6, 2, 6, 1) == 0
```

Debug your solution

The following cells contain code to generate links to Python Tutor for debugging your code when running the tests. **You need to first run the cell containing your solution code before running the cell containing the Python Tutor link.**

```
from IPython.display import HTML;import urllib.parse as u;HTML('<a href="https://pyth
```

Exercise 74: Maxsum Pairs

Exercise Description

Write a function `my_function(n, a, b, k)` that returns the **maximum sum** $x + y$ taken among all pairs (x, y) such that:

- y is a multiple of 3, strictly larger than 0 and strictly smaller than n .
- x is a number strictly larger than a and strictly smaller than b .
- The difference between x and y is at least k (included), i.e. $x - y \geq k$.

If no pair satisfies the conditions, the function should return 0.

Your solution

```
def my_function(n, a, b, k):  
    # initialize bestSum to 0  
    # for y from 3 to n-1 included, stepping by 3 (multiples of 3):  
        # for x from a+1 to b-1 included:  
            # if x - y >= k and x + y > bestSum:  
                # update bestSum to x + y  
    # return bestSum  
    pass
```

Test your solution

```
# Test case 1 (Example)
assert my_function(20, 1, 21, 12) == 26

# Test case 2
assert my_function(3, 1, 21, 12) == 0

# Test case 3
assert my_function(20, 1, 210, 12) == 227

# Test case 4
assert my_function(20, 1, 6, 2) == 8
```

Debug your solution

The following cells contain code to generate links to Python Tutor for debugging your code when running the tests. **You need to first run the cell containing your solution code before running the cell containing the Python Tutor link.**

```
from IPython.display import HTML; import urllib.parse as u; HTML('<a href="https://pyth
```

Exercise 75: Maxsum pairs Odd

Exercise Description

Write a function `my_function(n, a, b, k)` that returns the **maximum sum** $x + y$ taken among all pairs (x, y) such that:

1. x is a positive odd number smaller than or equal to n .
2. y is a number strictly larger than a and smaller than or equal to b .
3. The product $x * y$ is at most k (included).

If no pair satisfies the conditions, the function should return 0.

Your solution

```
def my_function(n, a, b, k):  
    # initialize bestSum to 0  
    # for x from 1 to n included, stepping by 2 (odd numbers):  
        # for y from a+1 to b included:  
            # if x * y <= k and x + y > bestSum:  
                # update bestSum to x + y  
    # return bestSum  
    pass
```

Test your solution

```
# Test case 1 (Example)  
assert my_function(20, 1, 6, 2) == 3  
  
# Test case 2  
assert my_function(2, 1, 6, 2) == 3
```

```
# Test case 3
assert my_function(2, 1, 6, 20) == 7

# Test case 4
assert my_function(2, 1, 6, 1) == 0
```

Debug your solution

The following cells contain code to generate links to Python Tutor for debugging your code when running the tests. **You need to first run the cell containing your solution code before running the cell containing the Python Tutor link.**

```
from IPython.display import HTML;import urllib.parse as u;HTML('<a href="https://pyth
```

Exercise 76: Difference between main and anti-diagonal

Exercise Description

Let M be an $(n \times m)$ matrix of numbers organized as a list-of-lists with (n) lists where each inner list has length (m) . You can assume that all inner lists have the same size (m) and you can assume M to be non-empty.

Write a Python function called `my_function(M)` that, given a matrix M , returns the absolute value of the difference between the sum of its main diagonal and the sum of its anti-diagonal.

Keep in mind the following caveats and definitions:

- normally, main diagonal and anti-diagonal are defined for square matrices only (namely matrices whose number of rows is equal to the number of columns): if (n) is not equal to (m), the function must return -1
- the main diagonal of a matrix is defined as the list of entries lying from the top left to the bottom right corner of the matrix
- the anti-diagonal of a matrix is defined as the list of entries lying from the top right to the bottom left corner of the matrix

Your solution

```
def my_function(M):  
    # compute number of rows and columns  
    # if matrix is not square, return -1  
    # compute sum of main diagonal  
    # compute sum of anti-diagonal  
    # return the absolute difference between the two sums  
    pass
```

Test your solution

```
# Test case 1 (Example)  
M = [[1,2,3], [4,5,6], [7,8,9]]  
assert my_function(M) == 0  
  
# Additional tests  
M = [[1,2,3], [4,5,6], [7,8,9], [10, 11, 12]]  
assert my_function(M) == -1
```



```
M = [[29, 10, 12, 33, 83, 28, 32, 81, 91, 84],
      [98, 60, 84, 68, 60, 18, 65, 10, 51, 50],
      [20, 15, 33, 33, 64, 37, 82, 50, 90, 45],
      [80, 38, 9, 43, 69, 82, 78, 39, 46, 44],
      [38, 69, 68, 20, 62, 53, 18, 59, 12, 12],
      [52, 14, 48, 3, 72, 64, 74, 45, 28, 97],
      [6, 27, 4, 2, 82, 67, 79, 96, 50, 55],
      [23, 83, 46, 45, 17, 26, 39, 48, 9, 75],
      [7, 58, 84, 63, 98, 25, 50, 78, 35, 30],
      [55, 36, 22, 32, 45, 14, 14, 5, 75, 34]]
assert my_function(M) == 62
```

Debug your solution

The following cells contain code to generate links to Python Tutor for debugging your code when running the tests. **You need to first run the cell containing your solution code before running the cell containing the Python Tutor link.**

```
from IPython.display import HTML;import urllib.parse as u;HTML('<a href="https://pyth
```

Exercise 77: Replace odd columns with previous max

Exercise Description

Let M be an $n \times m$ matrix of numbers organized as a list-of-lists with n lists where each inner list has length m . You can assume that all inner lists have the same size m and you can assume M to have at least 2 columns.

Write a Python function called `my_function(M)` that, given a matrix M , returns a modified version of M where the values in the odd columns are replaced with the maximum element of the previous even column.

Furthermore:

- if n is not equal to m , the function must return `-1`
- if n is equal to m , but there is at least one negative element (regardless of its position), the function must return `-2`

Your solution

```
def my_function(M):  
    # compute number of rows and columns  
    # if matrix is not square, return -1  
    # check for negative elements, if any return -2  
    # for each even column, compute its maximum over rows  
    # replace the following odd column with that maximum in every row  
    # return the modified matrix  
    pass
```

Test your solution

```
# Test case 1 (Example)
M = [[1,2,3], [4,5,6], [7,8,9]]
assert my_function(M) == [[1, 7, 3], [4, 7, 6], [7, 7, 9]]
```

Test your solution

```
# Additional tests
M = [[1,2,3], [4,5,6], [7,8,9], [10, 11, 12]]
assert my_function(M) == -1

M = [[1,2,3], [-0.01,5,6], [7,8,9]]
assert my_function(M) == -2

M = [[1, 2, 3, 0, 4], [3, 3, 1, 0, 3], [7, 3, 8, 4, 0], [1, 6, 7, 9, 0], [2, 4, 6, 9, 7]]
assert my_function(M) == [[1, 7, 3, 8, 4], [3, 7, 1, 8, 3], [7, 7, 8, 8, 0], [1, 7, 7, 9, 0], [2, 4, 6, 9, 7]]
```

Debug your solution

The following cells contain code to generate links to Python Tutor for debugging your code when running the tests. **You need to first run the cell containing your solution code before running the cell containing the Python Tutor link.**

```
from IPython.display import HTML;import urllib.parse as u;HTML('<a href="https://pyth
```

Exercise 78: Replace column i with row i

Exercise Description

Write a function `my_function(M, i)` that is given a list of lists of numbers `M` and an integer number `i` such that:

- `M` represents a square matrix containing $D \times D$ elements: you can assume that all its sublists (corresponding to rows) have the same length and that the number `D` of rows equals the number `D` of columns.
- Integer `i` is a row and column index: it is larger than or equal to 0, and strictly smaller than `D`.

The function should modify `M` by replacing the `i`-th column with the `i`-th row and should then return the modified matrix.

Back-of-the-envelope example: if `M = [[1,2,3],[4,5,6],[7,8,9]]` and `i = 1`, the returned matrix should be `[[1,4,3],[4,5,6],[7,6,9]]`.

Your solution

```
def my_function(M, i):  
    # compute matrix dimension D  
    # copy matrix to avoid modifying original reference  
    # store the i-th row  
    # for each row index k, set element in column i to the corresponding element from  
    # return the modified matrix  
    pass
```

Test your solution

```
# Test case 1 (Example)
a = my_function([[1,2,3],[4,5,6],[7,8,9]],1)
assert a == [[1, 4, 3], [4, 5, 6], [7, 6, 9]]
```

Test your solution

```
# Additional tests
a = my_function([[1,2,3],[4,5,6],[7,8,9]],2)
assert a == [[1, 2, 7], [4, 5, 8], [7, 8, 9]]

a = my_function([[1, 2, 3, 4], [5, 6, 7, 8], [9, 10, 11, 12], [13, 14, 15, 16]],0)
assert a == [[1, 2, 3, 4], [2, 6, 7, 8], [3, 10, 11, 12], [4, 14, 15, 16]]

a = my_function([[1, 2], [3, 4]],1)
assert a == [[1, 3], [3, 4]]
```

Debug your solution

The following cells contain code to generate links to Python Tutor for debugging your code when running the tests. **You need to first run the cell containing your solution code before running the cell containing the Python Tutor link.**

```
from IPython.display import HTML;import urllib.parse as u;HTML('<a href="https://pyth
```

Exercise 79: Replace row i with column j

Exercise Description

Write a function `my_function(M, i, j)` that is given a list of lists `M` of numbers and two integer numbers `i` and `j` such that:

- `M` represents a square matrix containing $D \times D$ elements: you can assume that all its sublists (corresponding to rows) have the same length and that the number `D` of rows equals the number `D` of columns.
- Integer `i` is a row index: it is larger than or equal to 0, and strictly smaller than `D`.
- Integer `j` is a column index: it is larger than or equal to 0, and strictly smaller than `D`.

The function should modify `M` by replacing the `i`-th row with the `j`-th column and should then return the modified matrix.

Back-of-the-envelope example: if `M = [[1,2,3],[4,5,6],[7,8,9]]` and `i = 1, j = 2`, the returned matrix should be `[[1,2,3],[3,6,9],[7,8,9]]`.

Your solution

```
def my_function(M, i, j):  
    # compute matrix dimension D  
    # copy matrix to avoid modifying original reference  
    # extract column j into a temporary list  
    # replace row i with that column
```

```
# return the modified matrix  
pass
```

Test your solution

```
# Test case 1 (Example)  
a = my_function([[1,2,3],[4,5,6],[7,8,9]],1,2)  
assert a == [[1, 2, 3], [3, 6, 9], [7, 8, 9]]
```

Test your solution

```
# Additional tests  
a = my_function([[1,2,3],[4,5,6],[7,8,9]],2,2)  
assert a == [[1, 2, 3], [4, 5, 6], [3, 6, 9]]  
  
a = my_function([[1,2],[4,5]],0,1)  
assert a == [[2, 5], [4, 5]]  
  
a = my_function([[1, 2, 3, 4], [5, 6, 7, 8], [9, 10, 11, 12], [13, 14, 15, 16]],3,0)  
assert a == [[1, 2, 3, 4], [5, 6, 7, 8], [9, 10, 11, 12], [1, 5, 9, 13]]
```

Debug your solution

The following cells contain code to generate links to Python Tutor for debugging your code when running the tests. **You need to first run the cell containing your solution code before running the cell containing the Python Tutor link.**

```
from IPython.display import HTML;import urllib.parse as u;HTML('<a href="https://pyth
```

Exercise 80: Replace row i with column i

Exercise Description

Write a function `my_function(M, i)` that is given a list `M` of lists of numbers and an integer number `i` such that:

- `M` represents a square matrix containing $D \times D$ elements: you can assume that all its sublists (corresponding to rows) have the same length and that the number `D` of rows equals the number `D` of columns.
- Integer `i` is a row and column index: it is larger than or equal to 0, and strictly smaller than `D`.

The function should modify `M` by replacing the `i`-th row with the `i`-th column and should then return the modified matrix.

Back-of-the-envelope example: if `M = [[1,2,3],[4,5,6],[7,8,9]]` and `i = 2`, the returned modified matrix should be `[[1,2,3],[4,5,6],[3,6,9]]`.

Your solution

```
def my_function(M, i):  
    # copy matrix to avoid modifying original reference  
    # build the i-th column as a list  
    # replace row i with this column
```



```
# return the modified matrix  
pass
```

Test your solution

```
# Test case 1 (Example)  
a = my_function([[1,2,3],[4,5,6],[7,8,9]],2)  
assert a == [[1, 2, 3], [4, 5, 6], [3, 6, 9]]
```

Test your solution

```
# Additional tests  
a = my_function([[1,2,3,4],[5,6,7,8],[9,10,11,12],[13,14,15,16]],3)  
assert a == [[1, 2, 3, 4], [5, 6, 7, 8], [9, 10, 11, 12], [4, 8, 12, 16]]  
  
a = my_function([[1, 2], [3, 4]],0)  
assert a == [[1, 3], [3, 4]]  
  
a = my_function([[1, 2], [3, 4]],1)  
assert a == [[1, 2], [2, 4]]
```

Debug your solution

The following cells contain code to generate links to Python Tutor for debugging your code when running the tests. **You need to first run the cell containing your solution code before running the cell containing the Python Tutor link.**

```
from IPython.display import HTML;import urllib.parse as u;HTML('<a href="https://pyth
```

Exercise 81: Sum of i-th row and i-th column

Exercise Description

Write a function `my_function(M, i)` that is given a list of lists of numbers `M` and an integer number `i` such that:

- `M` represents a square matrix containing $D \times D$ elements: you can assume that all of its sublists have the same length and that the number `D` of rows equals the number `D` of columns.
- Integer `i` is a row and column index: it is larger than or equal to 0, and strictly smaller than `D`.

The function should return the sum of the elements in the `i`-th row and the elements in the `i`-th column. Element in row `i` and column `i` should be counted twice.

Back-of-the-envelope example: if `M = [[1, 2, 3], [4, 5, 8], [7, 8, 0]]` and `i = 2`, the code should return 26 because $7 + 8 + 0 + 3 + 8 + 0 = 26$.

Your solution

```
def my_function(M, i):  
    # assume M is a D x D matrix  
    # extract the i-th row  
    # extract the i-th column
```

```
# sum all elements of row i and all elements of column i  
# return the total (note that M[i][i] is counted twice)  
pass
```

Test your solution

```
# Test case 1 (Example)  
a = my_function([[1, 2, 3],[4, 5, 8]],[7, 8, 0]], 2)  
assert a == 26
```

Test your solution

```
# Additional tests  
a = my_function([[1, 2, 3], [4, 5, 8], [1, 8, 0]], 0)  
assert a == 12  
  
a = my_function([[1, 2],[4, 5]], 1)  
assert a == 16  
  
a = my_function([[1, 2, 3, 0], [4, 5, 8, 0], [0, 8, 0, 0], [0, 8, 0, 0]], 0)  
assert a == 11
```

Debug your solution

The following cells contain code to generate links to Python Tutor for debugging your code when running the tests. **You need to first run the cell containing your solution code before running the cell containing the Python Tutor link.**

```
from IPython.display import HTML;import urllib.parse as u;HTML('<a href="https://pyth
```

Exercise 82: Sum of items in column range

Exercise Description

Write a function `my_function(L, i, j)` that is given a list `L` of lists of numbers and two integer numbers `i` and `j`. `L` represents a matrix with `R` rows and `C` columns (`R` and `C` are not given as input). You can assume that all the `R` sublists have the same length `C`, with $0 \leq i < C$ and $0 \leq j < C$.

The function shall return the sum of items in columns between column `i` and column `j`, or 0 if the matrix is empty or $i > j$.

Back-of-the-envelope example: `my_function([[1,2,3,4],[10,20,30,40],[5,6,7,8]],1,2)` should return 68 (2+20+6+3+30+7).

Your solution

```
def my_function(L, i, j):  
    # if matrix is empty or i > j, return 0  
    # compute number of rows R  
    # iterate over rows and over columns from i to j (inclusive)  
    # accumulate the sum of selected elements  
    # return the sum  
    pass
```

Test your solution

```
# Test case 1 (Example)  
a = my_function([[1,2,3,4],[10,20,30,40]],[5,6,7,8]],1,2)  
assert a == 68
```

Test your solution

```
# Additional tests  
a = my_function([[1,2,3,4],[10,20,30,40]],[5,6,7,8]],0,1)  
assert a == 44  
  
a = my_function([[1,2,3,4],[1,2,3,4]],[5,6,7,8]],0,1)  
assert a == 17  
  
a = my_function([[1,2,3,4],[1,2,3,4]],[5,6,7,8],[10,20,30,50]],0,2)  
assert a == 90
```

Debug your solution

The following cells contain code to generate links to Python Tutor for debugging your code when running the tests. **You need to first run the cell containing your solution code before running the cell containing the Python Tutor link.**

```
from IPython.display import HTML;import urllib.parse as u;HTML('<a href="https://pyth
```

Exercise 83: Sum of items in row range

Exercise Description

Write a function `my_function(L, i, j)` that is given a list of lists of numbers `L` and two integer numbers `i` and `j`. `L` represents a matrix with `R` rows and `C` columns (`R` and `C` are not given as input). You can assume that all the `R` sublists have the same length `C`, with $0 \leq i < R$ and $0 \leq j < R$.

The function shall return the sum of items in rows between row `i` and row `j`, or `0` if the matrix is empty or $i > j$.

Back-of-the-envelope example: `my_function([[1,2,3,4],[10,20,30,40],[5,6,7,8]],1,2)` should return `126` ($10+20+30+40+5+6+7+8$).

Your solution

```
def my_function(L, i, j):  
    # if matrix is empty or i > j, return 0  
    # compute number of rows R and columns C
```

```
# iterate over columns and rows in the given range  
# accumulate the sum of selected elements  
# return the sum  
pass
```

Test your solution

```
# Test case 1 (Example)  
a = my_function([[1,2,3,4],[10,20,30,40]],[5,6,7,8]],1,2)  
assert a == 126
```

Test your solution

```
# Additional tests  
a = my_function([[1,2,3,4],[10,20,30,40]],[5,6,7,8]],0,1)  
assert a == 110  
  
a = my_function([[1,2,3,4],[1,2,3,4]],0,1)  
assert a == 20  
  
a = my_function([[1,2,3,4],[1,2,3,4]],[5,0,0,10]],0,2)  
assert a == 35
```

Debug your solution

The following cells contain code to generate links to Python Tutor for debugging your code when running the tests. **You need to first run the cell containing your solution code before running the cell containing the Python Tutor link.**

```
from IPython.display import HTML;import urllib.parse as u;HTML('<a href="https://pyth
```

Exercise 84: Sum of main diagonal

Exercise Description

Write a function `my_function(L)` that accepts a list of lists `L` of numbers. `L` represents a square matrix and you can assume that all sublists have the same length and that the number of rows equals the number of columns.

The function shall return the sum of items in the top-left to bottom-right diagonal, or 0 if the matrix is empty.

Back-of-the-envelope example: `my_function([[1,2,3],[1,2,3],[1,2,3]])` returns 6 (1+2+3).

Your solution

```
def my_function(L):  
    # compute matrix dimension n  
    # if matrix is empty, return 0  
    # iterate over i from 0 to n-1  
    # add element on the main diagonal at row i, column i  
    # return the sum  
    pass
```


Test your solution

```
# Test case 1 (Example)  
assert my_function([[1,2,3],[1,2,3],[1,2,3]]) == 6
```

Test your solution

```
# Additional tests  
assert my_function([]) == 0  
assert my_function([[1,1,1],[1,1,1],[0,0,-2]]) == 0  
  
large_matrix = [  
    [1, 2, 3, 4, 5, 6, 7, 8, 9, 10],  
    [11, 12, 13, 14, 15, 16, 17, 18, 19, 20],  
    [21, 22, 23, 24, 25, 26, 27, 28, 29, 30],  
    [31, 32, 33, 34, 35, 36, 37, 38, 39, 40],  
    [41, 42, 43, 44, 45, 46, 47, 48, 49, 50],  
    [51, 52, 53, 54, 55, 56, 57, 58, 59, 60],  
    [61, 62, 63, 64, 65, 66, 67, 68, 69, 70],  
    [71, 72, 73, 74, 75, 76, 77, 78, 79, 80],  
    [81, 82, 83, 84, 85, 86, 87, 88, 89, 90],  
    [91, 92, 93, 94, 95, 96, 97, 98, 99, 100]  
]  
assert my_function(large_matrix) == 505
```

Debug your solution

The following cells contain code to generate links to Python Tutor for debugging your code when running the tests. **You need to first run the cell containing your solution code**

before running the cell containing the Python Tutor link.

```
from IPython.display import HTML;import urllib.parse as u;HTML('<a href="https://pyth
```

Exercise 85: Sum of top-right to bottom-left diagonal

Exercise Description

Write a function `my_function(L)` that accepts a list of lists `L` of numbers. `L` represents a square matrix and you can assume that all sublists have the same length and that the number of rows equals the number of columns.

The function shall return the sum of items in the top-right to bottom-left diagonal, or 0 if the matrix is empty.

Back-of-the-envelope example: `my_function([[1,2,3],[1,2,3],[1,2,3]])` returns 6 because $3 + 2 + 1 = 6$.

Your solution

```
def my_function(L):  
    # compute matrix dimension D as the number of rows in L  
    # create a variable s initialised to 0 to store the diagonal sum  
    # for each index i from 0 to D-1  
        # access the element on the top-right to bottom-left diagonal at row i and col  
        # add this element to s
```

```
# return s as the total diagonal sum
pass
```

Test your solution

```
# Test case 1 (Example)
a = my_function([[1,2,3],[1,2,3],[1,2,3]])
assert a == 6
```

Test your solution

```
# Additional tests
a = my_function([[10,10,3],[1,10,3],[10,2,3]])
assert a == 23

a = my_function([[10, 10, 3, 1],[1, 10, 3, 9],[10, 2, 3, 10], [0, 2, 3, 10]])
assert a == 6

a = my_function([])
assert a == 0
```

Debug your solution

The following cells contain code to generate links to Python Tutor for debugging your code when running the tests. **You need to first run the cell containing your solution code before running the cell containing the Python Tutor link.**

```
from IPython.display import HTML;import urllib.parse as u;HTML('<a href="https://pyth
```

Exercise 86: Matrix transpose

Exercise Description

Let M be an $(n \times m)$ matrix of numbers organized as a list-of-lists with (n) lists where each inner list has length (m) .

Write a function called `my_function(M)` that takes as input a matrix M and returns its transpose.

Keep in mind the following caveats and definitions:

- if the input matrix is empty, the function must return `-1`
- the input list-of-lists must indeed be a valid matrix where all rows have the same length (m) : if this does not hold, the function must return `-2`
- the transpose of an $(n \times m)$ matrix is a new $(m \times n)$ matrix where the item in position (i,j) of the original matrix lies in position (j,i) in the transposed matrix

Your solution

```
def my_function(M):  
    # if matrix is empty, return -1  
    # check that all rows have the same length, otherwise return -2  
    # compute the transpose using nested loops
```

```
# return the transposed matrix  
pass
```

Test your solution

```
# Test case 1 (Example)  
M = [[1, 2, 3], [4, 5, 6], [7, 8, 9], [10, 11, 12]]  
assert my_function(M) == [[1, 4, 7, 10], [2, 5, 8, 11], [3, 6, 9, 12]]  
  
# Additional tests  
M = [[29, 10, 12, 33, 83, 28, 32, 81, 91, 84],  
      [98, 60, 84, 68, 60, 18, 65, 10, 51, 50],  
      [20, 15, 33, 33, 64, 37, 82, 50, 90, 45, 8],  
      [80, 38, 9, 43, 69, 82, 78, 39, 46, 44],  
      [38, 69, 68, 20, 62, 53, 18, 59, 12, 12],  
      [52, 14, 48, 3, 72, 64, 74, 45, 28, 97],  
      [6, 27, 4, 2, 82, 67, 79, 96, 55],  
      [23, 83, 46, 45, 17, 26, 39, 48, 9, 75],  
      [7, 58, 84, 63, 98, 25, 50, 78, 35, 30],  
      [55, 36, 22, 32, 45, 14, 14, 5, 75, 34]]  
assert my_function(M) == -2  
  
M = [[29, 10, 12, 33, 83, 28, 32, 81, 91, 84],  
      [98, 60, 84, 68, 60, 18, 65, 10, 51, 50],  
      [20, 15, 33, 33, 64, 37, 82, 50, 90, 45, 8],  
      [80, 38, 9, 43, 69, 82, 78, 39, 46, 44],  
      [38, 69, 68, 20, 62, 53, 18, 59, 12, 12],  
      [52, 14, 48, 3, 72, 64, 74, 45, 28, 97],  
      [6, 27, 4, 2, 82, 67, 79, 96, 55],  
      [23, 83, 46, 45, 17, 26, 39, 48, 9, 75],  
      [7, 58, 84, 63, 98, 25, 50, 78, 35, 30],  
      [55, 36, 22, 32, 45, 14, 14, 5, 75, 34]]
```

