

**Luiss**

Libera Università Internazionale  
degli Studi Sociali Guido Carli

# Exercises: Branching

## Introduction to Computer Programming

**Management and Artificial Intelligence**

LUISS



Recap examples

## Simple `if` statement

```
x = 10

# If x is greater than 5, this block will be executed
if x > 5:
    print("x is greater than 5")
```

### **Explanation:**

The `if` statement checks if the condition (`x > 5`) is `True`. Since `x` is 10, the condition is true, so the print statement is executed.

## if-else statement

```
x = 3

# If x is greater than 5, this block will be executed, else the other block
if x > 5:
    print("x is greater than 5")
else:
    print("x is not greater than 5")
```

x is not greater than 5

### Explanation:

The `else` block is executed if the `if` condition is `False`. Since `x = 3`, the condition is false, so the `else` block runs.

## if-elif-else statement

```
x = 6

# Checking multiple conditions using if, elif, and else
if x > 3:
    print("x is greater than 3")
elif x > 5:
    print("x is greater to 5")
else:
    print("x is less than 5")
```

x is greater than 3

### Explanation:

`elif` allows for checking multiple conditions. Here, the program checks if `x` is greater than 5, equal to 5, or less than 5. Since `x == 5`, the corresponding block is executed.

## Nested `if` statements

```
x = 10
y = 5

# Nested branching
if x > 5:
    if y > 5:
        print("Both x and y are greater than 5")
    else:
        print("x is greater than 5, but y is not")
else:
    print("x is not greater than 5, we don't know about y")
```

x is greater than 5, but y is not

### Explanation:

You can nest `if` statements within each other. In this case, the program first checks if `x > 5`, then checks if `y > 5`. Since `x > 5` and `y <= 5`, the nested `else` block is executed.

## Using `and` in conditions

```
x = 10
y = 8

# Using and to check multiple conditions
if x > 5 and y > 5:
    print("Both x and y are greater than 5")
else:
    print("At least one of x or y is not greater than 5")
```

Both x and y are greater than 5

### **Explanation:**

The `and` operator ensures that both conditions ( `x > 5` and `y > 5` ) must be `True` for the code block to run. Since both conditions are true, the first print statement is executed.

## Using `or` in conditions

```
x = 4
y = 10

# Using or to check multiple conditions
if x > 5 or y > 5:
    print("At least one of x or y is greater than 5")
else:
    print("Neither x nor y is greater than 5")
```

At least one of x or y is greater than 5

### **Explanation:**

The `or` operator ensures that if either condition is `True`, the code block will run. Since `y > 5`, the first block is executed even though `x <= 5`.



## Using `not` in conditions

```
x = 4  
  
# Using not to negate the condition  
if not x > 5:  
    print("x is not greater than 5")
```

x is not greater than 5

### **Explanation:**

The `not` operator negates the condition. Here, the condition `x > 5` is false, but `not x > 5` is true, so the print statement is executed.

## Checking for membership in a list

```
fruits = "applebananacherryapple"

# Checking if an element is in the list
if "apple" in fruits:
    print("Apple is in the string of fruits")
else:
    print("Apple is not in the string")
```

Apple is in the string of fruits

### Explanation:

The `in` operator checks if an element exists within a collection (like a list). Since "apple" is in `fruits`, the first print statement is executed.

## Ternary (conditional) operator

```
x = 7

if x > 5:
    message = "x is greater than 5"
else:
    message = "x is not greater than 5"
print(message)

# Short form of if-else using ternary operator
message = "x is greater than 5" if x > 5 else "x is not greater than 5"
print(message)
```

```
x is greater than 5
x is greater than 5
```

### Explanation:

The ternary operator allows for a shorter syntax for `if-else` statements. It evaluates `x > 5` and assigns the result to `message` accordingly. Since `x > 5`, the string "x is greater than 5" is assigned to `message`.

```
x = 5

if x > 7:
    msg = "A"
else:
    msg = "B"
print(msg)

msg = "A" if x > 7 else "B"
print(msg)
```

B  
B

**Explanation:**

The ternary operator allows for a shorter syntax for `if-else` statements. It evaluates `x > 7` and assigns the result to `msg` accordingly. Since `x > 7`, the string "B" is assigned to `msg`.

## Using `pass` for empty branches

```
x = 10

# Pass is used as a placeholder when you need a block but don't want to do anything
if x > 5:
    pass # Later logic can be added here
else:
    print("x is not greater than 5")

print(x)
```

10

### **Explanation:**

The `pass` statement is a placeholder when you need to write an empty block of code. This is useful when you plan to implement functionality later but don't want an error for an empty block.

# Exercises

- [Notebook with exercises on branching \(no hints\)](#)
- [Notebook with exercises on branching \(with pseudocode\)](#)
- [Notebook with exercises on branching \(with solutions\)](#)

