

Python: exercises on classes

This notebook was generated in **pseudocode** mode.

Exercise 1: Simple Person Class

Exercise Description

Create a class called `Person` with attributes `name` and `age`. Add a method called `introduce` that prints "Hello, my name is [name] and I am [age] years old."

Example:

```
p = Person("Alice", 30)
p.introduce()
# Output: Hello, my name is Alice and I am 30 years old.
```

After creating the class, create a `Person` object with name "Alice" and age 30, and store it in a variable called `result`.

Your solution

```
class Person:
    # step 1: define the constructor method that takes self, name, and age as parameters
```

```
# step 2: assign the name parameter to self.name
# step 3: assign the age parameter to self.age

# step 4: define the introduce method that takes self as parameter
# step 5: print a formatted string with the person's name and age

# step 6: create a Person object with name "Alice" and age 30
# step 7: store the Person object in the result variable
```

Test your solution

```
# Test the Person class
assert hasattr(result, 'name'), "Person should have a name attribute"
assert hasattr(result, 'age'), "Person should have an age attribute"
assert result.name == "Alice", "Person name should be Alice"
assert result.age == 30, "Person age should be 30"
assert hasattr(result, 'introduce'), "Person should have an introduce method"
```

Test your solution

```
# Test creating different Person objects
p2 = Person("Bob", 25)
assert p2.name == "Bob"
assert p2.age == 25

# Test that objects are independent
assert result.name != p2.name
assert result.age != p2.age
```

Debug your solution

The following cells contain code to generate links to Python Tutor for debugging your code when running the tests. **You need to first run the cell containing your solution code**

before running the cell containing the Python Tutor link.

```
from IPython.display import HTML;import urllib.parse as u;HTML('<a href="https://pyth
```

Exercise 2: Dog Class with Default Values

Exercise Description

Create a class called `Dog` with attributes `name` and `breed`. If no breed is provided, default it to `"Unknown"`. Add a method `bark` that prints `"Woof! I am a [breed]!"`.

Example:

```
d1 = Dog("Max", "Golden Retriever")
d1.bark()
# Output: Woof! I am a Golden Retriever!

d2 = Dog("Buddy")
d2.bark()
# Output: Woof! I am an Unknown!
```

After creating the class, create two `Dog` objects: one with name "Max" and breed "Golden Retriever", and another with just name "Buddy". Store them in variables called `result1` and `result2`.

Your solution

```
class Dog:
    # step 1: define the constructor method that takes self, name, and breed with de
```

```
# step 2: assign the name parameter to self.name
# step 3: assign the breed parameter to self.breed

# step 4: define the bark method that takes self as parameter
# step 5: print a formatted string with "Woof! I am a" and the breed

# step 6: create a Dog object with name "Max" and breed "Golden Retriever"
# step 7: create a Dog object with just name "Buddy" (using default breed)
# step 8: store the Dog objects in result1 and result2 variables
```

Test your solution

```
# Test the Dog class with specified breed
assert hasattr(result1, 'name'), "Dog should have a name attribute"
assert hasattr(result1, 'breed'), "Dog should have a breed attribute"
assert result1.name == "Max", "First dog name should be Max"
assert result1.breed == "Golden Retriever", "First dog breed should be Golden Retriever"
assert hasattr(result1, 'bark'), "Dog should have a bark method"
```

Test your solution

```
# Test the Dog class with default breed
assert result2.name == "Buddy", "Second dog name should be Buddy"
assert result2.breed == "Unknown", "Second dog breed should default to Unknown"

# Test that objects are independent
assert result1.name != result2.name
assert result1.breed != result2.breed
```

Debug your solution

The following cells contain code to generate links to Python Tutor for debugging your code when running the tests. **You need to first run the cell containing your solution code**

before running the cell containing the Python Tutor link.

```
from IPython.display import HTML;import urllib.parse as u;HTML('<a href="https://pyth
```

Exercise 3: Rectangle Class with Methods

Exercise Description

Create a class `Rectangle` with attributes `length` and `width`. Add a method `area` that returns the area of the rectangle and a method `perimeter` that returns the perimeter.

Example:

```
r = Rectangle(5, 3)
print(r.area())      # Output: 15
print(r.perimeter()) # Output: 16
```

After creating the class, create a `Rectangle` object with length 5 and width 3, and store it in a variable called `result`.

Your solution

```
class Rectangle:
    # step 1: define the constructor method that takes self, length, and width as parameters
    # step 2: assign the length parameter to self.length
    # step 3: assign the width parameter to self.width

    # step 4: define the area method that takes self as parameter
    # step 5: return the product of length and width
```

```
# step 6: define the perimeter method that takes self as parameter  
# step 7: return 2 times the sum of length and width
```

```
# step 8: create a Rectangle object with length 5 and width 3  
# step 9: store the Rectangle object in the result variable
```

Test your solution

```
# Test the Rectangle class  
assert hasattr(result, 'length'), "Rectangle should have a length attribute"  
assert hasattr(result, 'width'), "Rectangle should have a width attribute"  
assert result.length == 5, "Rectangle length should be 5"  
assert result.width == 3, "Rectangle width should be 3"  
assert hasattr(result, 'area'), "Rectangle should have an area method"  
assert hasattr(result, 'perimeter'), "Rectangle should have a perimeter method"
```

Test your solution

```
# Test the methods  
assert result.area() == 15, "Area should be 15 (5 * 3)"  
assert result.perimeter() == 16, "Perimeter should be 16 (2 * (5 + 3))"  
  
# Test with different rectangle  
r2 = Rectangle(4, 6)  
assert r2.area() == 24, "Area should be 24 (4 * 6)"  
assert r2.perimeter() == 20, "Perimeter should be 20 (2 * (4 + 6))"
```

Debug your solution

The following cells contain code to generate links to Python Tutor for debugging your code when running the tests. **You need to first run the cell containing your solution code before running the cell containing the Python Tutor link.**

```
from IPython.display import HTML;import urllib.parse as u;HTML('<a href="https://pyth
```

Exercise 4: Bank Account Class

Exercise Description

Create a class `BankAccount` with attributes `balance` (initialized to 0). Add methods `deposit` to add to the balance and `withdraw` to subtract from the balance.

Example:

```
account = BankAccount()  
account.deposit(100)  
account.withdraw(40)  
print(account.balance)  # Output: 60
```

After creating the class, create a `BankAccount` object, deposit 100, withdraw 40, and store the account in a variable called `result`.

Your solution

```
class BankAccount:  
    # step 1: define the constructor method that takes self as parameter  
    # step 2: initialize self.balance to 0  
  
    # step 3: define the deposit method that takes self and amount as parameters  
    # step 4: add the amount to self.balance
```

```
# step 5: define the withdraw method that takes self and amount as parameters  
# step 6: subtract the amount from self.balance  
  
# step 7: create a BankAccount object  
# step 8: call deposit method with 100  
# step 9: call withdraw method with 40  
# step 10: store the BankAccount object in the result variable
```

Test your solution

```
# Test the BankAccount class  
assert hasattr(result, 'balance'), "BankAccount should have a balance attribute"  
assert hasattr(result, 'deposit'), "BankAccount should have a deposit method"  
assert hasattr(result, 'withdraw'), "BankAccount should have a withdraw method"  
assert result.balance == 60, "Balance should be 60 after deposit 100 and withdraw 40"
```

Test your solution

```
# Test with new account  
account2 = BankAccount()  
assert account2.balance == 0, "New account should start with balance 0"  
  
account2.deposit(50)  
assert account2.balance == 50, "Balance should be 50 after deposit"  
  
account2.withdraw(20)  
assert account2.balance == 30, "Balance should be 30 after withdraw"
```

Debug your solution

The following cells contain code to generate links to Python Tutor for debugging your code when running the tests. **You need to first run the cell containing your solution code before running the cell containing the Python Tutor link.**


```
from IPython.display import HTML;import urllib.parse as u;HTML('<a href="https://pyth
```

Exercise 5: Private Bank Account Class

Exercise Description

Modify `BankAccount` to have a private `balance` attribute (e.g., `_balance`). Ensure users can only view or change the balance through `deposit`, `withdraw`, and `get_balance` methods.

Example:

```
account = BankAccount()  
account.deposit(100)  
account.withdraw(40)  
print(account.get_balance())  # Output: 60
```

After creating the class, create a `BankAccount` object, deposit 100, withdraw 40, and store the account in a variable called `result`.

Your solution

```
class BankAccount:  
    # step 1: define the constructor method that takes self as parameter  
    # step 2: initialize self._balance to 0 (private attribute with underscore)  
  
    # step 3: define the deposit method that takes self and amount as parameters  
    # step 4: add the amount to self._balance
```

```
# step 5: define the withdraw method that takes self and amount as parameters
# step 6: subtract the amount from self._balance

# step 7: define the get_balance method that takes self as parameter
# step 8: return self._balance

# step 9: create a BankAccount object
# step 10: call deposit method with 100
# step 11: call withdraw method with 40
# step 12: store the BankAccount object in the result variable
```

Test your solution

```
# Test the BankAccount class with private balance
assert hasattr(result, '_balance'), "BankAccount should have a _balance private attri
assert hasattr(result, 'deposit'), "BankAccount should have a deposit method"
assert hasattr(result, 'withdraw'), "BankAccount should have a withdraw method"
assert hasattr(result, 'get_balance'), "BankAccount should have a get_balance method"
assert result.get_balance() == 60, "Balance should be 60 after deposit 100 and withdr
```

Test your solution

```
# Test with new account
account2 = BankAccount()
assert account2.get_balance() == 0, "New account should start with balance 0"

account2.deposit(75)
assert account2.get_balance() == 75, "Balance should be 75 after deposit"

account2.withdraw(25)
assert account2.get_balance() == 50, "Balance should be 50 after withdraw"
```

Debug your solution

The following cells contain code to generate links to Python Tutor for debugging your code when running the tests. **You need to first run the cell containing your solution code before running the cell containing the Python Tutor link.**

```
from IPython.display import HTML;import urllib.parse as u;HTML('<a href="https://pyth
```

Exercise 6: Vehicle Inheritance

Exercise Description

Create a `Vehicle` class with an attribute `speed` and a method `move`. Then, create a subclass `Car` that adds an attribute `fuel`.

Example:

```
v = Vehicle(60)
c = Car(100, "Full")
```

After creating the classes, create a `Vehicle` object with speed 60 and a `Car` object with speed 100 and fuel "Full". Store them in variables called `result1` and `result2`.

Your solution

```
class Vehicle:
    # step 1: define the constructor method that takes self and speed as parameters
    # step 2: assign the speed parameter to self.speed
```

```
# step 3: define the move method that takes self as parameter
# step 4: print a formatted string with "Moving at" and the speed
```

```
class Car:
```

```
# step 5: inherit from Vehicle class using parentheses
# step 6: define the constructor method that takes self, speed, and fuel as parameters
# step 7: call the parent constructor using super().__init__(speed)
# step 8: assign the fuel parameter to self.fuel
```

```
# step 9: create a Vehicle object with speed 60
# step 10: create a Car object with speed 100 and fuel "Full"
# step 11: store the objects in result1 and result2 variables
```

Test your solution

```
# Test the Vehicle class
assert hasattr(result1, 'speed'), "Vehicle should have a speed attribute"
assert hasattr(result1, 'move'), "Vehicle should have a move method"
assert result1.speed == 60, "Vehicle speed should be 60"

# Test the Car class
assert hasattr(result2, 'speed'), "Car should have a speed attribute"
assert hasattr(result2, 'fuel'), "Car should have a fuel attribute"
assert hasattr(result2, 'move'), "Car should inherit move method"
assert result2.speed == 100, "Car speed should be 100"
assert result2.fuel == "Full", "Car fuel should be Full"
```

Test your solution

```
# Test inheritance
assert isinstance(result2, Car), "result2 should be an instance of Car"
```

```
assert isinstance(result2, Vehicle), "result2 should also be an instance of Vehicle"
assert not isinstance(result1, Car), "result1 should not be an instance of Car"
```

Debug your solution

The following cells contain code to generate links to Python Tutor for debugging your code when running the tests. **You need to first run the cell containing your solution code before running the cell containing the Python Tutor link.**

```
from IPython.display import HTML;import urllib.parse as u;HTML('<a href="https://pyth
```

Exercise 7: Person String Representation

Exercise Description

Modify `Person` to add `__str__` to return a readable representation.

Example:

```
p = Person("Bob", 25)
print(p)  # Output: Bob, 25 years old
```

After creating the class, create a `Person` object with name "Bob" and age 25, and store it in a variable called `result`.

Your solution

```
class Person:
    # step 1: define the constructor method that takes self, name, and age as parameters
```

```
# step 2: assign the name parameter to self.name
# step 3: assign the age parameter to self.age

# step 4: define the __str__ method that takes self as parameter
# step 5: return a formatted string with name, comma, age, and "years old"

# step 6: create a Person object with name "Bob" and age 25
# step 7: store the Person object in the result variable
```

Test your solution

```
# Test the Person class
assert hasattr(result, 'name'), "Person should have a name attribute"
assert hasattr(result, 'age'), "Person should have an age attribute"
assert result.name == "Bob", "Person name should be Bob"
assert result.age == 25, "Person age should be 25"
assert hasattr(result, '__str__'), "Person should have a __str__ method"
```

Test your solution

```
# Test string representation
assert str(result) == "Bob, 25 years old", "String representation should be 'Bob, 25"

# Test with different person
p2 = Person("Alice", 30)
assert str(p2) == "Alice, 30 years old", "String representation should be 'Alice, 30"
```

Debug your solution

The following cells contain code to generate links to Python Tutor for debugging your code when running the tests. **You need to first run the cell containing your solution code before running the cell containing the Python Tutor link.**

```
from IPython.display import HTML;import urllib.parse as u;HTML('<a href="https://pyth
```

Exercise 8: Calculator Static Method

Exercise Description

Create a class `Calculator` with a static method `add`.

Example:

```
print(Calculator.add(5, 3)) # Output: 8
```

After creating the class, call `Calculator.add(5, 3)` and store the result in a variable called `result`.

Your solution

```
class Calculator:
    # step 1: use the @staticmethod decorator
    # step 2: define the add method that takes x and y as parameters (no self)
    # step 3: return the sum of x and y

    # step 4: call Calculator.add with arguments 5 and 3
    # step 5: store the result in the result variable
```

Test your solution

```
# Test the Calculator class
assert hasattr(Calculator, 'add'), "Calculator should have an add method"
```

```
assert result == 8, "Calculator.add(5, 3) should return 8"
```

```
# Test that it's a static method (can be called without instance)
```

```
assert Calculator.add(10, 20) == 30, "Calculator.add(10, 20) should return 30"
```

Test your solution

```
# Test with different values
```

```
assert Calculator.add(0, 0) == 0, "Calculator.add(0, 0) should return 0"
```

```
assert Calculator.add(-5, 5) == 0, "Calculator.add(-5, 5) should return 0"
```

```
assert Calculator.add(100, 200) == 300, "Calculator.add(100, 200) should return 300"
```

Debug your solution

The following cells contain code to generate links to Python Tutor for debugging your code when running the tests. **You need to first run the cell containing your solution code before running the cell containing the Python Tutor link.**

```
from IPython.display import HTML;import urllib.parse as u;HTML('<a href="https://pyth
```

Exercise 9: Inventory Management System

Exercise Description

Create a class `Product` with attributes `name`, `price`, and `quantity`. Add a method `total_value` that calculates the total value of the product (`price * quantity`). Then, create an `Inventory` class that manages multiple `Product` objects. The `Inventory` class should have methods to:

- Add a product.
- Remove a product by name.
- Calculate the total inventory value.

Example:

```
p1 = Product("Laptop", 1500, 10)
p2 = Product("Phone", 800, 20)
inventory = Inventory()
inventory.add_product(p1)
inventory.add_product(p2)
print(inventory.total_value()) # Output: 31000
```

After creating the classes, create the example scenario above and store the inventory in a variable called `result`.

Your solution

```
class Product:
    # step 1: define the constructor method that takes self, name, price, and quantity
    # step 2: assign the name parameter to self.name
    # step 3: assign the price parameter to self.price
    # step 4: assign the quantity parameter to self.quantity

    # step 5: define the total_value method that takes self as parameter
    # step 6: return the product of self.price and self.quantity

class Inventory:
    # step 7: define the constructor method that takes self as parameter
    # step 8: initialize self.products as an empty list

    # step 9: define the add_product method that takes self and product as parameters
```

```

# step 10: append the product to self.products list

# step 11: define the remove_product method that takes self and name as parameter
# step 12: create a new empty list called new_products
# step 13: iterate through each product in self.products
# step 14: if the product name is not equal to the given name, append it
# step 15: assign new_products to self.products

# step 16: define the total_value method that takes self as parameter
# step 17: initialize total to 0
# step 18: iterate through each product in self.products
# step 19: add the product's total_value to total
# step 20: return total

# step 21: create Product p1 with "Laptop", 1500, 10
# step 22: create Product p2 with "Phone", 800, 20
# step 23: create Inventory object
# step 24: add p1 to inventory
# step 25: add p2 to inventory
# step 26: store the inventory in result variable

```

Test your solution

```

# Test the Product class
p_test = Product("Test", 100, 5)
assert hasattr(p_test, 'name'), "Product should have a name attribute"
assert hasattr(p_test, 'price'), "Product should have a price attribute"
assert hasattr(p_test, 'quantity'), "Product should have a quantity attribute"
assert hasattr(p_test, 'total_value'), "Product should have a total_value method"
assert p_test.total_value() == 500, "Product total_value should be 500 (100 * 5)"

```

Test your solution

```
# Test the Inventory class
assert hasattr(result, 'products'), "Inventory should have a products attribute"
assert hasattr(result, 'add_product'), "Inventory should have an add_product method"
assert hasattr(result, 'remove_product'), "Inventory should have a remove_product method"
assert hasattr(result, 'total_value'), "Inventory should have a total_value method"
assert len(result.products) == 2, "Inventory should have 2 products"
assert result.total_value() == 31000, "Total inventory value should be 31000 (15000 + 16000)"
```

Debug your solution

The following cells contain code to generate links to Python Tutor for debugging your code when running the tests. **You need to first run the cell containing your solution code before running the cell containing the Python Tutor link.**

```
from IPython.display import HTML;import urllib.parse as u;HTML('<a href="https://pyth
```

Exercise 10: Library System

Exercise Description

Create a `Book` class with attributes `title`, `author`, and `is_checked_out` (default to `False`). Add methods `check_out` and `return_book` to update `is_checked_out`. Create a `Library` class that manages a collection of books. The `Library` class should have methods to:

- Add a book.
- Check out a book by title (if it's available).
- Return a book by title.
- List all books and their status.

Example:

```
b1 = Book("1984", "George Orwell")
b2 = Book("To Kill a Mockingbird", "Harper Lee")
library = Library()
library.add_book(b1)
library.add_book(b2)
library.check_out("1984")
```

After creating the classes, create the example scenario above and store the library in a variable called `result`.

Your solution

```
class Book:
    # step 1: define the constructor method that takes self, title, and author as parameters
    # step 2: assign the title parameter to self.title
    # step 3: assign the author parameter to self.author
    # step 4: set self.is_checked_out to False

    # step 5: define the check_out method that takes self as parameter
    # step 6: if self.is_checked_out is False, set it to True and return True
    # step 7: otherwise return False

    # step 8: define the return_book method that takes self as parameter
    # step 9: set self.is_checked_out to False
```

class Library:

```
# step 10: define the constructor method that takes self as parameter
# step 11: initialize self.books as an empty list

# step 12: define the add_book method that takes self and book as parameters
# step 13: append the book to self.books list

# step 14: define the check_out method that takes self and title as parameters
# step 15: iterate through each book in self.books
# step 16: if the book title matches and is not checked out, call book.check_out
# step 17: return "Book not available" if not found or already checked out

# step 18: define the return_book method that takes self and title as parameters
# step 19: iterate through each book in self.books
# step 20: if the book title matches and is checked out, call book.return_book
# step 21: return "Book not found or not checked out" if not found

# step 22: define the list_books method that takes self as parameter
# step 23: iterate through each book in self.books
# step 24: determine status based on is_checked_out ("Checked Out" or "Available")
# step 25: print the book title and status

# step 26: create Book b1 with "1984" and "George Orwell"
# step 27: create Book b2 with "To Kill a Mockingbird" and "Harper Lee"
# step 28: create Library object
# step 29: add b1 to library
# step 30: add b2 to library
# step 31: check out "1984"
# step 32: store the library in result variable
```

Test your solution

```
# Test the Book class
b_test = Book("Test Book", "Test Author")
```

```
assert hasattr(b_test, 'title'), "Book should have a title attribute"
assert hasattr(b_test, 'author'), "Book should have an author attribute"
assert hasattr(b_test, 'is_checked_out'), "Book should have an is_checked_out attribute"
assert b_test.is_checked_out == False, "Book should start as not checked out"
assert hasattr(b_test, 'check_out'), "Book should have a check_out method"
assert hasattr(b_test, 'return_book'), "Book should have a return_book method"
```

Test your solution

```
# Test the Library class and scenario
assert hasattr(result, 'books'), "Library should have a books attribute"
assert len(result.books) == 2, "Library should have 2 books"
assert result.books[0].title == "1984", "First book should be 1984"
assert result.books[0].is_checked_out == True, "1984 should be checked out"
assert result.books[1].is_checked_out == False, "To Kill a Mockingbird should be available"
```

Debug your solution

The following cells contain code to generate links to Python Tutor for debugging your code when running the tests. **You need to first run the cell containing your solution code before running the cell containing the Python Tutor link.**

```
from IPython.display import HTML;import urllib.parse as u;HTML('<a href="https://pyth
```

Exercise 11: Employee Management System with Inheritance

Exercise Description

Create a base class `Employee` with attributes `name`, `id`, and `salary`. Add a method `get_details` to display basic details. Create two subclasses `Manager` and `Developer` that inherit from `Employee`.

- `Manager` should have an additional attribute `team_size`.
- `Developer` should have an additional attribute `programming_language`. Each subclass should override the `get_details` method to display specific information.

Example:

```
m = Manager("Alice", 1, 75000, 5)
d = Developer("Bob", 2, 60000, "Python")
print(m.get_details())
print(d.get_details())
# Output: Manager: Alice, ID: 1, Salary: 75000, Team Size: 5
#          Developer: Bob, ID: 2, Salary: 60000, Language: Python
```

After creating the classes, create the example scenario above and store the manager and developer in variables called `result1` and `result2`.

Your solution

```
class Employee:
    # step 1: define the constructor method that takes self, name, id, and salary as
    # step 2: assign the name parameter to self.name
    # step 3: assign the id parameter to self.id
    # step 4: assign the salary parameter to self.salary

    # step 5: define the get_details method that takes self as parameter
    # step 6: return a formatted string with "Employee:", name, "ID:", id, "Salari
```

```

class Manager:
    # step 7: inherit from Employee class using parentheses
    # step 8: define the constructor method that takes self, name, id, salary, and team_size
    # step 9: call the parent constructor using super().__init__(name, id, salary, team_size)
    # step 10: assign the team_size parameter to self.team_size

    # step 11: define the get_details method that takes self as parameter (override)
    # step 12: return a formatted string with "Manager:", name, "ID:", id, "Salary:", salary, "Team Size:", team_size

class Developer:
    # step 13: inherit from Employee class using parentheses
    # step 14: define the constructor method that takes self, name, id, salary, and programming_language
    # step 15: call the parent constructor using super().__init__(name, id, salary, team_size)
    # step 16: assign the programming_language parameter to self.programming_language

    # step 17: define the get_details method that takes self as parameter (override)
    # step 18: return a formatted string with "Developer:", name, "ID:", id, "Salary:", salary, "Programming Language:", programming_language

# step 19: create Manager with "Alice", 1, 75000, 5
# step 20: create Developer with "Bob", 2, 60000, "Python"
# step 21: store the objects in result1 and result2 variables

```

Test your solution

```

# Test the Employee base class
e_test = Employee("Test", 999, 50000)
assert hasattr(e_test, 'name'), "Employee should have a name attribute"
assert hasattr(e_test, 'id'), "Employee should have an id attribute"
assert hasattr(e_test, 'salary'), "Employee should have a salary attribute"
assert hasattr(e_test, 'get_details'), "Employee should have a get_details method"

```

Test your solution


```

# Test the Manager class
assert isinstance(result1, Manager), "result1 should be a Manager instance"
assert isinstance(result1, Employee), "result1 should also be an Employee instance (i
assert hasattr(result1, 'team_size'), "Manager should have a team_size attribute"
assert result1.get_details() == "Manager: Alice, ID: 1, Salary: 75000, Team Size: 5"

# Test the Developer class
assert isinstance(result2, Developer), "result2 should be a Developer instance"
assert isinstance(result2, Employee), "result2 should also be an Employee instance (i
assert hasattr(result2, 'programming_language'), "Developer should have a programming
assert result2.get_details() == "Developer: Bob, ID: 2, Salary: 60000, Language: Pyth

```

Debug your solution

The following cells contain code to generate links to Python Tutor for debugging your code when running the tests. **You need to first run the cell containing your solution code before running the cell containing the Python Tutor link.**

```

from IPython.display import HTML;import urllib.parse as u;HTML('<a href="https://pyth

```

Exercise 12: E-commerce Order System

Exercise Description

Create a `Product` class with attributes `name` and `price`. Create an `Order` class that manages a list of `Product` objects. The `Order` class should have methods to:

- Add a product to the order.
- Remove a product by name.
- Calculate the total order value.

Example:

```
p1 = Product("Laptop", 1000)
p2 = Product("Headphones", 50)
order = Order()
order.add_product(p1)
order.add_product(p2)
print(order.total_order_value()) # Output: 1050
```

After creating the classes, create the example scenario above and store the order in a variable called `result`.

Your solution

```
class Product:
    # step 1: define the constructor method that takes self, name, and price as parameters
    # step 2: assign the name parameter to self.name
    # step 3: assign the price parameter to self.price

class Order:
    # step 4: define the constructor method that takes self as parameter
    # step 5: initialize self.products as an empty list

    # step 6: define the add_product method that takes self and product as parameters
    # step 7: append the product to self.products list

    # step 8: define the remove_product method that takes self and name as parameters
    # step 9: create a new empty list called new_products
```

```

        # step 10: iterate through each product in self.products
        # step 11: if the product name is not equal to the given name, append it
        # step 12: assign new_products to self.products

    # step 13: define the total_order_value method that takes self as parameter
    # step 14: initialize total to 0
    # step 15: iterate through each product in self.products
    # step 16: add the product's price to total
    # step 17: return total

# step 18: create Product p1 with "Laptop" and 1000
# step 19: create Product p2 with "Headphones" and 50
# step 20: create Order object
# step 21: add p1 to order
# step 22: add p2 to order
# step 23: store the order in result variable

```

Test your solution

```

# Test the Product class
p_test = Product("Test", 100)
assert hasattr(p_test, 'name'), "Product should have a name attribute"
assert hasattr(p_test, 'price'), "Product should have a price attribute"
assert p_test.name == "Test", "Product name should be Test"
assert p_test.price == 100, "Product price should be 100"

```

Test your solution

```

# Test the Order class
assert hasattr(result, 'products'), "Order should have a products attribute"
assert hasattr(result, 'add_product'), "Order should have an add_product method"
assert hasattr(result, 'remove_product'), "Order should have a remove_product method"
assert hasattr(result, 'total_order_value'), "Order should have a total_order_value n

```

```
assert len(result.products) == 2, "Order should have 2 products"
assert result.total_order_value() == 1050, "Total order value should be 1050 (1000 +
```

Debug your solution

The following cells contain code to generate links to Python Tutor for debugging your code when running the tests. **You need to first run the cell containing your solution code before running the cell containing the Python Tutor link.**

```
from IPython.display import HTML;import urllib.parse as u;HTML('<a href="https://pyth
```

Exercise 13: School Grading System

Exercise Description

Create a `Student` class with attributes `name`, `grades` (a list of integers), and methods:

- `add_grade` to add a grade.
- `average_grade` to calculate the average grade. Create a `Course` class that manages a list of `Student` objects. The `Course` class should have methods to:
 - Add a student.
 - Display all students' names and their average grade.

Example:

```
s1 = Student("Alice", [90, 80, 85])
s2 = Student("Bob", [70, 75, 80])
course = Course()
```

```
course.add_student(s1)
course.add_student(s2)
course.display_students()
# Output: Alice - Average Grade: 85.0
#         Bob - Average Grade: 75.0
```

After creating the classes, create the example scenario above and store the course in a variable called `result`.

Your solution

```
class Student:
    # step 1: define the constructor method that takes self, name, and grades with default value
    # step 2: assign the name parameter to self.name
    # step 3: if grades is provided, assign it to self.grades, otherwise assign empty list

    # step 4: define the add_grade method that takes self and grade as parameters
    # step 5: append the grade to self.grades list

    # step 6: define the average_grade method that takes self as parameter
    # step 7: if self.grades is not empty, return the sum divided by length
    # step 8: otherwise return 0

class Course:
    # step 9: define the constructor method that takes self as parameter
    # step 10: initialize self.students as an empty list

    # step 11: define the add_student method that takes self and student as parameter
    # step 12: append the student to self.students list

    # step 13: define the display_students method that takes self as parameter
    # step 14: iterate through each student in self.students
    # step 15: print the student name, dash, "Average Grade:", and the average grade
```

```
# step 16: create Student s1 with "Alice" and grades [90, 80, 85]
# step 17: create Student s2 with "Bob" and grades [70, 75, 80]
# step 18: create Course object
# step 19: add s1 to course
# step 20: add s2 to course
# step 21: store the course in result variable
```

Test your solution

```
# Test the Student class
s_test = Student("Test", [80, 90, 100])
assert hasattr(s_test, 'name'), "Student should have a name attribute"
assert hasattr(s_test, 'grades'), "Student should have a grades attribute"
assert hasattr(s_test, 'add_grade'), "Student should have an add_grade method"
assert hasattr(s_test, 'average_grade'), "Student should have an average_grade method"
assert s_test.average_grade() == 90.0, "Average should be 90.0 for grades [80, 90, 100]"
```

Test your solution

```
# Test the Course class and scenario
assert hasattr(result, 'students'), "Course should have a students attribute"
assert hasattr(result, 'add_student'), "Course should have an add_student method"
assert hasattr(result, 'display_students'), "Course should have a display_students method"
assert len(result.students) == 2, "Course should have 2 students"
assert result.students[0].name == "Alice", "First student should be Alice"
assert result.students[0].average_grade() == 85.0, "Alice's average should be 85.0"
assert result.students[1].name == "Bob", "Second student should be Bob"
assert result.students[1].average_grade() == 75.0, "Bob's average should be 75.0"
```

Debug your solution

The following cells contain code to generate links to Python Tutor for debugging your code

