

Introduction to Computer Programming

Prof. Alessio Martino

amartino@luiss.it

Department of Business and Management
Viale Romania 32, 00197 Rome



A.Y. 2024-2025

Mutability

Recall


Lists are **mutable**.

The assignment of an element at a given index changes the value!

```
>>> L = [2, 1, 3]
>>> L[1] = 5
>>> print(L)
[2, 5, 3]
```

Note

This is the **same object** L.



Iterating

Example: compute the sum of elements of a list.

Common strategy? Iterate over the elements of the list.

```
L = [2, 5, 3]
total = 0
for i in range(len(L)):
    total += L[i]
print(total)
```

```
L = [2, 5, 3]
total = 0
for i in L:
    total += i
print(total)
```

Note

- just like strings, you can iterate over list elements directly (right panel)
- list elements are indexed from 0 to `len(L)-1`
- `range(n)` goes from 0 to `n-1`

Basic Operations

Add elements to the end of a list L with:

```
L.append(<elements>)
```

Example:

```
>>> L = [2, 1, 3]
>>> L.append(5)    # lists are objects with data, methods and functions
>>> print(L)
[2, 1, 3, 5]
```

Note

append() mutates the list!

Note

Like methods in strings, methods in lists also use the dot notation.

Concatenate lists L1 and L2 together with:

`L1.extend(L2)`

or

`L1 + L2`

Example:

```
>>> L1 = [2, 1, 3]
>>> L2 = [4, 5, 6]
>>> L3 = L1 + L2    # L3 = [2, 1, 3, 4, 5, 6], L1 and L2 unchanged
>>> L1.extend(L2)    # L1 = [2, 1, 3, 4, 5, 6], L2 unchanged
```

Note

`extend()` mutates the list, whereas the `+` operator returns a new list.

Other Operations

Python has a set of built-in methods that you can use on lists.

You can find the full list at

<https://docs.python.org/3/tutorial/datastructures.html>

Note

Some list methods return new values. All main list methods mutate the list in-place.

Let's go through the most popular ones, shall we?


To mutate or not to mutate, that is the question.

- calling `sort()` mutates the list, returns nothing (`None`)
- calling `sorted()` does not mutate the list, must assign to a new variable

```
warm = ['red', 'yellow', 'orange']
sortedwarm = warm.sort()
print(warm)
print(sortedwarm)
```

Print output (drag lower right corner to resize)


```
['orange', 'red', 'yellow']
None
```



```
cool = ['grey', 'blue', 'green']
sortedcool = sorted(cool)
print(cool)
print(sortedcool)
```

Print output (drag lower right corner to resize)


```
['grey', 'blue', 'green']
['blue', 'green', 'grey']
```



Aliasing & Cloning

Aliasing: if `a` refers to an object and you assign `b = a`, then both variables refer to the same object.

```
>>> a = [1, 2, 3]
>>> b = a
>>> b is a
True
```



Reference: association of a variable with an object (in the example above, two references to the same object)

Aliased: an object with more than one reference has more than one name, so we say that the object is *aliased*.

If the aliased object is mutable (like lists), changes made to one alias affect the other:

```
>>> a = [1, 2, 3]
>>> b = a
>>> b[0] = 42
>>> print(b)
[42, 2, 3]
>>> print(a)
[42, 2, 3]
```

Warning

This aspect can be useful, but **error-prone**!

Hint

To be safe, **avoid aliasing** when working **with mutable objects**.

The aliasing side-effect also holds for list methods we saw earlier:

```
>>> warm = ['red', 'yellow', 'orange']
>>> hot = warm # we have an alias here
>>> hot.append('pink')
>>> print(hot)
>>> print(warm) # Breakpoint 1
>>> warm.sort()
>>> print(hot)
>>> print(warm) # Breakpoint 2
```

Print output (drag lower right corner to resize)


```
['red', 'yellow', 'orange', 'pink']
['red', 'yellow', 'orange', 'pink']
['red', 'yellow', 'orange', 'pink']
```



(a) Breakpoint 1

Print output (drag lower right corner to resize)

```
['red', 'yellow', 'orange', 'pink']
['red', 'yellow', 'orange', 'pink']
['orange', 'pink', 'red', 'yellow']
['orange', 'pink', 'red', 'yellow']
```




(b) Breakpoint 2

Cloning: create a new list (different object) by copying every element via assignment `b = a[:]`

```
>>> cool = ['blue', 'green', 'grey']  
>>> chill = cool[:] # we have a clone here  
>>> chill.append('black')  
>>> print(cool)  
>>> print(chill)
```

Print output (drag lower right corner to resize)

```
['blue', 'green', 'grey']  
['blue', 'green', 'grey', 'black']
```



Warning

Never mutate a list as you iterate through it.

Example: write a function that removes duplicates from two lists.

<pre>def remove_dups(L1, L2): for item in L1: if item in L2: L1.remove(item) return L1</pre>	<pre>def remove_dups(L1, L2): L1copy = L1[:] for item in L1copy: if item in L2: L1.remove(item) return L1</pre>
--	---

```
L1 = [1,2,3,4]
```

```
L2 = [1,2,5,6]
```

```
print(remove_dups(L1, L2)) # left panel returns [2, 3, 4]
```

```
print(remove_dups(L1, L2)) # right panel returns [3, 4]
```

Left panel is incorrect. Why?

- Python uses an internal counter to keep track of the position in the loop
- Mutation changes the length, but Python does not update the counter
- The loop never visits element 2 in L1

Nesting

Recall

Lists can be heterogeneous. An element of a list can itself be a list.


Warning

Mutation and aliasing affect also nested lists.

```
warm = ['yellow', 'orange']
hot = ['red']
brightcolors = [warm]
brightcolors.append(hot)
print(brightcolors)
hot.append('pink')
print(hot)
print(brightcolors)
```

Print output (drag lower right corner to resize)

```
[[['yellow', 'orange'], ['red']]
 [['red', 'pink']]
 [['yellow', 'orange'], ['red', 'pink']]]
```



References

- Gutttag, J. V. (2013). *Introduction to Computation and Programming using Python (Revised and Expanded Edition)*. MIT Press. [Sections 5.2 and 5.4]
- Downey, A. (2015). *Think Python*. Green Tea Press ed. 2nd. [Chapter 10]

