

Python: Recap II

This notebook was generated in **student** mode.

Exercise 1: Circle

Exercise Description

Create a Python class called `Circle` that models a geometric circle. The class should have the following features:

1. Attributes:

- radius: A numeric attribute representing the radius of the circle.

2. Methods:

- `__init__(self, radius)`: A constructor method to initialize the radius attribute when a Circle object is created.
- `get_area(self)`: A method that returns the area of the circle (use the formula $\pi \times \text{radius}^2$).
- `get_perimeter(self)`: A method that returns the perimeter (circumference) of the circle (use the formula $2 \times \pi \times \text{radius}$).
- `display_info(self)`: A method that prints the radius, area, and perimeter of the circle.

Your solution

```
# Write your solution here
```

Test your solution

```
# Test the Circle class
circle = Circle(5)
assert circle.radius == 5, "Test failed: Incorrect radius"

# Test area calculation
```

```
area = circle.get_area()
assert abs(area - 78.54) < 0.1, "Test failed: Incorrect area calculation"

# Test perimeter calculation
perimeter = circle.get_perimeter()
assert abs(perimeter - 31.42) < 0.1, "Test failed: Incorrect perimeter calculation"

# Test display_info method exists
circle.display_info()
```

Debug your solution

The following cells contain code to generate links to Python Tutor for debugging your code when running the tests. **You need to first run the cell containing your solution code before running the cell containing the Python Tutor link.**

```
from IPython.display import HTML;import urllib.parse as u;HTML('<a href="https://pyth
```

Exercise 2: Library Book

Exercise Description

Create a Python class called Book that models a book in a library. The class should have the following features:

1. Attributes:

- `title`: A string representing the title of the book.
- `author`: A string representing the author of the book.
- `isbn`: A string representing the unique ISBN number of the book.
- `is_checked_out`: A boolean attribute indicating if the book is currently checked out (default is `False`).

2. Methods:

- `__init__(self, title, author, isbn)`: A constructor method that initializes the `title`, `author`, `isbn`, and sets `is_checked_out` to `False`.
- `check_out(self)`: Marks the book as checked out by setting `is_checked_out` to `True` and returns `True`. If the book is already checked out, returns `False`.
- `return_book(self)`: Marks the book as returned by setting `is_checked_out` to `False` and returns `True`. If the book is not checked out, returns `False`.
- `get_info(self)`: returns, as a string, the details of the book, including its title, author, ISBN, and availability status.

Your solution

```
# Write your solution here
```

Test your solution

```

# Test the Book class
book = Book("1984", "George Orwell", "123-4567890123")
assert book.title == "1984", "Test failed: Incorrect title"
assert book.author == "George Orwell", "Test failed: Incorrect author"
assert book.isbn == "123-4567890123", "Test failed: Incorrect ISBN"
assert book.is_checked_out == False, "Test failed: Book should be initially available"

# Test check out
result = book.check_out()
assert result == True, "Test failed: Book should be checked out successfully"
assert book.is_checked_out == True, "Test failed: Book should be marked as checked out"

# Test return
result = book.return_book()
assert result == True, "Test failed: Book should be returned successfully"
assert book.is_checked_out == False, "Test failed: Book should be marked as available"

```

Debug your solution

The following cells contain code to generate links to Python Tutor for debugging your code when running the tests. **You need to first run the cell containing your solution code before running the cell containing the Python Tutor link.**

```

from IPython.display import HTML;import urllib.parse as u;HTML('<a href="https://pyth

```

Exercise 3: Shapes

Exercise Description

Create a base class called `Shape` with two derived classes, `Rectangle` and `Circle`, each with specific attributes. Override the `__eq__` operator in the base class to allow comparison between instances based on their attributes.

Class 1: Shape (Base Class)

- **Attributes:**

- `name`: A string representing the name of the shape.

- **Methods:**

- `__init__(self, name)`: Initializes the `name` attribute.
- `__eq__(self, other)`: Returns `True` if the `name` and specific attributes of two shapes are identical, and `False` otherwise.
- `area(self)`: A placeholder method that should be overridden by subclasses to calculate the area. If called directly, it should generate an error using `raise NotImplementedError`.

Class 2: Rectangle (inherits from Shape)

- **Additional Attributes:**
 - width: The width of the rectangle (a float).
 - height: The height of the rectangle (a float).
- **Methods:**
 - `__init__(self, width, height)`: Initializes the width and height attributes and sets name to "Rectangle".
 - `area(self)`: Returns the area of the rectangle ($\text{width} * \text{height}$).
 - `__eq__(self, other)`: Checks if two rectangles are equal by comparing width and height values in addition to name.

Class 3: Circle (inherits from Shape)

- **Additional Attributes:**
 - radius: The radius of the circle (a float).
- **Methods:**
 - `__init__(self, radius)`: Initializes the radius attribute and sets name to "Circle".
 - `area(self)`: Returns the area of the circle ($\pi * \text{radius}^2$).
 - `__eq__(self, other)`: Checks if two circles are equal by comparing their radius values in addition to name.

Your solution

Write your solution here

Test your solution

```
# Test Rectangle initialization
rect = Rectangle(3, 4)
assert rect.width == 3.0, "Rectangle width initialization failed"
assert rect.height == 4.0, "Rectangle height initialization failed"
assert rect.name == "Rectangle", "Rectangle name initialization failed"

# Test Circle initialization
circle = Circle(5)
assert circle.radius == 5.0, "Circle radius initialization failed"
assert circle.name == "Circle", "Circle name initialization failed"

import math

# Test area calculation for Rectangle
rect = Rectangle(3, 4)
assert rect.area() == 12.0, "Rectangle area calculation failed"

# Test area calculation for Circle
circle = Circle(5)
expected_area = math.pi * (5 ** 2)
assert math.isclose(circle.area(), expected_area, rel_tol=1e-9), "Circle area calculation failed"

# Test basic equality between two shapes of the same type
rect1 = Rectangle(3, 4)
rect2 = Rectangle(3, 4)
rect3 = Rectangle(5, 6)

assert rect1 == rect2, "Rectangles with the same dimensions should be equal"
assert rect1 != rect3, "Rectangles with different dimensions should not be equal"
```

```
# Test equality for circles
circle1 = Circle(5)
circle2 = Circle(5)
circle3 = Circle(10)

assert circle1 == circle2, "Circles with the same radius should be equal"
assert circle1 != circle3, "Circles with different radii should not be equal"

# Test inequality between different shape types
assert rect1 != circle1, "Rectangle and Circle should not be equal"
```

Test your solution

```
# Test Rectangle initialization
rect = Rectangle(3, 4)
assert rect.width == 3.0, "Rectangle width initialization failed"
assert rect.height == 4.0, "Rectangle height initialization failed"
assert rect.name == "Rectangle", "Rectangle name initialization failed"

# Test Circle initialization
circle = Circle(5)
assert circle.radius == 5.0, "Circle radius initialization failed"
assert circle.name == "Circle", "Circle name initialization failed"

import math

# Test area calculation for Rectangle
rect = Rectangle(3, 4)
assert rect.area() == 12.0, "Rectangle area calculation failed"
```

```

# Test area calculation for Circle
circle = Circle(5)
expected_area = math.pi * (5 ** 2)
assert math.isclose(circle.area(), expected_area, rel_tol=1e-9), "Circle area calculation failed"

# Test basic equality between two shapes of the same type
rect1 = Rectangle(3, 4)
rect2 = Rectangle(3, 4)
rect3 = Rectangle(5, 6)

assert rect1 == rect2, "Rectangles with the same dimensions should be equal"
assert rect1 != rect3, "Rectangles with different dimensions should not be equal"

# Test equality for circles
circle1 = Circle(5)
circle2 = Circle(5)
circle3 = Circle(10)

assert circle1 == circle2, "Circles with the same radius should be equal"
assert circle1 != circle3, "Circles with different radii should not be equal"

# Test inequality between different shape types
assert rect1 != circle1, "Rectangle and Circle should not be equal"

```

Debug your solution

The following cells contain code to generate links to Python Tutor for debugging your code when running the tests. **You need to first run the cell containing your solution code before running the cell containing the Python Tutor link.**

```
from IPython.display import HTML;import urllib.parse as u;HTML('<a href="https://pyth
```

Exercise 4: Vectors

Exercise Description

Create two Python classes, `Vector2D` and `Vector3D`, to represent vectors in 2D and 3D space. The `Vector3D` class should inherit from `Vector2D`, adding functionality specific to 3D vectors. Override arithmetic operators to perform vector operations in both classes.

Class 1: Vector2D

- **Attributes:**
 - `x`: The x-coordinate of the vector (a float).
 - `y`: The y-coordinate of the vector (a float).
- **Methods:**
 - `__init__(self, x, y)`: Initializes the `x` and `y` attributes.
 - `__add__(self, other)`: Defines vector addition (+ operator).
 - `__sub__(self, other)`: Defines vector subtraction (- operator).
 - `__mul__(self, scalar)`: Defines scalar multiplication (* operator) where `scalar` is a float or an int.
 - `__str__(self)`: Returns a string representation of the vector such as "(x, y)".

Class 2: Vector3D (inherits from Vector2D)

- **Additional Attributes:**
 - `z`: The z-coordinate of the vector (a float).
- **Methods:**
 - `__init__(self, x, y, z)`: Initializes `x`, `y` (from `Vector2D`), and `z` attributes.
 - `__add__(self, other)`: Overrides addition to handle 3D vector addition.
 - `__sub__(self, other)`: Overrides subtraction to handle 3D vector subtraction.
 - `__mul__(self, scalar)`: Overrides multiplication to handle 3D vector multiplication.
 - `__str__(self)`: Returns a string representation of the 3D vector such as "`(x, y, z)`".

Your solution

```
# Write your solution here
```

Test your solution

```
# Test initialization
v2d = Vector2D(3, 4)
assert v2d.x == 3.0, "Vector2D initialization failed for x"
assert v2d.y == 4.0, "Vector2D initialization failed for y"

# Test addition
v2d_1 = Vector2D(1, 2)
v2d_2 = Vector2D(3, 4)
```

```
v2d_add = v2d_1 + v2d_2
assert v2d_add.x == 4.0 and v2d_add.y == 6.0, "Vector2D addition failed"

# Test subtraction
v2d_sub = v2d_2 - v2d_1
assert v2d_sub.x == 2.0 and v2d_sub.y == 2.0, "Vector2D subtraction failed"

# Test scalar multiplication
v2d_mul = v2d_1 * 2
assert v2d_mul.x == 2.0 and v2d_mul.y == 4.0, "Vector2D scalar multiplication failed"

# Test string representation
assert str(v2d) == "(3.0, 4.0)", "Vector2D string representation failed"

# Test initialization
v3d = Vector3D(1, 2, 3)
assert v3d.x == 1.0, "Vector3D initialization failed for x"
assert v3d.y == 2.0, "Vector3D initialization failed for y"
assert v3d.z == 3.0, "Vector3D initialization failed for z"

# Test addition
v3d_1 = Vector3D(1, 2, 3)
v3d_2 = Vector3D(4, 5, 6)
v3d_add = v3d_1 + v3d_2
assert (v3d_add.x, v3d_add.y, v3d_add.z) == (5.0, 7.0, 9.0), "Vector3D addition failed"

# Test subtraction
v3d_sub = v3d_2 - v3d_1
assert (v3d_sub.x, v3d_sub.y, v3d_sub.z) == (3.0, 3.0, 3.0), "Vector3D subtraction failed"

# Test scalar multiplication
```

```

v3d_mul = v3d_1 * 2
assert (v3d_mul.x, v3d_mul.y, v3d_mul.z) == (2.0, 4.0, 6.0), "Vector3D scalar multipl

# Test string representation
assert str(v3d) == "(1.0, 2.0, 3.0)", "Vector3D string representation failed"

```

Test your solution

```

# Test initialization
v2d = Vector2D(3, 4)
assert v2d.x == 3.0, "Vector2D initialization failed for x"
assert v2d.y == 4.0, "Vector2D initialization failed for y"

# Test addition
v2d_1 = Vector2D(1, 2)
v2d_2 = Vector2D(3, 4)
v2d_add = v2d_1 + v2d_2
assert v2d_add.x == 4.0 and v2d_add.y == 6.0, "Vector2D addition failed"

# Test subtraction
v2d_sub = v2d_2 - v2d_1
assert v2d_sub.x == 2.0 and v2d_sub.y == 2.0, "Vector2D subtraction failed"

# Test scalar multiplication
v2d_mul = v2d_1 * 2
assert v2d_mul.x == 2.0 and v2d_mul.y == 4.0, "Vector2D scalar multiplication failed"

# Test string representation
assert str(v2d) == "(3.0, 4.0)", "Vector2D string representation failed"

# Test initialization

```

```

v3d = Vector3D(1, 2, 3)
assert v3d.x == 1.0, "Vector3D initialization failed for x"
assert v3d.y == 2.0, "Vector3D initialization failed for y"
assert v3d.z == 3.0, "Vector3D initialization failed for z"

# Test addition
v3d_1 = Vector3D(1, 2, 3)
v3d_2 = Vector3D(4, 5, 6)
v3d_add = v3d_1 + v3d_2
assert (v3d_add.x, v3d_add.y, v3d_add.z) == (5.0, 7.0, 9.0), "Vector3D addition failed"

# Test subtraction
v3d_sub = v3d_2 - v3d_1
assert (v3d_sub.x, v3d_sub.y, v3d_sub.z) == (3.0, 3.0, 3.0), "Vector3D subtraction failed"

# Test scalar multiplication
v3d_mul = v3d_1 * 2
assert (v3d_mul.x, v3d_mul.y, v3d_mul.z) == (2.0, 4.0, 6.0), "Vector3D scalar multiplication failed"

# Test string representation
assert str(v3d) == "(1.0, 2.0, 3.0)", "Vector3D string representation failed"

```

Debug your solution

The following cells contain code to generate links to Python Tutor for debugging your code when running the tests. **You need to first run the cell containing your solution code before running the cell containing the Python Tutor link.**

```

from IPython.display import HTML;import urllib.parse as u;HTML('<a href="https://pyth

```

Exercise 5: Books and Library

Exercise Description

Create two Python classes, `Library` and `Book`, to represent a system where a library can manage a collection of books. The classes should have the following features:

Class 1: `Book`

1. **Attributes:**

- `title`: A string representing the title of the book.
- `author`: A string representing the author of the book.
- `isbn`: A string representing the unique ISBN number of the book.
- `is_checked_out`: A boolean attribute indicating if the book is currently checked out (default is `False`).

2. **Methods:**

- `__init__(self, title, author, isbn)`: Initializes the `title`, `author`, `isbn`, and sets `is_checked_out` to `False`.
- `check_out(self)`: Marks the book as checked out by setting `is_checked_out` to `True` and returns `True`. If the book is already checked out, returns `False`.
- `return_book(self)`: Marks the book as returned by setting `is_checked_out` to `False` and returns `True`. If the book is not checked out, returns `False`.
- `get_info(self)`: returns, as a string, the details of the book, including its title, author, ISBN, and availability status.
- `get_title(self)`: returns, as a string, the title of the book.

Class 2: Library

1. Attributes:

- `name`: A string representing the name of the library.
- `books`: A list that holds instances of `Book` objects.

2. Methods:

- `__init__(self, name)`: Initializes the library with a name and an empty list of books.
- `add_book(self, book)`: Adds a `Book` instance to the library's collection and returns `True`. If the book is already in the library, returns `False`.
- `list_books(self)`: returns a list of the titles of all books in the library.
- `list_available_books(self)`: returns a list of the titles of all available books in the library.
- `check_out_book(self, isbn)`: Checks out a book by its ISBN if it is available, returning `True`. If the book is not available or does not exist, returns `False`.
- `return_book(self, isbn)`: Returns a book by its ISBN if it is checked out, returning `True`. If the book is not checked out or does not exist, returns `False`.

Your solution

```
# Write your solution here
```

Test your solution

```
# Test the Library and Book classes
library = Library("City Library")
assert library.name == "City Library", "Test failed: Incorrect library name"
assert len(library.books) == 0, "Test failed: Library should start empty"

# Create and add books
book1 = Book("1984", "George Orwell", "123-4567890123")
book2 = Book("To Kill a Mockingbird", "Harper Lee", "456-7890123456")

assert library.add_book(book1) == True, "Test failed: Book should be added successfully"
assert library.add_book(book2) == True, "Test failed: Second book should be added successfully"

# Test listing books
books_list = library.list_books()
assert "1984" in books_list, "Test failed: Book should be in the list"
assert "To Kill a Mockingbird" in books_list, "Test failed: Second book should be in the list"

# Test checking out a book
result = library.check_out_book("123-4567890123")
assert result == True, "Test failed: Book should be checked out successfully"
```

Test your solution

```
# Test the Library and Book classes
library = Library("City Library")
assert library.name == "City Library", "Test failed: Incorrect library name"
assert len(library.books) == 0, "Test failed: Library should start empty"

# Create and add books
book1 = Book("1984", "George Orwell", "123-4567890123")
```

```

book2 = Book("To Kill a Mockingbird", "Harper Lee", "456-7890123456")

assert library.add_book(book1) == True, "Test failed: Book should be added successfully"
assert library.add_book(book2) == True, "Test failed: Second book should be added successfully"

# Test listing books
books_list = library.list_books()
assert "1984" in books_list, "Test failed: Book should be in the list"
assert "To Kill a Mockingbird" in books_list, "Test failed: Second book should be in the list"

# Test checking out a book
result = library.check_out_book("123-4567890123")
assert result == True, "Test failed: Book should be checked out successfully"

```

Debug your solution

The following cells contain code to generate links to Python Tutor for debugging your code when running the tests. **You need to first run the cell containing your solution code before running the cell containing the Python Tutor link.**

```

from IPython.display import HTML;import urllib.parse as u;HTML('<a href="https://pyth

```

Exercise 6: Books and Ebooks

Exercise Description

Create a Python class called EBook that inherits from a base class Book. The EBook class will represent a digital version of a book with additional features related to digital media.

Base Class: Book

1. **Attributes:**

- `title`: A string representing the title of the book.
- `author`: A string representing the author of the book.
- `isbn`: A string representing the unique ISBN number of the book.
- `is_checked_out`: A boolean attribute indicating if the book is currently checked out (default is `False`).

2. **Methods:**

- `__init__(self, title, author, isbn)`: Initializes the `title`, `author`, `isbn`, and sets `is_checked_out` to `False`.
- `check_out(self)`: Marks the book as checked out by setting `is_checked_out` to `True` and returns `True`. If the book is already checked out, returns `False`.
- `return_book(self)`: Marks the book as returned by setting `is_checked_out` to `False` and returns `True`. If the book is not checked out, returns `False`.
- `get_info(self)`: Returns a string with the details of the book, including its title, author, ISBN, and availability status.

