
Tree-width driven SDP for MAX CUT problem

A Preprint

Sergei Anikin
Chair of Data Analysis
MIPT
Moscow, Russia
anikin.sd@phystech.edu

Alexandr Bulkin
MSU
Faculty of Mechanics and Mathematics
Moscow, Russia
a.bulkin@icdda.io

Abstract

This paper addresses the well-known Max Cut problem, which has various applications both in machine learning and theoretical physics. The Max Cut problem is computationally intractable over general graphs. This paper presents a novel empirical approach aimed at enhancing the quality of Max-Cut approximations within polynomial time bounds. While the problem is tractable for graphs with small tree-width, its solution over general graphs often relies on Semi-Definite Programming or Lovász-Schrijver relaxations. We achieve the described improvement of approximation quality by combining relaxation approaches, the tree-width ideas and various heuristics described in the paper.

Keywords SDP · Treewidth · Max Cut · Lovász-Schrijver relaxations

1 Introduction

In this paper, we will discuss a non-asymptotic improvement¹ of the solution to the MAX CUT problem² - the problem of finding the maximum cut in undirected graphs³. It involves partitioning the vertices of a graph into two sets such that the number of edges between the two sets (the cut) is maximized. This problem has applications in many spheres, including machine learning, theoretical physics, and theoretical computer science. It serves as a basis for developing approximation algorithms and heuristic methods for solving other optimization problems. Currently, for graphs in general⁴, the best solutions proposed by X. Goemans and David P. Williamson find a cut that contains at least 0.878... of the edges in the optimal cut [link]⁵. There are families of graphs for which this bound is asymptotically optimal unless $P = NP$.⁶

In this article, we focus on a non-asymptotic improvement of the solution in polynomial time on arbitrary graphs. The known solution⁷ utilizes Semi-Definite Programming problems, and here, we present reasoning that allows solving them with greater accuracy by combining optimization ideas, tree-width approach, and heuristics.⁸

2 Problem statement

We focus on weighted undirected graphs, where each edge (i, j) is assigned a weight w_{ij} . As the graph is undirected, $w_{ij} = w_{ji}$. Such graphs are represented as $G = (V, E)$, where V denotes the set of vertices and E is the symmetric matrix with w_{ij} indicating the weight of edge (i, j) . Later we will refer to weighted undirected graphs simply as graphs.

Given a fixed graph $G = (V, E)$ with the sum of weights denoted by W , a cut in the graph is defined as a subset $S \subseteq V$. The complement of S is denoted by $T = V \setminus S$. Notably, a cut partitions the vertices into two sets: S and T . Additionally, the edges are divided into three categories: those entirely within S , those entirely within T , and those split by the cut, where one vertex lies in S and the other in T . Let's define $W(S)$ to be

the weight of the cut:

$$W(S) = \sum_{i \in S} \sum_{j \notin S} w_{ij}$$

Our goal is to find in polynomial time cut $S_{found} \subseteq V$, such that the value ratio is as big as possible

$$ratio = \frac{W(S_{found})}{\max_{S \subseteq V} W(S)} \rightarrow \max$$

We decide on the efficiency of provided algorithm by comparing it with well-known ones using the different datasets [10 - 13] 10

Список литературы

- [1] Goemans-Williamson MAXCUT Approximation Algorithm by Jin-Yi Cai, Christopher Hudzik, Sarah Knoop, 2003: <https://pages.cs.wisc.edu/~jyc/02-810notes/lecture20.pdf>
- [2] The Lovasz-Schrijver relaxation by Madhur Tulsiani, 2010: <https://home.ttic.edu/~madhurt/Papers/lv.pdf>
- [4] Treewidth: <https://www.cs.cmu.edu/~odonnell/toolkit13/lecture17.pdf>
- [5] MAX CUT approximation algorithm and UGC-hardness, Lecture by Irit Dinur and Amey Bhangale: <https://www.wisdom.weizmann.ac.il/~dinuri/courses/19-inapprox/lec6.pdf>
- [6] Semidefinite Programming versus Burer-Monteiro Factorization for Matrix Sensing by Baturalp Yalcin, Ziyi Ma, Javad Lavaei, Somayeh Sojoudi, 2022 <https://arxiv.org/abs/2208.07469v1>
- [7] 0.878-approximation for the Max-Cut problem, Lecture by Divya Padmanabhan, 2022: <https://www.iitgoa.ac.in/~sreejithav/misc/maxcut.pdf>
- [8] Rank optimality for the Burer-Monteiro factorization by Irène Waldspurger, Alden Waters, 2019 <https://arxiv.org/abs/1812.03046>
- [9] Semidefinite relaxation and nonconvex quadratic optimization by Yury Nesterov, 1997 <https://www.tandfonline.com/doi/abs/10.1080/10556789808805690>
- [10] Datasets: Texas Data Repository: <https://dataverse.tdl.org/dataset.xhtml?persistentId=doi:10.18738/T8/VLTIVC>
- [11] Datasets: Biq Mac Library: <https://biqmac.aau.at/biqmaclib.html>
- [12] Datasets: MaxCut and BQP Instance Library: <http://bqp.cs.uni-bonn.de/library/html/index.html>
- [13] Datasets: MaxCut Instances: <https://grafo.etsii.urjc.es/opticom/maxcut.htmlbest-known-values>
- [14] Ellipsoid algorithm: <https://www.cs.toronto.edu/~avner/teaching/S5-2411/ln/lecture8.pdf>
- [15] Michel X. Goemans and David P. Williamson. Improved approximation algorithms for maximum cut and satisfiability problems using semidefinite programming. Journal of the ACM, 42(6):1115–1145, 1995

1. Посмотрите по литературе, насколько часто такую вещь называют intractable. Возможно, стоит заменить на NP-hard, например.
2. Здесь должен быть длинный дефис, см. презентацию с ошибками прошлого года
3. Нужна ссылка на фундаментальную статью или учебник с упоминанием $\max \text{ cut}$
4. Так обычно не пишут. Если это число вам так важно, можно написать approximately 0.87. Либо убрать число и указать, что там была получена некоторая хорошая оценка
5. Вставьте нормальную ссылку
6. Нужно вставить ссылку, где указаны семейства этих множеств
7. Ссылка
8. Здесь нужно указать как вы собираетесь проверять качество методов, например, можно вставить последнее предложение из вашей постановки сюда
9. Тут два максимума, по второму нужно указать, по какому множеству и какой переменной идет максимизация
10. См. комментарий 8. И точка нужна.