

Neural Networks Loss Landscape Convergence in Hessian Low-Dimensional Space

Tem Nikitin Nikita Kiselev Andrey Grabovoy Vladislav
Meshkov


Moscow Institute of Physics and Technology

2025

Goals

- ▶ Study how neural network loss landscape changes with dataset size
- ▶ Define and measure $\Delta_k = \mathbb{E}(\mathcal{L}_{k+1}(\mathbf{w}) - \mathcal{L}_k(\mathbf{w}))^2$
- ▶ Develop Hessian-based low-dimensional projection method
- ▶ Derive theoretical bound for Δ_k via top- d eigenvalues
- ▶ Validate threshold k^* beyond which further data yield negligible change

One-slide



- ▶ Hessian projection onto top- d eigenvectors
- ▶ Monte Carlo estimate of $\Delta_k^{emp} = \mathbb{E}(\mathcal{L}_{k+1} - \mathcal{L}_k)^2$.
- ▶ Analytical bound: $\Delta_k^{th} \geq \Delta_k^{emp}$
- ▶ Detect dataset threshold k^*

Main message: Loss landscape stabilizes after sufficient sample size.

- ▶ Wu *et al.* (2017): loss landscapes vs dataset size [2]
- ▶ Sagun *et al.* (2018): Hessian low effective rank [7]
- ▶ Li *et al.* (2018): visualizing loss surfaces [11]
- ▶ Ghorbani *et al.* (2019): eigenvalue density analysis [8]
- ▶ Bousquet & Elisseeff (2002): stability and generalization bounds [12]

Problem Statement: Hypothesis and Model

Hypothesis

Beyond some k^* , adding new samples changes the local loss landscape by less than a tolerance Δ_{tol} , i.e. $\forall k \geq k^* : \Delta_k < \Delta_{tol}$.

Model

- ▶ MLP with ReLU activations for K -class classification
- ▶ Empirical loss: $\mathcal{L}_k(\mathbf{w}) = \frac{1}{k} \sum_{i=1}^k \ell_i(\mathbf{w})$
- ▶ Hessian: $\mathbf{H}_k(\mathbf{w}) = \nabla_{\mathbf{w}}^2 \mathcal{L}_k(\mathbf{w})$

Problem Statement: Quality Criteria

- ▶ Convergence rate: $\Delta_k = O(1/k)$
- ▶ Theoretical bound via top- d eigenvalues upper-bounds empirical Δ_k
- ▶ Plateau in eigenvalue differences $\lambda_i^{k+1} - \lambda_i^k$ indicates threshold

Problem Solution: Theoretical Analysis

- Project parameters:

$$\mathbf{w} = \mathbf{w}^* + \mathbf{P}\boldsymbol{\theta},$$

$$\mathbf{P} = [\mathbf{e}_1, \dots, \mathbf{e}_d]$$

- Taylor approx:

$$\mathcal{L}_k(\mathbf{w}^* + \mathbf{P}\boldsymbol{\theta}) \approx$$

$$\mathcal{L}_k(\mathbf{w}^*) + \frac{1}{2}\boldsymbol{\theta}^\top \boldsymbol{\Lambda}_k \boldsymbol{\theta}$$




Figure 1: Eigenvalue decay (p.4)

- Bound:

$$\Delta_k \approx \frac{\sigma^4}{4} \left(2 \sum_{i=1}^d (\lambda_{k+1}^i - \lambda_k^i)^2 + \left(\sum_{i=1}^d (\lambda_{k+1}^i - \lambda_k^i) \right)^2 \right).$$

Goals of Computational Experiment

- ▶ Datasets: MNIST, Fashion-MNIST (60k train, 10k test)
- ▶ MLP: 2 hidden layers, $\sim 10^5$ parameters
- ▶ Subspace dimension $d = 10$, Monte Carlo samples $K = 64$, $\sigma = 1$
- ▶ Compare empirical Δ_k vs theoretical bound across k




Figure 8: Monte Carlo Δ_k vs k and $\Delta_k \cdot k^2$ (p.11)

Error Analysis

- ▶ Empirical Δ_k consistently below theoretical estimate
- ▶ Gap due to neglected eigen-modes beyond top- d
- ▶ Monte Carlo variance decreases with sample size K




Figure 9: Theoretical (dashed) vs empirical (solid) Δ_k (p.12)

Results and Conclusions

- ▶ Identified threshold k (MNIST), (Fashion-MNIST)
- ▶ Loss landscape stabilizes: additional data negligible beyond k^*
- ▶ Hessian-based bound provides reliable upper-bound for Δ_k
- ▶ Practical guideline for dataset sizing and early stopping