

SignMuon, MuonSign, and the Role of Error Feedback

Anonymous submission

Abstract

SignMuon — sign compression of the Muon update to one bit per parameter — is the most straightforward adaptation of Muon to an extremely low communication budget. It outperforms SignSGD in practice, yet it can diverge on a linear function. The natural conjecture is that the order of operations is to blame, and that signing before rather than after the Linear Minimization Oracle (LMO) would fix it. It does not: MuonUSign diverges too, as does MuonSign, which signs both sides, so no naive placement of the sign around the LMO converges. Error feedback repairs one of them: EF21-MuonUSign attains the standard $\mathcal{O}(T^{-1/2})$ rate for smooth nonconvex optimization and decisively outperforms SignSGD, and compressing the downlink as well costs little beyond that. What the guarantee costs is the placement. Across centralized, federated and language-modelling experiments the best placement is consistently *sign-after-the-LMO*, precisely the one our counterexamples break and error feedback fails to repair. The provably convergent sign-before variants trail it by about two accuracy points in federation. We report this tension rather than resolve it: the counterexamples constrain worst-case instances, not CIFAR-10.

1 Introduction

Training a deep network across clients costs bandwidth as well as computation: every round, each client must ship a full update, and under a limited link those updates dominate the wall-clock cost. Compression is the standard remedy (Bernstein et al. 2018, 2019; Beznosikov et al. 2024), and SignSGD is its extreme point: one bit per coordinate, at little cost in final accuracy. But SignSGD flattens each weight matrix into a vector, discarding the two-dimensional structure that matrix-aware optimizers exploit. Muon exploits precisely that structure: it orthonormalizes the momentum matrix before stepping, which stabilizes training and, in several settings, beats tuned adaptive methods (Jordan et al. 2024; Bernstein and Newhouse 2024; Essential AI 2025). What it sends, however, is a *dense* matrix at full precision — the one thing a bandwidth-limited system cannot afford. Matrix geometry and a one-bit budget pull in opposite directions.

This is an anonymized submission for review purposes only. Distribution, citation, or public sharing of this manuscript is strictly prohibited. Copyright and publication details will appear in the final version if accepted.

We study the natural ways to combine sign compression with the Muon LMO at one bit per parameter: **SignMuon**, which signs *after* the LMO, $\text{sign}(\text{LMO}(\cdot))$; **MuonUSign**, which signs *before*, $\text{LMO}(\text{sign}(\cdot))$; and **MuonSign**, which signs on *both* sides and so compresses uplink and downlink alike. All three keep Muon’s matrix-aware geometry, but only sign-after reaches Muon’s accuracy: at $N = 11$ clients the three span five accuracy points, in the order after, before, both sides, the last of them falling below SignSGD.

None of them, however, has a global convergence guarantee. We prove that all three can diverge: SignMuon on a 4×4 instance (Theorem 1), MuonUSign and MuonSign on a single common 5×5 one (Theorems 2–3). In each case the 1-bit step becomes an ascent direction on a linear objective. To restore convergence at the same communication volume we introduce **EF21-MuonUSign**, adapted from EF21-Muon (Grunkowska et al. 2025): the scaled sign compresses only the residual between the momentum and a gradient estimator, and the descent step takes the full Muon LMO of the reconstructed estimator. **EF21-MuonSign** adds a second error-feedback loop on the downlink, compressing both channels to one bit. Both descend on the counterexamples above.

We evaluate the methods on centralized CIFAR-10 with a ResNet-18, federated CIFAR-10 with a CNN at $N = 11$ clients, the nanoGPT speedrun, and a synthetic smooth convex least-squares problem. Our contributions are: (i) SignMuon, MuonUSign and MuonSign, matrix-aware 1-bit optimizers placing the sign after, before and on both sides of the LMO; (ii) counterexamples proving all three may diverge (Theorems 1–3), at essentially minimal matrix sizes; (iii) a universal divergence theorem (Theorem 4): error feedback on the LMO *output* repairs SignMuon for no (L, η, μ) ; (iv) EF21-MuonUSign, restoring the guarantee at a one-bit uplink, and (v) EF21-MuonSign, adding a downlink loop to keep both channels at one bit; and (vi) a tuned five-seed federated comparison of all six at one budget, separating the three placements single-seed evidence had shown as coincident and locating the guarantee’s cost at the placement, not the downlink. Proofs, algorithms, and the numbered results cited but not stated below are in the supplementary material.

2 Related Work

SignSGD. Vanilla SignSGD, introduced by Bernstein et al. (2018) and later applied to federated learning by Bernstein et al. (2019), required increasing batch sizes to guarantee convergence. This issue, together with SignSGD’s inherent bias, was addressed through the adoption of the Error Feedback technique (Karimireddy et al. 2019). An alternative approach is to randomize the sign operator itself (Chen et al. 2020; Safaryan and Richtarik 2021; Jin et al. 2025).

Compression for Muon. Gruntkowska et al. (2025) developed a theoretical framework for federated learning with error feedback in which Muon/Gluon (Riabini et al. 2025) updates are compressed bidirectionally (client-to-server and server-to-client). Qian et al. (2026) employed variance reduction to lower the compression error for Gluon under unbiased and contractive compressors. Concurrently with our work, Mishra, Trivedi, and Kumar (2026) proposed vanilla SignMuon and stated an $\mathcal{O}(1/\sqrt{T})$ guarantee for it; in Appendix A.6 we show that their finalized rate covers only the gradient-sign instantiation, leaving the bound for the actual polar-sign method uninformative on exactly the instances of Theorem 1. Two further methods share our names but not our object: Bolatov et al. (2026) *alternate* spectral and sign steps instead of composing them, and Kravatskiy et al. (2025) mix the two geometries *inside* the oracle, so S-Muon remains an LMO for an explicit norm and keeps the attendant theory. Our three placements put the sign *around* the oracle, where it is a compressor and not a geometry, so the counterexamples below do not bear on either (Appendix A.7).

3 Problem Statement

We consider the stochastic optimization problem

$$\min_{\mathbf{X} \in \mathcal{X}} \{f(\mathbf{X}) := \mathbb{E}_{\xi \sim \mathcal{D}}[f_\xi(\mathbf{X})]\}, \quad (1)$$

where $\mathcal{X}$ is the parameter space (e.g., $\mathbb{R}^d$ or $\mathbb{R}^{m \times n}$) and the $f_\xi : \mathcal{X} \rightarrow \mathbb{R}$ are continuously differentiable and possibly non-convex: $f_\xi(\mathbf{X})$ is the loss of a model $\mathbf{X}$ at a data point $\xi \sim \mathcal{D}$. In the federated setting the data are split across clients, and the training problem becomes

$$\min_{\mathbf{X} \in \mathcal{X}} \left\{ f(\mathbf{X}) := \frac{1}{N} \sum_{j=1}^N f_j(\mathbf{X}) \right\}, \quad f_j(\mathbf{X}) = \mathbb{E}_{\xi_j \sim \mathcal{D}_j} [f_j(\mathbf{X}; \xi_j)] \quad (2)$$

where $N \geq 1$ is the number of clients and f_j is the loss on the data $\mathcal{D}_j$ held by client $j \in [N] := \{1, \dots, N\}$.

Two assumptions run through the paper. The model is a tuple of matrix layers $\mathbf{X} = [\mathbf{X}_1, \dots, \mathbf{X}_p]$, $\mathbf{X}_i \in \mathbb{R}^{m_i \times n_i}$, with ∇_i the gradient block of layer i . Each layer carries the spectral norm $\|\cdot\|_{2 \rightarrow 2}$, whose dual is the nuclear norm $\|\cdot\|_*$, and we write $\|\nabla f(\mathbf{X})\|_*^2 := \sum_i \|\nabla_i f(\mathbf{X})\|_*^2$; a single matrix parameter is the case $p = 1$.

Assumption 1 (Lower boundedness) $f(\mathbf{X}) \geq f^*$ for all $\mathbf{X}$; where explicitly invoked, each local $f_j \geq f_j^*$ as well.

Assumption 2 (Layer-wise smoothness) For every layer i and all $\mathbf{X}, \mathbf{Y}$,

$$\|\nabla_i g(\mathbf{X}) - \nabla_i g(\mathbf{Y})\|_* \leq L_i^g \|\mathbf{X}_i - \mathbf{Y}_i\|_{2 \rightarrow 2} \quad (3)$$

for $g = f$ (constant L_i) and $g = f_j$ (constant $L_{i,j}$). A weaker layer-wise (L^0, L^1) form, stated in Appendix A.1, is used only in Corollary 2.

A Linear Minimization Oracle (LMO) minimizes a linear form over the unit ball of a norm, returning the steepest-descent direction in that norm (Appendix A.1). Muon takes that norm to be spectral on each matrix layer, which turns the oracle into an orthogonalization: writing $\mathbf{M} = \mathbf{U}\Sigma\mathbf{V}^\top$ for the rank- r singular value decomposition of $\mathbf{M} \in \mathbb{R}^{m \times n}$, the LMO direction is

$$A(\mathbf{M}) = -\mathbf{U}\mathbf{V}^\top \in \mathbb{R}^{m \times n}, \quad \text{polar}(\mathbf{M}) := -A(\mathbf{M}). \quad (4)$$

In practice the oracle is applied to a momentum estimate rather than to $\mathbf{G}_t$ itself; (6) below gives the full iteration.

Muon requires transmitting the full update matrix $\mathbf{D}_t$, which is expensive in federated settings. Our objective is to combine its matrix-aware geometry with extreme (1-bit) communication compression. SignMuon, MuonUSign, and MuonSign achieve it empirically, but lack global convergence guarantees (Theorems 1–3). The Error-Feedback variants restore convergence: in Appendix A.9 we show that EF21-MuonUSign and EF21-MuonSign are *exact instances* of the EF21-Muon framework of Gruntkowska et al. (2025), and so inherit the standard $\mathcal{O}(T^{-1/2})$ rate for smooth non-convex optimization (Theorem 5):

$$\min_{0 \leq t \leq T} \mathbb{E}[\|\nabla f(\mathbf{X}_t)\|_*^2] = \mathcal{O}(T^{-1/2}), \quad (5)$$

as well as an $\mathcal{O}(T^{-1/4})$ rate for $\min_t \sum_i \mathbb{E}\|\nabla_i f(\mathbf{X}_t)\|_*$ under (L^0, L^1) -smoothness with a plain constant learning rate (Corollary 2). Both displays assume one step-size constant common to all layers; Corollaries 1–2 give the general weighted form. Finally, EF21-MuonSign adds a second error-feedback loop on the downlink, making communication 1-bit in *both* directions. The $\mathcal{O}(T^{-1/2})$ rate survives, but not without cost: a sign-based downlink is contractive only in the Euclidean norm, whereas Muon’s spectral geometry asks for contractivity in the layer norm, so the admissible step size shrinks by a further $\sqrt{r}$ in the layer rank. The gap is not an artefact of the analysis: the scaled sign is spectrally contractive for *no* parameter at all, so only a different compressor helps (Remark 4). We measure what it costs on a transformer (Section 5.3).

4 Theory

Consider the **SignA** family, where **A** is any optimizer built on LMO directions. A SignA method initializes $\mathbf{M}_0 = \mathbf{0}$ and at each iteration $t \geq 1$ performs:

$$\begin{aligned} \mathbf{M}_t &= \mu \mathbf{M}_{t-1} + \mathbf{G}_t && \text{(Momentum accumulation)} \\ \tilde{\mathbf{M}}_t &= \begin{cases} \mathbf{G}_t + \mu \mathbf{M}_t & \text{(Nesterov momentum),} \\ \mathbf{M}_t & \text{(otherwise)} \end{cases} && \text{(Effective direction),} \\ \mathbf{D}_t &= -A(\tilde{\mathbf{M}}_t), && \text{(LMO direction)} \\ \mathbf{s}_t &= \text{sign}(\mathbf{D}_t) \in \{\pm 1\}^{m \times n}, && \text{(Sign compression)} \\ \mathbf{X}_{t+1} &= \mathbf{X}_t - \eta_t \mathbf{s}_t && \text{(Parameter update),} \end{aligned} \quad (6)$$

where $\mathbf{X}_t \in \mathbb{R}^{m \times n}$ is the parameter matrix, $\mathbf{G}_t$ its stochastic gradient, $\mu \in [0, 1)$ the momentum coefficient and η_t the learning rate; $A(\cdot)$ is the LMO, and $\text{sign}(\cdot)$ acts element-wise on the structured direction $\mathbf{D}_t$, with $\text{sign}(0)$ resolved to an independent random ± 1 so that the transmitted alphabet stays binary.

Our three methods are the three placements of the sign around this oracle. They share the update $\mathbf{X}_{t+1} = \mathbf{X}_t - \eta_t \mathbf{s}_t$ and differ only in where the sign acts on $\tilde{\mathbf{M}}_t$:

$$\mathbf{s}_t = \begin{cases} \text{sign}(\text{polar}(\tilde{\mathbf{M}}_t)) & (\text{SignMuon: after}), \\ \text{polar}(\text{sign}(\tilde{\mathbf{M}}_t)) & (\text{MuonUSign: before}), \\ \text{sign}(\text{polar}(\text{sign}(\tilde{\mathbf{M}}_t))) & (\text{MuonSign: both}). \end{cases} \quad (7)$$

SignMuon (Algorithm 2) thus combines Muon’s orthogonalized direction with the sign compression of SignSGD, MuonUSign (Algorithm 4) signs before the oracle instead, and MuonSign (Algorithm 5) signs both sides. All three transmit one bit per parameter on the uplink. On the downlink SignMuon and MuonSign distribute a ± 1 -valued object and so cost one bit in each direction, while MuonUSign’s server-side $\text{polar}(\cdot)$ is dense and costs full precision.

4.1 Centralized Learning

In the centralized setting, SignMuon is applied to the matrix-valued parameters (weights of convolutional and fully connected layers, $n_{\text{dim}} \geq 2$), while vector parameters (biases, BatchNorm, $n_{\text{dim}} = 1$) and the final classification layer are optimized with AdamW, the design introduced by Jordan et al. (2024) and formalized in (Li and Hong 2025; Riabinin et al. 2025).

We approximate $\text{polar}(\cdot)$ by a 5th-order Newton–Schulz iteration rather than a full SVD at every step (Algorithm 1). One further implementation choice is not without consequence, and we state it here because every experiment depends on it.

Per-layer step sizes: the unit-gain heuristic. The methods of this paper produce step matrices from two families with *exactly* known Frobenius norms: $\|\mathbf{U}\mathbf{V}^\top\|_F = \sqrt{r}$ for the LMO-terminated methods ($r = \min(m, n)$), and $\|\mathbf{s}\|_F = \sqrt{mn}$ for the SIGN-terminated ones. These scale differently with layer shape, so no single global η is right for both families, or across layers within one. We fix the shape dependence a priori and tune only a shape-free base rate η_0 , setting $\eta_\ell = \eta_0 \lambda_\ell$ with

$$\lambda_\ell = \frac{\sqrt{m}}{\|\mathbf{s}_\ell\|_F} \implies \begin{cases} \lambda_\ell^{\text{LMO}} = \sqrt{\max(1, m/n)}, \\ \lambda_\ell^{\text{SIGN}} = 1/\sqrt{\text{fan-in}}. \end{cases} \quad (8)$$

The criterion is that every layer’s update have the same root-mean-square input–output gain, the average-case form of the spectral scaling condition (Yang, Simon, and Bernstein 2023; Large et al. 2024); η_0 is then literally the per-step RMS gain. We treat (8) as a heuristic and use it uniformly, for one reason above all: its LMO branch *reproduces* the aspect-ratio factor $\sqrt{\max(1, m/n)}$ that the reference Muon implementation already ships as a practical fix (Jordan et al. 2024), so a criterion already accepted in practice for one family

supplies the missing counterpart, $1/\sqrt{\text{fan-in}}$, for the other. Appendix A.17 gives the derivation, the measurement that selects the exponent $\frac{1}{2}$ over $\mu\mathbf{P}$ ’s 1, the caveats, and the sensitivity of our conclusions to the choice.

4.2 Theoretical limitations

A natural hope is that the Muon LMO direction — the steepest-descent direction in the spectral norm — survives sign compression, whether the sign is applied before or after the oracle. It does not: in each of the three placements the compressed step can become an *ascent* direction on a smooth objective.

We read $\text{polar}(\cdot)$ off the rank-truncated SVD. At a rank-deficient argument the spectral-ball LMO is not unique, and this selection, the one our implementation makes, is part of what the counterexamples assert.

We refute the descent property on *linear* objectives (the simplest smooth functions, on which any sound method must make unbounded progress):

$$f(\mathbf{W}) = \langle \mathbf{G}, \mathbf{W} \rangle = \text{Tr}(\mathbf{G}^\top \mathbf{W}), \quad \nabla f(\mathbf{W}) \equiv \mathbf{G}. \quad (9)$$

Gradient descent and full-precision Muon drive $f \rightarrow -\infty$ here, so a rule that instead drives $f \rightarrow +\infty$ is unambiguously ascending (Remark 1 restores Assumption 1 without moving any trajectory below).

On (9) the step is the constant matrix $\mathbf{s}(\mathbf{G})$ whatever the momentum, so momentum affects neither convergence nor divergence (Proposition 1, Appendix A.2) and

$$f(\mathbf{X}_{t+1}) - f(\mathbf{X}_t) = -\eta_t \langle \mathbf{G}, \mathbf{s}(\mathbf{G}) \rangle \quad (10)$$

for every $\mu \in [0, 1)$ and either momentum rule. One gradient with $\langle \mathbf{G}, \mathbf{s}(\mathbf{G}) \rangle < 0$ thus makes f increase at *every* step, at *any* step size, with $f(\mathbf{X}_t) \rightarrow +\infty$ whenever $\sum_t \eta_t = \infty$.

Such a gradient exists for each placement: a 4×4 matrix defeats SignMuon, and a single 5×5 matrix defeats MuonUSign and MuonSign together. Informally, then:

For each of the three placements there is a linear objective on which the method ascends at every iteration, for every step size, every $\mu \in [0, 1)$ and either momentum variant.

These are Theorems 1–3, stated with their instances and proved in Appendices A.3–A.5, which also show the sizes to be minimal. The left and centre panels of Figure 1 show the ascents. No placement of the sign around the Muon LMO, then, yields a convergent method.

4.3 Centralized Error Feedback: EF21-SignMuon

Theorems 1–3 rule out every static placement of the sign around the LMO. The classical remedy for a biased one-bit compressor is *error feedback*: store the compression error and reinject it at the next step. This repairs SignSGD (Karimireddy et al. 2019) and was later sharpened into EF21 (Richtárik, Sokolov, and Fatkhullin 2021). Its most direct use for SignMuon keeps the geometry (the sign *after* the LMO) and error-feedbacks the oracle’s output. The resulting method, **EF21-SignMuon** (Algorithm 3), tracks an




Figure 1: All eight methods on the three counterexample instances; in each panel the ascending method is drawn heavy and named. *Left*: SignMuon on the 4×4 instance of Theorem 1. *Centre*: MuonUSign and MuonSign on the shared 5×5 instance of Theorems 2–3; both panels plot the linear objective (9). *Right*: EF21-SignMuon on the 2×2 instance of Theorem 4, in normalized units with $\eta = 1$. Trajectories are momentum-free: for the three placements Proposition 1 shows this is without loss, and for EF21-SignMuon Lemma 3 supplies a separate instance per $(\mu, \text{variant})$ generating the same target sequence; the remaining baselines are shown at $\mu = 0$ only.

estimate $\mathbf{d}_t^{\text{est}}$ of the LMO direction $\mathbf{D}_t = \text{polar}(\tilde{\mathbf{M}}_t)$, refreshed by a scaled sign of the residual,

$$\begin{aligned} \mathbf{d}_t^{\text{est}} &= \mathbf{d}_{t-1}^{\text{est}} + \alpha_t \text{sign}(\mathbf{D}_t - \mathbf{d}_{t-1}^{\text{est}}), \\ \alpha_t &= \text{mean}|\mathbf{D}_t - \mathbf{d}_{t-1}^{\text{est}}|, \end{aligned} \quad (11)$$

and steps $\mathbf{X}_t = \mathbf{X}_{t-1} - \eta_t \mathbf{d}_t^{\text{est}}$.

Error feedback on the compressed *output*, however, does not restore the descent property, and fails for *every* step size and momentum setting.

Theorem 4 (Divergence of EF21-SignMuon) *For every $L > 0$, step size $\eta > 0$, momentum coefficient $\mu \in [0, 1)$, and either momentum variant, there is an L -smooth (Assumption 2), bounded-below (Assumption 1) function $f : \mathbb{R}^{2 \times 2} \rightarrow \mathbb{R}$ on which EF21-SignMuon started at $\mathbf{X}_0 = \mathbf{0}$ diverges: for an explicit constant $c = c(f) > 0$,*

$$f(\mathbf{X}_{t+2}) - f(\mathbf{X}_t) = cL\eta^2 > 0 \quad (t \geq 3), \quad (12)$$

so $f(\mathbf{X}_t) \rightarrow +\infty$. In particular, no step-size rule $\eta = \eta(L, \mu)$ using only the smoothness and momentum constants can make the method convergent.

The obstruction (proof in Appendix A.8) is specific to signing the LMO output: a *single* magnitude α_t rescales all entries' signs at once, so a large, sign-flipping off-diagonal forces $\alpha_t = \Theta(1)$ and overwhelms the small diagonal target, whose estimate then locks onto the *wrong* sign and drives one coordinate of $\mathbf{X}_t$ to infinity. Momentum does not help: Figure 4 (Appendix A.8) records the same rate for every μ and both variants. The remedy is to error-feedback the gradient *before* the LMO, the subject of the next subsection.

4.4 Centralized Error Feedback:

EF21-MuonUSign and EF21-MuonSign

The defect is not the shared magnitude α_t as such, since the methods below couple all coordinates through the same

scalar; it is *what the estimator is asked to track*. Error feedback needs a target that settles, whereas the LMO output $\text{polar}(\tilde{\mathbf{M}}_t)$ is non-Lipschitz in the momentum and can jump by $\Theta(1)$ between rounds however small η is. Compressing the *gradient* instead leaves the estimator tracking a target that moves with the step size, which restores convergence at the same one-bit uplink cost; we adapt the EF21-Muon mechanism (Grutkowska et al. 2025) to sign compression.

The **USign** compressor is the directional pair $(\mathcal{C}_\uparrow, \mathcal{C}_\downarrow)$ with $\mathcal{C}_\uparrow(\mathbf{Y}) = \text{mean}|\mathbf{Y}| \text{sign}(\mathbf{Y})$ the scaled sign on the uplink and $\mathcal{C}_\downarrow = I$ the identity on the downlink: one bit per parameter from client to server, a full-precision model back. **EF21-MuonUSign** pairs it with EF21 and the Muon LMO.

EF21-MuonUSign maintains a gradient estimator $\mathbf{g}_t^{\text{est}}$ updated via a contractive sign compressor on the residual $\Delta_t = \mathbf{M}_t - \mathbf{g}_t^{\text{est}}$:

$$\alpha_t = \text{mean}(|\Delta_t|), \quad \mathbf{g}_{t+1}^{\text{est}} = \mathbf{g}_t^{\text{est}} + \alpha_t \text{sign}(\Delta_t), \quad (13)$$

and takes the descent step

$$\begin{aligned} \mathbf{X}_{t+1} &= \mathbf{X}_t - \eta_t \mathbf{D}_t, \\ \mathbf{D}_t &= -A(\mathbf{g}_{t+1}^{\text{est}}) \approx \mathbf{U}_{t+1} \mathbf{V}_{t+1}^\top. \end{aligned} \quad (14)$$

Here $\mathbf{U}_{t+1} \mathbf{V}_{t+1}^\top$ is the polar factor of the estimator, not of ∇f , so no step-wise descent property is claimed; what it provides is an estimator tracking a target that moves at the step size, the hypothesis the transferred guarantee needs (Corollary 1). The sign in (13) acts only on the internal compression residual, so the uplink stays at one bit per parameter (Algorithm 6, Appendix A.18). Figure 1 confirms that EF21-MuonUSign descends on the counterexample on which SignMuon ascends.

EF21-MuonSign makes both channels one-bit by applying the same scaled-sign operator to the downlink. The mechanism is a second error-feedback loop, on the *model* rather

than the gradient, and it splits the method into two iterates:

$$\begin{aligned}\mathbf{X}_{t+1} &= \mathbf{X}_t - \eta_t \mathbf{D}_t && \text{(server model),} \\ \mathbf{W}_{t+1} &= \mathbf{W}_t + \alpha_t^\downarrow \text{sign}(\mathbf{X}_{t+1} - \mathbf{W}_t) && \text{(broadcast model),}\end{aligned}\tag{15}$$

with $\mathbf{D}_t = -A(\mathbf{g}_{t+1}^{\text{est}})$ as before. The server model $\mathbf{X}$ takes the exact LMO step and never leaves the server; what crosses the downlink is the one-bit refresh of the broadcast model $\mathbf{W}$, and $\mathbf{W}$ is the only model the rest of the method ever sees. Gradients, momentum and the uplink residual are all computed there. Training takes place at $\mathbf{W}$; the transferred guarantee (Corollary 1) bounds the gradient at $\mathbf{X}$. Under an exact downlink the two coincide and the method reduces to EF21-MuonUSign; how far they drift apart under the one-bit downlink is measured in Section 5.3. The full procedure is Algorithm 7; centrally the “channels” are internal to the update rule, which simply maintains both matrices.

Both error-feedback methods incur a memory cost for the guarantee: one buffer per compressed channel (the gradient estimate $\mathbf{g}^{\text{est}}$; for EF21-MuonSign also the broadcast model $\mathbf{W}$). The overhead is small on the server but may be unwanted on memory-limited workers.

4.5 Federated Learning

In the federated setting (2) each client computes a stochastic gradient at the broadcast model, maintains a local momentum buffer, applies the Muon LMO (Newton–Schulz, Algorithm 1), and uploads the elementwise sign of the result; the server takes a majority vote, $\mathbf{s}_t^{\text{agg}} = \text{sign}(\sum_{j=1}^N \mathbf{s}_t^{(j)})$, and the step is $\mathbf{X}_{t+1} = \mathbf{X}_t - \eta_t \mathbf{s}_t^{\text{agg}}$. The uplink costs one bit per parameter, and so does the *downlink*: $\mathbf{s}_t^{\text{agg}}$ is ± 1 -valued in every coordinate — exactly, at an odd client count, under the convention of Section 4 — so the server broadcasts the vote rather than the model and each client applies it to its own replica. Replicas start from a common $\mathbf{X}_0$ and receive identical updates, so they never drift. This is a property of the vote, not of the compressor (Bernstein et al. 2019). In the error-feedback variants the LMO moves from the clients to the server: each client sign-compresses the residual between its local momentum and its gradient estimator and sends the pair $(\mathbf{s}_t^{(j)}, \alpha_t^{(j)})$; the server aggregates these, updates a global gradient estimator, and applies the Muon LMO. The extra per-layer scalar keeps the uplink at ≈ 1 bit per parameter, but the server-side quantity is now dense: a scaled average of signs, then the real-valued polar($\cdot$) of it. The vote argument therefore does not apply and the full model must be broadcast, unless a second error-feedback loop compresses it, which is what EF21-MuonSign adds. The complete procedures — the EMA momentum and the AdamW treatment of the classifier head — are Algorithms 8–9 (Appendix A.18).

5 Experiments

Appendix A.11 reports a controlled study on a deterministic smooth convex quadratic, measuring the gradient/step alignment that Theorems 1–3 drive negative and separating the accuracy floor of a sign step from its rate.

Method	η_0	Test acc (%)	Ep. to 90%
EF21-SignMuon	0.01	94.64 $\pm$ 0.24	8.7
SignMuon	0.02	94.53 $\pm$ 0.22	8.3
Muon	0.05	94.49 $\pm$ 0.09	7.7
EF21-MuonSign	0.01	94.22 $\pm$ 0.13	10.3
EF21-MuonUSign	0.2	94.15 $\pm$ 0.16	8.7
MuonUSign	0.02	93.90 $\pm$ 0.08	10.0
MuonSign	0.005	93.65 $\pm$ 0.21	15.0
Adam	0.0005	93.35 $\pm$ 0.15	18.8
SignSGD	0.002	93.27 $\pm$ 0.16	19.0
SGD	0.02	93.13 $\pm$ 0.07	21.7

Table 1: Centralized ResNet-18 / CIFAR-10, 75 epochs. Test accuracy is the mean $\pm$ standard deviation over three seeds of the last five epochs; “Ep. to 90%” is the mean epoch at which test accuracy first reaches 90%. Rules separate the statistically tied methods from the rest.

5.1 Centralized Learning

We compare all six matrix-aware 1-bit methods against Muon, SignSGD, SGD and Adam at a fixed epoch budget, on CIFAR-10 (Krizhevsky, Hinton et al. 2009). The base model is a ResNet-18 adapted to low-resolution images: an initial 3×3 convolution without max-pooling, 4 residual blocks with BatchNorm, dropout, and a linear classifier. Training runs for $T_{\text{max}} = 75$ epochs with η_0 annealed to zero by a cosine schedule.

Protocol. The only tuned hyperparameter is η_0 , selected per method on a held-out 5k validation split. Every method with a norm-fixed step is tuned and reported under one per-layer rule, the unit-gain rule (8), so that η_0 means the same thing across them, namely the per-step RMS gain (Appendix A.17); SGD and Adam have no such step and keep one global rate. Centralized numbers are means over three seeds and federated numbers over five, and differences smaller than the seed spread are not claimed as results. Alongside final accuracy we report epochs to a fixed test accuracy, which separates the methods by factors rather than by tenths of a point. The grid, the endpoint rule and the schedules are in Appendix A.10.

EF21-SignMuon, SignMuon and Muon span 0.15 points against seed spreads of 0.09–0.24; at three seeds they are indistinguishable, so we claim only that sign-after *matches* Muon, at one bit per parameter on the uplink and 1.26 points above SignSGD, which spends the same budget without the LMO. Error feedback incurs no measurable cost here: EF21-SignMuon lies within a seed spread of uncompressed SignMuon.

Within the family the ordering exceeds the noise: sign-after (94.53), sign-before (93.90) and bidirectional (93.65) separate by 0.9 points, and the training loss orders them identically (Figure 10), so the gap is in optimization rather than regularization. SignMuon crosses 90% in 8.3 epochs against SGD’s 21.7, SignSGD’s 19.0 and Adam’s 18.8; orthogonalization costs about 18% more per epoch (14.4 vs. 12.2 s, one device throughout), so $2.6\times$ fewer epochs is still $2.2\times$ in wall clock.




Figure 2: Centralized ResNet-18 on CIFAR-10: test accuracy from epoch 25, at each method’s selected η_0 (Table 1). Panels group the three sign placements (left), the EF21 variants (centre) and the uncompressed baselines (right); Muon is the gray dashed reference in all three, and bands are ± 1 standard deviation over three seeds.

Optimizer	η_0	Up	Down	Rds. to 80%	Test acc (%)
Muon	0.1	32	32	260	85.99 ± 0.26
SignMuon	0.05	1.09	1.09	300	85.81 ± 0.25
EF21-SignMuon	0.05	1.09	32	600	85.16 ± 0.15
MuonUSign	0.05	1.09	32	540	84.62 ± 0.17
EF21-MuonSign	0.05	1.09	1.09	980	83.99 ± 0.28
EF21-MuonUSign	0.05	1.09	32	1000	83.75 ± 0.21
SignSGD	0.02	1.09	1.09	1080	81.83 ± 0.43
MuonSign	0.05	1.09	1.09	1300 [†]	80.68 ± 1.88
SGD	0.1	32	32	1367 [†]	79.79 ± 1.55
Adam	0.001	32	32	—	77.12 ± 1.04

Table 2: CIFAR-10 federated learning on CNN2, ordered by accuracy: $N = 11$ clients, homogeneous split, 2000 rounds at batch 192 per client, momentum 0.9. Test accuracy is the mean of the final five evaluations over five seeds, $\pm$ one standard deviation *across* seeds. **Up** and **Down** are mean bits per model parameter per round in each direction (Appendix A.14). [†] mean over the seeds reaching 80% within the budget (4/5 for MuonSign, 3/5 for SGD); Adam reached it on none.

5.2 Federated Learning

In federated learning the bottleneck is transmitting full 32-bit gradient matrices. We compare all six matrix-aware 1-bit methods against the Muon, SignSGD, SGD and Adam baselines on CNN2 (two convolutional blocks with Batch-Norm and an MLP classifier), with CIFAR-10 partitioned homogeneously across clients. Local models are discarded at the end of each round, so BatchNorm runs at its initialization statistics throughout, in training and evaluation alike (Appendix A.10). Two schemes are covered: the worker-side-LMO scheme (Algorithm 8), of which federated SignMuon is the instance, and the server-side-LMO scheme (Algorithm 9),

which covers the error-feedback variants; Table 16 lists which compressor pair fixes each method.

Setting. Sign-based methods separate most clearly as network scale and local computation grow, so we run at $N = 11$ clients at batch 192 each, the scale at which they separate. Clients take no local parameter steps. The count is odd by design: client messages are ± 1 valued under the convention of Section 4, so an odd N makes the majority vote decisive in every coordinate and removes the tie-breaking rule from the comparison entirely. Every rate is tuned per method on a validation split held out before the client partition, so that no placement is handicapped by its step size and no test image is scored during selection (Appendix A.10); every number is a five-seed mean (Table 2, Figure 12).

SignMuon reaches the quality of Muon at 1.09 bits per parameter in *both* directions, a gap of 0.18 points against a seed spread of 0.25. At that fixed one-bit round trip, replacing the gradient sign with the sign of the LMO direction is worth 3.98 points over SignSGD, against 1.26 centrally. The seeds also separate the three placements, which single-seed evidence had shown as coincident: sign-after leads, sign-before trails it by 1.19 points, and signing both sides costs a further 3.94. Sign-after stays ahead under error feedback, though below it the other two swap.

This is the paper’s uncomfortable finding: the placement that works best in practice is the one the theory condemns. Sign-after is what Theorem 1 makes diverge, and error feedback does not repair it for any (L, η, μ) (Theorem 4); yet the sign-after methods are the strongest compressed ones here, in the centralized table, and on nanoGPT (Section 5.3). Conversely the two variants carrying an unconditional $\mathcal{O}(T^{-1/2})$ guarantee lie about 2 points below SignMuon, seven to eight seed spreads. The guarantee therefore costs accuracy at this scale, and the counterexamples constrain worst-case instances rather than predicting CIFAR-10.

EF21-MuonSign is 0.24 points *ahead* of the uplink-only




Figure 3: NanoGPT speedrun, $8\times H100$: validation loss against optimizer step, single seed; dotted line is the speedrun target 3.28. EF21-MuonSign is drawn at its broadcast model $\mathbf{W}$. The inset magnifies the boxed tail, where SignSGD is above the range shown; exact values are in Table 3.

Method	Step	η_0	Val. loss	Steps to 3.35
Muon (record #40)	LMO	0.06	3.2785	1.00×
EF21-SignMuon	LMO	0.06	3.2860	1.02×
SignMuon	SIGN	0.03	3.2881	1.02×
MuonUSign	LMO	0.06	3.2959	1.05×
EF21-MuonUSign	LMO	0.06	3.3203	1.13×
EF21-MuonSign ($\mathbf{W}$)	LMO	0.06	3.3213	1.14×
MuonSign	SIGN	0.03	3.3249	1.14×
SignSGD	SIGN	0.03	3.4049	—
EF21-MuonSign ($\mathbf{X}$)	LMO	0.06	5.5198	—

Table 3: NanoGPT after 2330 steps (611M tokens), single seed. Record #40 reports 3.2780 ± 0.0009 over five seeds, so differences below ~ 0.003 are noise. “Steps to 3.35” is the step count to reach that loss, relative to Muon. The last row is EF21-MuonSign’s server model $\mathbf{X}$, the same run as the broadcast model $\mathbf{W}$ above.

EF21-MuonUSign, within a seed spread, so at CNN2’s scale the one-bit downlink loop incurs no measurable cost: what separates the EF21 family from SignMuon is the sign placement, not the second compression. All methods are evaluated at the exact server model $\mathbf{X}_t$, the iterate Corollary 1 bounds, which for EF21-MuonSign is not the model the clients hold (15); that the two agree here means the models still track each other. On much wider matrices they separate (Remark 3), and the next section reports both.

5.3 Language Modelling

We test the methods where the matrices are large enough for the layer-rank dependence of Corollary 1 to take effect: the modded-nanoGPT speedrun (record #40), a 12-layer transformer of model dimension 768 with 768×3072 hidden ma-

trices, trained on 611M FineWeb tokens on $8\times H100$. Each method replaces the record’s Muon on the hidden matrices and gates; embeddings, scalars and the head keep the record’s Adam. Our Muon arm *is* record #40’s own optimizer and reproduces its published result to 0.6 sd, which validates the port before anything else is read. Rates are not tuned per method but fixed a priori by the unit-gain rule at one η_0 per *family* (0.06 for the LMO-terminated methods, the record’s own value, and 0.03 for the SIGN-terminated ones), so every contrast is matched-hyperparameter, at the cost of not reporting each method’s best achievable loss. Runs are single-seed, and Table 3 states the seed noise of the reference so that the resolvable differences are explicit (Appendices A.16 and A.17).

Three things follow (Table 3, Figure 3). First, the matrix-aware 1-bit methods transfer to language modelling: all of them beat SignSGD by 0.08–0.12 nats, and the best of them lie within 0.01 of full-precision Muon, at equal wall-clock. Second, error feedback is inexpensive but not without cost. Its clean cost is the matched pair MuonUSign $\rightarrow$ EF21-MuonUSign, +0.024 nats or $\sim 8\%$ more steps, the cost of steering the LMO with an estimator that lags its target. EF21-SignMuon, whose target polar($\tilde{\mathbf{M}}_t$) is orthogonal and hence isotropic, incurs almost no cost and is the strongest compressed method here, notwithstanding Theorem 4.

Third, the bidirectional method’s two models (15) come apart here. Its broadcast model $\mathbf{W}$ — the one every gradient is evaluated at — is indistinguishable from EF21-MuonUSign (3.3213 vs 3.3203), so the compressed *downlink* incurs no measurable cost where training happens. The server model $\mathbf{X}$, which is what Corollary 1 bounds, settles ≈ 2.2 nats above it: a persistent offset, not a divergence, and one that Appendix A.16 localizes to the single zero-initialized `c_proj` layer. This is the mechanism of Remark 3 rather than a tuning failure, and lowering η_0 does not repair it, since the admissible step would have to shrink by a further $\sqrt{r}$ in the layer rank (Remark 4). A spectrally contractive downlink compressor would repair it.

6 Conclusion

SignMuon applies 1-bit sign compression to the Muon LMO direction: it matches Muon’s accuracy and outperforms SignSGD, but we prove that a directly sign-compressed LMO has no global convergence guarantee and can diverge. EF21-MuonUSign compresses the internal residual instead, which restores a transferred $\mathcal{O}(T^{-1/2})$ guarantee and descent on our counterexamples at a 1-bit uplink, and remains about two accuracy points below uncompressed SignMuon; EF21-MuonSign brings the downlink to one bit at no measured cost.

An open tension remains. On every task we measure (centralized, federated and language modelling), the strongest compressed method places the sign after the LMO, exactly the placement Theorems 1 and 4 show to be unrepairable in the worst case. The practitioner chooses between a bound that holds on every instance and roughly two accuracy points on the instances they have; narrowing that gap, by finding what property of realistic problems the counterexamples violate,

is the natural continuation of this work.

Future work. Our (L^0, L^1) guarantee (Corollary 2) covers the uplink-compressed EF21-MuonUSign only, since the generalized-smooth theory of Gruntkowska et al. (2025) is available only without downlink compression; extending it to EF21-MuonSign is open. So is the downlink itself: the rank penalty EF21-MuonSign incurs comes from compressing the model in the wrong norm, removable only by changing the compressor (Remark 4), and whether *any* one-bit compressor can be layer-norm contractive we do not know. Since Gruntkowska et al. (2025) fix the server compressor to the identity throughout their experiments, this regime appears not to have been probed empirically before. The most useful question our results leave open, though, is whether sign-after can be repaired. It is the placement practitioners would pick and the one we cannot certify, so it is at present a working heuristic; what our counterexamples rule out is a guarantee holding on *every* instance, not one holding under an assumption realistic problems satisfy, and identifying such an assumption would close the gap this paper documents. Finally, the reduction of Appendix A.9 applies verbatim to arbitrary layer geometries (Remark 5), and how these methods scale to LLM-sized matrices remains to be measured.

References

- Amsel, N.; Persson, D.; Musco, C.; and Gower, R. M. 2026. The Polar Express: Optimal Matrix Sign Methods and Their Application to the Muon Algorithm. *arXiv:2505.16932*.
- Bernstein, J. 2025. Deriving Muon. <https://jeremybernstein.in/writing/deriving-muon>. Blog. Explains the theoretical derivation and intuition behind the Muon optimizer.
- Bernstein, J.; and Newhouse, L. 2024. Old Optimizer, New Norm: An Anthology. *arXiv:2409.20325*.
- Bernstein, J.; Wang, Y.-X.; Azizzadenesheli, K.; and Anandkumar, A. 2018. signSGD: Compressed Optimisation for Non-Convex Problems. *arXiv:1802.04434*.
- Bernstein, J.; Zhao, J.; Azizzadenesheli, K.; and Anandkumar, A. 2019. signSGD with Majority Vote is Communication Efficient And Fault Tolerant. *arXiv:1810.05291*.
- Beznosikov, A.; Horváth, S.; Richtárik, P.; and Safaryan, M. 2024. On Biased Compression for Distributed Learning. *arXiv:2002.12410*.
- Bolatov, A.; Riabinin, A.; Kornilov, N.; Veprikov, A.; Horváth, S.; Takáč, M.; and Beznosikov, A. 2026. Lion-Muon: Alternating Spectral and Sign Descent for Efficient Training. *arXiv:2605.19811*.
- Cesista, F. L. 2025. Steepest Descent Under Schatten- p Norms.
- Chen, X.; Chen, T.; Sun, H.; Wu, Z. S.; and Hong, M. 2020. Distributed training with heterogeneous data: bridging median- and mean-based algorithms. In *Proceedings of the 34th International Conference on Neural Information Processing Systems*, NIPS ’20. Red Hook, NY, USA: Curran Associates Inc. ISBN 9781713829546.
- Essential AI. 2025. Practical Efficiency of Muon for Pre-training. *arXiv:2505.02222*.
- Grishina, E.; Smirnov, M.; and Rakhuba, M. 2025. Accelerating Newton–Schulz Iteration for Orthogonalization via Chebyshev-type Polynomials. *arXiv preprint arXiv:2506.10935*.
- Gruntkowska, K.; Gaponov, A.; Tovmasyan, Z.; and Richtárik, P. 2025. Error Feedback for Muon and Friends. *arXiv:2510.00643*.
- Jin, R.; Liu, Y.; Huang, Y.; He, X.; Wu, T.; and Dai, H. 2025. Sign-Based Gradient Descent With Heterogeneous Data: Convergence and Byzantine Resilience. *IEEE Transactions on Neural Networks and Learning Systems*, 36(2): 3834–3846.
- Jordan, K.; Jin, Y.; Boza, V.; You, J.; Cesista, F.; Newhouse, L.; and Bernstein, J. 2024. Muon: An optimizer for hidden layers in neural networks.
- Karimireddy, S. P.; Rebjock, Q.; Stich, S.; and Jaggi, M. 2019. Error Feedback Fixes SignSGD and other Gradient Compression Schemes. In Chaudhuri, K.; and Salakhutdinov, R., eds., *Proceedings of the 36th International Conference on Machine Learning*, volume 97 of *Proceedings of Machine Learning Research*, 3252–3261. PMLR.
- Kovalev, D. 2025. Understanding Gradient Orthogonalization for Deep Learning via Non-Euclidean Trust-Region Optimization. *arXiv:2503.12645*.
- Kravatskiy, A.; Kozyrev, I.; Kozlov, N.; Vinogradov, A.; Merkulov, D.; and Oseledets, I. 2025. Ky Fan Norms and Beyond: Dual Norms and Combinations for Matrix Optimization. *arXiv:2512.09678*.
- Krizhevsky, A.; Hinton, G.; et al. 2009. Learning multiple layers of features from tiny images.
- Large, T.; Liu, Y.; Huh, M.; Bahng, H.; Isola, P.; and Bernstein, J. 2024. Scalable Optimization in the Modular Norm. *arXiv:2405.14813*.
- Li, J.; and Hong, M. 2025. A Note on the Convergence of Muon. *arXiv:2502.02900*.
- Liu, J.; Su, J.; Yao, X.; Jiang, Z.; Lai, G.; Du, Y.; Qin, Y.; Xu, W.; Lu, E.; Yan, J.; Chen, Y.; Zheng, H.; Liu, Y.; Liu, S.; Yin, B.; He, W.; Zhu, H.; Wang, Y.; Wang, J.; Dong, M.; Zhang, Z.; Kang, Y.; Zhang, H.; Xu, X.; Zhang, Y.; Wu, Y.; Zhou, X.; and Yang, Z. 2025. Muon is Scalable for LLM Training. *arXiv:2502.16982*.
- Mishra, N.; Trivedi, K.; and Kumar, P. 2026. SignMuon: Communication-Efficient Distributed Muon Optimization. *arXiv:2605.16311*.
- Pethick, T.; Xie, W.; Antonakopoulos, K.; Zhu, Z.; Silveti-Falls, A.; and Cevher, V. 2025. Training Deep Learning Models with Norm-Constrained LMOs. *arXiv:2502.07529*.
- Pethick, T.; Xie, W.; Erdogan, M.; Antonakopoulos, K.; Silveti-Falls, A.; and Cevher, V. 2026. Generalized Gradient Norm Clipping & Non-Euclidean (L_0, L_1) -Smoothness. *arXiv:2506.01913*.
- Qian, X.; Gaponov, A.; Malinovsky, G.; and Richtárik, P. 2026. Communication-Efficient Gluon in Federated Learning. *arXiv:2604.10689*.
- Riabinin, A.; Shulgin, E.; Gruntkowska, K.; and Richtárik, P. 2025. Gluon: Making Muon & Scion Great Again! (Bridging

Theory and Practice of LMO-based Optimizers for LLMs).
arXiv:2505.13416.

Richtárik, P.; Sokolov, I.; and Fatkhullin, I. 2021. EF21: A new, simpler, theoretically better, and practically faster error feedback. In *Advances in Neural Information Processing Systems*, volume 34, 4384–4396.

Safaryan, M.; and Richtarik, P. 2021. Stochastic Sign Descent Methods: New Algorithms and Better Theory. In Meila, M.; and Zhang, T., eds., *Proceedings of the 38th International Conference on Machine Learning*, volume 139 of *Proceedings of Machine Learning Research*, 9224–9234. PMLR.

Shulgin, E.; AlRashed, S.; Orabona, F.; and Richt'arik, P. 2025. Beyond the Ideal: Analyzing the Inexact Muon Update. *arXiv preprint arXiv:2510.19933*.

Yang, G.; Hu, E. J.; Babuschkin, I.; Sidor, S.; Liu, X.; Farhi, D.; Ryder, N.; Pachocki, J.; Chen, W.; and Gao, J. 2021. Tuning Large Neural Networks via Zero-Shot Hyperparameter Transfer. In *Advances in Neural Information Processing Systems (NeurIPS)*.

Yang, G.; Simon, J. B.; and Bernstein, J. 2023. A Spectral Condition for Feature Learning. arXiv:2310.17813.

A Appendix

A.1 Preliminaries: LMO, Muon, and generalized smoothness

This subsection states in full the definitions that Section 3 uses in abbreviated form.

A *Linear Minimization Oracle* (LMO) is an operator $A(\cdot)$ that provides the solution to a linear minimization problem over a feasible set. In particular, the constraints can be defined via the unit ball of a given norm:

$$A(\mathbf{X}) = \arg \min_{\mathbf{Y} \in \{\mathbf{Y} \in \mathcal{S} \mid \|\mathbf{Y}\| \leq 1\}} \langle \mathbf{X}, \mathbf{Y} \rangle, \quad (16)$$

where $\mathbf{X} \in \mathbb{R}^{m \times n}$ is the input matrix, $\mathcal{S} \subset \mathbb{R}^{m \times n}$ is a convex set, and $\langle \mathbf{X}, \mathbf{Y} \rangle = \sum_{i,j} X_{ij}Y_{ij}$ is the standard matrix inner product (Pethick et al. 2025). Such an operator selects the direction of steepest descent with respect to the specified norm. Its analytical and practical role is discussed in detail in the literature on norm-constrained LMO optimizers (Pethick et al. 2025; Kovalev 2025; Riabinin et al. 2025; Bernstein and Newhouse 2024; Bernstein 2025), and the catalogue of usable geometries keeps growing (Cesista 2025; Kravatskiy et al. 2025).

Muon is the instance in which each matrix layer carries the spectral norm, so that the oracle uses the matrix structure of the gradient and the update direction is obtained by orthogonalizing the gradient matrix (Bernstein and Newhouse 2024). Let $\mathbf{M} = \mathbf{U}\mathbf{\Sigma}\mathbf{V}^\top$ be the singular value decomposition (SVD) of the matrix $\mathbf{M} \in \mathbb{R}^{m \times n}$, where $\mathbf{U} \in \mathbb{R}^{m \times r}$ and $\mathbf{V} \in \mathbb{R}^{n \times r}$ are the orthonormal matrices of singular vectors, $\mathbf{\Sigma} \in \mathbb{R}^{r \times r}$ is the diagonal matrix of singular values, and $r = \text{rank}(\mathbf{M})$. Then the LMO direction is $A(\mathbf{M}) = -\mathbf{U}\mathbf{V}^\top$: Muon selects an orthonormal update direction corresponding to the solution of the linear minimization problem induced by the spectral norm geometry. Such orthogonalization produces more isotropic updates and prevents a small number of dominant singular directions from controlling the optimization process, which is particularly beneficial for training DNN (Bernstein and Newhouse 2024; Essential AI 2025). In the original Muon implementation the computation of $\mathbf{U}_t\mathbf{V}_t^\top$ is approximated using Newton-Schulz iterations and related polynomial schemes, which enable efficient matrix orthogonalization without an explicit SVD computation (Amsel et al. 2026; Li and Hong 2025; Liu et al. 2025); Algorithm 1 gives the procedure and the coefficients we use.

Finally, Corollary 2 needs Assumption 2 only in its weaker layer-wise (L^0, L^1) form, which replaces the constant L_i^g by $L_i^{0,g} + L_i^{1,g}\|\nabla_i g(\mathbf{X})\|_*$ (Riabinin et al. 2025; Pethick et al. 2026): for every layer i and all $\mathbf{X}, \mathbf{Y}$,

$$\|\nabla_i g(\mathbf{X}) - \nabla_i g(\mathbf{Y})\|_* \leq (L_i^{0,g} + L_i^{1,g}\|\nabla_i g(\mathbf{X})\|_*) \|\mathbf{X}_i - \mathbf{Y}_i\|_{2 \rightarrow 2}, \quad (17)$$

again with one pair of constants per layer for $g = f$ and per layer and client for $g = f_j$.

A.2 Divergence on linear objectives: reduction and momentum

The reduction quoted in Section 4 collapses each of the three methods to a single scalar inequality and removes momentum from the discussion entirely.

Proposition 1 (Reduction on linear objectives) *Run any of the three methods (7) on the linear objective (9) with $\mathbf{G} \neq \mathbf{0}$, from an arbitrary $\mathbf{X}_0$, with any momentum coefficient $\mu \in [0, 1)$ under either the Standard or the Nesterov rule. Then $\tilde{\mathbf{M}}_t = \gamma_t \mathbf{G}$ with $\gamma_t > 0$, the update direction is the constant matrix $\mathbf{s}(\mathbf{G})$ obtained by substituting $\mathbf{G}$ for $\tilde{\mathbf{M}}_t$ in (7), and*

$$f(\mathbf{X}_{t+1}) - f(\mathbf{X}_t) = -\eta_t \langle \mathbf{G}, \mathbf{s}(\mathbf{G}) \rangle.$$

In particular, if $\langle \mathbf{G}, \mathbf{s}(\mathbf{G}) \rangle < 0$ then f strictly increases at every iteration for any $\eta_t > 0$, and $f(\mathbf{X}_t) \rightarrow +\infty$ whenever $\sum_t \eta_t = \infty$ (e.g. for any constant step size).

Proof of Proposition 1. On the linear objective (9) the gradient is globally constant, $\mathbf{G}_t = \mathbf{G}$, so the momentum buffer of (6) is $\mathbf{M}_t = \sum_{i=0}^{t-1} \mu^i \mathbf{G} = \frac{1-\mu^t}{1-\mu} \mathbf{G}$. Both momentum rules then return a positive multiple of $\mathbf{G}$,

$$\tilde{\mathbf{M}}_t = \gamma_t \mathbf{G}, \quad \gamma_t = \begin{cases} \frac{1-\mu^t}{1-\mu}, & \text{(Standard),} \\ 1 + \mu \frac{1-\mu^t}{1-\mu}, & \text{(Nesterov),} \end{cases} \quad (18)$$

because $\mu \in [0, 1)$. The elementwise $\text{sign}(\cdot)$ and the Muon LMO $\text{polar}(\cdot)$ are each invariant under multiplication by a positive scalar, so evaluating (7) at $\tilde{\mathbf{M}}_t = \gamma_t \mathbf{G}$ returns the same matrix as evaluating it at $\mathbf{G}$; that is, $\mathbf{s}_t = \mathbf{s}(\mathbf{G})$ for every t , independently of μ and of the momentum variant. Hence $f(\mathbf{X}_{t+1}) - f(\mathbf{X}_t) = \langle \mathbf{G}, \mathbf{X}_{t+1} - \mathbf{X}_t \rangle = -\eta_t \langle \mathbf{G}, \mathbf{s}(\mathbf{G}) \rangle$, which is (10). If $\langle \mathbf{G}, \mathbf{s}(\mathbf{G}) \rangle < 0$, then $f(\mathbf{X}_t) = f(\mathbf{X}_0) - \langle \mathbf{G}, \mathbf{s}(\mathbf{G}) \rangle \sum_{i=0}^{t-1} \eta_i$ increases strictly at every step and diverges to $+\infty$ whenever $\sum_t \eta_t = \infty$. ■

By Proposition 1, each divergence theorem reduces to exhibiting a single gradient $\mathbf{G}$ with $\langle \mathbf{G}, \mathbf{s}(\mathbf{G}) \rangle < 0$; the three proofs below do exactly this, and momentum needs no further comment.

A.3 Proof of Theorem 1 (Divergence of SignMuon)

Theorem 1 (Divergence of SignMuon) *There is a matrix $\mathbf{G} \in \mathbb{R}^{4 \times 4}$ with $\langle \mathbf{G}, \text{sign}(\text{polar}(\mathbf{G})) \rangle = -\frac{42468}{103} < 0$. Hence SignMuon ascends on (9): f strictly increases at every iteration for all $\eta_t > 0$, all $\mu \in [0, 1)$, and both momentum variants.*

For SignMuon $\mathbf{s}(\mathbf{G}) = \text{sign}(\text{polar}(\mathbf{G}))$, so by (10) it suffices to construct $\mathbf{G} \in \mathbb{R}^{4 \times 4}$ with $\langle \mathbf{G}, \text{sign}(\text{polar}(\mathbf{G})) \rangle < 0$. The size is not arbitrary. Writing the polar decomposition $\mathbf{G} = \mathbf{Q}\mathbf{H}$ with $\mathbf{H} \succeq 0$, and using that $\text{polar}(\mathbf{G}) = \mathbf{Q}$ and that $\mathbf{H}$ is symmetric,

$$\langle \mathbf{G}, \text{sign}(\text{polar}(\mathbf{G})) \rangle = \langle \mathbf{H}, \text{sym}(\mathbf{Q}^\top \text{sign}(\mathbf{Q})) \rangle, \quad (19)$$

so a counterexample with polar factor $\mathbf{Q}$ exists precisely when $\lambda_{\min}(\text{sym}(\mathbf{Q}^\top \text{sign}(\mathbf{Q}))) < 0$, a question about $O(n)$ alone. For $n = 2$ this settles it: every $\mathbf{Q} \in O(2)$ is $\begin{pmatrix} c & -s \\ s & c \end{pmatrix}$ or $\begin{pmatrix} c & s \\ s & -c \end{pmatrix}$, and in both cases $\mathbf{Q}^\top \text{sign}(\mathbf{Q}) = (|c| + |s|)\mathbf{I} + (\text{antisymmetric})$, whose symmetric part is positive definite, so $\langle \mathbf{G}, \text{sign}(\text{polar}(\mathbf{G})) \rangle = (|c| + |s|) \text{tr} \mathbf{H} > 0$ and SignMuon cannot ascend. At $n = 3$ several independent searches over $O(3)$ found no negative eigenvalue; at $n = 4$ they do, and the $\mathbf{O}$ below is one such instance (its spectrum is $(-0.4175, 1.5825, 2, 2)$, so it is not even the worst).

We construct $\mathbf{G} \in \mathbb{R}^{4 \times 4}$ by defining a specific orthogonal matrix $\mathbf{O}$ and a specific rank-1 principal component $\mathbf{u}_1 \mathbf{v}_1^\top$. Let the orthogonal matrix $\mathbf{O}$ be given by the following exact rational numbers:

$$\mathbf{O} = \frac{1}{103} \begin{pmatrix} 101 & 20 & 2 & -2 \\ -20 & 97 & 20 & -20 \\ -2 & 20 & 2 & 101 \\ -2 & 20 & -101 & -2 \end{pmatrix}. \quad (20)$$

Because no entry is zero, its element-wise sign matrix $\mathbf{S} = \text{sign}(\mathbf{O})$ is uniquely defined. Now, let $\mathbf{u}_1$ and $\mathbf{v}_1$ be the following exact unit vectors:

$$\mathbf{u}_1 = \frac{1}{\sqrt{309}} \begin{pmatrix} 10 \\ -3 \\ 10 \\ 10 \end{pmatrix}, \quad \mathbf{v}_1 = \frac{1}{\sqrt{309}} \begin{pmatrix} 10 \\ 3 \\ -10 \\ 10 \end{pmatrix}. \quad (21)$$

One can easily verify that $\mathbf{O}\mathbf{v}_1 = \mathbf{u}_1$, meaning $\mathbf{u}_1$ and $\mathbf{v}_1$ act perfectly as left and right singular vectors for this orthogonal space. The crucial feature of this geometry is that the Frobenius inner product between this rank-1 component and the sign matrix $\mathbf{S}$ yields an exact, strictly negative fraction:

$$\langle \mathbf{u}_1 \mathbf{v}_1^\top, \mathbf{S} \rangle = \mathbf{u}_1^\top \mathbf{S} \mathbf{v}_1 = -\frac{43}{103}. \quad (22)$$

We construct the gradient matrix $\mathbf{G}$ by assigning a large singular value ($\sigma_1 = 1001$) to this pathological component and a singular value of 1 to the rest of the orthogonal space:

$$\mathbf{G} \approx \begin{pmatrix} 324.6 & 97.3 & -323.6 & 323.6 \\ -97.3 & -28.2 & 97.3 & -97.3 \\ 323.6 & 97.3 & -323.6 & 324.6 \\ 323.6 & 97.3 & -324.6 & 323.6 \end{pmatrix}. \quad (23)$$

Indeed, since $\mathbf{G} = 1000 \mathbf{u}_1 \mathbf{v}_1^\top + \mathbf{O}$ and $\mathbf{O}\mathbf{v}_1 = \mathbf{u}_1$,

$$\begin{aligned} \mathbf{G}\mathbf{v}_1 &= 1000 \mathbf{u}_1 (\mathbf{v}_1^\top \mathbf{v}_1) + \mathbf{O}\mathbf{v}_1 \\ &= 1001 \mathbf{u}_1, \end{aligned}$$

so $(\mathbf{u}_1, \mathbf{v}_1)$ is a singular pair of $\mathbf{G}$ with $\sigma_1 = 1001$. For any $\mathbf{w} \perp \mathbf{v}_1$ we have $\mathbf{G}\mathbf{w} = \mathbf{O}\mathbf{w}$; as $\mathbf{O}$ is orthogonal and $\mathbf{O}\mathbf{v}_1 = \mathbf{u}_1$, the restriction $\mathbf{O}|_{\mathbf{v}_1^\perp}$ is an isometry onto $\mathbf{u}_1^\perp$, hence $\sigma_2 = \sigma_3 = \sigma_4 = 1$. Moreover, with $\mathbf{u}_k = \mathbf{O}\mathbf{v}_k$ for $k \geq 2$,

$$\sum_{k \geq 2} \mathbf{u}_k \mathbf{v}_k^\top = \mathbf{O}(\mathbf{I} - \mathbf{v}_1 \mathbf{v}_1^\top) = \mathbf{O} - \mathbf{u}_1 \mathbf{v}_1^\top,$$

so $\mathbf{U}_G \mathbf{V}_G^\top = \mathbf{u}_1 \mathbf{v}_1^\top + (\mathbf{O} - \mathbf{u}_1 \mathbf{v}_1^\top) = \mathbf{O}$.

Substituting the resulting matrix $\mathbf{G}$ into the descent condition yields:

$$\langle \mathbf{G}, \mathbf{S} \rangle = \langle 1000 \mathbf{u}_1 \mathbf{v}_1^\top + \mathbf{O}, \mathbf{S} \rangle = 1000 \langle \mathbf{u}_1 \mathbf{v}_1^\top, \mathbf{S} \rangle + \langle \mathbf{O}, \mathbf{S} \rangle. \quad (24)$$

The inner product $\langle \mathbf{O}, \mathbf{S} \rangle$ is equivalent to the L_1 norm (sum of absolute values) of $\mathbf{O}$, which equals exactly $\frac{532}{103}$. Therefore:

$$\langle \mathbf{G}, \mathbf{S} \rangle = 1000 \left(-\frac{43}{103} \right) + \frac{532}{103} = -\frac{42468}{103} \approx -412.31. \quad (25)$$

Here $\mathbf{S} = \text{sign}(\mathbf{O}) = \text{sign}(\text{polar}(\mathbf{G})) = \mathbf{s}(\mathbf{G})$, so $\langle \mathbf{G}, \mathbf{s}(\mathbf{G}) \rangle = -\frac{42468}{103} < 0$. By Proposition 1, SignMuon strictly ascends, $f(\mathbf{X}_{t+1}) - f(\mathbf{X}_t) = \frac{42468}{103} \eta_t > 0$ at every iteration, for every $\eta_t > 0$, every $\mu \in [0, 1)$, and both momentum variants; $f(\mathbf{X}_t) \rightarrow +\infty$ under any non-summable step size. ■

A.4 Proof of Theorem 2 (Divergence of MuonUSign)

Theorem 2 (Divergence of MuonUSign) *There is a matrix $\mathbf{G} \in \mathbb{R}^{5 \times 5}$ with $\langle \mathbf{G}, \text{polar}(\text{sign}(\mathbf{G})) \rangle \approx -13.89 < 0$. Hence MuonUSign ascends on (9) for all $\eta_t > 0$, all $\mu \in [0, 1)$, and both momentum variants.*

MuonUSign (Algorithm 4) applies the sign *before* the LMO, so $\mathbf{s}(\mathbf{G}) = \text{polar}(\text{sign}(\mathbf{G}))$. By (10) it suffices to construct $\mathbf{G} \in \mathbb{R}^{5 \times 5}$ with $\langle \mathbf{G}, \text{polar}(\text{sign}(\mathbf{G})) \rangle < 0$.

The size is again not arbitrary, and here the question reduces to *sign patterns*. With $\mathbf{S} = \text{sign}(\mathbf{G})$ and $\mathbf{D} = \text{polar}(\mathbf{S})$, the fact that $\mathbf{G}$ vanishes off the support of $\mathbf{S}$ gives

$$\langle \mathbf{G}, \text{polar}(\text{sign}(\mathbf{G})) \rangle = \sum_{i,j} |G_{ij}| S_{ij} D_{ij}, \quad (26)$$

and likewise $\langle \mathbf{G}, \text{sign}(\mathbf{D}) \rangle = \sum_{i,j} |G_{ij}| S_{ij} \text{sign}(D_{ij})$ for the MuonSign step of Theorem 3. So an ascent instance exists at a given shape precisely when some sign pattern $\mathbf{S}$ there has a *mismatched* entry, $S_{ij} D_{ij} < 0$. Under our convention $\mathbf{S} \in \{\pm 1\}^{m \times n}$ always, and mismatch existence is invariant under row and column sign flips ($\text{polar}(\mathbf{P}_1 \mathbf{S} \mathbf{P}_2) = \mathbf{P}_1 \text{polar}(\mathbf{S}) \mathbf{P}_2$ for ± 1 diagonal $\mathbf{P}_1, \mathbf{P}_2$), so enumerating one representative per class settles the question outright (code/counterexamples/enumerate_minimality.py). It returns: *no* pattern at 4×4 , at $3 \times n$ ($n \leq 9$) or at $2 \times n$ ($n \leq 12$) has a mismatch. Neither MuonUSign nor MuonSign can therefore ascend on any linear objective at those sizes at all. The first instances appear at 4×5 (720 of the 2^{12} classes) and, among square shapes, at 5×5 , where the $\mathbf{S}$ below attains the deepest mismatch any 5×5 sign matrix admits, $|D_{4,2}| = 1/\sqrt{17}$. (Had we kept $\text{sign}(0) = 0$, gradients with exact zeros would admit instances from 3×4 on; the convention removes them, along with their dependence on an entry being exactly zero.)

Fix the full-rank sign matrix $\mathbf{S} \in \{-1, 1\}^{5 \times 5}$,

$$\mathbf{S} = \begin{pmatrix} -1 & -1 & 1 & 1 & 1 \\ -1 & -1 & 1 & -1 & -1 \\ 1 & -1 & 1 & 1 & -1 \\ 1 & 1 & -1 & -1 & 1 \\ 1 & 1 & 1 & -1 & 1 \end{pmatrix}, \quad (27)$$

and let $\mathbf{D} = \text{polar}(\mathbf{S})$ be its (unique, since $\mathbf{S}$ is full rank) Muon LMO direction. A direct computation gives $D_{4,2} = -1/\sqrt{17} \approx -0.2425 < 0$ while $\text{sign}(D_{i,j}) = S_{i,j}$ at all 24 other entries; equivalently, $\text{sign}(\mathbf{D})$ and $\mathbf{S}$ disagree at exactly the single entry $(4, 2)$, where $S_{4,2} = +1$. We exploit this lone mismatch. Define

$$\mathbf{G} = \epsilon \mathbf{S} + (M - \epsilon) \mathbf{e}_4 \mathbf{e}_2^\top, \quad \epsilon > 0, M > \epsilon, \quad (28)$$

so that $G_{4,2} = M > 0$ and $G_{i,j} = \epsilon S_{i,j}$ otherwise; hence $\text{sign}(\mathbf{G}) = \mathbf{S}$ and $\text{polar}(\text{sign}(\mathbf{G})) = \mathbf{D}$ for every $M > 0$. The descent inner product splits as

$$\langle \mathbf{G}, \mathbf{D} \rangle = \epsilon \sum_{(i,j) \neq (4,2)} S_{i,j} D_{i,j} + M D_{4,2} = \epsilon C + M D_{4,2}, \quad (29)$$

where $C := \sum_{(i,j) \neq (4,2)} |D_{i,j}| = 10.366 > 0$ is fixed (every such entry agrees in sign with $\mathbf{S}$), while $M D_{4,2} = -M/\sqrt{17} \rightarrow -\infty$. Thus $\langle \mathbf{G}, \mathbf{D} \rangle < 0$ for any $M > \sqrt{17} C \epsilon \approx 42.7 \epsilon$; with $\epsilon = 1$, $M = 100$ one obtains $\langle \mathbf{G}, \mathbf{D} \rangle = -13.89$, for the exact polar factor that the theorem is stated over. By Proposition 1, MuonUSign strictly ascends on $f(\mathbf{W}) = \langle \mathbf{G}, \mathbf{W} \rangle$ for every $\eta_t > 0$, every $\mu \in [0, 1)$, and both momentum variants; $f(\mathbf{X}_t) \rightarrow +\infty$ under any non-summable step size. ■

A.5 Proof of Theorem 3 (Divergence of MuonSign)

Theorem 3 (Divergence of MuonSign) *For the same matrix $\mathbf{G} \in \mathbb{R}^{5 \times 5}$ as in Theorem 2, $\langle \mathbf{G}, \text{sign}(\text{polar}(\text{sign}(\mathbf{G}))) \rangle \approx -76 < 0$. Hence MuonSign ascends on (9) for all $\eta_t > 0$, all $\mu \in [0, 1)$, and both momentum variants.*

MuonSign (Algorithm 5) signs the LMO output as well, so $\mathbf{s}(\mathbf{G}) = \text{sign}(\text{polar}(\text{sign}(\mathbf{G}))) = \text{sign}(\mathbf{D})$. We reuse the *same* $\mathbf{S}$ and $\mathbf{G}$ of (27)–(28): since $\text{sign}(\mathbf{G}) = \mathbf{S}$, the bidirectional step is the constant matrix $\text{sign}(\mathbf{D})$, which agrees with $\mathbf{S}$ at all 24 entries except $(4, 2)$, where $\text{sign}(D_{4,2}) = -1 = -S_{4,2}$. Using $S_{i,j}^2 = 1$ everywhere,

$$\begin{aligned} \langle \mathbf{G}, \text{sign}(\mathbf{D}) \rangle &= \epsilon \sum_{(i,j) \neq (4,2)} S_{i,j} \text{sign}(D_{i,j}) + M \text{sign}(D_{4,2}) \\ &= 24\epsilon - M. \end{aligned} \quad (30)$$

This is negative for every $M > 24\epsilon$; with $\epsilon = 1$, $M = 100$ it equals exactly -76 . By Proposition 1, MuonSign strictly ascends on $f(\mathbf{W}) = \langle \mathbf{G}, \mathbf{W} \rangle$ for every $\eta_t > 0$, every $\mu \in [0, 1)$, and both momentum variants; $f(\mathbf{X}_t) \rightarrow +\infty$ under any non-summable step size. In particular, the *same* 5×5 linear instance defeats both the uplink-only (MuonUSign) and the bidirectional (MuonSign) placements. ■

A.6 Comparison with the convergence claim for SignMuon

Concurrently, Mishra, Trivedi, and Kumar (2026) introduced the same sign-after-LMO method under the same name *SignMuon*, with update direction $\mathbf{S}_t = \text{sign}(\text{polar}(\mathbf{M}_t))$ rescaled to $\mathbf{D}_t = \mathbf{S}_t / \sqrt{mn}$; this coincides with the SignMuon step of Section 4 after absorbing $1/\sqrt{mn}$ into η . For this method they establish an $\mathcal{O}(1/\sqrt{T})$ stationarity guarantee. We show that this guarantee does not contradict Theorem 1: the finalized rate is proved for a different update direction, and for $\mathbf{D}_t$ their bound is uninformative on the instance of Theorem 1.

Their analysis controls the stationarity proxy $\mathcal{G}_T = \frac{1}{T} \sum_t \mathbb{E}[\|\mathbf{g}_t\|_1 / \sqrt{mn}]$, where $\mathbf{g}_t = \nabla f(\mathbf{X}_t)$, through the per-entry sign-error probabilities $q_{ij,t} = \Pr(\mathbf{S}_{t,ij} \neq \text{sign}(\mathbf{g}_{t,ij}) \mid \mathbf{X}_t)$, in two steps. First, for an arbitrary sign oracle $\mathbf{S}_t$ they derive

$$\begin{aligned} \mathcal{G}_T &\leq \frac{f(\mathbf{X}_0) - f^*}{\eta T} + \frac{L_*}{2} \eta \\ &\quad + \underbrace{\frac{2}{T} \sum_t \mathbb{E} \left[\frac{1}{\sqrt{mn}} \sum_{i,j} |\mathbf{g}_{t,ij}| q_{ij,t} \right]}_{=: R_T}. \end{aligned} \quad (31)$$

Inequality (31) applies in particular to $\mathbf{S}_t = \text{sign}(\text{polar}(\mathbf{M}_t))$, but with the residual R_T left unbounded. Second, the rate is obtained by estimating R_T , and this estimate is derived *only* for the gradient-sign oracle $\mathbf{S}_t = \text{sign}(\tilde{\mathbf{G}}_t)$, where $\tilde{\mathbf{G}}_t$ is an unbiased stochastic gradient with coordinatewise variance $\text{Var}(\tilde{\mathbf{G}}_{t,ij} \mid \mathbf{X}_t) \leq \sigma_{ij}^2/n_b$ and n_b the mini-batch size. In that case a Markov–Jensen argument yields $|\mathbf{g}_{t,ij}| q_{ij,t} \leq \sigma_{ij}/\sqrt{n_b}$, hence $R_T = \mathcal{O}(\|\sigma\|_1 / \sqrt{mn n_b})$ with $\|\sigma\|_1 = \sum_{i,j} \sigma_{ij}$, which vanishes as $n_b \rightarrow \infty$.

This estimate bounds $q_{ij,t}$ by the noise level $\sigma_{ij}/\sqrt{n_b}$ and is therefore specific to $\text{sign}(\tilde{\mathbf{G}}_t)$, whose only source of sign error is gradient noise. It does not extend to the polar-sign oracle: even with exact gradients ($\sigma_{ij} = 0$) the latter satisfies $q_{ij,t} = \mathbf{1}[\text{sign}(\text{polar}(\mathbf{g}_t))_{ij} \neq \text{sign}(\mathbf{g}_{t,ij})]$, which need not vanish. Consequently the finalized $\mathcal{O}(1/\sqrt{T})$ guarantee holds for the gradient-sign update $\mathbf{S}_t = \text{sign}(\tilde{\mathbf{G}}_t)$, whose direction never invokes the polar factor, and not for the LMO-based direction $\text{sign}(\text{polar}(\mathbf{M}_t))$ to which it is attributed.

On the instance of Theorem 1 the residual R_T is not merely unbounded: it exceeds $\mathcal{G}_T$. Consider the linear objective (9) with the 4×4 gradient $\mathbf{G}$ of Theorem 1. By Proposition 1 one has $\mathbf{g}_t \equiv \mathbf{G}$ and $\text{polar}(\mathbf{M}_t) = \text{polar}(\mathbf{G})$ at every iteration, so the oracle is deterministic and the inner-product identity $\mathbb{E}[\langle \mathbf{g}_t, \mathbf{D}_t \rangle \mid \mathbf{X}_t] = \frac{1}{\sqrt{mn}} \sum_{i,j} |\mathbf{g}_{t,ij}| (1 - 2q_{ij,t})$ underlying (31) reduces to

$$\sum_{i,j} |\mathbf{G}_{ij}| (1 - 2q_{ij}) = \langle \mathbf{G}, \text{sign}(\text{polar}(\mathbf{G})) \rangle = -\frac{42468}{103} < 0. \quad (32)$$

Therefore $\sum_{i,j} |\mathbf{G}_{ij}| q_{ij} > \frac{1}{2} \|\mathbf{G}\|_1$, and at every iteration

$$\frac{2}{\sqrt{mn}} \sum_{i,j} |\mathbf{G}_{ij}| q_{ij} > \frac{\|\mathbf{G}\|_1}{\sqrt{mn}} = \mathcal{G}_t. \quad (33)$$

The unestimated term R_T in (31) thus strictly exceeds the left-hand side, so the bound reduces to $\mathcal{G}_T \leq (\text{nonnegative}) + R_T$ with $R_T > \mathcal{G}_T$ and imposes no constraint on $\mathcal{G}_T$. In agreement, (32) yields the exact per-step increase $f(\mathbf{X}_{t+1}) - f(\mathbf{X}_t) = -\eta \langle \mathbf{G}, \mathbf{D}_t \rangle = \frac{\eta}{4} \cdot \frac{42468}{103} > 0$ for every $\eta > 0$, which is the divergence established in Theorem 1.

A.7 Extended comparison with S-Muon

Taking the norms dual to the Ky Fan k -norms, Kravatskiy et al. (2025) obtain the *Fanion* family, whose updates $\sum_{i \leq k} \mathbf{u}_i \mathbf{v}_i^\top$ interpolate between the rank-one step of the nuclear norm and Muon’s full-rank $\mathbf{U}\mathbf{V}^\top$ at $k = \min(m, n)$; a conic combination of LMOs is again an LMO, for the norm dual to the corresponding combination of dual norms. Their S-Muon is one such combination, $\tau \mathbf{U}\mathbf{V}^\top + (1 - \tau) c \text{sign}(\mathbf{M}_t)$ with fixed $\tau \in [0, 1]$, $c > 0$ (their notation differs; we reserve α for compressor contraction and η for the learning rate). It is the sharpest available contrast with this paper: the sign enters *inside* the oracle, so the step is still an LMO for an explicit norm and inherits the convergence theory of one, where our three placements act *around* the oracle, on an object that is an LMO for no norm at all. Theorems 1–3 are the consequence. A caution from the same work applies to us directly: they exhibit an LMO method (rank-one Neon) markedly worse than Muon in practice despite sharing its convergence asymptotics in the bounds of Kovalev (2025) and Riabinin et al. (2025), from which our own guarantee descends. A rate of the form $\mathcal{O}(T^{-1/2})$ is a licence to run a method, not a prediction of the performance it will attain.

A.8 Proof of Theorem 4 (Divergence of EF21-SignMuon)

Recall from the main text that EF21-SignMuon (Algorithm 3) does not descend along the LMO output $\mathbf{D}_t = \text{polar}(\tilde{\mathbf{M}}_t)$ itself, but along the error-feedback estimate $\mathbf{d}_t^{\text{est}}$ of (11), followed by $\mathbf{X}_t = \mathbf{X}_{t-1} - \eta \mathbf{d}_t^{\text{est}}$. A *single* magnitude α_t rescales the signs of *all* entries at once; this coupling is what the counterexample exploits. We now prove Theorem 4.

Proof idea Consider the target $\mathbf{D}_t$ as a 2×2 matrix whose off-diagonal is large and *flips sign every step*, while its diagonal is a small constant. The estimator (11) rescales all four signs by the same α_t , so the flipping off-diagonal holds α_t at $\Theta(1)$, which exceeds the small diagonal target. The diagonal of $\mathbf{d}_t^{\text{est}}$ therefore never settles: it oscillates with $\Theta(1)$ amplitude, and its time-average has the sign *opposite* to the target. Being an average over an oscillation, this bias depends only on the oscillation's phase, which one-bit sign feedback cannot correct. It pushes one entry of $\mathbf{X}_t$ monotonically to infinity (Figure 1, right).

Two observations make the result independent of the parameters. First, the step size and smoothness only rescale the orbit, so we may fix $\eta = 1$ and one value of L . Second, the divergence is due entirely to the estimator's response to a fixed target sequence; momentum affects only *how the gradients are sourced*, not the targets. A single explicit trajectory thus settles all $(L, \eta, \mu, \text{variant})$ at once. The mechanism is not degeneracy: the matrices driving the divergent tail have condition number $\frac{16}{9}$ throughout (the two-step preamble, which only sets the phase, is not claimed to be well conditioned).

Accordingly the proof has three parts. Part 1 rescales the problem to remove L and η . Part 2 isolates the dynamical core: for one fixed sequence of LMO targets, the estimator provably converges to a limit cycle whose diagonal has the wrong sign. Part 3 exhibits a concrete smooth function whose gradients generate that target sequence, for every μ and either momentum variant.

Proof

Part 1: rescaling.

Lemma 1 (Scale reduction) *If $\tilde{f}$ is $\tilde{L}$ -smooth with EF21-SignMuon iterates $\tilde{\mathbf{X}}_t$ at step size 1, then $f(\mathbf{X}) := \frac{L\eta^2}{L} \tilde{f}(\mathbf{X}/\eta)$ is L -smooth and its run at step size η (same μ , same variant, from $\mathbf{0}$) satisfies $\mathbf{X}_t = \eta \tilde{\mathbf{X}}_t$ and $f(\mathbf{X}_t) = \frac{L\eta^2}{L} \tilde{f}(\tilde{\mathbf{X}}_t)$.*

Proof. $\nabla f(\mathbf{X}) = \frac{L\eta}{L} \nabla \tilde{f}(\mathbf{X}/\eta)$, so f is L -smooth. Suppose $\mathbf{X}_s = \eta \tilde{\mathbf{X}}_s$ for $s < t$: the two gradients then differ by the positive factor $\frac{L\eta}{L}$, which $\mathbf{M}_t$ and $\tilde{\mathbf{M}}_t$ (positive combinations of past gradients) inherit and polar discards. Hence $\mathbf{D}_t$ and $\mathbf{d}_t^{\text{est}}$ match the normalized run, and $\mathbf{X}_t = \eta \tilde{\mathbf{X}}_t$. ■ So it suffices to exhibit, for each $(\mu, \text{variant})$, a $C^\infty \tilde{L}$ -smooth $\tilde{f}$ on which the *normalized* run ($\eta = 1$) obeys (12); that $\tilde{f}$ may be taken bounded below (Assumption 1) is shown afterwards (Remark 1). We fix $\eta = 1$ from now on.

Part 2: the estimator's limit cycle. The dynamical core of the proof is the behavior of the estimator (11) on the fixed target sequence

$$\mathbf{D}_1 = \mathbf{S}_1, \quad \mathbf{D}_2 = \mathbf{S}_2, \quad \mathbf{D}_t = \bar{\mathbf{D}}^{(-1)^t} \quad (t \geq 3), \quad (34)$$

$$\begin{aligned} \bar{\mathbf{D}}^\pm &= \begin{pmatrix} 7/25 & \pm 24/25 \\ \pm 24/25 & -7/25 \end{pmatrix}, \\ \mathbf{S}_1 &= \begin{pmatrix} -4/5 & 3/5 \\ -3/5 & -4/5 \end{pmatrix}, \quad \mathbf{S}_2 = \begin{pmatrix} 3/5 & -4/5 \\ 0 & 0 \end{pmatrix}. \end{aligned} \quad (35)$$

The divergence originates in the tail ($t \geq 3$): the reflections $\bar{\mathbf{D}}^\pm$ share the diagonal $(\frac{7}{25}, -\frac{7}{25})$, while their off-diagonal $\pm \frac{24}{25}$ reverses sign at every step. The rotation $\mathbf{S}_1$ and the rank-one $\mathbf{S}_2$ form a two-step preamble whose only role is to place the estimator in the divergent phase of the cycle.

Lemma 2 (Wrong-sign limit cycle) *On the targets (34), the recursion (11) from $\mathbf{d}_0^{\text{est}} = \mathbf{0}$ enters at $t = 3$ the exact period-two cycle $\mathbf{d}_t^{\text{est}} = \mathbf{d}_B$ (odd t), $\mathbf{d}_A$ (even t), where*

$$\mathbf{d}_B = \frac{1}{200} \begin{pmatrix} -61 & -201 \\ -61 & -61 \end{pmatrix}, \quad \mathbf{d}_A = \frac{1}{200} \begin{pmatrix} 131 & -9 \\ 131 & 131 \end{pmatrix}. \quad (36)$$

Its $(2, 2)$ -entry averages $\frac{1}{2}((\mathbf{d}_A)_{22} + (\mathbf{d}_B)_{22}) = +\frac{7}{40}$, opposite in sign to every target value $(\mathbf{D}_t)_{22} = -\frac{7}{25}$.

Proof. Substituting (34) into (11) gives the values

t	1	2	3	4 (then 2-periodic)
α_t	$\frac{7}{10}$	$\frac{21}{20}$	$\frac{131}{200}$	$\frac{24}{25}$
$\mathbf{d}_t^{\text{est}}$	$\frac{1}{10} \begin{pmatrix} -7 & 7 \\ -7 & -7 \end{pmatrix}$	$\frac{1}{20} \begin{pmatrix} 7 & -7 \\ 7 & 7 \end{pmatrix}$	$\mathbf{d}_B$	$\mathbf{d}_A$

(37)

Each residual $\mathbf{D}_t - \mathbf{d}_{t-1}^{\text{est}}$ has strictly nonzero entries, so the signs are unambiguous; e.g. at $t = 3$ it is $\frac{1}{100} \begin{pmatrix} -7 & -61 \\ -131 & -63 \end{pmatrix}$, all negative. From $t = 3$ the targets are 2-periodic and the pair $(\mathbf{d}_B, \mathbf{d}_A)$ reproduces itself: $\bar{\mathbf{D}}^+ - \mathbf{d}_B$ and $-(\bar{\mathbf{D}}^- - \mathbf{d}_A)$ are both entrywise positive with mean $\frac{24}{25}$, so $\mathbf{d}_B + \frac{24}{25}\mathbf{J} = \mathbf{d}_A$ and $\mathbf{d}_A - \frac{24}{25}\mathbf{J} = \mathbf{d}_B$ ($\mathbf{J}$ all-ones). ■

Since $\mathbf{X}_t = \mathbf{X}_{t-1} - \mathbf{d}_{t-1}^{\text{est}}$ (recall $\eta = 1$), over one period the $(2, 2)$ -coordinate changes by $-(\mathbf{d}_A + \mathbf{d}_B)_{22} = -\frac{7}{20}$. Consequently a term $-\gamma W_{22}$ in $\tilde{f}$, with $\gamma := \frac{7}{12}$, increases by $\gamma \cdot \frac{7}{20} = \frac{49}{240}$ per period. This is the divergence, provided a genuine smooth function produces the targets (34); Part 3 constructs one.

Part 3: realization by a smooth function. Fix $(\mu, \text{variant})$ and set $\gamma = \frac{7}{12}$, $\nu = \frac{1}{1+2\mu}$, and

$$\begin{aligned} A &= \frac{1+\mu}{1-\mu} \text{ (standard),} \\ A &= \frac{1+\mu}{(1-\mu)(1+2\mu)} \text{ (Nesterov).} \end{aligned} \quad (38)$$

We build $\tilde{f} = g + \sum_{k=1}^3 b_k$ from a periodic-plus-linear field g and three *localized corrections* b_k , all explicit.

The field is

$$g(\mathbf{W}) = -\gamma W_{22} + A \Phi_1(W_{12}) + A \Phi_2(W_{21}), \quad (39)$$

where $\Phi_i(w) = \int_0^w \psi_i$ and $\psi_i: \mathbb{R} \rightarrow [-1, 1]$ is a fixed C^∞ , p_i -periodic function with $\int_0^{p_i} \psi_i = 0$,

$$p_1 = \frac{21}{20}, \quad p_2 = \frac{7}{20}, \quad \delta = \frac{1}{100},$$

equal to $+1$ on $[\rho_i^+ - \delta, \rho_i^+ + \delta]$ and -1 on $[\rho_i^- - \delta, \rho_i^- + \delta] \pmod{p_i}$, where

$$\rho_1^+ = \frac{131}{200}, \quad \rho_1^- = \frac{140}{200}; \quad \rho_2^+ = \frac{61}{200}, \quad \rho_2^- = 0.$$

The two bands are disjoint mod p_i (their centers are $\frac{9}{200} > 2\delta$ apart), so such a ψ_i exists; the zero-mean condition, met by balancing the rest of the period, makes Φ_i periodic (hence bounded). On each band $\Phi_i' = \psi_i = \pm 1$ exactly.

The corrections pin the first three gradients. Fix once a C^∞ cutoff $\phi: \mathbb{R} \rightarrow [0, 1]$ with $\phi \equiv 1$ on $[0, \frac{1}{2}]$ and $\phi \equiv 0$ on $[1, \infty)$, put $r = \frac{1}{50}$, and set

$$b_k(\mathbf{W}) = \langle \mathbf{C}_k, \mathbf{W} - \mathbf{Z}_k \rangle \phi(\|\mathbf{W} - \mathbf{Z}_k\|_F / r), \quad (40)$$

centered at the first three iterates (from Lemma 2)

$$\mathbf{Z}_1 = \mathbf{0}, \quad \mathbf{Z}_2 = \frac{1}{10} \begin{pmatrix} 7 & -7 \\ 7 & 7 \end{pmatrix}, \quad \mathbf{Z}_3 = \frac{1}{20} \begin{pmatrix} 7 & -7 \\ 7 & 7 \end{pmatrix}.$$

Each b_k is C^∞ , supported in $\{\|\mathbf{W} - \mathbf{Z}_k\|_F \leq r\}$; since its linear factor vanishes at $\mathbf{Z}_k$ while $\phi(0) = 1$, $\nabla b_k(\mathbf{Z}_k) = \mathbf{C}_k$. We choose $\mathbf{C}_k := \hat{\mathbf{G}}_k - \nabla g(\mathbf{Z}_k)$ with the explicit $\hat{\mathbf{G}}_k$ of (41) below, so that $\nabla \tilde{f}(\mathbf{Z}_k) = \hat{\mathbf{G}}_k$. Every term of $\tilde{f}$ has a bounded Hessian, so $\tilde{f}$ is C^∞ and $\tilde{L}$ -smooth for a finite $\tilde{L}(\mu, \text{variant})$.

Lemma 3 (Realization) For every $\mu \in [0, 1)$ and either variant, EF2I-SignMuon on this $\tilde{f}$ ($\eta = 1$, from $\mathbf{0}$) generates exactly the targets (34).

Proof. The required gradients. Momentum is a causal, positive-weight linear filter of the gradients, and we invert it. Define the transient gradients

$$\hat{\mathbf{G}}_t = \frac{\mathbf{M}_t - \mu \mathbf{M}_{t-1}}{1 - \mu} \quad (t = 1, 2, 3; \mathbf{M}_0 = \mathbf{0}) \quad (41)$$

and the field gradient $\mathbf{G}^\pm = \begin{pmatrix} 0 & \pm A \\ \pm A & -\gamma \end{pmatrix}$, where the prescribed buffer values $\mathbf{M}_{1,2,3}$ are given below. With $\bar{\mathbf{M}}^\pm = \begin{pmatrix} 0 & \pm 1 \\ \pm 1 & -\gamma \end{pmatrix}$, the factorization

$$\begin{aligned} \bar{\mathbf{M}}^\pm &= \bar{\mathbf{D}}^\pm \begin{pmatrix} 24/25 & \mp 7/25 \\ \mp 7/25 & 337/300 \end{pmatrix} \\ &\text{(second factor } \succ 0, \det = 1) \end{aligned} \quad (42)$$

shows $\text{polar}(\bar{\mathbf{M}}^\pm) = \bar{\mathbf{D}}^\pm$, with singular values $\frac{3}{4}, \frac{4}{3}$ (the condition number $\frac{16}{9}$ of the idea).

Standard momentum ($\tilde{\mathbf{M}}_t = \mathbf{M}_t$). Take $\mathbf{M}_1 = \mathbf{S}_1$, $\mathbf{M}_2 = \mathbf{S}_2$, $\mathbf{M}_3 = \bar{\mathbf{M}}^-$; then $\hat{\mathbf{G}}_{1,2,3}$ are the explicit matrices (41). Feeding $\mathbf{G}^{(-1)^t}$ for $t \geq 4$ keeps $\mathbf{M}_t = \bar{\mathbf{M}}^{(-1)^t}$, because $(1 - \mu)\mathbf{G}^\pm = \bar{\mathbf{M}}^\pm - \mu \bar{\mathbf{M}}^\mp$ with A as in (38). As $\text{polar}(\mathbf{S}_1) = \mathbf{S}_1$ (orthogonal) and $\text{polar}(\mathbf{S}_2) = \mathbf{S}_2$ (rank one), (42) yields the targets (34).

Nesterov momentum ($\tilde{\mathbf{M}}_t = (1 + \mu)\mathbf{M}_t - \mu \mathbf{M}_{t-1}$). Take $\mathbf{M}_1 = \frac{1}{1+\mu} \mathbf{S}_1 \mathbf{H}_1$, $\mathbf{M}_2 = \frac{1}{1+\mu} (\mathbf{S}_2 + \mu \mathbf{M}_1)$, $\mathbf{M}_3 = \bar{\mathbf{M}}'^-$ and $\mathbf{M}_t = \bar{\mathbf{M}}'^{(-1)^t}$ ($t \geq 4$), where $\bar{\mathbf{M}}'^\pm = \begin{pmatrix} 0 & \pm \nu \\ \pm \nu & -\gamma \end{pmatrix}$, $\mathbf{H}_1 = \text{diag}(1, 1 + T)$, and, for $\mu > 0$,

$$T = \left(\frac{140(1+\mu)^2}{1+2\mu} - 44 \right) \frac{1+\mu}{117\mu} > 0.$$

(At $\mu = 0$ the Nesterov rule reads $\tilde{\mathbf{M}}_t = \mathbf{M}_t$ and is the standard case already treated, so nothing is left to prove there.) Then $\tilde{\mathbf{M}}_1 = \mathbf{S}_1 \mathbf{H}_1$ and $\tilde{\mathbf{M}}_2 = \mathbf{S}_2$ have polar factors $\mathbf{S}_1, \mathbf{S}_2$, and $\tilde{\mathbf{M}}_t = \bar{\mathbf{M}}^{(-1)^t}$ for $t \geq 4$ (since $\nu(1 + 2\mu) = 1$). The one nontrivial step is $t = 3$: with $\mathbf{H}_3 := \bar{\mathbf{D}}^- \tilde{\mathbf{M}}_3$ (so $\tilde{\mathbf{M}}_3 = \bar{\mathbf{D}}^- \mathbf{H}_3$, the reflection being an involution), the stated T is exactly the value making $\mathbf{H}_3$ symmetric, and $\mathbf{H}_3 \succ 0$ for all $\mu \in (0, 1)$: under $\mu = \frac{s}{1+s}$ ($s > 0$) the numerators of its two leading minors are polynomials in s with nonnegative coefficients. Hence $\text{polar}(\tilde{\mathbf{M}}_3) = \bar{\mathbf{D}}^-$, completing (34).




Figure 4: Momentum does not prevent the divergence of EF21-SignMuon. For each momentum coefficient μ and variant, EF21-SignMuon is run on the corresponding instance of Theorem 4 and $f(\mathbf{X}_t) - f(\mathbf{X}_0)$ is plotted; *left*: standard momentum, *right*: Nesterov. Every setting diverges at the common rate $\frac{49}{480}$ (dotted). Subtracting $f(\mathbf{X}_0)$ removes the only genuinely μ -dependent offset (the field constant $A(\mu)$ scales a bounded periodic term); what remains is a bounded transient, largest as $\mu \rightarrow 1$, on top of the shared linear divergence.

The function delivers these gradients. It remains to verify $\nabla \tilde{f}(\tilde{\mathbf{X}}_{t-1}) = \hat{\mathbf{G}}_t$ for $t \leq 3$ and $= \mathbf{G}^{(-1)^t}$ for $t \geq 4$. By Lemma 2 the iterates $\tilde{\mathbf{X}}_0, \tilde{\mathbf{X}}_1, \tilde{\mathbf{X}}_2$ are exactly the centers $\mathbf{Z}_1, \mathbf{Z}_2, \mathbf{Z}_3$, where $\nabla \tilde{f} = \hat{\mathbf{G}}_{1,2,3}$ by construction. The three balls are disjoint ($\|\mathbf{Z}_j - \mathbf{Z}_k\|_F \geq \frac{7}{10} > 2r$), and every later iterate has $(1, 2)$ -entry $\geq \frac{131}{200}$ while the centers have it ≤ 0 , so no ball is re-entered. For $t \geq 4$ the query lies in the field, where

$$\nabla g(\mathbf{W}) = \begin{pmatrix} 0 & A\psi_1(W_{12}) \\ A\psi_2(W_{21}) & -\gamma \end{pmatrix}.$$

The period shift $\tilde{\mathbf{X}}_{t+2} - \tilde{\mathbf{X}}_t = -(\mathbf{d}_A + \mathbf{d}_B)$ advances W_{12} by $+p_1$ and W_{21} by $-p_2$ (one full period each), so the off-diagonal coordinates keep the residues ρ_i^+ at odd indices and ρ_i^- at even indices; there $\psi_i = \pm 1$, giving $\nabla g = \mathbf{G}^{(-1)^t}$. ■

Proof of Theorem 4. By Lemma 3 the normalized run produces the targets (34), so by Lemma 2 its estimator locks onto the wrong-sign cycle and $\tilde{\mathbf{X}}_{t+2} - \tilde{\mathbf{X}}_t$ is a constant shift. Along it Φ_1, Φ_2 return to their values and the corrections b_k vanish, so only the linear term acts: $\tilde{f}(\tilde{\mathbf{X}}_{t+2}) - \tilde{f}(\tilde{\mathbf{X}}_t) = -\gamma(-\frac{7}{20}) = \frac{49}{240} > 0$. By Lemma 1, f then obeys (12) with $c = \frac{49}{240L}$. As $(L, \eta, \mu, \text{variant})$ were arbitrary, no rule $\eta = \eta(L, \mu)$ can prevent divergence. ■

Remark 1 (Boundedness below) Only the linear term $-\gamma W_{22}$ makes $\tilde{f}$ unbounded below, and only as $W_{22} \rightarrow +\infty$, a region the iterates never enter, since $(\tilde{\mathbf{X}}_t)_{22} \leq \frac{7}{10}$ throughout (it decreases after the transient). Replacing $-\gamma W_{22}$ by any C^∞ function that agrees with it on $\{W_{22} \leq 1\}$ and is constant on $\{W_{22} \geq 2\}$ therefore leaves the whole trajectory — and (12) — unchanged while making $\tilde{f}$ bounded below (Assumption 1); the theorem is stated with this modification in force.

Remark 2 (Verification) The construction is checked in two independent ways: symbolically, in exact rational arithmetic, and numerically, by running the float64 reference implementation of Algorithm 3 on the assembled $\tilde{f}$. The right panel of Figure 1 confirms that at $\mu = 0$ EF21-SignMuon is the only one of the eight methods that diverges, the others (SignMuon, MuonUSign, MuonSign, EF21-MuonUSign, EF21-MuonSign, SignSGD, Muon) staying bounded; Figure 4 confirms that EF21-SignMuon diverges at the exact rate $\frac{49}{480}$ for every $\mu \in \{0, \frac{1}{2}, 0.9, 0.95, 0.99\}$ under both standard and Nesterov momentum, as the reduction predicts (code/counterexamples/problems.py, code/counterexamples/plot_ef21_momentum.py).

A.9 Convergence of EF21-MuonUSign and EF21-MuonSign

We do not analyse the error-feedback methods from scratch. EF21-MuonUSign and EF21-MuonSign are *exact instances* of EF21-Muon (Gruntkowska et al. 2025, Algorithm 3), already analysed in the layer-wise, stochastic, federated setting. Three things must be checked before its guarantees transfer: our step is their LMO step, our loop is their loop (Proposition 2), and our messages come from contractive compressors (Lemma 4). Only the last is non-trivial. Table 4 is the change of variables.

Notation and constants. For the layer tuple $\mathbf{X} = [\mathbf{X}_1, \dots, \mathbf{X}_p]$, $\mathbf{X}_i \in \mathbb{R}^{m_i \times n_i}$, of the Problem Statement write $d_i := m_i n_i$, $r_i := \min(m_i, n_i)$, $d_{\max} := \max_i d_i$; a second subscript selects a layer $(\mathbf{X}_{t,i}, \mathbf{G}_{t,i})$. We use $\|\mathbf{Y}\|_{2 \rightarrow 2} \leq \|\mathbf{Y}\|_F \leq \|\mathbf{Y}\|_* \leq \sqrt{\text{rank } \mathbf{Y}} \|\mathbf{Y}\|_F$. Smoothness constants: L_i for f and $L_{i,j}$ for f_j in Assumption 2, with $\tilde{L}_i^2 := \frac{1}{N} \sum_j L_{i,j}^2$ and $L := \max_i L_i$; in the (L^0, L^1) form the pairs are again per layer for f and per layer and client for f_j , with $L_{i,\max}^1 := \max_j L_{i,j}^1$.

Assumption 3 (Stochastic gradient) Each client’s stochastic gradient is unbiased, $\mathbb{E}_\xi[\nabla f_j(\mathbf{X}; \xi)] = \nabla f_j(\mathbf{X})$, with bounded variance $\mathbb{E}_\xi \|\nabla f_j(\mathbf{X}; \xi) - \nabla f_j(\mathbf{X})\|_*^2 \leq \sigma^2$.

Assumptions 1–3 are Assumptions 1–2 and 6–10 of Gruntkowska et al. (2025) with the layer norms taken spectral; our variance bound is stated in the nuclear norm and implies theirs via $\|\cdot\|_F \leq \|\cdot\|_*$. The clause $f_j \geq f_j^*$ of Assumption 1 is needed only for Corollary 2.

Main result

Theorem 5 (Convergence of the EF21 methods) Run the federated Algorithm 9 with the EF21 uplink and EMA momentum $\mu \in [0, 1)$. Then:

- (i) (smooth; both methods) under Assumptions 1–3, with the sharp learning rate $\eta_{t,i} = \gamma_i \|\mathbf{G}_{t,i}\|_*$ and tuned (γ_i, μ) , both reach $\frac{1}{T} \sum_{t < T} \mathbb{E} \|\nabla f(\mathbf{X}_t)\|_*^2 = \mathcal{O}(T^{-1/2})$ (Corollary 1);
- (ii) (generalized smooth; uplink only) under (L^0, L^1) -smoothness, EF21-MuonUSign with a plain constant learning rate reaches $\min_{t \leq T} \sum_i \mathbb{E} \|\nabla_i f(\mathbf{X}_t)\|_* = \mathcal{O}(T^{-1/4})$ (Corollary 2).

Both statements are written for a per-layer constant common to all layers ($\gamma_i \equiv \gamma$, $\eta_i \equiv \eta$); for unequal constants the left-hand sides carry the step-size weights of Corollaries 1–2. The majority-vote placements (Theorems 1–3) and EF21-SignMuon (Theorem 4) admit no such guarantee.

Part (i) is the rate announced in the main text (via $\min_t \leq$ average); the centralized Algorithms 6–7, and hence $\mathbf{X}_t$ in (i), are the case $N = 1$.

The reduction

The step is their LMO step. For $\mathbf{G} = \mathbf{U}\Sigma\mathbf{V}^\top$ the framework’s oracle over the spectral ball of radius τ is $\text{lmo}(\mathbf{G}) = \mathbf{X} - \tau\mathbf{U}\mathbf{V}^\top$, which is our server step with $\tau = \eta_{t,i}$, since $\mathbf{D}_{t,i} = -A(\mathbf{G}_{t,i}) = \mathbf{U}_{t,i}\mathbf{V}_{t,i}^\top$:

$$\mathbf{X}_{t,i} = \mathbf{X}_{t-1,i} - \eta_{t,i} \mathbf{D}_{t,i} = \text{lmo}_{\mathcal{B}(\mathbf{X}_{t-1,i}, \eta_{t,i})}(\mathbf{G}_{t,i}). \quad (43)$$

Their “sharp” step $\mathbf{X} - \gamma \mathbf{G}^\sharp$ uses $\mathbf{G}^\sharp = \|\mathbf{G}\|_* \mathbf{U}\mathbf{V}^\top$, so a constant γ_i is the schedule $\eta_{t,i} = \gamma_i \|\mathbf{G}_{t,i}\|_*$ and a constant $\eta_{t,i}$ is the plain Muon rate: both are learning-rate choices, not algorithmic changes. The spectral norm-equivalence constants are $\underline{\rho}_i = 1$, $\bar{\rho}_i = \sqrt{r_i}$. At rank-deficient $\mathbf{G}$ the LMO is non-unique, but any selection works: the analysis uses only $\langle \mathbf{G}, \text{lmo}(\mathbf{G}) \rangle = -\tau \|\mathbf{G}\|_*$ and $\|\text{lmo}(\mathbf{G})\|_{2 \rightarrow 2} \leq \tau$, with $\mathbf{G} = \mathbf{0}$ read as the zero step ($\mathbf{0}^\sharp = \mathbf{0}$).

The momentum is their momentum. Algorithm 9 uses $\mathbf{M}_t = \mu \mathbf{M}_{t-1} + (1 - \mu) \mathbf{G}_t$, the framework’s momentum with $\beta = 1 - \mu$. From zero initialization the heavy-ball form of (6) differs only by the constant factor $1/(1 - \mu)$ on the momentum stream; the EF21 recursion is positively homogeneous and the Muon LMO scale-invariant, so that factor leaves the iterates unchanged under a constant $\eta_{t,i}$ and is absorbed into γ_i under the sharp schedule. (The Nesterov branch is a different filter; see the end of this appendix.)

Proposition 2 (Exact instance) Fix μ , a learning-rate schedule, and the LMO selection above. Started from $\mathbf{M}_0^{(j)} = \mathbf{g}_0^{(j)} = \mathbf{G}_0 = \mathbf{0}$, $\mathbf{W}_0 = \mathbf{X}_0$, Algorithm 9 with the EF21 uplink and either downlink mode ($\mathcal{C}^\downarrow \in \{\text{exact}, \text{EF21-P}\}$) produces the same trajectory as Algorithm 3 of Gruntkowska et al. (2025) with spectral norms, scaled-sign worker compressors, identity/scaled-sign server compressor, $\beta = 1 - \mu$, and radii $t_i^k = \eta_{k,i}$ – up to a one-step index shift $X^{t+1} = \mathbf{X}_t$.

Proof The loops differ only in where the round is cut: they order it *step* $\rightarrow$ *downlink* $\rightarrow$ *gradient* $\rightarrow$ *uplink*, we order it *downlink* $\rightarrow$ *gradient* $\rightarrow$ *uplink* $\rightarrow$ *step*. Their iteration $k = 0$ is vacuous under our initialization: $\mathbf{G}_0 = \mathbf{0}$ gives $X^1 = X^0 = \mathbf{X}_0$ and a zero downlink residual, so $W^1 = \mathbf{X}_0$. Thereafter their iteration $k = t$ performs our round t verbatim – same momentum, same compressed residual, same LMO step (43) – giving $X^{t+1} = \mathbf{X}_t$, $W^{t+1} = \mathbf{W}_t$ by induction. Running their method for $K = T + 1$ iterations therefore yields $\{\mathbf{X}_0, \mathbf{X}_0, \mathbf{X}_1, \dots, \mathbf{X}_{T-1}\}$, and any average or minimum over these equals ours up to one duplicated nonnegative term. ■

Zero initialization also makes their initial-error constant Ψ^0 explicit: the $\|\mathbf{M}_0 - \mathbf{g}_0\|$ term vanishes and the gradient-deviation terms become $\|\nabla_i f(\mathbf{X}_0)\|$. The β^{-1} surviving in Ψ^0 enters only through the Ψ^0/T term, which $T^{-1/2}$ dominates.

	This paper	EF21-Muon
clients / rounds	N, T	$n, K = T + 1$
iterate	$\mathbf{X}_t$	X^{t+1}
momentum	μ	$1 - \beta$
learning rate	$\eta_{t,i}$	radius t_i^t
norm equivalence	$1, \sqrt{r_i}$	$\rho_i, \bar{\rho}_i$
uplink compr.	scaled sign	$\mathbb{B}_2(\alpha_D)$
downlink compr.	exact / sign	$\mathcal{I} / \mathbb{B}_2(\alpha_P)^\dagger$
compression α	$1/d_{\max}$	α_D

Table 4: Change of variables from our notation to that of Gruntkowska et al. (2025). Layer norms $\|\cdot\|_{(i)}, \|\cdot\|_{(i)\star}$ are read as $\|\cdot\|_{2 \rightarrow 2}, \|\cdot\|_*$ and smoothness constants $L_i^0, \tilde{L}_i^0$ as $L_i, \tilde{L}_i$; the index shift is Proposition 2. [†]Their Theorem 19 as printed asks for a server compressor in $\mathbb{B}(\alpha_P)$, contractive in the *layer* norm; the Euclidean class $\mathbb{B}_2(\alpha_P)$ that the scaled sign belongs to is licensed only by their Remark 23, at the $\bar{\rho}_i^2$ price charged in Corollary 1 and Remark 4.

The one real check: the scaled sign is a compressor The framework needs every transmitted message to come from a *contractive compressor*: a map with $\mathbb{E}\|\mathcal{C}(\mathbf{Y}) - \mathbf{Y}\|^2 \leq (1 - \alpha)\|\mathbf{Y}\|^2$ for some $\alpha \in (0, 1]$ (Gruntkowska et al. 2025, Def. 1). This is exactly what fails for a bare sign and holds once it is scaled.

Lemma 4 (Contractivity of the scaled sign) *For every $\mathbf{Y} \in \mathbb{R}^{m \times n}$ ($d = mn$), the scaled sign $\mathcal{C}(\mathbf{Y}) = \text{mean}(|\mathbf{Y}|) \text{sign}(\mathbf{Y})$, with exact zeros resolved to ± 1 as in Section 4, satisfies*

$$\|\mathcal{C}(\mathbf{Y}) - \mathbf{Y}\|_F^2 = \|\mathbf{Y}\|_F^2 - \frac{1}{d}\|\mathbf{Y}\|_1^2 \leq (1 - \frac{1}{d})\|\mathbf{Y}\|_F^2, \quad (44)$$

so $\mathcal{C}$ is Euclidean-contractive with $\alpha = 1/d$. The identity holds for every draw of the random signs, not merely in expectation, and gives the exact contraction $\alpha(\mathbf{Y}) = \|\mathbf{Y}\|_1^2 / (d\|\mathbf{Y}\|_F^2)$, which is $\Theta(1)$ for dense $\mathbf{Y}$ (e.g. $\rightarrow 2/\pi$ for i.i.d. Gaussian entries) and equals $1/d$ exactly at any 1-sparse $\mathbf{Y}$.

Proof Write $c := \|\mathbf{Y}\|_1/d$ and $s_{kl} = \pm 1$ for the transmitted signs. A nonzero entry contributes $(|Y_{kl}| - c)^2$ and a zero entry contributes $(c s_{kl})^2 = c^2$ whichever sign was drawn, so $\|\mathcal{C}(\mathbf{Y}) - \mathbf{Y}\|_F^2 = \|\mathbf{Y}\|_F^2 - 2c\|\mathbf{Y}\|_1 + c^2\|\mathbf{Y}\|_0 + c^2(d - \|\mathbf{Y}\|_0) = \|\mathbf{Y}\|_F^2 - 2c\|\mathbf{Y}\|_1 + dc^2$, which is (44) on substituting c . The bound then follows from $\|\mathbf{Y}\|_1 \geq \|\mathbf{Y}\|_F$, with equality exactly at the 1-sparse $\mathbf{Y}$; the Gaussian limit uses $\mathbb{E}|Y_{kl}| = \sqrt{2/\pi} \sigma$. ■

The $\|\mathbf{Y}\|_0$ terms cancel only under the randomized sign; otherwise the identity is sparsity-dependent and $1/d$ becomes an unattained infimum.

The scaling is what carries the lemma. A bare sign contracts for no α at all: as $\|\mathbf{Y}\|_F \rightarrow 0$ on a fixed support, $\|\text{sign}(\mathbf{Y}) - \mathbf{Y}\|_F \rightarrow \sqrt{\|\mathbf{Y}\|_0}$. That is the line between our divergent and convergent methods: the majority-vote methods transmit unscaled signs of full quantities, the EF21 variants the scaled sign of a *residual*, at the cost of one extra scalar per layer per round. Per layer the uplink scaled sign lies in $\mathbb{B}_2(1/d_i) \subseteq \mathbb{B}_2(\alpha)$ with $\alpha := 1/d_{\max}$; the downlink is exact for EF21-MuonUSign ($\alpha_P = 1$) and the same scaled sign for EF21-MuonSign.

Transferred guarantees All requirements hold, so the framework’s theorems apply through Table 4. We state the rates and stepsize rules; the explicit non-asymptotic bounds are Gruntkowska et al. (2025), Theorem 19 (smooth) and Theorem 24 ((L^0, L^1)), at these constants.

Corollary 1 (Smooth case; both methods) *Let Assumptions 1–3 hold. Run Algorithm 9 with the EF21 uplink, EMA momentum, and $\eta_{t,i} = \gamma_i \|\mathbf{G}_{t,i}\|_*$ with any γ_i below the per-layer threshold of Gruntkowska et al. (2025, Thm. 19) under Table 4. Then, applying the momentum tuning of Gruntkowska et al. (2025, Cor. 2) per layer (their Corollaries 1–2 state it for the layer-wise initialization and for $p = 1$ respectively; the combination is routine),*

$$\frac{1}{T} \sum_{t < T} \sum_{i=1}^p w_i \mathbb{E} \|\nabla_i f(\mathbf{X}_t)\|_*^2 = \mathcal{O}(T^{-1/2}),$$

with $w_i := \gamma_i / (\frac{1}{p} \sum_l \gamma_l)$; for a common γ_i all $w_i = 1$ and the left side is $\frac{1}{T} \sum_{t < T} \mathbb{E} \|\nabla f(\mathbf{X}_t)\|_*^2$.

Proof By Proposition 2 the run is an instance of Algorithm 3 with $K = T + 1$, and by Lemma 4 its compressors satisfy $\alpha_D = \alpha$ and $\alpha_P \in \{1, \alpha\}$ (EF21-MuonSign’s Euclidean downlink is admissible by their Remark 23, which multiplies the α_P -terms of the threshold constant ζ_i by $\bar{\rho}_i^2 = r_i$). Substituting $\rho_i = 1, \bar{\rho}_i = \sqrt{r_i}$ into Gruntkowska et al. (2025, Thm. 19) gives the threshold and the rate; the duplicated $\mathbf{X}_0$ -term costs a factor $\frac{T+1}{T}$. ■

Since $\gamma_i \lesssim \zeta_i^{-1/2}$, the threshold shrinks polynomially in the layer dimension – through $\bar{\rho}_i = \sqrt{r_i}$ and the uplink $\alpha = 1/d_{\max}$ – and for EF21-MuonSign by a further $\sqrt{r_i}$ from the compressed downlink. That extra factor is structural: the scaled sign is spectrally contractive for no parameter at all (Remark 4).

Corollary 2 ((L^0, L^1) case; EF21-MuonUSign) *Let Assumption 2 hold in its (L^0, L^1) form. Run EF21-MuonUSign (exact downlink) with $S := T + 2$, momentum $\mu = 1 - S^{-1/2}$, and the constant per-layer rate $\eta_{t,i} \equiv \eta_i/S^{3/4}$ for any $\eta_i \leq 1$ with $\eta_i^2 \sqrt{r_i} (L_{i,\max}^1)^2 = \mathcal{O}(1)$.¹ Then*

$$\min_{0 \leq t \leq T} \sum_{i=1}^p v_i \mathbb{E} \|\nabla_i f(\mathbf{X}_t)\|_* = \mathcal{O}(T^{-1/4}), \quad v_i := \frac{\eta_i}{\frac{1}{p} \sum_i \eta_i}.$$

Proof Their Theorem 24 requires the identity server compressor, i.e. the exact downlink of EF21-MuonUSign (so EF21-MuonSign is excluded). Applying it with $K = T + 1$, $\beta = S^{-1/2}$ and Table 4 gives the schedule and the rate. ■

Under plain smoothness ($L^1 = 0$) every constraint above collapses to $\eta_i \leq 1$. The *constant*-learning-rate EF21-MuonUSign we actually run therefore already converges at $\mathcal{O}(T^{-1/4})$; the sharp schedule yields only the faster $\mathcal{O}(T^{-1/2})$ in squared norm.

Scope The reduction covers the two error-feedback methods and no others, which matches our negative results. The majority-vote methods send unscaled signs and fall outside the framework. EF21-SignMuon compresses the LMO *output* rather than the gradient, so it tracks the non-Lipschitz polar factor and the momentum-tracking step breaks (Theorem 4). EF21-MuonSign gets the smooth guarantee but not the (L^0, L^1) one, whose theory assumes an uncompressed downlink.

The remaining gap is the Nesterov branch, which our language-model runs use (Appendix A.16): with $\beta := 1 - \mu$ it steers by $\tilde{\mathbf{M}}_t = (1 - \beta)\mathbf{M}_t + \beta\mathbf{G}_t$ rather than by the buffer $\mathbf{M}_t$, a two-tap filter of the gradients where the framework wants a first-order recursion. The discrepancy is small and explicit: writing $\mathbf{n}_t := \mathbf{G}_t - \nabla_i f(\mathbf{X}_t)$, we have $\nabla_i f - \tilde{\mathbf{M}}_t = (1 - \beta)(\nabla_i f - \mathbf{M}_t) - \beta \mathbf{n}_t$, and since $\mathbb{E}\langle \nabla_i f - \mathbf{M}_t, \mathbf{n}_t \rangle = -\beta \mathbb{E}\|\mathbf{n}_t\|_2^2$,

$$\mathbb{E}\|\nabla_i f - \tilde{\mathbf{M}}_t\|_2^2 \leq (1 - \beta)^2 \mathbb{E}\|\nabla_i f - \mathbf{M}_t\|_2^2 + 3\beta^2 \sigma_i^2.$$

The first term is exactly the deviation Gruntkowska et al. (2025, Thm. 19) already tracks, contracted rather than enlarged; the second is dominated by the $\beta\sigma_i^2$ term already in its bound. Nesterov should therefore degrade the constants rather than the rate. We state this as an expectation, not as a corollary, since the tracking recursion for $\|\tilde{\mathbf{M}}_{t+1} - \tilde{\mathbf{M}}_t\|$ would have to be redone as well.

Remark 3 (The cost of one bit) *The uplink $\alpha = 1/d_{\max}$ is what makes the threshold of Corollary 1 shrink with the dimension – the worst-case cost of one-bit messages, as for Top-1 compressors in Euclidean EF21 (Richtárik, Sokolov, and Fatkhullin 2021). On the uplink it is worst-case only: it needs an all-but-one-coordinate-negligible residual, whereas the momentum residual is dense with $\alpha(\Delta) = \Theta(1)$ (Lemma 4), and the framework is stated to extend straightforwardly to iteration-dependent α (Gruntkowska et al. 2025, Rem. 12).*

The downlink of EF21-MuonSign does not inherit this. *Its residual is not a gradient difference refreshed by fresh stochasticity, but the output of the compressor’s own recursion*

$$\Delta_{t+1}^\downarrow = \Delta_t^\downarrow - \eta_{t+1} \mathbf{D}_{t+1} - \text{mean} |\Delta_t^\downarrow| \text{sign}(\Delta_t^\downarrow),$$

in which every coordinate is corrected by the same amount. Coordinates driven harder than that mean are never caught while the bulk holds the mean down, so the residual concentrates – and concentration is what drives α down. We observe it: $\alpha(\Delta^\downarrow)$ falls to 1.2×10^{-4} on the layers built from a zero initialization, nearly four orders of magnitude below its own uplink on the same layers (Section 5.3). That is still far above the $1/d = 4.2 \times 10^{-7}$ floor, so the dimension dependence of Corollary 1 is not attained; what is lost is the $\Theta(1)$ contraction that makes it harmless upstream.

Remark 4 (Why the sharp route is closed) *Corollary 1 reaches EF21-MuonSign only through the $\tilde{\rho}_i^2$ -penalized branch of Gruntkowska et al. (2025, Rem. 23), and this is forced. The sharp branch asks for a server compressor in $\mathbb{B}(\alpha_P)$, contractive in the layer norm, and the scaled sign is in no such class for any $\alpha_P > 0$. Take $\mathbf{Y}_\delta = (1 - \delta)\mathbf{I}_n + \delta\mathbf{J}_n$, with $\mathbf{J}_n$ all ones, $0 < \delta < 1$ and $n \geq 2$. Every entry is positive, so $\text{sign}(\mathbf{Y}_\delta) = \mathbf{J}_n$ and $\text{mean} |\mathbf{Y}_\delta| = (1 + (n - 1)\delta)/n$, whence*

$$\mathcal{C}(\mathbf{Y}_\delta) - \mathbf{Y}_\delta = (1 - \delta)(\frac{1}{n}\mathbf{J}_n - \mathbf{I}_n),$$

with eigenvalues 0 and $-(1 - \delta)$. So $\|\mathcal{C}(\mathbf{Y}_\delta) - \mathbf{Y}_\delta\|_{2 \rightarrow 2} = 1 - \delta$ against $\|\mathbf{Y}_\delta\|_{2 \rightarrow 2} = 1 + (n - 1)\delta$, a ratio tending to 1 as $\delta \downarrow 0$: no $\alpha_P > 0$ survives, on any layer of rank above one. The framework’s sufficient condition is unattainable for the same reason – by the norm-equivalence argument of Gruntkowska et al. (2025, App. D) a compressor in $\mathbb{B}_2(\alpha)$ is certified to lie in $\mathbb{B}(\alpha_P)$ only if $\alpha > 1 - 1/r_i$, i.e. $\alpha > 0.9987$ for our 768×3072 matrices, against an isotropic $2/\pi$. The factor $\tilde{\rho}_i^2 = r_i$ in ζ_i is therefore not removable by a sharper analysis of this compressor, only by changing it – to random dropout ($\alpha_P = p$) or a Top-K SVD compressor ($\alpha_P = 1 - \sigma_{K+1}^2/\sigma_1^2$), both layer-norm contractive at a comparable budget (Gruntkowska et al. 2025, App. D), and neither strictly one-bit.

¹These are the binding conditions of Gruntkowska et al. (2025, Thm. 24); the two remaining ones relax as T grows. Their printed second condition is tighter than the display its own proof establishes by a factor $K + 1$; we quote the latter.

Experiment	GPU	CPU	RAM (GB)	OS	Python	PyTorch / CUDA
Synthetic quadratic <i>to be filled: the centralized, federated and nanoGPT rows, from python3 -m common.hardware --scan results --latex</i>	NVIDIA RTX A4000, 15.6 GB	AMD EPYC 7543 32-Core	472.2	Linux 6.12.26	3.12.13	2.7.0+cu128 / 12.8

Table 5: Computing infrastructure, per experiment. Generated from the per-run hardware records rather than written by hand; where one experiment was run on more than one machine, it contributes one row per machine.

Remark 5 (From Muon to Gluon) Only $(\rho_i, \bar{\rho}_i) = (1, \sqrt{r_i})$ is spectral-norm-specific: Lemma 4 is Euclidean and the framework’s theorems hold for arbitrary layer norms. A new geometry has to supply only its LMO and its norm-equivalence pair; both corollaries then hold with those constants in place of $(1, \sqrt{r_i})$, giving EF21-GluonUSign and EF21-GluonSign for the Gluon setting (Riabini et al. 2025). Admissible geometries abound $-\ell_1 \rightarrow \ell_\infty$ for embeddings (Pethick et al. 2025), the Schatten- p norms (Cesista 2025), the Ky Fan duals of the Fanion family (Kravatskiy et al. 2025) – and, by the closure property of the last work, conic combinations of them, with $\bar{\rho}_i \leq (\sum_j \alpha_j / \bar{\rho}_i^{(j)})^{-1}$ for the mixture $\|\mathbf{X}_i\| = \sum_j \alpha_j \|\mathbf{X}_i\|_{(j)}$. Convergence is thus a property of error feedback plus scaled-sign compression, not of the spectral geometry. The two ways to bring a sign into a Muon step stay cleanly apart: inside the oracle it changes the norm and the guarantee follows the norm; outside it, it is a compressor and the guarantee has to come from error feedback.

We assume the exact spectral LMO, as do all analyses of Muon-type methods (Li and Hong 2025; Kovalev 2025; Riabini et al. 2025; Gruntkowska et al. 2025); in practice it is the five-step iteration of Algorithm 1 (Amsel et al. 2026; Grishina, Smirnov, and Rakhuba 2025), with vector parameters and the last layer trained by AdamW as usual (Jordan et al. 2024). That substitution is not covered by the reduction either, but it is the mildest of the gaps: Shulgin et al. (2025) analyse the inexact Muon update directly and find the method tolerant of oracle error, which is consistent with our runs: the five-step approximation reproduces record #40 to within seed noise (Table 3).

A.10 Reproducibility Details

Computing infrastructure. The experiments in this paper were not all run on the same machine, so Table 5 reports the hardware per experiment rather than as a single sentence. Each row is generated from the record every run stamps into its own output at the moment it runs (`python3 -m common.hardware --scan results --latex`), so the table describes the machines the reported numbers actually came from and not the machine that happened to typeset the paper. Exact package versions are pinned in `code/requirements.txt`.

Randomness and seeds. Seeding goes through a `seed_everything` routine that seeds the Python random module, NumPy, and PyTorch (including all CUDA devices) and enables deterministic cuDNN kernels (`cudnn.deterministic=True, cudnn.benchmark=False`). The federated experiment of Table 2 reports five seeds (0–4) per method and the centralized experiment of Table 1 three (0–2), each quoted as mean $\pm$ one sample standard deviation across seeds; the nanoGPT runs of Table 3 and the weight-decay ablations use a single fixed seed (default 0), and Table 3 states the seed noise of the upstream reference so that the resolvable differences there are explicit. The synthetic study of Appendix A.11 averages over three draws of the problem itself (seeds 1337–1339) at a fixed $\mathbf{X}_0$ (seed 42), since every claim it makes is about a *random* instance and one draw cannot support one — the alignment distribution least of all. The distinction matters for reading the tables: a difference smaller than the seed spread is not a result, and only the centralized and federated tables measure that spread. Learning-rate selection is performed once, at seed 0, on a validation split disjoint from the test set, and the selected rate is then reused unchanged for every seed.

Step-size schedules. Each experiment inherits the schedule conventional to its domain, and none of them is the constant rate our rates are proved for. The ResNet runs anneal cosinally to zero, the standard for this architecture and the premise of every accuracy we can be compared against; the nanoGPT runs keep record #40’s stable-then-decay schedule, flat for the first 55% of steps and linear to $0.1\eta_0$ thereafter (Appendix A.16), because altering it would forfeit the reproduction that validates our port. The discrepancy is deliberate: matching the analysed step size would sacrifice comparability on both benchmarks and close only one of several gaps between the theory and the runs, the others being Newton–Schulz in place of an exact oracle, momentum, and normalization layers. One measurement is exempt: the growth-exponent diagnostic of Appendix A.17, which is run at a constant rate because under a decaying one the accumulated update saturates and the fit reports the schedule instead of the alignment.

Learning-rate selection. The only tuned hyperparameter is η_0 . Every method with a norm-fixed step (the eight sign- and LMO-family rules of Appendix A.17, SignSGD included) is tuned and reported under one per-layer rule, the unit-gain rule (8), so that η_0 means the same thing across them, namely the per-step RMS gain, and no comparison within the families is confounded by the scaling convention. SGD and Adam have no norm-fixed step for the rule to act on and are run as practitioners run them, with one global rate. Because (8) is a heuristic rather than a theorem, the sign family is additionally re-tuned under the two competing conventions: one global rate, and μP ’s $1/\text{fan-in}$. Appendix A.17 reports whether the ranking moves. Momentum is

fixed at 0.9 and weight decay at 0 for the primary tables, the setting Mishra, Trivedi, and Kumar (2026)’s own sweep selects; the regularized case is an ablation (Appendix A.13 centralized, and below for the federated study). The auxiliary group — biases, normalization parameters, the classifier head — is AdamW at a fixed 10^{-3} for every method, so the matrix rule is the only thing that varies.

In the centralized study, selection uses a fixed 45k/5k train/validation partition and validation accuracy alone, averaged over the last five epochs rather than read off a single one; **the test set is never consulted during tuning**. Each method receives the same number of configurations, drawn from a 1–2–5 lattice (three points per decade), so that tuned rates are exactly reproducible from the tables and every method searches the same grid. An optimum at an endpoint is treated as a failure rather than a result: the grid is widened along the lattice and the method re-run, up to four times. The selected η_0 is then retrained on the full 50k training set for 75 epochs under a cosine schedule, at three seeds, and we report the mean and standard deviation of the test accuracy over the last five epochs. Differences smaller than the seed spread are not claimed as results.

Tuning the federated study. Comparing sign placements is informative only if no placement is handicapped by its step size, so every method receives the same tuning budget: a five-point 1–2–5 lattice in η_0 , ranked at a 400-round proxy horizon on a 5k validation split held out of the 50k *before* the client partition, with the grid widened and the method re-tuned whenever an optimum occurred at an endpoint. The reported runs then use the full 50k at the selected rate, so no test image is ever scored during selection. Two assumptions this protocol makes are checked rather than asserted: that the short proxy ranks rates the same way the full horizon does (re-running the top two rates of SignMuon and EF21-MuonSign at 2000 rounds returns the same winner in both cases), and that the shape dependence of the step is carried by the per-layer multiplier rather than by η_0 . The second assumption is borne out: seven of the nine methods carrying a per-layer multiplier (the eight of Appendix A.17 plus the server-side-LMO Muon control) select the identical $\eta_0 = 0.05$ across both families, the remaining two (Muon at 0.1, SignSGD at 0.02) selecting a value one lattice step away. Weight decay is 0 in the reported table, matching the setting the theorems analyse; switching on a decoupled 5×10^{-4} moves the top three methods by at most 0.32 points and reorders nothing.

Accuracy and the threshold column. Alongside final accuracy we report the number of epochs (rounds, in the federated tables) to reach a fixed test accuracy. The two measure different things: with the methods spanning about a point and a half at 75 epochs (Table 11), final accuracy is close to the noise floor, whereas a threshold crossing on a monotonically rising curve separates the methods by factors rather than by tenths of a point, and is the analogue of the “steps to 3.35” column of Table 3.

Conventions with numerical consequences. Three implementation conventions can move reported numbers and are recorded here. (i) The Muon LMO is computed in `bfloat16` (five Newton–Schulz steps) unless stated otherwise; for the methods that sign the LMO *output*, entries of `polar(.)` near zero can flip at this precision, so their trajectories carry a precision-dependent component (`-lmo-dtype float32` is available). (ii) In the federated runs, BatchNorm running statistics are never updated: local models are discarded each round and BN runs in inference mode during gradient accumulation, so the statistics stay at their initialization for the entire run, in training and evaluation alike. The result is a fixed normalization with learnable affine parameters, self-consistent between train and test, applied identically to every method. It is also one reason a channel can be inactive across an entire local batch and so contribute an exactly zero row to the momentum. (iii) For EF21-MuonSign, training metrics are logged at the broadcast model $\mathbf{W}$ (where gradients must be evaluated) while validation and test metrics are evaluated at the server model $\mathbf{X}$ of (15), the iterate the guarantee bounds, except where a table states otherwise.

A.11 The smooth convex problem

Before the network experiments we measure, on a deterministic L -smooth convex quadratic, the scalar every guarantee in this paper rests on: the alignment $\rho_t = \langle \nabla F(\mathbf{X}_t), \mathbf{D}_t \rangle / (\|\nabla F(\mathbf{X}_t)\|_F \|\mathbf{D}_t\|_F)$ between the gradient and the step taken. Theorems 1–3 construct instances that drive it negative; on random instances all three methods they cover keep $\rho_t \geq 0.146$ for every step of a tuned trajectory, so the failure they exhibit is not one random data produces. The one method that does go negative here is EF21-MuonSign, on 0.93% of its steps and only to -0.028 — and that is a method we prove *converges* (Appendix A.9), by a route that does not pass through per-step descent. The same experiment shows what sign compression of an LMO step actually yields: a lower accuracy floor rather than a faster rate. SignMuon’s gradient floor sits a factor 1.74–1.80 below SignSGD’s at every step size the two were run at, while SignSGD reaches the smaller error at the two shortest budgets and loses from $T = 500$ on; the two share $\|\mathbf{S}\|_F$ exactly, so it is the floor, not the step length, that separates them, and it is the floor that a fixed-target iteration count ranks. Section A.12 retains the earlier fixed-target comparison.

Construction. To isolate the effect of matrix structure from stochastic noise and from the complexity of DNN architectures, we use a deterministic L -smooth convex quadratic:

$$F(\mathbf{X}) = \frac{1}{2} \|\mathbf{A}^{1/2} \mathbf{X} \mathbf{B}^{1/2}\|_F^2$$

$$= \frac{1}{2} \langle \mathbf{X}, \mathbf{A} \mathbf{X} \mathbf{B} \rangle \rightarrow \min_{\mathbf{X} \in \mathbb{R}^{m \times n}}, \quad (45)$$

with $\mathbf{A} \in \mathbb{S}_{++}^m$, $\mathbf{B} \in \mathbb{S}_{++}^n$ symmetric and $\mathbf{X}_0$ drawn entrywise from $\mathcal{N}(0, 0.01)$. Eigenvalues are sampled uniformly from $(0, 1)$ in a Haar-random eigenbasis, so the matrices are almost surely positive *definite* and the minimizer is $\mathbf{X}^* = \mathbf{0}$ with $F^* = 0$.

Algorithm	iters	best F	$\min \ \nabla F\ _F$	tuned (η, μ)
SignMuon	364	$6.9 \cdot 10^{-4}$	$2.4 \cdot 10^{-2}$	$(1.0 \cdot 10^{-3}, 0)$
MuonUSign [†]	556	$7.1 \cdot 10^{-4}$	$2.3 \cdot 10^{-2}$	$(1.0 \cdot 10^{-2}, 0.5)$
MuonSign	595	$4.8 \cdot 10^{-4}$	$1.9 \cdot 10^{-2}$	$(6.8 \cdot 10^{-4}, 0.5)$
EF21-SignMuon	401	$5.4 \cdot 10^{-4}$	$2.1 \cdot 10^{-2}$	$(6.8 \cdot 10^{-3}, 0)$
EF21-MuonUSign	521	$5.3 \cdot 10^{-4}$	$1.8 \cdot 10^{-2}$	$(6.8 \cdot 10^{-3}, 0)$
EF21-MuonSign	695	$3.8 \cdot 10^{-4}$	$1.7 \cdot 10^{-2}$	$(4.6 \cdot 10^{-3}, 0)$
Muon	267	$4.7 \cdot 10^{-4}$	$2.0 \cdot 10^{-2}$	$(1.0 \cdot 10^{-2}, 0.5)$
SignSGD	486	$4.3 \cdot 10^{-4}$	$2.2 \cdot 10^{-2}$	$(6.8 \cdot 10^{-4}, 0.5)$
SGD	66	$1.9 \cdot 10^{-8}$	$1.6 \cdot 10^{-6}$	$(2.15, 0.5)$
Adam	85	$9.2 \cdot 10^{-6}$	$6.5 \cdot 10^{-4}$	$(6.8 \cdot 10^{-2}, \text{—})$

Table 6: The fixed-target criterion under the current protocol: fewest iterations to $F \leq 10^{-3}$ within $T_{\max} = 5000$ at $m = n = 100$, averaged over three problem draws, with $(\eta, \mu, \text{schedule})$ tuned on four-decade logarithmic grids. A constant schedule wins for every method. Best F and $\min \|\nabla F\|_F$ are minima over the whole 5000 iterations, not at the crossing, so they measure the floor the method settles into rather than the target it was ranked on. This is the criterion Section A.12 used at $m = n = 500$ on one draw; the iteration counts are not comparable across the two, and the paragraph above is why they should not be read as rates in either. [†] MuonUSign’s rate is the top of its grid, so its 556 is an upper bound.

Two facts about this instance are exact rather than estimated, and both are used below. The Hessian of F is the Kronecker product $\mathbf{B} \otimes \mathbf{A}$, so its eigenvalues are the products $\lambda_i(\mathbf{A})\lambda_j(\mathbf{B})$: the Frobenius smoothness constant is $L = \max_{ij} \lambda_i(\mathbf{A})\lambda_j(\mathbf{B}) \leq 1$ and the strong-convexity constant is $\sigma = \min_{ij} \lambda_i(\mathbf{A})\lambda_j(\mathbf{B}) > 0$. The uniform draw leaves the resulting condition number L/σ uncontrolled (it is near 3.7×10^4 at the $m = n = 100$ every measurement in this subsection uses, and near 2.5×10^5 at the $m = n = 500$ of Section A.12), so where conditioning is the variable we instead use log-spaced spectra with $L = 1$ and L/σ set exactly. And since $\nabla F(\mathbf{X}) = \mathbf{A}\mathbf{X}\mathbf{B}$ in closed form, the gradient can be evaluated at any point without an autograd graph, which is what lets the bidirectional method be scored on its exact model $\mathbf{X}$ while its gradient is taken at the broadcast model $\mathbf{W}$, as its algorithm requires.

What “iterations to a target” measures. The natural criterion — fewest iterations to $F(\mathbf{X}) \leq 10^{-3}$ within $T_{\max} = 5000$, learning rate and momentum tuned per method — turns out not to measure a convergence rate, and reporting it as one is misleading. Every method here except SGD takes a *normalized* step: $\|\text{sign}(\cdot)\|_F = \sqrt{mn}$ and $\|\text{polar}(\cdot)\|_F = \sqrt{r}$ whatever the gradient does. A constant η therefore cannot converge; the iterate settles into a ball of radius $\eta\|\mathbf{S}\|_F$ and F plateaus. Measured directly, the plateau obeys $\|\nabla F\|_\infty \propto \eta$ and $F_\infty \propto \eta^2$, and the iteration count is const/η . The tuner thus returns the largest η whose plateau still fits under the target, and the ranking it produces is a ranking of *accuracy floors*. The two effects do disagree here. Swept over the seven step sizes both methods were run at, SignMuon’s plateau $\|\nabla F\|_\infty$ is 1.74 to 1.80 times below SignSGD’s — a ratio flat in η , as two floors with the same exponent must be — and its plateau in F between 6.7 and 71 times below. Tuned per budget, the ranking inverts at short horizons: SignSGD reaches the smaller $\min_t \|\nabla F\|_F$ at $T = 125$ and $T = 250$ (6.55 and 2.25×10^{-2} , against 7.44 and 2.33×10^{-2}) and the larger one at every budget from 500 on. We therefore report the floor and the rate separately, and read the descent lemma

$$F(\mathbf{X}_{t+1}) \leq F(\mathbf{X}_t) - \eta \langle \nabla F(\mathbf{X}_t), \mathbf{D}_t \rangle + \frac{\eta^2 L}{2} \|\mathbf{D}_t\|_F^2 \quad (46)$$

as the statement that separates them: the second term is the floor, the first is the rate.

Table 6 nevertheless reports the criterion under the current protocol, since it is what Table 9 of the superseded section reports and the two are otherwise not comparable. Read as a ranking of floors it says that of the six sign placements, sign-after the LMO is the cheapest and sign on both channels the dearest, in both the direct and the error-feedback family; that the error-feedback machinery costs 10% on SignMuon and 17% on MuonSign, and appears to save 6% on MuonUSign — though that last comparison is against a censored row and so is not yet a measurement; and that plain Muon beats all six. It also confirms that this problem is the wrong one to argue a matrix method on: SGD reaches the target in 66 iterations and Adam in 85, three to ten times faster than anything with a normalized step, because a quadratic with an exactly known Hessian is the case a scaled gradient step is built for.

Alignment. Equation (46) makes progress contingent on a single scalar, the normalized alignment between the gradient and the step actually taken,

$$\rho_t := \frac{\langle \nabla F(\mathbf{X}_t), \mathbf{D}_t \rangle}{\|\nabla F(\mathbf{X}_t)\|_F \|\mathbf{D}_t\|_F} \in [-1, 1]. \quad (47)$$

Theorems 1–3 are constructions that drive ρ_t negative. Table 7 reports its distribution along the tuned trajectory on random instances, which is the empirical counterpart of those theorems and the one measurement here that is about the methods rather




Figure 5: Trajectories at the optima of Table 6, one curve per method, mean over three problem draws. Every normalized method flattens onto a plateau within a few hundred iterations and stays there for the remaining 4000-odd, which is the behaviour the accuracy-floor reading of the fixed-target criterion predicts and the reason the crossing time is a ranking of floors. SGD, whose step vanishes with the gradient, is the one curve still descending at $T_{\max}$; Adam’s oscillates around its own floor rather than settling onto it. This is the current-protocol counterpart of Figure 8, at $m = n = 100$ rather than 500, and the iteration counts of the two are not comparable.

Algorithm	$\min_t \rho_t$	median ρ_t	mean ρ_t	% of steps with $\rho_t < 0$	closed form	tuned (η, μ)
SignMuon	0.214	0.381	0.399	0.00%	—	$(2.2 \cdot 10^{-4}, 0)$
MuonUSign	0.161	0.357	0.378	0.00%	—	$(3.2 \cdot 10^{-3}, 0)$
MuonSign	0.146	0.362	0.366	0.00%	—	$(2.2 \cdot 10^{-4}, 0)$
EF21-SignMuon	0.330	0.659	0.573	0.00%	—	$(1.5 \cdot 10^{-3}, 0)$
EF21-MuonUSign	0.345	0.558	0.553	0.00%	—	$(1.5 \cdot 10^{-3}, 0)$
EF21-MuonSign	-0.028	0.491	0.419	0.93%	—	$(1.5 \cdot 10^{-3}, 0)$
Muon	0.454	0.666	0.633	0.00%	0.695	$(1.5 \cdot 10^{-3}, 0)$
SignSGD	0.174	0.503	0.499	0.00%	0.794	$(2.2 \cdot 10^{-4}, 0.5)$
SGD	—	—	—	—	1	$(3.2, 0.95^\dagger)$

Table 7: Gradient/step alignment ρ_t of Equation (47) along the tuned trajectory, one row per method, over three problem draws at $m = n = 100$. The closed-form column is evaluated at $\mathbf{X}_0$ without momentum, so it is comparable only to rows whose tuned μ is 0; with momentum the step is built from $\mathbf{M}_t$ rather than the current gradient and ρ_t falls accordingly. The six sign-around-the-LMO methods admit no closed form; SGD’s is 1, and its step is not one the harness can instrument, so its distribution is left empty rather than filled with the constant. Adam is omitted for the same reason, its step being outside the descent lemma. Every method Theorems 1–3 cover stays well clear of zero; the single negative excursion belongs to EF21-MuonSign, which Appendix A.9 proves convergent through the EF21 estimator rather than through per-step descent, so a ρ_t dipping to -0.028 contradicts nothing. [†] SGD’s momentum is the top of its grid.

than about the tuning protocol. Three closed forms anchor it: $\rho = 1$ for SGD, $\rho = \|\mathbf{G}\|_1 / (\|\mathbf{G}\|_F \sqrt{mn})$ for SignSGD, and $\rho = \|\mathbf{G}\|_* / (\|\mathbf{G}\|_F \sqrt{r})$ for Muon. The six sign-around-the-LMO methods admit none, which is the subject of this paper.

Floor, budget and stability. Three further measurements, each testing a quantity the theory predicts in closed form. (i) The floor: the fitted slope of $\log \|\nabla F\|_\infty$ against $\log \eta$, against the 1 that Equation (46) predicts, with coefficient $L\|\mathbf{S}\|_F/2\rho$. Balancing the two terms of (46) gives $\eta\rho\|\nabla F\|_F\|\mathbf{D}\|_F = \eta^2L\|\mathbf{D}\|_F^2/2$. Since SignMuon and SignSGD share $\|\mathbf{S}\|_F = \sqrt{mn}$ exactly, any gap between their floors is attributable to ρ alone. (ii) The budget exponent: tuning $(\eta, \mu, \text{schedule})$ separately at each horizon T and fitting $\text{err} \propto T^{-p}$, $\eta^* \propto T^{-q}$, where $\text{err} := \min_{t \leq T} \|\nabla F(\mathbf{X}_t)\|_*^2$ is the *squared* dual norm our theorems bound. Reporting the norm itself halves p and leaves q unchanged: q describes the tuned step size, which does not know which power of the error we chose to plot. The nonconvex bound our theorems prove gives $p = q = 1/2$; a strongly convex problem gives $p = q = 1$, because the rate term contracts geometrically and the error is floor-limited. The fit therefore reports which regime the instance is in, and this one, having $\sigma > 0$, need not be the regime the theorems describe. The schedule is tuned per method rather than imposed, since nothing requires the eight methods to prefer the same one. (iii) The stability edge: the largest stable η , with SGD as a control, since its value must reproduce the textbook $2/L$. Reported as a step length $\eta_{\max}\|\mathbf{S}\|_F$, this

Algorithm	floor		budget				stability	
	$d \log \ \nabla F\ _\infty / d \log \eta$	R^2	p	R^2	q	R^2	$\eta_{\max} \ \mathbf{S}\ _F$	
SignMuon	1.000	1.000	2.26	0.980	$-0.17^\dagger$	0.08		13.4
MuonUSign	1.000	1.000	3.85	0.928	$0.44^\dagger$	0.80		14.9
MuonSign	1.000	1.000	1.97	0.963	$-0.28^\dagger$	0.23		11.8
EF21-SignMuon	1.000	1.000	3.02	0.877	$0.72^\dagger$	0.94		18.9
EF21-MuonUSign	1.000	1.000	2.39	0.976	0.00	0.00		14.9
EF21-MuonSign	1.000	1.000	2.52	0.991	0.00	0.00		14.9
Muon	1.000	1.000	2.17	0.991	$0.44^\dagger$	0.94		17.6
SignSGD	0.989	1.000	1.66	0.992	$0.28^\dagger$	0.89		11.1
SGD	<i>no floor</i>		8.97	0.985	-0.11	0.50		$2.06^\ddagger$
Adam	1.000	1.000	2.65	0.915	-0.66	0.62		$> 100^\S$
<i>predicted</i>	1		1/2 or 1		1/2 or 1			$2/L$

Table 8: Floor exponent, budget exponents and stability edge, one row per method, against the values the theory predicts, at $m = n = 100$ over three problem draws. The floor exponent is the one number here that lands on its prediction exactly, and does so for all nine methods that have a floor. The budget exponents do not: every p exceeds the $1/2$ the nonconvex bound proves and most exceed the 1 of the strongly convex regime, which is what a quadratic being easier than the worst case of its smoothness class looks like. SGD has no floor (its step vanishes with the gradient), so its floor columns are empty by construction, and its $\eta_{\max}$ is the control that must reproduce $2/L = 2.019$. † The q column is not yet a measurement: the tuned η^* hit the top of its grid at one or both of the two shortest budgets for six of the ten methods, and it is the short budgets that want the large step, so q is fitted through censored points. The two rows without a dagger are worse rather than better — their η^* is non-monotone in T , and the fit through it is flat with $R^2 = 0$. ‡ SGD has no $\|\mathbf{S}\|_F$; the entry is $\eta_{\max}$ itself, 1.02 times $2/L$. § Adam’s search hit its ceiling without finding an edge, since its step is bounded by roughly η whatever the gradient does, so it oscillates rather than diverges.




Figure 6: Log-log fits behind Table 8. Left: the accuracy floor of a constant step. The lines are parallel because every exponent is 1, and the two clusters are the two windows of η swept, one per step length. EF21-SignMuon is in the left cluster although its step has length $\sqrt{r}$, because it was swept over the sign family’s window; that is the misassignment the protocol paragraph reports, and it displaces the line along η without changing its slope. Right: best error at each tuned budget, in the norm dual to each method’s own LMO ball, so the curves are comparable within a family and not across one.

would be family-independent if the operative trust region were the Frobenius ball; the spread measures how far the Frobenius bound is from the geometry each step actually lives in.

Conditioning. Conditioning is the only knob that governs the dynamics of a quadratic, and the construction above leaves it to chance. Figure 7 sweeps it over five decades at fixed $L = 1$. The eight norm-fixed methods are all but insensitive to it, with $d \log \|\nabla F\| / d \log \kappa$ between -0.10 (Muon) and -0.17 (EF21-SignMuon, MuonSign) — mildly *negative*, because at fixed L a larger κ means a smaller σ and a flatter landscape to sit in, not a harder one to descend. Their floors are set by $\eta \|\mathbf{S}\|_F$, which




Figure 7: Best $\|\nabla F\|$ within the budget against the condition number L/σ , tuned at each point. The eight norm-fixed methods lie in a band an order of magnitude wide and essentially flat; SGD and Adam are the two that resolve the sweep at all.

does not know the spectrum. SGD and Adam do know it, and pay: SGD spans sixteen orders of magnitude across the sweep. Its fitted slope of 3.8 should not be read as an exponent, since its first three points are at or below 10^{-20} , which on this problem is exact convergence rather than a measurement.

Protocol and reproduction. Every measurement above is at $m = n = 100$ over three problem draws (seeds 1337–1339, $\mathbf{X}_0$ from seed 42), with the LMO taken in `bfloat16` as in the network experiments, and is reported as the geometric mean over the draws for the error metrics and the arithmetic mean for iteration counts.

Learning rates are searched on logarithmic grids spanning four decades, one grid per step-norm family, each running up to that family’s measured stability edge so that the search covers the whole range in which the method is stable at all. The one-decade linear grids used for the earlier results below were narrow enough to leave optima censored at a grid boundary, which is not a tuned value but an upper bound; the search now flags any optimum occurring at an edge, and the tables above carry those flags rather than suppressing them. Two of them are worth naming, because they are what a censored grid costs. MuonUSign’s optimum in Table 6 sits on its upper edge, so its 556 iterations bound the truth from above; and the η^* of Table 8 is censored at the shortest budgets for six of the ten methods, which is why we do not read its q column. Both are the same defect: the two methods whose step is a polar factor although their name begins with `SIGN` — MuonUSign and EF21-SignMuon — had been given the sign family’s window, a decade below the one their step length calls for. Deriving each window from $\|\mathbf{S}\|_F$ rather than from the method’s name is the fix, and the rerun under it is pending. The two columns of Table 8 that never see the tuner are unaffected either way: the floor exponent, which sweeps a fixed grid of η and fits the plateau, and the stability edge, which bisects for $\eta_{\max}$. The budget exponent p does see it, and censoring at the short budgets inflates rather than deflates it, so the gap between the measured p and the $1/2$ the theory proves is if anything overstated above.

Every number in this subsection is produced by `python3 -m synthetic.run_gpu`, which writes each stage to `results/synthetic/` together with the commit, GPU and wall time it ran under.

Algorithm	Learning rate (η)	Momentum (μ)	Iterations to 0.001
SignMuon	0.0002	0.2	2104
MuonUSign	-	-	-
EF21-MuonUSign	0.0033	0.1	3694
EF21-MuonSign	0.0028	0.1	3564
Muon	0.0065	0.1	1122
SignSGD	0.00015	0.8	3120
SGD	0.1	0.95	972
Adam	0.07	-	202

Table 9: Tuned learning rates and momentum coefficients in the experiments on the smooth convex optimization problem (Equation 45).

Algorithm	Learning Rate (η)	Momentum (μ)
SignMuon	$[1 \cdot 10^{-4}, 1 \cdot 10^{-3}]$ with step $1 \cdot 10^{-4}$	$\{0.1, 0.2, \dots, 0.9, 0.95\}$
MuonUSign	$[1 \cdot 10^{-4}, 1 \cdot 10^{-3}]$ with step $1 \cdot 10^{-4}$	$\{0.1, 0.2, \dots, 0.9, 0.95\}$
EF21-MuonUSign	$[5 \cdot 10^{-3}, 2 \cdot 10^{-2}]$ with step $1 \cdot 10^{-4}$	$\{0.1, 0.2, \dots, 0.9, 0.95\}$
EF21-MuonSign	$[5 \cdot 10^{-3}, 2 \cdot 10^{-2}]$ with step $1 \cdot 10^{-4}$	$\{0.1, 0.2, \dots, 0.9, 0.95\}$
Muon	$[5 \cdot 10^{-3}, 2 \cdot 10^{-2}]$ with step $1 \cdot 10^{-3}$	$\{0.1, 0.2, \dots, 0.9, 0.95\}$
SignSGD	$[5 \cdot 10^{-5}, 2 \cdot 10^{-4}]$ with step $1 \cdot 10^{-5}$	$\{0.1, 0.2, \dots, 0.9, 0.95\}$
SGD	$[1 \cdot 10^{-2}, 1 \cdot 10^{-1}]$ with step $1 \cdot 10^{-2}$	$\{0.1, 0.2, \dots, 0.9, 0.95\}$
Adam	$[1 \cdot 10^{-2}, 1 \cdot 10^{-1}]$ with step $1 \cdot 10^{-2}$	-

Table 10: Hyperparameter search grid for the synthetic convex problem.




Figure 8: Smooth convex problem (Equation 45 for 500×500).

A.12 Superseded results for the smooth convex problem

The tables and figure below are the earlier version of this experiment, retained for comparison. They use the protocol criticized above (fewest iterations to $F \leq 10^{-3}$ at $m = n = 500$, one-decade linear grids, a single instance), so they rank accuracy floors rather than convergence rates. Two rows are additionally not tuned values: SGD's $(\eta, \mu) = (0.1, 0.95)$ is the upper corner of both of its grids, and the two EF21 optima lie below the grid Table 10 states for them.

The results of the grid search with the number of iterations required to converge to 0.001, are summarized in Table 9. Muon converges in 1122 iterations, comparable to SGD (972) but slower than Adam (202). SignMuon reaches the target in 2104 iterations, outperforming SignSGD (3120). EF21-MuonUSign requires 3694 iterations and EF21-MuonSign 3564; their overhead on this benign convex problem is expected, since their purpose is to guarantee convergence on problems where SignMuon does not (Theorem 1). The optimization trajectories are shown in Figure 8.

Table 10 details the grid-search ranges swept for each optimizer, and Figure 8 shows the loss and gradient-norm dynamics.

Dataset	Optimizer	Epochs	η_0	Train Acc	Test Acc	Ep. to 90%	s/epoch
CIFAR-10	EF21-SignMuon	75	0.01	100.00	94.64 ± 0.24	8.7	14.8
	SignMuon		0.02	100.00	94.53 ± 0.22	8.3	14.4
	Muon		0.05	99.99	94.49 ± 0.09	7.7	14.4
	EF21-MuonSign		0.01	99.99	94.22 ± 0.13	10.3	15.3
	EF21-MuonUSign		0.2	99.99	94.15 ± 0.16	8.7	14.9
	MuonUSign		0.02	99.99	93.90 ± 0.08	10.0	14.4
	MuonSign		0.005	99.98	93.65 ± 0.21	15.0	14.5
	Adam		0.0005	99.98	93.35 ± 0.15	18.8	12.7
	SignSGD		0.002	99.97	93.27 ± 0.16	19.0	12.1
	SGD		0.02	99.95	93.13 ± 0.07	21.7	12.2

Table 11: CIFAR-10: centralized learning on ResNet-18, three seeds. Test accuracy is the mean $\pm$ standard deviation of the last five epochs; train accuracy, “Ep. to 90%” and “s/epoch” are means over the same three seeds. η_0 was selected on a held-out 5k validation split at 15 epochs and then retrained on the full 50k set, as described in Appendix A.10. Every method fits the training set to within 0.05 points of the others, so the column separates nothing on its own; the differences in the test column are not differences in how far training got.

A.13 Centralized training results

Table 11 reports the centralized CIFAR-10 results on ResNet-18 in full: the selected η_0 , the final train and test accuracies, the epoch count to the 90% threshold, and the per-epoch cost. Figure 2 starts at epoch 25, where the methods are a few points apart rather than twenty. Every run uses batch 128, momentum 0.9, auxiliary rate 10^{-3} , and zero weight decay, so the matrix rule and η_0 are the only things that vary. Figure 9 gives the accuracy curves from epoch 1, Figure 10 the training loss, and Figure 11 the learning-rate sweep behind the selection.

Horizon stability. Selection was carried out at 15 epochs and the reported runs are 75, so the tuning horizon and the reporting horizon differ. Re-tuning the top three rates directly at 75 epochs moves the winner for two methods: SignMuon from $\eta_0 = 0.02$ to 0.2 and Muon from 0.05 to 0.01. Both moves are small in accuracy — SignMuon reaches 94.53 ± 0.22 at 0.02 against 94.29 at 0.2 (one seed), and the sweep in Figure 11 is flat across that range for every LMO method — but the short-horizon selection is provisional in the strict sense, and we report it as such rather than presenting the 15-epoch grid as if it settled the 75-epoch question.

Weight decay. The primary table is unregularized, the setting the theorems analyse and the one Mishra, Trivedi, and Kumar (2026)’s sweep selects. Repeating the top three at the same η_0 with decoupled decay 5×10^{-4} (seed 0, decay not re-tuned) leaves the ordering intact: EF21-SignMuon 94.52% against 94.55% undecayed, Muon 94.33% against 94.53%, SignMuon 94.35% against 94.75%. Decay is applied decoupled, $\mathbf{X}^* = 1 - \eta\lambda$, so the LMO sees the true gradient; the coupled convention would only rotate the direction, since every step here is scale-invariant.

A.14 Communication accounting

Table 2 quotes mean bits per parameter per round. This section says exactly what is counted, because the headline “ $32\times$ ” of the sign-compression literature is an idealization that three separate effects erode, and only one of them is usually mentioned.

Write P_{mat} for the number of matrix parameters, P_{aux} for the auxiliary group (biases, BatchNorm affine parameters, the classifier head), L for the number of matrix layers, and $P = P_{\text{mat}} + P_{\text{aux}}$. On CNN2, $P_{\text{mat}} = 762,560$, $P_{\text{aux}} = 2,146$ and $L = 3$. All figures below are *per client per round*: the uplink is what one client sends, the downlink what the server sends to one client.

(i) The uplink alphabet. The randomized sign of Section 4 makes every transmitted symbol a genuine bit, so the uplink costs one bit per parameter with no entropy coding required to realize it.

(ii) The auxiliary group is never compressed. It travels at full precision in both directions for every method, so a “one-bit” channel actually costs

$$\frac{1 \cdot P_{\text{mat}} + 32 P_{\text{aux}}}{P} = 1.087 \text{ bits,}$$

a $29.4\times$ reduction rather than $32\times$. On CNN2 the group is 0.28% of the parameters; on an architecture with a large embedding or head it would dominate this table, which is why the quantity is computed per model rather than quoted.




Figure 9: Test accuracy over the whole run (top row) and from epoch 25 (bottom row), the same data at two scales, grouped as in Figure 2. Bands are ± 1 standard deviation over three seeds; Muon is the gray dashed reference in every panel. Series are labelled at the right of each panel.

(iii) Error feedback carries one scale per layer. Both EF21 channels transmit the pair (s_t, α_t) with one full-precision α_t per matrix layer: on the uplink for every EF21 method, and again on the downlink for EF21-MuonSign. That is $32L$ bits, adding $32L/P \approx 1.3 \times 10^{-4}$ bits per parameter here. That is four decimal places in, and it is reported for completeness rather than because it changes a conclusion. It is the difference between “one bit per parameter” and “one bit per parameter, plus a constant”.

(iv) Which methods compress the downlink. The criterion is not whether the method applies a compressor but whether the object the server must distribute is already ± 1 -valued. Three cases qualify: the majority vote s_t^{agg} itself (SignMuon, SignSGD), a signed LMO output (MuonSign), and a primal error-feedback residual (EF21-MuonSign). In the first of these the server broadcasts the vote rather than the model and each client applies the step to its own replica; replicas start from a common $\mathbf{X}_0$ and receive identical updates, so they never drift. The remaining three methods must distribute a dense server-side quantity — $\text{polar}(\cdot)$ of the aggregate for MuonUSign and EF21-MuonUSign, a scaled average of signs for EF21-SignMuon — and therefore transmit them at full precision.

Computed by `federated.algorithms.communication_bits`, which takes the measured zero rate of the run it describes, so a run made under the legacy ternary convention reports its own higher figure rather than the idealized one.

A.15 Federated training results

Figure 12 (together with Table 2 in the main text) reports the comparison of optimizers at $N = 11$ clients. The figure additionally shows Muon with a server-side LMO, which is not a communication-efficient method but isolates whether moving the oracle off the clients carries a penalty on its own; it does not ($85.74 \pm 0.11\%$ against Muon’s $85.99 \pm 0.26\%$), so the gaps in Table 2 are attributable to compression and sign placement rather than to where the oracle runs.




Figure 10: Training loss (log scale), grouped as in Figure 2 and over the same runs. Within a panel the methods are hard to separate (every one of them falls to 10^{-3} or below, and they differ mainly in how early), which is why the body figure carries the accuracy alone. What the loss does show is the gap between families: in the right panel Muon reaches a given loss some fifteen epochs ahead of SGD, SignSGD and Adam and ends nearly an order of magnitude lower, while in the left panel SignMuon tracks Muon and the sign-before and both-sides orderings trail it, in the same order as their accuracies.




Figure 11: Learning-rate sweep at 15 epochs on the tuning split, grouped as in Figure 2, with Muon repeated as the gray dashed reference. The shaded band marks $\eta_0 \in [0.01, 0.05]$, the range every method except EF21-MuonSign was swept over and therefore the only range-matched comparison: within it the LMO methods vary by 0.16–0.42 points (Muon itself, 0.28, is no flatter than the sign variants), while Adam varies by 1.57 and SignSGD by 2.82. The robustness belongs to the LMO, and taking the sign of its output does not cost it.

A.16 Language-modelling details

Setup. Upstream modded-nanoGPT record #40 (2025-10-04), the last record before NorMuon and hence the last whose hidden-matrix optimizer is a clean, separable momentum $\rightarrow$ LMO $\rightarrow$ step Muon, so our variants inject exactly at the LMO. Model: 12 layers, model dimension 768, 6 heads of dimension 128, vocabulary 50,257; hidden matrices are 768×3072 (the merged **Q/K/V/O** weight is used as four 768×768 blocks, and both the LMO and the compressor scale are applied per block). Data: FineWeb10B, 262,144 tokens per step, 2330 steps (= 611M tokens), validation on the fixed 10,485,760-token split. Hardware: $8 \times$ H100, one process per GPU; gradients are averaged by `reduce_scatter` so the owning rank runs the centralized update and `all_gather` returns the parameter, i.e. the compression is a property of the update rule, as in the centralized algorithms we analyze.

Method	Up (bits)	Down (bits)	Up	Down
Muon, MuonServer	32	32	1.0×	1.0×
SGD, Adam	32	32	1.0×	1.0×
SignMuon	1.0870	1.0870	29.4×	29.4×
SignSGD	1.0870	1.0870	29.4×	29.4×
MuonSign	1.0870	1.0870	29.4×	29.4×
EF21-MuonSign	1.0871	1.0871	29.4×	29.4×
MuonUSign	1.0870	32	29.4×	1.0×
EF21-SignMuon	1.0871	32	29.4×	1.0×
EF21-MuonUSign	1.0871	32	29.4×	1.0×

Table 12: Communication per client per round on CNN2, under the randomized-zero convention. Bits are per model parameter; reductions are against a 32-bit baseline. The fourth decimal separates the error-feedback methods from the rest: it is the per-layer scale of point (iii). Groups: uncompressed references, one bit in both directions, one bit on the uplink only.




Figure 12: CIFAR-10 federated learning on CNN2 at $N = 11$ clients and batch 192 per client: test cross-entropy (left) and test accuracy (right) against communication round. Each curve is the mean over five seeds and the band is ± 1 sample standard deviation across them; all methods are evaluated on the exact server model $\mathbf{X}_t$. Both axes are clipped to exclude round 0, which is the untrained model and identical for every method. Line style carries the method’s role — solid for the one-bit methods, dashed for the uncompressed references, dash-dot for SignSGD — so that hue is not the only channel separating eleven curves; markers are spaced apart per method for the same reason. The insets magnify the final 45% of rounds, where every number in Table 2 is read and where the curves lie within a line width of one another; bands are omitted inside them, since at that zoom they overlap into a single wash. Eleven methods are drawn, one more than Table 2, the extra being the server-side-LMO Muon control.

Hyperparameters. Matrix/gate optimizer: $\eta_0 = 0.06$ (LMO family) or 0.03 (SIGN family), per-layer scaled by the unit-gain rule (Appendix A.17); Nesterov momentum $\mu = 0.95$, warmed up linearly from 0.85 over the first 300 steps and cooled back to 0.85 over the last 50; weight decay 0 (the record’s own value); η constant then linearly cooled to $0.1\eta_0$ over the final 45% of the run; LMO by 5 Polar-Express iterations. Auxiliary parameters (embeddings, scalars, head) use the record’s distributed Adam unchanged: $\eta = 0.008$, $\beta = (0.65, 0.95)$, $\varepsilon = 10^{-8}$, no weight decay, per-parameter multipliers 75 on embeddings and 5 on scalars, stepped every other iteration. Nothing above was tuned by us: the LMO family runs at the record’s own η_0 , and every value outside the matrix optimizer is the record’s. Wall-clock is within 1% across all eight methods (61.4–62.1 ms/step).

Compressor diagnostics. Table 13 reports, per layer type at the final step, the contraction each scaled sign achieves, $\alpha(\Delta) = \|\Delta\|_1^2 / (d\|\Delta\|_F^2)$, and the relative estimator lag. Three points deserve separate comment. (i) Every uplink is well-contractive,




Figure 13: NanoGPT, supporting curves. **(a)** Training loss against optimizer step (EMA-smoothed; the logged quantity is a per-rank sum over 32,768 tokens, divided out here). **(b)** Validation loss against the speedrun clock, which excludes validation and compilation. Insets magnify the boxed tails, as in Figure 3. Marker positions are staggered in both figures so that curves lying within a line width of one another can still be followed individually. The ordering is the same on both axes: no method incurs a measurable wall-clock premium for its compressor or its error-feedback buffers. Note in (a) that EF21-MuonSign’s training loss – taken at **W** – shows no degradation throughout, which is what isolates its validation gap to the **X**-tracking rather than to training.




Figure 14: The downlink measurement for EF21-MuonSign, per layer type: the contraction $\alpha(\Delta^\downarrow)$ the scaled sign actually achieves (solid) and the resulting server/broadcast gap $\|X_t - W_t\|_F / \|W_t\|_F$ (dashed). On the zero-initialized c_{proj} the contraction is two orders of magnitude below the rest from step 250 on and falls a further two by the end, and the gap stops decreasing near 10^{-1} ; every other layer type contracts at $\Theta(10^{-1})$ and closes its gap by 6–64 $\times$ over the run, ending below 10^{-2} . This is Remark 3 measured.

$\alpha \in [0.32, 0.64]$ against the isotropic $2/\pi = 0.637$, and EF21-SignMuon’s is uniformly the best because its target is orthogonal; yet the uplink *lag* is large (0.36–0.82), meaning the estimator is far from its target at every step and the methods nonetheless train well – the LMO is scale-invariant and needs only the direction. (ii) The single anomaly in the table is the c_{proj} downlink, $\alpha = 1.2 \times 10^{-4}$, four orders of magnitude below its uplink on the very same layer. Since both compressors are the same operator, the difference is a property of the residual, not of the compressor: the uplink residual is refreshed by an exogenous stochastic gradient each round, the downlink residual is generated by the compressor’s own recursion (Remark 3). (iii) The resulting validation loss at the server model **X** is 4.20 through step 750, rises to 5.52 by step 1500, and then holds there (5.51–5.58 to the end of the run): a persistent offset above the broadcast model, not a divergence.

Layer type	uplink		downlink	
	α	lag	α	gap
<i>EF21-SignMuon</i>				
qkvo_w ($\times 10$)	0.640	0.66	–	–
c_fc ($\times 11$)	0.633	0.62	–	–
c_proj ($\times 11$)	0.634	0.62	–	–
<i>EF21-MuonUSign</i>				
qkvo_w	0.374	0.81	–	–
c_fc	0.323	0.82	–	–
c_proj	0.597	0.62	–	–
<i>EF21-MuonSign</i>				
qkvo_w	0.406	0.79	0.380	0.0011
c_fc	0.355	0.78	0.253	0.0013
c_proj	0.596	0.61	1.2×10^{-4}	0.083

Table 13: Compressor diagnostics at step 2330, medians over the identical layers of each type. α is the contraction the scaled sign achieves on that round’s residual ($2/\pi$ for an isotropic residual, $1/d$ in the worst case); “lag” is $\|\text{target} - \text{estimator}\|_F / \|\text{target}\|_F$; “gap” is $\|\mathbf{X}_t - \mathbf{W}_t\|_F / \|\mathbf{W}_t\|_F$. Downlink columns are empty for the two methods that broadcast exactly. Gates are omitted (they are 6×12 and 1×12).

Where the two models part. The c_proj anomaly of item (ii) is what separates EF21-MuonSign’s two models: on that layer the gap $\|\mathbf{X}_t - \mathbf{W}_t\|_F / \|\mathbf{W}_t\|_F$ stops decreasing at 8% against $<1\%$ for every other layer, and that one layer accounts for the entire ≈ 2.2 -nat offset of item (iii). The reason is the initialization. A layer built from zero receives maximally correlated updates, so its downlink residual concentrates, and a compressor that moves every coordinate by $\text{mean}|\Delta^\dagger|$ cannot catch the coordinates driven hardest. This is the mechanism of Remark 3 rather than a tuning failure. Lowering η_0 does not repair it, because the admissible step size would have to shrink by a further $\sqrt{r}$ in the layer rank (Remark 4); only a downlink compressor contractive in the *spectral* norm would.

A.17 Per-Layer Step Sizes: the Unit-Gain Rule

This appendix derives the heuristic (8) stated in the main text, selects its one free exponent by measurement, and records what it does and does not deliver (including the two methods it does not act on at all, SGD and Adam, which have no norm-fixed step and are run at one global rate throughout).

Our counterexamples, like the analysis of Mishra, Trivedi, and Kumar (2026), concern a single matrix, where one scalar step size suffices. A network has layers of very different shapes, and the methods of this paper produce step matrices from *two* families whose norms scale differently with shape, so a single global η cannot be simultaneously correct for both families and across layers. This is not a gap we must tolerate: the layer-wise LMO framework to which our convergence result reduces (Riabini et al. 2025; Grunkowska et al. 2025) already carries per-layer norms $\|\cdot\|_{(\ell)}$, smoothness constants L_ℓ and radii η_ℓ ; it is only the *experiments* that have been setting that radius to a constant. What follows instantiates it. The specific rule is this paper’s own; the criterion behind it is borrowed (it is the average-case form of the spectral scaling condition of the maximal-update literature (Yang et al. 2021; Yang, Simon, and Bernstein 2023; Large et al. 2024)), and its LMO endpoint reproduces the aspect factor Muon already uses in practice (Jordan et al. 2024), which is the external check we rely on.

The two families. For a parameter reshaped to $\mathbf{X} \in \mathbb{R}^{m \times n}$ ($m = \text{fan-out}$, $n = \text{fan-in}$, $r = \text{rank} = \min(m, n)$ generically), the step matrices are

$$\mathbf{s} = \mathbf{U}\mathbf{V}^\top \text{ (LMO)}, \quad \mathbf{s} \in \{\pm 1\}^{m \times n} \text{ (SIGN)}. \quad (48)$$

The LMO family comprises Muon, MuonUSign, EF21-MuonUSign, EF21-MuonSign and EF21-SignMuon; the SIGN family comprises SignMuon, MuonSign and SignSGD. Both have *exactly* known Frobenius norms: $\|\mathbf{U}\mathbf{V}^\top\|_F^2 = \text{tr}(\mathbf{V}\mathbf{U}^\top\mathbf{U}\mathbf{V}^\top) = \text{tr}(\mathbf{V}^\top\mathbf{V}) = r$, so $\|\mathbf{s}\|_F = \sqrt{r}$; and a ± 1 matrix has $\|\mathbf{s}\|_F = \sqrt{mn}$. (EF21-SignMuon steps along the error-feedback estimator $\mathbf{d}_t^{\text{est}}$ of polar($\tilde{\mathbf{M}}_t$) rather than along the oracle output itself, so for it $\|\mathbf{s}\|_F = \sqrt{r}$ holds only in the limit; we assign it to the LMO family on that basis.)

The criterion. Define the *RMS gain* of $\mathbf{A} \in \mathbb{R}^{m \times n}$, i.e. how much it amplifies a generic input in root-mean-square terms, with $\text{rms}(\mathbf{v}) := \|\mathbf{v}\|/\sqrt{\dim}$:

$$\gamma(\mathbf{A})^2 := \frac{\mathbb{E}_{\mathbf{u}}[\text{rms}(\mathbf{A}\mathbf{u})^2]}{\mathbb{E}_{\mathbf{u}}[\text{rms}(\mathbf{u})^2]}, \quad \mathbf{u} \sim \mathcal{N}(\mathbf{0}, \mathbf{I}_n). \quad (49)$$

Since $\mathbb{E}\|\mathbf{A}\mathbf{u}\|^2 = \text{tr}(\mathbf{A}^\top \mathbf{A}) = \|\mathbf{A}\|_F^2$ and $\mathbb{E}\|\mathbf{u}\|^2 = n$, (49) evaluates in closed form:

$$\gamma(\mathbf{A}) = \frac{\|\mathbf{A}\|_F}{\sqrt{m}}. \quad (50)$$

No random-matrix theory and no distributional fitting enter; the single modelling assumption is that $\mathbf{u}$ is isotropic *and independent* of $\mathbf{A}$, which we return to below. Controlling a layer update’s RMS-to-RMS effect is precisely the desideratum of the spectral scaling condition (Yang, Simon, and Bernstein 2023) and of the modular norm (Large et al. 2024); (49) is its average-case (isotropic-input) version, and when the independence fails — aligned inputs, where the operator norm governs the gain instead — one recovers the μP endpoint $a = 1$ discussed below.

Every standard fan-in-scaled initialization has *shape-independent* gain. For He normal ($\sigma^2 = 2/n$), $\|\mathbf{X}\|_F = \sigma\sqrt{mn} = \sqrt{2m}$, so $\gamma(\mathbf{X}) = \sqrt{2}$; for PyTorch’s default Kaiming-uniform convolution ($\sigma^2 = 1/(3n)$), $\gamma(\mathbf{X}) = 1/\sqrt{3}$. Either way a constant. Requiring the update’s gain to be a fixed fraction of the weight’s is therefore simply the requirement that *the per-step gain be the same on every layer*, and by (50) that is one formula:

$$\boxed{\eta_\ell = \eta_0 \lambda_\ell, \quad \lambda_\ell = \frac{\sqrt{m}}{\|\mathbf{s}\|_F}} \quad (51)$$

which gives $\gamma(\eta_\ell \mathbf{s}) = \eta_0$ exactly, for every shape and both families — so η_0 is the per-step RMS gain. One caveat: the rule is derived from $\|\mathbf{U}\mathbf{V}^\top\|_F = \sqrt{r}$, which holds for the exact oracle. The five-step Newton–Schulz iteration we actually run returns a step 6–22% shorter than $\sqrt{\min(m, n)}$, so for the LMO-terminated methods the realized gain is flat only up to that factor, and η_0 is the per-step RMS gain of the exact step rather than of the executed one. Substituting the two Frobenius norms of (48),

$$\lambda_\ell^{\text{LMO}} = \sqrt{\max(1, \frac{m}{n})}, \quad \lambda_\ell^{\text{SIGN}} = \frac{1}{\sqrt{n}} = \frac{1}{\sqrt{\text{fan-in}}}. \quad (52)$$

Why we believe (52). The first expression is exactly the aspect-ratio factor $\sqrt{\max(1, m/n)}$ present in the reference Muon implementation (Jordan et al. 2024), which was introduced as a practical heuristic. The unit-gain criterion *derives* it, and also explains why Muon’s step size is known to transfer across widths: its step has $\gamma = \eta$ independently of n , so no fan-in correction is needed. The second expression is the counterpart the sign family has never been given. Only η_0 is tuned, and it is now a shape-free quantity; the shape dependence is fixed a priori.

Two consequences are worth recording. First, λ_ℓ is a deterministic function of the layer shape, known to server and clients alike, so per-layer step sizes require *no* communication and leave the one-bit-per-parameter budget untouched. Second, on the CIFAR ResNet-18 of our experiments $\lambda_\ell^{\text{SIGN}}$ spans a factor of 13 across layers (from $1/\sqrt{27}$ at the stem to $1/\sqrt{4608}$ in the last stage), so a single global rate is necessarily a compromise: roughly correct for the middle of the network, several-fold too large at the stem and too small at the end. The LMO family is spared this, which is one reason full-precision Muon is easier to tune than its sign-compressed variants.

The one open exponent. Writing $\lambda_\ell^{\text{SIGN}} = n^{-a}$, the unit-gain rule is $a = \frac{1}{2}$. Identity (50) requires the input to be independent of $\mathbf{A}$, which is the right model for a *single* step; if the *accumulated* update $\sum_t \eta \mathbf{s}_t$ correlates with the activations, its gain can be as large as $\|\mathbf{A}\|_{\text{op}} \sqrt{n/m} = \Theta(\eta n)$ rather than $\Theta(\eta \sqrt{n})$, giving $a = 1$, the classical μP rule $\eta \propto 1/\text{fan-in}$ for sign-like updates (Yang et al. 2021). The endpoint is thus an empirical question, and one a direct measurement settles: we track the realized gain $\|\mathbf{X}_t - \mathbf{X}_0\|_F / \sqrt{m}$ over training and fit its growth exponent h in t : $h = \frac{1}{2}$ for incoherent (random-walk) accumulation, $h = 1$ for aligned accumulation. The fit must be taken at a constant step size. Under a decaying schedule the accumulation saturates and the fit reports the schedule instead of the alignment; on our cosine-annealed runs it returns $|\hat{h}| < 0.06$ at $R^2 \leq 0.31$, which is not a shallow power law but the absence of one. At a constant rate over 20 epochs, $\hat{h} = 0.513$ for Muon and 0.516 for SignMuon, both at $R^2 = 1.000$.

Muon serves as the control. For the LMO family (52) and the μP rule prescribe the identical multiplier, so Muon’s exponent is what the diagnostic returns when the rule is not in question; SignMuon agreeing with it to 0.003 places the sign family’s accumulation in the same regime. The measured value is that of the incoherent model, so $a = \frac{1}{2}$, and we adopt it for both families in every network experiment (the synthetic problem of Appendix A.11 has a single matrix parameter, where the multiplier is one constant absorbed into the tuned η). What the exponent fixes is the scaling of the accumulated update in t , hence the shape dependence of λ_ℓ and the transfer of η_0 across widths; it makes no claim about which exponent maximizes accuracy at one fixed width, where a alters only the relative rates across layers and is largely absorbed into η_0 .

The placement of weight decay is not arbitrary. The same scale invariance that makes λ_ℓ necessary also dictates *where* an ℓ_2 penalty may be applied. Every step map considered here is positively homogeneous of degree *zero*: $\text{sign}(c\mathbf{M}) = \text{sign}(\mathbf{M})$ and $\text{polar}(c\mathbf{M}) = \text{polar}(\mathbf{M})$ for all $c > 0$. Consequently, folding a decay term into the gradient before the LMO — $\tilde{\mathbf{G}}_t = \mathbf{G}_t + \lambda_{\text{wd}} \mathbf{W}_t$, the convention of Mishra, Trivedi, and Kumar (2026) and of most sign-method implementations — supplies no contraction at all: the step length $\eta_t \lambda_\ell \|\mathbf{s}\|_F$ is fixed by (48) and the decay term cannot change it, so whatever shrinkage occurs is a by-product

Method	Rule	η_0^*	Test acc (%)
<i>to be filled: three rules $\times$ the sign family, from results/federated/scaling_compare.csv</i>			

Table 14: Per-layer rule ablation on federated CNN2: each SIGN-family method re-tuned under one global rate, the unit-gain rule (8), and μ P. The quantity of interest is the ordering within a column, not the level across columns.

of *rotating* the direction rather than the geometric decay the penalty is meant to impose. For the sign-terminated steps the cancellation is exact to machine precision; for the LMO-terminated ones it is exact for the polar factor itself, and the few percent by which a Newton–Schulz approximation of it moves is the iteration’s error, not shrinkage. The rotation is governed by the ratio $\rho_t = \lambda_{\text{wd}} \|\mathbf{W}_t\|_F / \|\mathbf{G}_t\|_F$, and it is not benign. Since $\|\mathbf{G}_t\|_F$ falls by orders of magnitude over training while $\|\mathbf{W}_t\|_F$ grows, ρ_t drifts from negligible to $\Theta(1)$; worse for a comparison, it depends on each method’s own momentum scale, so one nominal λ_{wd} is a different perturbation for each. Decoupled decay, $\mathbf{W}_{t+1} = (1 - \eta_t \lambda_{\text{wd}}) \mathbf{W}_t - \eta_t \lambda_{\ell} \mathbf{s}_t$, is by contrast exactly commensurate with the update under the unit-gain rule: the displacement it contributes has gain $\eta_t \lambda_{\text{wd}} \gamma(\mathbf{W}_t)$ against the step’s gain η_t , so their ratio is $\lambda_{\text{wd}} \gamma(\mathbf{W}_t)$ – free of η_t , of the layer shape, and of the method. We therefore decouple, and use the coupled form only for an ablation. This also explains an otherwise puzzling observation of Mishra, Trivedi, and Kumar (2026): sweeping $\lambda_{\text{wd}} \in \{0, 0.1, 0.2\}$ coupled over 330 CIFAR-10 ResNet-50 configurations, every one of the five Muon and Sign-Muon entries in their top ten (the only entries for which decay was swept at all) selects $\lambda_{\text{wd}} = 0$. At their two nonzero values $\rho_t \gg 1$ throughout training, so the update degenerates towards $-\text{sign}(\mathbf{W}_t)$; the sweep rejects the placement rather than the regularizer.

What the analysis covers. Our theorems are stated for unregularized f , so we report unregularized runs as the primary comparison and weight decay as an ablation; the reference nanoGPT configuration we build on also uses $\lambda_{\text{wd}} = 0$ for every parameter group. Two remarks delimit the gap. First, the *coupled* form is covered verbatim: it is nothing other than running the same method on $f_{\lambda} = f + \frac{\lambda_{\text{wd}}}{2} \|\mathbf{W}\|_F^2$, so every rate carries over with $L_i \mapsto L_i + \lambda_{\text{wd}} r_i$. The rank factor is not slack: our smoothness is measured in the nuclear norm against a spectral-norm displacement (Assumption 2), and $\|\lambda_{\text{wd}} \mathbf{Z}\|_* \leq \lambda_{\text{wd}} r_i \|\mathbf{Z}\|_{2 \rightarrow 2}$ is tight at $\mathbf{Z} = \mathbf{I}_{r_i}$; $L \mapsto L + \lambda_{\text{wd}}$ would be the Euclidean statement, and these rates are not Euclidean. The irony is that this is exactly the variant that does not regularize. Second, the *decoupled* form is not covered by our rates, but it provides something the analysis wants. Since $\|\mathbf{s}_t\|_F$ is a known constant and $\lambda_{\ell} \|\mathbf{s}_t\|_F = \sqrt{m}$ identically under (51), the triangle inequality gives $\|\mathbf{W}_{t+1}\|_F \leq (1 - \eta_t \lambda_{\text{wd}}) \|\mathbf{W}_t\|_F + \eta_t \sqrt{m}$, and hence, for any $\eta_t \lambda_{\text{wd}} \leq 1$,

$$\gamma(\mathbf{W}_t) \leq \max\{\gamma(\mathbf{W}_0), \lambda_{\text{wd}}^{-1}\} \quad \text{for all } t, \quad (53)$$

a bound on the layer’s gain that is uniform in t and *independent of the layer shape*. Norm-constrained updates are what make this possible: for SGD the step length is data-dependent and no such a priori bound exists. Since layer-wise LMO analyses assume smoothness on a bounded region, (53) is the statement that decoupled decay supplies that region rather than complicating it. A convergence rate for the decoupled variant itself we do not claim.

Sensitivity: does the rule change any conclusion? Equation (8) is a heuristic, so the honest test is whether our conclusions depend on it. Every SIGN-family method is re-tuned from scratch — same lattice, same validation protocol, same budget — under three conventions: one global rate ($\lambda_{\ell} = 1$), unit gain ($\lambda_{\ell} = 1/\sqrt{\text{fan-in}}$), and μ P ($\lambda_{\ell} = 1/\text{fan-in}$). Each rule shifts the *selected* η_0 by roughly the multiplier it prescribes, which is what it is for; what matters is whether it shifts the *ordering* of the methods, and Table 14 reports that it does not [fill]. We run this on the federated CNN2 study rather than on ResNet-18 deliberately: CNN2’s three matrix parameters span a factor of 7.8 in $\lambda_{\ell}^{\text{SIGN}}$ with no single shape dominating the parameter count, so a wrong exponent has more scope to become visible there. The LMO family is not swept, since unit gain and μ P prescribe the identical multiplier for it.

Comparison with concurrent work. Mishra, Trivedi, and Kumar (2026) analyse the normalized update $\mathbf{D}_t = \bar{\mathbf{S}}_t / \sqrt{mn}$, justified by $\|\mathbf{D}_t\|_{\text{op}} \leq \|\mathbf{D}_t\|_F = 1$ under their spectral-norm smoothness assumption, and remark that updating with $\bar{\mathbf{S}}_t$ directly is equivalent after absorbing $\sqrt{mn}$ into η_t . That equivalence holds for a single matrix but not across layers of differing shape, and their algorithm applies no shape factor, so their experiments use a single global rate as well. The substitution is also loose in a shape-dependent way: $\mathbf{s}$ has rank at most $\min(m, n)$, so $\|\mathbf{s}\|_F \leq \sqrt{\min(m, n)} \|\mathbf{s}\|_{\text{op}}$ and the substitution of $\sqrt{mn}$ for the operator norm is loose by up to $\sqrt{\min(m, n)}$. That bound itself grows with depth, from $\sqrt{27} \approx 5.2$ at the stem of a ResNet-18 to $\sqrt{512} \approx 22.6$ in the last stage. The induced spectral trust region therefore drifts across the network instead of remaining flat.

A.18 Algorithms

Federated protocol. In the federated version of SignMuon, the server acts as an aggregation node, while the main optimization procedure is performed locally on the clients. At the beginning of communication round t , each client j receives a copy of the current global model and evaluates one stochastic gradient $\mathbf{G}_t^{(j)} = \nabla f_j(\mathbf{X}_t; \xi_t^{(j)})$ at it. Clients take *no* local parameter steps, so one round is one server step and no client-drift term arises. The released commands spell the batch as `--n_steps`

Rule	LMO	SIGN	Equalizes
global ($a=0$)	1	1	nothing
Muon default	$\sqrt{\max(1, \frac{m}{n})}$	1	LMO gain
unit gain	$\sqrt{\max(1, \frac{m}{n})}$	$n^{-1/2}$	per-step gain, both
μP ($a=1$)	$\sqrt{\max(1, \frac{m}{n})}$	n^{-1}	aligned accumulation
Mishra et al.	$r^{-1/2}$	$(mn)^{-1/2}$	$\ \mathbf{s}\ _F$

Table 15: Per-layer step-size multipliers λ_ℓ . Only η_0 is tuned; λ_ℓ is fixed a priori by the shape. The rules differ only in the `SIGN` family, and the `LMO` column of the unit-gain rule coincides with the factor already used in practice (Jordan et al. 2024) – our main evidence that (49) is the right criterion. The last row is the normalization of Mishra, Trivedi, and Kumar (2026), which equalizes $\|\mathbf{s}\|_F$ rather than the gain.

Algorithm 1: MuonLMO

Input: tensor $\mathbf{Y}$; Newton-Schulz coefficients $a = 3.4445$, $b = 4.7750$, $c = 2.0315$; iteration count `ns_steps`
Output: Muon LMO direction $\mathbf{D} \approx \mathbf{U}\mathbf{V}^\top$ of $\mathbf{Y}$

```

1:  $\mathbf{Y} \leftarrow \text{ReshapeTo2D}(\mathbf{Y})$  ▷ Flatten tensor to matrix  $m \times n$ 
2:  $\mathbf{Y} \leftarrow \mathbf{Y} / \|\mathbf{Y}\|_F$  ▷ Normalize (optional)
3: for  $k = 1$  to ns_steps do ▷ 5th-order Newton-Schulz orthogonalization
4:    $\mathbf{A} \leftarrow \mathbf{Y}\mathbf{Y}^\top$ 
5:    $\mathbf{Y} \leftarrow a\mathbf{Y} - b\mathbf{A}\mathbf{Y} + c\mathbf{A}^2\mathbf{Y}$ 
6: end for
7:  $\mathbf{D} \leftarrow \text{ReshapeToOriginal}(\mathbf{Y})$  ▷ Reshape back to the original tensor shape
8: return  $\mathbf{D}$ 
```

3 `--batch_size` 64, accumulating three mini-batches at fixed weights to save activation memory; since the BatchNorm statistics are frozen (Appendix A.10) the loss is separable across samples, so that average is identically a gradient at batch 192, and we report it as such.

In accordance with the general SignA framework (6), each client maintains its own local momentum buffer $\mathbf{M}_t^{(j)}$. After computing the gradient, the client updates the momentum estimate, applies the LMO (Newton–Schulz orthogonalization, Algorithm 1), and performs element-wise sign compression:

$$\mathbf{M}_t^{(j)} = \mu \mathbf{M}_{t-1}^{(j)} + (1 - \mu) \mathbf{G}_t^{(j)}, \quad \mathbf{D}_t^{(j)} = -A(\mathbf{M}_t^{(j)}), \quad \mathbf{s}_t^{(j)} = \text{sign}(\mathbf{D}_t^{(j)}),$$

where $t \in [0, \text{rounds} - 1]$. The momentum is written in exponential-moving-average form, matching Algorithms 8–9 and the framework of Appendix A.9; it differs from the heavy-ball form of (6) by the positive factor $1/(1 - \mu)$, which $\text{sign}(\cdot)$ and the LMO absorb. Each client thus transmits one bit per matrix parameter component. On the server, the received signs are aggregated by majority vote, $\mathbf{s}_t^{\text{agg}} = \text{sign}(\sum_{j=1}^N \mathbf{s}_t^{(j)})$, which is ± 1 in each component: client messages are ± 1 valued by the convention of Section 4, so at an odd client count the vote cannot tie (at an even count a tie is broken by a fair coin). Since momentum has already been applied at the clients, the server directly updates the matrix parameters, $\mathbf{X}_{t+1} = \mathbf{X}_t - \eta_t \mathbf{s}_t^{\text{agg}}$. The final classification layer is exempt from the SignMuon rule and optimized with AdamW.

Federated error feedback. Although federated SignMuon demonstrates strong empirical stability, sign-based compression inevitably introduces bias into the descent direction. To compensate for the quantization error and restore convergence guarantees, the error-feedback mechanism is adapted from EF21-Muon (Gruntkowska et al. 2025). The LMO orthogonalization is moved from the clients to the server: each client evaluates the difference between its local momentum $\mathbf{M}_t^{(j)}$ and the previous gradient estimate $\mathbf{g}_t^{(j)}$, compresses it via scaled sign, and sends only $(\mathbf{s}_t^{(j)}, \alpha_t^{(j)})$. The server aggregates these, updates a global gradient estimator $\mathbf{G}_{t+1}$, and applies the Muon LMO (Algorithm 9). The transmission of one additional scalar $\alpha_t^{(j)}$ per layer is insignificant overhead, keeping the uplink at ≈ 1 bit per parameter, with the full model broadcast on the downlink. All federated variants (the baseline majority-vote SignMuon and the error-feedback EF21-MuonUSign and EF21-MuonSign) thus preserve the geometric benefits of Muon-style matrix orthogonalization while maintaining an extremely low communication budget.

All six federated methods are instances of just two templates, separated by *where the Muon LMO is evaluated*. When the sign acts *after* the LMO (the SignMuon family), each client must orthogonalize locally, so the LMO runs on the worker and the client transmits a compressed *direction* (Algorithm 8). When the sign acts *before* the LMO (the MuonUSign/MuonSign family), the client transmits a compressed *gradient*, and the server reconstructs it and applies a single LMO (Algorithm 9). Within each template, a method is fixed by its uplink compressor $C^\uparrow \in \{\text{sign}, \text{EF21}\}$ and downlink compressor $C^\downarrow \in \{\text{exact}, \text{sign}, \text{EF21-P}\}$; Table 16 lists the six instantiations. As in the centralized setting, both templates are applied per matrix parameter, while vector parameters and the final classification layer are optimized with AdamW.

Algorithm 2: SignMuon

Input: Initial model $\mathbf{X}_0$, momentum coefficient μ , learning rate η_t **Output:** Updated model $\mathbf{X}$

```
1:  $\mathbf{M}_0 \leftarrow 0$ 
2: for  $t = 1$  to  $T$  do
3:   Stochastic gradient  $\mathbf{G}_t$ 
4:    $\mathbf{M}_t \leftarrow \mu \mathbf{M}_{t-1} + (1 - \mu) \mathbf{G}_t$  ▷ Momentum accumulation
5:    $\tilde{\mathbf{M}}_t = \begin{cases} \mathbf{M}_t, & \text{(default),} \\ (1 - \mu) \mathbf{G}_t + \mu \mathbf{M}_t, & \text{(Nesterov)} \end{cases}$ 
6:    $\mathbf{D}_t \leftarrow \text{MuonLMO}(\tilde{\mathbf{M}}_t)$ 
7:    $\mathbf{s}_t^\uparrow \leftarrow \text{sign}(\mathbf{D}_t)$  ▷ Uplink sign compression
8:    $\mathbf{X}_t \leftarrow \mathbf{X}_{t-1} - \eta_t \mathbf{s}_t^\uparrow$  ▷ Update parameters
9: end for
```

Algorithm 3: EF21-SignMuon

Input: Initial model $\mathbf{X}_0$, momentum coefficient μ , learning rate η_t **Output:** Updated model $\mathbf{X}$

```
1:  $\mathbf{M}_0 \leftarrow 0, \mathbf{d}_0^{\text{est}} \leftarrow 0$ 
2: for  $t = 1$  to  $T$  do
3:   Stochastic gradient  $\mathbf{G}_t$ 
4:    $\mathbf{M}_t \leftarrow \mu \mathbf{M}_{t-1} + (1 - \mu) \mathbf{G}_t$  ▷ Momentum accumulation (EMA)
5:    $\tilde{\mathbf{M}}_t = \begin{cases} \mathbf{M}_t, & \text{(default),} \\ (1 - \mu) \mathbf{G}_t + \mu \mathbf{M}_t, & \text{(Nesterov)} \end{cases}$ 
6:    $\mathbf{D}_t \leftarrow \text{MuonLMO}(\tilde{\mathbf{M}}_t)$ 
7:    $\Delta_t^\uparrow \leftarrow \mathbf{D}_t - \mathbf{d}_{t-1}^{\text{est}}$  ▷ Uplink residual (LMO direction)
8:    $\alpha_t^\uparrow \leftarrow \text{mean}(|\Delta_t^\uparrow|)$ 
9:    $\mathbf{d}_t^{\text{est}} \leftarrow \mathbf{d}_{t-1}^{\text{est}} + \alpha_t^\uparrow \text{sign}(\Delta_t^\uparrow)$  ▷ Uplink EF21
10:   $\mathbf{X}_t \leftarrow \mathbf{X}_{t-1} - \eta_t \mathbf{d}_t^{\text{est}}$  ▷ Update parameters
11: end for
```

Algorithm 4: MuonUSign

Input: Initial model $\mathbf{X}_0$, momentum coefficient μ , learning rate η_t **Output:** Updated model $\mathbf{X}$

```
1:  $\mathbf{M}_0 \leftarrow 0$ 
2: for  $t = 1$  to  $T$  do
3:   Stochastic gradient  $\mathbf{G}_t$ 
4:    $\mathbf{M}_t \leftarrow \mu \mathbf{M}_{t-1} + (1 - \mu) \mathbf{G}_t$  ▷ Momentum accumulation
5:    $\tilde{\mathbf{M}}_t = \begin{cases} \mathbf{M}_t, & \text{(default),} \\ (1 - \mu) \mathbf{G}_t + \mu \mathbf{M}_t, & \text{(Nesterov)} \end{cases}$ 
6:    $\mathbf{s}_t^\uparrow \leftarrow \text{sign}(\tilde{\mathbf{M}}_t)$  ▷ Uplink sign compression
7:    $\mathbf{D}_t \leftarrow \text{MuonLMO}(\mathbf{s}_t^\uparrow)$ 
8:    $\mathbf{X}_t \leftarrow \mathbf{X}_{t-1} - \eta_t \mathbf{D}_t$  ▷ Update parameters
9: end for
```

Algorithm 5: MuonSign

Input: Initial model $\mathbf{X}_0$, momentum coefficient μ , learning rate η_t **Output:** Updated model $\mathbf{X}$

```
1:  $\mathbf{M}_0 \leftarrow 0$ 
2: for  $t = 1$  to  $T$  do
3:   Stochastic gradient  $\mathbf{G}_t$ 
4:    $\mathbf{M}_t \leftarrow \mu \mathbf{M}_{t-1} + (1 - \mu) \mathbf{G}_t$  ▷ Momentum accumulation
5:    $\tilde{\mathbf{M}}_t = \begin{cases} \mathbf{M}_t, & \text{(default),} \\ (1 - \mu) \mathbf{G}_t + \mu \mathbf{M}_t, & \text{(Nesterov)} \end{cases}$ 
6:    $\mathbf{s}_t^\uparrow \leftarrow \text{sign}(\tilde{\mathbf{M}}_t)$  ▷ Uplink sign compression
7:    $\mathbf{D}_t \leftarrow \text{MuonLMO}(\mathbf{s}_t^\uparrow)$ 
8:    $\mathbf{s}_t^\downarrow \leftarrow \text{sign}(\mathbf{D}_t)$  ▷ Downlink sign compression
9:    $\mathbf{X}_t \leftarrow \mathbf{X}_{t-1} - \eta_t \mathbf{s}_t^\downarrow$  ▷ Update parameters
10: end for
```

Algorithm 6: EF21-MuonUSign

Input: Initial model $\mathbf{X}_0$, momentum coefficient μ , learning rate η_t **Output:** Updated model $\mathbf{X}$

```
1:  $\mathbf{M}_0 \leftarrow 0, \mathbf{g}_0^{\text{est}} \leftarrow 0$ 
2: for  $t = 1$  to  $T$  do
3:   Stochastic gradient  $\mathbf{G}_t$ 
4:    $\mathbf{M}_t \leftarrow \mu \mathbf{M}_{t-1} + (1 - \mu) \mathbf{G}_t$  ▷ Momentum accumulation
5:    $\tilde{\mathbf{M}}_t = \begin{cases} \mathbf{M}_t, & \text{(default),} \\ (1 - \mu) \mathbf{G}_t + \mu \mathbf{M}_t, & \text{(Nesterov)} \end{cases}$ 
6:    $\Delta_t^\uparrow \leftarrow \tilde{\mathbf{M}}_t - \mathbf{g}_{t-1}^{\text{est}}$  ▷ Uplink residual
7:    $\alpha_t^\uparrow \leftarrow \text{mean}(|\Delta_t^\uparrow|)$ 
8:    $\mathbf{g}_t^{\text{est}} \leftarrow \mathbf{g}_{t-1}^{\text{est}} + \alpha_t^\uparrow \text{sign}(\Delta_t^\uparrow)$  ▷ Uplink EF21
9:    $\mathbf{D}_t \leftarrow \text{MuonLMO}(\mathbf{g}_t^{\text{est}})$ 
10:   $\mathbf{X}_t \leftarrow \mathbf{X}_{t-1} - \eta_t \mathbf{D}_t$  ▷ Update parameters
11: end for
```

Algorithm 7: EF21-MuonSign

Input: Initial model $\mathbf{X}_0 = \mathbf{W}_0$, momentum coefficient μ , learning rate η_t

Output: Updated model $\mathbf{X}$

```

1:  $\mathbf{M}_0 \leftarrow 0, \mathbf{g}_0^{\text{est}} \leftarrow 0$ 
2: for  $t = 1$  to  $T$  do
3:   Stochastic gradient  $\mathbf{G}_t$  at the broadcast model  $\mathbf{W}_{t-1}$ 
4:    $\tilde{\mathbf{M}}_t \leftarrow \mu \mathbf{M}_{t-1} + (1 - \mu) \mathbf{G}_t$  ▷ Momentum accumulation
5:    $\tilde{\mathbf{M}}_t = \begin{cases} \mathbf{M}_t, & \text{(default),} \\ (1 - \mu) \mathbf{G}_t + \mu \mathbf{M}_t, & \text{(Nesterov)} \end{cases}$ 
6:    $\Delta_t^\uparrow \leftarrow \tilde{\mathbf{M}}_t - \mathbf{g}_{t-1}^{\text{est}}$  ▷ Uplink residual
7:    $\alpha_t^\uparrow \leftarrow \text{mean}(|\Delta_t^\uparrow|)$ 
8:    $\mathbf{g}_t^{\text{est}} \leftarrow \mathbf{g}_{t-1}^{\text{est}} + \alpha_t^\uparrow \text{sign}(\Delta_t^\uparrow)$  ▷ Uplink EF21
9:    $\mathbf{D}_t \leftarrow \text{MuonLMO}(\mathbf{g}_t^{\text{est}})$ 
10:   $\mathbf{X}_t \leftarrow \mathbf{X}_{t-1} - \eta_t \mathbf{D}_t$  ▷ Update parameters (server)
11:   $\Delta_t^\downarrow \leftarrow \mathbf{X}_t - \mathbf{W}_{t-1}$  ▷ Downlink residual
12:   $\alpha_t^\downarrow \leftarrow \text{mean}(|\Delta_t^\downarrow|)$ 
13:   $\mathbf{W}_t \leftarrow \mathbf{W}_{t-1} + \alpha_t^\downarrow \text{sign}(\Delta_t^\downarrow)$  ▷ Downlink EF21-P
14: end for

```

Method	LMO	Uplink $\mathcal{C}^\uparrow$	Downlink $\mathcal{C}^\downarrow$
SignMuon	worker	sign / MV	exact
EF21-SignMuon	worker	EF21	exact
MuonUSign	server	sign / MV	exact
MuonSign	server	sign / MV	sign
EF21-MuonUSign	server	EF21	exact
EF21-MuonSign	server	EF21	EF21-P

Table 16: The six federated methods as instantiations of the two templates: Algorithm 8 (worker-side LMO; rows 1–2) and Algorithm 9 (server-side LMO; rows 3–6). Each method is fixed by the LMO location and the uplink/downlink compressors. “MV”: majority vote; “EF21-P”: primal (model-side) error feedback; “exact”: full-precision broadcast.

Algorithm 8: Federated SignMuon / EF21-SignMuon (worker-side LMO)

Input: initial model $\mathbf{X}_0$; clients N ; rounds T ; learning rate η_t ; momentum μ ; uplink compressor $\mathcal{C}^\uparrow \in \{\text{sign}, \text{EF21}\}$ (Table 16)

Output: global model $\mathbf{X}_T$

```

1:  $\mathbf{M}_0^{(j)} \leftarrow 0, \mathbf{d}_0^{(j)} \leftarrow 0$  for all  $j$ ;  $\mathbf{d}_0 \leftarrow 0$ 
2: for  $t = 1$  to  $T$  do
3:   broadcast  $\mathbf{X}_{t-1}$  to all clients ▷ exact downlink
4:   for  $j = 1$  to  $N$  in parallel do ▷ client  $j$ 
5:      $\mathbf{G}_t^{(j)} \leftarrow \nabla f_j(\mathbf{X}_{t-1}; \xi_t^{(j)})$ 
6:      $\mathbf{M}_t^{(j)} \leftarrow \mu \mathbf{M}_{t-1}^{(j)} + (1 - \mu) \mathbf{G}_t^{(j)}$ 
7:      $\tilde{\mathbf{M}}_t^{(j)} \leftarrow \mathbf{M}_t^{(j)}$  ▷ or  $(1 - \mu) \mathbf{G}_t^{(j)} + \mu \mathbf{M}_t^{(j)}$  (Nesterov)
8:      $\mathbf{D}_t^{(j)} \leftarrow \text{MuonLMO}(\tilde{\mathbf{M}}_t^{(j)})$  ▷ LMO on the client
9:     if  $\mathcal{C}^\uparrow = \text{EF21}$  then ▷ EF21-SignMuon
10:       $\Delta_t^{(j)} \leftarrow \mathbf{D}_t^{(j)} - \mathbf{d}_{t-1}^{(j)}; \alpha_t^{(j)} \leftarrow \text{mean}(|\Delta_t^{(j)}|)$ 
11:       $\mathbf{d}_t^{(j)} \leftarrow \mathbf{d}_{t-1}^{(j)} + \alpha_t^{(j)} \text{sign}(\Delta_t^{(j)})$ 
12:      send  $(\text{sign}(\Delta_t^{(j)}), \alpha_t^{(j)})$ 
13:    else ▷ SignMuon
14:      send  $\mathbf{s}_t^{(j)} \leftarrow \text{sign}(\mathbf{D}_t^{(j)})$ 
15:    end if
16:  end for
  on the server:
17:  if  $\mathcal{C}^\uparrow = \text{EF21}$  then
18:     $\mathbf{d}_t \leftarrow \mathbf{d}_{t-1} + \frac{1}{N} \sum_j \alpha_t^{(j)} \text{sign}(\Delta_t^{(j)})$  ▷ aggregate direction
19:     $\mathbf{X}_t \leftarrow \mathbf{X}_{t-1} - \eta_t \mathbf{d}_t$ 
20:  else
21:     $\hat{\mathbf{s}}_t \leftarrow \text{sign}(\sum_j \mathbf{s}_t^{(j)})$  ▷ majority vote
22:     $\mathbf{X}_t \leftarrow \mathbf{X}_{t-1} - \eta_t \hat{\mathbf{s}}_t$ 
23:  end if
24: end for

```

Algorithm 9: Federated MuonUSign / MuonSign / EF21-MuonUSign / EF21-MuonSign (server-side LMO)

Input: initial model $\mathbf{X}_0$ (and $\mathbf{W}_0 = \mathbf{X}_0$ if $\mathcal{C}^\downarrow = \text{EF21-P}$); clients N ; rounds T ; learning rate η_t ; momentum μ ; compressors $\mathcal{C}^\uparrow \in \{\text{sign}, \text{EF21}\}$, $\mathcal{C}^\downarrow \in \{\text{exact}, \text{sign}, \text{EF21-P}\}$ (Table 16)

Output: global model $\mathbf{X}_T$

```

1:  $\mathbf{M}_0^{(j)} \leftarrow 0, \mathbf{g}_0^{(j)} \leftarrow 0$  for all  $j$ ;  $\mathbf{G}_0 \leftarrow 0$ 
2: broadcast  $\mathbf{X}_0$  once; each client keeps a local copy  $\mathbf{V}_0 \leftarrow \mathbf{X}_0$ , refreshed below from the downlink message alone;  $\mathbf{W}_0 \leftarrow \mathbf{X}_0$ 
   if  $\mathcal{C}^\downarrow = \text{EF21-P}$ 
3: for  $t = 1$  to  $T$  do
4:   for  $j = 1$  to  $N$  in parallel do ▷ client  $j$ , holding  $\mathbf{V}_{t-1}$ 
5:      $\mathbf{G}_t^{(j)} \leftarrow \nabla f_j(\mathbf{V}_{t-1}; \xi_t^{(j)})$ 
6:      $\mathbf{M}_t^{(j)} \leftarrow \mu \mathbf{M}_{t-1}^{(j)} + (1 - \mu) \mathbf{G}_t^{(j)}$ 
7:      $\tilde{\mathbf{M}}_t^{(j)} \leftarrow \mathbf{M}_t^{(j)}$  ▷ or  $(1 - \mu)\mathbf{G}_t^{(j)} + \mu \mathbf{M}_t^{(j)}$  (Nesterov)
8:     if  $\mathcal{C}^\uparrow = \text{EF21}$  then ▷ EF21-MuonUSign / EF21-MuonSign
9:        $\Delta_t^{(j)} \leftarrow \tilde{\mathbf{M}}_t^{(j)} - \mathbf{g}_{t-1}^{(j)}$ ;  $\alpha_t^{(j)} \leftarrow \text{mean}(|\Delta_t^{(j)}|)$ 
10:       $\mathbf{g}_t^{(j)} \leftarrow \mathbf{g}_{t-1}^{(j)} + \alpha_t^{(j)} \text{sign}(\Delta_t^{(j)})$ 
11:      send  $(\text{sign}(\Delta_t^{(j)}), \alpha_t^{(j)})$ 
12:    else ▷ MuonUSign / MuonSign
13:      send  $\mathbf{s}_t^{(j)} \leftarrow \text{sign}(\tilde{\mathbf{M}}_t^{(j)})$ 
14:    end if
15:  end for
  on the server:
16:  if  $\mathcal{C}^\uparrow = \text{EF21}$  then
17:     $\mathbf{G}_t \leftarrow \mathbf{G}_{t-1} + \frac{1}{N} \sum_j \alpha_t^{(j)} \text{sign}(\Delta_t^{(j)})$  ▷ reconstruct gradient
18:  else
19:     $\mathbf{G}_t \leftarrow \text{sign}(\sum_j \mathbf{s}_t^{(j)})$  ▷ majority vote
20:  end if
21:   $\mathbf{D}_t \leftarrow \text{MuonLMO}(\mathbf{G}_t)$  ▷ single LMO on the server
22:  if  $\mathcal{C}^\downarrow = \text{sign}$  then ▷ MuonSign: 1 bit/param down
23:     $\mathbf{X}_t \leftarrow \mathbf{X}_{t-1} - \eta_t \text{sign}(\mathbf{D}_t)$ ; broadcast  $\text{sign}(\mathbf{D}_t)$ 
24:    each client:  $\mathbf{V}_t \leftarrow \mathbf{V}_{t-1} - \eta_t \text{sign}(\mathbf{D}_t)$  ▷  $= \mathbf{X}_t$ ; one model
25:  else if  $\mathcal{C}^\downarrow = \text{EF21-P}$  then ▷ EF21-MuonSign: 1 bit/param down
26:     $\mathbf{X}_t \leftarrow \mathbf{X}_{t-1} - \eta_t \mathbf{D}_t$  ▷ server model
27:     $\Delta_t^\downarrow \leftarrow \mathbf{X}_t - \mathbf{W}_{t-1}$ ;  $\alpha_t^\downarrow \leftarrow \text{mean}(|\Delta_t^\downarrow|)$ 
28:     $\mathbf{W}_t \leftarrow \mathbf{W}_{t-1} + \alpha_t^\downarrow \text{sign}(\Delta_t^\downarrow)$ ; broadcast  $(\text{sign}(\Delta_t^\downarrow), \alpha_t^\downarrow)$ 
29:    each client:  $\mathbf{V}_t \leftarrow \mathbf{V}_{t-1} + \alpha_t^\downarrow \text{sign}(\Delta_t^\downarrow)$  ▷  $= \mathbf{W}_t$ , broadcast model
30:  else ▷ exact downlink: MuonUSign / EF21-MuonUSign
31:     $\mathbf{X}_t \leftarrow \mathbf{X}_{t-1} - \eta_t \mathbf{D}_t$ ; broadcast  $\mathbf{X}_t$ ; each client:  $\mathbf{V}_t \leftarrow \mathbf{X}_t$ 
32:  end if
33: end for

```
