

VR-SetsOp.

An Operational Set Theory Unifying ZFC and ZFA (Brouwer Edition)

(formerly titled *VR-Sets*; same Zenodo concept 10.5281/zenodo.20303535 — retitled to name the operational carrier *OpSet*)

Vitaly Reznik

2026 — Version 1.2.0

Abstract

We reconstruct set theory inside the VR programme as an operational universe: a set is a *functionality* that, on a query, reveals its members — formally, a pointed graph — and the identity of sets is a *witnessed bisimulation*, carried as a relation and never collapsed to a quotient. On this carrier we obtain, machine-checked in Lean 4 and almost entirely below the **Classical.choice** floor: membership, strong extensionality (identity is exactly co-membership), the empty set, pairing, union, the power set, the von Neumann naturals and ω , and the Separation and Replacement schemas — every axiom of ZF without Foundation. The power set is machine-checked *choice-free* but is *impredicative*, which isolates the obstruction to power set in the operational register as impredicativity, not choice. Anti-Foundation is a theorem — indeed axiom-free: a member is the same graph re-pointed, so nesting (including self-membership) is native, and decoration of any graph is almost definitional. Well-foundedness is not an axiom but a predicate **IsGrounded**: the ZFC universe and the anti-foundational (Aczel) universe are two fragments of one operational domain, not a foundational choice one is forced to make. Version 1.0.3 corrected the central error of earlier versions: the earlier text claimed the operational universe is countable and inferred that the Axiom of Choice is a free theorem and that paradoxes such as Banach–Tarski cannot arise — a Bishop reading that contradicts the operational continuum the cycle built on the Brouwer path. We replace it: the operational universe — sets as becoming — is genuinely non-enumerable (a machine-checked, choice-free diagonal), while the describable register (sets given by a finite rule) is countable. The Axiom of Choice is therefore not an operational theorem; only dependent choice is. The absence of Banach–Tarski is re-explained through conservativity, not countability.

Keywords: operational set theory, non-well-founded sets, bisimulation, strong extensionality, Brouwer, choice sequences, axiom of choice, constructive foundations, Lean 4.

Version note (1.2.0). No mathematics is altered, added, or removed. Two changes. (i) The work is retitled *VR-SetsOp* to name its operational carrier **OpSet** (the earlier title *VR-Sets* named the domain; the content, since Version 1.0.3, is entirely the operational universe); the Zenodo concept (10.5281/zenodo.20303535) is unchanged. (ii) A positioning paragraph is added to §7 stating the exact relation to ZFA: with VR’s formal register on (classical logic, choice) the set layer *realises* Aczel’s ZFA and is *equal to it in strength* (equiconsistent, at the level of ZF — neither stronger nor weaker), with ZFC recovered as the well-founded inner class **IsGrounded**; without the formal register the operational core is strictly weaker (constructive, choice-free). This resolves the imprecision in the Version 1.1.0 phrase “holds ZFC and ZFA natively” and records the one strict advantage at equal strength — nesting is a theorem in VR where ZFA posits it.

Version note (1.1.0). A minor version: new mathematics is added, none altered or removed. Adds the operational **power set** (§3.3): $\wp x$ with $z \in \wp x \iff z \subseteq x$, machine-checked

choice-free (**propext**). With it, **OpSet** verifies every axiom of ZF without Foundation. The construction is below the choice floor but *impredicative* — this isolates the obstruction to power set in the operational register as impredicativity, not choice, and corrects the blanket “no power-set operation” of the earlier §7 (Remark 3.10). It also states **Anti-Foundation as a theorem** on **OpSet** (§4.1), fully axiom-free, with the cost-of-quotient bridge to VR-Sets-ZFA; anchors §6.4 in Solovay’s model; and names two prices (the setoid discipline; impredicativity’s invisibility to the axiom audit, P-1). No prior mathematics is altered.

Version note (1.0.4). Editorial synchronisation, no mathematics altered: (i) Remark 5.2 is corrected — VR-Numbers’ $\mathbb{R}_{VR}$ is the *computable*, *countable* reals (its Lean isomorphism with the full classical line is an inexpressibility artifact, VR-Numbers §VIII.6), the genuinely non-enumerable object is the operational becoming-continuum (and this universe, §6.1), and classical $\mathbb{R}$ is a third thing; (ii) references carry correct, separated DOIs (the formal-system *paper* is DOI 10.5281/zenodo.20633314, concept 10.5281/zenodo.20212091; 20324240 is its Lean companion); (iii) the describable register is noted to be a minimal representative of “finite rule” (§6.2); (iv) the single mathlib borrowing is flagged already in §1.

Contents

1	Introduction and the change since Version 1.0.2	2
2	The carrier: sets as revealing functionalities	3
2.1	Operational sets	3
2.2	Operational identity: witnessed bisimulation, not a quotient	3
2.3	Membership and strong extensionality	3
3	The operations	4
3.1	Infinity	4
3.2	Separation and Replacement	4
3.3	Power set	5
4	Foundation is a predicate, not a choice	5
4.1	Anti-Foundation as a theorem	6
5	Numbers	6
6	Cardinality, the diagonal, and choice — the corrected core	7
6.1	The operational universe is non-enumerable	7
6.2	The describable register is countable	7
6.3	The Axiom of Choice is not a theorem	8
6.4	Why Banach–Tarski does not arise — through conservativity, not counting	8
7	Position and honest boundaries	9
	Acknowledgement of AI assistance	10
	References	10

1 Introduction and the change since Version 1.0.2

VR-Sets realises the set-theoretic layer of the VR programme. A set is not a “thing that contains elements”; it is an *operation* — a functionality that, when queried, reveals members, which are themselves functionalities. This reading is constitutive, not decorative: every notion below (membership, identity, the operations, well-foundedness) is defined in its terms, and every claim is checked by the Lean 4 kernel with its axiom cost recorded.

Versions through 1.0.2 presented the operational universe through a classical surrogate (mathlib’s well-founded `ZFSet`) and argued, in their §VI, that the universe is countable, whence the Axiom of Choice holds as a theorem and the classical “pathologies” (non-measurable sets, Banach–Tarski) do not arise. Two things were wrong. First, countability is false of the surrogate (`ZFSet` is the full classical uncountable universe), so the claim was carried by prose, not by the machine. Second, and more deeply, the countability reading is a *Bishop* reading, and it is incompatible with the operational continuum the VR cycle actually constructed, which took the *Brouwer* path: there the space of “becoming” (lawless choice sequences) is non-enumerable, choice-free, and Cantor’s diagonal works.

We resolve the tension on the side the cycle already chose. The operational universe of sets is rebuilt from scratch, as functionalities with witnessed-bisimulation identity (§2), and we prove (§6) that this universe — sets as becoming — is not enumerable, by a self-contained diagonal that is choice-free. The countable register is the register of *descriptions*: sets given by a finite rule. The contrast *done countable* / *becoming non-enumerable* is the corrected §VI. The Axiom of Choice loses its status as a free theorem; this is not a loss but the honest price of a genuinely uncountable operational continuum, and it aligns VR-Sets with VR-Forms (conservativity) and with the operational-continuum work.

What is machine-checked. The development lives in the Lean 4 formalisation of the VR cycle, module `VRCycle.SetsOp` (files `Pointed`, `Builder`, `Closure`, `Omega`, `Extensionality`, `Congruence`, `Becoming`, `Describable`, `Schemas`, `Grounded`, `Power`, `AFA`). It is self-contained: it imports nothing from mathlib for its core — precisely so that its axiom profile is visible — the *single* mathlib borrowing (the pairing inversion in the describable register) being flagged in Remark 6.5. Throughout, we name the Lean object backing each statement. Almost every object is axiom-free or depends only on `propext`; the single exception is flagged honestly in §6.

2 The carrier: sets as revealing functionalities

2.1 Operational sets

Definition 2.1 (Operational set; `OpSet`). *An operational set is a pointed graph $x = (V, E, \text{pt})$ with $V : \text{Type}$, $E : V \rightarrow V \rightarrow \text{Prop}$, $\text{pt} : V$. Read $E\ a\ b$ as “querying the functionality at vertex b reveals a as a member”; pt is the set itself. The member of x sitting at a vertex a is the same graph re-pointed there, $x.\text{child}\ a := (V, E, a)$. This is exactly the language in which Aczel’s anti-foundation axiom is stated (decoration of a graph), but we take no quotient: the identity of sets is supplied operationally, below.*

2.2 Operational identity: witnessed bisimulation, not a quotient

Definition 2.2 (Bisimulation; operational identity $\approx$). *A relation $R : x.V \rightarrow y.V \rightarrow \text{Prop}$ is a bisimulation between x and y if related vertices reveal matching members in both directions: for all*

a, b with $R a b$,

$$(\forall a', x.E a' a \Rightarrow \exists b', y.E b' b \wedge R a' b') \wedge (\forall b', y.E b' b \Rightarrow \exists a', x.E a' a \wedge R a' b').$$

We write $x \approx y$ (x and y are operationally identical) when some bisimulation relates their points: $\exists R, R x.pt y.pt \wedge R$ is a bisimulation.

Proposition 2.3 ($\approx$ is an equivalence; `Equiv.refl/symm/trans`). $\approx$ is reflexive, symmetric and transitive. Each is axiom-free in Lean (no `propext`, no `Quot.sound`, no `Classical.choice`).

The methodological point is decisive. To turn “bisimilar” into a type-level equality — to form the quotient — one must Skolemise the existential matches into functions; that step is exactly VR’s transit asymmetry (operational $\rightarrow$ formal is free, formal $\rightarrow$ operational has no mechanism), and it is precisely where mathlib’s coinductive set construction invokes `Classical.choice`. We therefore do not quotient. Identity remains a relation carried with its witness: a performed bisimulation, not a given completion. This is “doing, not being” made into the construction, and it is why the whole development stays below the choice floor.

2.3 Membership and strong extensionality

Definition 2.4 (Membership; `Mem`). $z \in x$ iff some member-vertex of x is operationally identical to z : $\exists a, x.E a x.pt \wedge z \approx x.child a$.

Theorem 2.5 (Membership respects identity; `mem_congr`). If $y \approx y'$ then $z \in y \Rightarrow z \in y'$. (Axiom-free.)

Theorem 2.6 (Strong extensionality; `ext`, `equiv_iff_same_mem`). Two operational sets are identical iff they have the same members: $x \approx y \iff \forall z, (z \in x \leftrightarrow z \in y)$. Both directions are axiom-free.

Theorem 2.6 is the heart of the carrier. The forward direction is Theorem 2.5 applied both ways; the backward direction is the coinductive content — one builds a bisimulation out of the member-matching (relate the two roots; relate any further pair whose rooted subtrees are already identical). It is the AFA-style strong extensionality, kept choice-free precisely because identity was never quotiented. It is what licenses $\approx$ as a faithful equality of sets.

3 The operations

All operations are instances of one constructor.

Definition 3.1 (Family supremum; `sup`). For a family $c : I \rightarrow \text{OpSet}$, the set `sup c` whose members are exactly the $c i$ is the pointed graph with a fresh root revealing each component’s point, components kept disjoint.

Theorem 3.2 (`mem_sup`). $z \in \text{sup } c \iff \exists i, z \approx c i$. (Axiom-free.)

From this single law the standard operations follow; each is axiom-free or depends only on `propext`:

- Empty set $\emptyset$ (`emptySup`): the empty family. $z \notin \emptyset$ (`not_mem_emptySup`). $\emptyset$ is the nullary operation — the functionality that reveals nothing — matching the base of the VR formal system.

- Singleton $\{a\}$: $z \in \{a\} \iff z \approx a$.
- Unordered pair $\{a, b\}$: $z \in \{a, b\} \iff z \approx a \vee z \approx b$.
- Union $\bigcup x$: $z \in \bigcup x \iff \exists y, y \in x \wedge z \in y$ (**mem_union**).
- Binary union $a \cup b$ and successor $\text{succ } a := a \cup \{a\}$: $z \in \text{succ } a \iff z \in a \vee z \approx a$ (**mem_succ**).

Proposition 3.3 (Operations respect identity; ***_congr**). *singleton, pair, $\bigcup$ and succ all respect $\approx$ (through Theorem 2.6).*

3.1 Infinity

Definition 3.4 (Von Neumann naturals and ω ; **vn, omega**). $\text{vn } 0 := \emptyset$, $\text{vn}(n+1) := \text{succ}(\text{vn } n)$; $\omega := \sup \text{vn}$.

Theorem 3.5 (Infinity; **mem_omega, empty_mem_omega, omega_succ_closed**). *The members of ω are exactly the $\text{vn } n$ up to $\approx$; $\emptyset \in \omega$; and ω is closed under successor for any member. (Axiom-free, resp. **propext**.)*

3.2 Separation and Replacement

A genuine property or function of sets cannot depend on the particular graph presenting a set; it must respect $\approx$. With that — and no decidability assumption — the two schemas hold.

Theorem 3.6 (Separation; **sep, mem_sep**). *For a species p respecting $\approx$, the set $\{z \in x \mid pz\}$ exists and $z \in \{z \in x \mid pz\} \iff z \in x \wedge pz$. (**propext**.)*

Theorem 3.7 (Replacement; **repl, mem_repl**). *For a rule F respecting $\approx$, the image $\{Fz \mid z \in x\}$ exists and $w \in \{Fz \mid z \in x\} \iff \exists z, z \in x \wedge w \approx Fz$. (**propext**.)*

3.3 Power set

A subset of x is selected by a predicate on x 's member-vertices; the power set ranges over all of them. (This is the one operation whose construction reaches into the ambient type theory; see Remark 3.10.)

Definition 3.8 (Subset; power set; **Subset, subsetOf, powerset**). $z \subseteq x : \iff \forall w, w \in z \Rightarrow w \in x$. For a vertex-predicate $s : x.V \rightarrow \text{Prop}$, **subsetOf** x s is the sup of the member-vertices of x kept by s . The power set $\wp x := \sup_{s : x.V \rightarrow \text{Prop}} \text{subsetOf } x \ s$ ranges over all such predicates.

Theorem 3.9 (Power set; **mem_powerset**). $z \in \wp x \iff z \subseteq x$. (**propext**; choice-free.) *The backward direction selects the predicate “ a is a member-vertex whose member lies in z ” and closes by strong extensionality (Theorem 2.6).*

With the power set, **OpSet** verifies every axiom of ZF without Foundation — Extensionality, $\emptyset$, Pairing, Union, Power, Separation, Replacement, Infinity — machine-checked below the choice floor; Foundation is the predicate **IsGrounded** of §4.

Remark 3.10 (The obstruction to power set is impredicativity, not choice). The completed power set $\wp x$ is constructed *choice-free* (Theorem 3.9); in particular $\wp \omega$ exists as a set with $z \in \wp \omega \iff z \subseteq \omega$. What this costs is *not* **Classical.choice** — the axiom audit reports **propext** only — but *impredicativity*: the index $x.V \rightarrow \text{Prop}$ is the full power of the representative's vertex type, a move

legitimate in Lean’s impredicative `Prop` but outside a predicative (Brouwer / Martin-Löf) discipline, and one that `#print axioms` cannot detect. So the operational register’s relation to power set is sharper than the “absent” of Version 1.0.4’s §7: the *predicative* content of $\wp\omega$ is the becoming — the non-enumerable diagonal of §6.1 — while the *impredicative completed* $\wp\omega$ also exists, choice-free, at the cost named here. The obstruction is isolated: it is impredicativity, not choice.

4 Foundation is a predicate, not a choice

Classical set theory must decide, at the level of its axioms, whether $\in$ -descent always terminates: ZFC posits Foundation, Aczel’s theory posits the Anti-Foundation Axiom (AFA). These are two incompatible commitments, and a classical theory is forced to pick one. VR is not. On the operational carrier, well-foundedness is a property of a set’s graph, observed and not postulated.

Definition 4.1 (Groundedness; `IsGrounded`). *x is grounded iff its point is accessible under the reveal relation: $\text{Acc}(E)x.\text{pt}$ — every membership descent from x terminates.*

Theorem 4.2 (Groundedness is a property of the set; `isGrounded_iff`). *If $x \approx y$ then x grounded $\iff y$ grounded. (Axiom-free.)*

Theorem 4.3 (The ZFC fragment is hereditary; `mem_grounded`). *A member of a grounded set is grounded. (Axiom-free.)*

Theorem 4.2 makes “well-founded” a well-defined predicate on operational sets (transported across a bisimulation; the key lemma `acc_bisim` carries accessibility along R). Hence the ZFC fragment is $\{x \mid x \text{ grounded}\}$ ($\emptyset$ is grounded; the fragment is closed downward under $\in$), and the ZFA fragment is the whole universe. The Quine atom $A = \{A\}$ is a perfectly good operational set — one vertex with a self-loop (`quine`), satisfying $A \in A$ (`quine_self_mem`) — and it is not grounded (`quine_not_grounded`); no anti-foundation axiom is invoked, the graph simply has a cycle. VR thus holds ZFC and ZFA natively, as fragments of one universe distinguished by a predicate, with uniform identity (witnessed bisimulation) throughout. The grounded fragment enjoys $\in$ -acyclicity: no von Neumann natural is a member of itself (`vn_not_self_mem`, by strong induction).

4.1 Anti-Foundation as a theorem

Because membership is the edge relation and a member is the same graph re-pointed (`child`), *nesting is native*: a set contains a set by an edge, never by copying a set into another, and self-membership is a self-loop. Aczel’s decoration of a graph is therefore almost definitional here.

Definition 4.4 (Decoration; `decorate`, `IsDecoration`). *A function $d : V \rightarrow \text{OpSet}$ decorates a graph (V, E) if the members of dv are exactly the dw with Ewv . The canonical decoration is $\text{decorate}Ev := (V, E, v)$ — the graph re-pointed at v .*

Theorem 4.5 (Anti-Foundation; `afa`, `decorate_isDecoration`, `decoration_unique`). *Every graph has a decoration, unique up to operational identity: $\text{decorate}E$ decorates (V, E) — by `rfl`, since membership is the decoration condition — and any decoration d is pointwise $\approx$ to it: for each v , the choice-free exhibited bisimulation $R_v a w := (dv).\text{child}a \approx dw$ witnesses $dv \approx \text{decorate}Ev$. Fully axiom-free (`[]`: no `propext`, no `Quot.sound`, no `Classical.choice`).*

AFA is thus a theorem, not an axiom; and ZFA is not even a separate commitment — the Quine atom (one vertex, a self-loop) and every cycle are simply admissible graphs. With this and Foundation-as-predicate, `OpSet` holds ZFC and ZFA natively on one carrier.

The cost of the quotient — bridge to VR-Sets-ZFA. The companion work VR-Sets-ZFA obtains the same anti-foundational content on mathlib’s coinductive M-types, by *quotienting* an extensional bisimulation. There AFA carries the full `[propext, Classical.choice, Quot.sound]`: forming the quotient Skolemises the bisimulation’s existential witnesses (VR’s transit asymmetry, §2.2), and uniqueness must select representatives by `Classical.choice` and run `PFunctor.M.bisim` through the choice-pulling destructor `dest`. The contrast is exact and is itself a result: *the relational identity is axiom-free precisely where its quotient sits at the full ceiling* — the price of turning a performed bisimulation into a given equality is `Classical.choice`. We read the two works together as the equivalence $\text{OSetZFA} \simeq \text{OpSet}/\approx$ — the version here being the choice-free floor of which VR-Sets-ZFA is the quotient. **This last equivalence is a prose-level reading, not yet machine-checked** (in the modality of Conjecture IV.2): formalising it — the `M.corec` unfolding of a graph, its descent through the quotient, and bijectivity on the $\approx$ -classes — is a single `Bridge` file, a candidate for VR-Sets-ZFA v1.1. Everything else in this paper carries a named Lean object and its profile.

5 Numbers

The natural numbers are the von Neumann naturals of §3, genuinely distinct as operational sets.

Theorem 5.1 (The operational naturals are distinct; `vn_inj`). $\text{vn } n \approx \text{vn } m \Rightarrow n = m$. (*propext.*)

The proof is the classical one read operationally: the members of $\text{vn } m$ are exactly $\text{vn } 0, \dots, \text{vn } (m-1)$, no $\text{vn } n$ is a member of itself, and these force injectivity by the trichotomy of $\mathbb{N}$.

Remark 5.2 (Three reals — stated honestly). The reals of the VR cycle come in distinct guises that must not be conflated.

- **VR-Numbers’ $\mathbb{R}_{VR}$** is built from Cauchy sequences with a *computable modulus of convergence*; it is isomorphic to the field of *computable* reals and is therefore *countable*. (Its Lean realisation additionally proves an isomorphism with the full classical line, but that is an artifact of Lean’s inability to express computability in a single type, not the content of the construction — see VR-Numbers §VIII.6.) This is the *done*/describable side.
- **The operational becoming-continuum** — the space of lawless choice sequences (and the Bishop reals over $\mathbb{Z}$ on the Brouwer path) — is built below the choice floor and is *genuinely non-enumerable*, choice-free. The non-enumerability is real, not classical: it is the same phenomenon this paper proves for the set universe (Theorem 6.1, `universe_not_enumerable`) and that the continuum work proves for $\mathbb{N} \rightarrow \text{Bool}$ (`branches_not_enumerable`).
- **The classical line $\mathbb{R}$** (mathlib) is uncountable in the usual, choice-laden sense.

These coexist. The countable computable reals are the performed/describable register; the non-enumerable becoming-continuum is the operational “ $\mathbb{R}$ ” of the Brouwer path; the classical line is the formal-register referent. Which is canonical for the VR continuum is the programme’s open Bishop/Brouwer question; this work commits the set universe to the Brouwer (non-enumerable) reading.

6 Cardinality, the diagonal, and choice — the corrected core

This section replaces the central claims of the earlier §VI.

6.1 The operational universe is non-enumerable

Theorem 6.1 (Non-enumerability of the universe; `universe_not_enumerable`). *No $\mathbb{N}$ -indexed enumeration of operational sets is surjective up to operational identity: $\neg \exists e : \mathbb{N} \rightarrow \text{OpSet}, \forall x, \exists n, e n \approx x$. The proof is choice-free (*propext* only).*

The proof is a self-contained Cantor diagonal inside the operational universe. Given a candidate e , form the diagonal set $D := \{vn n \mid vn n \notin en\}$, a legitimate operational set (a sup over the subtype of indices n with $vn n \notin en$; no decidability is needed). By the distinctness of the naturals (Theorem 5.1), $vn k \in D \iff vn k \notin ek$. If e were surjective, some $em \approx D$, whence by extensionality $vn m \in em \iff vn m \notin em$ — a contradiction.

This is the Brouwerian content of VR-Sets. The diagonal does not fail and the universe is not countable. (To be precise: the non-enumerability *theorem* is not itself Brouwerian — the same diagonal works classically; what is Brouwerian is its *profile* — *propext*-only, choice-free — and the contrast with the countable `Desc` register of §6.2.) Its meaning is the cut between the *done* and the *becoming*: the countable register of what has been performed never exhausts the universe of sets as becoming. (In the operational-continuum work the same phenomenon appears for the power set of ω : the characteristic functions $\mathbb{N} \rightarrow \text{Bool}$ are non-enumerable, choice-free.)

6.2 The describable register is countable

Definition 6.2 (Finite descriptions; `Desc`, `IsDescribable`). *Let `Desc` be the finite inductive syntax with constructors $\emptyset$, `pair`, `union`, ω , and let `eval`: `Desc` $\rightarrow$ `OpSet` be its interpretation. A set x is describable if $x \approx \text{eval } d$ for some $d : \text{Desc}$.*

Theorem 6.3 (The describable register is countable; `describable_countable`). *There is an $\mathbb{N}$ -indexed enumeration reaching every describable set (up to $\approx$), exhibited as $n \mapsto \text{eval}(\text{decoden})$.*

Remark 6.4 (`Desc` is a minimal representative of “finite rule”). `Desc` fixes one concrete finite syntax ($\{\emptyset, \text{pair}, \text{union}, \omega\}$, without Separation), so it is deliberately *narrower* than the intuitive “set given by a finite rule”. This is exactly why Theorems 6.1 and 6.3 do not collide: the diagonal D of §6.1 is itself given by a finite rule, yet it is *not* expressible in `Desc`. The contrast is robust under this choice: *any* fixed finite syntax yields a countable register, and the same diagonal escapes it. `Desc` is a minimal witness of the schema “done = countable”, not an exhaustion of the notion of description.

Remark 6.5 (Honest axiom note). Theorem 6.3 is the only object in the development that depends on `Classical.choice`, and the dependence is *borrowed*, not intrinsic. It enters solely through `mathlib`’s proof that the natural-number pairing is invertible (`Nat.unpair_pair`/`Nat.pair_eq_pair` use choice; `Nat.pair` itself is axiom-free). The fact is constructively true; `mathlib` merely proves it with incidental choice. We keep the theorem and record the cost. The countability of a register of descriptions is in any case a statement of the *formal register* — meta-accounting over a finite syntax — where classical reasoning is admitted with its cost made visible.

Theorems 6.1 and 6.3 together are the corrected §VI: the earlier “the operational universe is countable, hence AC is free” is false; the correct statement is the contrast — the describable (done) register is countable, the universe (becoming) is not.

6.3 The Axiom of Choice is not a theorem

The earlier §VI argued that AC holds because the universe is countable, so every family can be enumerated and “the first element of each” chosen. That argument is unsound: its premise (every

family has a countable enumeration) is exactly what Theorem 6.1 refutes. “AC is free” and “the continuum is genuinely uncountable” are two settings of one switch, and the VR cycle has set it on the Brouwer side. The honest operational picture:

- **Dependent choice** is operational and choice-free: a history-dependent rule determines a branch by recursion (the `operational_dependent_choice` of the continuum work).
- **Weak continuity (WC-N)** holds operationally for finite-information functionals (machine-checked there) and is classically false — the cleanest two-register exhibit.
- **Full AC** — a selection over an uncountable family with no rule — has no operational correlate. It is a label of the formal register, not an operational theorem.

6.4 Why Banach–Tarski does not arise — through conservativity, not counting

The earlier text located the absence of Banach–Tarski in the countability of the universe. With countability gone, the explanation must change — and the correct one is sharper and ties VR-Sets to VR-Forms. The Banach–Tarski construction is a form applied to a form ($T \rightarrow T$): in the formal register it builds a completed uncountable totality (the sphere as a set of points) with a selection by full AC (the Vitali set). Neither ingredient has an operational correlate: the completed uncountable totality is a formal-register referent, and full AC a formal-register label. By the invariance of the operational under the application of form — the ground of VR-Forms’ conservativity result, itself machine-checked — a formal-register construction does not transit to the operational register: form has no power to manufacture an operational object where none was built. The paradox lives entirely in the formal register and never returns through the operational floor. Its absence is a conservativity phenomenon, not a cardinality accident.

There is, moreover, a precise classical anchor. Solovay (1970) showed that $\text{ZF} + \text{DC} +$ “every set of reals is Lebesgue measurable” is consistent (relative to an inaccessible cardinal); in that model the Banach–Tarski paradox *provably fails*. The operational regime — dependent choice yes, full AC no (§6.3) — lands in exactly that territory. So the absence is not only a conservativity phenomenon but one with known metamathematical backing: Banach–Tarski is not derivable in the choice regime the operational register supports. (This is an anchor, not an identification — the operational register is not claimed to *be* Solovay’s model; the point is that its choice profile sits where the paradox is known to be underivable.)

7 Position and honest boundaries

What is established. The operational universe of sets is built without classical scaffolding: a set is a revealing functionality, identity is a witnessed bisimulation (no quotient), and on this carrier membership, strong extensionality, $\emptyset$, pairing, union, the power set, ω , Separation and Replacement, the distinctness of the naturals, Anti-Foundation (decoration of any graph, unique up to $\approx$; axiom-free), and the predicate character of well-foundedness are all machine-checked — almost entirely axiom-free or **propext**-only (the power set is **propext**, choice-free, though impredicative; Remark 3.10). **OpSet** thus verifies every axiom of ZF without Foundation and locates the ZFC and the ZFA universes as two fragments of one carrier (the precise, two-register sense in which it holds them is stated next). The corrected cardinality core (universe non-enumerable; describable register countable) is machine-checked, the substantive half choice-free.

The two registers, and the exact relation to ZFA. The relation of OpSet to the classical theories is stated most precisely through VR’s two registers. VR’s *operational* register is an unconditional, choice-free constructive ground; its *formal* register admits — as a first-class but conditional, cost-tagged act — any consistent posit (the axiom of choice, actual infinity, the uncountable). **With the formal register on** (classical logic, choice), the set layer of OpSet *realises* Aczel’s ZFA (that is, ZF^- with the Anti-Foundation Axiom — non-well-founded sets by self-membership, not by urelements) and is therefore **equal to ZFA in strength: equiconsistent, at the level of ZF** — neither stronger nor weaker. Within it ZFC is recovered as the well-founded inner class $\{x : \text{IsGrounded } x\}$. **Without the formal register**, the operational core is strictly *weaker* — constructive and choice-free (nearer CZF + AFA), not full classical ZFA. Three provisos keep this exact. (i) It is realisation, not identity of theories: OpSet is a model that satisfies ZFA’s axioms, so it decides statements (e.g. CH) that ZFA leaves open; “= ZFA” is at the level of axioms and consistency strength, not of the deductive closure. (ii) The equality is for the *set layer*; VR as a whole is a proper enrichment of ZFA — it adds the operational register and a machine-checked cost ledger that plain ZFA has not. (iii) The one place VR is strictly *better* than ZFA, at equal strength, is the price of nesting: Anti-Foundation is here a *theorem*, axiom-free (§4.1), where ZFA must *posit* it — the same universe, obtained at lower axiomatic cost, because the carrier (pointed graphs up to bisimulation) makes self-membership definitional rather than assumed. (The pluralist framing — consistent theories as legitimate, ranked by strength — is not itself novel, cf. Hilbert, the set-theoretic multiverse; what is new is the sharp operational/formal line, native choice-free Anti-Foundation, and the per-posit machine-checked ledger.)

What is open or deferred.

- *Bishop vs Brouwer.* The computable $\mathbb{R}_{VR}$ (countable, done) and the non-enumerable becoming-continuum coexist (Remark 5.2); which is canonical for the VR continuum is the programme’s open question. This version commits the set universe to the Brouwer reading, consistently with the operational-continuum work.
- *The metalanguage.* Lean treats the underlying types classically; the operational reading is carried in the metalanguage and tracked by axiom profile. “Below the choice floor” is a statement about the construction’s audited dependencies, exhibited build-time, not a claim that the ambient logic is intuitionistic.
- *The borrowed choice.* The countability of the describable register inherits one `Classical.choice` from mathlib’s pairing inversion (Remark 6.5); removing it would mean re-deriving the arithmetic choice-free, orthogonal to the foundations and left aside.
- *Power set — impredicative, not choice-laden.* A completed power set $\wp x$ is constructible choice-free (§3.3, Theorem 3.9), but only impredicatively (Remark 3.10): the obstruction is impredicativity, not choice. The *predicative* content of $\wp(\omega)$ remains the becoming — the non-enumerable diagonal of §6. CH is a statement about a formal-register referent; it is read philosophically, not coded.
- *Impredicativity is invisible to the axiom audit (P-1).* Remark 3.10 isolates a new kind of boundary: the power set is choice-free yet impredicative, and `#print axioms` cannot see the impredicativity — it reports `propext` only. The operational register therefore needs a *second dimension* of accounting beyond the axiom profile; naming it (P-1) is the honest cost of the power set, alongside B-1/B-2 (the choice floor in $\mathbb{R}$ / `Fin`) and TR-R1 (the cost of the quotient).

- *The setoid tax.* Declining the quotient is a permanent discipline, not a one-time saving: every operation carries a congruence lemma (`*_congr`, `mem_congr`, `isGrounded_iff`), and every downstream use of `OpSet` pays it. This is the named price of staying below the choice floor — relational identity in exchange for a standing congruence obligation. We pay it deliberately, in keeping with the cycle’s discipline of naming prices.

Relation to the earlier version. Versions through 1.0.2 stand as the classical-surrogate presentation (the ZFC axioms realised over `ZFSet`); their §VI cardinality claims are superseded by §6 here. The mathematics genuinely machine-checked there (the ZFC axioms as closure facts over the surrogate) is unaffected; what is corrected is the operational reading of cardinality and choice.

Acknowledgement of AI assistance

This preprint and its companion Lean 4 formalisation were prepared with the assistance of Claude (Anthropic), in the Variant A architecture used across the VR cycle: a human curator directing a model that served as architect and implementer. All mathematical content, definitions, theorems, and foundational positions are due to the author, Vitaly Reznik. The operational set universe (`VRCycle.SetsOp`), the correction of §VI, the operational power set (§3.3), and this Version 1.1.0 were developed with Claude Opus 4.8.

References

- P. Aczel, *Non-Well-Founded Sets*, CSLI Lecture Notes 14, 1988.
- E. Bishop, *Foundations of Constructive Analysis*, McGraw–Hill, 1967.
- L. E. J. Brouwer, collected works on choice sequences and the continuum.
- R. M. Solovay, *A model of set-theory in which every set of reals is Lebesgue measurable*, *Annals of Mathematics* **92** (1970), 1–56.
- J. von Neumann, *Zur Einführung der transfiniten Zahlen*, 1923.
- V. Reznik, *VR. A Formal System: An Axiom-Free Reconstruction of Arithmetic from Operations Alone*. Zenodo, 2026. DOI 10.5281/zenodo.20633314 (concept 10.5281/zenodo.20212091); Lean companion DOI 10.5281/zenodo.20324240.
- V. Reznik, *VR-Numbers: Operational Superstructures ... over the Natural Numbers of VR*. Zenodo, 2026. DOI 10.5281/zenodo.20633626 (concept 10.5281/zenodo.20272025).
- V. Reznik, *VR-Forms: An Operational Two-Register Apparatus over VR-Sets*. Zenodo, 2026. DOI 10.5281/zenodo.20355939.
- V. Reznik, *VR-Sets-ZFA*. Zenodo, 2026. DOI 10.5281/zenodo.20369346.
- The VR Cycle Lean 4 formalisation, <https://github.com/inventor1975/VRCycle>, module `VRCycle.SetsOp`.