

matlab4jax

Run MATLAB code from JAX with `jax.jit` support.

Example

```
import jax
import jax.numpy as jnp
from jax import ShapeDtypeStruct

import matlab4jax

x = jnp.array([[1.0, 2.0],
               [3.0, 4.0]])

[y] = jax.jit(lambda x: matlab4jax.run_matlab(
    inputs=[x],
    input_names=["x"],
    command="y = inv(x);",
    output_names=["y"],
    abstract_outputs=[ShapeDtypeStruct(x.shape, x.dtype)]
))(x)

print(y)
```

Output:

```
[[ -2.0000002   1.0000001 ]
 [  1.5000001  -0.50000006]]
```

Installation

Pre-compiled wheels are available for MATLAB R2026a with Python 3.12 and Python 3.13.

If you are using a supported configuration, install with:

```
pip install matlab4jax
```

Otherwise, install from source:

```
pip install --no-binary matlab4jax matlab4jax
```

Shape convention

MATLAB and JAX use different conventions for array shapes. While JAX supports 0-dimensional and 1-dimensional arrays, in MATLAB every array has at least two dimensions. Additionally, MATLAB hides trailing singleton dimensions. The following conversions will be applied:

JAX shape	MATLAB shape
()	(1, 1)
(n,)	(1, n)
(..., 1)	(...)

License

Licensed under the [MIT License](#).

Matlab library path

On Linux, set the Matlab library path before importing, for example:

```
export
LD_LIBRARY_PATH=/usr/local/MATLAB/R2026a/extern/bin/glnxa64:$LD_LIBRARY_PATH
H
```

To make this setting persistent, add it to your `~/ .bashrc`:

```
echo 'export
LD_LIBRARY_PATH=/usr/local/MATLAB/R2026a/extern/bin/glnxa64:$LD_LIBRARY_PATH
H' >> ~/.bashrc
source ~/.bashrc
```