investoyard

API REFERENCE FOR EMPANELLED PARTNERS

Partner API

The print-forms contract: authentication, the full request field list, the response and the error codes — with curl, JavaScript and Python examples.

v1.0	POST	HTTPS	JSON
API version	/partner/v1/print-forms	Only, key per tenant	Request and response

Safal Capital Services Private Limited

v1.0 · October 2026

Authentication

Every request must carry an `X-Api-Key` header. The value is a compound of the key identifier and its secret, separated by a single dot:

HTTP HEADER — REQUIRED ON EVERY CALL

```
X-Api-Key: pk_a1b2c3d4.3f9e7c5b8a2d1e4f6c8b0a2d5e7f9c1b3a5d7e9f1c3b5a7d9e1f3c5b7a9d1e3f5
```

- **keyId** is public — it identifies which partner is calling. It is safe to log server-side.
- **secret** is confidential. Rotate it if leaked; the operator can revoke a key from the admin panel and issue a new one.
- Keys are **tenant-scoped**. A key issued to Partner X only reads and writes Partner X's data.
- Every successful call updates the key's `lastUsedAt` timestamp on a best-effort basis, for the operator's monitoring.

> ! **Never embed the secret in client-side code.** API keys grant server-to-server access under your tenant. Store the secret in a server-only environment variable, a secrets manager, or an equivalent vault; never in a mobile binary, browser bundle, or repository.

Base URL & versioning

Production base URL	`Issued with your API key`
API prefix	`/partner/v1`
Transport	HTTPS only. Plain HTTP requests are refused at the edge.
Content type	Request: `application/json` · Response: `application/json`

Versioning policy

The API lives under `/v1`. We version by **breaking change**, not by feature release. New optional request fields, new response fields, new endpoints, and new enum values on existing fields do **not** bump the version — v1 stays v1 as we add. We publish a new major version only when the shape of an existing field changes, an existing field is required to disappear, or auth semantics change.

Print forms

Store final application data and receive prefilled ASBA form(s) as one merged PDF. Applications land in the partner's tenant with `applyMethod: "pdf"`; form numbers come from the same per-IPO PDF series the operator's own applications use.

`POST` `/partner/v1/print-forms`

Request body

Two top-level fields: the IPO's ticker symbol and an array of applicants. Up to **100 applicants per request**. The endpoint returns one merged PDF with a page per applicant, in the order sent.

BODY — APPLICATION/JSON — EXAMPLE

```
{
  "ipoSymbol": "PERNIASPOP",
  "applicants": [
    {
```

```
      "fullName":    "Ananya Kapoor",
      "pan":         "AAAPK1234C",
      "depository":  "CDSL",
      "clientId":    "1201060012345678",
      "bankAccount": "123456789012",
      "bankName":    "HDFC Bank",
      "branchName":  "Andheri West",
      "address":     "12 Sea View Rd",
      "city":        "Mumbai",
      "state":       "Maharashtra",
      "pincode":     "400058",
      "email":       "ananya@example.com",
      "mobile":      "9820012345",
      "category":    "Retail",
      "lots":        2,
      "shareQty":    52,
      "sharePrice":  575,
      "amount":      29900
    }
  ]
}
```

TOP-LEVEL FIELDS

FIELD	TYPE	NOTES
• `ipoSymbol`	`string`	Ticker symbol as it appears in the catalog (e.g. `PERNIASPOP`). Case-insensitive.
• `applicants`	`Applicant[]`	1 to 100 applicants. See applicant schema below.

- Required

APPLICANT SCHEMA

Every applicant field is **optional**. Missing values print as blanks on the form. There is no schema-level validation on PAN format, demat length, bid amount, or category caps — the correctness of every value is the partner's responsibility.

FIELD	TYPE	NOTES
`fullName`	`string`	Applicant's full name as on the demat account.
`pan`	`string`	10-character PAN. Stored under your tenant's PII vault.
`depository`	`"NSDL" | "CDSL"`	Selects which demat identifier layout to print.
`dpId`	`string`	**NSDL only.** Format `IN` + 6 digits. For CDSL, leave blank.
`clientId`	`string`	NSDL: 8 digits. CDSL: 16-digit demat account number.
`bankAccount`	`string`	Bank account number for the ASBA block. Stored under your tenant's PII vault.
`bankName`	`string`	Bank name — printed on the form.
`branchName`	`string`	Branch name — printed on the form.
`address`	`string`	
`city`	`string`	
`state`	`string`	
`pincode`	`string`	

FIELD	TYPE	NOTES
email	string	
mobile	string	
familyGroup	string	Grouping label — fills the form's *FamilyGroup* box for print organisation.
category	enum	One of "Retail", "sHNI", "bHNI", "Shareholder", "Employee".
lots	integer ≥ 0	Number of lots bid. Printed verbatim.
shareQty	integer ≥ 0	Final share quantity. Printed verbatim.
sharePrice	number ≥ 0	Bid price per share.
amount	number ≥ 0	Total blocked amount in rupees.

The API does not accept `ifsc` or `upiId`. The printed ASBA form carries only Bank Account, Bank Name, and Branch Name — the block runs on the applicant's own bank statement (no interbank routing means IFSC has no role), and UPI is a separate electronic rail that does not appear on the physical form at all. Requests containing either field succeed but the values are silently discarded.

Response

`200 OK` The response body carries the list of created applications and the merged PDF as base64.

RESPONSE — APPLICATION/JSON — EXAMPLE (TRUNCATED)


```
{
  "ipoSymbol": "PERNIASPOP",
  "batchId":   "6b3f2d7c-1a4e-4b8c-9f2d-1e3c4b5a6d7f",
  "applications": [
    {
      "applicationRef": "clw3k9qx0000v7u01g5h8m2b",
      "formNo":         "PERNIASPOP-000042",
      "fullName":       "Ananya Kapoor",
      "category":       "Retail",
      "lots":           2,
      "amount":         29900
    }
  ],
  "filename":  "PERNIASPOP-2026-09-07-forms.pdf",
  "pdfBase64": "JVBERi0xLjcKJcTl8uXrp/Og0MTGCjQg…"
}
```


RESPONSE FIELDS

FIELD	TYPE	NOTES
ipoSymbol	string	Echoes the request.
batchId	string	UUID linking every application created in this call. Useful for reconciliation.
applications	object[]	One entry per applicant, in the order sent. Carries the assigned form number and the applicationRef (Investoyard's stable ID).
filename	string	Suggested filename for the merged PDF.
pdfBase64	string	The full merged PDF encoded as base64. Decode with `Buffer.from(str, 'base64')` or equivalent.

Examples

CURL

BASH

```bash
# Save the response body to disk, then extract the PDF.
curl https://<your-base-url>/partner/v1/print-forms \
  -H "Content-Type: application/json" \
  -H "X-Api-Key: pk_a1b2c3d4.3f9e7c5b…" \
  -d @request.json \
  -o response.json

jq -r '.pdfBase64' response.json | base64 -d > forms.pdf
```

NODE.JS

JAVASCRIPT

```javascript
import fs from 'node:fs/promises';

const res = await fetch('https://<your-base-url>/partner/v1/print-forms', {
  method: 'POST',
  headers: {
    'Content-Type': 'application/json',
    'X-Api-Key': process.env.INVESTOYARD_API_KEY,
  },
  body: JSON.stringify({
    ipoSymbol: 'PERNIASPOP',
    applicants: [ /* … */ ],
  }),
});

if (!res.ok) throw new Error(`${res.status} ${await res.text()}`);
const { pdfBase64, filename } = await res.json();
await fs.writeFile(filename, Buffer.from(pdfBase64, 'base64'));
```

PYTHON

PYTHON

```python
import os, base64, requests

r = requests.post(
    "https://<your-base-url>/partner/v1/print-forms",
    headers={"X-Api-Key": os.environ["INVESTOYARD_API_KEY"]},
    json={
        "ipoSymbol": "PERNIASPOP",
        "applicants": [ # … ],
    },
    timeout=60,
)
r.raise_for_status()
data = r.json()
with open(data["filename"], "wb") as f:
    f.write(base64.b64decode(data["pdfBase64"]))
```

Error responses

All errors are JSON with a machine-readable status code and a human-readable message. The `Content-Type` is `application/json`. HTTP status classes:

STATUS	MEANING	TYPICAL CAUSE
`400`	Bad request	The body failed schema validation, or the IPO is not accepting prints yet. Example: `"Form printing is not enabled for PERNIASPOP yet."`
`401`	Unauthorised	Missing `X-Api-Key`, malformed header (not `keyId.secret`), invalid or revoked key, or partner account not active.
`404`	Not found	No IPO in the catalog matches the `ipoSymbol` you sent.
`5xx`	Server error	Rare — retry with exponential backoff. If the error persists, contact support with the request timestamp; every request is logged for audit.

Example error body

RESPONSE — APPLICATION/JSON — 401 UNAUTHORISED

```
{
  "statusCode": 401,
  "message":    "Invalid or revoked API key.",
  "error":      "Unauthorized"
}
```

Investoyard is a product of **Safal Capital Services Private Limited**. The Partner API is provided to empanelled distribution partners only.