

@ISS COACHING DELHI SUNRISE CLASSES

SERVICE, TRUST & RESULT



SUNRISE CLASSES

70. The correct answer is a)

Explanation: The text that gets transformed is called plain text. The algorithm used is called cipher.

SUNRISE CLASSES ISS

SUNRISE CLASSES



SUNRISE CLASSES

11

Basic Of C-Programming

- Who is the father of C language?
 - Steve Jobs
 - James Gosling
 - Dennis Ritchie
 - Rasmus Lerdorf
- Which of the following is not a valid C variable name?
 - int number;
 - float rate;
 - int variable_count;
 - int \$main;
- All keywords in C are in _____
 - LowerCase letters
 - UpperCase letters
 - CamelCase letters
 - None of the mentioned
- Which of the following is true for variable names in C?
 - They can contain alphanumeric characters as well as special characters
 - It is not an error to declare a variable to be one of the keywords (like goto, static)
 - Variable names cannot start with a digit
 - Variable can be of any length
- Which is valid C expression?
 - int my_num = 100,000;
 - int my_num = 100000;
 - int my_num = 1000;
 - int \$my_num = 10000;
- Which of the following cannot be a variable name in C?
 - volatile
 - true
 - friend
 - export
- What is short int in C programming?
 - The basic data type of C
 - Qualifier
 - Short is the qualifier and int is the basic data type
 - All of the mentioned
- Which of the following declaration is not supported by C language?
 - String str;
 - char *str;
 - float str = 3e2;
 - Both "String str;" and "float str = 3e2;"
- Which keyword is used to prevent any changes in the variable within a C program?

@ISS COACHING DELHI SUNRISE CLASSES

SERVICE, TRUST & RESULT



SUNRISE CLASSES

- a) immutable
- b) mutable
- c) const
- d) volatile

10. What is the result of logical or relational expression in C?

- a) True or False
- b) 0 or 1
- c) 0 if an expression is false and any positive number if an expression is true
- d) None of the mentioned

11. Which of the following typecasting is accepted by C language?

- a) Widening conversions
- b) Narrowing conversions
- c) Widening & Narrowing conversions
- d) None of the mentioned

12. Where in C the order of precedence of operators do not exist?

- a) Within conditional statements, if, else
- b) Within while, do-while
- c) Within a macro definition
- d) None of the mentioned

13. Which of the following is NOT possible with any 2 operators in C?

- a) Different precedence, same associativity
- b) Different precedence, different associativity

- c) Same precedence, different associativity
- d) All of the mentioned

14. What is an example of iteration in C?

- a) for
- b) while
- c) do-while
- d) all of the mentioned

15. Functions can return enumeration constants in C?

- a) true
- b) false
- c) depends on the compiler
- d) depends on the standard

16. Functions in C Language are always _____

- a) Internal
- b) External
- c) Both Internal and External
- d) External and Internal are not valid terms for functions

17. Which of following is not accepted in C?

- a) static a = 10; //static as
- b) static int func (int); //parameter as static
- c) static static int a; //a static variable prefixed with static
- d) all of the mentioned

18. Property which allows to produce different executable for different platforms in C is called?

- a) File inclusion

@ISS COACHING DELHI SUNRISE CLASSES

SERVICE, TRUST & RESULT



SUNRISE CLASSES

b) Selective inclusion

c) Conditional compilation

d) Recursive macros

19. What is #include <stdio.h>?

a) Preprocessor directive

b) Inclusion directive

c) File inclusion directive

d) None of the mentioned

20. C preprocessors can have compiler specific features.

a) True

b) False

c) Depends on the standard

d) Depends on the platform

21. Which of the following are C preprocessors?

a) #ifdef

b) #define

c) #endif

d) all of the mentioned

22. The C-preprocessors are specified with _____ symbol.

a) #

b) \$

c) " "

d) &

23. How is search done in #include and #include "somelibrary.h" according to C standard?

a) When former is used, current directory is searched and when latter is used, standard directory is searched

b) When former is used, standard

directory is searched and when

latter is used, current directory is searched

c) When former is used, search is done in implementation defined manner and when latter is used,

current directory is searched

d) For both, search for 'somelibrary' is done in implementation-defined places

24. How many number of pointer (*) does C have against a pointer variable declaration?

a) 7

b) 127

c) 255

d) No limits

25. Which of the following is not possible statically in C language?

a) Jagged Array

b) Rectangular Array

c) Cuboidal Array

d) Multidimensional Array

26. Which of the following return-type cannot be used for a function in C?

a) char *

b) struct

c) void

d) none of the mentioned

27. The standard header _____ is used for variable list arguments (...) in C.

SUNRISE CLASSES ISS

SUNRISE CLASSES

@ISS COACHING DELHI SUNRISE CLASSES

SERVICE, TRUST & RESULT



SUNRISE CLASSES

- a) <stdio.h >
- b) <stdlib.h>
- c) <math.h>
- d) <stdarg.h>

28. When a C program is started, O.S environment is responsible for opening file and providing pointer for that file?

- a) Standard input
- b) Standard output
- c) Standard error
- d) All of the mentioned

29. In C language, FILE is of which data type?

- a) int
- b) char *
- c) struct
- d) None of the mentioned

30. What is the sizeof(char) in a 32-bit C compiler?

- a) 1 bit
- b) 2 bits
- c) 1 Byte
- d) 2 Bytes

31. Which of the following is not an operator in C?

- a) ,
- b) sizeof()
- c) ~
- d) None of the mentioned

32. scanf() is a predefined function in _____ header file.

- a) stdlib.h
- b) ctype.h

- c) stdio.h
- d) stdarg.h

33. What is meant by 'a' in the following C operation?

fp = fopen("Random.txt", "a");

- a) Attach
- b) Append
- c) Apprehend
- d) Add

34. What will be the output of the following C code?

```
1. #include <stdio.h>
2. int main()
3. {
4.     int y = 10000;
5.     int x = 34;
6.     printf("Hello World!
7.     %d\n", y);
8.     return 0;
9. }
```

- a) Compile time error
- b) Hello World! 34
- c) Hello World! 1000
- d) Hello World! followed by a junk value

35. What will happen if the following C code is executed?

```
1. #include <stdio.h>
```

@ISS COACHING DELHI SUNRISE CLASSES

SERVICE, TRUST & RESULT



SUNRISE CLASSES

- ```

2. int main()
3. {
4. int main = 3;
5. printf("%d", main);
6. return 0;
7. }

```
- a) It will cause a compile-time error  
b) It will cause a run-time error  
c) It will run without any error and prints 3  
d) It will experience infinite looping

36. What will be the output of the following C code?

- ```

1.   #include <stdio.h>
2.   int main()
3.   {
4.       signed char chr;
5.       chr = 128;
6.       printf("%d\n", chr);
7.       return 0;
8.   }

```

- a) 128
b) -128
c) Depends on the compiler
d) None of the mentioned

37. What will be the output of the following C code on a 64 bit machine?

- ```

1. #include <stdio.h>
2. union Sti
3. {
4. int nu;
5. char m;
6. };
7. int main()
8. {
9. union Sti s;
10. printf("%d", sizeof(s));
11. return 0;
12. }

```

- a) 8  
b) 5  
c) 9  
d) 4

38. What will be the output of the following C function?

- ```

1.   #include <stdio.h>
2.   enum birds {SPARROW,
                PEACOCK, PARROT};
3.   enum animals {TIGER = 8,
                  LION, RABBIT, ZEBRA};
4.   int main()
5.   {
6.       enum birds m = TIGER;
7.       int k;

```

@ISS COACHING DELHI SUNRISE CLASSES

SERVICE, TRUST & RESULT



SUNRISE CLASSES

```
8.    k = m;
9.    printf("%d\n", k);
10.   return 0;
11. }
```

- a) 0
- b) Compile time error
- c) 1
- d) 8

39. What will be the output of the following C code?

```
1.  #include <stdio.h>
2.  int const print()
3.  {
4.
5.      printf("Sanfoundry.com");
6.      return 0;
7.  }
8.  void main()
9.  {
10.     print();
11. }
```

- a) Error because function name cannot be preceded by const
- b) Sanfoundry.com
- c) Sanfoundry.com is printed infinite times
- d) Blank screen, no output

40. Will the following C code compile without any error?

```
1.  #include <stdio.h>
2.  int main()
3.  {
4.      for (int k = 0; k < 10; k++);
5.      return 0;
6.  }
```

- a) Yes
- b) No
- c) Depends on the C standard implemented by compilers
- d) Error

41. What will be the final value of x in the following C code?

```
1.  #include <stdio.h>
2.  void main()
3.  {
4.      int x = 5 * 9 / 3 + 9;
5.  }
```

- a) 3.75
- b) Depends on compiler
- c) 24
- d) 3

42. What will be the output of the following C code? (Initial values: x=7, y=8)

```
1.  #include <stdio.h>
2.  void main()
3.  {
4.      float x;
```

@ISS COACHING DELHI SUNRISE CLASSES

SERVICE, TRUST & RESULT



SUNRISE CLASSES

```
5.    int y;
6.    printf("enter two
       numbers \n");
7.    scanf("%f %f", &x, &y);
8.    printf("%f, %d", x, y);
9.    }
```

- a) 7.000000, 7
- b) Run time error
- c) 7.000000, junk
- d) Varies

43. What will be the output of the following C code considering the size of a short int is 2, char is 1 and int is 4 bytes?

```
1.    #include <stdio.h>
2.    int main()
3.    {
4.        short int i = 20;
5.        char c = 97;
6.        printf("%d, %d, %d\n",
               sizeof(i), sizeof(c), sizeof(c +
               i));
7.        return 0;
8.    }
```

- a) 2, 1, 2
- b) 2, 1, 1
- c) 2, 1, 4
- d) 2, 2, 8

44. What is the difference between the following 2 C codes?

```
1.    #include <stdio.h>
       //Program 1
2.    int main()
3.    {
4.        int d, a = 1, b = 2;
5.        d = a++ + ++b;
6.        printf("%d %d %d", d, a,
       b);
7.    }
```

```
1.    #include <stdio.h>
       //Program 2
2.    int main()
3.    {
4.        int d, a = 1, b = 2;
5.        d = a++ +++b;
6.        printf("%d %d %d", d, a,
       b);
7.    }
```

- a) No difference as space doesn't make any difference, values of a, b, d are same in both the case
- b) Space does make a difference, values of a, b, d are different
- c) Program 1 has syntax error, program 2 is not
- d) Program 2 has syntax error, program 1 is not

@ISS COACHING DELHI SUNRISE CLASSES

SERVICE, TRUST & RESULT



SUNRISE CLASSES

45. What will be the output of the following C code snippet?

```
1. #include <stdio.h>
2. void main()
3. {
4.     1 < 2 ? return 1: return 2;
5. }
```

- a) returns 1
- b) returns 2
- c) varies
- d) Compile time error

46. What will be the value of the following assignment expression?

(x = foo()) != 1 considering foo() returns 2

- a) 2
- b) True
- c) 1
- d) 0

47. What will be the output of the following C function?

```
1. #include <stdio.h>
2. void reverse(int i);
3. int main()
4. {
5.     reverse(1);
6. }
7. void reverse(int i)
```

```
8. {
9.     if (i > 5)
10.         return ;
11.     printf("%d ", i);
12.     return reverse((i++, i));
13. }
```

- a) 1 2 3 4 5
- b) Segmentation fault
- c) Compilation error
- d) Undefined behaviour

48. What will be the final values of i and j in the following C code?

```
1. #include <stdio.h>
2. int x = 0;
3. int f()
4. {
5.     if (x == 0)
6.         return x + 1;
7.     else
8.         return x - 1;
9. }
10. int g()
11. {
12.     return x++;
13. }
14. int main()
15. {
```

@ISS COACHING DELHI SUNRISE CLASSES

SERVICE, TRUST & RESULT



SUNRISE CLASSES

16. `int i = (f() + g()) | g();`
`//bitwise or`

17. `int j = g() | (f() + g());`
`//bitwise or`

18.}

- a) i value is 1 and j value is 1
- b) i value is 0 and j value is 0
- c) i value is 1 and j value is undefined
- d) i and j value are undefined

49. Comment on the following C statement.

`n = 1;`

`printf("%d, %dn", 3*n, n++);`

- a) Output will be 3, 2
- b) Output will be 3, 1
- c) Output will be 6, 1
- d) Output is compiler dependent

50. How many times i value is checked in the following C program?

1. `#include <stdio.h>`

2. `int main()`

3. `{`

4. `int i = 0;`

5. `while (i < 3)`

6. `i++;`

7. `printf("In while loop\n");`

8. `}`

a) 2

b) 3

c) 4

d) 1

51. What will be the output of the following C code?

1. `#include <stdio.h>`

2. `int main()`

3. `{`

4. `int i = 0;`

5. `do`

6. `{`

7. `i++;`

8. `if (i == 2)`

9. `continue;`

10. `printf("In while loop\n");`

11. `} while (i < 2);`

12. `printf("%d\n", i);`

13. `}`

- a) In while loop 2
- b) In while loop in while loop 3
- c) In while loop 3
- d) Infinite loop

52. What will be the data type returned for the following C function?

1. `#include <stdio.h>`

@ISS COACHING DELHI SUNRISE CLASSES

SERVICE, TRUST & RESULT



SUNRISE CLASSES

```
2.   int func()
3.   {
4.       return (double)(char)5.0;
5.   }
```

- a) char
- b) int
- c) double
- d) multiple type-casting in return is illegal

53. What is the problem in the following C declarations?

```
int func(int);

double func(int);

int func(float);
```

- a) A function with same name cannot have different signatures
- b) A function with same name cannot have different return types
- c) A function with same name cannot have different number of parameters
- d) All of the mentioned

54. Which option should be selected to work the following C expression?

```
string p = "HELLO";
```

- a) typedef char [] string;
- b) typedef char *string;
- c) typedef char [] string; and typedef char *string;
- d) Such expression cannot be generated in C

55. What is the meaning of the following C statement?

```
printf("%10s", state);
```

- a) 10 spaces before the string state is printed
- b) Print empty spaces if the string state is less than 10 characters
- c) Print the last 10 characters of the string
- d) None of the mentioned

56. What are the elements present in the array of the following C code?

```
int array[5] = {5};
```

- a) 5, 5, 5, 5, 5
- b) 5, 0, 0, 0, 0
- c) 5, (garbage), (garbage), (garbage), (garbage)
- d) (garbage), (garbage), (garbage), (garbage), 5

57. What will be the output of the following C function when EOF returns?

```
int fputs(char *line, FILE *fp)
```

- a) '?' character of array line is encountered
- b) 'n' character in array line is encountered
- c) 't' character in array line is encountered
- d) When an error occurs

@ISS COACHING DELHI SUNRISE CLASSES

SERVICE, TRUST & RESULT



SUNRISE CLASSES

58. Which part of the program address space is p stored in the following C code?

1. `#include <stdio.h>`
2. `int *p;`
3. `int main()`
4. `{`
5. `int i = 0;`
6. `p = &i;`
7. `return 0;`
8. `}`

- a) Code/text segment
- b) Data segment
- c) Bss segment
- d) Stack

59. Which of the following sequences are unaccepted in C language?

a)

```
#if
#else
#endif
```

b)

```
#if
#elif
#endif
```

c)

```
#if
```

```
#if
```

```
#endif
```

d)

```
#if
```

```
#undef
```

```
#endif
```

60. What is the output of this C code?

1. `#include <stdio.h>`
2. `main()`
3. `{`
4. `if (sizeof(int) > -1)`
5. `printf("True");`
6. `else`
7. `printf("False");`
8. `}`

a) True

b) False

61. What is the output of this C code?

1. `#include <stdio.h>`
2. `main()`
3. `{`
4. `char *p = "Sanfoundry C-Test";`
5. `p[0] = 'a';`
6. `p[1] = 'b';`

SUNRISE CLASSES ISS

SUNRISE CLASSES

@ISS COACHING DELHI SUNRISE CLASSES

SERVICE, TRUST & RESULT



SUNRISE CLASSES

7. `printf("%s", p);`

8. `}`

a) abnfoundry C-Test

b) Sanfoundry C-Test

c) Compile time error

d) Run time error

62. What is the output of this C code?

1. `#include <stdio.h>`

2. `int main()`

3. `{`

4. `float f = 0.1;`

5. `if (f == 0.1)`

6. `printf("True");`

7. `else`

8. `printf("False");`

9. `}`

a) True

b) False

63. What is the output of this C code?

1. `#include <stdio.h>`

2. `main()`

3. `{`

4. `int n = 0, m = 0;`

5. `if (n > 0)`

6. `if (m > 0)`

7. `printf("True");`

8. `else`

9. `printf("False");`

10. `}`

a) True

b) False

c) No Output will be printed

d) Run Time Error

64. What will be the output of the following C code?

1. `#include <stdio.h>`

2. `void main()`

3. `{`

4. `int x = 0;`

5. `if (x = 0)`

6. `printf("Its zero\n");`

7. `else`

8. `printf("Its not zero\n");`

9. `}`

a) Its not zero

b) Its zero

c) Run time error

d) None

65. What will be the output of the following C code?

1. `#include <stdio.h>`

2. `void main()`

3. `{`

SUNRISE CLASSES ISS

SUNRISE CLASSES

@ISS COACHING DELHI SUNRISE CLASSES

SERVICE, TRUST & RESULT



SUNRISE CLASSES

4. `int k = 8;`
 5. `int x = 0 == 1 && k++;`
 6. `printf("%d%d\n", x, k);`
 7. `}`
- a) 0 9
 b) 0 8
 c) 1 8
 d) 1 9
66. What will be the output of the following C code?
1. `#include <stdio.h>`
 2. `void main()`
 3. `{`
 4. `char a = 'a';`
 5. `int x = (a % 10)++;`
 6. `printf("%d\n", x);`
 7. `}`
- a) 6
 b) Junk value
 c) Compile time error
 d) 7
67. What will be the output of the following C code snippet?
1. `#include <stdio.h>`
 2. `void main()`
 3. `{`
 4. `1 < 2 ? return 1: return 2;`
 5. `}`
- a) returns 1
 b) returns 2
 c) Varies
 d) Compile time error
68. What will be the output of the following C code snippet?
1. `#include <stdio.h>`
 2. `void main()`
 3. `{`
 4. `unsigned int x = -5;`
 5. `printf("%d", x);`
 6. `}`
- a) Run time error
 b) Aries
 c) -5
 d) 5
69. What will be the output of the following C code?
1. `#include <stdio.h>`
 2. `int main()`
 3. `{`
 4. `int x = 2, y = 1;`
 5. `x *= x + y;`
 6. `printf("%d\n", x);`
 7. `return 0;`
 8. `}`
- a) 5
 b) 6

@ISS COACHING DELHI SUNRISE CLASSES

SERVICE, TRUST & RESULT



SUNRISE CLASSES

- c) Undefined behaviour
- d) Compile time error

70. What will be the output of the following C code?

```
1. #include <stdio.h>
2. int main()
3. {
4.     int x = 2, y = 2;
5.     x /= x / y;
6.     printf("%d\n", x);
7.     return 0;
8. }
```

- a) 2
 - b) 1
 - c) 0.5
 - d) Undefined behaviour
- [View Answer](#)

71. What will be the output of the following C code?

```
1. #include <stdio.h>
2. int main()
3. {
4.     int x = 1, y = 0;
5.     x &&= y;
6.     printf("%d\n", x);
7. }
```

- a) Compile time error
- b) 1

- c) 0
- d) Undefined behaviour

72. What will be the output of the following C code?

```
1. #include <stdio.h>
2. int main()
3. {
4.     int x = 2, y = 0;
5.     int z = (y++) ? y == 1 && x
6.             : 0;
7.     printf("%d\n", z);
8.     return 0;
9. }
```

- a) 0
- b) 1
- c) Undefined behaviour
- d) Compile time error

73. What will be the output of the following C code?

```
1. #include <stdio.h>
2. int main()
3. {
4.     int x = 1;
5.     int y = x == 1 ? getchar():
6.             2;
7.     printf("%d\n", y);
8. }
```

@ISS COACHING DELHI SUNRISE CLASSES

SERVICE, TRUST & RESULT



SUNRISE CLASSES

- a) Compile time error
- b) Whatever character getchar function returns
- c) Ascii value of character getchar function returns
- d) 2

74. What will be the output of the following C code?

```
1. #include <stdio.h>
2. int main()
3. {
4.     int x = 1;
5.     short int i = 2;
6.     float f = 3;
7.     if (sizeof((x == 2) ? f : i) ==
        sizeof(float))
8.         printf("float\n");
9.     else if (sizeof((x == 2) ? f :
        i) == sizeof(short int))
10.        printf("short int\n");
11. }
```

- a) float
- b) short int
- c) Undefined behaviour
- d) Compile time error

75. What will be the output of the following C code?

```
1. #include <stdio.h>
2. int main()
```

```
3. {
4.     int a = 2;
5.     int b = 0;
6.     int y = (b == 0) ? a : (a > b)
        ? (b = 1): a;
7.     printf("%d\n", y);
8. }
```

- a) Compile time error
- b) 1
- c) 2
- d) Undefined behaviour

76. What will be the output of the following C code?

```
1. #include <stdio.h>
2. int main()
3. {
4.     int y = 1, x = 0;
5.     int l = (y++, x++) ? y : x;
6.     printf("%d\n", l);
7. }
```

- a) 1
- b) 2
- c) Compile time error
- d) Undefined behaviour

77. What will be the output of the following C code?

```
1. #include <stdio.h>
2. void main()
```

@ISS COACHING DELHI SUNRISE CLASSES

SERVICE, TRUST & RESULT



SUNRISE CLASSES

```
3.  {
4.      int k = 8;
5.      int m = 7;
6.      int z = k < m ? k++ : m++;
7.      printf("%d", z);
8.  }
```

- a) 7
- b) 8
- c) Run time error
- d) 15

78. What will be the output of the following C code?

```
1.  #include <stdio.h>
2.  void main()
3.  {
4.      int k = 8;
5.      int m = 7;
6.      int z = k < m ? k = m :
      m++;
7.      printf("%d", z);
8.  }
```

- a) Run time error
- b) 7
- c) 8
- d) Depends on compiler

79. What will be the output of the following C code?

```
1.  #include <stdio.h>
```

```
2.  void main()
3.  {
4.      1 < 2 ? return 1 : return
      2;
5.  }
```

- a) returns 1
- b) returns 2
- c) Varies
- d) Compile time error

80. What will be the output of the following C code?

```
1.  #include <stdio.h>
2.  void main()
3.  {
4.      int x = 5;
5.      if (x < 1)
6.          printf("hello");
7.      if (x == 5)
8.          printf("hi");
9.      else
10.         printf("no");
11. }
```

- a) hi
- b) hello
- c) no

81. What will be the output of the following C code?

```
1.  #include <stdio.h>
```

@ISS COACHING DELHI SUNRISE CLASSES

SERVICE, TRUST & RESULT



SUNRISE CLASSES

2. int x;
 3. void main()
 4. {
 5. if (x)
 6. printf("hi");
 7. else
 8. printf("how are u");
 9. }
- a) hi
b) how are you
c) compile time error
d) error

82. What will be the output of the following C code?

1. #include <stdio.h>
2. void main()
3. {
4. int x = 5;
5. if (true);
6. printf("hello");
7. }

- a) It will display hello
b) It will throw an error
c) Nothing will be displayed
d) Compiler dependent

83. What will be the output of the following C code?

1. #include <stdio.h>

2. void main()
3. {
4. int x = 0;
5. if (x == 0)
6. printf("hi");
7. else
8. printf("how are u");
9. printf("hello");
10. }

- a) hi
b) how are you
c) hello
d) hihello

84. What will be the output of the following C code?

1. #include <stdio.h>
2. void main()
3. {
4. int x = 5;
5. if (x < 1);
6. printf("Hello");
7. }
8. }

- a) Nothing
b) Run time error
c) Hello
d) Varies

@ISS COACHING DELHI SUNRISE CLASSES

SERVICE, TRUST & RESULT



SUNRISE CLASSES

85. What will be the output of the following C code? (Assuming that we have entered the value 1 in the standard input)

```
1. #include <stdio.h>
2. void main()
3. {
4.     double ch;
5.     printf("enter a value
   between 1 to 2:");
6.     scanf("%lf", &ch);
7.     switch (ch)
8.     {
9.         case 1:
10.            printf("1");
11.            break;
12.        case 2:
13.            printf("2");
14.            break;
15.    }
16. }
```

- a) Compile time error
- b) 1
- c) 2
- d) Varies

86. What will be the output of the following C code? (Assuming that

we have entered the value 1 in the standard input)

```
1. #include <stdio.h>
2. void main()
3. {
4.     char *ch;
5.     printf("enter a value
   between 1 to 3:");
6.     scanf("%s", ch);
7.     switch (ch)
8.     {
9.         case "1":
10.            printf("1");
11.            break;
12.        case "2":
13.            printf("2");
14.            break;
15.    }
16. }
```

- a) 1
- b) 2
- c) Compile time error
- d) No Compile time error

87. What will be the output of the following C code? (Assuming that we have entered the value 1 in the standard input)

```
1. #include <stdio.h>
```

@ISS COACHING DELHI SUNRISE CLASSES

SERVICE, TRUST & RESULT



SUNRISE CLASSES

```

2. void main()
3. {
4.     int ch;
5.     printf("enter a value
        between 1 to 2:");
6.     scanf("%d", &ch);
7.     switch (ch)
8.     {
9.         case 1:
10.            printf("1\n");
11.            break;
12.            printf("Hi");
13.        default:
14.            printf("2\n");
15.    }
16. }
```

- a) 1
- b) 2
- c) 1 2
- d) Run time error

88. What will be the output of the following C code? (Assuming that we have entered the value 2 in the standard input)

```

1. #include <stdio.h>
2. void main()
3. {
4.     int ch;
5.     printf("enter a value
        between 1 to 2:");
```

```

6.     scanf("%d", &ch);
7.     switch (ch)
8.     {
9.         case 1:
10.            printf("1\n");
11.            break;
12.            printf("Hi");
13.        default:
14.            printf("2\n");
15.    }
16. }
```

- a) 1
- b) Hi 2
- c) Run time error
- d) 2

89. What will be the output of the following C code? (Assuming that we have entered the value 1 in the standard input)

```

1. #include <stdio.h>
2. void main()
3. {
4.     int ch;
5.     printf("enter a value
        between 1 to 2:");
6.     scanf("%d", &ch);
7.     switch (ch, ch + 1)
8.     {
```