

@ISS COACHING DELHI SUNRISE CLASSES

SERVICE, TRUST & RESULT



SUNRISE CLASSES

9. case 1:
10. `printf("1\n");`
11. `break;`
12. case 2:
13. `printf("2");`
14. `break;`
15. `}`
16. `}`
- a) 1
- b) 2
- c) 3
- d) Run time error
90. What will be the output of the following C code?
1. `#include <stdio.h>`
 2. `const int a = 1, b = 2;`
 3. `int main()`
 4. `{`
 5. `int x = 1;`
 6. `switch (x)`
 7. `{`
 8. `case a:`
 9. `printf("yes");`
 10. `case b:`
 11. `printf("no\n");`
 12. `break;`
 13. `}`
 14. `}`
- a) yes no
- b) yes
- c) no
- d) Compile time error
91. What will be the output of the following C code?
1. `#include <stdio.h>`
 2. `#define max(a) a`
 3. `int main()`
 4. `{`
 5. `int x = 1;`
 6. `switch (x)`
 7. `{`
 8. `case max(2):`
 9. `printf("yes\n");`
 10. `case max(1):`
 11. `printf("no\n");`
 12. `break;`
 13. `}`
 14. `}`
- a) yes no
- b) yes
- c) no
- d) Compile time error
92. What will be the output of the following C code?
1. `#include <stdio.h>`

@ISS COACHING DELHI SUNRISE CLASSES

SERVICE, TRUST & RESULT



SUNRISE CLASSES

```

2.  int main()
3.  {
4.      switch (printf("Do"))
5.      {
6.          case 1:
7.              printf("First\n");
8.              break;
9.          case 2:
10.             printf("Second\n");
11.             break;
12.             default:
13.                 printf("Default\n");
14.                 break;
15.         }
16.     }

```

- a) Do
- b) DoFirst
- c) DoSecond
- d) DoDefault

93. Comment on the output of the following C code.

```

1.  #include <stdio.h>
2.  int main()
3.  {
4.      int a = 1;
5.      switch (a)
6.      {
7.          case 1:

```

```

7.          printf("%d", a);
8.          case 2:
9.              printf("%d", a);
10.             case 3:
11.                 printf("%d", a);
12.                 default:
13.                     printf("%d", a);
14.             }

```

- a) No error, output is 1111
 - b) No error, output is 1
 - c) Compile time error, no break statements
 - d) Compile time error, case label outside switch statement
94. Which datatype can accept the switch statement?
- a) int
 - b) char
 - c) long
 - d) all of the mentioned

95. What will be the output of the following C code?

```

1.  #include <stdio.h>
2.  int main()
3.  {
4.      int a = 1;
5.      switch (a)
6.      {
7.          case a:

```

@ISS COACHING DELHI SUNRISE CLASSES

SERVICE, TRUST & RESULT



SUNRISE CLASSES

```
8.      printf("Case A ");
9.      default:
10.     printf("Default");
11.     }
12.     }
```

- a) Output: Case A
- b) Output: Default
- c) Output: Case A Default
- d) Compile time error

96. What will be the output of the following C code?

```
1.  #include <stdio.h>
2.  switch (ch)
3.  {
4.      case 'a':
5.      case 'A':
6.          printf("true");
7.      }
```

- a) if (ch == 'a' && ch == 'A') printf("true");
- b)

if (ch == 'a')

if (ch == 'a') printf("true");

- c) if (ch == 'a' || ch == 'A') printf("true");
- d) none of the mentioned

97. What will be the output of the following C code?

```
1.  #include <stdio.h>
2.  void main()
3.  {
4.      double k = 0;
5.      for (k = 0.0; k < 3.0; k++);
6.      printf("%lf", k);
7.  }
```

- a) 2.000000
- b) 4.000000
- c) 3.000000
- d) Run time error

98. What will be the output of the following C code?

```
1.  #include <stdio.h>
2.  void main()
3.  {
4.      int k;
5.      for (k = -3; k < -5; k++)
6.          printf("Hello");
7.  }
```

- a) Hello
- b) Infinite hello
- c) Run time error
- d) Nothing

99. What will be the output of the following C code?

```
1.  #include <stdio.h>
2.  int main()
```

@ISS COACHING DELHI SUNRISE CLASSES

SERVICE, TRUST & RESULT



SUNRISE CLASSES

```
3. {
4.     int i = 0;
5.     for ( ; ; )
6.         printf("In for loop\n");
7.         printf("After loop\n");
8. }
```

- a) Compile time error
- b) Infinite loop
- c) After loop
- d) Undefined behaviour

100. What will be the output of the following C code?

```
1. #include <stdio.h>
2. int main()
3. {
4.     int i = 0;
5.     for (i++; i == 1; i = 2)
6.         printf("In for loop ");
7.         printf("After loop\n");
8. }
```

- a) In for loop after loop
- b) After loop
- c) Compile time error
- d) Undefined behaviour

101. What will be the output of the following C code?

```
1. #include <stdio.h>
2. int main()
```

```
3. {
4.     int i = 0;
5.     for (foo(); i == 1; i = 2)
6.         printf("In for loop\n");
7.         printf("After loop\n");
8. }
9. int foo()
10. {
11.     return 1;
12. }
```

- a) After loop
- b) In for loop after loop
- c) Compile time error
- d) Infinite loop

102. What will be the output of the following C code?

```
1. #include <stdio.h>
2. int main()
3. {
4.     int *p = NULL;
5.     for (foo(); p; p = 0)
6.         printf("In for loop\n");
7.         printf("After loop\n");
8. }
```

- a) In for loop after loop
- b) Compile time error
- c) Infinite loop
- d) Depends on the value of NULL

@ISS COACHING DELHI SUNRISE CLASSES

SERVICE, TRUST & RESULT



SUNRISE CLASSES

103. What will be the output of the following C code?

```
1. #include <stdio.h>
2. int main()
3. {
4.     for (int i = 0; i < 1; i++)
5.         printf("In for loop\n");
6. }
```

- a) Compile time error
- b) In for loop
- c) Depends on the standard compiler implements
- d) Run time error

104. What will be the output of the following C code?

```
1. #include <stdio.h>
2. void main()
3. {
4.     char *str = "";
5.     do
6.     {
7.         printf("hello");
8.     } while (str);
9. }
```

- a) Nothing
- b) Run time error
- c) Varies
- d) Hello is printed infinite times

105. What will be the output of the following C code?

```
1. #include <stdio.h>
2. void main()
3. {
4.     int i = 0;
5.     while (i < 10)
6.     {
7.         i++;
8.         printf("hi\n");
9.         while (i < 8)
10.        {
11.            i++;
12.            printf("hello\n");
13.        }
14.    }
15. }
```

- a) Hi is printed 8 times, hello 7 times and then hi 2 times
- b) Hi is printed 10 times, hello 7 times
- c) Hi is printed once, hello 7 times
- d) Hi is printed once, hello 7 times and then hi 2 times

106. What is an example of iteration in C?

- a) for
- b) while

@ISS COACHING DELHI SUNRISE CLASSES

SERVICE, TRUST & RESULT



SUNRISE CLASSES

- c) do-while
d) all of the mentioned

107. How many times while loop condition is tested in the following C code snippets, if i is initialized to 0 in both the cases?

1. while (i < n)
2. i++;
3. -----
4. do
5. i++;
6. while (i <= n);

- a) n, n
b) n, n+1
c) n+1, n
d) n+1, n+1

108. What will be the output of the following C code?

1. #include <stdio.h>
2. int main()
3. {
4. int i = 0;
5. while (i = 0)
6. printf("True\n");
7. printf("False\n");
8. }

- a) True (infinite time)
b) True (1 time) False

- c) False
d) Compiler dependent

109. What will be the output of the following C code?

1. #include <stdio.h>
2. int main()
3. {
4. int i = 0, j = 0;
5. while (i < 5, j < 10)
6. {
7. i++;
8. j++;
9. }
10. printf("%d, %d\n", i, j);
11. }

- a) 5, 5
b) 5, 10
c) 10, 10
d) Syntax error

110. Which loop is most suitable to first perform the operation and then test the condition?

- a) for loop
b) while loop
c) do-while loop
d) none of the mentioned

111. What will be the output of the following C code?

1. #include <stdio.h>

@ISS COACHING DELHI SUNRISE CLASSES

SERVICE, TRUST & RESULT



SUNRISE CLASSES

2. void main()

3. {

4. int i = 0;

5. if (i == 0)

6. {

7. printf("Hello");

8. continue;

9. }

10. }

a) Hello is printed infinite times

b) Hello

c) Varies

d) Compile time error

112. What will be the output of the following C code?

1. #include <stdio.h>

2. void main()

3. {

4. int i = 0;

5. if (i == 0)

6. {

7. printf("Hello");

8. break;

9. }

10. }

a) Hello is printed infinite times

b) Hello

c) Varies

d) Compile time error

113. What will be the output of the following C code?

1. #include <stdio.h>

2. int main()

3. {

4. int i = 0;

5. do

6. {

7. i++;

8. if (i == 2)

9. continue;

10. printf("In while loop\n");

11. } while (i < 2);

12. printf("%d\n", i);

13. }

a) In while loop 2

b) In while loop in while loop 3

c) In while loop 3

d) Infinite loop

114. What will be the output of the following C code?

1. #include <stdio.h>

2. int main()

3. {

4. int i = 0, j = 0;

SUNRISE CLASSES ISS

SUNRISE CLASSES

@ISS COACHING DELHI SUNRISE CLASSES

SERVICE, TRUST & RESULT



SUNRISE CLASSES

```

5.   for (i; i < 2; i++){
6.       for (j = 0; j < 3; j++)
7.       {
8.           printf("1\n");
9.           break;
10.      }
11.      printf("2\n");
12.  }
13.  printf("after loop\n");
14.  }

```

a)

1

2

after loop

b)

1

after loop

c)

1

2

1

2

after loop

d)

1

1

2

after loop

115. What will be the output of the following C code?

1. #include <stdio.h>

2. int main()

3. {

4. int i = 0;

5. while (i < 2)

6. {

7. if (i == 1)

8. break;

9. i++;

10. if (i == 1)

11. continue;

12. printf("In while
loop\n");

13. }

14. printf("After loop\n");

15. }

a)

In while loop

After loop

b) After loop

c)

@ISS COACHING DELHI SUNRISE CLASSES

SERVICE, TRUST & RESULT



SUNRISE CLASSES

In while loop

In while loop

After loop

d) In while loop

116. What will be the output of the following C code?

```
1. #include <stdio.h>
2. int main()
3. {
4.     int i = 0;
5.     char c = 'a';
6.     while (i < 2)
7.     {
8.         i++;
9.         switch (c)
10.        {
11.            case 'a':
12.                printf("%c ", c);
13.                break;
14.                break;
15.        }
16.    }
17.    printf("after loop\n");
18. }
```

- a) a after loop
- b) a a after loop

c) after loop

d) error

117. What will be the output of the following C code?

```
1. #include <stdio.h>
2. int main()
3. {
4.     printf("before continue\n");
5.     continue;
6.     printf("after\n");
7. }
```

- a) Before continue after continue
- b) Before continue
- c) After continue
- d) Compile time error

118. What will be the output of the following C code?

```
1. #include <stdio.h>
2. void main()
3. {
4.     int i = 0;
5.     if (i == 0)
6.     {
7.         printf("Hello");
8.         continue;
9.     }
```

SUNRISE CLASSES ISS

SUNRISE CLASSES

@ISS COACHING DELHI SUNRISE CLASSES

SERVICE, TRUST & RESULT



SUNRISE CLASSES

10. }
- a) Hello is printed infinite times
b) Hello
c) Varies
d) Compile time error
119. What will be the output of the following C code?

```
1. #include <stdio.h>
2. void main()
3. {
4.     int i = 0;
5.     if (i == 0)
6.     {
7.         printf("Hello");
8.         break;
9.     }
10. }
```

- a) Hello is printed infinite times
b) Hello
c) Varies
d) Compile time error

120. What will be the output of the following C code?

```
1. #include <stdio.h>
2. int main()
3. {
4.     int i = 0;
5.     do
```

```
6.     {
7.         i++;
8.         if (i == 2)
9.             continue;
10.        printf("In while loop\n");
11.    } while (i < 2);
12.    printf("%d\n", i);
13. }
```

- a) In while loop 2
b) In while loop in while loop 3
c) In while loop 3
d) Infinite loop

121. What will be the output of the following C code?

```
1. #include <stdio.h>
2. int main()
3. {
4.     int i = 0, j = 0;
5.     for (i; i < 2; i++){
6.         for (j = 0; j < 3; j++)
7.         {
8.             printf("1\n");
9.             break;
10.        }
11.        printf("2\n");
12.    }
```

@ISS COACHING DELHI SUNRISE CLASSES

SERVICE, TRUST & RESULT



SUNRISE CLASSES

13. `printf("after loop\n");`
 14. `}`

a) 1

2

after loop

b) 1

after loop

c) 1

2

1

2

after loop

d) 1

1

2

after loop

122. What will be the output of the following C code?

1. `#include <stdio.h>`

2. `int main()`

3. `{`

4. `int i = 0;`

5. `while (i < 2)`

6. `{`

7. `if (i == 1)`

8. `break;`

9. `i++;`

10. `if (i == 1)`

11. `continue;`

12. `printf("In while
loop\n");`

13. `}`

14. `printf("After loop\n");`

15. `}`

a) In while loop

After loop

b) After loop

c) In while loop

In while loop

After loop

d) In while loop

123. What will be the output of the following C code?

1. `#include <stdio.h>`

2. `int main()`

3. `{`

4. `int i = 0;`

5. `char c = 'a';`

6. `while (i < 2)`

7. `{`

8. `i++;`

9. `switch (c)`

@ISS COACHING DELHI SUNRISE CLASSES

SERVICE, TRUST & RESULT



SUNRISE CLASSES

```

10.      {
11.          case 'a':
12.              printf("%c ", c);
13.              break;
14.              break;
15.      }
16.  }
17.  printf("after loop\n");
18.  }

```

- a) a after loop
- b) a a after loop
- c) after loop
- d) error

124. What will be the output of the following C code?

```

1.  #include <stdio.h>
2.  int main()
3.  {
4.      printf("before continue\n");
5.      continue;
6.      printf("after\n");
7.  }

```

- a) Before continue after continue
- b) Before continue
- c) After continue
- d) Compile time error

125. Which of the following can never be sent by call-by-value?

- a) Variable
- b) Array
- c) Structures
- d) Both Array and Structures

126. Which type of variables can have the same name in a different function?

- a) Global variables
- b) Static variables
- c) Function arguments
- d) Both static variables and Function arguments

View Answer

Answer: d

Explanation: None.

127. Arguments that take input by user before running a program are called?

- a) Main function arguments
- b) Main arguments
- c) Command-Line arguments
- d) Parameterized arguments

128. What is the maximum number of arguments that can be passed in a single function?

- a) 127
- b) 253
- c) 361
- d) No limits in number of arguments

129. What will be the output of the following C code?

```

1.  #include <stdio.h>

```

@ISS COACHING DELHI SUNRISE CLASSES

SERVICE, TRUST & RESULT



SUNRISE CLASSES

```

2. void m(int *p, int *q)
3. {
4.     int temp = *p; *p = *q; *q
   = temp;
5. }
6. void main()
7. {
8.     int a = 6, b = 5;
9.     m(&a, &b);
10.    printf("%d %d\n", a, b);
11. }

```

- a) 5 6
- b) 6 5
- c) 5 5
- d) 6 6

130. What will be the output of the following C code?

```

1. #include <stdio.h>
2. void m(int *p)
3. {
4.     int i = 0;
5.     for(i = 0; i < 5; i++)
6.         printf("%d\t", p[i]);
7. }
8. void main()
9. {
10.    int a[5] = {6, 5, 3};

```

```

11.    m(&a);
12. }

```

- a) 0 0 0 0 0
- b) 6 5 3 0 0
- c) Run time error
- d) 6 5 3 junk junk

131. What will be the output of the following C code?

```

1. #include <stdio.h>
2. void m(int p, int q)
3. {
4.     int temp = p;
5.     p = q;
6.     q = temp;
7. }
8. void main()
9. {
10.    int a = 6, b = 5;
11.    m(a, b);
12.    printf("%d %d\n", a, b);
13. }

```

- a) 5 6
- b) 5 5
- c) 6 5
- d) 6 6

132. What will be the output of the following C code?

```

1. #include <stdio.h>

```

@ISS COACHING DELHI SUNRISE CLASSES

SERVICE, TRUST & RESULT



SUNRISE CLASSES

```

2. void m(int p, int q)
3. {
4.     printf("%d %d\n", p, q);
5. }
6. void main()
7. {
8.     int a = 6, b = 5;
9.     m(a);
10. }
```

- a) 6
- b) 6 5
- c) 6 junk value
- d) Compile time error

133. What will be the output of the following C code?

```

1. #include <stdio.h>
2. void m(int p)
3. {
4.     printf("%d\n", p);
5. }
6. void main()
7. {
8.     int a = 6, b = 5;
9.     m(a, b);
10.    printf("%d %d\n", a, b);
11. }
```

- a) 6
- b) 6 5
- c) 6 junk value
- d) Compile time error

134. What will be output of the following C code where we copy an array 'a' into array 'b' and then the array 'b' into 'a'?

```

#include <stdio.h>
#include <string.h>

main()
{
    char a[] = "hell";
    char b[] = "hello";
    strcpy(b, a);
    strcpy(a, b);
    printf("%s, %s", a, b);
}
```

- a) hello, hello
- b) hell, hell
- c) hell, hello
- d) Runtime Error

135. Which keyword is used to make the array size optional in C language during array declaration?

- a) auto
- b) static
- c) extern
- d) register

@ISS COACHING DELHI SUNRISE CLASSES

SERVICE, TRUST & RESULT



SUNRISE CLASSES

136. Which of the following is the correct syntax to send an array as a parameter to a C function?

- a) Both `func(&array)` and `func(*array)`;
- b) Both `func(#array)` and `func(&array)`;
- c) Both `func(array)` and `func(&array)`;
- d) Both `func(array[size])` and `func(*array)`;

137. What are the different ways to initialize an array with all elements as zero?

- a) `int array[5] = {};`
- b) `int array[5] = {0};`
- c)

`int a = 0, b = 0, c = 0;`

`int array[5] = {a, b, c};`

- d) All of the mentioned

138. What are the elements present in the array of the following C code?

`int array[5] = {5};`

- a) 5, 5, 5, 5, 5
- b) 5, 0, 0, 0, 0
- c) 5, (garbage), (garbage), (garbage), (garbage)
- d) (garbage), (garbage), (garbage), (garbage), 5

139. Which of the following declaration is illegal?

- a) `int a = 0, b = 1, c = 2;`

`int array[3] = {a, b, c};`

- b) `int size = 3;`

`int array[size];`

- c) `int size = 3;`

`int array[size] = {1, 2, 3};`

- d) All of the mentioned

140. An array of similar data types which themselves are a collection of dissimilar data type are

- a) Linked Lists
- b) Trees
- c) Array of Structure
- d) All of the mentioned

141. Comment on an array of the void data type.

- a) It can store any data-type
- b) It only stores element of similar data type to first element
- c) It acquires the data type with the highest precision in it
- d) You cannot have an array of void data type

142. An array in C cannot be initialized by which of the following statement?

- a) `char a[] = "Hello";`
- b) `char a[6] = {};`
- c) `char a[6] = {0};`
- d) `char a[6]; a = "Hello";`

143. What is the data type of the array passed from the command

@ISS COACHING DELHI SUNRISE CLASSES

SERVICE, TRUST & RESULT



SUNRISE CLASSES

line into the main() function in C?

- a) char arr[];
- b) char *arr[];
- c) char **arr[];
- d) char arr[][];

144. Which of the following c statement will calculate the correct size of an array of 10 integers?

(Assuming the declaration as int a[10];)

- a) sizeof(a[10]);
- b) sizeof(*a);
- c) sizeof(a);
- d) sizeof(&a);

145. What will be the output of the following C code?

- ```
1. #include <stdio.h>
2. void main()
3. {
4. char *s = "hello";
5. char *p = s * 3;
6. printf("%c\t%c", *p,
7. s[1]);
8. }
```

- a) h e
- b) l e
- c) Compile time error
- d) l h

146. What will be the output of the following C code?

- ```
1. #include <stdio.h>
2. void main()
3. {
4.     char *s = "hello";
5.     char *p = s + 2;
6.     printf("%c\t%c", *p,
7.         s[1]);
8. }
```

- a) l e
- b) h e
- c) l l
- d) h l

147. What will be the output of the following C code?

- ```
1. #include <stdio.h>
2. int main()
3. {
4. void *p;
5. int a[4] = {1, 2, 3, 8};
6. p = &a[3];
7. int *ptr = &a[2];
8. int n = p - ptr;
9. printf("%d\n", n);
10. }
```

- a) 1
- b) Compile time error
- c) Segmentation fault
- d) 4

# @ISS COACHING DELHI SUNRISE CLASSES

## SERVICE, TRUST & RESULT



# SUNRISE CLASSES

148. What will be the output of the following C code?

```
1. #include <stdio.h>
2. int main()
3. {
4. void *p;
5. int a[4] = {1, 2, 3, 4};
6. p = &a[3];
7. int *ptr = &a[2];
8. int n = (int*)p - ptr;
9. printf("%d\n", n);
10. }
```

- a) 1
- b) Compile time error
- c) Segmentation fault
- d) 4

149. What will be the output of the following C code?

```
1. #include <stdio.h>
2. int main()
3. {
4. int a[4] = {1, 2, 3, 4};
5. int b[4] = {1, 2, 3, 4};
6. int n = &b[3] - &a[2];
7. printf("%d\n", n);
8. }
```

- a) -3
- b) 5
- c) 4
- d) Compile time error

150. What will be the output of the following C code?

```
1. #include <stdio.h>
2. int main()
3. {
4. int a[4] = {1, 2, 3, 4};
5. int *p = &a[1];
6. int *ptr = &a[2];
7. ptr = ptr * 1;
8. printf("%d\n", *ptr);
9. }
```

- a) 2
- b) 1
- c) Compile time error
- d) Undefined behaviour

151. What will be the output of the following C code?

```
1. #include <stdio.h>
2. int main()
3. {
4. int a[4] = {1, 2, 3, 4};
5. int *ptr = &a[2];
6. float n = 1;
7. ptr = ptr + n;
```

# @ISS COACHING DELHI SUNRISE CLASSES

SERVICE, TRUST & RESULT



## SUNRISE CLASSES

8. `printf("%d\n", *ptr);`  
9. `}`

- a) 4
- b) 3
- c) Compile time error
- d) Undefined behaviour

152. What will be the output of the following C code?

```
1. #include <stdio.h>
2. int main()
3. {
4. int a[4] = {1, 2, 3, 4};
5. void *p = &a[1];
6. void *ptr = &a[2];
7. int n = 1;
8. n = ptr - p;
9. printf("%d\n", n);
10. }
```

- a) 1
- b) 4
- c) Compile time error
- d) Depends on the compiler

153. Which is the correct syntax to use typedef for struct?

```
a) typedef struct temp
{
 int a;
}TEMP;
```

b) typedef struct

```
{
 int a;
}TEMP;
```

c) struct temp

```
{
 int a;
};
```

typedef struct temp TEMP;

d) All of the mentioned

154. Which option should be selected to work the following C expression?

`string p = "HELLO";`

- a) `typedef char [] string;`
- b) `typedef char *string;`
- c) `typedef char [] string;` and `typedef char *string;`
- d) Such expression cannot be generated in C

155. Which of the given option is the correct method for initialization?

`typedef char *string;`

- a) `*string *p = "Hello";`
- b) `string p = "Hello";`
- c) `*string p = 'A';`
- d) Not more than one space should be given when using typedef

# @ISS COACHING DELHI SUNRISE CLASSES

## SERVICE, TRUST & RESULT



# SUNRISE CLASSES

156. Which of the following is false about typedef?

- a) typedef follow scope rules
- b) typedef defined substitutes can be redefined again. (Eg: typedef char a; typedef int a;)
- c) You cannot typedef a typedef with other term
- d) All of the mentioned

157. Which of the following may create problem in the typedef program?

- a) ,
- b) printf/scanf
- c) Arithmetic operators
- d) All of the mentioned

158. typedef int (\*PFI)(char\*, char\*) creates \_\_\_\_\_

- a) type PFI, for pointer to function (of two char \* arguments) returning int
- b) error
- c) type PFI, function (of two char \* arguments) returning int
- d) type PFI, for pointer

159. What is typedef declaration?

- a) Does not create a new type
- b) It merely adds a new name for some existing type
- c) Does not create a new type, It merely adds a new name for some existing type
- d) None of the mentioned

160. What will be the output of the following C code?

1. #include <stdio.h>
2. typedef struct student
3. {
4. char \*a;
5. }stu;
6. void main()
7. {
8. stu s;
9. s.a = "hi";
10. printf("%s", s.a);
11. }s

- a) Compile time error
- b) Varies
- c) hi
- d) h

161. Which of the following fopen() statements are illegal?

- a) fp = fopen("abc.txt", "r");
- b) fp = fopen("/home/user1/abc.txt", "w");
- c) fp = fopen("abc", "w");
- d) none of the mentioned

162. What does the following segment of code do?

```
fprintf(fp, "Copying!");
```

# @ISS COACHING DELHI SUNRISE CLASSES

## SERVICE, TRUST & RESULT



# SUNRISE CLASSES

- a) It writes "Copying!" into the file pointed by fp  
 b) It reads "Copying!" from the file and prints on display  
 c) It writes as well as reads "Copying!" to and from the file and prints it  
 d) None of the mentioned

163. What is FILE reserved word?

- a) A structure tag declared in stdio.h  
 b) One of the basic data types in c  
 c) Pointer to the structure defined in stdio.h  
 d) It is a type name defined in stdio.h

164. What will be the output of the following C code?

- ```
1. #include <stdio.h>
2. int main()
3. {
4.     FILE *fp = stdin;
5.     int n;
6.     fprintf(fp, "%d", 45);
7. }
```

- a) Compilation error
 b) 45
 c) Nothing
 d) Depends on the standard

165. What will be the output of the following C code?

- ```
1. #include <stdio.h>
```

- ```
2. #include <stdlib.h>
3. int main()
4. {
5.     FILE *fp = stdout;
6.     int n;
7.     fprintf(fp, "%d", 45);
8. }
```

a) Compilation error

b) 45

c) Nothing

d) Depends on the standard

166. stdout, stdin and stderr are

- a) File pointers
 b) File descriptors
 c) Streams
 d) Structure

167. Which of the following statements about stdout and stderr are true?

- a) Same
 b) Both connected to screen always
 c) Both connected to screen by default
 d) stdout is line buffered but stderr is unbuffered

168. What will be the output of the following C code?

- ```
1. #include <stdio.h>
2. int main()
```