

@ISS COACHING DELHI SUNRISE CLASSES

SERVICE, TRUST & RESULT



SUNRISE CLASSES

```
3. {
4.     FILE *fp = stdout;
5.     int n;
6.     fprintf(fp, "%d ", 45);
7.     fprintf(stderr, "%d ", 65);
8.     return 0;
9. }
```

- a) 45 65
- b) 65 45
- c) 65
- d) Compilation error

169. What will be the output of the following C code?

```
1. #include <stdio.h>
2. int main()
3. {
4.     FILE *fp = stdout;
5.     int n;
6.     fprintf(fp, "%d\n ", 45);
7.     fprintf(stderr, "%d ", 65);
8.     return 0;
9. }
```

- a) 45 65
- b) 65 45
- c) 65
- d) Compilation error

170. What will be the output of the following C code?

```
1. #include <stdio.h>
2. int main()
3. {
4.     FILE *fp = stdout;
5.     int n;
6.     fprintf(fp, "%d ", 45);
7.     fflush(stdout);
8.     fprintf(stderr, "%d", 65);
9.     return 0;
10. }
```

- a) 45 65
- b) 65 45
- c) 45
- d) Compilation error

171. Which of the following mathematical function requires 2 parameter for successful function call?

- a) fmod();
- b) div();
- c) atan2();
- d) all of the mentioned

172. Which mathematical function among the following does NOT require int parameters?

- a) div(x, y);
- b) srand(x);
- c) sqrt(x);
- d) all of the mentioned

173. What will sin(x) returns?

- a) sine of x where x is in radians

@ISS COACHING DELHI SUNRISE CLASSES

SERVICE, TRUST & RESULT



SUNRISE CLASSES

- b) sine of x where x is in degree
c) cosine of x where x is in radians
d) cosine of x where x is in degree

174. What will $\cos(x)$ return?

- a) sine of x where x is in radians
b) sine of x where x is in degree
c) cosine of x where x is in radians
d) cosine of x where x is in degree

175. What will be the output of the following C code?

```
1. #include <stdio.h>
2. #include <math.h>
3. void main()
4. {
5.     int k = pow(2, 3);
6.     printf("%d\n", k);
7. }
```

- a) 9
b) 8
c) -1
d) 6

176. What will be the output of the following C code?

```
1. #include <stdio.h>
2. #include <math.h>
3. void main()
4. {
5.     int k = fabs(-87);
6.     printf("%d\n", k);
```

7. }

- a) -87
b) 87
c) 78
d) error

177. What will be the output of the following C code?

```
1. #include <stdio.h>
2. #include <math.h>
3. void main()
4. {
5.     int k = sqrt(-4);
6.     printf("%d\n", k);
7. }
```

- a) -2
b) 2
c) Compile time error
d) NaN

178. Which among the following mathematical function do not have a "double" return-type?

- a) $\text{srand}(x)$;
b) $\text{ceil}(x)$;
c) $\text{floor}(x)$;
d) both $\text{ceil}(x)$; and $\text{floor}(x)$;

179. What will be the output of the following C code?

```
1. #include <stdio.h>
2. #include <stdlib.h>
3. int main()
```

@ISS COACHING DELHI SUNRISE CLASSES

SERVICE, TRUST & RESULT



SUNRISE CLASSES

```
4.  {
5.      printf("%d\n", rand() %
      1000);
6.      return 0;
7.  }
```

- a) Compile time error
- b) An integer between 0-1000
- c) An integer between 0-999 including 0 and 999
- d) An integer between 0-1000 including 1000

180. What will be the output of the following C code?

```
1.  #include <stdio.h>
2.  #include <stdlib.h>
3.  int main()
4.  {
5.      srand(9000);
6.      printf("%d\n", rand());
7.      return 0;
8.  }
```

- a) Compile time error
- b) An integer in the range 0 to RAND_MAX
- c) A double in the range 0 to 1
- d) A float in the range 0 to 1

181. What will be the output of the following C code?

```
1.  #include <stdio.h>
2.  int main()
3.  {
4.      printf("%d\n",
      srand(9000));
5.      return 0;
6.  }
```

- a) Compile time error
- b) An integer in the range 0 to 9000
- c) A float in the range 0 to 1
- d) A double in the range 0 to 9000

182. What will be the output of the following C code?

```
1.  #include <stdio.h>
2.  int main()
3.  {
4.      srand(time(NULL));
5.      printf("%d\n", rand());
6.      return 0;
7.  }
```

- a) Compile time error
- b) An integer in the range 0 to RAND_MAX
- c) A double in the range 0 to 1
- d) A float in the range 0 to 1

183. In the below C program, every time program is run different numbers are generated.

```
1.  #include <stdio.h>
```

@ISS COACHING DELHI SUNRISE CLASSES

SERVICE, TRUST & RESULT



SUNRISE CLASSES

```
2. #include <stdlib.h>
3. int main()
4. {
5.     printf("%d\n", rand());
6.     return 0;
7. }
```

- a) True
- b) False
- c) Depends on the platform
- d) Depends on the compiler

184. In the following C program, every time program is run different numbers are generated.

```
1. #include <stdio.h>
2. int main()
3. {
4.     srand(time(NULL));
5.     printf("%d\n", rand());
6.     return 0;
7. }
```

- a) True
- b) False
- c) Depends on the platform
- d) Depends on the compiler

185. Which of these is a correct way to generate numbers between 0 to 1(inclusive) randomly?

- a) `rand() / RAND_MAX`
- b) `rand() % 2`

- c) `rand(0, 1)`
- d) none of the mentioned

186. If by mistake you specify more number of arguments, the excess arguments will _____

- a) be ignored
- b) produce compile error
- c) produce run-time error
- d) produce logical error

187. What happens when zero flag is used with left justification?

- a) data is padded with zeros
- b) zero flag is ignored
- c) data is padded with blank spaces
- d) will give error

188. For floating point numbers, the precision flag specifies the number of decimal places to be printed.

When no precision modifier is specified, `printf()` prints _____

- a) six decimal positions
- b) five decimal positions
- c) four decimal positions
- d) three decimal positions

189. What will the given code result in `printf("\n you are \"awesome \"");?`

- a) compile error
- b) run-time error
- c) you are "awesome"
- d) you are awesome

190. What will be the output for the given code `printf("\n The number is %07d", 1212);`

@ISS COACHING DELHI SUNRISE CLASSES

SERVICE, TRUST & RESULT



SUNRISE CLASSES

- a) The number is 0001212
- b) The number is 1212
- c) The number is 1212
- d) The number is 1212000

191. What will be the output of the following code?

```
char t='N';
```

```
printf("\n %c\n %3c \n %5c",t,t,t);
```

- a) N
N
N
N
- b) N
N
N
N
- c) N
N
N
N
- d) N N N

192. Select the right explanation to the given code.

```
printf("%*.*f", 5,4,5700);
```

- a) the minimum field width has to be 4, the precision is given to be 5, and the value to be displayed is 5700
- b) the minimum field width is 5, the precision is 4, and the value to be displayed is 5700
- c) compile error
- d) run-time error

193. What will be the output of the following C code?

```
char str[] = "Hello Nancy";
```

```
printf("\n %.7s", str);
```

- a) Hello Nan
- b) Hello
- c) Hello N
- d) Hello Nancy

194. What will be the output of the following C code?

```
char str[] = "Too Good";
```

```
printf("\n %7s",str);
```

- a) Too Good
- b) Too G
- c) Too Go
- d) Too

195. What will be the output of the following C code?

```
printf("\n Output: %5d \t %x \t %x", 234,234,234);
```

- a) Output:234EA0xEA
- b) Output:00234 EA 0xEA
- c) Output: 234 EA 0xEA
- d) ERROR

196. Select the correct value of i from given options i=scanf("%d %d", &a, &b);

- a) 1
- b) 2
- c) 3
- d) No value assigned

@ISS COACHING DELHI SUNRISE CLASSES

SERVICE, TRUST & RESULT



SUNRISE CLASSES

197. If the user enters 1 3.2 s, what value will be returned by the scanf()?

scanf("%d %f %c", &s1, &s2, &s3);

- a) 1
- b) 2
- c) 3
- d) No return value

198. If the user enters 1 s 3.2, what value will be returned by the scanf()?

scanf("%d %f %c", &a, &b, &c);

- a) 1
- b) 2
- c) 3
- d) no return value

199. What error will be generated on using incorrect specifier for the datatype being read?

- a) compile error
- b) run-time error
- c) logical error
- d) no error

200. What is the prototype of scanf function?

- a) scanf("controlstring", arg1, arg2, arg3, ..., argn);
- b) scanf("control string", variable list);
- c) scanf(" variable list", control string);

d) scanf("arg1, arg2, arg3, ..., argn", control string);

201. Control string specifies the type and format of the data that has to be obtained from the keyboard.

- a) true
- b) false

202. What is the qualifying input for the type specifier G?

- a) floating point numbers
- b) floating point numbers in exponential format
- c) floating point numbers in the shorter of exponential format
- d) not a type specifier

203. scanf() is a predefined function in _____ header file.

- a) stdlib. h
- b) ctype. h
- c) stdio. h
- d) stdarg.

204. What does the C statement given below says?

scanf("%7s", ch);

- a) read string with minimum 7 characters.
- b) read string with maximum 7 characters
- c) read string exactly to 7 characters
- d) read string with any number of characters

SUNRISE CLASSES ISS

SUNRISE CLASSES

@ISS COACHING DELHI SUNRISE CLASSES

SERVICE, TRUST & RESULT



SUNRISE CLASSES

205. What is the meaning of the following C statement?

```
scanf("%[^\n]s", ch);
```

- a) read all character except new line
- b) read all characters
- c) read only new line character
- d) syntax error

206. what is the function of fputs()?

- a) read a line from a file
- b) read a character from a file
- c) write a character to a file
- d) write a line to a file

207. What does the following C code snippet mean?

```
char *gets(char *s)
```

- a) reads the next input line into the array s
- b) writes the line into the array s
- c) reads the next input character into the array s
- d) write a character into the array

208. Which function will return the current file position for stream?

- a) fgetpos()
- b) fseek()
- c) ftell()
- d) fsetpos()

209. Select the right explanation for the following C code snippet.

```
int fgetpos(FILE *stream, fpos_t *s)
```

- a) records the current position in stream in *s
- b) sets the file position for stream in *s
- c) positions stream at the position recorded in *s
- d) reads from stream into the array ptr

210. Which functions is declared in <errno.h>?

- a) fseek()
- b) ftell()
- c) ferror()
- d) fsetpos()

211. setvbuf() and setbuf() function controls buffering for the stream.

- a) true
- b) false

212. The functions vprintf(), fprintf(), and vsprintf() are not equivalent to the corresponding printf() functions except the variable argument list.

- a) true
- b) false

View Answer213.

The_____function reads atmost one less than the number of characters specified by size from the given stream and it is stored in the string str.

- a) fget()
- b) fgets()
- c) fput()
- d) fputs()

SUNRISE CLASSES ISS

SUNRISE CLASSES

@ISS COACHING DELHI SUNRISE CLASSES

SERVICE, TRUST & RESULT



SUNRISE CLASSES

214. What does the following C code snippet mean?

```
int ungetc(int c, FILE *stream)
```

- a) pushes c back onto a stream
- b) deletes c from the stream
- c) reads frequency of c in stream
- d) no action is taken by the command

215. Choose the correct difference between `getc()` and `fgetc()`.

- a) If it is not a macro, it may evaluate stream more than once
- b) if it is a macro, it may not evaluate stream more than once
- c) if it is a macro, it may evaluate stream more than once
- d) no difference between `fgetc()` and `getc()`

216. Which among the following is never possible in C when members are different in a structure and union?

```
//Let P be a structure
```

```
//Let Q be a union
```

- a) `sizeof(P)` is greater than `sizeof(Q)`
- b) `sizeof(P)` is less than `sizeof(Q)`
- c) `sizeof(P)` is equal to `sizeof(Q)`
- d) none of the mentioned

217. Which among the following is never possible in C when members in a structure are the same as that in a union?

```
//Let P be a structure
```

```
//Let Q be a union
```

- a) `sizeof(P)` is greater than `sizeof(Q)`
- b) `sizeof(P)` is equal to `sizeof(Q)`
- c) `sizeof(P)` is less than `sizeof(Q)`
- d) none of the mentioned

218. What will be the size of the following C structure?

```
1. #include <stdio.h>
2. struct temp
3. {
4.     int a[10];
5.     char p;
6. };
```

- a) 5
- b) 11
- c) 41
- d) 44

219. What will be the output of the following C code?

```
1. #include <stdio.h>
2. main()
3. {
4.     int a = 1;
5.     printf("size of a is %d",
6.           sizeof(++a));
7.     printf("value of a is %d",
8.           a);
```

@ISS COACHING DELHI SUNRISE CLASSES

SERVICE, TRUST & RESULT



SUNRISE CLASSES

219. `};`

- a) size of a is 4, value of a is 1
- b) size of a is 4, value of a is 2
- c) size of a is 2, value of a is 2
- d) size of a is 2, value of a is 2

220. Which among the following statement is right?

- a) `sizeof(struct stemp*) > sizeof(union utemp*) > sizeof(char*)`
- b) `sizeof(struct stemp*) < sizeof(union utemp*) < sizeof(char*)`
- c) `sizeof(struct stemp*) = sizeof(union utemp*) = sizeof(char*)`
- d) the order Depends on the compiler

221. What will be the output of the following C code?

```
1. #include <stdio.h>
2. printf("%d",
   sizeof(strlen("HELLOWORLD")));
```

- a) Output, 4
- b) Output, 10
- c) Output, 16
- d) Error, sizeof cannot evaluate size of a function

222. Which of the following cannot be used inside sizeof?

- a) pointers
- b) functions

c) macro definition

d) none of the mentioned

223. What will be the output of the following C code?

```
1. #include <stdio.h>
2. (sizeof double = 8, float = 4,
   void = 4)
3. #define PI 3.14
4. int main()
5. {
6.     printf("%d", sizeof(PI));
7. }
```

- a) Output is 8
- b) Output is 4
- c) Output is 1
- d) Error, we can't use sizeof on macro-definitions

224. What is the primary focus of frontend development?

- a) Server configuration
- b) User interface and user experience
- c) Database design
- d) Back-end optimization

225. Which programming languages are commonly used for frontend development?

- a) Python and Ruby
- b) JavaScript, HTML, and CSS

@ISS COACHING DELHI SUNRISE CLASSES

SERVICE, TRUST & RESULT



SUNRISE CLASSES

- c) Java and C++
d) PHP and SQL
226. What does HTML stand for?
- a) Hyper Transfer Markup Language
b) Hyper Text Markup Language
c) High-Level Text Markup Language
d) Home Tool Markup Language
227. Which technology is used for adding interactivity and dynamic behavior to web pages?
- a) HTML
b) CSS
c) JavaScript
d) PHP
228. What is the purpose of CSS (Cascading Style Sheets) in frontend development?
- a) To define the structure of a web page
b) To manage server-side logic
c) To style and format web page elements
d) To store data in a database
229. What is the primary responsibility of the backend in a web application?
- a) Handling user interface design
b) Managing client-side scripting
c) Processing server-side logic and data
d) Storing static files
230. Which programming languages are commonly used for backend development?
- a) HTML and CSS
b) JavaScript and TypeScript
c) Python, Ruby, and PHP
d) Java and C#
231. What is a common database management system (DBMS) used in backend development?
- a) MongoDB
b) AngularJS
c) React
d) Bootstrap
232. What does REST stand for in the context of backend services?
- a) Reliable State Transfer
b) Representational State Transfer
c) Remote Server Testing
d) Rapid Environment Setup and Testing
233. Which of the following is NOT a typical task of a backend developer?

@ISS COACHING DELHI SUNRISE CLASSES

SERVICE, TRUST & RESULT



SUNRISE CLASSES

- a) Creating API endpoints
- b) Designing user interfaces
- c) Handling authentication and authorization
- d) Managing server infrastructure

234. What is the purpose of control structures in programming?

- a) To control the flow of electricity
- b) To manage the physical structure of a computer
- c) To specify the order of execution of statements
- d) To control the design of the user interface

235. Which control structure allows a block of code to be executed repeatedly as long as a certain condition is true?

- a) If-else statement
- b) Switch statement
- c) For loop
- d) Function declaration

236. In programming, what does "conditional branching" refer to?

- a) Executing code sequentially
- b) Choosing different paths in code execution based on conditions
- c) Jumping randomly between code segments

- d) Running code concurrently

237. Which of the following control structures is used for making decisions based on a condition?

- a) While loop
- b) Function call
- c) If-else statement
- d) For loop

238. What does a "break" statement do within a loop?

- a) Terminates the program
- b) Exits the current loop prematurely
- c) Skips the next iteration of the loop
- d) Restarts the loop from the beginning

239. Which control structure allows you to define a group of statements that will execute at least once, regardless of the condition?

- a) For loop
- b) If-else statement
- c) Switch statement
- d) Do-while loop

240. What is the purpose of the "switch" statement in programming?

@ISS COACHING DELHI SUNRISE CLASSES

SERVICE, TRUST & RESULT



SUNRISE CLASSES

a) To execute a block of code repeatedly

b) To handle exceptions and errors

c) To select one of many code blocks to be executed

d) To define custom functions

241. What is an "else if" statement used for in programming?

a) To check if a variable is undefined

b) To handle errors and exceptions

c) To provide an alternative condition to check when the initial condition is false

d) To declare a new function

242. In a "for" loop, what are the three components typically specified within the parentheses?

a) Condition, initialization, and increment

b) Start, end, and condition

c) Counter, termination, and increment

d) Iterator, step size, and condition

243. Which control structure is most suitable for iterating through elements in an array?

a) While loop

b) For loop

c) If-else statement

d) Switch statement

244. What is an exception in computer programming?

a) An unusual hardware malfunction

b) A runtime error or abnormal condition

c) A standard computer operation

d) A type of debugging tool

245. Which part of a program is responsible for handling exceptions?

a) The compiler

b) The operating system

c) The exception handler

d) The user interface

246. In most programming languages, what keyword is used to raise or throw an exception explicitly?

a) Catch

b) Try

c) Raise

d) Throw

SUNRISE CLASSES ISS

SUNRISE CLASSES

@ISS COACHING DELHI SUNRISE CLASSES

SERVICE, TRUST & RESULT



SUNRISE CLASSES

247. What is the purpose of the "try" block in exception handling?

- a) To define the exception
- b) To catch and handle exceptions
- c) To specify the default exception handler
- d) To declare variables

248. In exception handling, what is the role of the "catch" block?

- a) To throw an exception
- b) To handle exceptions by specifying how they should be managed

- c) To terminate the program
- d) To define a variable

249. What is a "checked exception" in Java and similar languages?

- a) An exception that occurs at runtime
- b) An exception that must be explicitly caught or declared
- c) An exception related to hardware failures

- d) An exception that is automatically handled

250. Which of the following is NOT a common category of exceptions?

- a) Arithmetic exceptions
- b) Logic exceptions

- c) Input/output exceptions
- d) Null pointer exceptions

251. What is the purpose of the "finally" block in exception handling?

- a) To raise an exception
- b) To catch exceptions
- c) To specify the order of execution

- d) To ensure that certain code is always executed, regardless of whether an exception occurs

252. What is the term for preventing exceptions by checking for potential issues in advance?

- a) Exception handling
- b) Error propagation
- c) Exception prevention
- d) Defensive programming

253. What does the acronym "OOP" stand for in the context of exceptions?

- a) Object-Oriented Programming
- b) Operation of Procedures
- c) Out-of-Place Exception
- d) Overflow and Overrun Protection



SUNRISE CLASSES

Explanation

1. The correct answer is c)
Explanation: Dennis Ritchie is the father of C Programming Language. C programming language was developed in 1972 at American Telephone & Telegraph Bell Laboratories of USA.

2. The correct answer is d)
Explanation: Since only underscore and no other special character is allowed in a variable name, it results in an error.

3. The correct answer is a)
Explanation: None.

4. The correct answer is c)
Explanation: According to the syntax for C variable name, it cannot start with a digit.

5. The correct answer is b)
Explanation: Space, comma and \$ cannot be used in a variable name.

6. The correct answer is a)
Explanation: volatile is C keyword.

7. The correct answer is c)
Explanation: None.

8. The correct answer is a)
Explanation: It is legal in Java, but not in C language.

9. The correct answer is c)
Explanation: const is a keyword constant in C program.

10. The correct answer is b)
Explanation: None.

11. The correct answer is c)
Explanation: None.

12. The correct answer is d)
Explanation: None.

13. The correct answer is c)
Explanation: None.

14. The correct answer is d)
Explanation: None.

15. The correct answer is a)
Explanation: None.

16. The correct answer is c)
Explanation: In C programming, functions can be defined and used both internally (within the same source file) and externally (across multiple source files) depending on how they are declared and defined. Internal functions are typically defined within the same source file, while external functions can be declared in one source file and defined in another, allowing them to be used across multiple source

@ISS COACHING DELHI SUNRISE CLASSES

SERVICE, TRUST & RESULT



SUNRISE CLASSES

files when properly linked during compilation.

17. The correct answer is c)
Explanation: None.

18. The correct answer is c)
Explanation: Conditional compilation is the preprocessor facility to produce a different executable.

19. The correct answer is a)
Explanation: None.

20. The correct answer is a)
Explanation: #pragma is compiler specific feature.

21. The correct answer is d)
Explanation: None.

22. The correct answer is a)
Explanation: The C preprocessors are specified with # symbol.

23. The correct answer is b)
Explanation: None.

24. The correct answer is d)
Explanation: None.

25. The correct answer is a)
Explanation: None.

26. The correct answer is a)
Explanation: None.

27. The correct answer is d)
Explanation: None.

28. The correct answer is d)
Explanation: None.

29. The correct answer is c)
Explanation: None.

30. The correct answer is c)
Explanation: None.

31. The correct answer is d)
Explanation: None.

32. The correct answer is c)
Explanation: scanf() is a predefined function in "stdio.h" header file printf and scanf() carry out input and output functions in C. These functions statements are present in the header file stdio.h.

33. The correct answer is b)
Explanation: None.

34. The correct answer is a)
Explanation: Since y is already defined, redefining it results in an error.

Output:
\$ cc pgm2.c
pgm2.c: In function 'main':
pgm2.c:5: error: redefinition of 'y'
pgm2.c:4: note: previous definition of 'y' was here

35. The correct answer is c)
Explanation: A C program can have same function name and same variable name.

\$ cc pgm3.c
\$ a.out
3

@ISS COACHING DELHI SUNRISE CLASSES

SERVICE, TRUST & RESULT



SUNRISE CLASSES

36. The correct answer is b)

Explanation: The range of signed character is from -128 to +127.

Since we are assigning a value of 128 to the variable 'chr', the result will be negative. 128 in binary is represented as "1000 0000" for character datatype. As you can see that the sign bit is set to 1, followed by 7 zeros (0), its final decimal value will be -128 (negative 128).

Output:

```
$ cc pgm2.c
```

```
$ a.out
```

```
-128
```

37. The correct answer is d)

Explanation: Since the size of a union is the size of its maximum data type, here int is the largest data type. Hence the size of the union is 4.

Output:

```
$ cc pgm7.c
```

```
$ a.out
```

```
4
```

38. The correct answer is d)

Explanation: m is an integer constant, hence it is compatible.

Output:

```
$ cc pgm5.c
```

```
$ a.out
```

```
8
```

39. The correct answer is b)

Explanation: None.

Output:

```
$ cc pgm13.c
```

```
$ a.out
```

```
Sanfoundry.com
```

40. The correct answer is c)

Explanation: Compilers implementing C90 do not allow this, but compilers implementing C99 allow it.

Output:

```
$ cc pgm4.c
```

```
pgm4.c: In function 'main':
```

```
pgm4.c:4: error: 'for' loop initial declarations are only allowed in C99 mode
```

```
pgm4.c:4: note: use option -std=c99 or -std=gnu99 to compile your code
```

41. The correct answer is c)

Explanation: None.

42. The correct answer is c)

Explanation: None.

43. The correct answer is c)

Explanation: None.

44. The correct answer is d)

Explanation: None.

45. The correct answer is d)

Explanation: None.

46. The correct answer is a)

Explanation: None.

47. The correct answer is a)

Explanation: None.

SUNRISE CLASSES ISS

SUNRISE CLASSES

@ISS COACHING DELHI SUNRISE CLASSES

SERVICE, TRUST & RESULT



SUNRISE CLASSES

48. The correct answer is c)

Explanation: None.

49. The correct answer is d)

Explanation: None.

50. The correct answer is c)

Explanation: None.

51. The correct answer is a)

Explanation: None.

52. The correct answer is b)

Explanation: None.

53. The correct answer is d)

Explanation: None.

54. The correct answer is b)

Explanation: None.

55. The correct answer is b)

Explanation: None.

56. The correct answer is b)

Explanation: None.

57. The correct answer is d)

Explanation: None.

58. The correct answer is c)

Explanation: None.

59. The correct answer is c)

Explanation: None.

60. The correct answer is b)

Output:

\$ cc pgm.c

\$ a.out

False

61. The correct answer is d)

Output:

\$ cc pgm.c

\$ a.out

Segmentation fault (core dumped)

62. The correct answer is b)

Output:

\$ cc pgm.c

\$ a.out

False

63. The correct answer is c)

Output:

\$ cc pgm.c

\$ a.out

\$

64. The correct answer is a)

Explanation: In the above C code, we assign a zero value to the variable x. In the if condition, we are reassigning a value of zero to x.

Remember, we are "NOT" comparing its values to zero (you can see that it is a single '=' sign, it's not a double '==' sign). Hence, the if-condition becomes false and the printf() function of the else condition will be executed which will display "Its not zero".

65. The correct answer is b)

Explanation: None.

66. The correct answer is c)

Explanation: None.

67. The correct answer is d)

Explanation: None.

SUNRISE CLASSES ISS

SUNRISE CLASSES

@ISS COACHING DELHI SUNRISE CLASSES

SERVICE, TRUST & RESULT



SUNRISE CLASSES

68. The correct answer is c)

Explanation: None.

69. The correct answer is b)

Explanation: None.

70. The correct answer is a)

Explanation: None.

71. The correct answer is a)

Explanation: None.

72. The correct answer is a)

Explanation: None.

73. The correct answer is c)

Explanation: None.

74. The correct answer is a)

Explanation: None.

75. The correct answer is c)

Explanation: None.

76. The correct answer is a)

Explanation: None.

77. The correct answer is a)

Explanation: None.

78. The correct answer is b)

Explanation: None.

79. The correct answer is d)

Explanation: None.

80. The correct answer is a)

Explanation: None.

81. The correct answer is b)

Explanation: None.

82. The correct answer is b)

Explanation: None.

83. The correct answer is d)

Explanation: None.

84. The correct answer is c)

Explanation: None.

85. The correct answer is a)

Explanation: None.

86. The correct answer is c)

Explanation: None.

87. The correct answer is c)

Explanation: None.

88. The correct answer is d)

Explanation: None.

89. The correct answer is b)

Explanation: None.

90. The correct answer is d)

Explanation: We are violating a C programming rule which states that in switch-case statements, the labels must be integer constants.

When you compile the code, the c compiler will give an error message indicating that the case label is not an integer constant because the labels given in the code are integer variables 'a' and 'b'. You will get the following error message:

error: case label does not reduce to an integer constant

case a:

error: case label does not reduce to an integer constant

SUNRISE CLASSES ISS

SUNRISE CLASSES

@ISS COACHING DELHI SUNRISE CLASSES

SERVICE, TRUST & RESULT



SUNRISE CLASSES

case b:

91. The correct answer is c)

Explanation: None.

92. The correct answer is c)

Explanation: None.

93. The correct answer is d)

Explanation: None.

94. The correct answer is d)

Explanation: None.

95. The correct answer is d)

Explanation: None.

96. The correct answer is c)

Explanation: None.

97. The correct answer is c)

Explanation: None.

98. The correct answer is d)

Explanation: None.

99. The correct answer is a)

Explanation: None.

100. The correct answer is a)

Explanation: None.

101. The correct answer is a)

Explanation: None.

102. The correct answer is b)

Explanation: None.

103. The correct answer is c)

Explanation: None.

104. The correct answer is d)

Explanation: None.

105. The correct answer is d)

Explanation: None.

106. The correct answer is d)

Explanation: None.

107. The correct answer is d)

Explanation: None.

108. The correct answer is c)

Explanation: None.

109. The correct answer is c)

Explanation: None.

110. The correct answer is c)

Explanation: None.

111. The correct answer is d)

Explanation: None.

112. The correct answer is d)

Explanation: None.

113. The correct answer is a)

Explanation: None.

114. The correct answer is c)

Explanation: None.

115. The correct answer is b)

Explanation: None.

116. The correct answer is b)

Explanation: None.

117. The correct answer is d)

Explanation: None.

118. The correct answer is d)

Explanation: None.

119. The correct answer is d)

Explanation: None.

@ISS COACHING DELHI SUNRISE CLASSES

SERVICE, TRUST & RESULT



SUNRISE CLASSES

120. The correct answer is a)

Explanation: None.

121. The correct answer is c)

Explanation: None.

122. The correct answer is b)

Explanation: None.

123. The correct answer is b)

Explanation: None.

124. The correct answer is d)

Explanation: None.

125. The correct answer is b)

Explanation: None.

126. The correct answer is d)

Explanation: None.

127. The correct answer is c)

Explanation: None.

128. The correct answer is b)

Explanation: None.

129. The correct answer is a)

Explanation: None.

130. The correct answer is b)

Explanation: None.

131. The correct answer is c)

Explanation: None.

132. The correct answer is d)

Explanation: None.

133. The correct answer is d)

Explanation: None.

134. The correct answer is b)

Explanation: In the above code, we

are copying first the content of

array a into array b. So, "hell" gets

copied to array b. After that we are

copying the content of array b into

array a. Since, array b contained the

string "hell" now, it gets copied to

array a. Hence, the final answer will

be "hell, hell"

135. The correct answer is c)

Explanation: None.

136. The correct answer is c)

Explanation: None.

137. The correct answer is d)

Explanation: None.

138. The correct answer is b)

Explanation: None.

139. The correct answer is c)

Explanation: None.

140. The correct answer is c)

Explanation: None.

141. The correct answer is d)

Explanation: None.

142. The correct answer is d)

Explanation: None.

143. The correct answer is b)

Explanation: None.

144. The correct answer is c)

Explanation: None.

145. The correct answer is c)

Explanation: None.