

Inheritance and Polymorphism

Programming and Data Structures — Week 1, Lecture 3

Dr. Innocent Nyalala

Objectives

By the end of this lecture, you will be able to write a subclass using `class Child(Parent):`, explain polymorphism as the same method call producing different behavior depending on which object it is called on, and distinguish an “is-a” relationship, which calls for inheritance, from a “has-a” relationship, which calls for composition.

Outline

Today covers the repetition problem that motivates inheritance, using `Circle` and `Square` as the running example; how inheritance names an “is-a” relationship between classes; polymorphism, where one method call produces different behavior per object; the MTech-track material on composition versus inheritance and duck typing; an in-class quiz; and a summary.

The repetition problem

```
class Circle:
    def __init__(self, r):
        self.r = r
    def area(self):
        return 3.14159 * self.r ** 2

class Square:
    def __init__(self, s):
        self.s = s
    def area(self):
        return self.s ** 2
```


Nothing is wrong yet, but if you later want “loop over a list of shapes and print each area,” you need code that treats a Circle and a Square the same way despite them being unrelated classes.

Inheritance: naming the relationship

```
1 class Shape:
2     def area(self):
3         raise NotImplementedError # forces every subclass to override this
4
5 class Circle(Shape):                # Circle IS-A Shape
6     def __init__(self, r):
7         self.r = r
8     def area(self):
9         return 3.14159 * self.r ** 2
10
11 class Square(Shape):                # Square IS-A Shape
12     def __init__(self, s):
13         self.s = s
14     def area(self):
15         return self.s ** 2
```

`class Circle(Shape):` means “Circle inherits from Shape.” `Shape.area` exists only to guarantee every subclass provides its own — calling it directly on a bare `Shape` is a deliberate crash, catching the mistake of forgetting to override it.

The hierarchy, drawn out



Same method name, `area()`, different formula per subclass — that is polymorphism.

`Triangle(Shape)` fits the same pattern: its own `__init__`, its own `area()` formula, the same `Shape` parent.

Polymorphism: one call, many behaviors

```
shapes = [Circle(2), Square(3), Triangle(4, 5)]
for s in shapes:
    print(type(s).__name__, s.area())
```

```
Circle 12.566
Square 9
Triangle 10.0
```

The loop body never checks “is this a Circle or a Square?” It calls `s.area()` and trusts each object to answer for its own type. This is **polymorphism**: the same method call, `area()`, produces different behavior depending on which object it is called on. New shape added later? The loop above needs zero changes.

Where this pays off later in the course

A `Stack` and a `LinkedListStack` can both implement `push` and `pop`. Code that uses a stack — say, a parenthesis checker — can be written once against “anything with `push` and `pop`” and swapped between implementations without being rewritten. Polymorphism is what makes that swap free.

MTech addition — composition vs. inheritance

```
class Engine:
    def start(self):
        return "engine started"

class Car:
    def __init__(self):
        self.engine = Engine()    # composition: Car HAS an Engine

    def start(self):
        return self.engine.start()
```

Inheritance answers “*is this a kind of that?*” Composition answers “*does this have one of those?*” Confusing the two produces hierarchies that do not make sense. A Car is **not** a kind of Engine; it *contains* one. `class Car(Engine)` would technically run, but `car.start()` would then mean “the car itself starts,” collapsing a real-world distinction the code needs to keep.

MTech addition — duck typing and ABCs

```
from abc import ABC, abstractmethod

class Shape(ABC):
    @abstractmethod
    def area(self): ...

Shape()          # TypeError: can't instantiate abstract class Shape
```

Python does not require a shared base class to treat two objects identically — if an object has `.area()`, code that calls `.area()` accepts it, base class or not. `abc.ABC` is how you turn that implicit expectation into an enforced one. Without ABC, forgetting to override `area()` on a subclass fails only when `area()` is finally called, possibly far from the class definition. With ABC, it fails immediately, at the point the mistake was made.

Exercise

Add `Triangle(Shape)` to the hierarchy above, with `__init__(self, b, h)` and `area()` returning `0.5 * b * h`. Confirm it prints correctly inside the `for s in shapes:` loop with no changes to that loop.

Quiz — is-a or has-a?

For each pair below, decide whether the relationship is inheritance (“is-a”) or composition (“has-a”) before checking the answer: Dog and Animal; Car and Wheel; SavingsAccount and BankAccount; House and Room.

Quiz — answers

Dog(Animal) is inheritance — a dog genuinely is a kind of animal, and the relationship is stable. Car and Wheel is composition — a car has wheels, but is not itself a kind of wheel. SavingsAccount(BankAccount) is inheritance — a savings account is a kind of bank account, likely adding an interest rate. House and Room is composition — a house contains rooms, it is not a kind of room. Getting this distinction right is exactly the skill this lecture’s Car/Engine example was building.

Summary

Inheritance, written as `class Child(Parent):`, names a genuine “is-a” relationship between two classes. Polymorphism is the same method call — `s.area()` — producing different behavior depending on the actual type of the object it is called on, which is what lets code written once keep working as new subclasses are added. Composition (“has-a”) should be your default; reach for inheritance only when “is-a” is genuinely and stably true. We now have a working Shape family. Next lecture: why every data structure in the rest of this course — starting with Stack next week — is built using exactly this class pattern, and why counting operations, not seconds, is how we will judge them.