# Waterjet quote - Y front fins

One drawing, **6061**: the **two Y front fins**, both nested head to tail in **one square** of 10 mm plate. **The material is supplied** and the square drawn is the piece handed over, so the job is the holes and the two profiles cut out of it. **The gap between the two tapered edges is called out on the drawing** - please say if it is too tight for your kerf. **Every drawing is a separate DXF** and the file name is printed on its page.

## What is in it

| File | Part | Material | Overall | Holes |
|---|---|---|---|---|
| `4-front-fins.dxf` | Y FRONT FIN - QTY 2 | STOCK 302 mm (11.890 in) x 302 mm (11.890 in) x 10 mm (0.394 in) 6061 | 302 × 302 mm | 8 × ø4.2 mm (0.165 in) · 20 × ø9 mm (0.354 in) |

## How to read the drawings

- **Units are millimetres** and the origin is the lower-left corner of every drawing, marked with a **red dot**. Inch equivalents are printed alongside for reference only — work to the millimetre figures.
- **Hole offsets from that origin are printed on each page** — the **X** values across the top, the **Y** values down the left side, each on a leader from its own tick. They are there to read the drawing by; the **DXF is the authority** and the offsets are taken from it.
- **R12 DXF, lines, circles and arcs only.** No polylines, no splines, no blocks. Outlines are closed.
- **Layers:** OUTLINE is the cut profile, HOLES are the holes, NOTES and PARTS are text and are not to be cut.
- **Where a drawing says STOCK, the material is supplied** and the outline drawn IS that piece — the job is the holes, and any excess falls outside them. Where it says MATERIAL, the shop supplies the plate and the outline is the part to cut.
- **Holes called out as edge-bored are not drawn.** They run into a part's end face rather than through it, and are drilled here.
- **Where two parts share one piece**, both are drawn in position on it with the kerf allowed between them.

## What would help on the quote

- Price **per drawing**, and separately the material where you are supplying it.
- Say if any hole is **below your minimum for the thickness** — a pilot that gets opened out here is fine, and so is a scribed mark, so tell us which you would rather cut.
- Note any outline you would rather nest differently. Nesting is yours to choose; the drawings do not assume one.

# Y FRONT FIN - QTY 2

STOCK 302 mm (11.890 in) x 302 mm (11.890 in) x 10 mm (0.394 in) 6061

UNITS mm - ORIGIN LOWER LEFT

BOTH PARTS NEST IN THE ONE SQUARE, HEAD TO TAIL. THE TAPER IS ONE SHARED CUT - NOT TWO

CUT ORDER: HOLES FIRST, THEN BOTH PERIMETERS, THEN THE SHARED DIAGONAL LAST

THE DIAGONAL IS THE CUT THAT PARTS THEM - UNTIL IT RUNS THE PLATE IS ONE PIECE AND NOTHING CAN SHIFT

THE KERF COMES OFF BOTH PARTS AT THE TAPER. THAT IS ACCEPTED - DO NOT ADD A WEB BETWEEN THEM

THE SQUARE IS NOMINAL. INDEX EACH PART'S WIDE BASE EDGE ON A REAL PLATE EDGE, OPPOSITE EDGES

ANY SHORTFALL IN THE PLATE COMES OFF THE TAPERED ENDS, NOT OFF A BASE EDGE

**Holes** 8 × ø4.2 mm (0.165 in) · 20 × ø9 mm (0.354 in)

Drawn at 1:4 from the DXF itself · 4-front-fins.dxf · offsets are HOLE CENTRES from the red 0,0 dot - X across the top, Y down the left side

