

# Mega XL — custom upgrades & build notes

*Upgrades to a Kickstarter v1.0 Mega XL CNC router.*

This documents the changes made to a first-generation (Kickstarter v1.0) Mega XL: a taller, stiffer Z, closed-loop motors, all-proximity homing, and a complete electronics rebuild around a grblHAL controller in a custom enclosure with a proper 48 V power system, air assist, and probing.

## At a glance

| Subsystem             | Stock (v1.0)                 | Upgraded                                                            |
|-----------------------|------------------------------|---------------------------------------------------------------------|
| Vertical clearance    | stock                        | +3" via Mark Smith riser kit                                        |
| Z assembly            | stock Z                      | Mark Smith Z gantry (only V-wheels + X motor mount reused)          |
| Spindle               | DeWalt DWP611 (1¼ HP router) | 2.2 kW (3 HP) Ø80 mm water-cooled, ER20, 24k RPM, VFD-driven        |
| Stepper motors        | generic open-loop steppers   | all-in-one closed-loop steppers (driver integrated in motor)        |
| Limit / homing        | mechanical limit switches    | proximity sensors on every axis                                     |
| Probing               | —                            | touch plate + 3D probe in parallel; grounded spindle (no tool clip) |
| Controller            | 8-bit Arduino board          | grblHAL Teensy 4.x (USB + Ethernet)                                 |
| Electronics enclosure | cramped stock steel box      | custom 12×16×6" aluminum / plexiglass                               |
| Power                 | stock                        | 48 V Meanwell system, E-stop, buck-derived 12 V / 5 V rails         |
| Air assist            | none                         | Mist-relay 12 V solenoid → 30 PSI nozzle at the cut                 |

## Frame & mechanical

- **Mark Smith riser kit** — adds **3" of additional vertical (Z) clearance**, allowing taller stock and longer tooling.
- **Mark Smith Z gantry** — a **complete replacement of the Z assembly**. The only stock parts carried over are the **four V-wheels** and the **X stepper motor mount**; everything else is new.

# Spindle & cooling

The stock **DeWalt DWP611** (1¼ HP trim router) was replaced with a **2.2 kW (3 HP) water-cooled spindle** kit:

- **Spindle** — Ø80 mm body, 220 V, water-cooled, **ER20 collet**, up to **24,000 RPM at 400 Hz**.
- **VFD** — 2.2 kW (3 HP) inverter, fed from the 220 V circuit through the E-stop and commanded by the breakout board's **0–10 V PWM** speed signal (see Power distribution).
- **Mount** — 80 mm spindle clamp on the new Z gantry.

**Coolant loop.** A pump circulates coolant through the spindle; the warmed coolant is cooled by the 12 V fan (see the power tree) before returning. The pump is **interlocked to the spindle**: a **VFD digital output** drives the **NO contact of a 110 V relay** that the pump is plugged into, so the pump runs whenever the VFD runs the spindle — the spindle can't be run dry. (This is separate from the breakout board's Mist relay, which handles air assist.)

# Motors

The generic steppers that shipped with the Mega XL were replaced with **all-in-one closed-loop stepper motors** — each motor has its stepper driver built into the motor body. This removes the separate driver boards, adds closed-loop position feedback (lost-step detection / alarm), and simplifies wiring to a single cable per motor.

- **Individual enable** per motor — each stepper's **EN** line is driven separately.
- The motors' **AL (alarm) outputs are wire-OR'd together** and fed to the controller's **ST0 input**, so a stall / lost-step fault on any motor signals the controller.

All four axes are closed-loop. The machine is a **dual-Y gantry** — the two Y gantries are driven by ganged motors (**Y + A**), one per side.

| Axis  | Holding torque | Drives                                                |
|-------|----------------|-------------------------------------------------------|
| Y + A | 3.2 N·m each   | the two Y gantries (ganged)                           |
| X     | 2.0 N·m        | spindle carriage along the cross-beam (rack & pinion) |
| Z     | 1.2 N·m        | Z                                                     |

All motors have an **8 mm output shaft with a flat**, with pinions/couplings retained by a grub screw on the flat. *Build note:* the stock Mega XL pinions were 6 mm-bore and were **reamed to 8 mm** at a machine shop — this thinned the set-screw boss and reduced grub-screw thread engagement. See the [rack-and-pinion maintenance](#) appendix.

## Homing & limit sensing

---

The Mark Smith Z gantry uses a **proximity sensor** as its limit switch. To keep one sensing scheme across the machine, **all remaining stock mechanical limit switches were replaced with the same style of proximity sensor**, so every axis homes on identical, non-contact hardware.

## Probing

---

- The **touch-plate input is wired in parallel with the primary probe input**, alongside the **3D mechanical probe** — either device can trigger the same probe input.
- The **spindle mount is grounded**, so the tool itself is at ground through the spindle. That completes the touch-plate circuit on contact — **no alligator clip on the tool** is required.

## Controller & electronics enclosure

---

- Discarded the **cramped stock steel electronics enclosure** and the **stock 8-bit Arduino controller board**.
- Control is now a **grblHAL Teensy 4.x** controller on a breakout board (32-bit).
- Built a **custom 12" × 16" × 6" enclosure**:
  - Frame: **2020 aluminum extrusion**.
  - Five sides: **0.0625" (1/16") aluminum sheet**.
  - Top: **1/8" clear plexiglass** (visibility into the electronics).

## Connectivity

---

The Teensy 4.x supports Ethernet, and the breakout board has the **Ethernet option installed**. Both links to the Teensy are brought out as **panel patch-through connectors on the side of the enclosure**: a **female USB-A** jack and a **female Ethernet (RJ45)** jack.

## Power distribution

---

A single **220 V, 20 A branch circuit** feeds the machine through a **front-panel emergency-stop button** (the E-stop breaks the 220 V input, so it drops both the PSU and the spindle drive). The 220 V powers a **48 V Meanwell power supply** and the **VFD** (spindle drive). Everything else is derived from the 48 V rail through two buck converters.

**220 V, 20 A** → front-panel E-stop →

- └ 48 V Meanwell power supply
- └ VFD (spindle drive)

**48 V** (PSU output) →

- └ 4 × stepper motors
- └ 12 V / 3 A buck converter
- └ 5 V / 3 A buck converter

**12 V** (buck) →

- └ 4 × proximity limit sensors
- └ 12 V fan cooling the spindle coolant loop (runs while the spindle runs)
- └ grblHAL Teensy 4.x breakout board, 12 V input — the board uses 12 V to generate the **0–10 V PWM spindle-speed signal** to the VFD

**5 V** (buck) →

- └ breakout board 5 V input — board logic power, **separate from the Teensy** (the Teensy is powered over USB)
- └ 3D probe

## Relay outputs & air assist

The breakout board provides **5 relay outputs**, each **jumper-selectable for 5 V or 12 V**. Only the **Mist** output is in use, driving the air-assist nozzle:

Mist relay → 12 V solenoid valve (compressed-air inlet) → regulator @ 30 PSI → needle valve at top of Z gantry → 1/8" copper airline → swivel nozzle aimed where the tool meets the stock

## Connectors & terminations

**Ferrules are crimped on all terminal-block connections** — every stranded conductor landing on a terminal block is ferruled for a clean, captured, reliable termination.

Enclosure pass-throughs use **Molex Mini-Fit Jr panel-mount connectors**. The choice was deliberate: with roughly 60 terminations to make, the builder had far more confidence producing **~60 quality crimps** than ~60 quality solder joints on aircraft-style connectors.

## Cable & wiring schedule

All runs use shielded cable.

| Cable                | Run                                                     | Conductors                                       |
|----------------------|---------------------------------------------------------|--------------------------------------------------|
| <b>18/6 shielded</b> | enclosure → each stepper motor                          | 6 (assignment depends on motor type — see below) |
| <b>22/3 shielded</b> | enclosure → Y-axis proximity switches                   | 12V , Sig , GND                                  |
| <b>22/6 shielded</b> | enclosure → X & Z proximity sensors + 3D probe (shared) | 12V , GND , XLim , ZLim , P , 5V                 |

### 18/6 stepper cable — conductor assignment

| Conductor | Closed-loop stepper | Discrete (open-loop) stepper |
|-----------|---------------------|------------------------------|
| 1         | 48V                 | A+                           |
| 2         | GND                 | A-                           |
| 3         | DIR                 | B+                           |
| 4         | PUL                 | B-                           |
| 5         | EN                  | EN                           |
| 6         | AL                  | AL                           |

**All four axes on this build are closed-loop**, so they all use the left-column assignment ( 48V / GND / DIR / PUL / EN / AL ). DIR / PUL are direction/step to the integrated drives; EN = enable, AL = alarm. The discrete A± / B± column is kept for reference only — the same 18/6 cable would serve an open-loop motor if one were ever fitted.

## Rack-and-pinion drive — setup & maintenance

X (and the Y/A gantry drives) run on rack and pinion. After ~10 hours the X pinion crept **left** under load. A closed-loop motor can't see slip *downstream* of its shaft encoder, so a pinion loosening on the shaft is invisible until a fixed reference (the toolsetter at G59.3) exposes it. With the bores reamed 6→8 mm the set-screw boss is thin and grub-screw grip is the weak point; X slips first because it takes the most direct cutting side-load, but the other reamed pinions carry the same risk.

## Pinion-to-shaft — stop the slip

1. Pull the pinion; confirm the grub screw seats on the shaft **flat** (not a round section), and check whether the screw marred the flat or only kissed it.
2. **Degrease** shaft, bore, and screw threads — oil defeats both grip and threadlocker.
3. Use the **longest grub screw** the thinned boss will take, on the flat; add a second screw if there's room.
4. **Threadlocker:** blue (242/243) is normally enough; with the reduced thread engagement here, **red (271)** is justified as insurance against back-out — just note removal then needs heat (~250 °C, easy on a bare pinion).
5. Torque to screw size (M3 ~1.0–1.4, M4 ~2.5–3, M5 ~5–6 N·m); snug, don't strip the hex. Let red cure ~24 h before heavy cuts.

## Pinion-to-rack mesh & backlash

1. Loosen the motor mount so the pinion can move toward / away from the rack.
2. Shim **0.05–0.10 mm** (feeler gauge, or ~0.1 mm folded paper) between a pinion tooth and the rack, push the pinion in against the shim, tighten the mount, remove the shim.
3. Check the mesh over the **full travel** — it should stay lightly meshed everywhere. Tight at one end + slack at the other means the rack isn't parallel to the axis; realign the rack first.
4. Confirm full tooth-width engagement (pinion not riding a tooth edge).

## Verify

1. By hand: smooth full travel, minimal lash; rock the gantry and feel for play at the pinion.
2. Dial indicator: commanded vs actual on small moves; reverse direction to read backlash (a few thou).
3. Re-run a heavy back-and-forth / cut loop with paint-pen **witness marks** (motor shaft ↔ pinion, and a pinion tooth ↔ a rack tooth) — no separation = fixed.
4. Confirm the **AL → ST0** alarm actually halts grbHAL (force a stall) so a real fault can't pass silently.

## If it still creeps

A single grub screw — especially in a reamed, thin-wall boss — is marginal for rack-and-pinion loads. Durable fixes, in order: **proper 8 mm-bore pinions** (full set-screw boss) → **clamp / split-hub pinion** (grips the whole shaft, no set screw) → **keyed shaft**. Given the reamed pinions, the **clamp-hub style is the recommended upgrade** — it ends set-screw slip for good.

## Sourcing a replacement pinion


Match the rack on three things, plus the bore:

- **Module** (tooth size) —  $\text{module} = \text{tooth pitch} \div \pi$  (pitch 3.14 mm = Mod 1, 4.71 mm = Mod 1.5, 6.28 mm = Mod 2). Must match the rack exactly.
- **Pressure angle** — almost always **20°**.
- **Tooth count** — match the original to keep steps/mm, or pick a new count and recalibrate **\$100** (X steps/mm) in grblHAL.
- **Bore** — 8 mm, ideally a **clamp or keyed** bore, not a bare set-screw boss.

Sources that let you specify *module + 20° + 8 mm clamp/keyed bore*: **KHK / QTC** (khkgears.us, qtcgears.com — best for CNC rack & pinion), **SDP/SI** (sdp-si.com), **Misumi** (configurable bore & keyway), and **McMaster-Carr** (quick metric-module steel gears). Budget CNC rack-and-pinion sets are on Amazon / AliExpress (Mod 1/1.5, 20T, often 8 mm bore) with variable quality.

## Clamp hub vs set-screw hub

A **clamp (split) hub** grips like a clamp-style shaft collar: a slit is sawn through the bore and a screw bridges it; tightening the screw squeezes the slit closed so the **whole bore clamps the shaft 360°** — far more holding torque, no marring, and no dependence on a thin set-screw boss (exactly the reamed-pinion weakness).



Two routes to a clamp mount: a pinion with an **integral clamp bore** (specify it when ordering from KHK / Misumi / SDP), or a **keyless locking bushing** (Trantorque GT, Fenner B-LOC, ...) dropped inside a larger-bore pinion — the bushing expands to grip both the shaft and the bore, letting you use almost any pinion of the right module on the 8 mm shaft. The latter is handy here, since matching bore *and* gearing was the sticking point.