

LECTURE 05.

UI INTERACTIONS IN UIPATH

Robotic Process Automation

[29 October 2019]

Elective Course, 2019-2020, Fall Semester

Camelia Chisăliță-Crețu, Lecturer PhD

Babeș-Bolyai University

Acknowledgements

This course is presented to our Faculty with the support of UiPath Romania.



Contents

- **UI Interaction Types**
- **UI Input Methods**
 - Details
- **UiPath Input Methods**
 - Types
 - Default. Send Windows Messages
 - Simulate Type/Click
 - Demo 1 – Input Methods Applied
 - Summary
- **UI Output Methods**
 - Details
- **UiPath Screen Scraping Methods**
 - Types
 - FullText. Native
 - OCR
 - Google Tesseract
 - Microsoft MODI
 - Demo 2 – Output Methods Applied
 - Summary
- **Scraping Data**
 - Details
- **Structured Data**
 - Details
- **Extract Wizard**
 - Details. Steps
 - Demo 3 – Data Scraping Applied
- **Relative Scraping**
 - Details. Steps
 - Attributes
- **Intelligent OCR in UiPath**
- **Custom Activities**
 - Details
- **References**

UI Interaction. Types

- automations consist of different kinds of actions that may interact with UI elements;
- there are two types of interactions:
 - **Input** – inserting data into an application;
 - **Output** – reading data from an application.

Input Actions



- Clicks
- Text typing
- Keyboard shortcuts
- Mouse hover
- Clipboard actions (Paste)

Output Actions




- Getting text
- Finding elements
- Identifying images
- Clipboard actions (Copy)

UI Input Methods. Details

- *for humans:*
 - the only way to present **input actions** is to use **clicks**, **types** and so on;
 - **devices used:** the mouse, the keyboard;
- *for robots:*
 - there different ways to present **input actions**;
 - **actions that simulate devices:** mouse, keyboard, OS message sending, etc.
 - UiPath supports 3 input methods.

UiPath Input Methods. Types

- in UiPath there are 3 input methods available:



Default method:

- it replicates the **human method**, e.g., the mouse cursor moves on the screen;

Send Window Messages:

- it replicates the **messages that an application receives** when the user utilizes the keyboard and the mouse;

Simulate Type/Click:

- it acts like a developer programmatically changing the value of an editable field, using **the technology of the target application**.

UiPath Input Methods. Default

Working

- **Clicks:** The mouse cursor moves across the screen;
- **Typing:** The keyboard driver is used to type individual characters;

Strong points


- it supports special keys like **Enter**, **Tab**, and other **hotkeys**

Implications

- Attended user cannot touch the mouse or keyboard during the automation;
- it has a **lower speed** and load times can impact accuracy

Limitations

- **it does not automatically erase previously written text; it writes after it;**
- **it does not work in the background.**



Options	
CursorPosition	CursorPosition
KeyModifiers	None ▾
SendWindowMessages	<input type="checkbox"/>
SimulateClick	<input type="checkbox"/>

UiPath Input Methods. Send Window Messages

Working

- it replays the window messages that the target application receives when the mouse/keyboard is used;
- **Clicking** and **typing** occur instantly;

Implications


- **it works in the background;**
- it is comparable to the **Default** method in terms of speed;

Strong points

- Supports special keys like **Enter**, **Tab**, and other **hotkeys**;
- **Users can work on other activities during the execution of the automated processes;**

Limitations

- **it does not automatically erase previously written text;**
- **it works only with applications that respond to Window Messages.**



Options	
CursorPosition	CursorPosition
KeyModifiers	None ▾
SendWindowMessages	<input checked="" type="checkbox"/>
SimulateClick	<input type="checkbox"/>

UiPath Input Methods. Simulate Type/Click

Working

- it uses the technology of the target application to send instructions;
- **Clicking** and **typing** occur instantly;

Implications

- **it works in the background;**
- **actions are a lot faster,** but **there are some compatibility limitations;**

Strong points

- **it can automatically erase previously written text;**
- Users can work on other activities during the execution of the automated processes.

Limitations

- **it does not support special keys like Enter, Tab, and other hotkeys;**
- **it has a lower compatibility than the other 2 methods.**




Options	
CursorPosition	CursorPosition
KeyModifiers	None ▾
SendWindowMessages	<input type="checkbox"/>
SimulateClick	<input checked="" type="checkbox"/>

Demo 1. Input Methods Applied

- User Basic or Desktop recorder to create a process that performs the following actions:
 - 1. *open* the Notepad Application;
 - 2. *type* “Happy Tuesday!”;
 - 3. *minimize* the Notepad window;
 - 4. *restore* the Notepad window;
 - 5. *type* “Sent on Tuesday.”;
- Perform the following tasks:
 - Swap steps 4 and 5;
 - Switch between the three input methods. Discuss the followings:
 - *Is the field blank?*
 - *Are hotkeys handled correctly?*
 - *How fast does the automation work?*
 - *Does the automation work in the background?*

UiPath Input Methods. Summary

- input methods available in UiPath:




	Compatibility	Background	Speed	Hotkeys	Empty Field
Default	100%	NO	50%	YES	NO
Window Messages	80%	YES	50%	YES	NO
Simulate Type/Click	99% (for Web Apps) 60% (for Desktop Apps)	YES	100%	NO	YES

UI Output Methods. Details

- *for humans:*
 - **output action** are **read** and **process** the data resulted from applications and files;
- *for robots:*
 - there different ways to present **output actions**;
 - **activities** that simulate output actions use **variables** and **arguments**;
 - **tools** that take out data (simulate read) from screens and documents;
 - they enable data extraction from UI elements the automation workflows interact with;
 - UiPath supports 3 output (screen scraping) methods;




UiPath Screen Scraping Wizard. Details

- the **Screen Scraping Wizard** enables:
 - **to point** at a UI element and
 - **to extract text** from it, using one of the **three output methods**;
- the steps to perform screen scraping are:
 - 1. start the Screen Scraping Wizard;
 - 2. select the UI element in Computer Vision mode;
 - 3. select the screen scraping method from the options panel;
 - *(optional)* 4. if required, switch to another output method that gets the needed results.



UiPath Screen Scraping Wizard. Steps

- Steps:
 - 1. the **Screen Scraping Wizard** is started from the **Design Ribbon** in UiPath Studio.
 - 2. the screen goes in *Computer Vision mode*, highlighting the UI elements that it identifies with **blue**;
 - select the UI element;
 - UiPath Studio *automatically* chooses a screen scraping method;
 - 3. after it finishes extracting the text, the wizard shows the outcome;
 - the user is allowed to switch between the 3 output methods and customize using the properties;
 - the **Refresh** button can be used to see the outcome according to the new settings.



UiPath Output Methods. Types

- in UiPath there are 3 output methods available:



FullText method:

- **it is the default output method in most cases;**
- **it is the fastest method, has 100% accuracy and can work in the background;**
- moreover, it is able to extract hidden text (for example, options in a drop-down list). However, **it doesn't support Citrix and doesn't capture text position and formatting.**

Native method:

- **it is compatible with applications that use the Graphics Design Interface, the Microsoft API responsible for representing graphical object;**
- **it can extract the text position (coordinates) and formatting; it has 100% accuracy;**
- **its speed is lower than FullText method and it cannot work in the background;**
- **like FullText method, it doesn't support Citrix.**

OCR (Optical Character Recognition) method:

- **it is the only one that works with Citrix;**
- **its technology relies on recognizing each character just like we recognize faces in a photography;**
- **like Native method, it also captures the text position;**
- **it cannot work in the background, cannot extract hidden text, and its speed is by far the lowest;**
- its accuracy varies from one text to another, and changing settings can also improve the results.


FullText Method. Details

FullText method: captures all the text from a terminal screen;

- it is the default output method in most cases;
- it is the fastest method, has 100% accuracy and can work in the background;
- moreover, it is able to extract hidden text (for example, options in a drop-down list). However, it doesn't support Citrix and doesn't capture text position and formatting.

Ignore Hidden:

- when this check box is selected, the hidden text from the selected UI Element is not copied.



The screenshot shows a configuration window for a scraping tool. It features a 'Scraping Method' dropdown menu set to 'FullText'. Below it, under 'Scrape Options', is an unchecked checkbox labeled 'Ignore Hidden'. A 'Refresh' button is located at the bottom right of the options section.

Scraping Method: FullText

Scrape Options

☐ Ignore Hidden

Refresh

Native Method. Details

Native method:

- it is compatible with applications that use the Graphics Design Interface, the Microsoft API responsible for representing graphical object;
- it can extract the text position (coordinates) and formatting; it has 100% accuracy;
- its speed is lower than FullText method and it cannot work in the background;
- like FullText method, it doesn't support Citrix.

No Formatting:

- when this check box is selected, the copied text does **not** extract formatting information from the text, i.e., font, color, similar to FullText method;

Get Words Info:

- when this check box is selected, the screen coordinates of each word are extracted;
- It supports several separators; if the Custom Separator field is empty all known separators are used.

The screenshot shows a configuration window for the 'Native' scraping method. At the top, 'Scraping Method' is set to 'Native'. Below this, under 'Scrape Options', there are two checkboxes: 'No Formatting' (checked) and 'Get Words Info' (unchecked). A 'Refresh' button is located at the bottom right of the options section.

Scraping Method
Native

Scrape Options
<input checked="" type="checkbox"/> No Formatting
<input type="checkbox"/> Get Words Info

Refresh

OCR Method. Details

- the **OCR output method**
 - uses the OCR technology (**Optical Character Recognition**) for:
 - extracting information from virtual environments (Citrix or Remote Desktop);
 - “reading” text from images;
 - **it attempts to recognize each letter or given image in the target document;**
- it has two default engines:
 - **Google Tesseract;**
 - **Microsoft MODI.**

OCR (Optical Character Recognition) method:

- **it is the only one that works with Citrix;**
- **its technology relies on recognizing each character just like we recognize faces in a photography;**
- **like Native method, it also captures the text position;**
- **it cannot work in the background, cannot extract hidden text, and its speed is by far the lowest;**
- its accuracy varies from one text to another, and changing settings can also improve the results.

Google Tesseract OCR Engine. Details (1)

- the **Google Tesseract OCR** engine
 - is more effective with **character recognition** on **small size areas**;
 - it offers **multiple customization** options.

Languages:

- it enables language change for the scraped text;
- by default, English is selected; others are available at <https://github.com/tesseract-ocr/tessdata>;
- downloaded and copied it in the 'tessdata' subfolder of the UiPath installation folder;

Characters:

- it enables the selection of type of characters to be extracted: any character, numbers only, letters, uppercase, lowercase, phone numbers, currency, date and custom;
- **Custom** option two additional fields, **Allowed** and **Denied**, which allow the user to choose which types of characters to scrape and which to avoid.

The screenshot shows the 'Scraping Method' dropdown set to 'OCR'. Under the 'Scrape Options' section, the 'OCR Engine' is set to 'Google OCR'. The 'Languages' dropdown is set to 'eng' and the 'Characters' dropdown is set to 'Any character'. The 'Scale' is set to '2'. There are checkboxes for 'Invert' and 'Get Words Info', both of which are unchecked. A 'Refresh' button is located at the bottom right of the dialog box.

Scraping Method	OCR
Scrape Options	
OCR Engine	Google OCR
Languages	eng
Characters	Any character
Scale	2
<input type="checkbox"/> Invert	
<input type="checkbox"/> Get Words Info	
Refresh	

Google Tesseract OCR Engine. Details (2)

Scale:

- it helps the user specify the scale of the text to be scraped;
- if the results are not satisfactory, it is recommended to change the scale both ways (up, down) and see if it makes any difference;

Invert:

- when this check box is selected, the colors of the UI element are inverted before scraping;
- useful for: **darker themed applications, websites** and **scanned documents**;

Get Words Info:

- it gets the on-screen position of each scraped word.

Scraping Method: OCR

Scrape Options

OCR Engine: Google OCR

Languages: eng

Characters: Any character

Scale: 2

☐ Invert

☐ Get Words Info

Refresh

Microsoft MODI OCR Engine. Details

- the **Microsoft Office Document Imaging (MODI)**
 - is best used **to read Microsoft fonts** on **large size areas**;
 - it offers multiple customization options.

Languages:

- it enables language change for the scraped text;
- by default, English is selected;
- once the languages are added using the Windows Settings (using the Region & language sub-menu), they can be selected as options in Studio.

Scale:

- it helps the user specify the scale of the text to be scraped;

Get Words Info:

- it gets the on-screen position of each scraped word.

Scraping Method: OCR

Scrape Options

OCR Engine: Microsoft OCR

Languages: English (United States)


Scale: 1

☐ Get Words Info

Refresh

UiPath Output Methods. Summary

- in UiPath there are 3 output methods available:



	Speed	Accuracy	Background	Extract Text Position	Extracts Hidden Text	Supports Citrix
FullText	10/10	100%	YES	NO	YES	NO
Native	8/10	100%	NO	YES	NO	NO
OCR	3/10	98%	NO	YES	NO	YES

UiPath Output Methods. Activities Overview

- the activities associated to the output methods are presented below;


Output Method	Manual action/Activity
Basic Recording	Get Text activity
FullText	Get Full Text activity
Native	Get Visible Text activity
OCR	Get OCR Text activity

Demo 2. Output Methods Applied

- Use **Screen Scraping Wizard** to take out data from:
 - a .txt file open in **Notepad** and having the following content:
 - 1. “Flow Chart” and “Assign” activity.
 - 2. “Write Line” and “Do While”.
 - 3. “Sequence” and “Input Dialog” activity.
 - 4. “If” activity and how to set conditions.
 - 5. Display output in “Message Box”.
 - a folder content from a **Total Commander** application window;
 - the **www.cs.ubbcluj.ro** web page opened in Chrome browser
 - an image, a text;
 - the **www.imdb.com** web page opened in Chrome browser;
 - The **IrfanVlewer** application with an image that contains the text *“și a mers cale lungă. Țintea vizuina monstrului numaidecât.”*
- Perform the following tasks:
 - Switch between output methods and their options.

Data Scraping. Details

- **Data Scraping** is the **process of extracting structured data**
 - from a **browser, application, or document**
 - to a **database, .csv file, or Excel spreadsheet**;
- **Data Scraping** is a functionality of UiPath Studio for extracting structured information and storing it in a **DataTable** variable.




Structured Data. Details

- **Structured data**
 - is a specific kind of information that is **highly organized** and is presented in a **predictable pattern**.
- For example, **Announcements** page available on www.cs.ubbcluj.ro consists of a list of elements having the same structure:
 - a title;
 - a date;
 - a content.



Extract Wizard. Details

- **Extract Wizard** consists of the following steps:
 - 1. Wizard opening;
 - 2. Field selection;
 - 3. Column naming;
 - 4. Pattern preview;
 - 5. Correlated data (where steps 2-->5 repeat as required);
 - 6. Multiple page selection;
 - 7. Extraction of results.



Extract Wizard. Step 1

Wizard opening

Field selection


Column naming

Pattern preview


Correlated data

Multiple page selection


Extraction of results



- the **Extract Wizard** window prompts the user to open the browser, application or document to scrape data from
- after 'Next' button is clicked, the screen enters in the *Computer Vision mode*, where each UI element that is identified is shown in a **blue screen with a yellow frame**.



Extract Wizard. Step 2



- the user selects the **first entry** and **last entry of the field** in the web page, document, or application that they want to extract data from.

Extract Wizard. Step 3

Wizard opening

Field selection


Column naming

Pattern preview

Correlated data

Multiple page selection

Extraction of results



- the user can customize **column header names** and **choose whether or not to extract URLs**.

Extract Wizard. Step 4

Wizard opening

Field selection


Column naming

Pattern preview

Correlated data

Multiple page selection

Extraction of results



- after the 'Next' button is clicked, a preview of the data is shown, and the user may change the **order of the columns** and **specify the maximum number of entries to be extracted** (default = 100, 0 means extracting all the available the results).

Extract Wizard. Step 5

Wizard
opening

Field
selection


Column
naming

Pattern
preview

Correlated
data



Multiple
page
selection

Extraction
of results



- this is particularly useful when the user wants to extract multiple fields;
- after each field is indicated, the user can add the name of the column;
- the operation of **extracting correlated data can be repeated multiple times.**

Extract Wizard. Step 6



- after the 'Next' button is clicked, the wizard asks whether the **data spans on multiple pages**, and if so, the user needs to point out the **next button** (*not the number of the next page*).

Extract Wizard. Step 7

Wizard opening

Field selection

Column naming


Pattern preview

Correlated data

Multiple page selection

Extraction of results

- the **Designer** will be populated with a **sequence of all the activities**, just like for **Screen Scraping**;
- a **DataTable** variable is initialized with the extracted information.




Demo 3. Data Scraping Applied

- Automate the following process;
 - *open* the www.cs.ubbcluj.ro web page opened in Chrome browser;
 - *save* the extract the data available in Announcements section;
 - *the Announcements section consists of title, date and content;*
 - *use Data Scraping Wizard /Extract Wizard to take out data from the web page;*
 - *specify the maximum number of results;*
 - *save* the extracted data into an Excel workbook;
 - *use Write Range activity from Workbook activity package.*



Relative Scraping. Details

- **Relative Scraping**
 - is a technique that enables retrieving text from special UI elements by
 - using **visual anchors** and
 - the **OCR technology**;
- **When to use it?**
 - in situations where **selectors cannot be found**;
 - when **certain UI elements are difficult to access** by normal means;
 - with applications in **virtual environments** (such as Citrix apps);
- **Screen Relative** option is available under **Image Recording**, in **Screen Scraping** category of activities.



Relative Scraping. Steps

- **Steps to perform relative scraping:**
 - 1. **Start Image Recording**, go to **Screen Scraping** and select **Scrape Relative**.
 - 2. Point the UI element to extract data from. The OCR engine will attempt to identify the text right away.
 - 3. Select a visual area related to the text that will be scraped. The wizard will retain the position of the text relative to the specified anchor.
 - 4. The **Attach Window** container that is generated contains a **Find Image** activity that locates the position of the anchor on the screen.
- after the above operations are being done, the sequence is created in the Designer. The specificity relies on the fact that a **Find Image** activity is placed before the **Get OCR text** activity.



Relative Scraping. Extracting Attributes

- the attributes of a UI element, such as its exact screen position or its ancestor can be extracted;
- there are 3 different UiPath activities available;

Get Ancestor: Retrieves an ancestor for a specified UI element.

- **Input:** UpLevel: specifies at which level of the UI hierarchy to find the ancestor.
- **Output:** Ancestor as a UI Element variable.

Get Attribute: Retrieves the value of a specified attribute of a UI element.


- **Input:** the name of the Attribute as string.
- **Output:** the value of the specified Attribute.

Get Position: Retrieves the bounding rectangle of a specified UI element.

- **Output:** the resulting bounding Rectangle variable for the specified UI element in screen coordinates.

Intelligent OCR in UiPath

- This pack is built around the **ABBYY FlexiCapture** technology, that enables complex OCR activities, such as:
 - Document classification;
 - Structured data extraction;
 - Table extraction;
 - Document exporting;
 - Document digitalization.



Custom Activities. Details

- **Custom activities** development provides:
 - improved clarity of the workflow;
 - increased reusability for similar processes/steps of processes;;
- there are several ways to develop custom activities:
 - Creating and publishing a UiPath library `.nupkg` file;
 - Create a C# `.dll` and building a `.nupkg` file imported in UiPath;
- **Demo:**
 - Create a package consisting of an activity that allows to insert an item in a collection;
 - this is similar to the use of **Invoke Method** activity with the benefit of not requiring signature knowledge on the `Insert` method.

References

- UiPath Academy - <https://academy.uipath.com>
 - Level 1 – Foundation Training, Lesson 5;
- UiPath Docs - <https://docs.uipath.com/studio>
 - UI Elements - <https://docs.uipath.com/studio/v2018.3/docs/about-ui-elements>