


SPLASH

SEA PARAMETER LOGGING AND SENSOR HUB

Lamprinidis Iasonas, Zoidis Vasileios,
Michalainas Ioannis, Tzanetis Savvas



★ TABLE OF CONTENTS ★

01

INTRODUCTION

The general premise and goal

02

ARDUINO

Sensor selection, transmission, and power efficiency

03

BACKEND



Data ingestion and analysis

04

FRONTEND

Data display





INTRODUCTION

Iasonas Lamprinidis



GOAL AND PREMISE



Objective:


To develop an autonomous meteorological station in the form of a floating buoy, designed to collect and record oceanographic data such as wave height and wave period.

Functionality:

By applying mathematical and statistical analysis methods, the system will dynamically assess wave-related risk levels to enable timely alerts and enhance maritime safety.





OUR VISION



We imagined a fully autonomous weather and wave monitoring system using solar-powered drones in a mesh network. Each drone follows a pre-set route, collects data, and transmits it to a central, self-propelled, hydrodynamic vessel — no external support needed. The system is smart, self-charging, and designed for real-time analysis.





02

ARDUINO


Vasileios Zoidis



OBJECTIVES

- Design a distributed sensor node that gathers environmental data
- Implement wireless communication between sensor and receiver using RF modules
- Display gathered information on a centralized platform
- Optimize energy use through staggered data transmission and low-power components


SENSOR SELECTION



BMP280:

Measures temperature and pressure with high precision and stability

SENSOR SELECTION




MPU6050:

A 6-axis accelerometer and used to estimate wave impact and surface motion dynamics



SENSOR SELECTION



NEO-6M:

A GPS module, known for its compact size, affordability, and reliable performance.

COMMUNICATION

We use two arduinos:

- The **transmitter** arduino captures and transmits the live data using the RFM22 antenna.
- The **receiver** arduino passes on the data through the serial connection to the backend.

POWER EFFICIENCY

We use a powerbank, so to be power efficient:



- Selective data transmission, sending full packets only once per second
- Configurable transmission power
- Power-efficient sensors

uuuuu

03

BACKEND

Ioannis Michalainas





DATA INGESTION

Two modes:

- **DEMO**, with simulated data for testing purposes
- **DEPLOY**, real sensor data

High Frequency: accel_z

Low frequency: lat, lon, signal, temp, pressure, accel_z



WAVE ANALYSIS (1/2)

We normalize the z axis
accelerometer data

```
lsb_to_ms2 = 9.81 / 16384  
data = np.array(accelerometer_data) * lsb_to_ms2  
data = data - np.mean(data) # remove DC offset
```

Then, using FFT and
heuristics we extract the
wave frequency and height.

```
fft = np.fft.rfft(data)  
fft_freqs = np.fft.rfftfreq(n, d=1.0/sampling_rate)  
magnitudes = np.abs(fft)  
dominant_freq = fft_freqs[np.argmax(valid_magnitudes)]
```

```
std_accel = np.std(data)  
scaling_factor = 0.25  
wave_height = scaling_factor*std_accel / (dominant_freq**2)
```

WAVE ANALYSIS (2/2)

Knowing f and H , and assuming β we calculate the vertical and horizontal runup

$$T = \frac{1}{f} \quad L_0 = \frac{gT^2}{2\pi} \quad \xi = \frac{\beta}{\sqrt{\frac{H}{L}}}$$

$$R_2 = \begin{cases} 0.043\sqrt{H_s L_0}, & \text{if } \xi < 0.3 \\ 1.1 \left(0.35\beta\sqrt{H_s L_0} + 0.5\sqrt{H_s L_0 (0.563\beta^2 + 0.004)} \right), & \text{if } \xi \geq 0.3 \end{cases}$$

$$I = \frac{R_2}{\beta}$$

If $R_2 > 0.9$ the wave is deemed dangerous (VE), otherwise safe (AE)



API ENDPOINTS

The API provides four endpoints:

- **status:** online, battery level, coordinates and signal strength
- **info:** temperature and pressure
- **waves:** runup, inundation and danger zone
- **weather:** wind speed and direction and general weather condition

These endpoint are called upon by the frontend, in order to display this information in a meaningful and aesthetic manner



04

FRONTEND



Savvas Tzanetis



TOOLS USED

The application is built using several tools and frameworks, more specifically:

- **React** with the help of **Typescript**
- **Recharts**: Powers the data visualization for the wave height
- **Lucide React**: Supplies the iconography used throughout the interface
- **Framer Motion**: Provides fluid animations and transitions for the UI elements
- **Tailwind CSS**: Implements custom styling, creating consistent design patterns across components



Recharts



LOOK AND FEEL

The layout of the web app consists of several independent widgets to display information:


- **Current Condition:** Changes it's icon as well as color depending on the current weather
- **Air Temperature:** Displays the current temperature as measured by the drone
- **Pressure:** Shows the atmospheric pressure as measured by the drone
- **Wind:** Provides the wind speed and direction
- **Avg Dist to Shore:** Displays the projected distance the average wave react to the shore
- **Drone Status:** Gives information about the drones battery and signal strength
- **Wave Height:** Shows a graph the current wave in 1 second intervals



IMPLEMENTING NOTIFICATIONS

The user is notified with in-app alerts about extreme weather conditions and/or connection issues with the backend server. These alerts are categorized based on their priority:

- **Low priority:** Low priority alerts are indicated with a **yellow** color
- **High priority:** High priority alerts are indicated with a **red** color





API REQUESTS

Each widget handles API requests independently with different time intervals depending on their needs. For example:

- The **Current Condition** widget makes API requests every 3 minutes as it relies on an external API, limiting the number of requests the system can make daily
- The **Wave Height** widget, makes a request every second as this makes its corresponding graph more responsive and informative

Other widgets and alerts have different request intervals, most of them being set at 30 seconds.






SIMULATED MODE

Considering the difficulties associated with setting up a drone and backend infrastructure for a live demo, we have also set up the ability for the user to test our application with the help of an always online backend server.

This setting can be changed any time at the bottom of the page from the widget shown below:





VIDEO EVIDENCE★

Demo: <https://www.youtube.com/watch?v=GDOr5xGcenA>

Spot: <https://www.youtube.com/watch?v=TnTkDOKx9Sq>

Repo: <https://github.com/ioannisam/SPLASH>





THANKS FOR
YOUR
ATTENTION