

ARCHITECTURAL GENERAL NOTES

DIMENSION SYMBOLS DIMENSION SHOWN TO: - STRUCTURAL GRID - LAYOUT GRID - CENTERLINE OF ASSEMBLY - CENTER OF OPENING - CENTER OF EQUIP/ FURN GRID OR CENTER LINE TYPICAL DIMENSION SHOWN TO: - PARTITION ASSEMBLY - EDGE OF DOOR OPENING - OTHER BUILDING ELEMENT - WORKING POINT INDICATED ON DETAIL	FIRE EXTINGUISHER SYMBOLS FEXT FIRE EXTINGUISHER BRACKET MOUNTED FEC FIRE EXTINGUISHER SURFACE MOUNTED FEC FIRE EXTINGUISHER CABINET SEMI-RECESSED FEC FIRE EXTINGUISHER CABINET RECESSED		
GENERAL SYMBOLS BASE CABINETS BASE AND WALL CABINETS WALL CABINETS TOILET PARTITION AND DOOR HANDRAIL BUMPER GUARD CG CG CORNER GUARD EG EDGE GUARD OVERHEAD ITEMS UNDER-COUNTER ITEMS NIC NOT-IN-CONTRACT ITEMS	PLUMBING SYMBOLS TOILET - WALL HUNG URINAL - FLOOR/WALL HUNG LAVATORY - COUNTERTOP LAVATORY - PEDESTAL/WALL HUNG UTILITY SINK DRINKING FOUNTAIN / EWC JANITOR'S RECEPTOR FLOOR DRAIN IN SLOPING FLOOR		
ARCHITECTURAL DEMOLITION SYMBOLS EXISTING PARTITION TO REMAIN EXISTING PARTITION TO BE REMOVED EXISTING DOOR TO REMAIN EXISTING DOOR AND FRAME TO BE REMOVED EXISTING WINDOW TO REMAIN EXISTING WINDOW TO BE REMOVED EXISTING LAY-IN CEILING TO REMAIN EXISTING LAY-IN CEILING TO BE REMOVED			
DOOR AND INTERIOR OPENING SYMBOLS DOOR OPENING MARK SINGLE OPENING DOOR DOUBLE ACTING DOOR PAIR DOORS - EQUAL SIZES PAIR DOORS - UNEQUAL SIZES PAIR DOORS - DOUBLE EGRESS 2 PANEL BI-FOLD DOOR PAIR - BI FOLD DOOR OVERHEAD ROLLING DOOR INTERIOR GLAZED WINDOW DOOR WITH SIDE LIGHT SLIDING DOOR - BETWEEN JAMBS SLIDING POCKET DOOR			
ARCH REFLECTED CEILING PLAN SYMBOLS <table> <tr> <td data-bbox="1029 1520 1252 1816"> ARCHITECTURAL 2X4' LAY IN ACOUSTIC TILE CEILING 2X2' LAY IN ACOUSTIC TILE CEILING GYPSUM BOARD AP ACCESS PANEL </td><td data-bbox="1252 1520 1439 1816"> ELECTRICAL 2X4' LIGHTING FIXTURE 2X2' LIGHTING FIXTURE 1X4' LIGHTING FIXTURE LIGHTING STRIP FIXTURE RECESSED DOWN LIGHT WALL WASH TRACK LIGHTING </td></tr> </table>		ARCHITECTURAL 2X4' LAY IN ACOUSTIC TILE CEILING 2X2' LAY IN ACOUSTIC TILE CEILING GYPSUM BOARD AP ACCESS PANEL	ELECTRICAL 2X4' LIGHTING FIXTURE 2X2' LIGHTING FIXTURE 1X4' LIGHTING FIXTURE LIGHTING STRIP FIXTURE RECESSED DOWN LIGHT WALL WASH TRACK LIGHTING
ARCHITECTURAL 2X4' LAY IN ACOUSTIC TILE CEILING 2X2' LAY IN ACOUSTIC TILE CEILING GYPSUM BOARD AP ACCESS PANEL	ELECTRICAL 2X4' LIGHTING FIXTURE 2X2' LIGHTING FIXTURE 1X4' LIGHTING FIXTURE LIGHTING STRIP FIXTURE RECESSED DOWN LIGHT WALL WASH TRACK LIGHTING		

THE FOLLOWING GENERAL NOTES APPLY TO ALL ARCHITECTURAL SERIES SHEETS. FOR GENERAL NOTES APPLICABLE TO ALL SHEETS REFER TO THE "PROJECT GENERAL NOTES". A. THE ARCHITECTURAL SERIES SHEETS ARE PART OF A COMPLETE SET OF CONSTRUCTION DOCUMENTS DESCRIBING THE WORK FOR THIS PROJECT. USERS OF THESE DOCUMENTS ARE RESPONSIBLE TO REVIEW ALL CONSTRUCTION DOCUMENTS TO UNDERSTAND AND COORDINATE THE GRAPHIC AND ANNOTATED INFORMATION PROVIDED IN THESE ARCHITECTURAL SERIES SHEETS.	B. EXCEPT WHERE DIRECTED TO PLACE ITEMS OF WORK AT THE APPROXIMATE LOCATIONS SHOWN, DO NOT SCALE DRAWINGS FOR DIMENSIONAL INFORMATION. ALL ELEMENTS OF THE DRAWINGS MAY NOT BE DRAWN TO EXACT SCALE. ALL DIMENSIONS REQUIRED ARE SHOWN OR MAY BE DERIVED FROM THOSE SHOWN ON THE FLO PLANS, DETAIL PLANS, ELEVATIONS, SECTIONS, DETAILS, SCHEDULES, AND SPECIFICATIONS. C. ALL VISUALLY EXPOSED STRUCTURAL, MECHANICAL AND ELECTRICAL ELEMENTS, INCLUDING EXPOSED METAL FLOOR AND ROOF DECK, ARE TO BE PAINTED UNLESS OTHERWISE NOTED. THIS INCLUDES ELEMENTS THAT MAY BE VISIBLE THROUGH GRILLES, LOUVERS OR CEILING COLORS AND PAINT MATERIALS ARE CHAINED IN THE FINISH SCHEDULE, THE SPECIFICATIONS, AND THE DRAWINGS AS APPLICABLE TO THE CONSTRUCTION DOCUMENTS.
REFERENCE ELEVATION DEFINITIONS	
A. THE TERM "REFERENCE" ELEVATION OR DIMENSIONS REFERS TO A NOMINAL WORK POINT. THE ACTUAL ELEVATION MAY VARY FROM THE REFERENCE POINT. REFER TO APPLICABLE DETAIL TO DETERMINE THE RELATIONSHIP BETWEEN THE ACTUAL ELEVATION OR DIMENSION AND THE STATED REFERENCE POINT." B. THE DESIGN REFERENCE ELEVATION "+0.0" SHOWN ON THE ARCHITECTURAL DRAWINGS CORRESPONDS TO THE FINISH FLOOR ELEVATION OF THE GROUND FLOOR. ESTABLISH THE ACTUAL ELEVATION WITH RESPECT TO SITE-SPECIFIC BENCHMARKS AND CONTROL POINTS AS DEFINED IN THE CIVIL DRAWINGS. C. "FINISH FLOOR" ELEVATIONS ARE MEASURED AT THE TOP OF THE CONCRETE FLOOR SLAB UNLESS OTHERWISE NOTED. APPLIED FINISHES SUCH AS RESILIENT FLOORING OR CARPET MAY RAISE THE ACTUAL FINISH SURFACE ABOVE THE REFERENCE ELEVATION PROVIDED FOR THE FINISH FLOOR.	D. WHERE CONCRETE FLOOR SLAB IS DERESSED TO ACCOMMODATE MORTAR BEDS, SETTING BEDS, RAISED ACCESS FLOORS, AND OTHER SIMILAR FLOOR ASSEMBLIES, "FINISHED FLOOR" ELEVATIONS ARE MEASURED AS IF CONCRETE DEPRESSION DOES NOT OCCUR. E. CEILING HEIGHT ELEVATIONS ARE MEASURED TO BOTTOM OF FINISH SURFACES AND STATED IN RELATION TO DISTANCE ABOVE THE REFERENCE ELEVATION FOR THE FINISH FLOOR UNLESS OTHERWISE NOTED. F. ROOF ELEVATIONS ARE MEASURED TO TOP OF SURFACE AND STATED IN RELATION TO DISTANCE ABOVE THE REFERENCE ELEVATION PROVIDED FOR THE UPPERMOST FINISH FLOOR UNLESS OTHERWISE NOTED. ELEVATION GIVEN ARE: TO TOP OF STEEL (TOS), TOP OF DECK (TOD) OR TOP OF TAPERED INSULATION (TOI) UNLESS OTHERWISE NOTED.
ARCHITECTURAL ASSEMBLY SYSTEM TAGS	
TYPICAL ARCHITECTURAL ASSEMBLY IDENTIFICATION MARK FOR THE ASSEMBLY TYPES LISTED, SEE THE FOLLOWING SHEETS FOR SYSTEM DETAILS AND DESCRIPTIONS: PLAN TYPE A = EXTERIOR WALLS - ABOVE GRADE - SHEET A5.0 X TYPE B = EXTERIOR WALLS - BELOW GRADE - SHEET A5.0 X TYPE H = EXTERIOR WALLS - 1/2 HEIGHT AND PARAPETS - SHEET A5.0 X TYPE L = FOUNDATION SLAB SYSTEMS - SHEET A5.0 X TYPE R = ROOFING SYSTEMS - SHEET A5.0 X TYPE T = EXTERIOR SOFFITS - SHEET A5.0 X TYPE T = EXTERIOR TRIM AND COPING - SHEET A5.0 X SECTION TYPE G = EXTERIOR GLAZING / PANEL SYSTEMS - SHEET A5.4 X TYPE X = EXTERIOR FENESTRATION SYSTEMS - SHEET A5.4 X TYPE W = EXTERIOR FRAMED WINDOWS AND LOUVERS - SHEET A5.4 X TYPE F = FLOORING SYSTEMS - SHEET A9.1 X TYPE P = INTERIOR WALL PARTITIONS - SHEET A9.2 X TYPE C = INTERIOR CEILINGS - SHEET A9.4 X TYPE E = INTERIOR GLAZING / PANEL SYSTEMS - SHEET A9.3 X TYPE Y = INTERIOR FENESTRATION SYSTEMS - SHEET A9.3 X TYPE M = INTERIOR FRAMED WINDOWS AND LOUVERS - SHEET A9.3 X ASSEMBLY NAME REPRESENTING: - MAJOR GROUP - FINISH SYSTEM - SUBSTRATE - CONFIGURATION - ASSEMBLY VARIABLE (NOT ALWAYS PRESENT) ASSEMBLY TAG DESIGNATION	
FIRE RESISTIVE RATING INDICATION	ARCHITECTURAL SYMBOL NOTES
0 HOUR SMOKE PARTITION 1 HOUR FIRE RESISTANCE RATING 2 HOUR FIRE RESISTANCE RATING 3 HOUR FIRE RESISTANCE RATING 4 HOUR FIRE RESISTANCE RATING	A. THE PURPOSE OF THIS SHEET IS TO ILLUSTRATE AND DEFINE TYPICAL GRAPHIC SYMBOLS WHICH MAY TYPICALLY OCCUR ON THE ARCHITECTURAL DRAWINGS. B. ADDITIONAL SYMBOLS NOT SHOWN OR DEFINED ON THIS SHEET MAY BE USED ON THE ARCHITECTURAL DRAWINGS AND ARE TYPICALLY DEFINED ON OTHER SHEETS. C. SYMBOLS ARE NOT DRAWN TO SCALE. TO DETERMINE THE ACTUAL SIZES OF ELEMENTS REPRESENTED BY SYMBOLS, REFER TO THE SPECIFICATIONS AND OTHER SHEETS, AS MAY APPLY.
MODULAR LAYOUT / DETAIL NUMBER	
	DETAIL MODULE LAYOUT DETAILS ARE NUMBERED ACCORDING TO THEIR LOCATION ON EACH SHEET AND ARE NOT NUMBERED CONSECUTIVELY. EACH MODULE MAINTAINS THE NUMBER ASSOCIATED WITH IT THIS SYSTEM CAN BE APPLIED TO ANY SHEET THAT CONTAINS MULTIPLE IMAGES. THE IMAGES ARE NUMBERED ACCORDING TO THE MODULE SYSTEM SHOWN ILLUSTRATED TO THE LEFT EACH DETAIL MAY OCCUPY ONE OR MORE WHOLE MODULES. THE DETAIL MODULE IS USED TO ESTABLISH THE IDENTIFYING LABEL FOR EACH DETAIL, NOT TO LIMIT THE SIZE OF THE DETAIL.

