



Components and Services



XMOD

Version: 1.0

# XMOD

XMOD service handles [configuration](#) for ShellyX and Powered by Shelly devices.

- `XMOD.ApplyProductJWS` to apply a product configuration JWS token from the [developer portal](#).
- `XMOD.GetProductJWS` to obtain the currently-applied product configuration JWS.
- `XMOD.GetInfo` to obtain the parsed `jws` token as `json`.

## Methods

### XMOD.ApplyProductJWS

Used to apply a product configuration JWS token obtained from the [developer portal](#).

#### Request

Properties:

Property	Type	Description
<code>jws</code>	<i>string</i>	Product configuration JWS

#### Response

On success, an empty (`null`) response is returned. The module performs a factory reset and reboots into its "new product" mode.

On error, the token is not applied. Possible error codes are:

- `-107` Permission denied: if the module already has a JWS with the `final` flag set.
- `-103` Invalid argument: if `jws` is missing, malformed or otherwise invalid.

## XMOD.GetProductJWS

Returns the currently-applied product configuration JWS.

### Request

This method takes no parameters.

### Response

Attributes in the result:

Property	Type	Description
<code>jws</code>	<i>string</i>	The applied token.

On error, the request has failed if the device has never been provisioned. Possible error codes:

- `-114` Unavailable – no JWS has been applied to the device.

## XMOD.GetInfo

Returns the parsed `jws` token as `json`. Notable properties are:

### Request

This method takes no parameters.

### Response

Attributes in the result:

Property	Type	Description
<code>aud</code>	<i>string</i>	The application for which the token is intended.
<code>iat</code>	<i>number</i>	The time when the token was issued.

Property	Type	Description												
jti	string	A unique identifier assigned to the token.												
v	string	Version												
p	string	Product prefix, used as part of AP SSID, hostname, MQTT Client Id and other system identifiers												
n	string	Product Name												
m	string	Manufacturer Name												
url	string	Product URL												
f	bitfield	<table><tr><th>Flag</th><th>Description</th></tr><tr><td>0x01</td><td>Final. If set, no new JWS can be applied.</td></tr></table>	Flag	Description	0x01	Final. If set, no new JWS can be applied.								
Flag	Description													
0x01	Final. If set, no new JWS can be applied.													
xmod	object	<div>XMOD-specific settings</div> <table><tr><th>Property</th><th>Type</th><th>Description</th></tr><tr><td>ni</td><td>number</td><td>Number of Inputs</td></tr><tr><td>no</td><td>number</td><td>Number of Outputs (Switches)</td></tr><tr><td>led</td><td>number</td><td>Type of system led. 1: Plain, active-low; 2: WS2812 or compatible RGB</td></tr></table>	Property	Type	Description	ni	number	Number of Inputs	no	number	Number of Outputs (Switches)	led	number	Type of system led. 1: Plain, active-low; 2: WS2812 or compatible RGB
Property	Type	Description												
ni	number	Number of Inputs												
no	number	Number of Outputs (Switches)												
led	number	Type of system led. 1: Plain, active-low; 2: WS2812 or compatible RGB												

## XMOD.ApplyProductJWS example

## XMOD.ApplyProductJWS

## Mos Request

null

## XMOD.GetProductJWS

## Mos Request

## Response

```
{  
  "jwt":  
    "ewogICAgImFsZyI6IkVTMzg0IiwKICAgICJ0eXAiOiJKV1QiCn0.ewogICAgImF1ZCI6IlhUMSIscSiAg  
    2Xk66Nr9g8UcBpng4sm7xBbTaLbhVlu10iQnGfyccuCuBMz0QKawVPYwQr6Dlj7d1b5qo1Y0SiTyVZOAl  
}
```

## XMOD.GetInfo example

## XMOD.GetInfo HTTP GET Request

## XMOD.GetInfo Curl Request

## XMOD.GetInfo Mos Request

```
http://192.168.33.1/rpc/XMOD.GetInfo
```

## Response

```
{
  "jwt": {
    "aud": "XT1",
    "iat": 1000000000,
    "jti": "000000000000",
    "v": 1,
    "p": "WaterValve",
    "n": "Water Valve",
    "m": "",
    "url": "",
    "f": 0,
    "xt1": {
      "svc0": {
        "type": "water-valve"
      }
    }
  }
}
```