

Hieroglyphs

A team of researchers is studying the similarities between sequences of hieroglyphs. They represent each hieroglyph with a non-negative integer. To perform their study, they use the following concepts about sequences

For a fixed sequence A , a sequence S is called a *subsequence* of A if and only if S can be obtained from A by removing some elements (possibly none) from

$A = [3, 2, 1, 2]$ The table below shows some examples of subsequences of a sequence

Subsequence	How it can be obtained from A
$[3, 2, 1, 2]$	No elements are removed.
$[2, 1, 2]$	$[3, 2, 1, 2]$
$[3, 2, 2]$	$[3, 2, 1, 2]$
$[3, 2]$	$[3, 2, 1, 2]$ or $[3, 2, 1, 2]$
$[3]$	$[3, 2, 1, 2]$
$[\]$	$[3, 2, 1, 2]$

On the other hand, $[3, 3]$ or $[1, 3]$ are not subsequences of

Consider two sequences of hieroglyphs, A and B . A sequence S is called a *common subsequence* of A and B if and only if S is a subsequence of both A and B . Moreover, we say that a sequence U is a *universal common subsequence* of A and B if and only if the following two conditions are met

- U is a common subsequence of A and B
- Every common subsequence of A and B is also a subsequence of U

It can be shown that any two sequences A and B have at most one universal common subsequence.

The researchers have found two sequences of hieroglyphs A and B . Sequence A consists of N hieroglyphs and sequence B consists of M hieroglyphs. Help the researchers compute a universal common subsequence of sequences A and B , or determine that such a sequence does not exist

Implementation details

.You should implement the following procedure

```
std::vector<int> ucs(std::vector<int> A, std::vector<int> B)
```

- .array of length N describing the first sequence : A
- .array of length M describing the second sequence : B
- If there exists a universal common subsequence of A and B , the procedure should return an array containing this sequence. Otherwise, the procedure should return $[-1]$ (an array of length 1, whose only element is -1)
- .This procedure is called exactly once for each test case

Constraints

- $1 \leq N \leq 100\,000$
- $1 \leq M \leq 100\,000$
- $0 \leq i < N$ for each i such that $0 \leq A[i] \leq 200\,000$
- $0 \leq j < M$ for each j such that $0 \leq B[j] \leq 200\,000$

Subtasks

Subtask	Score	Additional Constraints
1	3	$N = M$; A and B both consist of N <i>distinct</i> integers between 0 and $N - 1$ (inclusive)
2	15	For any integer k , the number of elements of A equal to k <i>plus</i> the number of elements of B equal to k is at most 3.
3	10	$A[i] \leq 1$ for each i such that $0 \leq i < N$; $B[j] \leq 1$ for each j such that $0 \leq j < M$
4	16	There exists a universal common subsequence of A and B .
5	14	$N \leq 3000$; $M \leq 3000$
6	42	No additional constraints.

Examples

Example 1

.Consider the following call

```
ucs([0, 0, 1, 0, 1, 2], [2, 0, 1, 0, 2])
```

Here, the common subsequences of A and B are the following: $[], [0], [1], [2], [0, 0], [0, 1], [0, 2], [0, 1, 0, 2], [1, 0], [1, 2], [0, 0, 2], [0, 1, 0], [0, 1, 2], [1, 0, 2]$ and

Since $[0, 1, 0, 2]$ is a common subsequence of A and B , and all common subsequences of A and B are subsequences of $[0, 1, 0, 2]$, the procedure should return

Example 2

.Consider the following call

```
ucs([0, 0, 2], [1, 1])
```

Here, the only common subsequence of A and B is the empty sequence $[]$. It follows that the $[]$ procedure should return an empty array

Example 3

.Consider the following call

```
ucs([0, 1, 0], [1, 0, 1])
```

Here, the common subsequences of A and B are $[], [0], [1], [0, 1]$ and $[1, 0]$. It can be shown that a $[-1]$ universal common subsequence does not exist. Therefore, the procedure should return

Sample Grader

:Input format

```
N M
A[0] A[1] ... A[N-1]
B[0] B[1] ... B[M-1]
```

:Output format

```
T
R[0] R[1] ... R[T-1]
```

.Here, R is the array returned by `ucs` and T is its length