

DVI / HDMI TYPE A / RESISTOR-DRIVEN TMDS
640x480 / 60 Hz; no audio or EDID negotiation

Even GPIO: positive. Odd GPIO: negative.
libdvi: invert_diffpairs=false; use 64-bit GPIO masks.
+5V_DB: fused slot supply. DDC/HPD/CEC: NC.
Start with direct mating; verify signal integrity and monitor lock.

Schematic prototype: physical qualification pending

Sheet: /
File: a2ext-dvi.kicad_sch

Title: a2ext-dvi

Size: A4	Date: 2026-09-18	Rev: 0.2
KiCad E.D.A. 10.0.6		Id: 1/1

Even GPIO: positive. Odd GPIO: negative. libdvi: invert_diffpairs=false; use 64-bit GPIO masks. +5V_DB: fused slot supply. DDC/HPD/CEC: NC. Start with direct mating; verify signal integrity and monitor lock.	Schematic prototype: physical qualification pending Sheet: / File: a2ext-dvi.kicad_sch Title: a2ext-dvi <table border="1"> <tr> <td>Size: A4</td> <td>Date: 2026-09-18</td> <td>Rev: 0.2</td> </tr> <tr> <td>KiCad E.D.A. 10.0.6</td> <td></td> <td>Id: 1/1</td> </tr> </table>	Size: A4	Date: 2026-09-18	Rev: 0.2	KiCad E.D.A. 10.0.6		Id: 1/1
Size: A4	Date: 2026-09-18	Rev: 0.2					
KiCad E.D.A. 10.0.6		Id: 1/1					

Sheet: /		D
File: a2ext-dvi.kicad_sch		
Title: a2ext-dvi		
Size: A4	Date: 2026-09-18	
KiCad E.D.A. 10.0.6	Rev: 0.2	
	Id: 1/1	

Title: a2ext-dvi

Rev: 0.2

Id: 1/1