

CONTROLLER FOR JUMPING ANIMATIONS TO ACHIEVE TARGET POSITIONS

By

Ian Charles Ooi

A Thesis Submitted to the Graduate

Faculty of Rensselaer Polytechnic Institute

in Partial Fulfillment of the

Requirements for the Degree of

MASTER OF SCIENCE

Major Subject: COMPUTER SCIENCE

Examining Committee:

Barbara Cutler, Thesis Adviser

Charles Stewart, Member

Shawn Lawson, Member

Rensselaer Polytechnic Institute
Troy, New York

November 2015
(For Graduation December 2015)

CONTENTS

LIST OF TABLES	iv
LIST OF FIGURES	v
ACKNOWLEDGMENT	vi
ABSTRACT	vii
1. INTRODUCTION	1
1.1 An Example of Animation Creation	4
1.2 Contributions	6
1.2.1 Unity3D	6
2. PREVIOUS WORK	9
2.1 Background	9
2.1.1 Existing Technologies	10
3. ANIMATION	12
3.1 Description of the Motion	12
3.2 Setup and Inputs	13
3.2.1 User Specified Constants	14
3.2.2 Skeleton, Joints, and Muscles	16
3.3 Center of Mass and Balance	20
3.4 Inverse Kinematic Solving	22
3.5 Torque-based simulation	23
3.5.1 Path Estimation	24
3.5.2 Windup	25
3.5.2.1 Sampling	26
3.5.3 Thrust and Takeoff	28
3.6 Energy Based Calculation	29
3.6.1 Path Estimation and Windup	30
3.6.2 Solutions to the Energy Assignment Problem	31
3.6.3 Thrust, In Air, and Landing	32
3.7 Summary	32

4. VISUALIZATION	34
4.1 Motivation and Inspiration	34
4.2 Motion Visualization	35
4.3 Summary	38
5. RESULTS	40
5.1 Output Animations	42
5.2 Limitations	43
5.3 Summary	46
6. FUTURE WORK AND CONCLUSION	53
6.1 Future Work	53
6.2 Conclusion and Summary	54
References	56

LIST OF TABLES

3.1	Values for calculated necessary velocity given air and windup times for a skeleton with muscle k values around 20000. This table shows separate columns for each vector component, where v_0 is the velocity when the character leaves the ground, x_0 is initial position, x is the destination position, g is gravity, t_a is air time, a is acceleration to reach v_0 from rest, and t_w is the windup time in which a is applied to reach velocity v_0 .	15
3.2	Table of estimated forces given k values and times	21
5.1	Table of spring constants for each trial	42
5.2	Table of frame sequences for forward and box jumps, $k = 20000$ global .	47
5.3	Table of frame sequences for sideways jumps, $k = 20000$ global	48
5.4	Table of frame sequences for forward and box jumps, $k = 20000$ varying .	49
5.5	Table of frame sequences for jumps with uneven leg strengths, $k = 20000$ global	50
5.6	Table of frame sequences for forward jumps, $k = 1 \times 10^{10}$ global	51
5.7	Table of frame sequences for box jumps, $k = 1 \times 10^{10}$ global	52

LIST OF FIGURES

1.1	Example of a 2D Sprite Animation	2
1.2	Screenshot of the Unity3D Editor	8
3.1	Example of Rigged 3D Character Model	17
3.2	Diagram of muscle setup	18
3.3	Diagram of spring displacement calculation	20
3.4	A plot of a sample field for the torque based simulation	27
3.5	A plot of a sample field for energy based simulation	31
4.1	Marker trail visualization of motion	35
4.2	Ghost image visualization	36
4.3	Composite frame visualization	37
4.4	Screenshot of Gizmos used for debug visualizations in Unity3D	38
4.5	Screenshot of Handles used for setting and visualizing joint constraints in Unity3D	39
5.1	Animation of a jump over an obstacle	44

ACKNOWLEDGMENT

I would like to thank Rosa Tung and Jim McCarthy for acting as consultants for existing artistic methods as well as usage of tools which allowed me to produce the mesh and rig used in this thesis and showed me an artist's view of animation. I would like to thank Jon Holman for discussing the mathematics of optimization problems with me, which helped to direct my choice for how to solve the problems.

ABSTRACT

Animating a character for video games and films is difficult and time consuming, requiring hours of artist labor to produce each animation. These animations are set and inflexible, requiring changes to the animation or sometimes fully new animations to suit new characters or situations for natural looking movements. Jumping is one such animation, where the size, mass, strength, and environment affect the movement of the character.

"Physics-based simulation... "(?) [+] Traditionally these animations are produced by manually posing the character for certain key frames and interpolating between the frames to produce a smooth animation. The more detailed or lengthy an animation, the more work required to specify it. Simulation for animation production can reduce this work, creating animations for a variety of situations based on constants set for the character and environment. These animations can then be easily recreated or adjusted for different environments by changing the constants set for generation.

This thesis work presents a simulation based method of control for a character, focusing on the lower body, to produce jumping animations for a variety of situations and body parameters. Two methods of simulation are described, one using a torque calculation and the other **using [+]** calculation to determine poses for the character. Our simulation **s**takes as input a mesh representing the character, a tree of joints describing the skeleton, a set of muscles, **mass assigned limbs** of the body, and a description of the desired path through desired timings, gravity, and desired displacement. An inverse kinematic solver is used to aid in posing the character.

Contributions of this thesis include an implementation of a simulation to produce jump animations in Unity3D, a description of character poses based on torque as well as another based on energy, a sampling based method for choosing a target position, and visualization of the produced animations in several ways to aid in analysis and presentation.

**and debugging (?)
[+]**

"sampling-based" [+]

isn't gravity an input? [?] this sentence is describing inputs, is this not clear as an input? thesis, I suppose, with more explanation but unclear for abstract) [+]

CHAPTER 1

INTRODUCTION

might be nice
to insert a
specific
example... in
video game X,
character Y
runs uphill,
walks
downhill,
and ...

Animations of human characters in fields. Especially with the film and video games, motion with small changes to tune the motion to the particular situation, environment, and character. Creation of such animations is largely done by hand by artists, posing the character for each time step of the animation. In 2D animation this takes the form of a sprite sheet as shown in Figure 1.1. These sprites may be drawn by hand or generated through 3D models.

did they call them
sprites in traditional
animation? [+]
only in computer
graphics

ly in video games, movies, and other complex environment traversal in both of athletic motions must be created

key framing also 2D animation, right? [+]
I added a chunk but I'm not sure if my
wording is good

In 3D artists will frequently use key framing. "Key" parts of the animated sequence are specified, with the remaining frames filled in, or "tweened" using an automated interpolation method or manual frame addition. For 2D animation, the artist will need to generate the intermediate images themselves or have a program interpolate between images. In 3D, key frame animations are performed on a 3D model, storing transformation data about the model for each frame and playing back the animation by repeating the transformations, interpolating between them to produce smooth animations.

Specifying these animation frames is work intensive, taking up significant time and resources to produce for a single character. Additionally, similar animations may need to be produced for slightly different scenarios, with only minor modifications required. These minor modifications can be made to fit a different setting, such as a character jumping on Earth or on the moon, or can be for different characters, such as a large person moving in contrast with a small child. Though the movement itself may be similar, manual changes must be made, requiring artist time which could be spent generating new assets.

Recent work in animation generation seeks to automate this process, replacing the manual process with a procedural one. Physics based simulations can be used to produce controllers for the skeleton, determining joint positions and rotations




Figure 1.1: This example shows a 2D sprite sheet used to produce a jumping animation for a stick figure character. The frames in this case are laid out in a single image for demonstration purposes, progressing in order starting with frame 0, the frame farthest left in this sprite sheet. An artist may create key frames and then fill in intermediary poses to produce a full sprite sheet as above. These sprite sheets were created by Clint Bellanger using a 3D model and are licensed under Creative Commons Attribution 3.0, retrieved from opengameart.org.

for keyframes automatically. Not only does this reduce the effort involved in the creation process, but this also provides a basis for dynamic interaction between a character's animation and the environment, which is not possible with manual keyframe animations.

We present a controller that takes a skeleton as input, with additional parameters describing the character. We then simulate a jumping motion on the character, determining a sequence of poses based on the character's muscles to produce a series of frames of an animation. The additional character parameters describe the character's mass, muscles, the constraints placed on each joint to prevent unnatural rotations, and a description of the jump indicating desired time and distance. Mass is specified per-joint to allow for calculation of the character's center of

We divide a jump into five stages: path estimation, windup, thrust, in air maneuvering, and landing. Our controller works with the initial path estimation, windup, and thrust stages of the motion. Poses are calculated by modeling muscles as Hookean springs attached to the skeleton at 2 points and crossing a joint. Spring constants for the muscles are specified by the user, allowing our simulate characters of various strengths and body makeups. Spring displac

what exactly is your output?
what is a sequence?
Aren't you just outputting the squat depth & muscle force(?)
[-] no, we're outputting an animation and actually posing the character through this animation

much more difficult (requires more animator skill & time?) or actually impossible ? [+] requires more animator time, not possible

add diagram of these stages? [+]

to manually create

earlier you said "per limb" Isn't per limb more correct/intuitive than per joint? Or are they equivalent? (explain & justify your method) [+] explained better, stored at the joint, but specified per limb

diagram? [?] organization-wise I have this diagram later, should I put it earlier and then reference it again later? added reference

rest is calculated using the

isn't this actually muscle + tendon?
isn't the tendon the thing that stretches
across/around the joint?) [+]
yes but
we're mostly thinking about the muscle
for this

g the skeleton.

Using the spring displacement, a particular pose of a joint is related to the usage of the character's muscle.

pre-jump bent/squat/windup pose? (being more descriptive will help reader)

Two approaches are described in this thesis, one using torque and one using elastic energy. As the springs contract, they produce forces on the bones, which result in torques at each joint. These torques are then used to calculate a pose for the character by calculating resultant linear acceleration for the character's center of mass, which is compared to a calculated necessary acceleration to make the jump. Our second approach uses the spring displacement to calculate the elastic potential energy of each muscle. By assuming perfect conservation of energy, we compare the total elastic potential energy of the character's muscles to a calculated necessary kinetic energy for the jump to be completed.

To control the motion and maintain plausibility, we calculate the character's center of mass and supporting polygon each frame. This allows the character to maintain balance while flexing its joints, the position of the character's joints are adjusted to keep the center of mass positioned over the supporting polygon. While flexing, the character constantly checks the position of its center of mass against the calculated supporting polygon, ensuring the center of mass is over the support and as close to the center as possible.

We use an inverse kinematic solver to help determine poses of intermediate joints. This allows us to find the necessary pose for the ankle and knee of the character given the position of its foot and hip. Many solutions in this region are possible, so we constrain the skeleton such that only those poses where the joints are within human ranges of motion are possible.

The next stage of the motion is the thrust stage where the character releases from the ground by using the potential energy of the spring-muscles to accelerate its center of mass upward. This is handled by applying the calculated accelerations from the windup stage to the character's pelvis to accelerate the center of mass, with the inverse kinematic solver determining the poses of the legs as they unbend. Due to the nature of the inverse kinematics algorithm used, the extension propagates from the hip to the feet.

might be nice to hint at the complexity of jumping. must unbend hip/knee and ankle joints simultaneously and synchronously. too much on one joint and the character will topple [+]

doesn't this depend
on how quickly the
character stands?
[+] i'm using this to
calculate how
quickly the
character stands

descriptions
are very
clear.
(diagram
would help
someone
not familiar
with this
problem
tho)

friction, wind, ? [+] i
ignore these so I'll
just say gravity!

4

The character then proceeds through the in-air portion of the jump, where the acceleration changes due to gravity as well as other forces before they finally land. We assume a simple trajectory for the in-air phase, though more complex motions with turns, flips, or interaction with the environment could be created. Our simulation ends when the character's feet contact the ground, ending the in-air phase. Other work, such as that by Ha et al., has handled landing and creating a separate controller to handle this is beyond the scope of this thesis. [1]

Our controller is made to be a module, able to be used with other controllers as part of a larger system. Its modularity is in the form of detecting and handling its condition at each stage, performing actions when it has a response to its current condition and ending control when it no longer has an appropriate response to allow a separate controller to handle the situation. This allows each controller to do a smaller job well. Several such controllers can be connected to produce complex animations or animation sequences, utilizing bounded starting and ending conditions for the character.

1.1 An Example of Animation Creation

To motivate the necessity for an automated animation method, we present an example of the method for producing an animation by hand. First a mesh and rig must be produced, which we also require for our simulation. This is a time and skill intensive process, requiring the artist to exercise their technical and creative knowledge and ability to create the character's figure, the mesh, and to create and attach a skeleton, the rig. The mesh is composed of vertices, and each vertex must be assigned a weight for each joint of the rig to indicate the way the vertex should transform when the joint in the rig is transformed. These joints serve not only as a joint in the anatomical sense, but as a tracked point in the skeleton. The joints are connected by bones, but the information is stored at the joint, which sometimes necessitates a joint to be placed in a non-anatomical way. For example, in our rig we have a joint placed at the head, which not only allows us to rotate the head but tracks the position. A similar situation arises with the toe and heel, where a joint is used to facilitate the placement of a connecting bone. Once the mesh and rig are

what do you
mean? [+]
condition meaning
the state

this
paragraph is
confusing...
[?] need
clarification
on what
specifically is
confusing,
this is a fairly
standard
description of
this type of
controller as
used in

also artist
must know
what types of
movement
will be
expected of
the mesh/
skeleton/rig
for this

define rig. also
probably good to
define mesh. [-]
defined later, this is
an introduction not
the explanation so I
chose to keep the
definition in a later
section

e.g. "grasp" moves many joints in all fingers of the hand?
[+/-] yes

5

created and the weights for the rig are assigned to the mesh, an animator may create controls to manipulate several joints at once, such as for hand or arm movements. These controls are formed from an object such as a simple spline to which several joints are constrained, allowing movement of several joints through manipulation of the control object.

Once the rig and mesh are set up, an animator must manipulate the mesh to pose the model. For a jumping motion they would need to decide how they want the character to start the animation to allow blending from other movements such as walking, running, or standing. They must then position the model and record a key frame. Key frames are hand-created frames of the animation which a renderer or game engine may interpolate between to produce a final animation, allowing an animator to create and store few frames, while still creating a 60 frame per second animation in the final setting. This also allows few frames to be stored to produce any frame rate of animation, while also reducing the storage requirements in exchange for a minor increase in computation, which is an extra interpolation for each joint in the character.

e.g. a heavier character will need to bend more, or jump with more speed/force to achieve the same height as a lighter character. A character with shorter legs will

While the key frames can be sparse and there are tools for aiding in generation, this process requires heavy manual input for each animation for each character. Characters that move differently due to differences in weight or body makeup must be animated separately, requiring an artist to perform similar, time consuming work. With a simulation based approach this work could be reduced, especially repeated work, to setting variables such as weight, height, and musculature for the different characters and generating the set of animations desired. As techniques and technologies improve, a simulation could be used in place of a stored key frame animation, creating the animation in place based on its environment and situation.

For a jump specifically, a human loads the muscles in their legs, quickly moving to a particular bend based on the feedback they feel in their muscles and joints, as well as balance feedback and their knowledge of the jumps they have performed in the past. The appearance of bearing and lifting weight is difficult to achieve, as the animator must visually match the poses to their knowledge of bodies or to a visual of a similar human to their character performing the motion. Simulation

to ensure realism, often animators work from source video of real humans or animals performing similar movements
[+] yes but i need a citation for

the burden for the artist/ animator will shift from preparing pose keyframes to adjusting body weight & dimensions & muscle strength & joint constraints
[+/-]

allows a computer to calculate movement based on physical aspects of the character incorporating knowledge such as the character's weight and body make up, allowing an animator to produce animations of motions they are less familiar with with higher degree of accuracy.

maybe "physical plausibility" or "physical realism" (accuracy is ok, but can be controversial) [+]
yep, let's be safe

confused who "we" is.
The artist/ animator?
The author of the thesis? (I prefer "I" for thesis.) The "system"?

1.2 Contributions

This thesis describes a controller which simulates a jumping motion character. The generated animation is created to be plausible in appearance, using a simplified physical representation. We sacrifice some physical accuracy in favor of speed and simplicity of creating, describing, and implementing the simulation. Specifically, we contribute a description for the windup, thrust, and a jump and created a controller using a physical simulation and an in Unity3D. In short, our contributions are:

- A controller which simulates a windup and thrust phase of the character from the ground into the air
- A description of character poses based on torque generated by muscles
- A description of character poses based on elastic energy of the muscles
- A sampling based method for choosing a pose given muscles and a desired output

in general should i not be using "we"? I was emulating paper-style wording that I've encountered in literature.

yes...
accuracy vs.
realism...

citation needed. [?]
is this for the
features available?
can I just cite the
documentation
site?

- Visualizations of the animations and values for analysis and presentation

2.1 Unity3D

To help separate the work performed for this thesis from features provided by Unity3D, we give a brief description of what Unity3D provides. This also helps motivate our choice of the engine, though an implementation using a different tool could fit better into the existing work flow used for creation of animation.

Unity3D is a game engine which we used to develop this system. It provides infrastructure for rendering, scene management, skeletal animation, asset management, lighting, and scripting. Our simulation leverages the

and system
could be
implemented
in other
engines? or
are there
restrictions?

[.] is unity similar to other engines? was
unity chosen because you are most
familiar with it? because it is free? open
source? [+1 yes to all except open source]

unclear (and not as
important to
mention?) [+]
i'll leave this sort of
discussion to
limitations section
later

citation needed [?] is it just a citation for mentioning maya? should i include a trademark symbol or something? i think maya usually uses (R) registered trademark

s a developer to write scripts for calculation

ported model. Models

features through the Unity3D scriptin
s in C# to use the functions a
isicle forces, as well as for apply
created in AutoDesk Maya and imported using Unity3D's asset import as
3D **GameObjects** with attached **Transform** components which allow arbitrary
formations. The skeleton, specified in AutoDesk Maya, was imported as a
with each joint as a separate GameObject node of the tree, with a parent
eObject as the root node, which also was parent to the GameObjects carrying
reated mesh.

Unity3D tracks and manages each GameObject, running the **update** loop for
ser. Unity3D uses a component-object model, where GameObjects are given
aviors by having a particular **Component**. Each **component** has a various up-

date functions for different stages of the engine's pipeline, but the main function
is **Update**. Components allow rendering and simulation behaviors to be separated
from each other, decoupling them from each other and the objects. The update loop
handles rendering related updates as well as running Update for each component on
the object. Our simulation is implemented as several Component scripts attached
to the character, with additional Components to carry extra information with each
joint of the skeleton and Components on each hip for inverse kinematic solving. The
scene manager provided by Unity3D allows for simple access and manipulation of
these Components and their objects, managing many useful data structures, namely
the tree of all objects present in the scene.

Unity3D also provides matrix and vector math libraries as well as generalized
math libraries to aid in physics calculations and subsequent transformations on
the objects. There are rigid body and physics components available, but for the
purposes of our simulation we performed the physics calculations ourselves to gain
greater control. We utilized Unity3D ~~new code for~~ detecting collisions between the
character's feet and the floor.

user-specified [+]

Inspector(?)
[+] also
changed
Editor

For managing the numerous user specified values, we use the Unity3D in-
spector. Unity3D provides an editor for creating and managing scenes and object
within, which is depicted in Figure 1.2. Within this editor the inspector is a window

why capitalized?
should these be in
courier or italics? (as
long as you're
consistent... whatever
is fine) [?] these are
names of objects,
should those be
italicized? checking
IEEE and ACM didn't
provide much info. also
should it be italicized
GameObject with a
normal s or a italic s
when it's italicized?

this is getting
rather
implementation-
y. Probably
belongs in an
implementation
chapter not the
intro. [?] will
consider, i think
you might be




Figure 1.2: Pictured is the Unity3D editor. At left a representation of the scene, allowing for visualization and manipulation of the hierarchy of objects. At right is the inspector, showing the interface for setting and editing the values specified in our simulation, the JumpController Component. In the center is a visual of the scene, allowing for intuitive placement and manipulation of objects, showing the character.

showing the Components attached to the selected GameObject. Unity3D utilizes serialization to allow public class variables to be set and modified through the inspector, providing a form of fields into which numbers can be entered. Using this, we allow the user to specify the desired constants for the simulation.

intro chapter should end with a transition to the rest of the thesis. often a summary of the remaining chapters, so the reader is prepare (and knows e.g., what chapters can be skimmed before getting to the reader's specific area of interest)

the summary could be your list of contributions with forward references to the upcoming chapters. The unity section feels misplaced.

each chapter starts with an opening paragraph (or two) before the X.1 section, transitioning from the previous chapter and giving an overview of the sections that make up this chapter.

not sure what you mean, editing motion capture is very difficult, but some research has tackled this problem (maybe not in commercial tools tho?)[+] i don't quite remember what I meant here either

CHAPTER 2 PREVIOUS WORK

need better section titles.. organization of related work.

2.1 Background

Producing athletic animations for human characters is motion capture is used for production of realistic animations for human athletics and other motions. However it requires the collection of information for each motion and does not adapt to the virtual environment. Muscle-based approaches produce realistic motions which adapt to the environment, using a complex model of the musculo-skeletal structure. Geijtenbeek et al. use a rough, user-created [+] routing on a skeleton to produce various gaits that are learned based on the velocity and environment. The muscle routing is optimized to remain within a region while providing optimal forces on the skeleton based on freedom of motion of the skeletal joints and the calculated optimal length of the muscle. This model is then used to compute sequences of muscle activations, modeling neural signals, which produce the final animations. This method is effective, producing good levels of gravity on at least 10 different bipedal skeletons [3].

Inverse kinematics approaches attempt to generate the motion based on a desired final position, determining the skeletal position by solving the system given constraints. Koga et. al use path planning, inverse kinematics, and forward simulation to generate animations of arm motions for robots and humans working cooperatively. They produce arm manipulations that avoid collisions and result in final positions and orientations for specified parts of the arm to produce motions such as a human putting on glasses and a robot arm and human cooperating to flip a chessboard [4].

Physical simulations utilize a rigid-body character with a user-defined skeleton to find optimal poses based on desired conditions. Ha et al. utilize such a scheme to generate landing motions for human characters based off linear velocity, global angular velocity, and angle of attack. The system chooses either a feet first or hands first landing strategy and moves into a roll to reduce stress on the body using

mocap, inverse kinematics, simulation, ... (seem like obvious categories)

physical space or configuration space?

put citation within or at end of first sentence

more discussion? pros & cons of each method. what is target application & how does that compare to your goal application?

define?
citations?
methods for obtaining data?
(not necessary to list all, but could expand your bibliography with

new paragraph/ section? [+]

principles from biomechanics and robotics. A sampling method is applied to determine successful conditions, producing bounding planes for the data. The movement is broken into stages of airborne and landing, in which the character re-positions for the designated landing strategy, and executes the landing strategy respectively. Each of these is separated into impact, roll, and get-up stages. Movement and joint positions are produced using PID servos [1]. Other work on producing such controllers was produced by Faloutsos et al. who described a method of composing such controllers by giving pre-conditions, post-conditions, and intermediate state requirements. The composed controllers are then chosen at each step based on the current pose and which controller is deemed most suitable [2]. Hodgins et al. created several controllers for running, vaulting, and bicycling, creating realistic motions and

should not have rigid bodies and spring-mass simulations [5]. Geijtenbeek and a .1 without also having a .2 [+] solve during reorg detailed review of physics based simulations [6].

2.1.1 Existing Technologies

commercial software? [+]

Several technologies exist to similarly aid in animation production. Unity3D MecAnim applies constructed animations of various types to similar skeletons, providing joint constraints and muscle definitions in a similar manner to our simulation.

MecAnim provides functionality for constraining range of motion and blending between existing animations, utilizing existing clips to produce complex animations in a manner similar to the composable controllers described by Faloutsos et al., as well as inverse kinematics solving. Due to a lack of understanding of the features and limitations, as well as what level of control is available, we chose not to utilize

MecAnim for our current implementation. As discussed in chapter 6, future work would ideally take advantage of MecAnim.

3ds Max footsteps offer a method of positioning feet and producing walk, run, and jump cycles based on number of parameters. Without knowledge of the algorithm, analysis is difficult, but it seems to produce animations by specifying timing and parameters about the stride. Parameters defined include stride width, length, and height. Our simulation seeks to produce more natural looking animations through use of a muscle simulation. The footstep style of animation may be

citation

poor documentation? intentionally opaque commercial product? or just very complex requiring more study/training/ experimentation?

capitalization?
also citation

preferable to artists however as it gives very strong control over the timing and spacing of the individual events of the animation, such as foot falls.

aim to stretch this chapter to 4-5 pages total. not necessarily many more papers, but more discussion & organization.

all chapters should have a summary section/paragraph. What is the takeaway message from this chapter. and transition... why should the reader continue to learn about your work?

CHAPTER 3

ANIMATION

good overview.
could add forward
references to each
section. e.g.,
(Section 3.2) [+]

longer title probably
appropriate. This is
describing your animation
method, not animation in
general. "Animation by
Physically Based
Simulation" or
something [+]

In this chapter we describe our method for simulating a character. We begin by describing the motion, breaking it into stages. We then describe the setup of the problem and inputs to our simulation. As part of our description of the inputs to the simulation, we describe the representation of a skeleton in detail. Following the skeleton section, we describe our inverse kinematics solver. We then describe two methods of simulation: one using torque to describe the motion and one using energy to describe the motion. The stages of jumping are described for each of these calculation paths.

3.1 Description of the Motion

use better (longer,
more descriptive)
titles for sections?

Overview of a
Jumping Motion
[+] sure

Jumping is the acceleration of a character's center of mass upward. Acceleration is applied in excess and in opposition to gravity, resulting in the character breaking contact with the ground and traveling a short distance before contact is re-established. This acceleration results due to the character pushing against the ground, first bending ?

Jumping motions can be divided into several stages. First is the lead-up or wind-up stage in which the character flexes, preparing their muscles for contraction and providing space for their body to extend. This takes the form of a slight crouch. Next comes the thrust stage, in which the character extends and exerts a force against the ground to accelerate upward. The character pushes against the floor with their feet, the contractions of the muscles causing joints to unbend and as a result displace the character's center of mass causing work to be done. This extension and resulting thrust is caused by the contraction of muscles, which produce torques on the skeleton.

Once the character has broken contact with the ground, they travel through the air, their velocity decreasing steadily due to gravity, air resistance, and other forces until they eventually land. Once they regain contact with the ground, the

be consistent
singular vs.
plural [-] they is
singular in this
case

I'd suggest using "I" everywhere, but if you prefer "we" and "our", that's fine [?]

how did it fail? would not converge? crashed? output was obviously wrong? [+] would not converge, output was incorrect

13

character absorbs or disperses the kinetic energy of their jump.

We attempted two main approaches to producing a jump motion through muscle simulation. The first method focused heavily on the torques produced by the muscles, but ultimately failed due to unknown reasons. The second method focused on the kinetic energy calculations to match the energy of the muscles, which simplifies the

Model
Initialization
and Jump
Setup [+]

culations to match the energy of the
duced a success
despite repeating the math
derivation and careful efforts
for debugging. [+]

before you said "mesh & rig"
what's the difference
[+] they're the same,
tried to make it

3.2 Setup and Input

The character in our system consists of a mesh, a skeleton, and a controller which has itself several sub-components. First we constructed a mesh, a 3D visual representation of our character. Our mesh is a simple, blocky humanoid, lacking arms in order to focus more heavily on motion of the lower body. A more complex human character, or even a humanoid non-human character could be substituted. This mesh consists of vertices, which each have a position as well as other information not relevant to our simulation such as normal and texture coordinate, which are used by Unity3D for displaying the mesh. This mesh can also be referred to as a character model, but in the context of this simulation we will refer to it as the mesh. Three vertices form a triangular face, though these are often created as quadrilaterals by the artist as the topology of the model can be simpler to work with due to the grid patterns formed as compared to triangular meshes. In the case of quad meshes, the mesh is often treated as a triangle mesh by the game engine or renderer, with each quad split into two triangles.

Our mesh was created using AutoDesk Maya, positioning the vertices in groups or individually, using several rectangular prisms as a base. Using the edge loop tool, more vertices were inserted, with loops of edges circling the torso and legs to produce the final shape. This mesh was then rigged, meaning a skeleton was added. As described in further detail in section 3.2.2, joints were positioned individually relative to the mesh, attempting to mimic the positioning of joints in the human skeleton. The connections were made simply, with each joint acting as a ball and socket joint, meaning that constraints needed to be specified at a later stage to facilitate hinge joints such as the knee and ankle and that complex, multi-boned

also, avoid repeating yourself too much

what?
"bipedal
non
human"?
[+]

does this repeat the rigging discussion earlier?
Make sure you're not too repetitive.
Maybe give this a section or subsection or paragraph label.
Maybe put a forward reference to this from the first mention of rigging.
[+] yes, todo. a forward reference would be much

consider adding tree diagram with all of your joints/bones [1]

add count of your # of joints/bones/degrees of freedom & compare to the counts of the scientifically accurate human skeleton/lower body (or fully articulated human skeleton/lower body) Does anyone bother to animate fully articulated human body?

[?] this is a possible thing, i don't know if some artists do but this is a lot of extra work is this necessary? i wasn't particularly able to find a

structures as found in the foot and shin were simplified to a single bone containing two joints. The hierarchy of joints for the skeleton was rooted at the pelvis, which has three children: one leading to the upper body and one to each hip. From each hip, a single joint was used for the manipulation of the upper body, with separate joints for each hip, knee, ankle, toe, and heel. Though there is no movement in the joints themselves, placing a bone for the foot requires an end joint for the bone to connect to.

Joints are then associated with the mesh through weight painting, in which each vertex of the mesh is assigned a weight for each joint. This weight determines how much a vertex transforms when a joint is moved. Each vertex is assigned a weight for each joint of the model. Careful weight assignment is important as this determines the behavior of the character's "skin" when they move, affecting how the mesh deforms over the bones. The joints map to the mesh with each key frame, defining the weight of each vertex. [19]

lost/misplaced citation? [?] no this is a citation for description of "how artists do things" should i even cite?

3.2.1 Use Specified Constants "Model and Jump"

or "Environment and Jump"

Within the controller there are a number of constants the user can specify, outside of the character itself. These specify constants for the simulation environment as well as some constants describing the animation to be produced. Our only environmental constant is gravity, which we specify as $-10 \frac{m}{s^2}$, where the negative value indicates the downward direction. Other constants include the air time, windup time, error allowance, and constants for the PID controllers which specify the multiplicative factor for the proportional, integral, and derivative components of the PID controller.

The times indicate how much time the character is expected to spend in the air and winding up for the jump. Air time in our case consists of the time during the animation where the character's feet are not in contact with the ground. Windup time refers to the time in which the character has their feet on the ground and is in the process of accelerating their mass upwards as the initial takeoff of the jump. A long windup time gives a very slow, exaggerated jumping motion.

why not 9.8? Ok to admit you rounded.
[?] why use 9.8? I used -10 mostly because that was the number we used throughout AP physics and honestly most things here are approximated heavily anyhow

instead of making me scan the whole table... give me the range for each constant I can set..... e.g., windup time (typically 0.1 -> 0.3 sec)

15

what are the rows of this table? a sampling of tests? all of your tests?

what do you expect the reader to learn/conclude from studying this chart? My eyes have kind of glazed over. Tell me what I'm supposed to see. What is the logic (if any) for the order of the rows?

rapid, clipped motion. While we allow the user to set windup, in practice there is a limited range of reasonable character. Values outside of the reasonable range produce behaviors in the simulation, such as either failing

to find a muscle load that can feasibly produce the jump or attempting to produce the jump and failing partway.

inputs													outputs			
v_{0x}	v_{0y}	v_{0z}	x_{0x}	x_{0y}	x_{0z}	x_x	x_y	x_z	g_x	g_y	g_z	t_a	a_x	a_y	a_z	t_w
0	0.5	10	0	0	0	0	0	1	0	-10	0	0.1	0	2.5	50	0.2
0	1	5	0	0	0	0	0	1	0	-10	0	0.2	0	5	25	0.2
0	1.5	3.33	0	0	0	0	0	1	0	-10	0	0.3	0	7.5	16.67	0.2
0	2	2.5	0	0	0	0	0	1	0	-10	0	0.4	0	10	12.5	0.2
0	2.5	2	0	0	0	0	0	1	0	-10	0	0.5	0	12.5	10	0.2
0	3	1.67	0	0	0	0	0	1	0	-10	0	0.6	0	15	8.33	0.2
0	3.5	1.43	0	0	0	0	0	1	0	-10	0	0.7	0	17.5	7.14	0.2
0	4	1.25	0	0	0	0	0	1	0	-10	0	0.8	0	20	6.25	0.2
0	4.5	1.11	0	0	0	0	0	1	0	-10	0	0.9	0	22.5	5.56	0.2
0	5	1	0	0	0	0	0	1	0	-10	0	1	0	25	5	0.2
0	5.5	0.91	0	0	0	0	0	1	0	-10	0	1.1	0	27.5	4.55	0.2
0	6	0.83	0	0	0	0	0	1	0	-10	0	1.2	0	30	4.17	0.2
0	6.5	0.77	0	0	0	0	0	1	0	-10	0	1.3	0	32.5	3.85	0.2
0	7	0.71	0	0	0	0	0	1	0	-10	0	1.4	0	35	3.57	0.2
0	7.5	0.67	0	0	0	0	0	1	0	-10	0	1.5	0	37.5	3.33	0.2

Table 3.1: Values for calculated necessary velocity given air and windup times for a skeleton with muscle k values around 20000. This table shows separate columns for each vector component, where v_0 is the velocity when the character leaves the ground, x_0 is initial position, x is the destination position, g is gravity, t_a is air time, a is acceleration to reach v_0 from rest, and t_w is the windup time in which a is applied to reach velocity v_0 .

Error allowance in our simulation is a widely used value indicating a percent error tolerance. This tolerance is used for determining the allowable difference between the desired values of either resultant linear acceleration and desired acceleration for the torque based simulation, or calculated kinetic energy and total elastic energy for the energy based simulation. The allowable difference is used for choosing samples and determining if the character has satisfied either the energy or acceleration requirements to complete the windup stage. The same error allowance

actually, maybe it is if you're doing a percent?
[?]

error is your epsilon? Is the error/epsilon the same for values with different units? (no it shouldn't be)

squish this to fit page margins or grad office will flip out.
Can rotate to

what epsilon do you use? (don't have hidden constants that might prevent replication of your results)
[+] need to look this up, i thought i mentioned it somewhere

is also used to determine if the windup stage, which is used to force a degree of bend in extreme cases, where very little bend is required as the muscles are extremely strong or the minimum is very small. This minimum is applied to compensate for the contralateral muscles, which would require a higher degree of bend than our muscles leading to a more realistic simulation. Below is an example of the inequality for the error allowance.

$$E_{kinetic} - E_{elastic} \leq \epsilon E_{kinetic}$$

citation?/reference? does everyone use these? [-] not generally cited in literature, I believe these are widely used and widely known

Lastly, we utilize proportional-integral-derivative (PID) controllers, which require 3 constants for each controller. A PID controller modifies an input based on error in 3 ways: proportional to the error, proportional to the integral of the error, and proportional to the derivative of the error. This allows changes to the system to have gains directly related to the error through the proportional component, eliminate steady-state error with the integral component, and to adjust gain with the derivative to improve stability of the changes. Our system does not require an integral component, meaning our controllers are just PD controllers with their integral gain for I set to 0. For our controllers, as we work in discrete frames, our controller calculation is as follows.

$$u(t) = k_p e(t) + k_i \sum_{\tau=0}^t e(\tau) + k_d (e(t) - e(t-1))$$


3.2.2 Skeleton, Joints, and Muscles

For the purposes of animation, a joint is an object with an associated position, an associated transformation, a parent joint, and some number of child joints. In the case of the root, the parent joint is absent and in the case of the end joints, such as tips of the fingers there are no child joints. Each child joint is connected to the parent by a rigid bone, which protrudes from the parent at a given resting angle. These joints are structured in a tree, as the parent and child joints imply, with the root of the tree at the pelvis. This tree serves as a hierarchy for transformations. Figure 3.1 shows the skeleton for our character.

define/intuitively explain these terms. [?] maybe I should but again the lit. seems to indicate these are generally understood in robotics and simulations. also this paragraph gives the intuition of what the terms do

how does this definition compare to your earlier definition/use of joint? (consider adding a forward reference to this section at your first mention)

make the title more descriptive... "geometric relationship between skeleton joints & muscles" (?)



first mention of deformer group? probably shouldn't be in the caption. Do you need it in the thesis? (are you working with it? Is it flavor about how a full animation process works?) [+] flavor, but it is not the first mention of deformer groups

Figure 3.1: Above is an example of a character model in AutoDesk Maya. The character skin or mesh is shown in gray, with a rig shown in multicolor. While it is visualized as a series of spherical joints with connecting solids, the rig itself does not have a visual component in practice. The rig acts as a skeleton, forming the mesh of the character model to make animation easier. Additional tools such as **deformer groups** and inverse kinematics handles can be used to further simplify the creation of animations for artists. While these tools simplify movement of the model, the artist **still must position each joint for each frame of the animation**, which is then stored for later playback.

Should this be inverse-kinematics? [?]

Joints are associated with a set of vertices from the mesh. Each of these may be associated with multiple joints, and are assigned a weight for each joint which acts as a scale factor for the transformations performed on the vertex. When a joint is transformed, the transformation is propagated to the children, with the parent as the origin of the child node's coordinate system.


In addition to the animation-related functions, joints in our system handle a

this figure should maybe be placed in earlier chapter or at least have forward reference (too many forward references is annoying to reader, so it is nice to put them earlier and have backward references ---reader is familiar with them and can flip back if they forgot. [+] I use a diagram like this twice, I put one in the intro now as the "general overview" and the other is the specifically labelled one

mark & label attachment point
(these are fixed geometry dimensions, right?)
[+] right!

this looks like a knee joint that should really have angle < 180 . What happens mathematically if this angle is > 180 ? Does the spring displacement go negative? [+] due to restrictions on the angles and the problem

explain this term to reader? what are other choices? euler angles quaternions? [+]



consider having 2 versions of this figure... a simple one that goes in the intro, showing bones & springs. And a model labeled version that goes in this chapter when you are talking details

Figure 3.2: Visual representation of the setup of bones and muscle for a single joint. This illustrates the method by which we calculate the spring displacement, taking the bones as rigid rods which separate and stretch the string as the joint bends.

also label the "width"(?) of the bone, since that is proportional to the displacement

number of other functions and values. Each joint keeps track of its constraints on rotation. Rotations are performed axis-angle, which makes the constraints somewhat more complicated. Constraints are specified through euler angles: pitch, roll, and yaw. These correspond to a rotation about the x, z, and y axes respectively in Unity3D's coordinate system. When rotating using a traditional rotation matrix through Euler angles, constraints simply prevent any of the angles from exceeding the bounds. The other issue was how to constrain a joint when rotation about a certain axis was fully prohibited, such as the knee joint which can only rotate about the x-axis. To constrain the axis-angle rotation thus, simply zero the undesirable component of the vector. Constraining the axis-angle rotation to a region with degree minima and maxima for rotations around the x, y, and z axes requires definition and constraint to the region of a sphere the rotation constraints covers. Instead of solving this complex problem, we instead clamp the euler angles to their constrained regions after each rotation.

Along with constraints, each joint tracks a weight, which allows distribution of weight over the body. This distribution affected the torque simulation heavily

~~is weight a discrete lumped mass at each joint or at center of each bone or a true continuous distribution across bone?~~
~~reality vs. simulation? Can lumping at a point calculate same answer as continuous? (I think it can, but claim the math appropriately. maybe a reference?)~~

is axis angle the same as euler angle?
[-] is this something i should do

what error does this introduce?
? non optimality
? [-] no this is adding a constraint to the

in your initial tests?

kinda weird, when in your diagram the spring is bend and is not "in a line" (pointing out a confusion the reader may have) [-] linear spring is a term they will need to look up themselves

diagram of muscle? is it the "spring" in figure 3.2? add the "3 joints" to

is a spring only at rest if the angle is 180? Or for the ankle, is the spring at rest at 90 degrees? Does your model allow for

did you mean to reference a figure or a citation? (using the author name or paper title in the sentence can make it clear what you are citing) [+ i meant to use a figure

19

the torque of each joint resulted in mass distribution. The energy simulation considered the character as a rigid body, not considering the changes occurring due to weight distribution except for balance issues and the effects on the muscles as described shortly. Joints also provide functions for calculating the direction to the next joint for muscle calculations, and a utility function for returning to a resting position.

Several joints form a muscle. Though any number of joints is possible, our muscles only utilize 3 joints each. These joints serve as anchor points, as seen in [3]. The muscle itself is a linear spring, obeying Hooke's law. This gives force (F) and elastic energy ($E_{elastic}$) as

do the springs attach mid bone or do they run the length of the bone and attach at the joint?

$$F = -ks$$

$$E = \frac{1}{2}ks^2$$


also... "[3]" should not be used as a noun. it should not be a required piece of the sentence (it should be a parenthetical), it should still be a complete sentence if you omit the "[3]"

where k is the spring constant for the muscle and s is the displacement of the spring. The negation of k in the force calculation indicates the force restores the spring to rest.

Considering a muscle as a spring models a muscle at maximum activation. A relaxed muscle has very little contractual or restoring force, and thus a low value for k , while a flexed muscle has a large k . While the muscle model could take muscle activation level into account, we chose the simpler system, allowing the user to specify k for their particular case. This gives more control for the animation, but also allows for more errors and issues. The results with poorly chosen k values resemble the results with poorly chosen times.

Along with the s values, a muscle keeps track of its center joint, anchor joints, and the bone width. A muscle has two anchor points and crosses the center joint. The positions of the anchors are specified as values in the range $[0, 1]$ along the bone between the center joint and the anchors. Bones are considered to be rectangular prisms with a square cross-section, with a width r specified by the user. Spring displacement can then be calculated directly from the angle of the joint using these constants and our assumptions as illustrated in Figure 3.2 with the equation below

is the joint in the center of the bone? is the width really $2 * r$? Or is the joint at the edge of the bone (seems complex to organize) [+] we treat it as the center of rotation is at the edge of the bone. we're consistent so it doesn't matter! it was thought of like a pair of wood blocks tied together with rubber bands allowing bending in the directions of motion



what happens if theta > 180? Is x negative? Or is theta the smaller joint angle? (also raised earlier) [+] we restrict it but it also will always be -180

Figure 3.3: Above is a visual representation of the angles used to calculate the spring displacement. The angle of the joint, θ , is used to calculate the displacement s using the bone width r and the law of sines.

muscle are primarily along bones.... (at least that's my understanding), but in your world, muscles are across joints. (mention/discuss somewhere)

derived from the law of sines:

$$s = \frac{r \sin(\pi - \theta)}{\sin \frac{\theta}{2}}$$

explain these terms

We derive this equation by calculating the supplementary angle, opposite the spring displacement. This angle can therefore be expressed as $\pi - \theta$. The sum of the remaining angles of the triangle formed by the spring displacement and bone ends can then be expressed as $\frac{\theta}{2}$. These angles are shown in Figure 3.3. We assume uniform bone width, which allows a simpler calculation of the angles.

For utility purposes we have each muscle calculate its utilization, giving a value in $[0, 1]$. This utilization is calculated as the dot product of the normalized vectors between the center joint and the anchor points. The value is then scaled from $[-1, 1]$ to $[0, 1]$ by adding 1 and dividing by 2.

what is the intuition? [+] the intuition is that the muscle-tendon spring stretches as the joint rotates

Maintaining

3.3 Center of Mass and Balance

The center of mass (CoM) is calculated as the centroid of the character. More specifically, joint positions are averaged, with a weight assigned to each joint based on the weight of the limb associated. The CoM must be recalculated with each update to the character's pose as the shift in weight changes the position.

numbers should be right aligned and have same # of decimal places. [+] hhhh

21

k	r	θ_{deg}	θ_{rad}	x	F	E
200000	0.05	170	2.96	0.0087	1743.11	7.59
200000	0.05	160	2.79	0.0173	3472.96	30.15
200000	0.05	150	2.61	0.0258	5176.38	66.98
200000	0.05	140	2.44	0.0342	6840.40	116.97
200000	0.05	130	2.26	0.0422	8452.36	178.60
200000	0.05	120	2.09	0.05	10000	250
200000	0.05	110	1.91	0.0573	11471.5	328.98
200000	0.05	100	1.74	0.0642	12855.7	413.17
200000	0.05	90	1.57	0.0707	14142.1	500
20000	0.05	170	2.96	0.0087	174.311	0.75
20000	0.05	160	2.79	0.0173	347.296	3.01
20000	0.05	150	2.61	0.0258	517.638	6.69
20000	0.05	140	2.44	0.0342	684.040	11.69
20000	0.05	130	2.26	0.0422	845.236	17.86
20000	0.05	120	2.09	0.05	1000	25
20000	0.05	110	1.91	0.0573	1147.15	32.89
20000	0.05	100	1.74	0.0642	1285.57	41.31
20000	0.05	90	1.57	0.0707	1414.21	50
24000	0.05	90	1.57	0.0707	1697.05	60
16000	0.05	90	1.57	0.0707	1131.37	40
40000	0.05	90	1.57	0.0707	2828.42	100

Table 3.2

caption? [+]

what are the rows?
difference tests?
what are the units for
each column? what
is the order of the
data? what
conclusion is the
reader to draw from
staring at these

where is
callout to
this table?
every figure
should be
"called out"
at least
once and
should be
close to the

this is
repetitive to
earlier... (can
be ok, but
review and
make sure its
necessary)

diagram would
be nice?

Using the calculated CoM, the balance of the character can be determined by the position of the CoM relative to the supporting polygon of the character. The supporting polygon is a polygon determined by the points of contact of the character with the ground or other supports which provide a normal force to counteract gravity and other external forces. During the windup and thrust phases, the character maintains contact with the ground through their feet, with the outer edges of the feet forming two sides of a quad, a line between the two feet at the toes forming a third, and a line between the heels of the character forming the fourth side. This polygon should be parallel to the ground plane, and is positioned at the bottom of the feet. If the character's center of mass is over this supporting polygon, the character is balanced.

To quantify balance, the vector between the center of the supporting polygon and the position of the CoM is measured. This vector is then projected into the

same plane as the supporting polygon, giving a 2 dimensional error between where the CoM is currently and where it would need to be perfectly centered. The PD controller then attempts to minimize the magnitude of this vector by moving in the proscribed direction while bending to achieve the desired force, constraining the number of solutions possible to provide the desired force.

the position of the upper body does have an impact on how high the jump will be, correct? If you bend forward, and then straighten as you jump, that will make your jump higher too, correct? [+] yes i think

As the character bends for the windup and extends for thrusting, the character must rebalance without using its legs in order to maintain the calculated load on the muscles. For these cases, the upper body is used to rebalance. The character bends forwards, backwards, left, and right to shift the weight of the upper body to offset the balance error created by the lower body pose. This is performed using a PD controller, with the error input as the balance error as calculated above, and the output as the amount to rotate in each direction subject to skeletal constraints.

3.4 Inverse Kinematic Solving

As the skeleton is a hierarchy assumed arises with applying rotations to joints. To floor as is expected, positions must be solved for the desired position for the hip, and the desired position of the root, the joint angles and positions of the knee and ankle are solved for. Constraints are placed on each joint, limiting the range of motion to an expected range as well as limiting the axes about which each joint can rotate, preventing unnatural directions of motion. These values are specified per joint and can be edited by the user to simulate varied levels of flexibility or alternate body shapes.

solving what? "Using Inverse Kinematics to Position Ankle & Knee" (?) [+] Inverse Kinematic Solving for Knee and Ankle Position

p, a problem rooted to the mathematics. Given

A solution to the joint positions is found greedily using these constraints, and gradient descent method **tho** works on single-chains of joints. A single chain of joints is a sequence of joints in which each joint has a single child and a single parent, with one root joint and one leaf joint which lack a parent and child respectively. Given the hierarchy of joints and a desired position for one of the non-root nodes of the chain, cyclic-coordinate descent (CCD) is used to determine rotations of the joints between the joint in question and the root that will minimize the distance between the joint in question and the desired position. This algorithm is shown in

is this similar to stating it works on a tree but not a graph with cycles? [+] yes, but it's a restricted tree in which each node has only ...

citation?reference? [+]

proscribed
vs
proscribed?

without
raising the
height of
the hips?

(dangling
preposition)...
we/the program
solves for the joint
angles and
positions of the
knee and angle.
[+] reworded to
active instead of
passive to avoid

"that" vs.
"which" (look up
rule & check for
other swaps
within document)

Algorithm 3.1.

who calls this
function? How do
they decide what
"D" should be?

Algorithm 3.1: Given chain of joints C, move joint E to position D using cyclic coordinate descent. This process iteratively moves joint E closer to the location D, concentrating on each joint R in the chain one at a time and solving the geometric problem of minimizing distance between E and D by rotating R.

i'm confused. is
R a 3 coordinate
vector? R is a
joint, is that it's at
rest skeleton
position? Are D
& E also 3
coordinate
vectors? I don't
understand
intuitively what
this equation is
doing. [+] added
more
explanation, I'll
add a diagram

```
function SINGLECHAINIK(C, D, E)
repeat
    for all Joints R between E and the root, starting with the end E do
         $\theta_R = \mathbf{RD} \times \mathbf{RE}$ 
    end for
    until Desired number of iterations performed or E is close enough to D
end function
```

This approach is simpler to implement than other approaches such as the pseudo-inverse of the Jacobian for the specific case of single chains of joints. In addition, this approach allows some flexibility, specifically in constraints of the system. As each joint is addressed individually instead of the system as a whole, any constraints placed on the joint can easily be accounted for by simply preventing the joint from rotating out of the desired range while the rest of the system continues to move as close as possible to the solution. One downside is that a halting condition must be determined, through a minimum acceptable distance. To handle cases where the joint cannot be moved within this minimum distance, a maximum number of iterations must be designated. In practice, 100 iterations is enough to converge, with as few as 30 working well for our simulation.

also, are you
guaranteed to find
an answer? Also
are you guaranteed
to find an optimal
answer? Ok if the
answer is no, but it
works in practice
for the less
complex problems
you are tackling.

3.5 Torque-based simulation

One method of simulation we attempted used springs placed along the length of each limb to produce a torque on the joints of the character. This method failed for unknown reasons. **Torques on the joints results** from the force of the muscle pulling a bone to rotate about the joint, resulting in a complex system of motion with each bone rotating around the joints. These rotations combine to move the body in a direction, allowing a character's control to be centered around degree and timing of muscle activation. Our method for this type of simulation was inspired by the other work in complex muscle based simulation for bipeds such as in Geijtenbeek

repetitive from
earlier
description...

singular
plural
mismatch

description
confusing

et al.. [3] In our case, we take the muscle as constantly activated, which means that its spring constant defines the strength of the muscle, allowing the user to set the activation manually. This muscle is then stretched to produce the desired torque by bending the affected limb. The restoring force of the spring-muscles produce torques which are used to calculate angular momentum, and from that linear momentum. Linear momentum is then used to calculate the resulting acceleration.

3.5.1 Path Estimation

need better title. what is being described in this section? "Calculating initial velocity and acceleration from desired air and windup times"

initial
ematic

Before calculations relating to the path estimation of the jump path is performed

calculation to determine the velocity required to move an object through the air from the initial position of the model to a final position.

The user specifies a desired time (t_{air}), which indicates the time the character will spend airborne during the animation, i.e. the time between when the character's feet break contact with the ground and when they regain contact with the ground. This is useful as the desired animation can be more easily adjusted to fit a desired time as an in-game animation or to fit a particular storyboard for an animated film sequence.

awkward to read,
rephrase

The initial velocity is given by a manipulation of a simple kinematic equation

$$\mathbf{x} = \mathbf{x}_0 + \mathbf{v}_0 t_{air} + \frac{1}{2} \mathbf{a} t_{air}^2$$

derived from the relationships between acceleration (\mathbf{a}), velocity (\mathbf{v}), and displacement ($\mathbf{x} - \mathbf{x}_0$), namely

$$\mathbf{v} = \frac{d\mathbf{x}}{dt}$$

$$\mathbf{a} = \frac{d\mathbf{v}}{dt}$$

This relationship gives us the velocity, given a known start position (\mathbf{x}_0), destination (\mathbf{x}), acceleration (\mathbf{a}), and time (t_{air}). As this describes the path of the character once it breaks contact with the ground, the time referred to only covers

physics intuitively and specifying time might be difficult to control/understand. just mention this in your writeup. its a challenge/limitation.

it seems like this can be unnatural to specify (an error prone), but maybe after a few tries maybe it does become intuitive? For game timing, so many games or non photorealistic animations are *not* physically plausible. The pause during a jump is unrealistic for effect (e.g. wile e. coyote hang time)

the desire to have a long hang time does not necessarily equate to it being acceptable to having a very high jump

i know you are calculating physically plausible jumps. but I claim artists might not intuitively understand the

the time between the character breaking contact with the ground and when their feet touch again at the end of the jump. The only force, and therefore acceleration acting upon the character while in the air is gravity, thus giving

$$\mathbf{v}_0 = \frac{\mathbf{x} - \mathbf{x}_0}{t_{air}} - \frac{\mathbf{g}t}{2}$$

to describe the initial velocity our character has upon breaking contact with the ground, which then decays over the course of the jump due to gravity to produce a parabolic path. The equation considers the character as a point mass traveling in a vacuum, meaning there is no consideration of friction, drag, or rotational movements. Acceleration can then be determined as

$$\begin{aligned} a &= \frac{dv}{dt} \\ &= \frac{\mathbf{v}_f - \mathbf{v}_i}{t_{windup}} \\ &= \frac{\mathbf{v}_0 - v_i}{t_{windup}} \end{aligned}$$

where \mathbf{v}_i is the initial velocity of the character before the jump calculations began. This accommodates jumps where the character is already moving.

3.5.2 Windup

need better title

Using the calculated velocity and acceleration, we compare the desired values to achieve a particular path with the values produced by the muscles on the skeleton. To compute a resultant instant linear acceleration, we start from the muscle and calculate the torque resulting from the muscle's contraction. First we calculate the scalar force of the muscle-spring as $F = -ks$ where s is the spring displacement as calculated in section 3.2.2. Using the scalar force, we calculate the torque and the angular momentum. Torque magnitude can be calculated as

$$\tau = rF$$

where r in this case is the scalar distance between the pivot point and the location of force application. In our case, this is the distance from the center of the joint

to the major anchor point, which we consider to be the anchor point highest in the hierarchy, which is the bone most expected to move. The direction of the torque is the normal vector to the plane of rotation, calculated as the cross product between the directions to each anchor point which gives the plane of rotation about the joint.

Angular momentum is derived from torque, as

$$\tau = \frac{d\mathbf{L}}{dt}$$

where τ is torque and \mathbf{L} is the angular momentum. The angular momentum can then be calculated as τt_{windup} . Angular momentum is used to calculate linear momentum by finding the tangent to the circle at the moment of takeoff. The magnitude of the linear momentum is then calculated as

$$p = \frac{L}{r}$$

which then gives the acceleration as follows

$$\mathbf{a} = \frac{1}{m} \left(\frac{d\mathbf{p}}{dt} \right)$$

where m is the mass of the character.


3.5.2.1 Sampling sampling what?

In order to determine the position of the character that produces this acceleration, we sample uniformly over the region in which the character is balanced. A sample is described by the position of the pelvis joint, the resulting linear momentum, and a vector describing the displacement of the character's center of mass from the center of its support to indicate balance as described above. Samples were restricted to a box defined by a rectangle around the character's feet with a height reaching the position of the character's pelvis when standing at rest. Any sample outside of this volume was assumed to put the character off balance. Samples were then taken at uniformly distributed positions in this region. The calculated acceleration was projected onto the desired acceleration vector through the dot product,

these two things are not the same, right? You discard points in the box that does not allow the character to be balanced and you might miss some samples where he his balanced (right?)

with values greater than or equal to the desired acceleration's magnitude indicating a plausible solution. These plausible solutions are then ordered by their balance error, calculated as the difference in position between the center of mass and the center of the supporting polygon. The first result of this list is then chosen as the candidate answer and the pelvis is moved towards this sample. At each iteration this is repeated until the desired acceleration is achieved. A plot of samples for a particular set of values, in this case all muscle constants set to $k = 20000$, is shown in Figure 3.4. An equation for the described calculation is shown below.

$$E_{accel} = \mathbf{a}_{desired}^2 - \mathbf{a}_{desired} \cdot \mathbf{a}_{calc} \leq \epsilon (\mathbf{a}_{desired}^2)$$



axis label
"position" is
wrong, this is
acceleration? [-]
no the axes are
actually
position, the
color is

Figure 3.4: Pictured above is a plot of instant linear acceleration samples at different pelvis positions within the balanced region. Color indicates the magnitude, with the red, green, and blue channels corresponding to the x, y, and z components respectively of the acceleration sample. Lighter color indicates a larger magnitude. This is a clear example of the failures of this simulation method, as the samples seem to continuously increase from the one corner of the bounding box to the opposite diagonally, which does not produce a plausible animation as the character heavily favors one side, even with symmetric strengths.

so this might be a
visualization bug as
well as a computation
bug? Or it might just
be a computation bug?
[+] only computation,
the visualization shows
that all of the values
are biased in
unexpected, nonsense
ways i.e. there is a
favoritism of one side
when there should not

Each iteration the error for the skeleton is calculated as for the samples but

unclear

for the current state of the skeleton. If the error is above the tolerance, a new position for the hip is calculated using proportional-derivative control, where the new position for the iteration of the controller, $u(i)$, is calculated as

$$u(i) = k_p E_{all}(i - 1) + k_d(E_{all}(i - 1) - E_{all}(i - 2))$$

where i is the iteration, and k_p and k_d are weights which determine the rate of change. The input to this PD controller is calculated by selecting a sample from the set of samples based on the acceleration error of the sample. After filtering all plausible candidates from the samples, the candidate which minimizes balance error is selected and the vector between the current pelvis position and the sample pelvis position is given to the PD controller.

The hip is repositioned based on the output of the PD controller, and the inverse kinematics component then iterates to calculate the positions of the remaining leg joints, assuming the feet should remain in the same position on the ground and the pelvis should remain at the chosen position. This chooses a solution for the intervening joints. At the next iteration, these new joint positions and angles are then used to compute the instant linear acceleration, center of mass, balance error, and acceleration error which are then passed back to the PD controller until the error in acceleration is below the tolerance.

3.5.3 Thrust and Takeoff

better title?

Upward acceleration is animated by calculating the angular accelerations of the joints given the forces acting upon them and the resulting torques. Torque is the change in angular momentum over time, allowing for the acceleration to be calculated as the mass can be assumed to be constant:

$$\tau = \frac{dL}{dt} = m \frac{dv_\theta}{dt} = ma_\theta$$

where τ is the torque of a joint, L is the angular momentum, m is the mass of the limb, which must take into account the mass of the rest of the body which is also moved by the limb, v_θ is the angular velocity and a_θ is the angular acceleration.

word extension
does not appear
in section 3.2.2

This results in the below equation for determining angular acceleration.

$$a_\theta = \frac{\tau}{m}$$

Using angular acceleration, the intermediary poses for the model can be determined at each time step. For each frame, an explicit Euler integration is performed to determine first angular velocity and finally angle. As the character continues to extend, a check is made for if the character has yet reached full extension as described in section 3.2.2. At full extension, the character can no longer accelerate in the direction of the jump, and the character breaks contact with the ground to enter the in-air phase.

As the windup phase of the torque based simulation fails, it is difficult to quantify or qualify the success and failure of this portion of the simulation. For values where the simulation could not complete the windup phase, the in-air portion is unavailable and for values where the windup phase completes, the values are erratic and fail to produce valid poses, often resulting in extreme contortions of the model.

might we
break contact
with the
ground
BEFORE
reaching full
extension?
(yes!) [+]
actually yeah,
hmm, i need
mv ~ mgi ~ at

use symmetric
title to 3.5
(used
"simulation"
instead of
"calculation",
which is more
appropriate?)

this is also
assuming
that full
extension
of the leg
will be
reached
before
contact
with the
ground is
broken?

shouldn't you be able to compare
the result for a particular input
between the two methods and they
should be the (approximately) same
answer? would this help with
debugging? [+] some parts of it
should be the same, which is a
further indicator of the failure of
torque simulation. the problem is
also that this is a much rougher
approximation, caring only about
the strength of the muscles instead
of caring about the torques

3.6 Energy Based Calculation

Another way we simulated jumping motions was that the kinetic energy of the character traveling at a start position to the destination position is equivalent to the potential energies of the leg muscles. The direction of the velocity vector in the direction the center of mass is accelerated after the windup phase. This means that this is achievable given that the character can achieve

Change in direction is accomplished through usage of the feet and shift of weight during the acceleration and windup phases, applied through balance and inverse kinematic calculations. If a character wishes to move forward, they shift their weight back farther during windup, allowing them to accelerate forward farther before becoming airborne. In the same way, shifting to one side can allow the character to accelerate in the opposite direction for non-forward jumps. As with the

torque-based simulation, the jump follows the stages of path estimation, windup, thrust, in-air, and landing.

3.6.1 Path Estimation and Windup

Kinetic energy is calculated as

better titles & match titles from previous section where appropriate

$$E_k = \frac{1}{2}mv^2$$

where m is the mass of the character and v is the velocity. Mass is a constant specified by the user, and we calculate the desired velocity and acceleration as in the torque based path estimation as described in section 3.5.1.

Like with the torque-based method, we took samples in the region where the character maintains balance as in section 3.5.2.1. Samples were collected at regular intervals within a bounding box defined by the character's supporting polygon, the ground, and the height of the character's pelvis at full extension. The pelvis was repositioned and the resulting elastic potential energy measured. Candidate samples were selected by finding all samples with

$$E_{kinetic} - E_{elastic} \leq \epsilon(E_{kinetic})$$

and the candidate with the lowest incurred balance error was selected.

Our sampling method does not guarantee an optimal solution, but can be seen as guaranteeing an approximate minimum. We choose a sample with minimum balance error and iteratively approach it, which greedily finds the nearest sample to the rest pose which satisfies the energy equivalence, $E_{kinetic} = \sum E_{elastic}$. While not guaranteed to be the minimum, this guarantees that we find a near-minimum value assuming the region is continuous. Figure 3.5 is a graph of samples for a particular run with all muscle k values set to 20000. Color indicates the calculated energy for the sample point, with higher saturation of blue indicating a higher energy value for the sample. The high energy points are clustered toward the center of the sample group, while the low energy points are clustered toward the periphery such that their hip is bent past 90 degrees.

its not clear why this is expected. athletic trainers say not to bend knee past 90 degrees, but this is because it hurts your knee joint or something, i would not expect this from an optimization [-] if you think about what is happening with the spring when you bend past 90, you lose all strength as the spring is now exerting its force with no leverage

can you argue that the region is continuous? what would cause it to be discontinuous?
[+] should be continuous but i can't really articulate why




Figure 3.5: A graph of samples for the character with all muscle k values set to 20000. The pelvis positions are plotted, with the color of the data point indicating the energy. A darker point indicates a higher total elastic energy calculated for the skeleton when the pelvis is positioned at that point.

their knees.

3.6.2 Solutions to the Energy Assignment Problem

The setup of the problem resembles a quadratic program. To solve this problem, we minimize:

$$\mathbf{x}^T \mathbf{Q} \mathbf{x}$$

subject to

$$\mathbf{x}^T \mathbf{P} \mathbf{x} \leq r$$

id like a diagram to
 see the 6 springs
 that correpond to
 these 6 constants.
 (I initially thought
 the 6 dimensions
 were position +
 rotation) [-] they're
 just leg muscles...is
 this helpful really?

where $x \in R^6$ and \mathbf{Q} and \mathbf{P} are square, 6×6 matrices. \mathbf{Q} for our problem is a diagonal matrix, where the diagonals contain the spring constants $\{k_1, k_2, \dots, k_6\}$ and \mathbf{P} is $-\mathbf{Q}$. We can introduce additional constraints in the form of maximum and minimum values for all $x_i \in \mathbf{x}$, where the minimum and maximum are calculated at the minimum and maximum rotations of the joint, producing the extremes in spring displacement.

This problem of quadratically constrained quadratic programming is NP-hard

not sure which function you are talking about

32

and as such we sought a simpler problem or approximation to solve to obtain a solution. As with the torque method, we choose a sampling-based approach as there is a known limit on the possible solutions in our case: balance.

3.6.3 Thrust, In Air, and Landing

Thrust for the energy based simulation works off of explicit euler integration. The calculated acceleration from the path estimation stage is used to accelerate the character over the duration of t_{windup} . At each time step, the pelvis is translated by $v_{takeoff}$, which begins at 0 and gains adt per frame. Each frame the character's extension is checked using the function described in section 3.2.2, and when it falls below a tolerance of 0.1, the character is considered fully extended and the in air phase begins. During the thrust, the movement can sometimes proceed faster than the IK solver can converge, so we pause the simulation briefly and only iterate the solver until it converges.

The in air phase proceeds similarly, with the character translated by the calculated velocity from the path estimate each frame. Velocity is modified by gdt where g is the acceleration due to gravity, resulting in the desired parabolic path of the player through the air. Ray casts are performed to check if the character's feet have contacted a surface to land on. These ray casts are made from above toe, heel, and middle of the foot, starting above and passing through the points to produce a longer ray for more stable results. Once one of these ray casts indicates the feet have touched such a surface, the character enters the landing phase.

A landing controller is beyond the scope of this thesis, and thus we end the simulation as the character's feet touch a suitable surface. As described in chapter 2, other controllers can be composed with this controller to produce a full animation, handling the complexities of the landing motion as a separate, modular controller.

3.7 Summary

The character is modeled as a mesh was created as a tree of joints with the the limbs, crossing a single joint and an

as you can tell from my previous comments about extension, I'm

why "ray cast", why not a collision detection? Or in unity is a collision detection done with ray cast? [+ ray cast provides a sort of selective vertex collision

[comment added later, when i was reading chapter 5...] this is first real mention of timing.... need for computation efficiency/ speed should be motivated earlier. this impacts sampling density choices.. I wasn't aware speed was important... [+ i was going for interactive framerates but I haven't been talking about it, should i?

and energy outputs of the muscles were calculated as linear springs, with spring displacements calculated from the angle of the joint. An inverse kinematic solver was used to aid in creating poses.

Two methods were used for the simulation, one using torque based calculations and the other using energy based calculations. Each method proceeded through the stages of path estimate, windup, thrust, in air, and landing, with similar calculations used to produce an error function to quantify character poses. In the torque based simulation, error was calculated by using the muscles to calculate torques, and from the torques accelerations. In the energy based simulation, error was calculated as the difference between elastic potential energy and target kinetic energy.

Samples were collected using these error functions, with the selected best sample minimizing both the balance error and either the acceleration or energy errors for the torque and energy simulations respectively. A PD controller iteratively moved the character's pelvis position towards the selected sample until the error between the calculated values for the frame and the desired values were below a tolerance. After the character moved its pelvis to the chosen sample position to reduce the error below tolerance, it performed the thrust and in air portions of the jump treated as a rigid body, with the simulation ending when the character's feet touch the ground.

ok, but could move beyond a summary
and a bit more into discussion,
compare/contrast, could discuss in
theory both methods should produce
the same answer... could discuss your
visualization, your debugging, speed of
calculation, limitations (not the optimal
soln) etc.

also add transition to
next chapter(s)

could add a bit
of transition
from previous
chapter "now
that we know
how to ... " (but
don't get too
repetitive with
the summary of
previous
chapter)

CHAPTER 4

VISUALIZATION

you mean "video"?
[?] i guess?
animations that
aren't videos i guess
kind of fall under
video?

In this chapter we motivate the need for good visualizations, as well as the ambiguity of visualizing character animation in print format as well as moving media. We then discuss techniques we utilized to visualize our data for presentation as well as for debugging and analysis.

4.1 Motivation and Inspiration

Showing a motion in a static medium such as print presents numerous challenges. The static image or images must convey a sense of time that is understandable, such that a viewer may intuit the direction and rate of movement. Especially for a complex object such as a figure, occlusion can obstruct information, and prevent understanding of the motion of hidden portions of the body. The projection of a 3D scene can also create similar issues as occlusion, creating ambiguity in depth and obscuring motions in some direc dimensione

We drew from several sources for inspiration on how to visualize our results. A video by KORB created for the CCTV Documentary Channel shows “motion sculptures,” in which the people in the scene leave trails of material as they move. These sculptures very cleverly captured the movement of the body throughout the space of the video, creating aesthetically pleasing, if somewhat difficult to parse, visuals.

Another film of a similar nature is Choros by Michael Langan and Terah Maher. Images of a single dancer follow her through her movements, leaving a traceable pattern of movement. This technique was inspired by chronophotography, a precursor to video which utilizes multiple successive photographs or multiple exposures on the same film to visualize movement of a figure or object. These can be laid out in animation strips or superimposed to create a single image.

should
this be
capitali
zed?
(i'm not
sure)
[+] they
didn't
so I
didn't

citation needed!

citation needed! [?]
i'm claiming that the
citation for choros
covers this as they
themselves
reference
chronophotography

citation needed!

4.2 Motion Visualization

Markers were used to highlight motion of particular parts of the body, such as the pelvis or center of mass. Other indicators placed on or around the figure can indicate other values, such as arrows to represent vectors of force. This however can result in clutter within the images, scene, or frame of video, occluding or distraction from the primary animation. Copies of the character could be left behind to produce an after image effect such as in the videos discussed in section 4.1. We used these techniques in conjunction with each other, enabling and disabling them as the situation required.




Figure 4.1: Above is an example of the markers tracking joints. With a high sample rate, a curve forms trailing along the path of the joint. Markers were placed at a rate of 10 per second of simulation time.

Markers were implemented as camera-facing “billboard” planes with a texture that were spawned with a user-specified frequency, following an arbitrary joint of the character. Each frame the orientation of the planes adjusts such that it faces the main active camera, allowing very little geometry to be used to produce an always visible visual to be placed in the scene. We used one of these for each joint in the legs as well as one for the pelvis in order to track the paths of the joints. This visualization was an interesting one to view, and gave a similar effect to motion sculptures, but was very difficult to understand without a reference to know which

should this
be
capitalized
?

color of marker corresponded to which joint. Even with knowledge of which joint followed which trail of markers, the visualization was difficult to understand, though it gave a good overview of the whole motion. These marker trails are shown in Figure 4.1.




Figure 4.2: Pictured above are examples of a ghost image visualization achieved by placing copies of the character model at a rate of 1 per 0.5s (pictured left) and 1 per 0.2s (pictured right).

We used a ghost image visualization as well in 2 ways: leaving copies of the character behind at a user defined rate and layering collected frame data. In the first method, we make a copy of only the model and necessary skeleton components, leaving out the extra data such as mass, constraints, and muscles used in our simulation, and match the positions and rotations of each of its joints to the character at the current time. The ghosts use a semi-transparent material to help differentiate between them and the model, as well as to provide some clarity as to each ghost's pose and combat the issues of occlusion. Examples of this visualization are shown in Figure 4.2.

An alternate method of forming the ghost image visualization was to layer numerous collected frames in an image editing program. This method was very work intensive, requiring each layer to be matte painted by hand. Algorithms and techniques in image processing and computer vision for automating this process, but for our purposes it was necessary to manually select the desired region in each image that should be visible in the final combined image. To reduce the negative effects of occlusion, layers above the first were given an opacity of 75%. Though work intensive, this produced an excellent visual for still media to show the path of the entire motion, but was a poor visual in many cases for showing detail of the movement as images often occlude each other. Examples of this visualization are

did you consider/attempt to show two different jumps overlaid on the same image? This allows more direct comparison. but has a host of added/different challenges. [+] i did not is this something i should add?




Figure 4.3: An example of the composited frames visualization, in which several frames of the animation are layered on top of each other, and matte painted to produce a combined image with all frames superimposed.

shown in Figure 4.3 and in Figure 5.1. As a compliment to this visual, we used animation strips, in which the frames were simply presented adjacent to each other in order from left to right. These strips are also found in the data tables presented in section 5.1 and in Figure 5.1.

For debugging visuals, we used a feature in Unity3D called Gizmos, which allowed debug drawing of primitive shapes. We used small spheres of various colors to show sample positions, target positions for the IK solver, corners of the supporting polygon, and the position of the center of mass. Rays were used to visualize velocity, acceleration, distance to the destination, and value of the samples. A screenshot of our Gizmos active for an energy based simulation are shown in Figure 4.4.

Similar to the Gizmos, we utilized a feature called Handles to ease setting and visualization of the joint constraints on the skeleton. Unlike a Gizmo, a Handle can be manipulated by the user to affect values in the simulation before run time. As shown in Figure 4.5, three handles were used to adjust pitch, yaw, and roll, color coded as red, green, and blue. Colors were chosen to correspond to the colors of the reference axes placed in the scene to aid the user, showing the red, green, and blue handles as limiting rotation about the x, y, and z axes respectively.

I prefer capitalizing any reference
"Section 1" and
"Figure 1" and
"Table 1" and
"Chapter 1". Be consistent.
Search through whole document.

add citation to documentation [?]
should the other unity3d and maya citations be to docs?




Figure 4.4: Pictured above are screenshots of Gizmos in the Unity3D Editor. The green points illustrate the sample field taken at the beginning of the jump, while the gray lines show the energy measured at this sample. The rays beginning at the player's pelvis show the magnitude and direction of the acceleration (magenta) and velocity (blue) of the character. The green line at the player's feet shows the displacement from the start position to the destination, and the cyan line starting at the player's pelvis shows the calculated kinetic energy. At right, a closer view of the samples is shown to show the blue dots which outline the balanced region which the samples were restricted to. The character is distanced from these samples as the Gizmos are drawn at the character's start position, and the character in this scene has completed its jump and is at the destination position. The orange particle is a marker placed at the start position.

add section on discussion... What did you use these visuals for? Anecdotes of what they helped you discover. Or what you hoped they'd help you discover.

Summary

In this chapter we discussed some difficulties in visualizing animations in both animated and non-animated settings. We presented some sources of inspiration and discussed the different methods we used to visualize data for presentation, analysis, and debugging. Methods we used for analysis and presentation included trails of markers, ghost images created by duplicating the player model in the scene, layering frames to create a single image, and animation strips. Our debugging visualizations took advantage of Unity3D utilities, using Gizmos and Handles to allow the user to see information about the simulation, as well as to more easily adjust constraints on the skeleton.



Figure 4.5: Shown above are Handles, a tool similar to Gizmos but with the addition of changing a value. In this case, the Handles affect the minimum and maximum rotation for the joints. Handles are only visible when the corresponding object is selected by the user, reducing clutter. All three Handles are shown in the left image, allowing the user to set the constraints for pitch (red), yaw (green), and roll (blue) as the pelvis is set to allow rotations about all three axes. At right, we show the Handle for adjusting the constraints of the left knee, which is only able to rotate about the x-axis (pitch).

this is so cool, your writeup on handles is too short! pros & cons... discuss! what else could benefit from this visual?

transition from previous chapters.

why is speed important? can't these be solved offline? What about in 10 years when computers are faster, is your thesis still an interesting analysis? [+] this is more about not adjusting relative to the movement of the character in a timestep, i.e. more iterations are required for convergence than in the rest of the simulation. while we normally used about 30 iterations to converge this required more like 300

citation for source of "normal" human constants?

are these numbers your estimate, or do they come from references? [+]/my estimate

expert judgement. (not expected for your thesis) but to state scientifically, would need to be verified by either a panel of non expert humans or some bio expert(s).

CHAPTER 5 RESULTS

windup PD controller was given constants of $k_p = 0.25$ and $k_d = 0.25$. These were chosen empirically to offset irregularities due to time step and slow convergence of the inverse kinematic solver. With higher values, the translation of the pelvis results in the character's feet embedding in the ground plane due to too great a movement in a single frame. The feet then fail to adjust as the inverse kinematic solver cannot converge quickly enough. These values were found to generally produce smooth windup phases without compromising on speed of the animation too much.

Muscle spring constants were tested in various configurations, with several runs for each set of constants for varying distances, directions, and situations. Animations were created for forward jumps between 1m and 2m for the normal human and at 1m, 10m, and 100m for the super human. A jump onto a box was also simulated, with 0.5m and 0.75m boxes for the normal human and 1m and 100m boxes for the super human. The normal human muscle constants were initially used for sideways jumping animations, as well as a more complex one in which the character is made to jump from on top of a box, over an obstacle, finally landing on the ground.

seems very far.
What about smaller jumps?

Jump animations appear plausible, and the spring values result in forces similar to a human muscle. Human muscles have about $30 \frac{N}{cm^2}$ force per cross-sectional area. [7] The character's leg thickness is about 0.20m forward to back narrowing towards the knee, with a left-right thickness of around 0.15m. If we assume that skin is about 0.002m thick (2mm) and about 15% of the remainder is subcutaneous fat, we are left with a 0.1683m by 0.1258m cross section. This gives an axial cross sectional area of approximately 0.021m². We use a bone width of 0.05m, giving a cross sectional bone area of 0.0025m² which leaves an area of 0.019m² of non-bone muscle. If half of this is extensor muscle, then we have an approximate cross sectional area of 0.0095m² or 95cm². This means that the estimated maximum isometric force for the muscle is $F = (30 \frac{N}{cm^2}) (95cm^2) = 2850N$. With a k of 20000,

diagram of this math? [-] maybe, probably not.

citation should be before period.
Would be good to drop in the title/ name of this source. Hopefully it is a bio source not a CSCI source?

our muscle produces

$$F = -k \left(\frac{r \sin(\pi - \theta)}{\sin \frac{\theta}{2}} \right)$$

is this reasonable number? I have no idea

which for a joint bend of $\frac{\pi}{2}$ radians is 1414N. A more accurate k value for the single muscle would be 40000 but 20000 suffices as the smaller muscles of the calf are modeled as overly strong. The k value was determined empirically, following the assumption that an average person has a max long jump in the range of 1.5m to 2m. A possible explanation is that our simulated character can perfectly execute the movement, maintaining balance and applying force. There is a non-trivial technical aspect to performing a jump, meaning that a human with the capability to perform a longer jump may not be capable of maximizing their range due to imperfect technique.

The produced animations are plausible and recognizable as jump animations. The character loads its limbs appropriately, giving the appearance of weight, and extends its knees, hips, and lastly ankles to show thrust corresponding to the usage of its muscles. As in a real jump, the character extends its ankles last, the calf muscle providing the final thrust of the motion.

according to who?

The simulation runs in an interactive frame rate, with a delay on start up for the calculation of the sample field. As long as the mass and the muscle constants remain the same, the sample field need not be re-calculated. The sample field calculation is linear in the number of samples taken. A major bottleneck aside from populating the sample field is the convergence of the inverse kinematic solver. The solver is guaranteed to run every frame, usually for many iterations unless it has already converged. While the cost is manageable due to the linear nature of the algorithm, the main issue is when convergence does not occur and the simulation must either stop and wait for the solver to catch up, or continue on and risk corrupting the simulation due to misplaced joints or limbs. There are two major cases of this occurring: the character's feet sinking into the ground instead of the knees bending during windup and the character's feet prematurely breaking contact with the ground during thrust. Our simulation suspends its activities when a compromising situation is detected, iterating the inverse kinematic solver until the issue

are you implying that humans are imperfect machines? (citation on typically how imperfect?)

have you shown them to others? give some credentials to yourself or others for making these judgements (comparing to videos... other simulation, lots of studying... etc)

citation?

I like that you have real numbers here, but please be more liberal with the citations

include the title/author with the citation, to give more weight & confidence to these numbers (when you have a reference)

"According to the American Academy on Physiology..." (i made that up)

only second mention of timing [first at end of chapter 3?], should be (more clearly?) in intro if this is a requirement/goal of your work.

chapter needs an introduction and subsection organization. 2.5 pages before first section isn't right...

did you use this term consistently when you introduced the sampling method in earlier chapter? Include a back reference to one of your figures showing this.

guaranteed? Or it is necessary to run every frame?

how bad is this
"undesired time"?
What is the
application? Is
this for a game?
(again, more
clearly discuss
this in the intro
and in the
method/
implementation
choices chapters.

is resolved. The solver usually converges within a few frames, but this can add undesired time to the simulation and undesired frames to the animation.

Frame data was collected at a rate of 1 frame per 0.1s of simulation time, giving a frame rate of 10 frames per second. This granularity was used to ensure capture of any irregularities in the simulation and to ensure changes in pose were recorded as shorter trials ran in under 1s of simulation time, though the real time was several seconds. Finer granularity was found to have little benefit. We show one of five frames in the tables discussed in section 5.1 to reduce the size of the animation strips presented and thereby reduce the size of our tables.

	Left Hip	Left Knee	Left Ankle	Right Hip	Right Knee	Right Ankle
Global, Normal	20000	20000	20000	20000	20000	20000
Varying, Normal	20000	24000	16000	20000	24000	16000
Uneven Global, Normal	16000	16000	16000	24000	24000	24000
Uneven Varying, Normal	24000	28000	20000	16000	20000	12000
Global, Super	1×10^{10}					

Table 5.1: This table shows muscle spring constants (k) values used for several trial runs. Each column represents a muscle, described by the center joint which indicates the joint the muscle crosses and affects. Each row represents a different trial, with a set of k values. Global runs used a uniform k for one or both sides of the body, while varying runs used different spring constants for each muscle. Uneven runs were meant to mimic a character with an injury or other source of imbalance where one leg was significantly stronger than the other.

5.1 Output Animations

Several trials were run with different, empirically determined k values as shown in Table 5.1. The destination position was chosen for each to demonstrate the range of motions possible with our simulation. Trials can be divided into several types: forward jumps, sideways jumps, and box jumps. In a forward jump, the character starts from standing and jumps forward to a destination. A sideways jump is the same, except requiring the character to jump to the right without first turning. Box jumps required the character to jump from standing to land on an obstacle in front of them. Additionally, a more complex scene was constructed, in which the character starts standing on a box. The character then jumps off the box, over and

chapter
disorganize
d. better
section title
needed for
this
paragraph

is this "the complex scene" or
do you want to call it the "box
jump off w/ obstacle scene" (or
some other consistent name)

why
paragraph
break?

obstacle, and lands on the floor below.

The complex scene is pictured in the box on which the character starts is 1m in height, and the obstacle is 1.4m in height. To achieve the path shown, the destination was set at $(0, 1.5, 1)$, with the starting position at $(0, 0, 0)$. Muscle spring constants were set for all muscles globally as $k = 20000$.

get the figure placed earlier

provide a motivation for the choice of these jump distances... what are you hoping to test/demonstrate? a pre-discussion :)

Forward jumps are shown in Tables 5.2, 5.4, and 5.6. For the super human, jump destinations were set 1m and 100m in front of the character's starting position. For the normal human, jumps were set at 1m, 1.3m, 1.6m, and 1.9m, shown in Table 5.2 for a globally set k and in Table 5.4 for a varying k . Box jumps are also included in these tables, with 1m, 10m, and 100m boxes for the super human and 0.5m and 1m for the normal human. Animations were produced for normal human strength with both a globally set $k = 20000$, where each muscle had the same constant, and varying with $k = 20000 \pm 4000$ as shown in Table 5.1.

In Table 5.5 we show forward jumping motions of 1.6m and 1.9m where the character has uneven strength in their legs. These values were chosen similar to the normal human run. There is little effect, which is why lengths shown were only at the extreme of distance possible for the character. However, the character's right leg can be seen to dangle in the trial with varying k values, indicating that more load is on the left leg.

To demonstrate the flexibility of a simulation-based animation, we also include a jump to the side. The destination was specified as 1m, 1.3m, and 1.6m to the right, i.e. the direction $(1, 0, 0)$ relative to the character, of the character's start position. Instead of the pelvis thrusting forward and up, in these trials the pelvis thrust is to the side and upwards as expected. These animations are shown in Table 5.3 and were collected with a global $k = 20000$.

5.2 Limitations

Our system has a number of limitations and failure cases. First is that there are many constants to be specified, which is work intensive but gives freedom to make wide changes to the animation by tuning parameters

There are numerous small issues with the calculations caused by strange or

by "run" do you mean like the running motion or do you mean like a test case?

citation for "normal"

did you consider/test diagonal jump (forward & to the right)?




Figure 5.1: Pictured is an animation of a complex scene, in which the character must jump from on top of a box, over another box and land on the ground. The first image in the figure shows the frames composited into one image to visualize the full motion, while the remaining images show the individual frames. This run used $t_{windup} = 0.2s$ and $t_{air} = 0.5s$.

unexpected interactions. Foremost is the behavior of rotations and angle measurement in Unity3D. Angles are read and interacted with as Euler angles, pitch, roll, and yaw, or rotation about the x, z, and y axes respectively. Rotations, however, are stored and calculated by the engine in the form of quaternions. Due to the conversions between the two, and various manipulations that occur in the scene, this can result in angles not restricted to $[-360, 360]$ degrees, and can result in jumps between positive and negative angles. A solution would be to restrict the angles to positive angles in the range $[0, 360]$ for all calculations and manipulations, but this

euler angles has the classic problem of gimbal lock. is/was that a problem for you? [+] conversion of specify as euler -> use quaternions prevents this

makes specifying constraints more complex.

confusing wording. i don't know what you mean.

Problems with angle also arise as the angle of the joint does not necessarily reflect the angle between the bones. For example, when the knee is fully extended, the joint angle stored in the object is 0, but the angle between the bones is π radians. A solution is to calculate the angle between the bones of the joint when needed using the dot product of the vectors between the joint and its parent and the joint and its child. We did not realize that there was still an issue with angle specification as the issue was balanced out as the supplementary angle was used erroneously, but a fully correct implementation would be desirable for true consistency. The data was collected with the flawed implementation, though as previously stated it produced similar results.

Movement of the upper body is very minimal, and is quite unlike a human performing a long jump. This is likely due to the restriction of pelvis reposition to the region over the supporting polygon. Humans frequently move their pelvises far behind their supporting polygon, compensating using the weight of their upper body. The usage of rapid movement of the upper body to aid in acceleration is also a factor we do not consider, such as the effects of arm swing on a jump.

As our simulation was focused on the movements leading to the airborne phase, the handling of in air maneuvers and landing are overly simplistic. After the character becomes airborne, the pelvis will generally be displaced in the direction of acceleration relative to the feet. The character should maneuver while airborne such that their feet are in front of their body to prepare for landing. For landing, a reverse of the windup for the energy simulation could be used, loading the muscles in the legs to offset the kinetic energy the character has from the jump, converting it to elastic energy in the muscles. Landing and airborne phases should be handled ideally by a separate controller.

Our inverse kinematic solver is also very simple, and brings its own issues due to this simplicity. This algorithm was chosen specifically to minimize time, effort, and resources spent on the inverse kinematic component, in favor of the simulation itself. With a different inverse kinematic solver, better results could be achieved.

The output of our simulation is currently image frames as well as the direct

in what way? more natural human like? favoring certain joints over others?

"I" would be more natural here.

can humans achieve near their maximum long jump without their arms? (I think this would be a significant limitation!)

what is this?
citation?

46

visualization through Unity3D, as opposed to a key frame animation in a format such as FBX, which could be utilized in video games. An AutoDesk Maya plugin that runs our simulation would also be more useful for allowing creation of animations if a real-time frame rate cannot be achieved.

citation

5.3 Summary

Plausible animations were created, with empirically determined k values around 20000. Analysis shows different values would be theoretically more realistic, but the empirically determined values still produced reasonable animations. Animations were produced for a normal strength human as well as a super human for forward standing jumps, sideways standing jumps, and box jumps. A scene was constructed in which the character jumped from on top of a box, over an obstacle, and landed on the ground below to show a more complex scene. We discussed in this chapter the values used and method for collecting data, and presented sets of frames collected from several simulations with a variety of scenes. Animations depicted forward, sideways, and box jumps for a normal human range of strength and for a super human strength. An animation of a character jumping over an obstacle was also presented.


this paragraph is quite dull. might be better combined with previous section? Or focus more on transition to next chapter?

the "k values" you mention in the opening sentence of this chapter is 0.25. WHAT??? I'm confused.

way too small!!!!

crop crop crop

47



call this a figure not a table. the labels are nice, but it's a figure.

Table 5.2: Table of forward and box jump motions for a character with global $k = 20000$, $t_{windup} = 0.2s$, and $t_{air} = 0.5s$. The boxes were placed 0.75m in front of the character, with the character's target destination set 0.3m in front of the character on top of the box.

get these figures placed closer to their call out. Perhaps use the [p] option for latex figure.

1m right				
1.3m right				
1.6m right				

Table 5.3: Table of right jump motions for a character with global $k = 20000$, $t_{windup} = 0.2s$, and $t_{air} = 0.5s$. The target was placed at the distance listed in the table in the direction $(1, 0, 0)$ relative to the character.

1m forward				
1.3m forward				
1.6m forward				
1.9m forward				
0.5m box				
0.75m box				

Table 5.4: Table of forward and box jump motions for a character with varying $k \approx 20000$, $t_{windup} = 0.2s$, and $t_{air} = 0.5s$. The boxes were placed 0.75m in front of the character, with the character's target destination set 0.3m in front of the character on top of the box.



				
1.6m forward (global $k =$ 20000)				
1.9m forward (global $k =$ 20000)				
1.6m forward (varying $k =$ 20000)				
1.9m forward (varying $k =$ 20000)				

Table 5.5: Table of forward jumping motions with uneven muscle strengths between legs, using $t_{windup} = 0.2s$ and $t_{air} = 0.5s$.




Table 5.6: Above are generated frame sequences for the super human trial, where the k values were chosen such that the character could leap over a tall building, a 100m tall box. Animations above were generated for 1m, 10m, and 100m forward jumps. The 100m forward jump is not pictured due to the difficulty of capture, as either the jump was out of the range of the camera or the camera was too far to clearly see the animation.




Table 5.7: Animations of 1m and 100m box jumps for the super human.
This run uses $t_{windup} = 1s$ and $t_{air} = 5s$.

transition from previous chapters. this opening paragraph is dull and isn't telling me much more than the chapter title is.

CHAPTER 6

FUTURE WORK AND CONCLUSION

In this chapter we discuss future work and conclude our discussion of research on this simulation. Section 6.1 discusses possible and planned work on this topic, as well as potential future work in this and closely related lines of study. Section 6.2 concludes this document with final thoughts and a summary of the document.

6.1 Future Work

We planned some further work that we decided was beyond the scope of this thesis. Our current system does not allow much flexibility with specification of the path the character travels for its jump. Jumping path estimation could be performed based on a policy. Possible policies are achieving a height while jumping to a target destination, pathing to clear an object or intersect with an object, follow a path defined by the user, and jumping with a user specified velocity or speed. These policies would require a smarter handling of the in air phase of the jump, which would be best implemented as a secondary controller to allow controller composition for more complex motions. A more complex in air controller would ideally handle cases such as acrobatics, in air maneuvers, and checking for citations.

Current work exists for landing motions such as described in chapter 2. Ha et al. describes an example of one such controller for a falling and landing motions. Incorporation of such other controllers would allow creation of more complex animations. A separate controller could also be used for improving the motions of the upper body for each of these phases. This could be used to create complex freerunning animations such as vaults and wall runs which are becoming prevalent in video games such as Mirror's Edge.

To help with choosing values, a learning model could be applied. Animations could be marked as successful and desirable by humans to train an algorithm to choose desirable constants for the muscles given target destinations. Machine learning could also be applied for learning a function to determine muscle load in the

are their prior work examples of this?

windup phase of our simulation. Intuitively the situation seems to fit a learning model well, but more study would be required.

Both simulations were solved using a sampling solution, but could have been solved using an optimization problem. Solving the optimization problem, such as the quadratic program in 3.6.2 would likely provide a better solution and would give stronger guarantees of optimality. This would likely decrease performance.

Our animation output is currently images. A more desirable animation output would be key frames storing the positions and orientations for each joint of the character's skeleton, which could then be used in a game or video as a pre-baked animation. An implementation as a plugin for AutoDesk Maya could also be more desirable, as it could then be incorporated into an artist's work flow. We chose not to use AutoDesk Maya initially for an implementation initially due to familiarity with Unity3D and so that we could obtain live visuals of the simulation with debugging information easily as the simulation was performed and animation played.

Another option would be to utilize MecAnim, a feature of Unity3D. We chose not to use this feature while performing the initial research, due to lack of understanding of the limitations and features available in MecAnim. After completing further research, there are many components of MecAnim that would improve our simulation and increase its ease of incorporation into game development and animation workflows. Our simulation could be re-tooled to output animation clips for MecAnim, and our constraint system replaced with the one provided by MecAnim. MecAnim muscles do not provide the functionality required, so our muscle component would need to be modified and reapplied to the skeleton. As is, our simulation is very close to producing output that could be used as an input to MecAnim, making this a promising direction for future work on the implementation.

6.2 Conclusion and Summary

In this thesis, we discussed the need for a more efficient way to produce character animations for video games and film. We then presented a simulation based approach for creating such animations for a jumping motion of a character to reach a given target position. Our system used two different types of simulation: torque

based and energy based. The torque based simulation failed to produce good results, but we collected frame data for a variety of situations using the energy based simulation. We then described our methods for visualizing the animations to quantify and qualify the performance, giving visual information in an animated format and still format.

References

- [1] S. Ha, Y. Ye, and C. K. Liu, “Falling and landing motion control for character animation,” *ACM Trans. Graph.*, vol. 31, no. 6, pp. 155:1–155:9, Nov. 2012. [Online]. Available: <http://doi.acm.org/10.1145/2366145.2366174>
- [2] P. Faloutsos, M. van de Panne, and D. Terzopoulos, “Composable controllers for physics-based character animation,” in *Proceedings of the 28th Annual Conference on Computer Graphics and Interactive Techniques*, ser. SIGGRAPH ’01. New York, NY, USA: ACM, 2001, pp. 251–260. [Online]. Available: <http://doi.acm.org/10.1145/383259.383287>
- [3] T. Geijtenbeek, M. van de Panne, and A. F. van der Stappen, “Flexible muscle-based locomotion for bipedal creatures,” *ACM Transactions on Graphics*, vol. 32, no. 6, 2013.
- [4] Y. Koga, K. Kondo, J. Kuffner, and J.-C. Latombe, “Planning motions with intentions,” in *Proceedings of the 21st Annual Conference on Computer Graphics and Interactive Techniques*, ser. SIGGRAPH ’94. New York, NY, USA: ACM, 1994, pp. 395–408. [Online]. Available: <http://doi.acm.org/10.1145/192161.192266>
- [5] J. K. Hodgins, W. L. Wooten, D. C. Brogan, and J. F. O’Brien, “Animating human athletics,” in *Proceedings of the 22Nd Annual Conference on Computer Graphics and Interactive Techniques*, ser. SIGGRAPH ’95. New York, NY, USA: ACM, 1995, pp. 71–78. [Online]. Available: <http://doi.acm.org/10.1145/218380.218414>
- [6] T. Geijtenbeek and N. Pronost, “Interactive character animation using simulated physics: A state-of-the-art review,” *Computer Graphics Forum*, vol. 31, no. 8, pp. 2492–2515, 2012. [Online]. Available: <http://dx.doi.org/10.1111/j.1467-8659.2012.03189.x>

- [7] P. M. McGinnis, *Biomechanics of Sport and Exercise*. Champaign, IL, USA: Human Kinetics, March 2013.
- [8] i. Pei-shan Xie¹ and i. Xing Cai², “Research on computer modeling of human movement.” *Advanced Materials Research*, no. 926-930, pp. 4190 – 4193, 2014. [Online]. Available: <http://libproxy.rpi.edu/login?url=http://search.ebscohost.com/login.aspx?direct=true&zdb=aci&AN=96297571&site=eds-live&scope=site>
- [9] S. Jain and C. K. Liu, “Controlling physics-based characters using soft contacts.”
- [10] M. Alexander and A. Honish, “Footwork for the volleyball block.”
- [11] T. Amasay, “Static block jump techniques in volleyball: Upright versus squatting start position.”
- [12] S. Jain, Y. Ye, and C. K. Liu, “Optimization-based interactive motion synthesis,” *ACM Trans. Graph.*, vol. 28, no. 1, pp. 10:1–10:12, Feb. 2009. [Online]. Available: <http://doi.acm.org/10.1145/1477926.1477936>
- [13] R. S. S. G. C. Roberto Lobietti, Silvia Fantozzi, “A biomechanical comparison of jumping techniques in the volleyball block and spike.”
- [14] S. Coros, P. Beaudoin, and M. van de Panne, “Robust task-based control policies for physics-based characters,” *ACM Trans. Graph.*, vol. 28, no. 5, pp. 170:1–170:9, Dec. 2009. [Online]. Available: <http://doi.acm.org/10.1145/1618452.1618516>
- [15] H. C. Sun and D. N. Metaxas, “Automating gait generation,” in *Proceedings of the 28th Annual Conference on Computer Graphics and Interactive Techniques*, ser. SIGGRAPH ’01. New York, NY, USA: ACM, 2001, pp. 261–270. [Online]. Available: <http://doi.acm.org/10.1145/383259.383288>
- [16] J. Babič and J. Lenarčič, *Vertical Jump: Biomechanical Analysis and Simulation Study*. InTech, June 2007, ch. 31.

- [17] Z. M. R. Zajac, Felix E. and W. S. Levine, "Hindlimb muscular activity, kinetics and kinematics of cats jumping to their maximum achievable heights," *The Journal of Experimental Biology*, vol. 91, pp. 73–86, 1980.
- [18] F. E. Zajac, "Thigh muscle activity during maximum-height jumps by cats," *Journal of Neurophysiology*, vol. 53, no. 4, pp. 979–994, 1985.
- [19] J. Hayes, "Creating character animation assets," pp. 2–3, November 1999.
[Online]. Available: http://www.gamasutra.com/view/feature/131796/creating_character_animation_assets.php