

Job Coach - Runbook operational, deployment, update si migrare

Document de knowledge pentru oameni si AI (Copilot / Claude)

Data: 22.06.2026 — Versiunea 2

Scopul documentului

Acest document are 3 scopuri principale:

- sa poata fi urmarit cap-coada pentru 4 scenarii clare: **deploy de la zero, update-uri ulterioare, publicare in Google Play, mutare pe alta infrastruktura;**
- sa fie o sursa de knowledge pentru AI (Copilot, Claude) daca istoricul chat-ului dispare si trebuie reconstruit contextul tehnic si operational;
- sa documenteze toate secretele, cheile si configurarile necesare pentru a reconstitui environment-ul complet.

Limba folosita este in principal romana fara diacritice. Unde termenii tehnici sunt mai clari in engleza, au fost pastrati in engleza.

Context tehnic si arhitectura

Aplicatia este impartita in 2 componente majore:

- **mobile**: aplicatia Flutter Android, cu modulele Job Fit, Cover Letter, Profile Boost;
- **server**: backend Python/FastAPI publicat in Azure App Service, cu PostgreSQL Flexible Server ca baza de date.

Elemente importante folosite in proiect

Element	Valoare
Repo GitHub	ionutc19/job-pack
App Service API	jobcoach-api-ionut-se
Resource Group	rg-jobcoach-prod
App Service Plan	jobcoach-asp-linux (B1 Linux)
PostgreSQL Server	jobcoach-pg-ionut (Flexible Server, Burstable B1ms)
PostgreSQL Database	jobcoach
PostgreSQL Admin User	jobcoachadmin
VNet	jobcoach-vnet (10.20.0.0/16)
Subnet App Service	snet-appservice (10.20.1.0/24)
Subnet PostgreSQL	snet-postgres (10.20.2.0/24)
Package Android	com.ionutc19.jobcoach
Base URL backend	https://jobcoach-api-ionut-se.azurewebsites.net
AdMob App ID	ca-app-pub-1738145743199175~1335978994
AdMob Banner Unit ID	ca-app-pub-1738145743199175/4301053689
Google Cloud Project	jobcoach-500216

Service Account (Play Billing)	jobcoach-play-billing@jobcoach-500216.iam.gserviceaccount.com
Subscription Premium Product ID	jobcoach_premium_monthly (\$3.99/luna)
Subscription Pro Product ID	jobcoach_pro_monthly (\$9.99/luna)
Privacy Policy URL	https://ionutc19.github.io/job-pack/privacy-policy.html
Terms of Service URL	https://ionutc19.github.io/job-pack/terms-of-service.html

Secrete si variabile de mediu (Azure App Settings)

Variabila	Descriere	Obligativiu
DATABASE_URL	Connection string PostgreSQL	Da
GOOGLE_PLAY_CREDENTIALS_JSON	JSON complet al service account-ului Google Cloud (pentru verificare achizitii)	Da (pentru billing)
RTDN_SECRET	Secret partajat pentru webhook-ul Real-Time Developer Notifications	Recomandat
AI_API_KEY	API key pentru Azure OpenAI / alt provider AI	Nu (fallback rule-based)
AI_BASE_URL	Base URL pentru API-ul AI	Nu
AI_MODEL	Model identifier (ex: gpt-4o)	Nu
GITHUB_TOKEN	GitHub PAT pentru feedback → issues	Nu

ADMIN_SECRET	Secret pentru endpoint-urile admin	Recomandat
SCM_DO_BUILD_DURING_DEPLOYMENT	Trebuie setat pe "true" pentru build automat la deploy	Da
WEBSITES_PORT	Portul pe care asculta backend-ul (8000)	Da

Modelul operational corect: cod in GitHub → deploy backend in Azure App Service → testare mobile → build release APK/AAB → Play Console Internal Testing → apoi rollout mai larg.

Capitolul 1 - Cum fac deploy de la zero

Acest capitol descrie constructia unui environment nou, pornind de la zero. Se presupune ca ai acces la Azure, GitHub si local workstation Windows cu Flutter, Android Studio, Azure CLI si Git instalate.

1.1. Prerequisites locale

- Git instalat si configurat (git clone, git pull, git push);
- Azure CLI autentificat: `az login` ;
- Flutter SDK functional: `flutter doctor` fara erori critice;
- Android Studio + Android SDK + emulator sau telefon Android pentru testare;
- Python local pentru operatii auxiliare, daca este nevoie;
- Acces la contul de GitHub si la subscription-ul Azure.

1.2. Clonare repository

```
git clone https://github.com/ionutc19/job-pack
cd C:\github\job-pack
```

1.3. IaC pentru infrastructura - variabile standard

```
$loc = "westeurope"
$rg = "rg-jobcoach-prod"
$vnet = "jobcoach-vnet"
$subnetApp = "snet-appservice"
$subnetPg = "snet-postgres"
$plan = "jobcoach-asp-linux"
$app = "jobcoach-api-ionut-se"
$pg = "jobcoach-pg-ionut"
$pgDb = "jobcoach"
$pgUser = "jobcoachadmin"
```

1.4. IaC - provisioning Azure prin Azure CLI

```
az group create --name $rg --location $loc

az network vnet create `
  --resource-group $rg `
  --name $vnet `
  --address-prefix 10.20.0.0/16 `
  --subnet-name $subnetApp `
  --subnet-prefix 10.20.1.0/24
```

```

az network vnet subnet create `
  --resource-group $rg `
  --vnet-name $vnet `
  --name $subnetPg `
  --address-prefixes 10.20.2.0/24 `
  --delegations Microsoft.DBforPostgreSQL/flexibleServers

az appservice plan create `
  --resource-group $rg `
  --name $plan `
  --location $loc `
  --is-linux `
  --sku B1

az webapp create `
  --resource-group $rg `
  --plan $plan `
  --name $app `
  --runtime "PYTHON|3.12"

az postgres flexible-server create `
  --resource-group $rg `
  --name $pg `
  --location $loc `
  --tier Burstable `
  --sku-name Standard_B1ms `
  --version 17 `
  --admin-user $pgUser `
  --admin-password "<PAROLA_SIGURA_AICI>" `
  --vnet $vnet `
  --subnet $subnetPg `
  --private-dns-zone "<private-dns-zone>"

az postgres flexible-server db create `
  --resource-group $rg `
  --server-name $pg `
  --database-name $pgDb

az webapp vnet-integration add `
  --resource-group $rg `
  --name $app `
  --vnet $vnet `
  --subnet $subnetApp

```

1.5. IaC alternativ - Bicep minimal (recomandat pentru portabilitate)

```

param location string = resourceGroup().location
param appName string
param planName string
param vnetName string
param appSubnetName string
param pgSubnetName string
param pgServerName string
param pgAdminUser string

```

```

@secure()
param pgAdminPassword string

resource vnet 'Microsoft.Network/virtualNetworks@2023-09-01' = {
  name: vnetName
  location: location
  properties: {
    addressSpace: { addressPrefixes: ['10.20.0.0/16'] }
    subnets: [
      {
        name: appSubnetName
        properties: { addressPrefix: '10.20.1.0/24', delegations: [] }
      }
      {
        name: pgSubnetName
        properties: {
          addressPrefix: '10.20.2.0/24'
          delegations: [{
            name: 'pgDelegation'
            properties: { serviceName: 'Microsoft.DBforPostgreSQL/flexibleServers' }
          }]
        }
      }
    ]
  }
}

resource plan 'Microsoft.Web/serverfarms@2023-12-01' = {
  name: planName
  location: location
  sku: { name: 'B1', tier: 'Basic' }
  kind: 'linux'
  properties: { reserved: true }
}

resource web 'Microsoft.Web/sites@2023-12-01' = {
  name: appName
  location: location
  kind: 'app,linux'
  properties: {
    serverFarmId: plan.id
    siteConfig: {
      linuxFxVersion: 'PYTHON|3.12'
      appSettings: [
        { name: 'SCM_DO_BUILD_DURING_DEPLOYMENT'; value: 'true' }
        { name: 'WEBSITES_PORT'; value: '8000' }
      ]
    }
  }
}

```

1.6. Configurare backend in App Service

```
$dbUrl = "postgresql+psycopg2://<user>:<password>@<hostname>:5432/jobcoach?sslmode=require"
```



```

az webapp config appsettings set `
  --resource-group $rg `
  --name $app `
  --settings DATABASE_URL=$dbUrl

az webapp config appsettings set `
  --resource-group $rg `
  --name $app `
  --settings SCM_DO_BUILD_DURING_DEPLOYMENT=true WEBSITES_PORT=8000

az webapp config set `
  --resource-group $rg `
  --name $app `
  --startup-file "bash /home/site/wwwroot/startup.sh"

```

Atentie: startup.sh trebuie sa fie LF (nu CRLF) si sa nu aiba caractere ascunse.

1.7. Deploy backend initial

```

cd C:\github\job-pack\server
Compress-Archive -Path * -DestinationPath ..\jobcoach-server.zip -Force

az webapp deploy `
  --resource-group "rg-jobcoach-prod" `
  --name "jobcoach-api-ionut-se" `
  --src-path "C:\github\job-pack\jobcoach-server.zip" `
  --type zip

az webapp restart `
  --resource-group "rg-jobcoach-prod" `
  --name "jobcoach-api-ionut-se"

```

Zip-ul trebuie sa contina direct fisierele din folderul **server**, nu folderul server in sine.

1.8. Validare backend

```

curl https://jobcoach-api-ionut-se.azurewebsites.net/api/health

az webapp log tail `
  --resource-group "rg-jobcoach-prod" `
  --name "jobcoach-api-ionut-se"

```

1.9. Testare mobile initiala

```

cd C:\github\job-pack\mobile
flutter clean

```

```
flutter pub get
flutter run -d emulator-5554 --dart-define=USE MOCKS=false --dart-define=BASE_URL=https://jobcoach-a

# sau pe telefon real
flutter run -d R3CTC0DST2V --dart-define=USE MOCKS=false --dart-define=BASE_URL=https://jobcoach-api
```

1.10. Release signing + AAB pentru Play Console

```
# generare upload keystore (o singura data)
& "C:\Program Files\Android\Android Studio\jbr\bin\keytool.exe" -genkeypair -v `
  -keystore "C:\github\job-pack\mobile\android\app\jobcoach-upload-keystore.jks" `
  -keyalg RSA `
  -keysize 2048 `
  -validity 10000 `
  -alias jobcoachupload

# build AAB
cd C:\github\job-pack\mobile
flutter build appbundle --release --dart-define=USE MOCKS=false --dart-define=BASE_URL=https://jobco
```

Fisierul `key.properties` (in `mobile/android/key.properties` , NU in git):

```
storePassword=rhTKwgorpnYbo0bByjX9
keyPassword=rhTKwgorpnYbo0bByjX9
keyAlias=jobcoachupload
storeFile=jobcoach-upload-keystore.jks
```

storeFile este doar filename-ul (nu path relativ cu app/), pentru ca build.gradle.kts il rezolva relativ la `android/app/` .

Capitolul 2 - Google Play: configurare completa si publicare

Acest capitol acopera tot ce trebuie configurat in Google Play Console, Google Cloud si Azure pentru ca subscriptiile, verificarea achizitiilor si publicarea sa functioneze corect.

2.1. Google Play Console - subscriptii

In Play Console → Monetize → Products → Subscriptions, creeaza:

Product ID	Nume	Pret	Tier
jobcoach_premium_monthly	Premium	\$3.99/ luna	premium - 20 requests/day/ module, fara ads
jobcoach_pro_monthly	Pro	\$9.99/ luna	pro - 100 requests/day/ module, fara ads

Aceste product ID-uri sunt hardcodate in `mobile/lib/services/billing_service.dart` si in `server/app/services/subscription_service.py`. Daca le schimbi in Play Console, trebuie schimbate si in cod.

2.2. Google Cloud - service account pentru purchase verification

Backend-ul verifica achizitiile server-side prin Google Play Developer API. Pentru asta ai nevoie de un service account.

1. Google Cloud Console → IAM & Admin → Service Accounts → Create Service Account
2. Nume: `jobcoach-play-billing`
3. Nu adauga roluri IAM (nu e nevoie)
4. Creeaza key: tab Keys → Add Key → Create new key → JSON → Download
5. Leaga in Play Console: Play Console → Setup → API access → Link Google Cloud project → Grant access service account-ului

2.3. Setare GOOGLE_PLAY_CREDENTIALS_JSON in Azure

Copiaza tot continutul fisierului JSON descarcat si seteaza-l ca app setting:

```
az webapp config appsettings set `
--resource-group "rg-jobcoach-prod" `
--name "jobcoach-api-ionut-se" `
--settings GOOGLE_PLAY_CREDENTIALS_JSON='<CONTINUTUL_COMPLET_AL_JSON_ULUI>'
```

Exemplu real (inlocuieste cu continutul JSON descarcat de la Google Cloud):

```
az webapp config appsettings set `
--resource-group "rg-jobcoach-prod" `
--name "jobcoach-api-ionut-se" `
--settings GOOGLE_PLAY_CREDENTIALS_JSON='{"type":"service_account","project_id":"jobcoach-500216",
```

Securitate: Daca private key-ul a fost expus (de exemplu in chat, email, repo), roteste-l imediat:
Google Cloud Console → Service Accounts → jobcoach-play-billing → Keys → Add Key (noua) → Delete key (veche) → Re-ruleaza comanda az cu noul JSON.

2.4. Setare RTDN_SECRET in Azure

```
az webapp config appsettings set `
--resource-group "rg-jobcoach-prod" `
--name "jobcoach-api-ionut-se" `
--settings RTDN_SECRET="FVjBx6Y2kBdeu0GZEnKL"
```

Apoi configureaza in Play Console → Monetization setup → Real-time developer notifications:

- Endpoint URL: `https://jobcoach-api-ionut-se.azurewebsites.net/api/admin/rtdn`
- Trimite header-ul `X-RTDN-Secret: FVjBx6Y2kBdeu0GZEnKL`

2.5. Google Play Console - Data Safety

Formularul Data Safety trebuie completat exact asa:

Sectioniune	Ce se bifeaza	Detalii
Fisiere si documente	Colectate	Prelucrate temporar = Da, Necesare = Da, Scop = Functionalitatea aplicatiei
Istoricul achizitiilor	Colectate	Prelucrate temporar = Nu (tier-ul e persistent), Necesare = Da, Scop = Functionalitatea aplicatiei
Activitatea in aplicatii → Alte actiuni	Colectate	Prelucrate temporar = Da, Necesare = Da, Scop = Functionalitatea aplicatiei
Identificatorii dispozitivului	Colectate	

		Prelucrate temporar = Nu (UUID persistent), Necesare = Da, Scop = Functionalitatea aplicatiei
ID publicitar	Da, foloseste	Scop = Publicitate sau marketing (AdMob)
Informatii personale	Nu se bifeaza	-
Informatii financiare → Plati	Nu se bifeaza	Google Play gestioneaza platile direct
Sanatate si fitness	Nu se bifeaza	-
Mesaje / Fotografii / Audio	Nu se bifeaza	-
Calendar / Agenda / Navigare web	Nu se bifeaza	-
Functii financiare	Nu se bifeaza nimic	App-ul nu ofera servicii financiare
Aplicatii de sanatate	Nu se aplica	-

2.6. Google Play Console - alte configurari

Sectioniune	Valoare
Categorie aplicatie	Business sau Productivity
Target audience	13+
Contine reclame	Da (AdMob banner ads)
Content rating	Completat chestionarul IARC
Email contact	popa.ionut9619@gmail.com
Privacy Policy URL	https://ionutc19.github.io/job-pack/privacy-policy.html
Pictograma (512x512)	branding/logo-icon-512.png

Feature graphic (1024x500)	branding/feature-graphic-1024x500.png
Screenshots	2-8 capturi din aplicatie (Job Fit, Profile Boost, Cover Letter)

2.7. Publicare - flux complet

1. Build AAB: `flutter build appbundle --release --dart-define=USE MOCKS=false --dart-define=BASE_URL=https://jobcoach-api-ionut-se.azurewebsites.net`
2. Play Console → Release → Internal testing → Create new release → Upload AAB
3. Distribuie linkul de testare inchisa catre testeri
4. Dupa validare: promoveaza din Internal Testing → Production

Capitolul 3 - Cum fac update-uri ulterioare

Acest capitol este folosit indiferent cine a facut modificarile: tu, Claude, Copilot sau orice alta persoana care a lucrat in GitHub.

3.1. Pull din GitHub

```
cd C:\github\job-pack
git pull origin <branch-ul-corect>
```

3.2. Decide ce s-a modificat

- **Doar server** → faci doar zip deploy in App Service si validare /api/health;
- **Doar mobile** → faci flutter clean, flutter pub get, test debug si apoi build release/APK/AAB daca este necesar;
- **Server + mobile** → faci ambele fluxuri, in ordinea server → mobile.

3.3. Update backend

```
cd C:\github\job-pack\server
Compress-Archive -Path * -DestinationPath ..\jobcoach-server.zip -Force

az webapp deploy `
  --resource-group "rg-jobcoach-prod" `
  --name "jobcoach-api-ionut-se" `
  --src-path "C:\github\job-pack\jobcoach-server.zip" `
  --type zip

az webapp restart `
  --resource-group "rg-jobcoach-prod" `
  --name "jobcoach-api-ionut-se"

curl https://jobcoach-api-ionut-se.azurewebsites.net/api/health
```

3.4. Update mobile in debug

```
cd C:\github\job-pack\mobile
flutter clean
flutter pub get
flutter run -d emulator-5554 --dart-define=USE MOCKS=false --dart-define=BASE_URL=https://jobcoach-a
```

```
# sau pe telefon
flutter run -d R3CTC0DST2V --dart-define=USE MOCKS=false --dart-define=BASE_URL=https://jobcoach-api
```

3.5. Update mobile in release (APK/AAB)

```
cd C:\github\job-pack\mobile
flutter build apk --release --dart-define=USE MOCKS=false --dart-define=BASE_URL=https://jobcoach-api

# instalare manuala pe device
$adb = "$env:LOCALAPPDATA\Android\Sdk\platform-tools\adb.exe"
& $adb install -r .\build\app\outputs\flutter-apk\app-release.apk

# build AAB pentru Play
flutter build appbundle --release --dart-define=USE MOCKS=false --dart-define=BASE_URL=https://jobcoach-api
```

3.6. Teste minime dupa orice update

- app porneste fara crash;
- banner free plan apare unde trebuie;
- paid plans nu afiseaza banner;
- upload PDF / DOCX / TXT merge;
- daca PDF-ul este scanat si nu contine text, mesajul trebuie sa fie clar;
- setarile de debug nu apar in productie;
- iconul si branding-ul sunt corecte.

Capitolul 4 - Mutare pe alta subscriptie Azure

Scenariu tipic: Subscription-ul curent (Visual Studio Enterprise - MPN) expira sau vrei sa muti pe o alta subscriptie Azure. Este posibil ca `az resource move` sa nu functioneze pentru toate resursele (PostgreSQL Flexible Server cu Private DNS este deseori nemutabil). Acest capitol presupune **recreare completa** pe noua subscriptie.

4.1. Ce trebuie salvat INAINTE de expirare

Ce	Unde este	Cum salvezi
Codul complet	GitHub ionutc19/job-pack	Deja in repo (sigur)
Upload keystore (.jks)	mobile/android/app/ jobcoach-upload- keystore.jks	Backup local + cloud storage personal
key.properties	mobile/android/ key.properties (local)	Backup local
Service account JSON (Google)	Google Cloud Console	Regenereaza oricand din Google Cloud
Toate app settings Azure	Azure Portal / CLI	Comanda de mai jos
Dump baza de date	PostgreSQL	pg_dump (comanda de mai jos)
RTDN_SECRET	Azure App Settings	Notat: FVjBx6Y2kBdeu0GZEnKL
AdMob IDs	AdMob Console	Notate in tabel de mai sus
Product IDs subscriptii	Play Console	Notate in tabel de mai sus

4.2. Export app settings existente

```
# Exporta toate app settings curente (pentru referinta)
az webapp config appsettings list `
```

```
--resource-group "rg-jobcoach-prod" \  
--name "jobcoach-api-ionut-se" \  
--output json > jobcoach-app-settings-backup.json
```

4.3. Export baza de date

```
# De pe o masina care are acces la PostgreSQL (sau prin VNet)  
pg_dump "postgresql://jobcoachadmin:<PASSWORD>@jobcoach-pg-ionut.postgres.database.azure.com:5432/jobcoach" --username jobcoachadmin --host jobcoach-pg-ionut.postgres.database.azure.com --port 5432 --sslmode require --pghost jobcoach-pg-ionut.postgres.database.azure.com --pgport 5432 --pguser jobcoachadmin --pgpass jobcoachadmin:5432:jobcoach:jobcoachadmin --pgpassfile /dev/null --format json --file jobcoach-app-settings-backup.json
```

Fara acest dump, mutarea pastreaza doar codul, nu si datele (useri, subscriptii, usage).

4.4. Provisioning pe noua subscriptie

Selecteaza noua subscriptie:

```
az account list --output table  
az account set --subscription "<NOUA_SUBSCRIPTIE>"
```

Ruleaza laC-ul complet (adapteaza numele daca e nevoie, dar recomandat sa pastrezi aceleasi nume):

```
$loc = "westeurope"  
$rg = "rg-jobcoach-prod"  
$vnet = "jobcoach-vnet"  
$subnetApp = "snet-appservice"  
$subnetPg = "snet-postgres"  
$plan = "jobcoach-asp-linux"  
$app = "jobcoach-api-ionut-se"  
$pg = "jobcoach-pg-ionut"  
$pgDb = "jobcoach"  
$pgUser = "jobcoachadmin"  
  
# 1. Resource Group  
az group create --name $rg --location $loc  
  
# 2. VNet + subnets  
az network vnet create \  
  --resource-group $rg \  
  --name $vnet \  
  --address-prefix 10.20.0.0/16 \  
  --subnet-name $subnetApp \  
  --subnet-prefix 10.20.1.0/24  
  
az network vnet subnet create \  
  --resource-group $rg \  
  --vnet-name $vnet \  
  --name $subnetPg \  
  --address-prefixes 10.20.2.0/24 \  
  --delegations Microsoft.DBforPostgreSQL/flexibleServers  
  
# 3. App Service Plan + Web App
```

```

az appservice plan create `
  --resource-group $rg `
  --name $plan `
  --location $loc `
  --is-linux `
  --sku B1

az webapp create `
  --resource-group $rg `
  --plan $plan `
  --name $app `
  --runtime "PYTHON|3.12"

# 4. PostgreSQL Flexible Server
az postgres flexible-server create `
  --resource-group $rg `
  --name $pg `
  --location $loc `
  --tier Burstable `
  --sku-name Standard_B1ms `
  --version 17 `
  --admin-user $pgUser `
  --admin-password "<PAROLA_NOUA_SIGURA>" `
  --vnet $vnet `
  --subnet $subnetPg `
  --private-dns-zone "<private-dns-zone>"

az postgres flexible-server db create `
  --resource-group $rg `
  --server-name $pg `
  --database-name $pgDb

# 5. VNet Integration
az webapp vnet-integration add `
  --resource-group $rg `
  --name $app `
  --vnet $vnet `
  --subnet $subnetApp

```

Nota: Daca numele `jobcoach-api-ionut-se` este ocupat pe noua subscriptie (putin probabil daca e aceeasi), alege alt nume si actualizeaza `BASE_URL` in build-urile mobile.

4.5. Restore baza de date

```
pg_restore -d "postgresql://jobcoachadmin:<PAROLA_NOUA>@<NEW-PG-HOST>:5432/jobcoach?sslmode=require"
```

4.6. Configurare app settings pe noul App Service

```

# DATABASE_URL (cu noua parola si hostname)
$dbUrl = "postgresql+psycpg2://jobcoachadmin:<PAROLA_NOUA>@<NEW-PG-HOST>.postgres.database.azure.com"

```

```

az webapp config appsettings set `
  --resource-group $rg `
  --name $app `
  --settings `
    DATABASE_URL=$dbUrl `
    SCM_DO_BUILD_DURING_DEPLOYMENT=true `
    WEBSITES_PORT=8000 `
    GOOGLE_PLAY_CREDENTIALS_JSON='<CONTINUT_JSON_SERVICE_ACCOUNT>' `
    RTDN_SECRET="FVjBx6Y2kBdeu0GZEnKL" `
    AI_API_KEY="<DACA_EXISTA>" `
    AI_BASE_URL="<DACA_EXISTA>" `
    AI_MODEL="<DACA_EXISTA>"

az webapp config set `
  --resource-group $rg `
  --name $app `
  --startup-file "bash /home/site/wwwroot/startup.sh"

```

4.7. Deploy backend pe noul App Service

```

cd C:\github\job-pack\server
Compress-Archive -Path * -DestinationPath ..\jobcoach-server.zip -Force

az webapp deploy `
  --resource-group "rg-jobcoach-prod" `
  --name "jobcoach-api-ionut-se" `
  --src-path "C:\github\job-pack\jobcoach-server.zip" `
  --type zip

az webapp restart `
  --resource-group "rg-jobcoach-prod" `
  --name "jobcoach-api-ionut-se"

curl https://jobcoach-api-ionut-se.azurewebsites.net/api/health

```

4.8. Verificare si testare

1. `/api/health` returneaza `{"status":"ok"}`
2. Testeaza mobile in debug pe telefon / emulator
3. Daca BASE_URL s-a schimbat, rebuild AAB cu noul URL si upload in Play Console
4. Daca BASE_URL e acelasi (acelasi app name), nu e nevoie de rebuild
5. Verifica subscriptii, upload documente, toate cele 3 module

4.9. Checklist complet de mutare

1. ☐ Backup cod (GitHub - deja ok)
2. ☐ Backup keystore + key.properties
3. ☐ Export app settings: `az webapp config appsettings list`
4. ☐ Export baza de date: `pg_dump`

5. ☐ Noteaza / salveaza toate secretele (DATABASE_URL, GOOGLE_PLAY_CREDENTIALS_JSON, RTDN_SECRET, AI keys)
6. ☐ Selecteaza noua subscriptie: `az account set`
7. ☐ Provision IaC (Resource Group, VNet, App Service, PostgreSQL)
8. ☐ Restore baza de date: `pg_restore`
9. ☐ Seteaza app settings pe noul App Service
10. ☐ Deploy backend si verifica health
11. ☐ Testeaza mobile debug pe telefon
12. ☐ Daca BASE_URL s-a schimbat: rebuild AAB, upload in Play Console
13. ☐ Testeaza release APK pe telefon
14. ☐ Verifica subscriptii, upload, toate modulele
15. ☐ Actualizeaza RTDN endpoint in Play Console (daca URL-ul s-a schimbat)
16. ☐ Sterge resursele din vechea subscriptie (optional, dupa validare completa)

Tip: Daca pastrezi acelasi app name (`jobcoach-api-ionut-se`) si acelasi domeniu, nu trebuie rebuild mobile si nu trebuie actualizat nimic in Play Console. Totul continua sa functioneze transparent.

Troubleshooting - probleme intalnite si rezolvarea lor

T1. Emulator sau telefon nu este vazut corect

```
$adb = "$env:LOCALAPPDATA\Android\Sdk\platform-tools\adb.exe"
$emu = "$env:LOCALAPPDATA\Android\Sdk\emulator\emulator.exe"
& $adb kill-server
& $adb start-server
& $adb devices
# emulator offline -> cold boot
& $emu -avd "Pixel_8_Pro" -no-snapshot-load
```

T2. adb / emulator / keytool nu sunt recunoscute in PowerShell

Pe Windows, foloseste path complet si operatorul `&` in PowerShell.

T3. Eroare gradle legata de google_mobile_ads vechi

Solutia: upgrade la versiune compatibila (ex: 9.0.0), apoi `flutter clean` si `flutter pub get`.

T4. compileSdk prea mic pentru dependinte noi

Solutia: ridica compileSdk (si targetSdk) la 36 in `build.gradle.kts`.

T5. App crash la launch: MainActivity ClassNotFoundException

Cauza: namespace / applicationId / AndroidManifest / folder path pentru MainActivity nu sunt aliniate. Toate trebuie sa fie coerente pe `com.ionutc19.jobcoach`.

T6. Debug merge, release APK nu porneste

Cauza tipica: release-only issue (R8 / minify). Solutia: logcat pe telefon, investigheaza cu `proguard-rules.pro`.

T7. PDF upload esueaza cu 'Could not extract text'

PDF scanat / image-only: fara OCR, mesaj clar. PDF corupt / protejat: mesaj specific. PDF text-based: trebuie sa mearga.

T8. Consent / permisiuni la upload documente

Cu Storage Access Framework, nu trebuie broad storage permission. UX-ul explica ce se intampla si afiseaza fisierul selectat + remove/replace.

T9. Iconita / branding nu se actualizeaza

Dezinstaleaza aplicatia si reinstaleaz-o.

T10. Startup.sh / CRLF / Alembic in Azure

Verifica startup.sh sa fie LF, fara caractere ascunse.

T11. Zip deploy esueaza sau app-ul nu porneste dupa deploy

Verifica structura zip-ului (fisierele direct, nu folder-ul server ca root). Dupa deploy: `/api/health` si `az webapp log tail`.

T12. Deploy 502 - build automation not enabled

Seteaza `SCM_DO_BUILD_DURING_DEPLOYMENT=true` inainte de deploy:

```
az webapp config appsettings set `
--resource-group "rg-jobcoach-prod" `
--name "jobcoach-api-ionut-se" `
--settings SCM_DO_BUILD_DURING_DEPLOYMENT=true
```

T13. Rotire chei Google Cloud service account

Daca private key-ul a fost expus:

1. Google Cloud Console → IAM → Service Accounts → jobcoach-play-billing
2. Tab Keys → Add Key → Create new key → JSON → Download
3. Re-ruleaza: `az webapp config appsettings set ...`
`GOOGLE_PLAY_CREDENTIALS_JSON='<NOU_JSON>'`
4. Sterge cheia veche din Google Cloud Console
5. Restart App Service: `az webapp restart ...`

Anexa - Comenzi esentiale rapide

```
# Pull din GitHub
cd C:\github\job-pack
git pull origin <branch>

# Deploy backend
cd C:\github\job-pack\server
Compress-Archive -Path * -DestinationPath ..\jobcoach-server.zip -Force
az webapp deploy --resource-group "rg-jobcoach-prod" --name "jobcoach-api-ionut-se" --src-path "C:\g
az webapp restart --resource-group "rg-jobcoach-prod" --name "jobcoach-api-ionut-se"

# Health check
curl https://jobcoach-api-ionut-se.azurewebsites.net/api/health

# Mobile debug pe telefon
cd C:\github\job-pack\mobile
flutter clean
flutter pub get
flutter run -d R3CTC0DST2V --dart-define=USE MOCKS=false --dart-define=BASE_URL=https://jobcoach-api

# Mobile release APK
flutter build apk --release --dart-define=USE MOCKS=false --dart-define=BASE_URL=https://jobcoach-ap

# Mobile release AAB
flutter build appbundle --release --dart-define=USE MOCKS=false --dart-define=BASE_URL=https://jobco

# Export app settings (backup inainte de mutare)
az webapp config appsettings list --resource-group "rg-jobcoach-prod" --name "jobcoach-api-ionut-se"

# Export baza de date (backup inainte de mutare)
pg_dump "postgresql://jobcoachadmin:<PASSWORD>@jobcoach-pg-ionut.postgres.database.azure.com:5432/job

# Setare secret nou
az webapp config appsettings set --resource-group "rg-jobcoach-prod" --name "jobcoach-api-ionut-se"

# Logs
az webapp log tail --resource-group "rg-jobcoach-prod" --name "jobcoach-api-ionut-se"
```