BioDataGuide

Darwin Core Marine Example Compendium

Standardizing Marine Biological Data Working Group

2026-10-29

Table of contents

Preface 4

1 Introduction 5

I Applications 6

2 Aligning Data to Darwin Core - Event Core with Extended Measurement or Fact 8
- 2.0.1 General information about this notebook . . . 8
- 2.0.2 Event file . . . 8
- 2.0.3 Occurrence file . . . 11
- 2.0.4 Extended Measurement or Fact extension file . . . 13
- 2.0.5 Cleaning up Event and Occurrence files . . . 17

3 Darwin Core Salmon Data Remap 20
- 3.1 Salmon Ocean Ecology Data . . . 20
  - 3.1.1 Intro . . . 20
  - 3.1.2 event . . . 20
  - 3.1.3 occurrence . . . 21
  - 3.1.4 measurementOrFact . . . 23

4 Seagrass Density to DWC eMoF format 24
- 4.1 Hakai Seagrass . . . 24
  - 4.1.1 Setup . . . 24
  - 4.1.2 Convert Data to Darwin Core - Extended Measurement or Fact format 30
  - 4.1.3 Session Info . . . 35

5 trawl_catch_data 37
- 5.1 Trawl Data . . . 37
  - 5.1.1 Workflow Overview . . . 37
  - 5.1.2 FAQ . . . 42

6 dataset-edna 44
- 6.1 Introduction . . . 44
- 6.2 Published data . . . 45
- 6.3 Repo structure . . . 45

7 Converting ATN netCDF file to Darwin Core **46**
7.1 Downloading and preprocessing the source data . . . 47
7.1.1 Open the netCDF file . . . 47
7.1.2 Collect all the metadata from the netCDF file. . . . 58
7.1.3 Store the data as a tibble . . . 59
7.1.4 Dealing with time . . . 59
7.2 Converting to Darwin Core . . . 61
7.2.1 Occurrence Core . . . 61
7.2.2 Create a dataGeneralizations column to describe how many duplicates were found for each deprecation series . . . 68
7.3 Print session info . . . 76

Appendices **77**

A FAQ **77**

B Tools **79**
B.1 R . . . 79
B.2 Python . . . 81
B.3 Google Sheets . . . 83
B.4 Validators . . . 84

C Extras **85**
C.1 Ecological Metadata Language (EML) . . . 85
C.2 Example using GitHub to resolve errors . . . 87

References **92**

Preface

This book contains a collection of examples and resources related to mobilizing marine biological data to the Darwin Core standard for sharing though OBIS. This book has been developed by the Standardizing Marine Biological Data Working Group (SMBD). The working group is an open community of practitioners, experts, and scientists looking to learn and educate the community on standardizing and sharing marine biological data.

If you would like to join the SMBD or learn more, checkout this README.

1 Introduction

The world of standardizing marine biological data can seem complex for the naive oceanographer, biologist, scientist, or programmer. This book intends to ease the burden of learning about the Darwin Core standard by compiling a list of example applications and tools for translating source data into Darwin Core. This collection of resources does not replace the Darwin Core standards documentation (https://dwc.tdwg.org/) or the OBIS Manual (https://manual.obis.org/), but instead it supplements those resources with examples of real world applications.

In this book we cover:

- Applications - These are the real world examples of aligning data to Darwin Core.
- Frequently Asked Questions - A collection of Frequently Asked Questions.
- Tools - A collection of useful tools, packages, and programs for working with marine biological data.
- Extras - Some useful extra tidbits about metadata and using GitHub to debug data issues.

If you would like to learn more about standardizing biological data (not only marine), the Earth Science Information Partners (ESIP) Biological Data Standards Cluster developed this primer for managers of biological data to provide a quick, easy resource for navigating a selection of the standards that exist. The goal of the primer is to spread awareness about existing standards and is intended to be shared online and at conferences to increase the adoption of standards for biological data and make them FAIR.

Part I

Applications

This chapter contains a series of example applications to convert source data to the Darwin Core standard. You can find these examples (and more!) in the GitHub repository under the `datasets/` directory.

2 Aligning Data to Darwin Core - Event Core with Extended Measurement or Fact

Abby Benson
January 9, 2022

2.0.1 General information about this notebook

Script to process the Texas Parks and Wildlife Department (TPWD) Aransas Bay bag seine data from the format used by the Houston Advanced Research Center (HARC) for bays in Texas. Taxonomy was processed using a separate script (TPWD_Taxonomy.R) using a taxa list pulled from the pdf "2009 Resource Monitoring Operations Manual". All original data, processed data and scripts are stored on an item in USGS ScienceBase.

```
# Load some of the libraries
library(reshape2)
library(tidyverse)
library(readr)
```

```
# Load the data
BagSeine <- read.csv("https://www.sciencebase.gov/catalog/file/get/53a887f4e4b075096c60cfdd?
```

Note that if not already done you'll need to run the TPWD_Taxonomy.R script to get the taxaList file squared away or load the taxonomy file to the World Register of Marine Species Taxon Match Tool https://www.marinespecies.org/aphia.php?p=match

2.0.2 Event file

To start we will create the Darwin Core **Event** file. This is the file that will have all the information about the sampling event such as date, location, depth, sampling protocol. Basically anything about the cruise or the way the sampling was done will go in this file. You can see all the Darwin Core terms that are part of the event file here http://tools.gbif.org/dwca-validator/extension.do?id=dwc:Event.

The original format for these TPWD HARC files has all of the information associated as the event in the first approximately 50 columns and then all of the information about the occurrence (species) as columns for each species. We will need to start by limiting to the event information only.

```
event <- BagSeine[,1:47]
```

Next there are several pieces of information that need 1) to be added like the geodeticDatum 2) to be pieced together from multiple columns like datasetID or 3) minor changes like the minimum and maximum depth.

```
event <- event %>%
  mutate(type = "Event",
         modified = lubridate::today(),
         language = "en",
         license = "http://creativecommons.org/publicdomain/zero/1.0/legalcode",
         institutionCode = "TPWD",
         ownerInstitutionCode = "HARC",
         coordinateUncertaintyInMeters = "100",
         geodeticDatum = "WGS84",
         georeferenceProtocol = "Handheld GPS",
         country = "United States",
         countryCode = "US",
         stateProvince = "Texas",
         datasetID = gsub(" ", "_", paste("TPWD_HARC_Texas", event$Bay, event$Gear_Type)),
         eventID = paste("Station", event$station_code, "Date", event$completion_dttm, sep =
         sampleSizeUnit = "hectares",
         CompDate = lubridate::mdy_hms(event$CompDate, tz="America/Chicago"),
         StartDate = lubridate::mdy_hms(event$StartDate, tz="America/Chicago"),
         minimumDepthInMeters = ifelse(start_shallow_water_depth_num < start_deep_water_depth
                                       start_shallow_water_depth_num, start_deep_water_depth_
         maximumDepthInMeters = ifelse(start_deep_water_depth_num > start_shallow_water_depth
                                       start_deep_water_depth_num, start_shallow_water_depth_
```

```
head(event[,48:64], n = 10)
    type   modified language                                                    license insti
1  Event 2022-01-09       en http://creativecommons.org/publicdomain/zero/1.0/legalcode
2  Event 2022-01-09       en http://creativecommons.org/publicdomain/zero/1.0/legalcode
3  Event 2022-01-09       en http://creativecommons.org/publicdomain/zero/1.0/legalcode
4  Event 2022-01-09       en http://creativecommons.org/publicdomain/zero/1.0/legalcode
5  Event 2022-01-09       en http://creativecommons.org/publicdomain/zero/1.0/legalcode
6  Event 2022-01-09       en http://creativecommons.org/publicdomain/zero/1.0/legalcode
```

```
7  Event 2022-01-09       en http://creativecommons.org/publicdomain/zero/1.0/legalcode
8  Event 2022-01-09       en http://creativecommons.org/publicdomain/zero/1.0/legalcode
9  Event 2022-01-09       en http://creativecommons.org/publicdomain/zero/1.0/legalcode
10 Event 2022-01-09       en http://creativecommons.org/publicdomain/zero/1.0/legalcode
   ownerInstitutionCode coordinateUncertaintyInMeters geodeticDatum georeferenceProtocol
1                  HARC                          100         WGS84         Handheld GPS Unit
2                  HARC                          100         WGS84         Handheld GPS Unit
3                  HARC                          100         WGS84         Handheld GPS Unit
4                  HARC                          100         WGS84         Handheld GPS Unit
5                  HARC                          100         WGS84         Handheld GPS Unit
6                  HARC                          100         WGS84         Handheld GPS Unit
7                  HARC                          100         WGS84         Handheld GPS Unit
8                  HARC                          100         WGS84         Handheld GPS Unit
9                  HARC                          100         WGS84         Handheld GPS Unit
10                 HARC                          100         WGS84         Handheld GPS Unit
   countryCode stateProvince                              datasetID
1           US         Texas TPWD_HARC_Texas_Aransas_Bay_Bag_Seine Station_95_Date_09JAN1997
2           US         Texas TPWD_HARC_Texas_Aransas_Bay_Bag_Seine Station_95_Date_18AUG2000
3           US         Texas TPWD_HARC_Texas_Aransas_Bay_Bag_Seine Station_96_Date_28JUN2005
4           US         Texas TPWD_HARC_Texas_Aransas_Bay_Bag_Seine Station_96_Date_23AUG2006
5           US         Texas TPWD_HARC_Texas_Aransas_Bay_Bag_Seine Station_96_Date_17OCT2006
6           US         Texas TPWD_HARC_Texas_Aransas_Bay_Bag_Seine Station_96_Date_19FEB1996
7           US         Texas TPWD_HARC_Texas_Aransas_Bay_Bag_Seine Station_96_Date_11JUN2001
8           US         Texas TPWD_HARC_Texas_Aransas_Bay_Bag_Seine Station_96_Date_16MAR1992
9           US         Texas TPWD_HARC_Texas_Aransas_Bay_Bag_Seine Station_96_Date_25SEP1996
10          US         Texas TPWD_HARC_Texas_Aransas_Bay_Bag_Seine Station_96_Date_08MAY1997
   sampleSizeUnit minimumDepthInMeters maximumDepthInMeters
1       hectares                   0.0                   0.6
2       hectares                   0.1                   0.5
3       hectares                   0.4                   0.6
4       hectares                   0.2                   0.4
5       hectares                   0.7                   0.8
6       hectares                   0.1                   0.3
7       hectares                   0.4                   0.5
8       hectares                   0.0                   0.4
9       hectares                   0.3                   0.7
10      hectares                   0.4                   0.6
```

For this dataset there was a start timestamp and end timestamp that we can use to identify the sampling effort which can be really valuable information for downstream users when trying to reuse data from multiple projects.

```
## Calculate duration of bag seine event
event$samplingEffort <- ""
for (i in 1:nrow(event)){
  event[i,]$samplingEffort <- abs(lubridate::as.duration(event[i,]$CompDate - event[i,]$Start
}
event$samplingEffort <- paste(event$samplingEffort, "seconds", sep = " ")
```

Finally there were a few columns that were a direct match to a Darwin Core term and therefore just need to be renamed to follow the standard.

```
event <- event %>%
  rename(samplingProtocol = Gear_Type,
         locality = Estuary,
         waterBody = SubBay,
         decimalLatitude = Latitude,
         decimalLongitude = Longitude,
         sampleSizeValue = surface_area_num,
         eventDate = CompDate)
```

2.0.3 Occurrence file

The next file we need to create is the **Occurrence** file. This file includes all the information about the species that were observed. An occurrence in Darwin Core is the intersection of an organism at a time and a place. We have already done the work to identify the time and place in the event file so we don't need to do that again here. What we do need to is identify all the information about the organisms. Another piece of information that goes in here is basisOfRecord which is a required field and has a controlled vocabulary. For the data we work with you'll usually put `HumanObservation` or `MachineObservation`. If it's eDNA data you'll use `MaterialSample`. If your data are part of a museum collection you'll use `PreservedSpecimen`.

Important to note that there is overlap in the Darwin Core terms that "allowed" to be in the event file and in the occurrence file. This is because data can be submitted as "Occurrence Only" where you don't have a separate event file. In that case, the location and date information will need to be included in the occurrence file. Since we are formatting this dataset as a sampling event we will not include location and date information in the occurrence file. To see all the Darwin Core terms that can go in the occurrence file go here https://tools.gbif.org/dwca-validator/extension.do?id=dwc:occurrence.

This dataset in its original format is in "wide format". All that means is that data that we would expect to be encoded as values in the rows are instead column headers. We have to

pull all the scientific names out of the column headers and turn them into actual values in the data.

```
occurrence <- melt(BagSeine, id=1:47, measure=48:109, variable.name="vernacularName", value.
```

You'll notice when we did that step we went from 5481 obs (or rows) in the data to 334341 obs. We went from wide to long.

```
dim(BagSeine)
[1] 5481  109
dim(occurrence)
[1] 334341     49
```

Now as with the event file we have several pieces of information that need to be added or changed to make sure the data are following Darwin Core. We always want to include as much information as possible to make the data as reusable as possible.

```
occurrence <- occurrence %>%
  mutate(vernacularName = gsub("\\.",' ', vernacularName),
         eventID = paste("Station", station_code, "Date", completion_dttm, sep = "_"),
         occurrenceStatus = ifelse(relativeAbundance == 0, "Absent", "Present"),
         basisOfRecord = "HumanObservation",
         organismQuantityType = "Relative Abundance",
         collectionCode = paste(Bay, Gear_Type, sep = " "))
```

We will match the taxa list with our occurrence file data to bring in the taxonomic information that we pulled from WoRMS. To save time you'll just import the processed taxa list which includes the taxonomic hierarchy and the required term scientificNameID which is one of the most important pieces of information to include for OBIS.

```
taxaList <- read.csv("https://www.sciencebase.gov/catalog/file/get/53a887f4e4b075096c60cfdd?
## Merge taxaList with occurrence
occurrence <- merge(occurrence, taxaList, by = "vernacularName", all.x = T)
## Test that all the vernacularNames found a match in taxaList_updated
Hmisc::describe(occurrence$scientificNameID)
       n  missing distinct
  334341        0       61

lowest : urn:lsid:marinespecies.org:taxname:105792 urn:lsid:marinespecies.org:taxname:107034
highest: urn:lsid:marinespecies.org:taxname:367528 urn:lsid:marinespecies.org:taxname:396707
```

For that last line of code we are expecting to see no missing values for scientificNameID. Every row in the file should have a value in scientificNameID which should be a WoRMS LSID that look like this `urn:lsid:marinespecies.org:taxname:144531`

We need to create a unique ID for each row in the occurrence file. This is known as the `occurrenceID` and is a required term. The `occurrenceID` needs to be globally unique and needs to be permanent and kept in place if any updates to the dataset are made. You should not create brand new occurrenceIDs when you update a dataset. To facilitate this I like to build the `occurrenceID` from pieces of information available in the dataset to create a unique ID for each row in the occurrence file. For this dataset I used the `eventID` (Station + Date) plus the scientific name. This only works if there is only one scientific name per station per date so if you have different ages or sexes of species at the same station and date this method of creating the occurrenceID won't work for you.

```
occurrence$occurrenceID <- paste(occurrence$eventID, gsub(" ", "_",occurrence$scientificName)
occurrence[1,]$occurrenceID
[1] "Station_95_Date_09JAN1997:14:35:00.000_Atractosteus_spatula"
```

For the occurrence file we only have one column to rename. We could have avoided this step if we had named it `organismQuantity` up above but I kept this to remind me what the data providers had called this.

```
occurrence <- occurrence %>%
  rename(organismQuantity = relativeAbundance)
```

2.0.4 Extended Measurement or Fact extension file

The final file we are going to create is the **Extended Measurement or Fact extension (emof)**. This is a bit like a catch all for any measurements or facts that are not captured in Darwin Core. Darwin Core does not have terms for things like temperature, salinity, gear type, cruise number, length, weight, etc. We are going to create a long format file where each of these is a set of rows in the extended measurement or fact file. You can find all the terms in this extension here https://tools.gbif.org/dwca-validator/extension.do?id=http://rs.iobis.org/obis/terms/ExtendedMeasurementOrFact.

OBIS uses the BODC NERC Vocabulary Server to provide explicit definitions for each of the measurements https://vocab.nerc.ac.uk/search_nvs/.

For this dataset I was only able to find code definitions provided by the data providers for some of the measurements. I included the ones that I was able to find code definitions and left out any that I couldn't find those for. The ones I was able to find code definitions for were `Total.Of.Samples_Count`, `gear_size`, `start_wind_speed_num`,

start_barometric_pressure_num, start_temperature_num, start_salinity_num, start_dissolved_oxygen_num. All the others I left out.

```
totalOfSamples <- event[c("Total.Of.Samples_Count", "eventID")]
totalOfSamples <- totalOfSamples[which(!is.na(totalOfSamples$Total.Of.Samples_Count)),]
totalOfSamples <- totalOfSamples %>%
  mutate(measurementType = "Total number of samples used to calculate relative abundance",
         measurementUnit = "",
         measurementTypeID = "",
         measurementUnitID = "",
         occurrenceID = "") %>%
  rename(measurementValue = Total.Of.Samples_Count)

gear_size <- event[c("gear_size", "eventID")]
gear_size <- gear_size[which(!is.na(gear_size$gear_size)),]
gear_size <- gear_size %>%
  mutate(measurementType = "gear size",
         measurementUnit = "meters",
         measurementTypeID = "http://vocab.nerc.ac.uk/collection/P01/current/MTHAREA1/",
         measurementUnitID = "http://vocab.nerc.ac.uk/collection/P06/current/ULAA/",
         occurrenceID = "") %>%
  rename(measurementValue = gear_size)

start_wind_speed_num <- event[c("start_wind_speed_num", "eventID")]
start_wind_speed_num <- start_wind_speed_num[which(!is.na(start_wind_speed_num$start_wind_sp
start_wind_speed_num <- start_wind_speed_num %>%
  mutate(measurementType = "wind speed",
         measurementUnit = "not provided",
         measurementTypeID = "http://vocab.nerc.ac.uk/collection/P01/current/EWSBZZ01/",
         measurementUnitID = "",
         occurrenceID = "") %>%
  rename(measurementValue = start_wind_speed_num)

start_barometric_pressure_num <- event[c("start_barometric_pressure_num", "eventID")]
start_barometric_pressure_num <- start_barometric_pressure_num[which(!is.na(start_barometric_
start_barometric_pressure_num <- start_barometric_pressure_num %>%
  mutate(measurementType = "barometric pressure",
         measurementUnit = "not provided",
         measurementTypeID = "http://vocab.nerc.ac.uk/collection/P07/current/CFSN0015/",
         measurementUnitID = "",
         occurrenceID = "") %>%
  rename(measurementValue = start_barometric_pressure_num)
```

```
start_temperature_num <- event[c("start_temperature_num", "eventID")]
start_temperature_num <- start_temperature_num[which(!is.na(start_temperature_num$start_tempe
start_temperature_num <- start_temperature_num %>%
  mutate(measurementType = "water temperature",
         measurementUnit = "Celsius",
         measurementTypeID = "http://vocab.nerc.ac.uk/collection/P01/current/TEMPPR01/",
         measurementUnitID = "http://vocab.nerc.ac.uk/collection/P06/current/UPAA/",
         occurrenceID = "") %>%
  rename(measurementValue = start_temperature_num)

start_salinity_num <- event[c("start_salinity_num", "eventID")]
start_salinity_num <- start_salinity_num[which(!is.na(start_salinity_num$start_salinity_num)
start_salinity_num <- start_salinity_num %>%
  mutate(measurementType = "salinity",
         measurementUnit = "ppt",
         measurementTypeID = "http://vocab.nerc.ac.uk/collection/P01/current/ODSDM021/",
         measurementUnitID = "http://vocab.nerc.ac.uk/collection/P06/current/UPPT/",
         occurrenceID = "") %>%
  rename(measurementValue = start_salinity_num)

start_dissolved_oxygen_num <- event[c("start_dissolved_oxygen_num", "eventID")]
start_dissolved_oxygen_num <- start_dissolved_oxygen_num[which(!is.na(start_dissolved_oxygen_
start_dissolved_oxygen_num <- start_dissolved_oxygen_num %>%
  mutate(measurementType = "dissolved oxygen",
         measurementUnit = "ppm",
         measurementTypeID = "http://vocab.nerc.ac.uk/collection/P09/current/DOX2/",
         measurementUnitID = "http://vocab.nerc.ac.uk/collection/P06/current/UPPM/",
         occurrenceID = "") %>%
  rename(measurementValue = start_dissolved_oxygen_num)

alternate_station_code <- event[c("alternate_station_code", "eventID")]
alternate_station_code <- alternate_station_code[which(!is.na(alternate_station_code$alternat
alternate_station_code <- alternate_station_code %>%
  mutate(measurementType = "alternate station code",
         measurementUnit = "",
         measurementTypeID = "",
         measurementUnitID = "",
         occurrenceID = "") %>%
  rename(measurementValue = alternate_station_code)

organismQuantity <- occurrence[c("organismQuantity", "eventID", "occurrenceID")]
organismQuantity <- organismQuantity[which(!is.na(organismQuantity$organismQuantity)),]
```

```
organismQuantity <- organismQuantity %>%
  mutate(measurementType = "relative abundance",
         measurementUnit = "",
         measurementTypeID = "http://vocab.nerc.ac.uk/collection/S06/current/S0600020/",
         measurementUnitID = "") %>%
  rename(measurementValue = organismQuantity)

# Bind the separate measurements together into one file
mof <- rbind(totalOfSamples, start_barometric_pressure_num, start_dissolved_oxygen_num,
             start_salinity_num, start_temperature_num, start_wind_speed_num, gear_size,
             alternate_station_code, organismQuantity)
head(mof)
 measurementValue                                 eventID
1               18 Station_95_Date_09JAN1997:14:35:00.000
2              103 Station_95_Date_18AUG2000:11:02:00.000
3              401 Station_96_Date_28JUN2005:08:41:00.000
4               35 Station_96_Date_23AUG2006:11:47:00.000
5               57 Station_96_Date_17OCT2006:14:23:00.000
6                5 Station_96_Date_19FEB1996:10:27:00.000
                                          measurementType measurementUnit measurementTyp
1 Total number of samples used to calculate relative abundance
2 Total number of samples used to calculate relative abundance
3 Total number of samples used to calculate relative abundance
4 Total number of samples used to calculate relative abundance
5 Total number of samples used to calculate relative abundance
6 Total number of samples used to calculate relative abundance
  measurementUnitID occurrenceID
1
2
3
4
5
6
tail(mof)
       measurementValue                                   eventID    measurementType measuremer
334336        0.0000000 Station_217_Date_03APR2003:13:28:00.000 relative abundance
334337        0.0000000 Station_217_Date_24FEB2006:10:12:00.000 relative abundance
334338        0.1428571 Station_217_Date_23JUN2001:12:28:00.000 relative abundance
334339        0.0000000 Station_212_Date_23MAY1990:10:43:00.000 relative abundance
334340        0.1224490 Station_212_Date_24JUL1990:09:34:00.000 relative abundance
334341        0.0000000 Station_212_Date_21MAR2001:11:52:00.000 relative abundance
                                        measurementTypeID measurementUnitID
```

```
334336 http://vocab.nerc.ac.uk/collection/S06/current/S0600020/
334337 http://vocab.nerc.ac.uk/collection/S06/current/S0600020/
334338 http://vocab.nerc.ac.uk/collection/S06/current/S0600020/
334339 http://vocab.nerc.ac.uk/collection/S06/current/S0600020/
334340 http://vocab.nerc.ac.uk/collection/S06/current/S0600020/
334341 http://vocab.nerc.ac.uk/collection/S06/current/S0600020/
                                                        occurrenceID
334336 Station_217_Date_03APR2003:13:28:00.000_Litopenaeus_setiferus
334337 Station_217_Date_24FEB2006:10:12:00.000_Litopenaeus_setiferus
334338 Station_217_Date_23JUN2001:12:28:00.000_Litopenaeus_setiferus
334339 Station_212_Date_23MAY1990:10:43:00.000_Litopenaeus_setiferus
334340 Station_212_Date_24JUL1990:09:34:00.000_Litopenaeus_setiferus
334341 Station_212_Date_21MAR2001:11:52:00.000_Litopenaeus_setiferus

# Write out the file
write.csv(mof, file = (paste0(event[1,]$datasetID, "_mof_", lubridate::today(),".csv")), file
```

2.0.5 Cleaning up Event and Occurrence files

Now that we have all of our files created we can clean up the **Event** and **Occurrence** files to remove the columns that are not following Darwin Core. We had to leave the extra bits in before because we needed them to create the **emof** file above.

```
event <- event[c("samplingProtocol","locality","waterBody","decimalLatitude","decimalLongitud
                 "eventDate","sampleSizeValue","minimumDepthInMeters",
                 "maximumDepthInMeters","type","modified","language","license","institutionC
                 "ownerInstitutionCode","coordinateUncertaintyInMeters",
                 "geodeticDatum", "georeferenceProtocol","country","countryCode","stateProvi
                 "datasetID","eventID","sampleSizeUnit","samplingEffort")]
head(event)
  samplingProtocol                locality   waterBody decimalLatitude decimalLongitude
1        Bag Seine Mission-Aransas Estuary Aransas Bay        28.13472        -97.00833
2        Bag Seine Mission-Aransas Estuary Aransas Bay        28.13528        -97.00722
3        Bag Seine Mission-Aransas Estuary Aransas Bay        28.13444        -96.99611
4        Bag Seine Mission-Aransas Estuary Aransas Bay        28.13444        -96.99611
5        Bag Seine Mission-Aransas Estuary Aransas Bay        28.13444        -96.99611
6        Bag Seine Mission-Aransas Estuary Aransas Bay        28.13472        -96.99583
            eventDate sampleSizeValue minimumDepthInMeters maximumDepthInMeters  type   modi
1 1997-01-09 14:35:00            0.03                  0.0                  0.6 Event 2022-0
2 2000-08-18 11:02:00            0.03                  0.1                  0.5 Event 2022-0
3 2005-06-28 08:41:00            0.03                  0.4                  0.6 Event 2022-0
```

```
4 2006-08-23 11:47:00           0.03                 0.2                 0.4 Event 2022-0
5 2006-10-17 14:23:00           0.03                 0.7                 0.8 Event 2022-0
6 1996-02-19 10:27:00           0.03                 0.1                 0.3 Event 2022-0
                                                    license institutionCode ownerInstitutio
1 http://creativecommons.org/publicdomain/zero/1.0/legalcode            TPWD
2 http://creativecommons.org/publicdomain/zero/1.0/legalcode            TPWD
3 http://creativecommons.org/publicdomain/zero/1.0/legalcode            TPWD
4 http://creativecommons.org/publicdomain/zero/1.0/legalcode            TPWD
5 http://creativecommons.org/publicdomain/zero/1.0/legalcode            TPWD
6 http://creativecommons.org/publicdomain/zero/1.0/legalcode            TPWD
  coordinateUncertaintyInMeters geodeticDatum georeferenceProtocol       country countryCode
1                           100         WGS84         Handheld GPS United States          US
2                           100         WGS84         Handheld GPS United States          US
3                           100         WGS84         Handheld GPS United States          US
4                           100         WGS84         Handheld GPS United States          US
5                           100         WGS84         Handheld GPS United States          US
6                           100         WGS84         Handheld GPS United States          US
                             datasetID                                 eventID sampleSizeUni
1 TPWD_HARC_Texas_Aransas_Bay_Bag_Seine Station_95_Date_09JAN1997:14:35:00.000       hectares
2 TPWD_HARC_Texas_Aransas_Bay_Bag_Seine Station_95_Date_18AUG2000:11:02:00.000       hectares
3 TPWD_HARC_Texas_Aransas_Bay_Bag_Seine Station_96_Date_28JUN2005:08:41:00.000       hectares
4 TPWD_HARC_Texas_Aransas_Bay_Bag_Seine Station_96_Date_23AUG2006:11:47:00.000       hectares
5 TPWD_HARC_Texas_Aransas_Bay_Bag_Seine Station_96_Date_17OCT2006:14:23:00.000       hectares
6 TPWD_HARC_Texas_Aransas_Bay_Bag_Seine Station_96_Date_19FEB1996:10:27:00.000       hectares
  samplingEffort
1    120 seconds
2    120 seconds
3    120 seconds
4    120 seconds
5    120 seconds
6    120 seconds
```

```
write.csv(event, file = paste0(event[1,]$datasetID, "_event_", lubridate::today(),".csv"), fi

occurrence <- occurrence[c("vernacularName","eventID","occurrenceStatus","basisOfRecord",
                           "scientificName","scientificNameID","kingdom","phylum","class",
                           "order","family","genus",
                           "scientificNameAuthorship","taxonRank", "organismQuantity",
                           "organismQuantityType", "occurrenceID","collectionCode")]
head(occurrence)
```

```
  vernacularName                                eventID occurrenceStatus    basisOfRecord
1  Alligator gar Station_95_Date_09JAN1997:14:35:00.000           Absent HumanObservation
```

```
2  Alligator gar Station_95_Date_18AUG2000:11:02:00.000           Absent HumanObservation
3  Alligator gar Station_96_Date_28JUN2005:08:41:00.000           Absent HumanObservation
4  Alligator gar Station_96_Date_23AUG2006:11:47:00.000           Absent HumanObservation
5  Alligator gar Station_96_Date_17OCT2006:14:23:00.000           Absent HumanObservation
6  Alligator gar Station_96_Date_19FEB1996:10:27:00.000           Absent HumanObservation
       scientificName                          scientificNameID  kingdom   phylum       clas
1 Atractosteus spatula urn:lsid:marinespecies.org:taxname:279822 Animalia Chordata Actinopter
2 Atractosteus spatula urn:lsid:marinespecies.org:taxname:279822 Animalia Chordata Actinopter
3 Atractosteus spatula urn:lsid:marinespecies.org:taxname:279822 Animalia Chordata Actinopter
4 Atractosteus spatula urn:lsid:marinespecies.org:taxname:279822 Animalia Chordata Actinopter
5 Atractosteus spatula urn:lsid:marinespecies.org:taxname:279822 Animalia Chordata Actinopter
6 Atractosteus spatula urn:lsid:marinespecies.org:taxname:279822 Animalia Chordata Actinopter
            order        family        genus scientificNameAuthorship taxonRank organismQuan
1 Lepisosteiformes Lepisosteidae Atractosteus         (Lacepède, 1803)   Species
2 Lepisosteiformes Lepisosteidae Atractosteus         (Lacepède, 1803)   Species
3 Lepisosteiformes Lepisosteidae Atractosteus         (Lacepède, 1803)   Species
4 Lepisosteiformes Lepisosteidae Atractosteus         (Lacepède, 1803)   Species
5 Lepisosteiformes Lepisosteidae Atractosteus         (Lacepède, 1803)   Species
6 Lepisosteiformes Lepisosteidae Atractosteus         (Lacepède, 1803)   Species
  organismQuantityType                                          occurrenceID        col
1   Relative Abundance Station_95_Date_09JAN1997:14:35:00.000_Atractosteus_spatula Aransas Ba
2   Relative Abundance Station_95_Date_18AUG2000:11:02:00.000_Atractosteus_spatula Aransas Ba
3   Relative Abundance Station_96_Date_28JUN2005:08:41:00.000_Atractosteus_spatula Aransas Ba
4   Relative Abundance Station_96_Date_23AUG2006:11:47:00.000_Atractosteus_spatula Aransas Ba
5   Relative Abundance Station_96_Date_17OCT2006:14:23:00.000_Atractosteus_spatula Aransas Ba
6   Relative Abundance Station_96_Date_19FEB1996:10:27:00.000_Atractosteus_spatula Aransas Ba

write.csv(occurrence, file = paste0(event[1,]$datasetID, "_occurrence_",lubridate::today(),"
```

3 Darwin Core Salmon Data Remap

3.1 Salmon Ocean Ecology Data

3.1.1 Intro

One of the goals of the Hakai Institute and the Canadian Integrated Ocean Observing System (CIOOS) is to facilitate Open Science and FAIR (findable, accessible, interoperable, reusable) ecological and oceanographic data. In a concerted effort to adopt or establish how best to do that, several Hakai and CIOOS staff attended an International Ocean Observing System (IOOS) Code Sprint in Ann Arbour, Michigan between October 7–11, 2019, to discuss how to implement FAIR data principles for biological data collected in the marine environment.

The Darwin Core is a highly structured data format that standardizes data table relations, vocabularies, and defines field names. The Darwin Core defines three table types: `event`, `occurrence`, and `measurementOrFact`. This intuitively captures the way most ecologists conduct their research. Typically, a survey (event) is conducted and measurements, counts, or observations (collectively measurementOrFacts) are made regarding a specific habitat or species (occurrence).

In the following script I demonstrate how I go about converting a subset of the data collected from the Hakai Institute Juvenile Salmon Program and discuss challenges, solutions, pros and cons, and when and what's worthwhile to convert to Darwin Core.

The conversion of a dataset to Darwin Core is much easier if your data are already tidy (normalized) in which you represent your data in separate tables that reflect the hierarchical and related nature of your observations. If your data are not already in a consistent and structured format, the conversion would likely be very arduos and not intuitive.

3.1.2 event

The first step is to consider what you will define as an event in your data set. I defined the capture of fish using a purse seine net as the `event`. Therefore, each row in the `event` table is one deployment of a seine net and is assigned a unique `eventID`.

My process for conversion was to make a new table called `event` and map the standard Darwin Core column names to pre-existing columns that serve the same purpose in my original `seine_data` table and populate the other required fields.

```
event <- tibble(eventID = survey_seines$seine_id,
                eventDate = date(survey_seines$survey_date),
                decimalLatitude = survey_seines$lat,
                decimalLongitude = survey_seines$long,
                geodeticDatum = "EPSG:4326 WGS84",
                minimumDepthInMeters = 0,
                maximumDepthInMeters = 9, # seine depth is 9 m
                samplingProtocol = "http://dx.doi.org/10.21966/1.566666" # This is the DOI fo
               )

write_csv(event, here::here("datasets", "hakai_salmon_data", "event.csv"))
```

3.1.3 occurrence

Next you'll want to determine what constitutes an occurrence for your data set. Because each event caputers fish, I consider each fish to be an occurrence. Therefore, the unit of observation (each row) in the occurrence table is a fish. To link each occurence to an event you need to include the `eventID` column for every occurrence so that you know what seine (event) each fish (occurrence) came from. You must also provide a globally unique identifier for each occurrence. I already have a locally unique identifier for each fish in the original `fish_data` table called `ufn`. To make it globally unique I pre-pend the organization and research program metadata to the `ufn` column.

```
#TODO: Include bycatch data as well

## make table long first
seines_total_long <- survey_seines %>%
  select(seine_id, so_total, pi_total, cu_total, co_total, he_total, ck_total) %>%
  pivot_longer(-seine_id, names_to = "scientificName", values_to = "n")

seines_total_long$scientificName <- recode(seines_total_long$scientificName, so_total = "Onc

seines_taken_long <- survey_seines %>%
  select(seine_id, so_taken, pi_taken, cu_taken, co_taken, he_taken, ck_taken) %>%
  pivot_longer(-seine_id, names_to = "scientificName", values_to = "n_taken")

seines_taken_long$scientificName <- recode(seines_taken_long$scientificName, so_taken = "Onc

## remove records that have already been assigned an ID
seines_long <-  full_join(seines_total_long, seines_taken_long, by = c("seine_id", "scientifi
  drop_na() %>%
```

```
  mutate(n_not_taken = n - n_taken) %>% #so_total includes the number taken so I subtract n_t
  select(-n_taken, -n) %>%
  filter(n_not_taken > 0)

all_fish_caught <-
  seines_long[rep(seq.int(1, nrow(seines_long)), seines_long$n_not_taken), 1:3] %>%
  select(-n_not_taken) %>%
  mutate(prefix = "hakai-jsp-",
         suffix = 1:nrow(.),
         occurrenceID = paste0(prefix, suffix)
  ) %>%
  select(-prefix, -suffix)

#

# Change species names to full Scientific names
latin <- fct_recode(fish_data$species, "Oncorhynchus nerka" = "SO", "Oncorhynchus gorbuscha"
  as.character()

fish_retained_data <- fish_data %>%
  mutate(scientificName = latin) %>%
  select(-species) %>%
  mutate(prefix = "hakai-jsp-",
         occurrenceID = paste0(prefix, ufn)) %>%
  select(-semsp_id, -prefix, -ufn, -fork_length_field, -fork_length, -weight, -weight_field)

occurrence <- bind_rows(all_fish_caught, fish_retained_data) %>%
  mutate(basisOfRecord = "HumanObservation",
        occurenceStatus = "present") %>%
  rename(eventID = seine_id)
```

For each occuerence of the six different fish species that I caught I need to match the species name that I provide with the official `scientificName` that is part of the World Register of Marine Species database http://www.marinespecies.org/

```
# I went directly to the WoRMS webite (http://www.marinespecies.org/) to download the full ta

species_matched <- readxl::read_excel(here::here("datasets", "hakai_salmon_data", "raw_data"

occurrence <- left_join(occurrence, species_matched, by = c("scientificName" = "ScientificNa
  select(occurrenceID, basisOfRecord, scientificName, eventID, occurrenceStatus = occurenceSt
```

```
write_csv(occurrence, here::here("datasets", "hakai_salmon_data", "occurrence.csv"))
```

3.1.4 measurementOrFact

To convert all your measurements or facts from your normal format to Darwin Core you essentially need to put all your measurements into one column called measurementType and a corresponding column called MeasurementValue. This standardizes the column names are in the `measurementOrFact` table. There are a number of predefined `measurementTypes` listed on the NERC database that should be used where possible. I found it difficult to navigate this page to find the correct `measurementType`.

Here I convert length, and weight measurements that relate to an event and an occurrence and call those `measurementTypes` as `length` and `weight`.

```
fish_data$weight <- coalesce(fish_data$weight, fish_data$weight_field)
fish_data$fork_length <- coalesce(fish_data$fork_length, fish_data$fork_length_field)

fish_length <- fish_data %>%
  mutate(occurrenceID = paste0("hakai-jsp-", ufn)) %>%
  select(occurrenceID, eventID = seine_id, fork_length, weight) %>%
  mutate(measurementType = "fork length", measurementValue = fork_length) %>%
  select(eventID, occurrenceID, measurementType, measurementValue) %>%
  mutate(measurementUnit = "millimeters",
         measurementUnitID = "http://vocab.nerc.ac.uk/collection/P06/current/UXMM/")

fish_weight <- fish_data %>%
  mutate(occurrenceID = paste0("hakai-jsp-", ufn)) %>%
  select(occurrenceID, eventID = seine_id, fork_length, weight) %>%
  mutate(measurementType = "mass", measurementValue = weight) %>%
  select(eventID, occurrenceID, measurementType, measurementValue) %>%
  mutate(measurementUnit = "grams",
         measurementUnitID = "http://vocab.nerc.ac.uk/collection/P06/current/UGRM/")

measurementOrFact <- bind_rows(fish_length, fish_weight) %>%
  drop_na(measurementValue)

rm(fish_length, fish_weight)

write_csv(measurementOrFact, here::here("datasets", "hakai_salmon_data", "measurementOrFact.
```

4 Seagrass Density to DWC eMoF format

4.1 Hakai Seagrass

4.1.1 Setup

This section clears the workspace, checks the working directory, and installs packages (if required) and loads packages, and loads necessary datasets

```
library("knitr")
# Knitr global chunk options
opts_chunk$set(message = FALSE,
               warning = FALSE,
               error   = FALSE)
```

4.1.1.1 Load Data

First load the seagrass density survey data, set variable classes, and have a quick look

```
# Load density data
seagrassDensity <-
  read.csv(seagrassDensity_csv,
           colClass = "character") %>%
  mutate(date             = ymd(date),
         depth            = as.numeric(depth),
         transect_dist    = factor(transect_dist),
         collected_start  = ymd_hms(collected_start),
         collected_end    = ymd_hms(collected_end),
         density          = as.numeric(density),
         density_msq      = as.numeric(density_msq),
         canopy_height_cm = as.numeric(canopy_height_cm),
         flowering_shoots = as.numeric(flowering_shoots)) %T>%
  glimpse()
```

```
Rows: 3,031
Columns: 22
$ X                <chr> "1", "2", "3", "4", "5", "6", "7", "8", "9", "10", "1~
$ organization     <chr> "HAKAI", "HAKAI", "HAKAI", "HAKAI", "HAKAI", "HAKAI",~
$ work_area        <chr> "CALVERT", "CALVERT", "CALVERT", "CALVERT", "CALVERT"~
$ project          <chr> "MARINEGEO", "MARINEGEO", "MARINEGEO", "MARINEGEO", "~
$ survey           <chr> "PRUTH_BAY", "PRUTH_BAY", "PRUTH_BAY", "PRUTH_BAY", "~
$ site_id          <chr> "PRUTH_BAY_INTERIOR4", "PRUTH_BAY_INTERIOR4", "PRUTH_~
$ date             <date> 2016-05-13, 2016-05-13, 2016-05-13, 2016-05-13, 2016~
$ sampling_bout    <chr> "4", "4", "4", "4", "4", "4", "4", "6", "6", "6", "6"~
$ dive_supervisor  <chr> "Zach", "Zach", "Zach", "Zach", "Zach", "Zach", "Zach~
$ collector        <chr> "Derek", "Derek", "Derek", "Derek", "Derek", "Derek",~
$ hakai_id         <chr> "2016-05-13_PRUTH_BAY_INTERIOR4_0", "2016-05-13_PRUTH~
$ sample_type      <chr> "seagrass_density", "seagrass_density", "seagrass_den~
$ depth            <dbl> 6.0, 6.0, 6.0, 6.0, 5.0, 6.0, 6.0, 9.1, 9.0, 8.9, 9.0~
$ transect_dist    <fct> 0, 5, 10, 15, 20, 25, 30, 10, 15, 20, 25, 30, 0, 5, 1~
$ collected_start  <dttm> NA, NA, NA, NA, NA, NA, NA, NA, NA, NA, NA, NA, NA, ~
$ collected_end    <dttm> NA, NA, NA, NA, NA, NA, NA, NA, NA, NA, NA, NA, NA, ~
$ density          <dbl> 13, 10, 18, 22, 16, 31, 9, 5, 6, 6, 6, 3, 13, 30, 23,~
$ density_msq      <dbl> 208, 160, 288, 352, 256, 496, 144, 80, 96, 96, 96, 48~
$ canopy_height_cm <dbl> 60, 63, 80, 54, 55, 50, 63, 85, 80, 90, 95, 75, 60, 6~
$ flowering_shoots <dbl> NA, NA, NA, NA, NA, NA, NA, 0, 0, 0, 0, 0, NA, NA, NA~
$ comments         <chr> NA, NA, NA, NA, NA, NA, NA, NA, NA, NA, NA, NA, NA, N~
$ quality_log      <chr> NA, NA, NA, NA, NA, NA, NA, NA, NA, NA, NA, NA, NA, N~
```

Next, load the habitat survey data, and same as above, set variable classes as necessary, and have a quick look.

```
# load habitat data, set variable classes, have a quick look
seagrassHabitat <-
  read.csv(seagrassHabitat_csv,
           colClasses = "character") %>%
  mutate(date            = ymd(date),
         depth           = as.numeric(depth),
         hakai_id        = str_pad(hakai_id, 5, pad = "0"),
         transect_dist   = factor(transect_dist),
         collected_start = ymd_hms(collected_start),
         collected_end   = ymd_hms(collected_end)) %T>%
  glimpse()
```

```
Rows: 2,052
Columns: 28
```

```
$ X                <chr> "1", "2", "3", "4", "5", "6", "7", "8", "9", "10", "1~
$ organization     <chr> "HAKAI", "HAKAI", "HAKAI", "HAKAI", "HAKAI", "HAKAI",~
$ work_area        <chr> "CALVERT", "CALVERT", "CALVERT", "CALVERT", "CALVERT"~
$ project          <chr> "MARINEGEO", "MARINEGEO", "MARINEGEO", "MARINEGEO", "~
$ survey           <chr> "CHOKED_PASS", "CHOKED_PASS", "CHOKED_PASS", "CHOKED_~
$ site_id          <chr> "CHOKED_PASS_INTERIOR6", "CHOKED_PASS_INTERIOR6", "CH~
$ date             <date> 2017-11-22, 2017-11-22, 2017-11-22, 2017-11-22, 2017~
$ sampling_bout    <chr> "6", "6", "6", "6", "6", "6", "1", "1", "1", "1", "1"~
$ dive_supervisor  <chr> "gillian", "gillian", "gillian", "gillian", "gillian"~
$ collector        <chr> "zach", "zach", "zach", "zach", "zach", "zach", "kyle~
$ hakai_id         <chr> "10883", "2017-11-22_CHOKED_PASS_INTERIOR6_5 - 10", "~
$ sample_type      <chr> "seagrass_habitat", "seagrass_habitat", "seagrass_hab~
$ depth            <dbl> 9.2, 9.4, 9.3, 9.0, 9.2, 9.2, 3.4, 3.4, 3.4, 3.4, 3.4~
$ transect_dist    <fct> 0 - 5, 10-May, 15-Oct, 15 - 20, 20 - 25, 25 - 30, 0 -
~
$ collected_start  <dttm> NA, NA, NA, NA, NA, NA, NA, NA, NA, NA, NA, NA, NA, ~
$ collected_end    <dttm> NA, NA, NA, NA, NA, NA, NA, NA, NA, NA, NA, NA, NA, ~
$ bag_uid          <chr> "10883", NA, NA, "11094", NA, "11182", "7119", NA, "7~
$ bag_number       <chr> "3557", NA, NA, "3520", NA, "903", "800", NA, "318", ~
$ density_range    <chr> NA, NA, NA, NA, NA, NA, NA, NA, NA, NA, NA, NA, NA, N~
$ substrate        <chr> "sand,shell hash", "sand,shell hash", "sand,shell has~
$ patchiness       <chr> "< 1", "< 1", "02-Jan", "< 1", "< 1", "< 1", "< 1", "~
$ adj_habitat_1    <chr> "seagrass", "seagrass", "seagrass", "seagrass", "seag~
$ adj_habitat_2    <chr> NA, NA, NA, NA, NA, NA, NA, NA, NA, NA, NA, NA, NA, N~
$ sample_collected <chr> "TRUE", "FALSE", "FALSE", "TRUE", "FALSE", "TRUE", "T~
$ vegetation_1     <chr> NA, NA, NA, NA, NA, NA, "des", NA, "des", NA, NA, NA,~
$ vegetation_2     <chr> NA, NA, NA, NA, NA, NA, NA, NA, NA, NA, NA, NA, NA, N~
$ comments         <chr> NA, NA, NA, NA, NA, NA, NA, NA, NA, NA, NA, NA, NA, N~
$ quality_log      <chr> "1: Flowering shoots 0 for entire transects", NA, NA,~
```

Finally, load coordinate data for surveys, and subset necessary variables

```
coordinates <-
  read.csv(coordinate_csv,
           colClass = c("Point.Name" = "character")) %>%
  select(Point.Name, Decimal.Lat, Decimal.Long) %T>%
  glimpse()
```

```
Rows: 70
Columns: 3
$ Point.Name   <chr> NA, NA, NA, NA, NA, NA, NA, NA, NA, NA, NA, NA, NA, NA, N~
$ Decimal.Lat  <dbl> 52.06200, 52.05200, 51.92270, 51.92500, 51.80900, 51.8090~
```

```
$ Decimal.Long <dbl> -128.4120, -128.4030, -128.4648, -128.4540, -128.2360, -
1~
```

4.1.1.2 Merge Datasets

Now all the datasets have been loaded, and briefly formatted, we'll join together the habitat and density surveys, and the coordinates for these.

The seagrass density surveys collect data at discrete points (ie. 5 metres) along the transects, while the habitat surveys collect data over sections (ie. 0 - 5 metres) along the transects. In order to fit these two surveys together, we'll narrow the habitat surveys from a range to a point so the locations will match. Based on how the habitat data is collected, the point the habitat survey is applied to will be the distance at the end of the swath (ie. 10-15m will become 15m). To account for no preceeding distance, the 0m distance will use the 0-5m section of the survey.

First, well make the necessary transformations to the habitat dataset.

```
# Reformat seagrassHabitat to merge with seagrassDensity
## replicate 0 - 5m transect dist to match with 0m in density survey;
## rest of habitat bins can map one to one with density (ie. 5 - 10m -> 10m)
seagrass0tmp <-
  seagrassHabitat %>%
  filter(transect_dist %in% c("0 - 5", "0 - 2.5")) %>%
  mutate(transect_dist = factor(0))

## collapse various levels to match with seagrassDensity transect_dist
seagrassHabitat$transect_dist <-
  fct_collapse(seagrassHabitat$transect_dist,
               "5" = c("0 - 5", "2.5 - 7.5"),
               "10" = c("5 - 10", "7.5 - 12.5"),
               "15" = c("10 - 15", "12.5 - 17.5"),
               "20" = c("15 - 20", "17.5 - 22.5"),
               "25" = c("20 - 25", "22.5 - 27.5"),
               "30" = c("25 - 30", "27.5 - 30"))

## merge seagrass0tmp into seagrassHabitat to account for 0m samples,
## set class for date, datetime variables
seagrassHabitatFull <-
  rbind(seagrass0tmp, seagrassHabitat) %>%
  filter(transect_dist != "0 - 2.5")  %>% # already captured in seagrass0tmp
  droplevels(.)  # remove now unused factor levels
```

With the distances of habitat and density surveys now corresponding, we can now merge these two datasets plus there coordinates together, combine redundant fields, and remove unnecessary fields.

```
# Merge seagrassHabitatFull with seagrassDensity, then coordinates
seagrass <-
  full_join(seagrassHabitatFull, seagrassDensity,
            by = c("organization",
                   "work_area",
                   "project",
                   "survey",
                   "site_id",
                   "date",
                   "transect_dist")) %>%
  # merge hakai_id.x and hakai_id.y into single variable field;
  # use combination of date, site_id, transect_dist, and field uid (hakai_id
  # when present)
  mutate(field_uid = ifelse(sample_collected == TRUE, hakai_id.x, "NA"),
         hakai_id = paste(date, "HAKAI:CALVERT", site_id, transect_dist, sep = ":"),
         # below, aggregate metadata that didn't merge naturally (ie. due to minor
         # differences in watch time or depth gauges)
         dive_supervisor = dive_supervisor.x,
         collected_start = ymd_hms(ifelse(is.na(collected_start.x),
                                          collected_start.y,
                                          collected_start.x)),
         collected_end   = ymd_hms(ifelse(is.na(collected_start.x),
                                          collected_start.y,
                                          collected_start.x)),
         depth_m         = ifelse(is.na(depth.x), depth.y, depth.x),
         sampling_bout   = sampling_bout.x) %>%
  left_join(., coordinates,  # add coordinates
            by = c("site_id" = "Point.Name")) %>%
  select( - c(X.x, X.y, hakai_id.x, hakai_id.y,  # remove unnecessary variables
              dive_supervisor.x, dive_supervisor.y,
              collected_start.x, collected_start.y,
              collected_end.x, collected_end.y,
              depth.x, depth.y,
              sampling_bout.x, sampling_bout.y)) %>%
  mutate(density_msq = as.character(density_msq),
         canopy_height_cm = as.character(canopy_height_cm),
         flowering_shoots = as.character(flowering_shoots),
         depth_m = as.character(depth_m)) %T>%
  glimpse()
```

```
Rows: 3,743
Columns: 38
$ organization     <chr> "HAKAI", "HAKAI", "HAKAI", "HAKAI", "HAKAI", "HAKAI",~
$ work_area        <chr> "CALVERT", "CALVERT", "CALVERT", "CALVERT", "CALVERT"~
$ project          <chr> "MARINEGEO", "MARINEGEO", "MARINEGEO", "MARINEGEO", "~
$ survey           <chr> "CHOKED_PASS", "CHOKED_PASS", "CHOKED_PASS", "PRUTH_B~
$ site_id          <chr> "CHOKED_PASS_INTERIOR6", "CHOKED_PASS_EDGE1", "CHOKED~
$ date             <date> 2017-11-22, 2017-05-19, 2017-05-19, 2017-07-03, 2017~
$ collector.x      <chr> "zach", "kyle", NA, "tanya", "zach", "zach", "zach", ~
$ sample_type.x    <chr> "seagrass_habitat", "seagrass_habitat", "seagrass_hab~
$ transect_dist    <fct> 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0,~
$ bag_uid          <chr> "10883", "7119", "7031", "2352", "10255", "10023", "1~
$ bag_number       <chr> "3557", "800", "301", "324", "3506", "3555", "3534", ~
$ density_range    <chr> NA, NA, NA, NA, NA, NA, NA, NA, NA, NA, NA, NA, NA, N~
$ substrate        <chr> "sand,shell hash", "sand,shell hash", "sand,shell has~
$ patchiness       <chr> "< 1", "< 1", "< 1", "< 1", "< 1", "05-Apr", "04-
Mar"~
$ adj_habitat_1    <chr> "seagrass", "sand", "standing kelp", "seagrass", "sea~
$ adj_habitat_2    <chr> NA, NA, NA, NA, NA, NA, "standing kelp", NA, NA, NA, ~
$ sample_collected <chr> "TRUE", "TRUE", "TRUE", "TRUE", "TRUE", "TRUE", "TRUE~
$ vegetation_1     <chr> NA, "des", "des", "zm", "des", NA, NA, NA, NA, NA, NA~
$ vegetation_2     <chr> NA, NA, NA, NA, NA, NA, NA, NA, NA, NA, NA, NA, NA, "~
$ comments.x       <chr> NA, NA, NA, NA, NA, NA, NA, NA, NA, NA, NA, NA, NA, N~
$ quality_log.x    <chr> "1: Flowering shoots 0 for entire transects", NA, NA,~
$ collector.y      <chr> "derek", "ondine", "ondine", "derek", "derek", "derek~
$ sample_type.y    <chr> "seagrass_density", "seagrass_density", "seagrass_den~
$ density          <dbl> 4, 10, 6, 13, 6, 1, 2, 6, 21, 3, 7, 4, 3, 14, 17, 11,~
$ density_msq      <chr> "64", "160", "96", "208", "96", "16", "32", "96", "33~
$ canopy_height_cm <chr> "80", "80", "110", "60", "125", "100", "100", "125", ~
$ flowering_shoots <chr> "0", NA, NA, NA, NA, NA, NA, "0", NA, NA, NA, "0", NA~
$ comments.y       <chr> NA, NA, NA, NA, NA, NA, NA, NA, NA, NA, NA, NA, NA, N~
$ quality_log.y    <chr> NA, NA, NA, NA, NA, NA, NA, NA, NA, NA, NA, NA, NA, "~
$ field_uid        <chr> "10883", "07119", "07031", "02352", "10255", "10023",~
$ hakai_id         <chr> "2017-11-22:HAKAI:CALVERT:CHOKED_PASS_INTERIOR6:0", "~
$ dive_supervisor  <chr> "gillian", "gillian,gillian.sadlierbrown", "gillian,g~
$ collected_start  <dttm> NA, NA, NA, NA, NA, NA, NA, NA, NA, NA, NA, NA, NA, ~
$ collected_end    <dttm> NA, NA, NA, NA, NA, NA, NA, NA, NA, NA, NA, NA, NA, ~
$ depth_m          <chr> "9.2", "3.4", "4.8", "2.4", "5.3", "5.6", "4.4", "2.5~
$ sampling_bout    <chr> "6", "1", "3", "5", "5", "3", "5", "2", "1", "2", "6"~
$ Decimal.Lat      <dbl> 51.67482, 51.67882, 51.67493, 51.64532, 51.67349, 51.~
$ Decimal.Long     <dbl> -128.1195, -128.1148, -128.1237, -128.1193, -128.1180~
```

4.1.2 Convert Data to Darwin Core - Extended Measurement or Fact format

The Darwin Core ExtendedMeasurementOrFact (eMoF) extension bases records around a core event (rather than occurrence as in standard Darwin Core), allowing for additional measurement variables to be associated with occurrence data.

4.1.2.1 Add Event ID and Occurrence ID variables to dataset

As this dataset will be annually updated, rather than using natural keys (ie. using package::uuid to autogenerate) for event and occurence IDs, here we will use surrogate keys made up of a concatenation of date survey, transect location, observation distance, and sample ID (for occurrenceID, when a sample is present).

```
# create and populate eventID variable
## currently only event is used, but additional surveys and abiotic data
## are associated with parent events that may be included at a later date
seagrass$eventID <- seagrass$hakai_id

# create and populate occurrenceID; combine eventID with transect_dist
# and field_uid
## in the event of <NA> field_uid, no sample was collected, but
## measurements and occurrence are still taken; no further subsamples
## are associated with <NA> field_uids
seagrass$occurrenceID <-
  with(seagrass,
       paste(eventID, transect_dist, field_uid, sep = ":"))
```

4.1.2.2 Create Event, Occurrence, and eMoF tables

Now that we've created eventIDs and occurrenceIDs to connect all the variables together, we can begin to create the Event, Occurrence, and extended Measurement or Fact table necessary for DarwinCore compliant datasets

4.1.2.2.1 Event Table

```
# subset seagrass to create event table
seagrassEvent <-
  seagrass %>%
  distinct %>%  # some duplicates in data stemming from database conflicts
  select(date,
```

```
         Decimal.Lat, Decimal.Long, transect_dist,
         depth_m, eventID) %>%
  rename(eventDate                      = date,
         decimalLatitude                = Decimal.Lat,
         decimalLongitude               = Decimal.Long,
         coordinateUncertaintyInMeters = transect_dist,
         minimumDepthInMeters           = depth_m,
         maximumDepthInMeters           = depth_m) %>%
  mutate(geodeticDatum  = "WGS84",
         samplingEffort = "30 metre transect") %T>% glimpse
```

```
Rows: 3,659
Columns: 8
$ eventDate                     <date> 2017-11-22, 2017-05-19, 2017-05-
19, 201~
$ decimalLatitude               <dbl> 51.67482, 51.67882, 51.67493, 51.64532, ~
$ decimalLongitude              <dbl> -128.1195, -128.1148, -128.1237, -
128.11~
$ coordinateUncertaintyInMeters <fct> 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0~
$ maximumDepthInMeters          <chr> "9.2", "3.4", "4.8", "2.4", "5.3", "5.6"~
$ eventID                       <chr> "2017-11-22:HAKAI:CALVERT:CHOKED_PASS_IN~
$ geodeticDatum                 <chr> "WGS84", "WGS84", "WGS84", "WGS84", "WGS~
$ samplingEffort                <chr> "30 metre transect", "30 metre transect"~
```

```
# save event table to csv
write.csv(seagrassEvent, seagrassEvent_csv)
```

4.1.2.2.2 Occurrence Table

```
# subset seagrass to create occurrence table
seagrassOccurrence <-
  seagrass %>%
  distinct %>%  # some duplicates in data stemming from database conflicts
  select(eventID, occurrenceID) %>%
  mutate(basisOfRecord = "HumanObservation",
         scientificName   = "Zostera subg. Zostera marina",
         occurrenceStatus = "present")

# Taxonomic name matching
# in addition to the above metadata, DarwinCore format requires further
```

```r
# taxonomic data that can be acquired through the WoRMS register.
## Load taxonomic info, downloaded via WoRMS tool
# zmWorms <-
#   read.delim("raw_data/zmworms_matched.txt",
#              header = TRUE,
#              nrows  = 1)

zmWorms <- wm_record(id = 145795)

# join WoRMS name with seagrassOccurrence create above
seagrassOccurrence <-
  full_join(seagrassOccurrence, zmWorms,
            by = c("scientificName" = "scientificname")) %>%
  select(eventID, occurrenceID, basisOfRecord, scientificName, occurrenceStatus, AphiaID,
         url, authority, status, unacceptreason, taxonRankID, rank,
         valid_AphiaID, valid_name, valid_authority, parentNameUsageID,
         kingdom, phylum, class, order, family, genus, citation, lsid,
         isMarine, match_type, modified) %T>%
  glimpse
```

```
Rows: 3,660
Columns: 27
$ eventID           <chr> "2017-11-22:HAKAI:CALVERT:CHOKED_PASS_INTERIOR6:0", ~
$ occurrenceID      <chr> "2017-11-22:HAKAI:CALVERT:CHOKED_PASS_INTERIOR6:0:0:~
$ basisOfRecord     <chr> "HumanObservation", "HumanObservation", "HumanObserv~
$ scientificName    <chr> "Zostera subg. Zostera marina", "Zostera subg. Zoste~
$ occurrenceStatus  <chr> "present", "present", "present", "present", "present~
$ AphiaID           <int> NA, NA, NA, NA, NA, NA, NA, NA, NA, NA, NA, NA, NA, ~
$ url               <chr> NA, NA, NA, NA, NA, NA, NA, NA, NA, NA, NA, NA, NA, ~
$ authority         <chr> NA, NA, NA, NA, NA, NA, NA, NA, NA, NA, NA, NA, NA, ~
$ status            <chr> NA, NA, NA, NA, NA, NA, NA, NA, NA, NA, NA, NA, NA, ~
$ unacceptreason    <lgl> NA, NA, NA, NA, NA, NA, NA, NA, NA, NA, NA, NA, NA, ~
$ taxonRankID       <int> NA, NA, NA, NA, NA, NA, NA, NA, NA, NA, NA, NA, NA, ~
$ rank              <chr> NA, NA, NA, NA, NA, NA, NA, NA, NA, NA, NA, NA, NA, ~
$ valid_AphiaID     <int> NA, NA, NA, NA, NA, NA, NA, NA, NA, NA, NA, NA, NA, ~
$ valid_name        <chr> NA, NA, NA, NA, NA, NA, NA, NA, NA, NA, NA, NA, NA, ~
$ valid_authority   <chr> NA, NA, NA, NA, NA, NA, NA, NA, NA, NA, NA, NA, NA, ~
$ parentNameUsageID <int> NA, NA, NA, NA, NA, NA, NA, NA, NA, NA, NA, NA, NA, ~
$ kingdom           <chr> NA, NA, NA, NA, NA, NA, NA, NA, NA, NA, NA, NA, NA, ~
$ phylum            <chr> NA, NA, NA, NA, NA, NA, NA, NA, NA, NA, NA, NA, NA, ~
$ class             <chr> NA, NA, NA, NA, NA, NA, NA, NA, NA, NA, NA, NA, NA, ~
$ order             <chr> NA, NA, NA, NA, NA, NA, NA, NA, NA, NA, NA, NA, NA, ~
```

```
$ family            <chr> NA, NA, NA, NA, NA, NA, NA, NA, NA, NA, NA, NA, NA, ~
$ genus             <chr> NA, NA, NA, NA, NA, NA, NA, NA, NA, NA, NA, NA, NA, ~
$ citation          <chr> NA, NA, NA, NA, NA, NA, NA, NA, NA, NA, NA, NA, NA, ~
$ lsid              <chr> NA, NA, NA, NA, NA, NA, NA, NA, NA, NA, NA, NA, NA, ~
$ isMarine          <int> NA, NA, NA, NA, NA, NA, NA, NA, NA, NA, NA, NA, NA, ~
$ match_type        <chr> NA, NA, NA, NA, NA, NA, NA, NA, NA, NA, NA, NA, NA, ~
$ modified          <chr> NA, NA, NA, NA, NA, NA, NA, NA, NA, NA, NA, NA, NA, ~
```

```
# save occurrence table to csv
write.csv(seagrassOccurrence, seagrassOccurrence_csv)
```

4.1.2.2.3 Extended MeasurementOrFact table

```
seagrassMof <-
  seagrass %>%
  # select variables for eMoF table
  select(date,
         eventID, survey, site_id, transect_dist,
         substrate, patchiness, adj_habitat_1, adj_habitat_2,
         vegetation_1, vegetation_2,
         density_msq, canopy_height_cm, flowering_shoots) %>%
  # split substrate into two variables (currently holds two substrate type in same variable)
  separate(substrate, sep = ",", into = c("substrate_1", "substrate_2")) %>%
  # change variables names to match NERC database (or to be more descriptive where none exist
  rename(measurementDeterminedDate   = date,
         SubstrateTypeA              = substrate_1,
         SubstrateTypeB              = substrate_2,
         BarePatchLengthWithinSeagrass = patchiness,
         PrimaryAdjacentHabitat      = adj_habitat_1,
         SecondaryAdjacentHabitat    = adj_habitat_2,
         PrimaryAlgaeSp              = vegetation_1,
         SecondaryAlgaeSp            = vegetation_2,
         BedAbund                    = density_msq,
         CanopyHeight                = canopy_height_cm,
         FloweringBedAbund           = flowering_shoots) %>%
  # reformat variables into DwC MeasurementOrFact format
  # (single values variable, with measurement type, unit, etc. variables)
  pivot_longer( - c(measurementDeterminedDate, eventID, survey, site_id, transect_dist),
                names_to = "measurementType",
                values_to = "measurementValue",
                values_ptypes = list(measurementValue = "character")) %>%
```

```
  # use measurement type to fill in remainder of variables relating to
  # NERC vocabulary and metadata fields
  mutate(
    measurementTypeID = case_when(
      measurementType == "BedAbund" ~ "http://vocab.nerc.ac.uk/collection/P01/current/SDBIOL
      measurementType == "CanopyHeight" ~ "http://vocab.nerc.ac.uk/collection/P01/current/OB
      # measurementType == "BarePatchWithinSeagrass" ~ "",
      measurementType == "FloweringBedAbund" ~ "http://vocab.nerc.ac.uk/collection/P01/curre
    measurementUnit = case_when(
      measurementType == "BedAbund" ~ "Number per square metre",
      measurementType == "CanopyHeight" ~ "Centimetres",
      measurementType == "BarePatchhLengthWithinSeagrass" ~ "Metres",
      measurementType == "FloweringBedAbund" ~ "Number per square metre"),
    measurementUnitID = case_when(
      measurementType == "BedAbund" ~ "http://vocab.nerc.ac.uk/collection/P06/current/UPMS/"
      measurementType == "CanopyHeight" ~ "http://vocab.nerc.ac.uk/collection/P06/current/UL
      measurementType == "BarePatchhLengthWithinSeagrass" ~ "http://vocab.nerc.ac.uk/collecti
      measurementType == "FloweringBedAbund" ~ "http://vocab.nerc.ac.uk/collection/P06/curre
    measurementAccuracy = case_when(
      measurementType == "CanopyHeight" ~ 5),
    measurementMethod = case_when(
      measurementType == "BedAbund" ~ "25cmx25cm quadrat count",
      measurementType == "CanopyHeight" ~ "in situ with ruler",
      measurementType == "BarePatchhLengthWithinSeagrass" ~ "estimated along transect line",
      measurementType == "FloweringBedAbund" ~ "25cmx25cm quadrat count")) %>%
  select(eventID, measurementDeterminedDate, measurementType, measurementValue,
         measurementTypeID, measurementUnit, measurementUnitID, measurementAccuracy,
         measurementMethod) %T>%
#  select(!c(survey, site_id, transect_dist)) %T>%
  glimpse()
```

```
Rows: 37,430
Columns: 9
$ eventID                 <chr> "2017-11-22:HAKAI:CALVERT:CHOKED_PASS_INTERI~
$ measurementDeterminedDate <date> 2017-11-22, 2017-11-22, 2017-11-22, 2017-
11~
$ measurementType         <chr> "SubstrateTypeA", "SubstrateTypeB", "BarePat~
$ measurementValue        <chr> "sand", "shell hash", "< 1", "seagrass", NA,~
$ measurementTypeID       <chr> NA, NA, NA, NA, NA, NA, NA, "http://vocab.ne~
$ measurementUnit         <chr> NA, NA, NA, NA, NA, NA, NA, "Number per squa~
$ measurementUnitID       <chr> NA, NA, NA, NA, NA, NA, NA, "http://vocab.ne~
$ measurementAccuracy     <dbl> NA, NA, NA, NA, NA, NA, NA, NA, 5, NA, NA, N~
```

```
$ measurementMethod         <chr> NA, NA, NA, NA, NA, NA, NA, "25cmx25cm quadr~
```

```
# save eMoF table to csv
write.csv(seagrassMof, seagrassMof_csv)
```

4.1.3 Session Info

Print session information below in case necessary for future reference

```
# Print Session Info for future reference
sessionInfo()
```

```
R version 4.4.1 (2024-06-14)
Platform: aarch64-apple-darwin20
Running under: macOS 26.6.2

Matrix products: default
BLAS:   /Library/Frameworks/R.framework/Versions/4.4-arm64/Resources/lib/libRblas.0.dylib
LAPACK: /Library/Frameworks/R.framework/Versions/4.4-arm64/Resources/lib/libRlapack.dylib;  L

locale:
[1] en_US.UTF-8/en_US.UTF-8/en_US.UTF-8/C/en_US.UTF-8/en_US.UTF-8

time zone: UTC
tzcode source: internal

attached base packages:
[1] stats     graphics  grDevices utils     datasets  methods   base

other attached packages:
 [1] worrms_0.4.3    magrittr_2.0.5  lubridate_1.9.5 forcats_1.0.1
 [5] stringr_1.6.0   dplyr_1.2.1     purrr_1.2.2     readr_2.2.0
 [9] tidyr_1.3.2     tibble_3.3.1    ggplot2_4.0.3   tidyverse_2.0.0
[13] here_1.0.2      knitr_1.52

loaded via a namespace (and not attached):
 [1] gtable_0.3.6       jsonlite_2.0.0     compiler_4.4.1     Rcpp_1.1.2
 [5] tidyselect_1.2.1   urltools_1.7.3.1   scales_1.4.0       triebeard_0.4.1
 [9] yaml_2.3.12        fastmap_1.2.0      R6_2.6.1           generics_0.1.4
[13] curl_8.1.0         crul_1.6.0         rprojroot_2.1.1    pillar_1.11.1
[17] RColorBrewer_1.1-3 tzdb_0.5.0         rlang_1.3.0        httpcode_0.3.0
```

```
[21] stringi_1.8.9      xfun_0.62          S7_0.2.2           otel_0.2.0
[25] timechange_0.4.0   cli_3.6.6          withr_3.0.3        digest_0.6.39
[29] grid_4.4.1         hms_1.1.4          lifecycle_1.0.5    vctrs_0.7.3
[33] evaluate_1.0.5     glue_1.8.1         farver_2.1.2       rmarkdown_2.32
[37] tools_4.4.1        pkgconfig_2.0.3    htmltools_0.5.9
```

5 trawl_catch_data

5.1 Trawl Data

One of the more common datasets that can be standardized to Darwin Core and integrated within OBIS is catch data from e.g. a trawl sampling event, or a zooplankton net tow. Of special concern here are datasets that include both a total (species-specific) catch weight, in addition to individual measurements (for a subset of the overall data). In this case, through our standardization to Darwin Core, we want to ensure that data users understand that the individual measurements are a part of, or subset of, the overall (species-specific) record, whilst at the same time ensure that data providers are not duplicating occurrence records to OBIS.

The GitHub issue related to application is can be found here

5.1.1 Workflow Overview

In our current setup, this relationship between the overall catch data and subsetted information is provided in the resourceRelationship extension. This extension *cannot* currently be harvested by GBIF. The required terms for this extension are `resourceID`, `relatedResourceID`, `resourceRelationshipID` and `relationshipOfResource`. The `relatedResourceID` here refers to the *object* of the relationship, whereas the `resourceID` refers to the *subject* of the relationship:

- resourceRelationshipID: a unique identifier for the relationship between one resource (the subject) and another (relatedResource, object).
- resourceID: a unique identifier for the resource that is the subject of the relationship.
- relatedResourceID: a unique identifier for the resource that is the object of the relationship.
- relationshipOfResource: The relationship of the subject (identified by the resourceID) to the object (relatedResourceID). The relationshipOfResource is a free text field.

A few resources have been published to OBIS that contain the resourceRelationship extension (examples). Here, I'll lay out the process and coding used for the Trawl Catch and Species Abundance from the 2019 Gulf of Alaska International Year of the Salmon Expedition. In the following code chunks some details are omitted to improve the readability - the overall code to standardize the catch data can be found here. This dataset includes species-specific total

catch data at multiple stations (sampling events). From each catch, individual measurements were also taken. Depending on the number of individual caught in the trawl, this was either the total number of species individuals caught, or only a subset (in case of large numbers of individuals caught).

In this specific data record, we created a single Event Core with three extensions: an *occurrence* extension, *measurement or fact* extension, and the *resourceRelationship* extension. However, in this walk-through I'll only touch on the Event Core, occurrence extension and resourceRelationship extension.

The trawl data is part of a larger project collecting various data types related to salmon ocean ecology. Therefore, in our Event Core we nested information related to the sampling event in the specific layer. (include a visual representation of the schema). Prior to creating the Event Core, we ensured that e.g. dates and times followed the correct ISO-8601 standards, and converted to the correct time zone.

```
# Time is recorded numerically (1037 instead of 10:37), so need to change these columns:
trawl2019$END_DEPLOYMENT_TIME <- substr(as.POSIXct(sprintf("%04.0f", trawl2019$END_DEPLOYMENT
trawl2019$BEGIN_RETRIEVAL_TIME <- substr(as.POSIXct(sprintf("%04.0f", trawl2019$BEGIN_RETRIEV
# Additionally, the vessel time is recorded in 'Vladivostok' according to the metadata tab. T
trawl2019 <- trawl2019 %>%
  mutate(eventDate_start = format_iso_8601(as.POSIXct(paste(EVENT_DATE_START, END_DEPLOYMENT_
                                                      tz = "Asia/Vladivostok")),
         eventDate_start = str_replace(eventDate_start, "\\+00:00", "Z"),
         eventDate_finish = format_iso_8601(as.POSIXct(paste(EVENT_DATE_FINISH, BEGIN_RETRIEV
                                                       tz = "Asia/Vladivostok")),
         eventDate_finish = str_replace(eventDate_finish, "\\+00:00", "Z"),
         eventDate = paste(eventDate_start, eventDate_finish, sep = "/"),
         project = "IYS",
         cruise = paste(project, "GoA2019", sep = ":"),
         station = paste(cruise, TOW_NUMBER, sep=":Stn"),
         trawl = paste(station, "trawl", sep=":"))
```

Then we created the various layers of our Event Core. We created these layers/data frames from two separate datasets that data are pulled from - one dataset that contains the *overall* catch data, and one dataset that contains the *specimen* data:

```
trawl2019_allCatch <- read_excel(here("Trawl", "2019", "raw_data",
                                      "2019_GoA_Fish_Trawl_catchdata.xlsx"), sheet = "CATCH_D
  mutate(project = "IYS",
         cruise = paste(project, "GoA2019", sep = ":"),
         station = paste(cruise, `TOW_NUMBER (number)`, sep = ":Stn"),
         trawl = paste(station, "trawl", sep = ":"))
```

```
trawl2019_specimen <- read_excel(here("Trawl", "2019", "raw_data", "2019_GoA_Fish_Specimen_da
                                      sheet = "SPECIMEN_FINAL") %>%
  mutate(project = "IYS",
         cruise = paste(project, "GoA2019", sep = ":"),
         station = paste(cruise, TOW_NUMBER, sep = ":Stn"),
         trawl = paste(station, "trawl", sep = ":"),
         sample = paste(trawl, "sample", sep = ":"),
         sample = paste(sample, row_number(), sep = ""))
```

Next we created the Event Core, ensuring that we connect the data to the right layer (i.e. date and time should be connected to the layer associated with the sampling event). Please note that because we are creating multiple layers and nesting information, and then at a later stage combining different tables, this results in cells being populated with `NA`. These have to be removed prior to publishing the Event Core through the IPT.

```
trawl2019_project <- trawl2019 %>%
  select(eventID = project) %>%
  distinct(eventID) %>%
  mutate(type = "project")

trawl2019_cruise <- trawl2019 %>%
  select(eventID = cruise,
         parentEventID = project) %>%
  distinct(eventID, .keep_all = TRUE) %>%
  mutate(type = "cruise")

trawl2019_station <- trawl2019 %>%
  select(eventID = station,
         parentEventID = cruise) %>%
  distinct(eventID, .keep_all = TRUE) %>%
  mutate(type = "station")

# The coordinates associated to the trawl need to be presented in a LINESTRING.
# END_LONGITUDE_DD needs to be inverted (has to be between -180 and 180, inclusive).
trawl2019_coordinates <- trawl2019 %>%
  select(eventID = trawl,
         START_LATITUDE_DD,
         longitude,
         END_LATITUDE_DD,
         END_LONGITUDE_DD) %>%
  mutate(END_LONGITUDE_DD = END_LONGITUDE_DD * -1,
```

```
         footprintWKT = paste("LINESTRING (", longitude, START_LATITUDE_DD, ",",
                              END_LONGITUDE_DD, END_LATITUDE_DD, ")"))
trawl2019_linestring <- obistools::calculate_centroid(trawl2019_coordinates$footprintWKT)
trawl2019_linestring <- cbind(trawl2019_coordinates, trawl2019_linestring) %>%
  select(eventID, footprintWKT, decimalLatitude, decimalLongitude, coordinateUncertaintyInMe

trawl2019_trawl <- trawl2019 %>%
  select(eventID = trawl,
         parentEventID = station,
         eventDate,
         year,
         month,
         day) %>%
  mutate(minimumDepthInMeters = 0, # headrope was at the surface
         maximumDepthInMeters = trawl2019$MOUTH_OPENING_HEIGHT,
         samplingProtocol = "midwater trawl", # when available add DOI to paper here
         locality = case_when(
           trawl2019$EVENT_SUB_TYPE == "Can EEZ" ~ "Canadian EEZ"),
         locationID = case_when(
           trawl2019$EVENT_SUB_TYPE == "Can EEZ" ~ "http://marineregions.org/mrgid/8493")) %>
  left_join(trawl2019_linestring, by = "eventID") %>%
  distinct(eventID, .keep_all = TRUE) %>%
    mutate(type = "midwater trawl")

trawl2019_sample <- trawl2019_specimen %>%
  select(eventID = sample,
         parentEventID = trawl) %>%
  distinct(eventID, .keep_all = TRUE) %>%
  mutate(type = "individual sample")

trawl2019_event <- bind_rows(trawl2019_project,
                             trawl2019_cruise,
                             trawl2019_station,
                             trawl2019_trawl,
                             trawl2019_sample)

# Remove NAs from the Event Core:
trawl2019_event <- sapply(trawl2019_event, as.character)
trawl2019_event[is.na(trawl2019_event)] <- ""
trawl2019_event <- as.data.frame(trawl2019_event)
```

TO DO: Add visual of e.g. the top 10 rows of the Event Core.

Now that we created the Event Core, we create the occurrence extension. To do this, we create two separate occurrence data tables: one that includes the occurrence data for the *total* catch, and one data table for the *specimen* data. Finally, the Occurrence extension is created by combining these two data frames. Personally, I prefer to re-order it so it makes visual sense to me (nest the specimen occurrence records under their respective overall catch data).

```
trawl2019_allCatch_worms <- worrms::wm_records_names(unique(trawl2019_allCatch$scientificname
trawl2019_occ <- left_join(trawl2019_allCatch, trawl2019_allCatch_worms, by = "scientificname
  rename(eventID = trawl,
         specificEpithet = species,
         scientificNameAuthorship = authority,
         taxonomicStatus = status,
         taxonRank = rank,
         scientificName = scientificname,
         scientificNameID = lsid,
         individualCount = `CATCH_COUNT (pieces)(**includes Russian expansion for some specie
         occurrenceRemarks = COMMENTS) %>%
  mutate(occurrenceID = paste(eventID, "occ", sep = ":"),
         occurrenceID = paste(occurrenceID, row_number(), sep = ":"),
         occurrenceStatus = "present",
         sex = "")

trawl2019_catch_ind_worms <- worrms::wm_records_names(unique(trawl2019_catch_ind$scientificna
trawl2019_catch_ind_occ <- left_join(trawl2019_catch_ind, trawl2019_catch_ind_worms, by = "sc
  rename(scientificNameAuthorship = authority,
         taxonomicStatus = status,
         taxonRank = rank,
         scientificName = scientificname,
         scientificNameID = lsid) %>%
  mutate(occurrenceID = paste(eventID, "occ", sep = ":"),
         occurrenceStatus = "present",
         individualCount = 1)

# Combine the two occurrence data frames:
trawl2019_occ_ext <- dplyr::bind_rows(trawl2019_occ_fnl, trawl2019_catch_ind_fnl)

# To re-order the occurrenceID, use following code:
order <- stringr::str_sort(trawl2019_occ_ext$occurrenceID, numeric=TRUE)
trawl2019_occ_ext <- trawl2019_occ_ext[match(order, trawl2019_occ_ext$occurrenceID),] %>%
  mutate(basisOfRecord = "HumanObservation")
```

TO DO: Add visual of e.g. the top 10 rows of the Occurrence extension.

Please note that in the *overall* species-specific occurrence data frame, *individualCount* was not included. This term should not be used for abundance studies, but to avoid confusion and the appearance that the specimen records are an additional observation on top of the overall catch record, the *individualCount* term was left blank for the overall catch data.

A resource relationship extension is created to further highlight that the individual samples in the occurrence extension are part of a larger overall catch that was also listed in the occurrence extension. In this extension, we wanted to make sure to highlight that the *specimen* occurrence records are *a subset of* the *overall* catch data through the field `relationshipOfResource1`. Each of these relationships gets a unique `resourceRelationshipID`.

```
trawl_resourceRelationship <- trawl2019_occ_ext %>%
  select(eventID, occurrenceID, scientificName) %>%
  mutate(resourceID = ifelse(grepl("sample", trawl2019_occ_ext$occurrenceID), trawl2019_occ_e
  mutate(eventID = gsub(":sample.*", "", trawl2019_occ_ext$eventID)) %>%
  group_by(eventID, scientificName) %>%
  filter(n() != 1) %>%
  ungroup()

trawl_resourceRelationship <- trawl_resourceRelationship %>%
  mutate(relatedResourceID = ifelse(grepl("sample", trawl_resourceRelationship$occurrenceID)
  mutate(relationshipOfResource = ifelse(!is.na(resourceID), "is a subset of", NA)) %>%
  dplyr::arrange(eventID, scientificName) %>%
  fill(relatedResourceID) %>%
  filter(!is.na(resourceID))

order <- stringr::str_sort(trawl_resourceRelationship$resourceID, numeric = TRUE)
trawl_resourceRelationship <- trawl_resourceRelationship[match(order, trawl_resourceRelations

trawl_resourceRelationship <- trawl_resourceRelationship %>%
  mutate(resourceRelationshipID = paste(relatedResourceID, "rr", sep = ":"),
         ID = sprintf("%03d", row_number()),
         resourceRelationshipID = paste(resourceRelationshipID, ID, sep = ":")) %>%
  select(eventID, resourceRelationshipID, resourceID, relationshipOfResource, relatedResourc
```

TO DO: Add visual of e.g. the top 10 rows of the ResourceRelationship extension.

5.1.2 FAQ

Q1. Why not use the terms *associatedOccurrence* or *associatedTaxa*? **A**. There seems to be a movement away from the term *associatedOccurrence* as the `resourceRelationship` extension

has a much broader use case. Some issues that were raised on GitHub exemplify this, see e.g. here. *associatedTaxa* is used to provide identifiers or names of taxa and the associations of an Occurrence with them. This term is not apt for establishing relationships between taxa, only between specific Occurrences of an organism with other taxa. As noted on the TDWG website, *[…] Note that the ResourceRelationship class is an alternative means of representing associations, and with more detail.* See also e.g. this issue.

6 dataset-edna

By Diana LaScala-Gruenewald



Figure 6.1: Binder

6.1 Introduction

Rationale:

DNA derived data are increasingly being used to document taxon occurrences. To ensure these data are useful to the broadest possible community, GBIF published a guide entitled "Publishing DNA-derived data through biodiversity data platforms." This guide is supported by the DNA derived data extension for Darwin Core, which incorporates MIxS terms into the Darwin Core standard.

This use case draws on both the guide and the extension to illustrate how to incorporate a DNA derived data extension file into a Darwin Core archive.

For further information on this use case and the DNA Derived data extension in general, see the recording of the OBIS Webinar on Genetic Data.

Project abstract:

The example data employed in this use case are from marine filtered seawater samples collected at a nearshore station in Monterey Bay, California, USA. They were collected by CTD rosette and filtered by a peristaltic pump system. Subsequently, they underwent metabarcoding for the 18S V9 region. The resulting ASVs, their assigned taxonomy, and the metadata associated with their collection are the input data for the conversion scripts presented here.

A selection of samples from this collection were included in the publication "Environmental DNA reveals seasonal shifts and potential interactions in a marine community" which was published with open access in *Nature Communications* in 2020.

Contacts: - Francisco Chavez - Principle Investigator (chfr@mbari.org) - Kathleen Pitz - Research Associate (kpitz@mbari.org) - Diana LaScala-Gruenewald - Point of Contact (dianalg@mbari.org)

6.2 Published data

- GBIF
- OBIS

6.3 Repo structure

```
.
+-- README.md                   :Description of this repository
+-- LICENSE                     :Repository license
+-- .gitignore                  :Files and directories to be ignored by git
+-- environment.yml             :Conda environment configuration file for Binder
|
+-- raw
|   +-- asv_table.csv           :Source data containing ASV sequences and number of reads
|   +-- taxa_table.csv          :Source data containing taxon matches for each ASV
|   +-- metadata_table.csv      :Source data containing metadata about samples (e.g. collecti
|
+-- src
|   +-- conversion_code.py      :Darwin Core mapping script
|   +-- conversion_code.ipynb   :Darwin Core mapping Jupyter Notebook
|   +-- WoRMS.py                :Functions for querying the World Register of Marine Species
|
+-- processed
|   +-- occurrence.csv          :Occurrence file, generated by conversion_code
|   +-- dna_extension.csv       :DNA Derived Data Extension file, generated by conversion_coo
```

7 Converting ATN netCDF file to Darwin Core

An R Markdown document converted from "atn_satellite_telemetry_netCDF2DwC.ipynb"

Created: 2022-03-23 Updated: 2025-07-21

Credit: Stephen Formel, Mathew Biddle

This notebook walks through downloading an example netCDF file from the an Archive package at NCEI and translating it to a Darwin Core Archive compliant package for easy loading and publishing via the Integrated Publishing Toolkit (IPT). The example file follows a specific specification for ATN satellite trajectory observations as documented here. More information about the ATN netCDF specification can be found in the repository https://github.com/ioos/ioos-atn-data.

This example uses the tidync package to work with netCDF data.

Data used in this notebook are available from NCEI at the following link https://www.ncei.noaa.gov/archive/accession/0282699.

```
#Load libraries

library(tidync)
library(obistools)
library(ncdf4)
library(tidyverse) #includes stringr
```

```
-- Attaching core tidyverse packages ------------------------ tidyverse 2.0.0 --
v dplyr     1.2.1     v readr     2.2.0
v forcats   1.0.1     v stringr   1.6.0
v ggplot2   4.0.3     v tibble    3.3.1
v lubridate 1.9.5     v tidyr     1.3.2
v purrr     1.2.2
-- Conflicts ------------------------------------------ tidyverse_conflicts() --
x dplyr::filter() masks stats::filter()
x dplyr::lag()    masks stats::lag()
i Use the conflicted package (<http://conflicted.r-lib.org/>) to force all conflicts to beco
```

```
library(lubridate)
library(maps)
```

```
Attaching package: 'maps'

The following object is masked from 'package:purrr':

    map
```

```
library(mapdata)
library(here)
```

```
here() starts at /Users/runner/work/bio_data_guide/bio_data_guide
```

7.1 Downloading and preprocessing the source data

See https://www.ncei.noaa.gov/archive/accession/0282699

```
# paths ----

url_base    <- "https://www.ncei.noaa.gov/data/oceans/archive"
url_package <- "/arc0217/0282699/1.1/data/0-data/"
url_file    <- "atn_45866_great-white-shark_trajectory_20090923-20091123.nc"
dir_data    <- here("datasets/atn_satellite_telemetry/data")

url_nc  <- paste0(url_base, url_package, url_file)
file_nc <- file.path(dir_data, "src", url_file)

# stopifnot(dir.exists(dir_data))

if (!file.exists(file_nc))
  download.file(url_nc, file_nc, mode = "wb")
```

7.1.1 Open the netCDF file

Once the file is opened, we print out the details of what the netCDF file contains.

```
atn <- nc_open(file_nc)
atn
```

```
File /Users/runner/work/bio_data_guide/bio_data_guide/datasets/atn_satellite_telemetry/data/s
white-shark_trajectory_20090923-20091123.nc (NC_FORMAT_NETCDF4):

     36 variables (excluding dimension variables):
        string deploy_id[]   (Contiguous storage)
            long_name: id for this deployment. This is typically the tag ptt
            comment: Friendly name given to the tag by the user. If no specific friendly name
            coordinates: time z lon lat
            instrument: instrument_location
            platform: animal
            coverage_content_type: referenceInformation
            _FillValue: -9999
        double time[obs]   (Contiguous storage)
            units: seconds since 1990-01-01 00:00:00Z
            standard_name: time
            axis: T
            _CoordinateAxisType: Time
            calendar: standard
            long_name: Time of the measurement, in seconds since 1990-01-01
            actual_min: 2009-09-23T00:00:00Z
            actual_max: 2009-11-23T05:12:00Z
            ancillary_variables: qartod_time_flag qartod_rollup_flag qartod_speed_flag
            instrument: instrument_location
            platform: animal
            coverage_content_type: coordinate
            _FillValue: NaN
        int z[obs]   (Contiguous storage)
            _FillValue: -9999
            axis: Z
            long_name: depth of measurement
            positive: down
            standard_name: depth
            units: m
            actual_min: 0
            actual_max: 0
            instrument:
            platform: animal
            comment: This variable is synthetically generated to represent the depth of obser
            coverage_content_type: coordinate
```

```
double lat[obs]   (Contiguous storage)
    axis: Y
    _CoordinateAxisType: Lat
    long_name: Latitude portion of location in decimal degrees North
    standard_name: latitude
    units: degrees_north
    valid_max: 90
    valid_min: -90
    actual_min: 23.59
    actual_max: 34.045
    ancillary_variables: qartod_location_flag qartod_rollup_flag qartod_speed_flag er
    instrument: instrument_location
    platform: animal
    coverage_content_type: coordinate
    _FillValue: NaN
double lon[obs]   (Contiguous storage)
    axis: X
    _CoordinateAxisType: Lon
    long_name: Longitude portion of location in decimal degrees East
    standard_name: longitude
    units: degrees_east
    valid_max: 180
    valid_min: -180
    actual_min: -166.18
    actual_max: -118.504
    ancillary_variables: qartod_location_flag qartod_rollup_flag qartod_speed_flag er
    instrument: instrument_location
    platform: animal
    coverage_content_type: coordinate
    _FillValue: NaN
int ptt[obs]   (Chunking: [29])  (Compression: shuffle,level 1)
    _FillValue: -9999
    coordinates: time z lon lat
    long_name: Platform Transmitter Terminal (PTT) id used for Argos transmissions
    comment: PTT id for this deployment. PTT ids may be used on multiple deployments
    coverage_content_type: referenceInformation
    instrument: instrument_location
    platform: animal
string instrument[obs]   (Contiguous storage)
    coordinates: time z lon lat
    comment: Wildlife Computers instrument family. Variable may report manufacturer c
    long_name: Instrument family
    instrument: instrument_location
```

```
            platform: animal
            coverage_content_type: referenceInformation
        string type[obs]   (Contiguous storage)
            coordinates: time z lon lat
            comment: Type of location: Argos, FastGPS or User
            long_name: Type of location information - Argos, GPS satellite or user provided l
            instrument: instrument_location
            platform: animal
            coverage_content_type: referenceInformation
        string location_class[obs]   (Contiguous storage)
            coordinates: time z lon lat
            standard_name: quality_flag
            comment: Quality codes from the ARGOS satellite (in meters): G,3,2,1,0,A,B,Z. See
system.org/manual/3-location/34_location_classes.htm
            long_name: Location Quality Code from ARGOS satellite system
            code_values: G,3,2,1,0,A,B,Z
            code_meanings: estimated error less than 100m and 1+ messages received per satell
            instrument: instrument_location
            platform: animal
            ancillary_variables: lat lon
            coverage_content_type: qualityInformation
        int error_radius[obs]   (Chunking: [29])  (Compression: shuffle,level 1)
            _FillValue: -9999
            coordinates: time z lon lat
            long_name: Error radius
            units: m
            comment: If the position is best represented as a circle, this field gives the ra
            instrument: instrument_location
            platform: animal
            ancillary_variables: lat lon offset offset_orientation
            coverage_content_type: qualityInformation
        int semi_major_axis[obs]   (Chunking: [29])  (Compression: shuffle,level 1)
            _FillValue: -9999
            coordinates: time z lon lat
            long_name: Error - ellipse semi-major axis
            units: m
            comment: If the estimated position error is best expressed as an ellipse, this fi
major elliptical axis (one half of the major axis).
            instrument: instrument_location
            platform: animal
            ancillary_variables: lat lon ellipse_orientation offset offset_orientation
            coverage_content_type: qualityInformation
        int semi_minor_axis[obs]   (Chunking: [29])  (Compression: shuffle,level 1)
```

```
            _FillValue: -9999
            coordinates: time z lon lat
            long_name: Error - ellipse semi-minor axis
            units: m
            comment: If the estimated position error is best expressed as an ellipse, this fi
minor elliptical axis (one half of the minor axis).
            instrument: instrument_location
            platform: animal
            ancillary_variables: lat lon ellipse_orientation offset offset_orientation
            coverage_content_type: qualityInformation
        int ellipse_orientation[obs]   (Chunking: [29])  (Compression: shuffle,level 1)
            _FillValue: -9999
            coordinates: time z lon lat
            long_name: Error - ellipse orientation in degrees clockwise from true north
            units: degrees
            comment: The angle in degrees of the ellipse from true north, proceeding clockwis
            instrument: instrument_location
            platform: animal
            ancillary_variables: lat lon semi_major_axis semi_minor_axis offset offset_orient
            coverage_content_type: qualityInformation
        int offset[obs]   (Chunking: [29])  (Compression: shuffle,level 1)
            _FillValue: -9999
            coordinates: time z lon lat
            long_name: Error - offset in meters to center of error ellipse or circle
            units: m
            comment: This field is non-zero if the circle or ellipse are not centered on the
            instrument: instrument_location
            platform: animal
            ancillary_variables: lat lon error_radius semi_major_axis semi_minor_axis offset_
            coverage_content_type: qualityInformation
        int offset_orientation[obs]   (Chunking: [29])  (Compression: shuffle,level 1)
            _FillValue: -9999
            coordinates: time z lon lat
            long_name: Error - offset orientation angle to ellipse center
            units: degrees
            comment: If the "Offset" field is non-zero, this field is the angle in degrees fr
            instrument: instrument_location
            platform: animal
            ancillary_variables: lat lon error_radius semi_major_axis semi_minor_axis offset
            coverage_content_type: qualityInformation
        double gpe_msd[obs]   (Chunking: [29])  (Compression: shuffle,level 1)
            coordinates: time z lon lat
            comment: Historical. No longer applicable.
```

```
    long_name:
    units:
    instrument: instrument_location
    platform: animal
    coverage_content_type: auxillaryInformation
    _FillValue: NaN
double gpe_u[obs]   (Chunking: [29])  (Compression: shuffle,level 1)
    coordinates: time z lon lat
    comment: Historical. No longer applicable.
    long_name:
    units:
    instrument: instrument_location
    platform: animal
    coverage_content_type: auxillaryInformation
    _FillValue: NaN
int count[obs]   (Chunking: [29])  (Compression: shuffle,level 1)
    _FillValue: -9999
    coordinates: time z lon lat
    comment: Total number of times a particular data item was received, verified, and
    long_name: Count
    units: count
    instrument: instrument_location
    platform: animal
    coverage_content_type: auxillaryInformation
unsigned byte qartod_time_flag[obs]   (Chunking: [29])  (Compression: shuffle,level
    _FillValue: 241
    coordinates: time z lon lat
    standard_name: gross_range_test_quality_flag
    long_name: Time QC test - gross range test
    implementation: https://github.com/ioos/ioos_qc/
    flag_meanings: PASS NOT_EVALUATED SUSPECT FAIL MISSING
    flag_values: 1
     flag_values: 2
     flag_values: 3
     flag_values: 4
     flag_values: 9
    references: https://cdn.ioos.noaa.gov/media/2020/03/QARTOD_TS_Manual_Update2_2003
    coverage_content_type: qualityInformation
unsigned byte qartod_speed_flag[obs]   (Chunking: [29])  (Compression: shuffle,level
    _FillValue: 241
    coordinates: time z lon lat
    standard_name: gross_range_test_quality_flag
    long_name: Speed QC test - gross range test
```

```
    references: https://cdn.ioos.noaa.gov/media/2020/03/QARTOD_TS_Manual_Update2_2003
    implementation: https://github.com/ioos/ioos_qc/
    flag_meanings: PASS NOT_EVALUATED SUSPECT FAIL MISSING
    flag_values: 1
     flag_values: 2
     flag_values: 3
     flag_values: 4
     flag_values: 9
    coverage_content_type: qualityInformation
unsigned byte qartod_location_flag[obs]   (Chunking: [29])  (Compression: shuffle,lev
    _FillValue: 241
    coordinates: time z lon lat
    standard_name: location_test_quality_flag
    long_name: Location QC test - Location test
    implementation: https://github.com/ioos/ioos_qc/
    flag_meanings: PASS NOT_EVALUATED SUSPECT FAIL MISSING
    flag_values: 1
     flag_values: 2
     flag_values: 3
     flag_values: 4
     flag_values: 9
    references: https://cdn.ioos.noaa.gov/media/2020/03/QARTOD_TS_Manual_Update2_2003
    coverage_content_type: qualityInformation
unsigned byte qartod_rollup_flag[obs]   (Chunking: [29])  (Compression: shuffle,level
    _FillValue: 241
    coordinates: time z lon lat
    standard_name: aggregate_quality_flag
    long_name: Aggregate QC value
    implementation: https://github.com/ioos/ioos_qc/
    flag_meanings: PASS NOT_EVALUATED SUSPECT FAIL MISSING
    flag_values: 1
     flag_values: 2
     flag_values: 3
     flag_values: 4
     flag_values: 9
    references: https://cdn.ioos.noaa.gov/media/2020/03/QARTOD_TS_Manual_Update2_2003
    coverage_content_type: qualityInformation
int crs[]   (Contiguous storage)
    epsg_code: EPSG:4326
    grid_mapping_name: latitude_longitude
    inverse_flattening: 298.257223563
    long_name: Coordinate Reference System - http://www.opengis.net/def/crs/EPSG/0/43
    semi_major_axis: 6378137
```

```
    coverage_content_type: referenceInformation
string trajectory[]   (Contiguous storage)
    cf_role: trajectory_id
    long_name: trajectory identifier
int animal_age[]   (Contiguous storage)
    _FillValue: -9999
    units:
    long_name: age of the animal as measured or estimated at deployment
    coverage_content_type: referenceInformation
    animal_age: Not provided
string animal_life_stage[]   (Contiguous storage)
    animal_life_stage: juvenile
    long_name: Lifestage of the animal at time of deployment
    coverage_content_type: referenceInformation
string animal_sex[]   (Contiguous storage)
    animal_sex: male
    long_name: sex of the animal at time of tag deployment
    coverage_content_type: referenceInformation
float animal_weight[]   (Contiguous storage)
    _FillValue: NaN
    units: kg
    long_name: mass of the animal as measured or estimated at deployment
    animal_weight: Not provided
    coverage_content_type: referenceInformation
float animal_length[]   (Contiguous storage)
    _FillValue: NaN
    animal_length_type: total length
    units: cm
    animal_length: 213.0 (cm) total length
    long_name: length of the animal as measured or estimated at deployment
    coverage_content_type: referenceInformation
float animal_length_2[]   (Contiguous storage)
    _FillValue: NaN
    animal_length_2_type: Not provided
    units:
    animal_length_2: Not provided
    long_name: length of the animal as measured or estimated at deployment
    coverage_content_type: referenceInformation
string animal[]   (Contiguous storage)
    rank: Species
    infraorder:
    scientificname: Carcharodon carcharias
    long_name: tagged animal id
```

```
        superdomain: Biota
        order: Lamniformes
        authority: (Linnaeus, 1758)
        kingdom: Animalia
        species: Carcharodon carcharias
        genus: Carcharodon
        megaclass:
        family: Lamnidae
        taxonRankID: 220
        class: Elasmobranchii
        cf_role: trajectory_id
        coverage_content_type: referenceInformation
        subphylum: Vertebrata
        phylum: Chordata
        AphiaID: 105838
        valid_name: Carcharodon carcharias
        infraphylum: Gnathostomata
        subclass: Neoselachii
        suborder:
    string instrument_tag[]   (Contiguous storage)
        manufacturer: Wildlife Computers
        make_model: SPOT5
        serial_number: 07S0230
        long_name: telemetry tag applied to animal
        coverage_content_type: referenceInformation
        calibration_date: Not Provided
    string instrument_location[]   (Contiguous storage)
        manufacturer: Wildlife Computers
        make_model: SPOT5
        serial_number: 07S0230
        long_name: Wildlife Computers SPOT5
        location_type: argos / modeled
        comment: Location
        coverage_content_type: referenceInformation
        calibration_date: Not Provided
    string taxon_name[]   (Contiguous storage)
        standard_name: biological_taxon_name
        long_name: most precise taxonomic classification for the tagged animal
        coverage_content_type: referenceInformation
        source: Froese, R. and D. Pauly. Editors. (2023). FishBase. Carcharodon carcharia
08-16
        url: https://www.marinespecies.org/aphia.php?p=taxdetails&id=105838
    string taxon_lsid[]   (Contiguous storage)
```

```
            standard_name: biological_taxon_lsid
            long_name: Namespaced Taxon Identifier for the tagged animal
            coverage_content_type: referenceInformation
            source: Froese, R. and D. Pauly. Editors. (2023). FishBase. Carcharodon carcharia
08-16
            url: https://www.marinespecies.org/aphia.php?p=taxdetails&id=105838
        string comment[obs]   (Contiguous storage)
            long_name: Comment
            comment: Optional text field
            coordinates: time z lon lat
            instrument: instrument_location
            platform: animal
            coverage_content_type: auxillaryInformation

     1 dimensions:
        obs  Size:29 (no dimvar)

    89 global attributes:
        date_created: 2023-08-16T20:00:00Z
        featureType: trajectory
        cdm_data_type: Trajectory
        Conventions: CF-1.10, ACDD-1.3, IOOS-1.2
        argos_program_number: 2414
        creator_email: chris.lowe@csulb.edu
        id: 5f0668a86321be13bc7ef628
        tag_type: SPOT5
        source: Service Argos
        acknowledgement: NOAA IOOS, Axiom Data Science, Navy ONR, NOAA NMFS, Wildlife Compute
        creator_name: Chris G. Lowe
        creator_url:
        geospatial_lat_units: degrees_north
        geospatial_lon_units: degrees_east
        infoUrl: https://portal.atn.ioos.us/#metadata/6e2ba85c-2f61-4bc5-
8c2b-34d6734155ed/project
        institution: California State University Long Beach
        keywords: EARTH SCIENCE > AGRICULTURE > ANIMAL SCIENCE > ANIMAL ECOLOGY AND BEHAVIOR
U.S. FEDERAL AGENCIES > DOC > NOAA > IOOS, PROVIDERS > COMMERCIAL > Axiom Data Science
        license: These data may be used and redistributed for free, but are not intended for
        metadata_link:
        naming_authority: com.wildlifecomputers
        platform_category: animal
        platform: fish
        platform_vocabulary: https://vocab.nerc.ac.uk/collection/L06/current/
```

```
        processing_level: NetCDF file created from position data obtained from Wildlife Compu
        project: Project White Shark: Juvenile Satellite Biotelemetry, 2001-
2020
        publisher_email: atndata@ioos.us
        publisher_institution: US Integrated Ocean Observing System Office
        publisher_name: US Integrated Ocean Observing System (IOOS) Animal Telemetry Network
        publisher_url: https://atn.ioos.us
        publisher_country: USA
        standard_name_vocabulary: CF-v78
        vendor: Wildlife Computers
        geospatial_lat_min: 23.59
        geospatial_lat_max: 34.045
        geospatial_lon_min: -166.18
        geospatial_lon_max: -118.504
        geospatial_bbox: POLYGON ((-118.504 23.59, -118.504 34.045, -166.18 34.045, -
166.18 23.59, -118.504 23.59))
        geospatial_bounds: POLYGON ((-166.18 23.59, -118.581 34.038, -118.53 34.045, -
118.504 33.989, -118.534 33.972, -119.75 33.517, -166.18 23.59))
        geospatial_bounds_crs: EPSG:4326
        time_coverage_start: 2009-09-23T00:00:00Z
        time_coverage_end: 2009-11-23T05:12:00Z
        time_coverage_duration: P61DT5H12M0S
        time_coverage_resolution: P2DT2H39M43S
        date_issued: 2023-08-16T20:00:00Z
        date_modified: 2023-08-16T20:00:00Z
        history: 2023-08-07T20:24:04Z - Created by the IOOS ATN DAC from the Wildlife Compute
        summary: Wildlife Computers SPOT5 tag (ptt id 45866) deployed on a great white shark
09-23 to 2009-11-23
        title: Great white shark (Carcharodon carcharias) location data from a satellite tele
09-23 to 2009-11-23, deployment id 5f0668a86321be13bc7ef628
        uuid: ff554ebf-bf4b-5a82-8a90-9c0ceb799d96
        platform_name: Carcharodon carcharias
        platform_id: 105838
        vendor_id: 5f0668a86321be13bc7ef628
        sea_name: North Pacific Ocean
        arbitrary_keywords: ATN, Animal Telemetry Network, IOOS, Integrated Ocean Observing S
        contributor_role_vocabulary: https://vocab.nerc.ac.uk/collection/G04/current/
        creator_role_vocabulary: https://vocab.nerc.ac.uk/collection/G04/current/
        creator_sector_vocabulary: https://mmisw.org/ont/ioos/sector
        creator_type: person
        date_metadata_modified: 20230816
        instrument: Satellite telemetry tag
        instrument_vocabulary:
```

```
        keywords_vocabulary: GCMD Science Keywords v15.1
        ncei_template_version: NCEI_NetCDF_Trajectory_Template_v2.0
        product_version:
        program: IOOS Animal Telemetry Network
        publisher_type: institution
        references:
        animal_common_name: great white shark
        animal_id: 09_13
        animal_scientific_name: Carcharodon carcharias
        deployment_id: 5f0668a86321be13bc7ef628
        deployment_start_datetime: 2009-09-23T00:00:00Z
        deployment_end_datetime: 2009-11-23T00:00:00Z
        wmo_platform_code:
        comment: 09_13-45866
        ptt_id: 45866
        deployment_start_lat: 34.03
        deployment_start_lon: -118.56
        contributor_name: Thomas Farrugia
        contributor_email: tjfarrugia@alaska.edu
        contributor_role: collaborator
        contributor_institution: California State University Long Beach
        contributor_url:
        creator_role: principalInvestigator
        creator_sector: academic
        creator_country: USA
        creator_institution: California State University Long Beach
        creator_institution_url: https://www.csulb.edu/shark-lab
        citation: Lowe, Chris G.; Farrugia, Thomas. (2023) great white shark (Carcharodon ca
09-23 to 2009-11-23, deployment id 5f0668a86321be13bc7ef628. [Dataset]. US Integrated Ocean
```

7.1.2 Collect all the metadata from the netCDF file.

This gathers not only the global attributes, but the variable level attributes as well. As you can see in the **variable** column the term `NC_GLOBAL` refers to global attributes.

```
metadata <- ncmeta::nc_atts(file_nc)
metadata
```

```
# A tibble: 381 x 4
      id name                 variable  value
   <int> <chr>                <chr>     <named list>
 1     0 long_name            deploy_id <chr [1]>
```

```
 2     1 comment               deploy_id <chr [1]>
 3     2 coordinates           deploy_id <chr [1]>
 4     3 instrument            deploy_id <chr [1]>
 5     4 platform              deploy_id <chr [1]>
 6     5 coverage_content_type deploy_id <chr [1]>
 7     6 _FillValue            deploy_id <dbl [1]>
 8     0 units                 time      <chr [1]>
 9     1 standard_name         time      <chr [1]>
10     2 axis                  time      <chr [1]>
# i 371 more rows
```

7.1.3 Store the data as a tibble

Collect the data dimensioned by `time` from the netCDF file as a tibble. Then, print the first ten rows.

```
atn <- tidync(file_nc)

atn_tbl <- atn %>% hyper_tibble(force=TRUE)

head(atn_tbl, n=4)
```

```
# A tibble: 4 x 23
       time     z   lat   lon   ptt instrument type  location_class error_radius
      <dbl> <int> <dbl> <dbl> <int> <chr>      <chr> <chr>                 <int>
1 622512000     0  34.0 -119. 45866 SPOT       User  nan                      NA
2 622708920     0  23.6 -166. 45866 SPOT       Argos A                        NA
3 622724940     0  34.0 -119. 45866 SPOT       Argos 1                        NA
4 622725060     0  34.0 -119. 45866 SPOT       Argos 0                        NA
# i 14 more variables: semi_major_axis <int>, semi_minor_axis <int>,
#   ellipse_orientation <int>, offset <int>, offset_orientation <int>,
#   gpe_msd <dbl>, gpe_u <dbl>, count <int>, qartod_time_flag <int>,
#   qartod_speed_flag <int>, qartod_location_flag <int>,
#   qartod_rollup_flag <int>, comment <chr>, obs <chr>
```

7.1.4 Dealing with time

Notice the data in the **time** column aren't formatted as times. We need to read the metadata associated with the time variable to understand what the units are. Below, we print a tibble of all the attributes from the **time** variable.

Notice the *units* attribute and it's value of `seconds since 1990-01-01 00:00:00Z`. We need to use that information to convert the time variable to something useful that `ggplot` can handle.

```
time_attrs <- metadata %>% dplyr::filter(variable == "time")
time_attrs
```

```
# A tibble: 13 x 4
      id name                  variable value
   <int> <chr>                 <chr>    <named list>
 1     0 units                 time     <chr [1]>
 2     1 standard_name         time     <chr [1]>
 3     2 axis                  time     <chr [1]>
 4     3 _CoordinateAxisType   time     <chr [1]>
 5     4 calendar              time     <chr [1]>
 6     5 long_name             time     <chr [1]>
 7     6 actual_min            time     <chr [1]>
 8     7 actual_max            time     <chr [1]>
 9     8 ancillary_variables   time     <chr [1]>
10     9 instrument            time     <chr [1]>
11    10 platform              time     <chr [1]>
12    11 coverage_content_type time     <chr [1]>
13    12 _FillValue            time     <dbl [1]>
```

So, we grab the value from the `units` attribute, split the string to collect the date information, and apply that to a time conversion function `as.POSIXct`.

```
#library(stringr) - loaded with tidyverse
# grab origin date from time variable units attribute
tunit <- time_attrs %>% dplyr::filter(name == "units")
lunit <- str_split(tunit$value,' ')[[1]]
atn_tbl$time <- as.POSIXct(atn_tbl$time, origin=lunit[3], tz="GMT")

str(atn_tbl)
```

```
tibble [29 x 23] (S3: tbl_df/tbl/data.frame)
 $ time                : POSIXct[1:29], format: "2009-09-23 00:00:00" "2009-
09-25 06:42:00" ...
 $ z                   : int [1:29] 0 0 0 0 0 0 0 0 0 0 ...
 $ lat                 : num [1:29] 34 23.6 34 34 34 ...
 $ lon                 : num [1:29] -119 -166 -119 -119 -119 ...
```

```
$ ptt                 : int [1:29] 45866 45866 45866 45866 45866 45866 45866 45866 45866 458
$ instrument          : chr [1:29] "SPOT" "SPOT" "SPOT" "SPOT" ...
$ type                : chr [1:29] "User" "Argos" "Argos" "Argos" ...
$ location_class      : chr [1:29] "nan" "A" "1" "0" ...
$ error_radius        : int [1:29] NA NA NA NA NA NA NA NA NA NA ...
$ semi_major_axis     : int [1:29] NA NA NA NA NA NA NA NA NA NA ...
$ semi_minor_axis     : int [1:29] NA NA NA NA NA NA NA NA NA NA ...
$ ellipse_orientation : int [1:29] NA NA NA NA NA NA NA NA NA NA ...
$ offset              : int [1:29] NA NA NA NA NA NA NA NA NA NA ...
$ offset_orientation  : int [1:29] NA NA NA NA NA NA NA NA NA NA ...
$ gpe_msd             : num [1:29] NaN NaN NaN NaN NaN NaN NaN NaN NaN NaN ...
$ gpe_u               : num [1:29] NaN NaN NaN NaN NaN NaN NaN NaN NaN NaN ...
$ count               : int [1:29] NA NA NA NA NA NA NA NA NA NA ...
$ qartod_time_flag    : int [1:29] 1 1 1 1 1 1 1 1 1 1 ...
$ qartod_speed_flag   : int [1:29] 2 4 4 4 1 1 1 1 1 1 ...
$ qartod_location_flag: int [1:29] 1 1 1 1 1 1 1 1 1 1 ...
$ qartod_rollup_flag  : int [1:29] 1 4 4 4 1 1 1 1 1 1 ...
$ comment             : chr [1:29] "" "" "" "" ...
$ obs                 : chr [1:29] "1" "2" "3" "4" ...
```

7.2 Converting to Darwin Core

Now let's work through converting this netCDF file to Darwin Core. Following the guidance published at https://github.com/tdwg/dwc-for-biologging/wiki/Data-guidelines and https://github.com/ocean-tracking-network/biologging_standardization/tree/master/examples/braun-blueshark/darwincore-example

7.2.1 Occurrence Core

Below is the mapping table from DarwinCore to the netCDF file.

DarwinCore Term	Status	netCDF source
occurrenceStatus	Required	hardcoded to `present`.
basisOfRecord	Required	data contained in the `type` variable where `type` of `User` = `HumanObservation` and `Argos` = `MachineObservation`.

DarwinCore Term	Status	netCDF source
occurrenceID	Required	`eventDate`, plus data contained in `z` variable, plus `animal_common_name` global attribute.
organismID	Required	`platform_id` global attribute plus the `animal_common_name` global attribute.
eventDate	Required	data contained in `time` variable. Converted to ISO8601.
decimalLatitude & decimalLongitude	Required	data in `lat` and `lon` variable, respectively.
geodeticDatum	Required	attribute `epsg_code` in the `crs` variable.
scientificName	Required	data from the variable `taxon_name`.
scientificNameID		data from the variable `taxon_lsid`.
eventID	Strongly recommended	`animal_common_name` global attribute plus the `eventDate`.
samplingProtocol	Strongly recommended	hardcoded to `satellite telemetry`
kingdom	Strongly recommended	`kingdom` attribute in the `animal` variable.
taxonRank	Strongly recommended	`rank` attribute in the `animal` variable.
coordinateUncertaintyInMeters	Share if available	maximum value of the data from the variables `error_radius`, `semi_major_axis`, and `offset`.
lifeStage	Share if available	data from the variable `animal_life_stage`.
sex	Share if available	data from the variable `animal_sex`.
associatedReferences	Share if available	NCEI accession url.

Now start working through the crosswalk. A few thoughts about some of the functions we use:

1. `case_when` is a function from dplyr that is essentially a 'vectorized' ifelse function. The take-home is that it plays nice with other `tidyverse` functions, like `mutate` and IMO is a bit more readable than a complex ifelse statement.

2. `rename` is another nice dplyr function for renaming columns. It workes well following `mutate` because you can see the mutation applied to a column and then the column renamed, rather than a complex creation of a new column and dropping of the old column.

```
# Defined to grab attributes in subsequent code
nc <- nc_open(file_nc)

occurrencedf <- atn_tbl %>%
    select( # Select desired columns

        time,
        lat,
        lon,
        type,
        location_class,
        qartod_time_flag,
        qartod_speed_flag,
        qartod_location_flag,
        qartod_rollup_flag

          ) %>%
    mutate( # add and mutate columns.

        type = case_when(type == 'User' ~ 'HumanObservation',
                         type == 'Argos' ~ 'MachineObservation'),

        time = format(time, '%Y-%m-%dT%H:%M:%SZ'),

        kingdom = metadata %>% dplyr::filter(variable == "animal" & name == "kingdom") %>% pu

        taxonRank = metadata %>% dplyr::filter(variable == "animal" & name == "rank") %>% pul

        occurrenceStatus = "present",

        sex = ncvar_get( nc, 'animal_sex'),

        lifeStage = ncvar_get( nc, 'animal_life_stage'),

        scientificName = ncvar_get( nc, 'taxon_name'),

        scientificNameID = ncvar_get( nc, "taxon_lsid")
```

```
        ) %>%

    rename(  # rename columns to Darwin Core terms

        basisOfRecord = type,
        eventDate = time,
        decimalLatitude = lat,
        decimalLongitude = lon) %>%

    arrange(eventDate) #arrange by increasing date

# minimumDepthInMeters = z,
occurrencedf$minimumDepthInMeters = atn_tbl$z

# maximumDepthInMeters = z,
occurrencedf$maximumDepthInMeters = atn_tbl$z

# organismID - {platformID}_{common_name}
common_name_tbl <- metadata %>% dplyr::filter(variable == "NC_GLOBAL") %>% dplyr::filter(name
common_name <- chartr(" ", "_", common_name_tbl$value)
platform_id_tbl <- metadata %>% dplyr::filter(variable == "NC_GLOBAL") %>% dplyr::filter(name
platform_id <- chartr(" ", "_", platform_id_tbl$value)
occurrencedf$organismID <- paste(platform_id , common_name, sep = "_")

# occurrenceID - {eventDate}_{depth}_{common_name}
occurrencedf$occurrenceID <- sub(" ", "_", paste("ioos_atn", occurrencedf$eventDate, atn_tbl$

# geodeticDatum
gd_tbl <- metadata %>% dplyr::filter(variable == "crs") %>% dplyr::filter(name == "epsg_code"
occurrencedf$geodeticDatum <- paste(gd_tbl$value)

# eventID
#eventID - {common_name}_{dateTime}
cname = metadata %>% dplyr::filter(variable == "NC_GLOBAL") %>% dplyr::filter(name == "animal
occurrencedf$eventID <- sub(" ", "_", paste0(cname$value, "_", occurrencedf$eventDate))

# associatedReferences
occurrencedf$associatedReferences <- paste0("https://www.ncei.noaa.gov/archive/accession/",st
```

```
str(occurrencedf)
```

```
tibble [29 x 23] (S3: tbl_df/tbl/data.frame)
```

```
 $ eventDate           : chr [1:29] "2009-09-23T00:00:00Z" "2009-09-25T06:42:00Z" "2009-
09-25T11:09:00Z" "2009-09-25T11:11:00Z" ...
 $ decimalLatitude     : num [1:29] 34 23.6 34 34 34 ...
 $ decimalLongitude    : num [1:29] -119 -166 -119 -119 -119 ...
 $ basisOfRecord       : chr [1:29] "HumanObservation" "MachineObservation" "MachineObservati
 $ location_class      : chr [1:29] "nan" "A" "1" "0" ...
 $ qartod_time_flag    : int [1:29] 1 1 1 1 1 1 1 1 1 1 ...
 $ qartod_speed_flag   : int [1:29] 2 4 4 4 1 1 1 1 1 1 ...
 $ qartod_location_flag: int [1:29] 1 1 1 1 1 1 1 1 1 1 ...
 $ qartod_rollup_flag  : int [1:29] 1 4 4 4 1 1 1 1 1 1 ...
 $ kingdom             : chr [1:29] "Animalia" "Animalia" "Animalia" "Animalia" ...
 $ taxonRank           : chr [1:29] "Species" "Species" "Species" "Species" ...
 $ occurrenceStatus    : chr [1:29] "present" "present" "present" "present" ...
 $ sex                 : chr [1:29] "male" "male" "male" "male" ...
 $ lifeStage           : chr [1:29] "juvenile" "juvenile" "juvenile" "juvenile" ...
 $ scientificName      : chr [1:29] "Carcharodon carcharias" "Carcharodon carcharias" "Carcha
 $ scientificNameID    : chr [1:29] "urn:lsid:marinespecies.org:taxname:105838" "urn:lsid:mar
 $ minimumDepthInMeters: int [1:29] 0 0 0 0 0 0 0 0 0 0 ...
 $ maximumDepthInMeters: int [1:29] 0 0 0 0 0 0 0 0 0 0 ...
 $ organismID          : chr [1:29] "105838_great_white_shark" "105838_great_white_shark" "10
 $ occurrenceID        : chr [1:29] "ioos_atn_2009-09-23T00:00:00Z_0_great_white_shark" "ioos
09-25T06:42:00Z_0_great_white_shark" "ioos_atn_2009-09-25T11:09:00Z_0_great_white_shark" "ioo
09-25T11:11:00Z_0_great_white_shark" ...
 $ geodeticDatum       : chr [1:29] "EPSG:4326" "EPSG:4326" "EPSG:4326" "EPSG:4326" ...
 $ eventID             : chr [1:29] "great_white shark_2009-09-23T00:00:00Z" "great_white sha
09-25T06:42:00Z" "great_white shark_2009-09-25T11:09:00Z" "great_white shark_2009-
09-25T11:11:00Z" ...
 $ associatedReferences: chr [1:29] "https://www.ncei.noaa.gov/archive/accession/0282699" "ht
```

7.2.1.1 Add coordinateUncertaintyInMeters AND filter by location_class

When we add `coordinateUncertaintyInMeters` we are also filtering out where `location_class` == `A`,`B`,or `Z`.

In these data we also have additional information about the Location Quality Code from ARGOS satellite system. Below are the codes and those meanings.

code_values	code meanings
G	estimated error less than 100m and 1+ messages received per satellite pass
3	estimated error less than 250m and 4+ messages received per satellite pass

code_values	code meanings
2	estimated error between 250m and 500m and 4+ messages per satellite pass
1	estimated error between 500m and 1500m and 4+ messages per satellite pass
0	estimated error greater than 1500m and 4+ messages received per satellite pass
A	no least squares estimated error or unbounded kalman filter estimated error and 3 messages received per satellite pass
B	no least squares estimated error or unbounded kalman filter estimated error and 1 or 2 messages received per satellite pass
Z	invalid location (available for Service Plus or Auxilliary Location Processing)

Since codes `A`, `B`, and `Z` are essentially bad values, I propose that we filter those out.

Also, create a mapping table for `coordinateUncertaintyInMeters` that corresponds to the ARGOS code maximum error as shown in the table below:

code	coordinateUncertaintyInMeters
G	100
3	250
2	500
1	1500
0	10000 (ref)

Below we create a lookup table for the `location_class` values we agree are good, which contains the `coordinateUncertaintyInMeters` for the appropriate location class. When we merge that table with our raw data, the observations that don't match the location_classes in our lookup table will not be transfered over (ie. they will be filtered out).

```
occurrencedf <- occurrencedf %>%
    filter(location_class %in% c('nan','G','3','2','1','0')) %>%
    mutate(  # This returns NA for any other values than those defined below
        coordinateUncertaintyInMeters = case_when(location_class == 'nan' ~ 0,
                                                  location_class == 'G' ~ 200,
                                                  location_class == '3' ~ 250,
                                                  location_class == '2' ~ 500,
```

```
                                                    location_class == '1' ~ 1500,
                                                    location_class == '0' ~ 10000) # <https
          ) %>%
    arrange(eventDate) # arrange by increasing date


occurrencedf
```

```
# A tibble: 19 x 24
   eventDate       decimalLatitude decimalLongitude basisOfRecord location_class
   <chr>                     <dbl>            <dbl> <chr>         <chr>
 1 2009-09-23T00:~            34.0            -119. HumanObserva~ nan
 2 2009-09-25T11:~            34.0            -119. MachineObser~ 1
 3 2009-09-25T11:~            34.0            -119. MachineObser~ 0
 4 2009-09-27T17:~            34.0            -119. MachineObser~ 1
 5 2009-10-08T20:~            34.0            -119. MachineObser~ 2
 6 2009-10-15T11:~            34.0            -119. MachineObser~ 0
 7 2009-10-17T06:~            34.0            -119. MachineObser~ 0
 8 2009-10-17T09:~            34.0            -119. MachineObser~ 2
 9 2009-10-17T10:~            34.0            -119. MachineObser~ 3
10 2009-10-18T08:~            34.0            -119. MachineObser~ 1
11 2009-10-18T10:~            34.0            -119. MachineObser~ 2
12 2009-10-18T11:~            34.0            -119. MachineObser~ 0
13 2009-10-23T23:~            34.0            -119. MachineObser~ 2
14 2009-10-24T00:~            34.0            -119. MachineObser~ 0
15 2009-10-26T10:~            34.0            -119. MachineObser~ 3
16 2009-10-27T16:~            34.0            -119. MachineObser~ 1
17 2009-10-27T16:~            34.0            -119. MachineObser~ 2
18 2009-10-29T11:~            34.0            -119. MachineObser~ 2
19 2009-10-31T21:~            34.0            -119. MachineObser~ 0
# i 19 more variables: qartod_time_flag <int>, qartod_speed_flag <int>,
#   qartod_location_flag <int>, qartod_rollup_flag <int>, kingdom <chr>,
#   taxonRank <chr>, occurrenceStatus <chr>, sex <chr>, lifeStage <chr>,
#   scientificName <chr>, scientificNameID <chr>, minimumDepthInMeters <int>,
#   maximumDepthInMeters <int>, organismID <chr>, occurrenceID <chr>,
#   geodeticDatum <chr>, eventID <chr>, associatedReferences <chr>,
#   coordinateUncertaintyInMeters <dbl>
```

Notice how we went from 29 rows down to 19 rows by only selecting specific the location_class.

7.2.2 Create a dataGeneralizations column to describe how many duplicates were found for each deprecation series

Add a `dataGeneralizations` column containing a string like 'first of # records' to indicate there are more records in the raw dataset to be discovered by the super-curious.

The dataGeneralizations string is compiled by counting the number of consecutive duplicates and inserting that into a standard string. That string is "first of [n] records" which will make more sense once we've filtered down to keep the first occurrence of the hour.

The next step below this, we filter out only the first observation of the hour.

```
# sort by date
occurrencedf <- occurrencedf %>% arrange(eventDate)

occurrencedf <- occurrencedf %>%
    mutate(eventDateHrs = format(as.POSIXct(eventDate, format="%Y-%m-%dT%H:%M:%SZ"),"%Y-%m-%d
           ) %>%
    add_count(eventDateHrs) %>%
    mutate(dataGeneralizations = case_when(n == 1 ~ "",
                                           TRUE ~ paste("first of ", n ,"records")
                                           )
           ) %>%
    select(-n)

occurrencedf
```

```
# A tibble: 19 x 26
   eventDate       decimalLatitude decimalLongitude basisOfRecord location_class
   <chr>                     <dbl>            <dbl> <chr>         <chr>
 1 2009-09-23T00:~            34.0            -119. HumanObserva~ nan
 2 2009-09-25T11:~            34.0            -119. MachineObser~ 1
 3 2009-09-25T11:~            34.0            -119. MachineObser~ 0
 4 2009-09-27T17:~            34.0            -119. MachineObser~ 1
 5 2009-10-08T20:~            34.0            -119. MachineObser~ 2
 6 2009-10-15T11:~            34.0            -119. MachineObser~ 0
 7 2009-10-17T06:~            34.0            -119. MachineObser~ 0
 8 2009-10-17T09:~            34.0            -119. MachineObser~ 2
 9 2009-10-17T10:~            34.0            -119. MachineObser~ 3
10 2009-10-18T08:~            34.0            -119. MachineObser~ 1
11 2009-10-18T10:~            34.0            -119. MachineObser~ 2
12 2009-10-18T11:~            34.0            -119. MachineObser~ 0
13 2009-10-23T23:~            34.0            -119. MachineObser~ 2
```

```
14 2009-10-24T00:~            34.0            -119. MachineObser~ 0
15 2009-10-26T10:~            34.0            -119. MachineObser~ 3
16 2009-10-27T16:~            34.0            -119. MachineObser~ 1
17 2009-10-27T16:~            34.0            -119. MachineObser~ 2
18 2009-10-29T11:~            34.0            -119. MachineObser~ 2
19 2009-10-31T21:~            34.0            -119. MachineObser~ 0
# i 21 more variables: qartod_time_flag <int>, qartod_speed_flag <int>,
#   qartod_location_flag <int>, qartod_rollup_flag <int>, kingdom <chr>,
#   taxonRank <chr>, occurrenceStatus <chr>, sex <chr>, lifeStage <chr>,
#   scientificName <chr>, scientificNameID <chr>, minimumDepthInMeters <int>,
#   maximumDepthInMeters <int>, organismID <chr>, occurrenceID <chr>,
#   geodeticDatum <chr>, eventID <chr>, associatedReferences <chr>,
#   coordinateUncertaintyInMeters <dbl>, eventDateHrs <chr>, ...
```

7.2.2.0.1 Decimate occurrences down to the first detection/location per hour

Here we've done the decimation in Python: https://gist.github.com/MathewBiddle/d434ac2b538b2728aa80c6a7945f94be

Essentially we build a new colum that is the date plus the two digit hour. Then we find where that column has duplicates and keep the first entry.

In R, we do something slightly different as we only keep the distinct (ie. unique) rows and if there are duplicates, pick the first row of the duplicate.

```
# sort by date
occurrencedf_dec <- occurrencedf %>% arrange(eventDate)

# filter table to only unique date + hour and pick the first row.
occurrencedf_dec <- distinct(occurrencedf_dec,eventDateHrs,.keep_all = TRUE) %>%
    select(-eventDateHrs)

occurrencedf_dec
```

```
# A tibble: 17 x 25
   eventDate       decimalLatitude decimalLongitude basisOfRecord location_class
   <chr>                     <dbl>            <dbl> <chr>         <chr>
 1 2009-09-23T00:~            34.0            -119. HumanObserva~ nan
 2 2009-09-25T11:~            34.0            -119. MachineObser~ 1
 3 2009-09-27T17:~            34.0            -119. MachineObser~ 1
 4 2009-10-08T20:~            34.0            -119. MachineObser~ 2
 5 2009-10-15T11:~            34.0            -119. MachineObser~ 0
 6 2009-10-17T06:~            34.0            -119. MachineObser~ 0
```

```
 7 2009-10-17T09:~            34.0            -119. MachineObser~ 2
 8 2009-10-17T10:~            34.0            -119. MachineObser~ 3
 9 2009-10-18T08:~            34.0            -119. MachineObser~ 1
10 2009-10-18T10:~            34.0            -119. MachineObser~ 2
11 2009-10-18T11:~            34.0            -119. MachineObser~ 0
12 2009-10-23T23:~            34.0            -119. MachineObser~ 2
13 2009-10-24T00:~            34.0            -119. MachineObser~ 0
14 2009-10-26T10:~            34.0            -119. MachineObser~ 3
15 2009-10-27T16:~            34.0            -119. MachineObser~ 1
16 2009-10-29T11:~            34.0            -119. MachineObser~ 2
17 2009-10-31T21:~            34.0            -119. MachineObser~ 0
# i 20 more variables: qartod_time_flag <int>, qartod_speed_flag <int>,
#   qartod_location_flag <int>, qartod_rollup_flag <int>, kingdom <chr>,
#   taxonRank <chr>, occurrenceStatus <chr>, sex <chr>, lifeStage <chr>,
#   scientificName <chr>, scientificNameID <chr>, minimumDepthInMeters <int>,
#   maximumDepthInMeters <int>, organismID <chr>, occurrenceID <chr>,
#   geodeticDatum <chr>, eventID <chr>, associatedReferences <chr>,
#   coordinateUncertaintyInMeters <dbl>, dataGeneralizations <chr>
```

Notice that we have gone from 19 rows to 17 rows. Removing rows observed on `2009-09-25T11:11:00Z` and `2009-10-27T16:22:00Z` as they were the second points within that specifc hour.

7.2.2.0.2 Filter on QARTOD flags?

We also have QARTOD flags and they are as follows:

value	meaning
1	PASS
2	NOT_EVALUATED
3	SUSPECT
4	FAIL
9	MISSING

The QARTOD tests are:

variable	long_name
qartod_time_flag	Time QC test - gross range test
qartod_speed_flag	Speed QC test - gross range test
qartod_location_flag	Location QC test - Location test

variable	long_name
qartod_rollup_flag	Aggregate QC value

I'm not sure what to do here. My preference would be to include all rows where `qartod_rollup_flag` == 1 and drop the rest. But I'm open to suggestions.

```
# perform filter but don't save it.
filter(occurrencedf_dec, qartod_rollup_flag == 1)
```

```
# A tibble: 16 x 25
   eventDate       decimalLatitude decimalLongitude basisOfRecord location_class
   <chr>                     <dbl>            <dbl> <chr>         <chr>
 1 2009-09-23T00:~            34.0            -119. HumanObserva~ nan
 2 2009-09-27T17:~            34.0            -119. MachineObser~ 1
 3 2009-10-08T20:~            34.0            -119. MachineObser~ 2
 4 2009-10-15T11:~            34.0            -119. MachineObser~ 0
 5 2009-10-17T06:~            34.0            -119. MachineObser~ 0
 6 2009-10-17T09:~            34.0            -119. MachineObser~ 2
 7 2009-10-17T10:~            34.0            -119. MachineObser~ 3
 8 2009-10-18T08:~            34.0            -119. MachineObser~ 1
 9 2009-10-18T10:~            34.0            -119. MachineObser~ 2
10 2009-10-18T11:~            34.0            -119. MachineObser~ 0
11 2009-10-23T23:~            34.0            -119. MachineObser~ 2
12 2009-10-24T00:~            34.0            -119. MachineObser~ 0
13 2009-10-26T10:~            34.0            -119. MachineObser~ 3
14 2009-10-27T16:~            34.0            -119. MachineObser~ 1
15 2009-10-29T11:~            34.0            -119. MachineObser~ 2
16 2009-10-31T21:~            34.0            -119. MachineObser~ 0
# i 20 more variables: qartod_time_flag <int>, qartod_speed_flag <int>,
#   qartod_location_flag <int>, qartod_rollup_flag <int>, kingdom <chr>,
#   taxonRank <chr>, occurrenceStatus <chr>, sex <chr>, lifeStage <chr>,
#   scientificName <chr>, scientificNameID <chr>, minimumDepthInMeters <int>,
#   maximumDepthInMeters <int>, organismID <chr>, occurrenceID <chr>,
#   geodeticDatum <chr>, eventID <chr>, associatedReferences <chr>,
#   coordinateUncertaintyInMeters <dbl>, dataGeneralizations <chr>
```

Drop the quality flag columns to align with DarwinCore standard.

```
occurrencedf_dec <- occurrencedf_dec %>%
    select(
        -c(location_class,
           qartod_time_flag,
           qartod_speed_flag,
           qartod_location_flag,
           qartod_rollup_flag
           ))

names(occurrencedf_dec)
```

```
 [1] "eventDate"                     "decimalLatitude"
 [3] "decimalLongitude"              "basisOfRecord"
 [5] "kingdom"                       "taxonRank"
 [7] "occurrenceStatus"              "sex"
 [9] "lifeStage"                     "scientificName"
[11] "scientificNameID"              "minimumDepthInMeters"
[13] "maximumDepthInMeters"          "organismID"
[15] "occurrenceID"                  "geodeticDatum"
[17] "eventID"                       "associatedReferences"
[19] "coordinateUncertaintyInMeters" "dataGeneralizations"
```

7.2.2.0.3 Write decimated occurrence file as csv

```
tag_id <- metadata %>% dplyr::filter(variable == "NC_GLOBAL" & name == "ptt_id")

occurrencedf_dec_csv <- glue::glue("{dir_data}/dwc/atn_{tag_id$value}_occurrence.csv")

write.csv(occurrencedf_dec, file=occurrencedf_dec_csv, row.names=FALSE, fileEncoding="UTF-8"
```

7.2.2.1 Measurement or Fact

Since we do have any additional observations, we can create a measurement or fact file to include those data. Might be worthwhile to include tag/device metadata, some of the animal measurements, and the detachment information. Each term should have a definition URI.

The measurementOrFact file will only contain information referencing the `basisOfRecord` = `HumanObservation` as these observations were made when the animal was directly tagged, in person (ie. when `basisOfRecord` == `HumanObservation`).

DarwinCore Term	Status	netCDF
organismID		The `platform_id` global attribute plus the `animal_common_name` global attribute.
occurrenceID	Required	`eventDate`, plus data contained in `z` variable, plus `animal_common_name` global attribute.
measurementType	Required	`long_name` attribute of the `animal_weight`, `animal_length`, `animal_length_2` variables.
measurementValue	Required	The data from the `animal_weight`, `animal_length`, `animal_length_2` variables.
eventID	Strongly Recommended	`animal_common_name` global attribute plus the `eventDate`.
measurementUnit	Strongly Recommended	`unit` attribute of the `animal_weight`, `animal_length`, `animal_length_2` variables.
measurementMethod	Strongly Recommended	`animal_weight`, `animal_length`, `animal_length_2` attributes of their respective variables.
measurementTypeID	Strongly Recommended	mapping table somewhere?
measurementMethodID	Strongly Recommended	mapping table somewhere?

DarwinCore Term	Status	netCDF
measurementUnitID	Strongly Recommended	mapping table somewhere?
measurementAccuracy	Share if available	
measurementDeterminedDate	Share if available	
measurementDeterminedBy	Share if available	
measurementRemarks	Share if available	
measurementValueID	Share if available	

7.2.2.1.1 Extracting variables for Extended Measurement Or Fact (eMOF)

Here there are two approaches to transforming a variable to the eMOF Darwin Core extension. The goal is to collapse the measurement name, value, unit, related identifiers and remarks into a generalized long format that can be linked to occurrences and events. For more info see:

1. The OBIS manual
2. The Marine Biological Data Mobilization Workshop 2023 (SF:Not sure if it's cool to reference the workshop like this)

The first several lines of the below code show an example of pulling out the variable attributes and individually mapping them to the eMOF terms. However, this can be done more efficiently (although less readable) via this chunk of code:

```
# Supply vector of variable names
c("animal_length",
  "animal_length_2",
  "animal_weight") %>%

      # Create a named list of the variable attributes and convert it into a data frame, for
      purrr::map_df(function(x) {
        Olist(measurementValue = ncvar_get( nc, x),
              measurementType = ncatt_get( nc, x)$long_name,
              measurementUnit = ncatt_get( nc, x)$units,
              measurementMethod = ncatt_get( nc, x)[[paste0(x,'_type')]])
        })
```

```
# # Measurement or Fact extension
# # Need to find the occurrence where basisOfRecord == HumanObservation, then pull the organi

emof_data <- #var_names %>%
    #filter(str_starts(name, pattern = "animal_[lw]e")) %>% #example using regex to parse nar
```

```
    #    pull(name) %>%

    # Example using vector of variables
    c("animal_length",
      "animal_length_2",
      "animal_weight") %>%
    purrr::map_df(function(x) {
        list(measurementValue = ncvar_get( nc, x),
             measurementType = ncatt_get( nc, x)$long_name,
             measurementUnit = ncatt_get( nc, x)$units,
             measurementMethod = ncatt_get( nc, x)[[paste0(x,'_type')]])
    }) %>%

    filter(measurementValue != "NaN")


emofdf <- occurrencedf %>%
    filter(basisOfRecord == 'HumanObservation') %>%
    select(organismID, eventID, occurrenceID) %>%
    cbind(emof_data)

str(emofdf)
```

```
'data.frame':   1 obs. of  7 variables:
 $ organismID       : chr "105838_great_white_shark"
 $ eventID          : chr "great_white shark_2009-09-23T00:00:00Z"
 $ occurrenceID     : chr "ioos_atn_2009-09-23T00:00:00Z_0_great_white_shark"
 $ measurementValue : num 213
 $ measurementType  : chr "length of the animal as measured or estimated at deployment"
 $ measurementUnit  : chr "cm"
 $ measurementMethod: chr "total length"
```

7.2.2.1.2 Write emof file as csv

```
tag_id <- metadata %>% dplyr::filter(variable == "NC_GLOBAL") %>% dplyr::filter(name == "ptt_

emof_csv <- glue::glue("{dir_data}/dwc/atn_{tag_id$value}_emof.csv")

write.csv(emofdf, file=emof_csv, row.names=FALSE, fileEncoding="UTF-8", quote=TRUE, na="")
```

7.3 Print session info

```
sessionInfo()
```

```
R version 4.4.1 (2024-06-14)
Platform: aarch64-apple-darwin20
Running under: macOS 26.6.2

Matrix products: default
BLAS:   /Library/Frameworks/R.framework/Versions/4.4-arm64/Resources/lib/libRblas.0.dylib
LAPACK: /Library/Frameworks/R.framework/Versions/4.4-arm64/Resources/lib/libRlapack.dylib;  L

locale:
[1] en_US.UTF-8/en_US.UTF-8/en_US.UTF-8/C/en_US.UTF-8/en_US.UTF-8

time zone: UTC
tzcode source: internal

attached base packages:
[1] stats     graphics  grDevices utils     datasets  methods   base

other attached packages:
 [1] here_1.0.2      mapdata_2.3.1   maps_3.4.3      lubridate_1.9.5
 [5] forcats_1.0.1   stringr_1.6.0   dplyr_1.2.1     purrr_1.2.2
 [9] readr_2.2.0     tidyr_1.3.2     tibble_3.3.1    ggplot2_4.0.3
[13] tidyverse_2.0.0 ncdf4_1.24      obistools_0.1.0 tidync_0.4.0

loaded via a namespace (and not attached):
 [1] utf8_1.2.6          rappdirs_0.3.4      generics_0.1.4      xml2_1.6.0
 [5] stringi_1.8.9       hms_1.1.4           digest_0.6.39       magrittr_2.0.5
 [9] evaluate_1.0.5      grid_4.4.1          timechange_0.4.0    RColorBrewer_1.1-
3
[13] fastmap_1.2.0       rprojroot_2.1.1     jsonlite_2.0.0      ncmeta_0.5.0
[17] crosstalk_1.2.2     scales_1.4.0        cli_3.6.6           RNetCDF_2.11-2
[21] rlang_1.3.0         withr_3.0.3         yaml_2.3.12         otel_0.2.0
[25] tools_4.4.1         tzdb_0.5.0          vctrs_0.7.3         R6_2.6.1
[29] lifecycle_1.0.5     leaflet_2.2.3       htmlwidgets_1.6.4   pkgconfig_2.0.3
[33] pillar_1.11.1       gtable_0.3.6        glue_1.8.1          xfun_0.62
[37] tidyselect_1.2.1    data.tree_1.2.0     knitr_1.52          farver_2.1.2
[41] htmltools_0.5.9     rmarkdown_2.32      compiler_4.4.1      S7_0.2.2
```

A FAQ

Frequently Asked Questions

1. **Q.** What data structure does OBIS recommend?

   A. The OBIS-ENV Darwin Core Archive Data Structure. OBIS manual

2. **Q.** What is a controlled vocabulary, why use them?

   A. There are a number of controlled vocabularies that are used to describe parameters commonly used in specific research domains. Using terms defined in a controlled vocabulary allows for greater interoperability of data sets within the domain, and ideally between domains by ensuring that variables that are the same can be identified.

3. **Q.** What controlled vocabularies does OBIS rely on?

   A. WoRMS, NERC Vocabulary Server inlcuding:

   - Device categories using the SeaDataNet device categories
   - Device make/model using the SeaVoX Device Catalogue
   - Platform categories using SeaVoX Platform Categories
   - Platform instances using the ICES Platform Codes
   - Unit of measure

4. **Q.** How can I find out which common measurementTypes are used in measurement or facts tables in existing OBIS datasets?

   A. See Measurement Types in OBIS

5. **Q.** What is an ontology?

   A. An ontology is a classification system for establishing a hierarchically related set of concepts. Concepts are often terms from controlled vocabularies. Ontologies can include all of the following, but are not required to include them.

   - Classes (general things, types of things)
   - Instances (individual things)
   - Relationships among things

- Properties of things
- Functions, processes, constraints, and rules relating to things

6. **Q.** What is ERDDAP?

   A. ERDDAP is a data server. It provides 'easier access to scientific data' by providing a consistent interface that aggregates many disparate data sources. It does this by providing translation services between many common file types for gridded arrarys ('net CDF' files) and tabular data (spreadsheets). Data access is also made easier because it unifies different types of data servers and access protocols.

7. **Q.** What metadata profile does OBIS use?

   A. OBIS uses the GBIF EML profile (version 1.1)

8. **Q.** Can Darwin Core be used in the Semantic Web/Resrouce Description Framework?

   A. See Darwin Core Resource Description Framework Guide and Lessons learned from adapting the Darwin Core vocabulary standard for use in RDF

B Tools

Below are some of the tools and packages used in workflows. R and Python package "Type" is BIO for packages specifically for biological applications, and GEN for generic packages.

B.1 R

Package	Type	Description
bdveRse	BIO	A family of R packages for biodiversity data.
ecocomDP	BIO	Work with the Ecological Community Data Design Pattern. 'ecocomDP' is a flexible data model for harmonizing ecological community surveys, in a research question agnostic format, from source data published across repositories, and with methods that keep the derived data up-to-date as the underlying sources change.
EDIorg/EMLasseblyline	BIO	For scientists and data managers to create high quality EML metadata for dataset publication.
finch	BIO	Parse Darwin Core Files
iobis/obistools	BIO	Tools for data enhancement and quality control.
robis	BIO	R client for the OBIS API
ropensci/EML	BIO	Provides support for the serializing and parsing of all low-level EML concepts

Package	Type	Description
taxize	BIO	Interacts with a suite of web 'APIs' for taxonomic tasks, such as getting database specific taxonomic identifiers, verifying species names, getting taxonomic hierarchies, fetching downstream and upstream taxonomic names, getting taxonomic synonyms, converting scientific to common names and vice versa, and more.
worrms	BIO	Client for World Register of Marine Species. Includes functions for each of the API methods, including searching for names by name, date and common names, searching using external identifiers, fetching synonyms, as well as fetching taxonomic children and taxonomic classification.
Hmisc	GEN	Contains many functions useful for data analysis, high-level graphics, utility operations, functions for computing sample size and power, simulation, importing and annotating datasets, imputing missing values, advanced table making, variable clustering, character string manipulation, conversion of R objects to LaTeX and html code, and recoding variables. Particularly check out the describe() function.

Package	Type	Description
lubridate	GEN	Functions to work with date-times and time-spans: fast and user friendly parsing of date-time data, extraction and updating of components of a date-time (years, months, days, hours, minutes, and seconds), algebraic manipulation on date-time and time-span objects.
stringr	GEN	Simple, Consistent Wrappers for Common String Operations
tidyverse	GEN	The 'tidyverse' is a set of packages that work in harmony because they share common data representations and 'API' design. This package is designed to make it easy to install and load multiple 'tidyverse' packages in a single step.
uuid	GEN	Tools for generating and handling of UUIDs (Universally Unique Identifiers).

B.2 Python

Package	Type	Description
metapype	BIO	A lightweight Python 3 library for generating EML metadata

Package	Type	Description
python-dwca-reader	BIO	A simple Python package to read and parse Darwin Core Archive (DwC-A) files, as produced by the GBIF website, the IPT and many other biodiversity informatics tools.
pyworms	BIO	Python client for the World Register of Marine Species (WoRMS) REST service.
numpy	GEN	NumPy (Numerical Python) is an open source Python library that's used in almost every field of science and engineering. It's the universal standard for working with numerical data in Python, and it's at the core of the scientific Python and PyData ecosystems.
pandas	GEN	pandas is a fast, powerful, flexible and easy to use open source data analysis and manipulation tool, built on top of the Python programming language. Super helpful when manipulating tabular data!
uuid	GEN	This module provides immutable UUID objects (class UUID) and the functions uuid1(), uuid3(), uuid4(), uuid5() for generating version 1, 3, 4, and 5 UUIDs as specified in RFC 4122. Built in – part of the Python standard library.

Package	Type	Description
obis-qc	BIO	Quality checks on occurrence records. Checks `occurrenceStatus`, `individualCount`, `eventDate`, `decimalLatitude`, `decimalLongitude`, `coordinateUncertaintyInMeters`, `minimumDepthInMeters`, `maximumDepthInMeters`, `scientificName`, `scientificNameID`. Checks from Vandepitte et al. flags not implemented: 3, 9, 14, 15, 16, 10, 17, 21-30.
biopython	BIO	Biopython is a set of freely available tools for biological computation written in Python by an international team of developers. It is a distributed collaborative effort to develop Python libraries and applications which address the needs of current and future work in bioinformatics.

B.3 Google Sheets

Package	Description
Google Sheet DarwinCore Archive Assistant add-on	Google Sheet add-on which assists the creation of Darwin Core Archives (DwCA) and publising to Zenodo. DwCA's are stored into user's Google Drive and can be downloaded for upload into IPT installations or other software which is able to read DwC-archives.

B.4 Validators

Name	Description
Darwin Core Archive Validator	This validator verifies the structural integrity of a Darwin Core Archive. It does not check the data values, such as coordinates, dates or scientific names.
GBIF DATA VALIDATOR	The GBIF data validator is a service that allows anyone with a GBIF-relevant dataset to receive a report on the syntactical correctness and the validity of the content contained within the dataset.
LifeWatch Belgium	Through this interactive section of the LifeWatch.be portal users can upload their own data using a standard data format, and choose from several web services, models and applications to process the data.

C Extras

Below is some more in-depth information into specific areas associated with standardizing your data to Darwin Core and uploading it through the IPT.

C.1 Ecological Metadata Language (EML)

The Ecological Metadata Language (EML) is a community developed and maintained metadata standard that is typically associated with ecological-, and earth and environmental data. The purpose of EML is to provide the ecological community with an extensible, flexible, metadata standard used in data analysis and archiving, which will allow automated machine processing, searching and retrieval. EML has been around since 2003, and can be considered a "dialect" or specification to XML to describe tables and other data objects. The XML Schema provides a framework for the metadata, with defined "rules" on how to organize the metadata without any stipulations (another way to put it, *XML is the language that defines the rules that govern the EML syntax*). The XML Schema defines the structure of some information in a document (e.g. elements and attributes names and relationships), but does not provide any specific details the information included within. An EML document or file (eml.xml) is used to provide detailed description of metadata related to data objects, including tables (and other data objects), their columns, typing etc, and how data tables are linked or grouped. EML is widely used for datasets about ecosystem level observations, and can be used to detail data table information to a high granularity, which allows data users to arrange data tables in any way they need to. EML is particularly useful for wide data tables as table level details are entirely contained within the metadata document, meaning that there is not necessarily a need for external definitions such as a code list. However, if you have a long table arrangement, like the Darwin Core Archive (DwC-A), you can define the allowable values for the column in the metadata as well.

EML is excellent at describing the details of a column of data so that the data values in the tables can be read into analysis systems or an analysis environment using the metadata, or even into a relational database. EML allows for tables to be easily reusable, and read into workflows, translated or reformatted. A drawback to EML is that, compared to the ISO standard, EML is a community standard, adopting a more 'bottom-up' approach. This is contrary to the ISO standard, which are internationally agreed upon standards by experts ('top-down'). However, at the time of EML development in the early 2000's there was a gap in metadata options to describe ecological data tables, with ISO standards typically being

more applicable to geographic data. EML can cover almost anything and is particularly good at tabular data. But at the same time, due to the self-contained nature, there can be little control from outside lists, which means that the description is left to the EML constructor (data provider/manager) and consequently, individual datasets can look quite different from each other, even when they contain similar measurements. As such, it will be important to document best practices and clear mapping of fields between different metadata schemas (e.g. cross-walks between ISO.xml and EML.xml). As of version 2.2, EML can link to external ontologies, and there is capacity for annotation with external terms (e.g. through their URIs). Code lists and external dictionaries can help as they sometimes contain additional information that might not fit into EML (e.g. protocols, or code lists stored in ontologies). Having these external code lists and exporting them as EML snippets could go a long way in reducing that heterogeneity, because the constructors can then select measurements from lists when developing EML documents.

EML is implemented as a series of XML document types (modules) that can be used in an extensible manner to document ecological data. Each EML module is designed to describe one logical part of the total metadata that should be included with any ecological dataset. The architecture of EML was designed to serve the needs of the ecological community, and has benefitted from previous work in other related metadata standards. Using this format can facilitate future growth of the metadata language, and EML supports an active developer community (see e.g. NCEAS EML GitHub). EML adopts much of its syntax from the other metadata standards that have evolved from the expertise of groups in other disciplines. Whenever possible, EML adopted entire trees of information in order to facilitate conversion of EML documents into other metadata languages. The GBIF IPT is a tool used to create a single eml.xml file format inside the DwC-A data package. However, the IPT does not use any of the EML's built-in table description modules, and perhaps primarily uses one EML module (resource module) for high-level metadata.


However, it is important to know how both OBIS and GBIF use EML, as often a higher granularity of the metadata can be found in the original data tables. An example of this is spatial coverage. The IPT only allows for either a bounding box to be documented (populating North, South, East, and West coordinates), or a single polygon. The EML document however would be able to capture multiple polygons worth of spatial coverage (i.e. a polygon for each transect surveyed). This more detailed information however is often captured in the data (in an OBIS record). Additionally, not all fields that can be populated in an EML document can be translated to the IPT, or harvested by OBIS and GBIF. The GBIF IPT only produces a select number of fields or attributes available in EML.

Important: When reading the EML section in the OBIS manual, you'll notice that it reads that OBIS uses the GBIF EML profile (version 1.1). However, the current EML version is 2.2.0, as per EcoInformatics. This does not mean that these versions are not compatible, rather, it means that the GBIF IPT currently uses a subset of available EML 2.2.0 fields and attributes, the subset of which they have versioned 1.1.


If you are interested in creating an EML metadata file, it is possible to upload those into the IPT. There are R packages that can help in developing an EML.xml file. These packages are e.g. EML, emld or EMLassemblyline.

C.2 Example using GitHub to resolve errors

1. Dataset sent to OBIS-USA via email.
2. OBIS-USA uploaded to IPT.
3. Once the data were uploaded, the IPT identified there was an issue with the `occurrenceID` field. The issue was then presented and discussed in a GitHub ticket:



4. The data manager uploaded the raw data and code to GitHub through the pull request



below. This included a fix for the `occurrenceID` issue.

5. The OBIS node manager was notified of the availability of a revised dataset by pointing directly to the appropriate commit in GitHub:



6. The OBIS node manager downloaded the data from the commit above and uploaded

them to the IPT.

7. The IPT returned a summary of the dataset including that 434 records had invalid `scientificNameID` records in the occurrence file.
8. After some data sleuthing, the data manager noticed that the code accidentally removed trailing zeros from `scientificNameID` that ended in `0`:

```
#taxonid needs to not have trailin
taxons = df[['taxonID']].astype('s
t=taxons['taxonID'].convert_dtypes
t=t.str.strip('.0')
t
df['taxonID']=t
df.head()
```

9. So, the data manager updated the code to resolve the issue and generate a new occurrence file.





```
#OK, rename and then add new columns
#rename columns as necessary

df.rename(columns={'Depth_[m]': 'minimumDepthInMeters',
                   'Life_Stage': 'lifeStage',
                   'Type': 'samplingProtocol',
                   'Longitude_[decimal_degrees_east]': 'decimalLongitude',
                   'Latitude_[decimal _degrees_north]': 'decimallatitude',
                   'Accepted_Organism_Identification': 'scientificName',
                   'APHIA_ID': 'taxonID' }, inplace=True)

# add new parameters

df['scientificNameID'] = 'urn:lsid:marinespecies.org:taxname:'+df['taxonID'].astype(str)

df['identificationReferences'] = 'WoRMS'
df['basisOfRecord'] = 'HumanObservation' #nospace!
df['occurenceStatus'] = 'present'

df.head()
```

1. Here is fixing the `scientificNameID` generation:

```
#finally!
#nope it's scientificNameID that needs this
sciids = df[['scientificNameID']].astype('string', errors='ignore')
s = sciids['scientificNameID'].convert_dtypes()
s=s.str.strip('.0')
df['scientificNameID']=s



df.head()
```

2. Here is removing the problematic code:


```
#finally!
#nope it's scientificNameID that needs this

# mmb - Think this was not necessary.
# sciids = df[['scientificNameID']].astype('string', errors='ignore')
# s = sciids['scientificNameID'].convert_dtypes()
# s=s.str.strip('.0')
# df['scientificNameID']=s
# df.head()
```

10. The revised occurrence file was then resubmitted to the OBIS node manager by pointing them at the appropriate commit record:



11. The OBIS node manager downloaded the data from the commit above and uploaded them to the IPT.
12. The IPT and OBIS landing page now indicated that no more issues with these data are


OBIS
Zooplankton Species Distribution and Abundance Data, Arctic Marine Biodiversity Observing Network (AMBON) Chukchi Sea research cruise, August 2017
STATISTICS
DISTRIBUTION
RECORDS
DATA QUALITY
COMPOSITION
DATA PROVIDERS
TOP TAXA

present:

References

Allaire, JJ, Yihui Xie, Christophe Dervieux, et al. 2026. *Rmarkdown: Dynamic Documents for r*. https://github.com/rstudio/rmarkdown.

Barbier, Edward B. 2017. "Marine Ecosystem Services." In *Current Biology*, vol. 27. Cell Press. https://doi.org/10.1016/j.cub.2017.03.020.

Benson, Abigail, Cassandra M. Brooks, Gabrielle Canonico, et al. 2018. "Integrated Observations and Informatics Improve Understanding of Changing Marine Ecosystems." In *Frontiers in Marine Science*, vol. 5. Frontiers Media S.A. https://doi.org/10.3389/fmars.2018.00428.

Benson, Abigail, Diana LaScala-Gruenewald, Robert McGuinn, et al. 2021. *Biological Observation Data Standardization - a Primer for Data Managers*. ESIP. https://doi.org/10.6084/m9.figshare.16806712.v1.

Benson, Abigail, Tylar Murray, Gabrielle Canonico, et al. 2021. "Data Management and Interactive Visualizations for the Evolving Marine Biodiversity Observation Network." *Oceanography*, ahead of print. https://doi.org/10.5670/oceanog.2021.220.

Borer, Elizabeth T., Eric W. Seabloom, Matthew B. Jones, and Mark Schildhauer. 2009. "Some Simple Guidelines for Effective Data Management." *Bulletin of the Ecological Society of America* 90 (April). https://doi.org/10.1890/0012-9623-90.2.205.

Canonico, Gabrielle, Pier Luigi Buttigieg, Enrique Montes, et al. 2019. "Global Observational Needs and Resources for Marine Biodiversity." In *Frontiers in Marine Science*, vol. 6. Frontiers Media S.A. https://doi.org/10.3389/fmars.2019.00367.

Crystal-Ornelas, Robert, Charuleka Varadharajan, Ben Bond-Lamberty, et al. 2021. "A Guide to Using GitHub for Developing and Versioning Data Standards and Reporting Formats." *Earth and Space Science*, July, e2021EA001797. https://doi.org/10.1029/2021EA001797.

Davies, Neil, John Deck, Eric C Kansa, et al. 2021. "Internet of Samples (iSamples): Toward an Interdisciplinary Cyberinfrastructure for Material Samples." *GigaScience* 10: 1–5. https://doi.org/10.1093/gigascience/giab028.

Djurhuus, Anni, Collin J. Closek, Ryan P. Kelly, et al. 2020. "Environmental DNA Reveals Seasonal Shifts and Potential Interactions in a Marine Community." *Nature Communications* 11 (December): 1–9. https://doi.org/10.1038/s41467-019-14105-1.

Duffy, J. Emmett, Linda A. Amaral-Zettler, Daphne G. Fautin, et al. 2013. "Envisioning a Marine Biodiversity Observation Network." *BioScience* 63 (May): 350–61. https://doi.org/10.1525/bio.2013.63.5.8.

Fornwall, M, R Gisiner, S E Simmons, et al. 2012. *Expanding Biological Data Standards Development Processes for US IOOS: Visual Line Transect Observing Community for Mammal, Bird, and Turtle Data*. IOOS. https://www.researchgate.net/publication/255681522.

Hardisty, Alex R., William K. Michener, Donat Agosti, et al. 2019. "The Bari Manifesto: An Interoperability Framework for Essential Biodiversity Variables." *Ecological Informatics* 49 (January): 22–31. https://doi.org/10.1016/j.ecoinf.2018.11.003.

Heberling, J Mason, Joseph T Miller, Daniel Noesgaard, Scott B Weingart C, Dmitry Schigel, and Douglas E Soltis. 2021. "Data Integration Enables Global Biodiversity Synthesis." *Proceedings of the National Academy of Sciences of the United States of America*, ahead of print. https://doi.org/10.1073/pnas.2018093118/-/DCSupplemental.

Jonathan A. Hare, Mark W. Nelson, Wendy E. Morrison. n.d. "A Vulnerability Assessment of Fish and Invertebrates to Climate Change on the Northeast u.s. Continental Shelf." *PLoS ONE* 11 (2): e0146756. https://doi.org/10.1371/journal.pone.0146756.

Jones, Matthew B., Mark P. Schildhauer, O. J. Reichman, and Shawn Bowers. 2006. "The New Bioinformatics: Integrating Ecological Data from the Gene to the Biosphere." In *Annual Review of Ecology, Evolution, and Systematics*, vol. 37. https://doi.org/10.1146/annurev.ecolsys.37.091305.110031.

Kavanaugh, Maria T., Matthew J. Oliver, Francisco P. Chavez, Ricardo M. Letelier, Frank E. Muller-Karger, and Scott C. Doney. 2016. "Seascapes as a New Vernacular for Pelagic Ocean Monitoring, Management and Conservation." *ICES Journal of Marine Science* 73 (July): 1839–50. https://doi.org/10.1093/icesjms/fsw086.

Kot, Connie Y., Ei Fujioka, Lucie J. Hazen, Benjamin D. Best, Andrew J. Read, and Patrick N. Halpin. 2010. "Spatio-Temporal Gap Analysis of OBIS-SEAMAP Project Data: Assessment and Way Forward." *PLoS ONE* 5 (September): 12990. https://doi.org/10.1371/journal.pone.0012990.

Lab, Malin Pinksy. n.d. "OceanAdapt." In *GitHub*. https://oceanadapt.rutgers.edu/.

Lamprecht, Anna-Lena, Leyla Garcia, Mateusz Kuzak, et al. 2019. "Towards FAIR Principles

for Research Software." *Data Science*, 1–23. https://doi.org/10.3233/DS-190026.

Maria Dornelas, Brian McGill, Nicholas J. Gotelli. 2014. "Assemblage Time Series Reveal Biodiversity Change but Not Systematic Loss." *Science* 344 (6181): 296–99. https://doi.org/10.1126/science.1248484.

McKenna, Megan F., Simone Baumann-Pickering, Annebelle C. M. Kok, et al. 2021. "Advancing the Interpretation of Shallow Water Marine Soundscapes." *Frontiers in Marine Science* 0 (September): 1426. https://doi.org/10.3389/FMARS.2021.719258.

Miloslavich, Patricia, Nicholas J. Bax, Samantha E. Simmons, et al. 2018. "Essential Ocean Variables for Global Sustained Observations of Biodiversity and Ecosystem Changes." *Global Change Biology* 24 (June): 2416–33. https://doi.org/10.1111/gcb.14108.

Montes, Enrique, Anni Djurhuus, Frank E. Muller-Karger, Daniel Otis, Christopher R. Kelble, and Maria T. Kavanaugh. 2020. "Dynamic Satellite Seascapes as a Biogeographic Framework for Understanding Phytoplankton Assemblages in the Florida Keys National Marine Sanctuary, United States." *Frontiers in Marine Science* 7 (July): 575. https://doi.org/10.3389/fmars.2020.00575.

Moustahfid, Hassan, and Philip Goldstein. 2014. *IOOS Biological Data Services Enrollment Procedures*.

Moustahfid, Hassan, Jim Potemra, Philip Goldstein, Roy Mendelssohn, and Annette Desrochers. 2011. *Making United States Integrated Ocean Observing System (u.s. IOOS) Inclusive of Marine Biological Resources*. https://www.researchgate.net/publication/254013004.

Muller-Karger, Frank E., Erin Hestir, Christiana Ade, et al. 2018. "Satellite Sensor Requirements for Monitoring Essential Biodiversity Variables of Coastal Ecosystems." *Ecological Applications* 28 (April): 749–60. https://doi.org/10.1002/eap.1682.

Muller-Karger, Frank E., Patricia Miloslavich, Nicholas J. Bax, et al. 2018. "Advancing Marine Biological Observations and Data Requirements of the Complementary Essential Ocean Variables (EOVs) and Essential Biodiversity Variables (EBVs) Frameworks." In *Frontiers in Marine Science*, vol. 5. Frontiers Media S.A. https://doi.org/10.3389/fmars.2018.00211.

Neeley, Aimee, Stace E. Beaulieu, Chris Proctor, et al. 2021. *Standards and Practices for Reporting Plankton and Other Particle Observations from Images*. https://doi.org/10.1575/1912/27377.

O'Brien, Margaret, Colin A. Smith, Eric R. Sokol, et al. 2021. "ecocomDP: A Flexible Data Design Pattern for Ecological Community Survey Data." *Ecological Informatics* 64

(September): 101374. https://doi.org/10.1016/J.ECOINF.2021.101374.

Pooter, Daphnis De, Ward Appeltans, Nicolas Bailly, et al. 2017. "Toward a New Data Standard for Combined Marine Biological and Environmental Datasets - Expanding OBIS Beyond Species Occurrences." *Biodiversity Data Journal* 5 (January): 10989. https://doi.org/10.3897/BDJ.5.e10989.

Provoost, Pieter. n.d. "Iobis/Ebsa." In *GitHub*. https://github.com/iobis/ebsa.

R Core Team. 2024. *R: A Language and Environment for Statistical Computing*. R Foundation for Statistical Computing. https://www.R-project.org/.

Rücknagel, J., P. Vierkant, R. Ulrich, et al. 2015. *Metadata Schema for the Description of Research Data Repositories. Version 3.0*. https://doi.org/10.2312/re3.008.

Rule, Adam, Amanda Birmingham, Cristal Zuniga, et al. 2019. "Ten Simple Rules for Writing and Sharing Computational Analyses in Jupyter Notebooks." *PLOS Computational Biology* 15 (July): e1007007. https://doi.org/10.1371/JOURNAL.PCBI.1007007.

Santora, Jarrod A., Elliott L. Hazen, Isaac D. Schroeder, Steven J. Bograd, Keith M. Sakuma, and John C. Field. 2017. "Impacts of Ocean Climate Variability on Biodiversity of Pelagic Forage Species in an Upwelling Ecosystem." *Marine Ecology Progress Series* 580 (September): 205–20. https://doi.org/10.3354/meps12278.

Schmid, Moritz S, Dominic Daprano, Kyler M Jacobson, et al. 2021. *A Convolutional Neural Network Based High-Throughput Image Classification Pipeline - Code and Documentation to Process Plankton Underwater Imagery Using Local HPC Infrastructure and NSF's XSEDE*. Zenodo. https://doi.org/10.5281/ZENODO.4641158.

Taylor, Gordon T., Frank E. Muller-Karger, Robert C. Thunell, et al. 2012. "Ecosystem Responses in the Southern Caribbean Sea to Global Climate Change." *Proceedings of the National Academy of Sciences of the United States of America* 109 (November): 19315–20. https://doi.org/10.1073/pnas.1207514109.

Tittensor, Derek P, Camilo Mora, Walter Jetz, et al. 2010. "Global Patterns and Predictors of Marine Biodiversity Across Taxa." *Nature* 466 (7310): 1098.

Warren, R., J. Price, E. Graham, N. Forstenhaeusler, and J. VanDerWal. 2018. "The Projected Effect on Insects, Vertebrates, and Plants of Limiting Global Warming to 1.5°c Rather Than 2°c." *Science* 360 (May): 791–95. https://doi.org/10.1126/science.aar3646.

Wieczorek, John, David Bloom, Robert Guralnick, et al. 2012. "Darwin Core: An Evolving Community-Developed Biodiversity Data Standard." *PLoS ONE* 7 (January): 29715.

https://doi.org/10.1371/journal.pone.0029715.

Wilkinson, Mark D., Michel Dumontier, IJsbrand Jan Aalbersberg, et al. 2016. "The FAIR Guiding Principles for Scientific Data Management and Stewardship." *Scientific Data* 3 (March): 1–9. https://doi.org/10.1038/sdata.2016.18.

Xie, Yihui. 2014. "Knitr: A Comprehensive Tool for Reproducible Research in R." In *Implementing Reproducible Computational Research*, edited by Victoria Stodden, Friedrich Leisch, and Roger D. Peng. Chapman; Hall/CRC.

Xie, Yihui. 2015b. *Dynamic Documents with R and Knitr*. 2nd ed. Chapman; Hall/CRC. http://yihui.name/knitr/.

Xie, Yihui. 2015a. *Dynamic Documents with R and Knitr*. 2nd ed. Chapman; Hall/CRC. https://yihui.org/knitr/.

Xie, Yihui. 2016. *Bookdown: Authoring Books and Technical Documents with R Markdown*. Chapman; Hall/CRC. https://pkg.yihui.org/bookdown/.

Xie, Yihui. 2026a. *Bookdown: Authoring Books and Technical Documents with r Markdown*. https://github.com/rstudio/bookdown.

Xie, Yihui. 2026b. *Knitr: A General-Purpose Package for Dynamic Report Generation in r*. https://yihui.org/knitr/.

Xie, Yihui, J. J. Allaire, and Garrett Grolemund. 2018. *R Markdown: The Definitive Guide*. Chapman; Hall/CRC. https://pkg.yihui.org/rmarkdown-book/.

Xie, Yihui, Christophe Dervieux, and Emily Riederer. 2020. *R Markdown Cookbook*. Chapman; Hall/CRC. https://pkg.yihui.org/rmarkdown-cookbook/.