

Water Well for Commercial Operation	Top	Bottom
sandy clay	0	3
dark gray	3	6
sand	6	25
brown clay	25	55
sand & gravel w/rocks	55	65
brown clay	65	108
gray clay	108	113
fine 10 slot sand	113	135
10-12 slot	135	151
15-20 slot	151	165
Total Depth		165
Casing: 5" PVC from 0' to 159'		
3" STAINLESS STL SCREEN from 159' to 163'		
Screen: 4' of 3" diameter 15 slot		
Grout: 20% BENTONITE from 0 to 159.		
Grout: MUSCATINE #0 from 159 to 163.		
Water from sand at 65' to 163'.		
Static level 36' below casing top which is 1' above GL		
Pumping level ' when pumping at 60 gpm for 1 hour		
Permanent pump installed at 80'		
on May 31, 2008, with a capacity of 33 gpm		
Remarks: Driller's Estimated Well Yield 60 gpm		
Owner Address: 8158 2700 N Ave Walnut, IL		
Address of well: 105?? 2550 N Ave		
Walnut, IL		
Location source: Location from permit		
Image viewing help: New users please read this.		

Permit Date: April 30, 2008

Permit #: 011-019

COMPANY Jet Hall/Lutes H2o Well Drlg.

FARM Woodley, Craig

DATE DRILLED May 1, 2008

NO.

ELEVATION

COUNTY NO. 23282

LOCATION SW SW SE


LATITUDE 41.512373

LONGITUDE -89.655221

COUNTY Bureau

API 120112328200

26 - 18N - 7E



[GET FILE](#)

IL State Water Survey Document