

# Building Documentation and Diagrams

## Table of Contents

|                                            |   |
|--------------------------------------------|---|
| What you can build .....                   | 1 |
| Option A: Local tools .....                | 1 |
| Option B: Docker (no local installs) ..... | 1 |
| Cleaning generated files .....             | 2 |
| Notes .....                                | 2 |

This guide explains how to generate the architecture diagrams and PDF documents for the WebUp project, either with local tooling or using Docker.

## What you can build

- PlantUML diagrams → `docs/images/*.png`
- AsciiDoc → PDF for:
- `index.adoc`, `theming.adoc`, `deployment.adoc`, `quick-reference.adoc`, `learning.adoc`

## Option A: Local tools

Install:

- PlantUML and Graphviz (`dot`)
- AsciiDoctor PDF (`gem install asciidoctor-pdf`)

Then run from the project root:

- `make diagrams` → renders all `docs/diagrams/*.puml` to `docs/images/.png`
- `make pdfs` → builds PDFs for all docs (excludes `docs/README.adoc`)
- `make docs` → both diagrams and PDFs

## Option B: Docker (no local installs)

Requires Docker. From the project root:

- `make docker-diagrams` → renders diagrams using `plantuml/plantuml`
- `make docker-pdfs` → builds PDFs using `asciidoctor/docker-asciidoctor`

# Cleaning generated files

- `make clean-diagrams` → removes generated `docs/images/*.png`
- `make clean-pdfs` → removes `docs/*.pdf`
- `make clean` → both

## Notes

- The docs include `:imagesdir:` declarations where needed. If adding new docs, consider setting `:imagesdir: images` at the top to ensure image paths resolve in both HTML and PDF.
- If your PlantUML version complains about unsupported elements, stick to basic elements (rectangle, note, cloud) as used here.
- PDF rendering supports tables of contents and font icons by default; customize flags in the Makefile if needed.
- To validate locally without deploying, use the Makefile targets: + `make validate-html` – POST each HTML file to W3C Nu validator (remote). + `make validate-css` – Sends CSS to W3C Jigsaw service. + `make validate-all` – Runs both.
- If the HTML validator rate-limits or shows a challenge page, wait and retry or validate pages individually in a browser.