DESTILADORA DEL VALLE DE TEQUILA S.A. DE C.V.

SAFETY DATA SHEET

in accordance with (OFFICIAL MEXICAN STANDARD NOM-018-STPS-2015)
Date of preparation 20.08.2025

TEQUILA 40% Alc. Vol.

TACO TUESDAY

Section 1. Identification of the substance or mixture and of the company or undertaking

Identification of the substance
Name: TEQUILA 40% v/v
Use of the substance or preparation: Human consumption.

Identification of the company or enterprise

Company: Destiladora Del Valle de Tequila S.A. de C.V. Calle Carretera Internacional No. 102, Colonia Santa Cruz de los Espinos
C.P. 46403, Tequila, Jalisco – Mexico

Emergency telephone number: Emergency Transport System for the Chemical Industry (SETIQ) – Mexico 01 800-00-214-00

Restrictions on Use: Pictograms on label in accordance with Official Mexican Standard, NOM-142-SSA1/SCFI-2014- Alcoholic beverages - Health specifications - Health and commercial labeling. Prohibition of consumption for: Minors under 18 years of age, pregnant women, and driving under the influence of alcohol.

Section 2. Hazard Identification.

Hazards	SAC Classification	Hazard Statement
Physical	Flammable liquids, category 3.	H226 Flammable liquid and vapor.
Health	May cause serious eye irritation, category 2A. Causes skin irritation, category 2. May damage fertility or the unborn child, category 1A and 1B.	H319 Causes serious eye irritation. H315 Causes skin irritation. H360 May damage fertility or the unborn child.
Environmental	Not available	Not available

Elements of SAC labels Pictogram

Word of caution: Danger

Safety advice

General:	Not available
Prevention:	(H226) P210 Keep away from heat, hot surfaces, sparks, open flames, and other ignition sources. No smoking. P233 Keep container tightly closed. P240 Ground and bond receiving equipment. P241 Use non-sparking equipment. P242 Do not use tools that produce sparks. P243 Take precautionary measures against electrostatic discharge. (H226/H319/H315/H360) P280 Use personal protective equipment such as safety glasses, rubber gloves, and a respirator with an organic vapor filter for the eyes, skin, and respiratory tract. (H319/H315/H360) P201 Obtain instructions before use. P202 Do not handle until all safety precautions have been read and understood.
Intervention:	(H226) P303+P361+P353 IF ON SKIN (or hair): Take off all your clothes that got dirty. Rinse skin with water [or take a shower]. P370+P378 If there's a fire: use water spray or alcohol-resistant foam to put it out. (H315/H319) P352+P353 IF IN EYES OR ON SKIN: Rinse thoroughly with water and/or shower. P331 DO NOT induce vomiting. (H360) P308+P313 IF exposed or concerned: Get medical advice/attention.
Storage:	(H226) P403+P235 Store in a well-ventilated place. Keep cool.
Disposal:	(H226/H315/H319/H360) P501 Dispose of contents/container as hazardous waste in accordance with local regulations.
Other hazards not listed in the classification	May cause skin irritation; May cause drowsiness or dizziness; May impair fertility or harm the fetus.
Additional information	Not applicable

Ethanol (C2H5OH)	40% v/v
Water	60% v/v
Secondary components	Congeners, residual sugars, aromatic compounds

Section 3. Composition/information on ingredients

CAS-nº: 64-17-15
Molecular weight: 46,07 g/mol
Molecular formula (Hill): C2H6O
Molecular formula: C2H5OH o H3CH2OH (structured)
DOT Classification: UN 3065 DOT Guide-026 PG III

name	CAS No.	Concentration	ONU No.	IPVS DLH)	LMPE-PPT	LMPE-CT	Synonym
Ethanol	64-17-5	40 %	1170	3300 ppm	1900 mg/m3	ND	Alcohol
Water	7732-18-5	60%	N/A	N/A	N/A	ND	Water

Section 4. First Aid

Inhalation	Move to fresh air, seek medical attention if breathing is difficult.
Skin contact	Wash with soap and water
Eye contact	Rinse with plenty of water for 15 minutes
Ingestion	Do not induce vomiting, give water, seek immediate medical attention

Section 5. Firefighting measures

Suitable extinguishing media:
CO2, dry powder, water + foam.

Special hazards:
Fuel: Vapors heavier than air. Explosive mixtures with air are possible at normal temperatures.

Additional references:
Prevent extinguishing water from entering surface or underground aquifers. Keep away from sources of ignition.

Section 6. Measures to be taken in case of accidental spillage

Precautionary measures for people:
Do not inhale vapors/aerosols. Ventilate enclosed spaces.

Environmental protection measures:
Do not dispose of in drains.

Section 7. Handling and storage

Handling:
Avoid electrostatic charging. Keep away from sources of ignition.
Use only with natural or explosion-proof ventilation.
Do not use tools, equipment, or devices that produce sparks.

Storage:
Closed containers, cool, ventilated, and dry place..

Section 8. Exposure controls/personal protection

Specific control parameters:

Exposure limits/guidelines				
	Result	ACGIH	NIOSH	OSHA
Ethanol (64-17-5)	TWA	Not established	1000 ppm TWA; 1900 mg/m3 TWA	1000 ppm TWA; 1900 mg/m3 TWA
	STEL	1000 ppm STEL	Not established	Not established

ACGIH: American Conference of Governmental Industrial Hygiene
STEL: Short Term Exposure Limits are based on 15-minute exposures
NIOSH: National Institute of Occupational Safety and Health
TWA: Time-Weighted Averages are based on exposures of 8 hours/day, 40 hours/week. OSHA: Occupational Safety and Health Administration
Engineering controls/measures
Good general ventilation should be used. Ventilation rates should match conditions. If applicable, use process enclosures, local exhaust, ventilation, or other engineering controls to keep airborne levels below recommended exposure limits. If exposure limits have not been established, keep airborne levels at an acceptable level. Use explosion-proof electrical/ventilation/lighting equipment..

Personal protective equipment (if necessary)
Respiratory. Use self-contained breathing apparatus in case of insufficient ventilation.
Eyes/face: Wear safety glasses.
Skin/body: Wear suitable gloves.

Environmental exposure controls
Controls should be designed to prevent release to the environment, including procedures to prevent spills, release to the atmosphere, and release to waterways/storm drains. Follow best practices for site management and waste disposal.

Section 9. Physical and chemical properties

State	Clear liquid
Odor	Characteristic of Tequila
Density	0.948–0.952 g/mL (20 °C)
pH	4.5–5.5
Solubility	Total water and alcohols

Section 10. Stability and reactivity

Stability	Stable under normal conditions
Avoid	Sources of ignition, strong oxidants

Section 11. Toxicological information

Oral LD50 (rat, ethanol)	7,060 mg/kg
Effects	Drowsiness, dizziness, intoxication, risk of addiction

Section 12. Ecological information

Abiotic degradation:
Rapid degradation (air).

Biodegradability:
Biodegradation: 94% modified OECD Screening test; Easily biodegradable.

Behavior in ecological compartments:
Distribution: log P(oc): -0.32;
Bioaccumulation is not expected (log P (o/w) < 1).

Ecotoxic effects:
Biological effects: At high concentrations, harmful effect on aquatic organisms. No interference in sewage treatment plants is expected if used properly.
Fish toxicity: Leuciscus iuds LC 50: 8140 mg/l /48h;
Daphnia toxicity: Daphnia magna EC50: 9268-14221 mg/l/48;
Toxic concentration limit:
Toxicity to algae: Sc. quadricauda CI5: 5000 mg/l / 7d;
Toxicity to bacteria: Ps. putida CE5:6500 mg/l / 16h; Protozoa: E. sulcatum CE5: 65 mg/l / 72h.

Other ecological observations:
BOD: 0.93-1.67 g/g; COD: 1.99 g/g; Th OD: 2.10 g/g; BOD 74% of ThOd /5d; COD 90% of Th OD; Under normal handling conditions, no ecological problems are expected.

Section 13. Disposal considerations

Product:
At present, there are no uniform criteria for the disposal of chemical waste in the European Union. Chemical products that result as waste from everyday use are generally classified as special waste. Their disposal in EU countries is regulated by local laws and regulations. Please contact the appropriate authority in each case (public administration or a company specializing in waste disposal) for information on your specific case.

Packaging:
Disposal must be carried out in accordance with official regulations. Contaminated packaging must be treated in the same way as the contaminating product. Uncontaminated packaging should be treated as household waste or recyclable material.

Section 14. Transportation Information

Name: ALCOHOLIC BEVERAGES
with more than 24% but less than 70% alcohol by volume (According to provision 145, alcoholic beverages transported in containers of 250 L or less are not subject to the provisions of this code).

NU	1170 (Ethanol solution)
Class	3 (flammable liquids)
Packaging group	II

CARGA NO PELIGROSA

(NON-HAZ CARGO)

Ref. IMDG-CODE SPECIAL PROVISION
145

Section 15. Regulatory information

15.1 Specific safety, health, and environmental regulations or legislation for the substance or mixture
SARA hazard classifications
•Acute, chronic, fire

Destiladora Del Valle de Tequila S.A. de C.V. cannot control the regulations on substances that exist in the customer's country; therefore, that task is the customer's responsibility.

Section 16. Other information

The information provided in the safety data sheet is based on our current knowledge. It describes only the safety measures for handling this product and does not represent a guarantee of its described properties. In turn, it refers exclusively to this product and will not be valid if it is used in combination with another product or products.

This sheet will remain in effect until there is a change in the chemical composition of the product.

This general format is designed in accordance with the official Mexican standard NOM-018-STPS-2015.