





Q1)

a) after deletion $k=66$ and insertion $k=5, 9$ and 12 b) Insertion $k=10, 15$ and deletion $k=20$ (from original tree)c) insertion $k=85, 95$ (into original tree)

d) deletion $k=11$ (from the resulting tree in part-c)

ipek
02108
22003250



Q2)


a) min. number of key value insertions \rightarrow 2

To cause the bucket address table to double, we need to insert a key value that results in a new bit being added to the bucket address table.

This means that the least significant bit of the hash value of the inserted key should be different from the existing bit values.

One such sequence of insertions:

- 1- Insert key value 4. (100)
- 2- Insert key value 13. (1101)



b) Max. number of insertions = 24

ipek 02105 22003250

When the bucket address table doubles, a new bit is added, so there are $2^3 = 8$ addresses. Each can direct to one bucket which can contain 4 key values at most. $8 \times 4 = 32$ key values are possible. There are already 8 key values in B1 and B2. Thus, max. number of insertions is $32 - 8 = \underline{24}$.

One such sequence of insertions:

- 1- Insert 4.
- 2- Insert 13.
- 3- Insert 17
- 4- Insert 21
- 5- Insert 12
- 6- Insert 16
- 7- Insert 38
- 8- Insert 31
- 9- Insert 42
- 10- Insert 30
- 11- Insert 22
- 12- Insert 14

- 13- Insert 20
- 14- Insert 28
- 15- Insert 36
- 16- Insert 44
- 17- Insert 39
- 18- Insert 47
- 19- Insert 55
- 20- Insert 19
- 21- Insert 25
- 22- Insert 29
- 23- Insert 33
- 24- Insert 37

Final contents:

