

CUE - Cooperation in Urban Environments: Theoretical Notation

April 12, 2023

1 Model general notation

- A – Agent;
- P – Place;
- σ – trait value;
- D – critical Hamming distance of trait;
- R – critical radius;
- C – openness to contamination, or degree of interaction influence;
- M – memory size;

2 Simulation notation

- t – Timestep;
- i – Agent ID: unique integer number;
- j – Place ID: unique integer number;
- T – Total number of timesteps;
- x – position coordinate;
- y – position coordinate;

3 Agents

Agents are denoted by A . Any specific Agent is denoted by A^i , where i is the ID number of the Agent in a world of N_A Agents.

3.1 Parameters of Agents

Parameters are those static, constant attributes. They can be accessed by their names in the Agent subscript:

- A_D^i – D of A^i ;
- A_R^i – R of A^i ;
- A_C^i – C of A^i ;
- A_M^i – M of A^i ;

3.2 Variables of Agents

Variables are those mutable, changing attributes. They can be accessed by their names in the Agent subscript and by time step t in the Agent superscript:

- $A_\sigma^i(t)$ – σ of A^i in time step t ;
- $A_x^i(t)$ – x position coordinate of A^i in time step t ;
- $A_y^i(t)$ – y position coordinate of A^i in time step t ;

4 Places

Places are denoted by P . Any specific Agent is denoted by P^j , where j is the ID number of the Place in a world of N_P Places. Any specific Place j is also denoted by its own unique position: $P_{x,y}$ in 2D or P_x in 1D.

4.1 Parameters of Places

Parameters are those static, constant attributes. They can be accessed by their names in the Agent subscript:

- P_C^j – C of P^j ;
- P_x^j – x position coordinate of P^j ;
- P_y^j – y position coordinate of P^j ;

4.2 Variables of Places

Variables are those mutable, changing attributes. They can be accessed by their names in the Place subscript and by time step t in the Place superscript:

- $P_\sigma^j(t)$ – σ of P^j in time step t ;

5 Model equations

5.1 Interaction equations

When Agents interact with Places, both get some contamination from each other. Their next $t + 1$ value of σ changes by the following equations. For Agents:

$$A_\sigma^i(t+1) = \frac{A_\sigma^i(t) + P_\sigma^j(t) \cdot A_C^i}{1 + A_C^i} \quad \forall i, t \quad (1)$$

And for Places:

$$P_\sigma^j(t+1) = \frac{P_\sigma^j(t) + A_\sigma^i(t) \cdot P_C^j}{1 + P_C^j} \quad \forall i, j, t \quad (2)$$

Where $P_x^j = A_x^i(t)$ and $P_y^j = A_y^i(t)$. The value of $A_\sigma^{i,t}$ is a function of the Agent's previous traits (A_σ) and memory size (A_M):

$$A_\sigma^i(t) = \Psi(A_\sigma^i, A_M^i) \quad \forall i, t \quad (3)$$

Currently, the function Ψ the average of σ values allocated in the Agent's memory:

$$A_\sigma^i(t) = \frac{1}{A_M^i} \sum_{n=0}^{A_M^i} A_\sigma^i(t-n) \quad \forall i, t \quad (4)$$

5.2 Random walk

5.2.1 Set of candidate Places

At any time step, each Agent has a set \mathbb{P} of candidate Places to move in so they can interact. This set is made of Places P within the Agent's window of sight of size A_R and below the Agent's interaction threshold A_D .

In the case of considering **euclidean** distances between positions:

$$P \in \mathbb{P} \mid |P_x - A_x| \leq A_R \cap |P_y - A_y| \leq A_R \cap |P_\sigma - A_\sigma| \leq A_D \quad (5)$$

In the case of considering **non-euclidean** distances between positions:

$$P \in \mathbb{P} \mid \Phi(A_{x,y}, P_{x,y}) \leq A_R \cap |P_\sigma - A_\sigma| \leq A_D \quad (6)$$

Where $\Phi(A_{x,y}, P_{x,y})$ is a function that returns the **path distance** from position $A_{x,y}$ to $P_{x,y}$.

5.2.2 Uniform weighting function

The **uniform** weighting function is defined to set all available places the same likelihood to be chosen by a given Agent. Therefore:

$$P_L^j = \frac{1}{\mathbb{P}_N} \quad (7)$$

Where P_L^j is the likelihood of the candidate Place P^j and \mathbb{P}_N is the number of candidate Places in \mathbb{P} .

5.2.3 Linear weighting function

The **linear** weighting function is defined to set the likelihoods of candidate Places proportional to the σ discrepancy. Therefore, Agents are biased to go to Places like themselves. The function:

$$P_L^j = 1 - \frac{|A_\sigma - P_\sigma^j|}{\sum_{j=0}^{\mathbb{P}_N} |A_\sigma - P_\sigma^j|} \quad (8)$$

Where P_L^j is the likelihood of the candidate Place P^j and \mathbb{P}_N is the number of candidate Places in \mathbb{P} .

5.2.4 Exception cases

When the set \mathbb{P} of candidate Places is empty so $\mathbb{P}_N = 0$ then there is no interaction. This Agent will remain quiet until the surroundings Places yield a non-empty set \mathbb{P} .

When the set \mathbb{P} of candidate Places holds only one candidate place so $\mathbb{P}_N = 1$ then the likelihood of interaction is unity (100%).