

# Neural Word Embedding as Implicit Matrix Factorization

Shih-Ming Wang

NLPLab, Institute of Information Science, Academia Sinica

February 8, 2016

# Outline

## Introduction

## Skip-Gram with Negative Sampling (SGNS)

- Skip-Gram Model

- Negative Sampling

## SGNS as Implicit Matrix Factorization

## Alternative Word Representations

- Point-wise Mutual Information

- Singular Value Decomposition

## Empirical Results

- Experiment Setting

- Deviation from Optimal

- Linguistic Tasks

## Conclusion

# Introduction

- Word representation - why and how
- Distributional hypothesis
  - Words in similar contexts have similar meanings
  - Word-context matrix
- Skip-gram model
  - Neural-network based
  - Represent both word and context as vector
  - Maximize the dot-product of frequently occurring word-context vector pairs
  - Not well (theoretically) understood
- Analyze skip-gram as an implicit word-context matrix factorization

# Skip-Gram Model


- Words as dense vector (projected from one-hot)
- Different projection matrix for input and output words (context)

- Loss function:

$$\frac{1}{T} \sum_{t=1}^T \sum_{-c \leq j \leq c} \log p(w_{t+j} | w_t), \text{ where}$$

$$p(w_o | w_t) = \frac{\exp(\vec{w}_o \cdot \vec{w}_t)}{\sum_{i=1}^{||V||} \exp(\vec{w}_i \cdot \vec{w}_t)}$$

- Problem: softmax impractical because  $||V||$  is usually large





# Negative Sampling

- From now on, represent input and context word as  $w$  and  $c$
- Skip-Gram optimizes conditional probability  $P(c|w)$
- Negative Sampling optimizes joint probability  $P(w, c)$ 
  - Maximize observed pairs  $\sigma(\vec{w} \cdot \vec{c})$
  - Minimize  $k$  randomly sampled negative pairs  $\sigma(\vec{w} \cdot \vec{c}_N)$
  - $\sigma(x) = \frac{1}{1+\exp(-x)}$ , Property:  $\sigma(-x) = 1 - \sigma(x)$
- Paired-wise loss function
 
$$L(w, c) = \log(\sigma(\vec{w} \cdot \vec{c})) + k \mathbb{E}_{c_N \sim P(D)} [\log(\sigma(-\vec{w} \cdot \vec{c}_N))]$$
- Global loss function:  $\sum_{w \in V_w} \sum_{c \in V_c} \#(w, c) L(w, c)$

## SGNS as Implicit Matrix Factorization I

- SGNS learn a (input) word embedding  $W$  and a (output) context embedding  $C$
- Rows of  $W$  are used as word vectors while  $C$  is usually ignored
- But effectively, SGNS is implicitly factorizing a word-context matrix  $M = W \cdot C^T$
- Each cell of  $M$  equals  $\vec{w} \cdot \vec{c}$ , measuring the strength of association for a  $(w, c)$  pair
- But what is the explicit form  $f(w, c) = \vec{w} \cdot \vec{c}$ ?

## SGNS as Implicit Matrix Factorization II

- Assume that SGNS can fully reconstruct  $M$  (this requires infinite dimension for  $W, C$ )
- The global loss then equals the summation of  $M$ 's cells  

$$\sum_{w \in V_w} \sum_{c \in V_c} \#(w, c) \cdot L(w, c) = \sum_i \sum_j M_{ij} = \sum_i \sum_j f(w_i, c_j)$$
- The global loss is optimized when each cell of  $M$  is optimized
- Goal: find explicit form  $f(w, c) = \vec{w} \cdot \vec{c}$
- Strategy: Find

$$\sum_{w \in V_w} \sum_{c \in V_c} \ell(w, c) = \sum_{w \in V_w} \sum_{c \in V_c} \#(w, c) \cdot L(w, c), \text{ and let}$$

$$\frac{\partial \ell(w, c)}{\partial (\vec{w} \cdot \vec{c})} = 0 \text{ to find } \vec{w} \cdot \vec{c} \text{ that optimizes } \ell(w, c)$$

## SGNS as Implicit Matrix Factorization III

- $\ell(w, c) = \#(w, c) \log \sigma(\vec{w}, \vec{c}) + k \cdot \#(w) \cdot \frac{\#(c)}{|D|} \log \sigma(-\vec{w} \cdot \vec{c})$
- $\vec{w} \cdot \vec{c} = \log \left( \frac{\#(w, c) \cdot |D|}{\#(w) \cdot \#(c)} \right) - \log k$  (Wait, PMI?)
- $M_{ij}^{SGNS} = W_i \cdot C_j = \vec{w}_i \cdot \vec{c}_j = PMI(w_i, c_j) - \log k = M_{ij}^{PMI} - \log k$
- $M^{SGNS}$  was assumed to be fully reconstructed (not possible)
- In  $\ell(w, c)$ , the deviation of  $\vec{w}_i \cdot \vec{c}_j$  from  $M^{PMI} - \log k$  is weighted by  $\#(w, c)$  and  $k \cdot \#(w) \cdot \frac{\#(c)}{|D|}$
- SGNS is a weighted matrix factorization of  $M^{PMI} - \log k$
- Deviation of frequent word-context pairs pay more



## Point-wise Mutual Information

- $PMI(x, y) = \log \frac{P(x, y)}{P(x)P(y)}$
- Empirically,  $PMI(w, c) = \log \frac{\#(w, c) \cdot |D|}{\#(w) \cdot \#(c)}$
- Issue:  $M^{PMI}$  is dense
  - For unobserved  $(w, c)$ ,  $PMI(w, c) = \log 0 = -\infty$
  - Solution:  $PPMI(w, c) = \max(PMI(w, c), 0)$
  - $PPMI$  lose information of infrequent word-context pairs
  - Intuition: prefer positive ('Canada', 'Snow') association against negative ('Canada', 'Desert') association
- $M^{SGNS} = M^{PMI} - \log k$  is dense
- Modify:  $M^{SPPMI}$ , where
$$SPPMI(w, c) = \max(PMI(w, c) - \log k, 0)$$

# Singular Value Decomposition

- $M^{SPPMI}$  could directly be used as word embedding
- But it's sparse, dense vectors sometimes could be better?
- $M^{SPPMI} = U \cdot \Sigma \cdot V^T \Rightarrow U_d \cdot \Sigma_d \cdot V_d^T = M^{SVD}$
- Choose  $W^{SVD} = U_d \cdot \Sigma_d$  and  $C^{SVD} = V_d$ 
  - Under-perform SGNS empirically
  - $C^{SVD}$  is orthogonal while  $W^{SVD}$  is not
  - Both  $C^{SGNS}$  and  $W^{SGNS}$  are not orthogonal
  - $W^{SVD_{1/2}} = U_d \cdot \sqrt{\Sigma_d}$  and  $C^{SVD_{1/2}} = V_d \cdot \sqrt{\Sigma_d}$
  - Generally  $W^{SVD_\alpha} = U_d \cdot \Sigma^\alpha$  (set to 1/2 in experiments)

# Experiment Setting

- Corpus: English Wikipedia, 77.5 million sentences, 1.5 billion tokens
- Window size is set to 5, dropping words appears less than 100 times
- 189533 terms derived for both words and contexts

## Deviation from Optimal

Method	PMI – log $k$	SPPMI	SVD			SGNS		
			$d = 100$	$d = 500$	$d = 1000$	$d = 100$	$d = 500$	$d = 1000$
$k = 1$	0%	0.00009%	26.1%	25.2%	24.2%	31.4%	29.4%	7.40%
$k = 5$	0%	0.00004%	95.8%	95.1%	94.9%	39.3%	36.0%	7.13%
$k = 15$	0%	0.00002%	266%	266%	265%	7.80%	6.37%	5.97%

- The optimal solution is  $PMI - \log k$
- SPPMI is near-perfect approximation of the optimum
- SVD is better when  $d < 500$  and  $k = 1$
- SVD fails to leverage higher dimension as SGNS does
- $k$ 's meaning for SGNS
  - higher  $k$  means more sample and better estimation of negative sample distribution (good news)
  - higher  $k$  means that negative examples are more probable (actually not a good thing)
- $SPPMI(w, c) = \max(PMI(w, c) - \log k, 0)$ , only losing information as  $k$  increases

# Linguistic Tasks

WS353 (WORDSIM) [13]			MEN (WORDSIM) [4]		MIXED ANALOGIES [20]		SYNT. ANALOGIES [22]				
Representation		Corr.	Representation		Representation		Representation				
				Corr.		Acc.		Acc.			
SVD	(k=5)	0.691	SVD	(k=1)	0.735	SPPMI	(k=1)	0.655	SGNS	(k=15)	0.627
SPPMI	(k=15)	0.687	SVD	(k=5)	0.734	SPPMI	(k=5)	0.644	SGNS	(k=5)	0.619
SPPMI	(k=5)	0.670	SPPMI	(k=5)	0.721	SGNS	(k=15)	0.619	SGNS	(k=1)	0.59
SGNS	(k=15)	0.666	SPPMI	(k=15)	0.719	SGNS	(k=5)	0.616	SPPMI	(k=5)	0.466
SVD	(k=15)	0.661	SGNS	(k=15)	0.716	SPPMI	(k=15)	0.571	SVD	(k=1)	0.448
SVD	(k=1)	0.652	SGNS	(k=5)	0.708	SVD	(k=1)	0.567	SPPMI	(k=1)	0.445
SGNS	(k=5)	0.644	SVD	(k=15)	0.694	SGNS	(k=1)	0.540	SPPMI	(k=15)	0.353
SGNS	(k=1)	0.633	SGNS	(k=1)	0.690	SVD	(k=5)	0.472	SVD	(k=5)	0.337
SPPMI	(k=1)	0.605	SPPMI	(k=1)	0.688	SVD	(k=15)	0.341	SVD	(k=15)	0.208

- Similarity test (WD353, Men)
  - $SVD \geq SPPMI \geq SGNS$  (but the difference is small)
  - $k$  matters, SVD, SPPMI prefer small  $k$ , SGNS prefers large  $k$
- Analogies test (Mixed, Synt)
  - SVD is not good
  - SGNS significantly outperforms others on syntactic dataset
  - Might be due to that SGNS's higher weight for frequent word such as "the", "will", "each", "had"

# Conclusion

- SGNS is shown to implicitly factorizing the  $M^{PMI} - \log k$  matrix
- $M^{SPPMI}$ , where  $SPPMI = \max(PMI - \log k, 0)$ 
  - Practical modification of SPMI
  - Approximate  $M^{PMI} - \log k$  better than SGNS
  - Not necessarily performs better on linguistic tasks
  - Might be due to SGNS's ability to perform weighted matrix factorization
- SVD
  - Leads to no significantly improvement but sometimes worse performance
  - The data is “big” enough to support  $M^{SPPMI}$ ?