

Investigation on Optimal Mixing with Linkage Sets and Its Application

Presenter: 王士銘

Advisor: 于天立 教授

Outline



1. Background Knowledge
2. Motivation
3. Investigation on Different Masks
4. Optimal Mixing with Mask Selection
5. Conclusion

Outline

1. Background Knowledge
2. Motivation
3. Investigation on Different Masks
4. Optimal Mixing with Mask Selection
5. Conclusion


Simple GA \Rightarrow Model Building GA

Schemata	fitness
000	0.9
001,010,100	0.45
011,101,110	0
111	1




Optimal Mixing

- GA/MBGA : Large enough population \Rightarrow conquer sampling noise




- Optimal Mixing : Donation and evaluation \Rightarrow noise free



Linkage Tree (LT)

- Hierarchical Clustering
- Utilized (donation) in top-down order
- Robust since it is likely to cover all BBs




Outline

1. Background Knowledge
2. **Motivation**
3. Investigation on Different Masks
4. Optimal Mixing with Mask Selection
5. Conclusion

Motivational Experiment

- Small mask \Rightarrow find local optima
- Large Mask \Rightarrow recombine local optima
- An experiment on trap problem with $k=5$
 - Two stage
 - 1^{st} generation : masks of size < 5
 - Other generations : masks of size ≥ 5




Outline


1. Background Knowledge
2. Motivation
3. Investigation on Different Masks
4. Optimal Mixing with Mask Selection
5. Conclusion

Problem Instances

- Homogeneous separable problem
- The one-max problem



- The (m, k) - trap problem



Linkage Set


- Homogeneous and isomorphic set of masks

- Marginal product model (MP)

$(\ell, 1)$ -MP 

(m, k) -MP 


- (m, k) - LT



CP Index


- $CP_{theo}(\mathbb{M}, P) = \frac{E[\text{GAIN}(S_{\mathbb{M},P}, S_{\mathbb{M},P}, \mathbb{M})]}{E[\text{COST}(S_{\mathbb{M},P}, S_{\mathbb{M},P}, \mathbb{M})]}$
- $S_{\mathbb{M},P}$: random variable of schemata
- Learn distribution of $S_{\mathbb{M},P}$ from population

Schemata	fitness	rank
000	0.9	2
001,010,100	0.45	1
011,101,110	0	0
111	1	3





$$\text{GAIN}(r, d, \mathbb{M}) = 3 - 1 = 2$$

$$\text{COST}(r, d, \mathbb{M}) = 2$$



Model Efficiency

Model	Pop	NFEs
316		<u>49982</u>
264		129300
Fail		Fail
188		50013
181		45889
137		<u>39356</u>
188		113440
160		91393





Population sizing

- Decision making \Rightarrow noise-free decision making
- Model building \Rightarrow rather robust hierarchal linkage tree
- Initial supply

Population sizing

- Perform OM+LT on the (m, k) -trap problem
- Discard masks of size 1 at different generation
- Small masks in early generations and large masks in late generations



Normalized CP


- $CP_{theo}(\mathbb{M}, P) = \frac{E[\text{GAIN}(S_{\mathbb{M},P}, S_{\mathbb{M},P}, \mathbb{M})]}{E[\text{COST}(S_{\mathbb{M},P}, S_{\mathbb{M},P}, \mathbb{M})]}$
- $CP_{prac}(M, P) = \frac{E[\text{GAIN}(S_{M,P}^e, S_{M,P}^e, \{M\})]}{E[\text{COST}(S_{M,P}^e, S_{M,P}^e, \{M\})]}$
- $CP_{norm}(M, P) = \frac{CP_{prac}(M, P)}{R(S_{M,P}^e)H(S_{M,P}^e)}$
- $S_{M,P}^e$: (random variable) schemata in population
- $R(S_{M,P}^e)$: highest rank of
- $H(S_{M,P}^e)$: entropy of $S_{M,P}^e$

Outline

1. Background Knowledge
2. Motivation
3. Investigation on Different Masks
4. Optimal Mixing with Mask Selection
5. Conclusion

Modification of OM+LT


- Stage 1, OM+ 'some masks' : $P \Rightarrow O_{meta}$, CP_{norm} info
- $CP_{norm} \Rightarrow$ 'promising masks'
- Stage 2, OM + 'promising masks' : $O_{meta} \Rightarrow O$



CP Estimation

- Run OM one time, for each mask, CP= total gain/total cost
- Utilize (estimate CP) which masks for each receiver?
Different layers for different parents
All layers for all parents



Parents(receivers)



Experiment


- The one-max
- The trap problem
- The NK-landscape problem with no overlap
general case of fully separable problem

Experiment Results – One-Max




Problem length \blacktriangle OM \circ OMCPE1 \times OMCPE2 Problem length


Experiment Results – Trap



Problem length \blacktriangle OM \circ OMCPE1 \times OMCPE2 Problem length



Experiment Results –NK-landscape




Problem length

—△— OM

—○— OMCPE1

—×— OMCPE2

Problem length



Population Size

Summary & Conclusion


- OM is analyzed from the perspective of model efficiency and population sizing
- Mask pruning metric is designed
- OM-based algorithm with mask selection technique is designed
- Mask selection not only reduce NFEs but also make OM scale better
- This work can be extended to more complex scenario and help to improve OM



End


Overlap problem

- The aggregate trap problem




Overlap problem


Fail	Fail
645	71433
620	68103
719	188352



Rank Estimation



Overlap NK-LandScape



Overlap NK-LandScape

