

RWorksheet_camasa#3b

April Marie

2024-10-23

1. Create a data frame using the table below.

a. Write the codes.

```
Respondents <- c(1:20)
Respondents

## [1] 1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18 19 20

Sex <- c(2, 2, 1, 2, 2, 2, 2, 2, 2, 2, 1, 2, 2, 2, 2, 2, 2, 1, 2)
Sex

## [1] 2 2 1 2 2 2 2 2 2 1 2 2 2 2 2 2 2 1 2

Occupation <- c(1, 2, 2, 2, 1, 2, 3, 1, 1, 1, 3, 2, 1, 3, 3, 1, 3, 1, 2, 1)
Occupation

## [1] 1 2 2 2 1 2 3 1 1 1 3 2 1 3 3 1 3 1 2 1

Persons <- c(5, 7, 3, 8, 5, 9, 6, 7, 8, 4, 7, 5, 4, 7, 8, 8, 3, 11, 7, 6)
Persons

## [1] 5 7 3 8 5 9 6 7 8 4 7 5 4 7 8 8 3 11 7 6

Siblings <- c(6, 4, 4, 1, 2, 1, 5, 3, 1, 2, 3, 2, 5, 5, 2, 1, 2, 5, 3, 2)
Siblings

## [1] 6 4 4 1 2 1 5 3 1 2 3 2 5 5 2 1 2 5 3 2

Houses <- c(1, 2, 3, 1, 1, 3, 3, 1, 2, 3, 2, 3, 2, 2, 3, 3, 3, 3, 3, 2)
Houses

## [1] 1 2 3 1 1 3 3 1 2 3 2 3 2 2 3 3 3 3 3 2

data <- data.frame(Respondents, Sex, Occupation, Persons, Siblings, Houses)
data

## Respondents Sex Occupation Persons Siblings Houses
## 1 1 2 1 5 6 1
## 2 2 2 2 7 4 2
## 3 3 1 2 3 4 3
## 4 4 2 2 8 1 1
## 5 5 2 1 5 2 1
## 6 6 2 2 9 1 3
## 7 7 2 3 6 5 3
## 8 8 2 1 7 3 1
## 9 9 2 1 8 1 2
```

```
## 10      10      2      1      4      2      3
## 11      11      1      3      7      3      2
## 12      12      2      2      5      2      3
## 13      13      2      1      4      5      2
## 14      14      2      3      7      5      2
## 15      15      2      3      8      2      3
## 16      16      2      1      8      1      3
## 17      17      2      3      3      2      3
## 18      18      2      1     11      5      3
## 19      19      1      2      7      3      3
## 20      20      2      1      6      2      2
```

b. Describe the data. Get the structure or the summary of the data

```
str(data)
```

```
## 'data.frame':  20 obs. of  6 variables:
## $ Respondents: int  1 2 3 4 5 6 7 8 9 10 ...
## $ Sex        : num  2 2 1 2 2 2 2 2 2 2 ...
## $ Occupation : num  1 2 2 2 1 2 3 1 1 1 ...
## $ Persons    : num  5 7 3 8 5 9 6 7 8 4 ...
## $ Siblings   : num  6 4 4 1 2 1 5 3 1 2 ...
## $ Houses     : num  1 2 3 1 1 3 3 1 2 3 ...
```

```
summary(data)
```

```
##   Respondents      Sex      Occupation      Persons      Siblings
##   Min.   : 1.00   Min.   :1.00   Min.   :1.00   Min.   : 3.0   Min.   :1.00
##   1st Qu.: 5.75   1st Qu.:2.00   1st Qu.:1.00   1st Qu.: 5.0   1st Qu.:2.00
##   Median :10.50   Median :2.00   Median :2.00   Median : 7.0   Median :2.50
##   Mean   :10.50   Mean   :1.85   Mean   :1.80   Mean   : 6.4   Mean   :2.95
##   3rd Qu.:15.25   3rd Qu.:2.00   3rd Qu.:2.25   3rd Qu.: 8.0   3rd Qu.:4.25
##   Max.    :20.00   Max.    :2.00   Max.    :3.00   Max.    :11.0   Max.    :6.00
##   Houses
##   Min.    :1.0
##   1st Qu.:2.0
##   Median :2.5
##   Mean    :2.3
##   3rd Qu.:3.0
##   Max.    :3.0
```

c. Is the mean number of siblings attending is 5?

NO

```
mean_num <- mean(Siblings)
mean_num
```

```
## [1] 2.95
```

d. Extract the 1st two rows and then all the columns using the subsetting functions. Write the codes and its output.

```
extract <- data[1:2, ]
extract
```

	Respondents	Sex	Occupation	Persons	Siblings	Houses
## 1	1	2	1	5	6	1
## 2	2	2	2	7	4	2

e. Extract 3rd and 5th row with 2nd and 4th column. Write the codes and its result.

```
extracted_data <- data[c(3, 5), c(2, 4)]
(extracted_data)
```

	Sex	Persons
## 3	1	3
## 5	2	5

f. Select the variable types of houses then store the vector that results as types_houses. Write the codes.

```
types_houses <- class(Houses)
types_houses
```

```
## [1] "numeric"
```

g. Select only all Males respondent that their father occupation was farmer. Write the codes and its output.

```
male_farmers <- data[data$Sex == 1 & data$Occupation == 1, ]
print(male_farmers)
```

```
## [1] Respondents Sex Occupation Persons Siblings Houses
## <0 rows> (or 0-length row.names)
```

h. Select only all females respondent that have greater than or equal to 5 number of siblings attending school. Write the codes and its outputs.

```
female <- data[data$Sex == 2 & data$Siblings >= 5, ]
print(female)
```

	Respondents	Sex	Occupation	Persons	Siblings	Houses
## 1	1	2	1	5	6	1
## 7	7	2	3	6	5	3
## 13	13	2	1	4	5	2

```
## 14      14  2      3      7      5      2
## 18      18  2      1     11      5      3
```

2. Write a R program to create an empty data frame. Using the following codes:

```
df = data.frame(Ints=integer(),
Doubles=double(), Characters=character(),
Logicals=logical(),
Factors=factor(),
stringsAsFactors=FALSE)
print("Structure of the empty dataframe:")

## [1] "Structure of the empty dataframe:"
str(df)

## 'data.frame':    0 obs. of  5 variables:
## $ Ints      : int
## $ Doubles   : num
## $ Characters: chr
## $ Logicals  : logi
## $ Factors   : Factor w/ 0 levels:
```

a. Describe the results.

The provided R code creates an empty data frame named `df` with five specified column types: integers, doubles, characters, logicals, and factors. When the structure of this empty data frame is printed using the `str()` function, it reveals that each column labeled `Ints`, `Doubles`, `Characters`, `Logicals`, and `Factors` is defined with the appropriate data type, but all columns contain zero observations (rows). The argument `stringsAsFactors = FALSE` ensures that any character data remains as character type rather than being automatically converted to factors. Overall, the output confirms that while the data frame is correctly structured to hold various data types, it currently holds no data.

3. Create a .csv file of this. Save it as `HouseholdData.csv`

```
household_data <- data.frame(
  Respondents = 1:10,
  Sex = c("Male", "Female", "Female", "Male", "Male", "Female", "Female", "Male", "Female", "Male"),
  Fathers_Occupation = c(1, 2, 3, 3, 1, 2, 2, 1, 1, 3),
  Persons_at_Home = c(5, 7, 3, 8, 6, 4, 2, 4, 11, 6),
  Siblings_at_School = c(5, 3, 3, 5, 6, 3, 1, 2, 6, 6),
```

```
Types_of_Houses = c("Wood", "Concrete", "Concrete", "Wood", "Semi-concrete", "Semi-concrete", "Wood",
household_data
```

```
## Respondents Sex Fathers_Occupation Persons_at_Home Siblings_at_School
## 1 1 Male 1 5 5
## 2 2 Female 2 7 3
## 3 3 Female 3 3 3
## 4 4 Male 3 8 5
## 5 5 Male 1 6 6
## 6 6 Female 2 4 3
## 7 7 Female 2 2 1
## 8 8 Male 1 4 2
## 9 9 Female 1 11 6
## 10 10 Male 3 6 6
## Types_of_Houses
## 1 Wood
## 2 Concrete
## 3 Concrete
## 4 Wood
## 5 Semi-concrete
## 6 Semi-concrete
## 7 Wood
## 8 Semi-concrete
## 9 Semi-concrete
## 10 Concrete
```

```
write.csv(df, "HouseholdData.csv", row.names = FALSE)
```

a. Import the csv file into the R environment. Write the codes.

```
household_data <- read.csv("HouseholdData.csv")

print(household_data)

## [1] Ints Doubles Characters Logicals Factors
## <0 rows> (or 0-length row.names)
```

b. Convert the Sex into factor using factor() function and change it into integer.[Legend: Male = 1 and Female = 2]. Write the R codes and its output.

```
household_data$Sex <- factor(household_data$Sex, levels = c("Male", "Female"), labels = c(1, 2))

household_data$Sex <- as.integer(household_data$Sex)
print(household_data)

## [1] Ints Doubles Characters Logicals Factors Sex
## <0 rows> (or 0-length row.names)
```

c. Convert the Type of Houses into factor and change it into integer. [Legend: Wood = 1; Congrete = 2; Semi-Congrete = 3]. Write the R codes and its output.

```
household_data$Types_of_Houses <- factor(household_data$Types_of_Houses, levels = c("Wood", "Concrete", "Semi-Concrete"))
household_data$Types_of_Houses <- as.integer(household_data$Types_of_Houses)
print(household_data)
```

```
## [1] Ints          Doubles          Characters          Logicals
## [5] Factors        Sex              Types_of_Houses
## <0 rows> (or 0-length row.names)
```

d. On father's occupation, factor it as Farmer = 1; Driver = 2; and Others = 3. What is the R code and its output?

```
household_data$Fathers_Occupation <- factor(household_data$Fathers_Occupation, levels = c(1, 2, 3), labels = c("Farmer", "Driver", "Others"))
household_data$Fathers_Occupation <- as.integer(household_data$Fathers_Occupation)
print(household_data)
```

```
## [1] Ints          Doubles          Characters          Logicals
## [5] Factors        Sex              Types_of_Houses    Fathers_Occupation
## <0 rows> (or 0-length row.names)
```

e. Select only all females respondent that has a father whose occupation is driver. Write the codes and its output.

```
fem_driver_respondents <- subset(household_data, Sex == 2 & Fathers_Occupation == 2)
print(fem_driver_respondents)
```

```
## [1] Ints          Doubles          Characters          Logicals
## [5] Factors        Sex              Types_of_Houses    Fathers_Occupation
## <0 rows> (or 0-length row.names)
```

f. Select the respondents that have greater than or equal to 5 number of siblings attending school. Write the codes and its output.

```
siblings_gte_5 <- subset(household_data, Siblings >= 5)
print(siblings_gte_5)
```

```
##      Ints Doubles Characters Logicals Factors Sex Types_of_Houses
## NA      NA      NA          NA        NA     NA      NA
## NA.1    NA      NA          NA        NA     NA      NA
## NA.2    NA      NA          NA        NA     NA      NA
## NA.3    NA      NA          NA        NA     NA      NA
## NA.4    NA      NA          NA        NA     NA      NA
```

##	Fathers_Occupation
## NA	NA
## NA.1	NA
## NA.2	NA
## NA.3	NA
## NA.4	NA