



Golang Programming

Methods. Composing Structs by Type Embedding

Where to Find The Code and Materials?

<https://github.com/iproduct/coursego>

Methods

```
type Vertex struct {  
    X, Y float64  
}
```

```
func (v Vertex) Abs() float64 {  
    return math.Sqrt(v.X*v.X + v.Y*v.Y)  
}
```

```
func main() {  
    v := Vertex{3, 4}  
    fmt.Println(v.Abs())  
    abs := Vertex.Abs  
    fmt.Println(abs(v))  
}
```

Methods on Non Structs

```
type MyFloat float64

func (f MyFloat) Abs() float64 {
    if f < 0 {
        return float64(-f)
    }
    return float64(f)
}

func main() {
    f := MyFloat(-math.Sqrt2)
    fmt.Println(f.Abs())
}
```

Methods on Non Structs

```
type Role int

const (
    User Role = 1 << iota
    Manager
    Admin
    RoleMask = (1 << (iota)) - 1
)

func (r Role) String() string {
    switch r {
    case User:
        return "User"
    case Manager:
        return "Manager"
    case Admin:
        return "Admin"
    default:
        return "Invalid role"
    }
}
```

```
// Status type
type Status int
```

```
// User statuses enum
const (
    Registered Status = iota
    Active
    Disabled
)
```

```
// Returns string representation of the Role
func (r Status) String() string {
    switch r {
    case Registered:
        return "Registered"
    case Active:
        return "Active"
    case Disabled:
        return "Disabled"
    default:
        return "Invalid status"
    }
}
```

Value and Pointer Receivers

```
type Vertex struct {  
    X, Y float64  
}  
  
func (v Vertex) Abs() float64 {  
    return math.Sqrt(v.X*v.X + v.Y*v.Y)  
}  
  
func (v *Vertex) Scale(f float64) {  
    v.X = v.X * f  
    v.Y = v.Y * f  
}  
  
func main() {  
    v := Vertex{3, 4}  
    v.Scale(10)  
    fmt.Println(v.Abs())  
}
```

Methods Are Just Like Functions

```
type Vertex struct {  
    X, Y float64  
}  
  
func Abs(v Vertex) float64 {  
    return math.Sqrt(v.X*v.X + v.Y*v.Y)  
}  
  
func Scale(v *Vertex, f float64) {  
    v.X = v.X * f  
    v.Y = v.Y * f  
}  
  
func main() {  
    v := Vertex{3, 4}  
    Scale(&v, 10)  
    fmt.Println(Abs(v))  
}
```

Methods and Pointer Indirection

```
type Vertex struct {
    X, Y float64
}
func (v *Vertex) Scale(f float64) {
    v.X = v.X * f
    v.Y = v.Y * f
}
func ScaleFunc(v *Vertex, f float64) {
    v.X = v.X * f
    v.Y = v.Y * f
}
func (v Vertex) Abs() float64 {
    return math.Sqrt(v.X*v.X + v.Y*v.Y)
}
func AbsFunc(v Vertex) float64 {
    return math.Sqrt(v.X*v.X + v.Y*v.Y)
}
```

```
func main() {
    // Pointer receiver methods
    v := Vertex{3, 4}
    v.Scale(2)
    ScaleFunc(&v, 5)

    p := &Vertex{4, 3}
    p.Scale(5)
    ScaleFunc(p, 2)
    fmt.Println(v, p)

    // Value receiver methods
    fmt.Println(v.Abs())
    fmt.Println(AbsFunc(v))

    fmt.Println(p.Abs())
    fmt.Println(AbsFunc(*p))
}
```


Methods: Value and Pointer Receivers

```
type ByteSlice []byte
```

```
func (slice ByteSlice) Append(data []byte) []byte {  
    return append([]byte(slice), data...)  
}
```

```
func (slice *ByteSlice) AppendPointer(data []byte) {  
    *slice = append([]byte(*slice), data...)  
}
```

```
func (slice *ByteSlice) Write(data []byte) (n int, err error) {  
    *slice = append([]byte(*slice), data...)  
    return len(data), nil  
}
```

```
func main() {  
    var b ByteSlice  
    fmt.Fprintf(&b, "This hour has %d days\n", 7)  
    fmt.Printf("%v", b)  
}
```

Choosing Value or Pointer Receiver

There are two reasons to use a pointer receiver:

- The first is so that the **method can modify the value** that its receiver points to.
- The second is to **avoid copying the value** on each method call. This can be more efficient if the receiver is a large **struct**, for example.
- In general, **all methods** on a given type **should have either value or pointer receivers**, but not a mixture of both.
- More about selectors and method expressions:
<https://golang.org/ref/spec#Selectors>

Method Receivers and Interfaces

```
type Abser interface {
    Abs() float64
}

func main() {
    var a Abser
    f := MyFloat(-math.Sqrt2)
    v := Vertex{3, 4}

    a = f // MyFloat implements Abser
    fmt.Println(a.Abs())
    a = &v // *Vertex implements Abser

    // Vertex do not implement Abser
    //a = v

    fmt.Println(a.Abs())
}
```

```
type MyFloat float64

func (f MyFloat) Abs() float64 {
    if f < 0 {
        return float64(-f)
    }
    return float64(f)
}

type Vertex struct {
    X, Y float64
}

func (v *Vertex) Abs() float64 {
    return math.Sqrt(v.X*v.X + v.Y*v.Y)
}
```

Methods with Nil Receivers

// Path represents a sequence of Vertices. A nil Path represents empty sequence.

```
type Path []Vertex
func (p *Path) Distance() (dist float64) {
    dist = 0
    if *p == nil || len(*p) == 0 {
        return 0
    }
    v1 := (*p)[0]
    var v2 Vertex
    for i := 1; i < len(*p); i++ {
        v2 = (*p)[i]
        dist += v1.Distance(v2)
        v1 = v2
    }
    return
}

func main() {
    var path Path
    path = Path{{1, 1}, {4, 5}, {4, 1}, {1, 1}}
    fmt.Println("Perimeter = ", path.Distance())
}
```

Composing structs by Type Embedding

```
type ColorVertex struct {  
    Vertex  
    Color color.RGBA  
}  
  
func main() {  
    green := color.RGBA{0, 255, 0, 255}  
    yellow := color.RGBA{255, 255, 0, 255}  
    cv1 := ColorVertex{Vertex{2, 3}, green}  
    cv2 := ColorVertex{Vertex{6, 6}, yellow}  
    fmt.Println(cv1.Distance(cv2.Vertex)) // 5  
    cv1.Scale(4)  
    cv2.Scale(4)  
    fmt.Println(cv1.Distance(cv2.Vertex)) // 20  
    // cv1.Distance(cv2) // no cv1.Distance(ColorVertex)  
}
```

```
type Vertex struct {  
    X, Y float64  
}  
  
func (v Vertex) Distance(o Vertex) float64 {  
    return math.Hypot(o.X-v.X, o.Y-v.Y)  
}  
  
func (v *Vertex) Scale(f float64) {  
    v.X = v.X * f  
    v.Y = v.Y * f  
}
```

Composing structs by Pointer Type Embedding

```
type ColorVertexP struct {  
    *Vertex  
    Color color.RGBA  
}  
  
cvp1 := ColorVertexP{&Vertex{2, 7}, green}  
cvp2 := ColorVertexP{&Vertex{5, 3}, yellow}  
fmt.Println(cvp1.Distance(*cvp2.Vertex)) // "5"  
cvp1.Vertex = cvp2.Vertex  
cvp1.Scale(3)  
fmt.Println(*cvp1.Vertex, *cvp2.Vertex) // {15 9} {15 9}
```

Rules for Method Promotion – Value vs. Pointer Fields

Given a **struct** type S and a **defined type** T , promoted methods are included in the **method set** of the **struct** as follows:

- If S contains an embedded field T , the method sets of S and $*S$ both include promoted methods with **receiver** T . The method set of $*S$ also includes promoted methods with **receiver** $*T$.
- If S contains an embedded field $*T$, the method sets of S and $*S$ both include promoted methods with **receiver** T or $*T$.

Method Values and Expressions

```
a := Vertex{2, 7}
b := Vertex{5, 3}
```

```
distance := Vertex.Distance // method expression
fmt.Println(distance(a, b)) // 5
fmt.Printf("%T\n", distance) // func(main.Vertex, main.Vertex) float64
```

```
scale := (*Vertex).Scale // method expression
scale(&a, 2)
fmt.Println(a) // {4 14}
fmt.Printf("%T\n", scale) // func(*main.Vertex, float64)
```

```
scaleB := (&b).Scale // method value
fmt.Printf("%T\n", scaleB) // func(float64)
scaleB(2)
fmt.Printf("Scaling b with factor 2: b now is %f\n", b) //{10 6}
```

```
distanceFromA := a.Distance // method value
fmt.Printf("%T\n", distanceFromA) // func(*Vertex, float64)
fmt.Printf("Distance from A of B is %f\n", distanceFromA(b)) //10
```


Encapsulation

- State encapsulation:

```
type IntSet struct {  
    words []uint64  
}
```

- No state encapsulation:

```
type IntSet []uint64
```

Examples

- IntBitSet
- PriorityQueue
- HttpServer

JSON Marshalling and Unmarshalling

// Structs --> JSON

```
data, err := json.Marshal(goBooks)
if err != nil {
    log.Fatalf("JSON marshaling failed: %s", err)
}
fmt.Printf("%s\n", data)
```

// Prettier formatting

```
data, err = json.MarshalIndent(goBooks, "", "    ")
if err != nil {
    log.Fatalf("JSON marshaling failed: %s", err)
}
fmt.Printf("%s\n", data)
```

// JSON -> structs

```
var books []Book
if err := json.Unmarshal(data, &books); err != nil {
    log.Fatalf("JSON unmarshaling failed: %s", err)
}
fmt.Println("AFTER UNMARSHAL:\n", books)
```

HTTP Client Example (from Lesson 1)

```
import ("bufio"; "fmt"; "log"; "net/http")

func main() {
    //resp, err := http.Get("http://localhost:8080/headers")
    //resp, err := http.Get("http://google.com")
    req, err := http.NewRequest("GET", "http://localhost:8080/headers", nil)
    req.Header.Add("Accept", `Accept: text/html,application/xhtml+xml,application/xml;q=0.9,*/*;q=0.8`)
    req.Header.Add("Custom-Header", `Custom Value`)
    resp, err := http.DefaultClient.Do(req)
    if err != nil {
        log.Fatal(err)
    }

    fmt.Println("Response status:", resp.Status)
    scanner := bufio.NewScanner(resp.Body)
    for i := 0; scanner.Scan() && i < 10; i++ {
        fmt.Println(i+1, ":", scanner.Text())
    }
}
```

Homework 2 (GitHub API Client)

Implement GitHub API HTTP client that will:

- Read a text file given as command line argument to the program and parse different Github usernames – each username on separate line in the file
- Fetch GitHub users data in JSON format using public GitHub API:
[https://api.github.com/users/\\${username}](https://api.github.com/users/${username})
- Fetch GitHub user repositories data in JSON format from:
[https://api.github.com/users/\\${username}/repos](https://api.github.com/users/${username}/repos)
- Fetch information about programming languages in each repo from:
[https://api.github.com/repos/\\${username}/\\${repo-name}/languages](https://api.github.com/repos/${username}/${repo-name}/languages)
- Parse the JSON data using [json.Unmarshal](#) into appropriate data structures in Go (you could define only fields that are interesting, all fields exported = starting with capital letter).
- Print a statistics report containing the information about the user, the number of user repositories, the distribution of programming languages according to their usage numbers (third URL), the total number of followers, number of forks for all repositories, by year distribution of user activity calculated using repositories creation and last update dates. Format the report and print it to the console as a table with all users to allow comparison.

Recommended Literature

- The Go Documentation - <https://golang.org/doc/>
- The Go Bible: Effective Go - https://golang.org/doc/effective_go.html
- David Chisnall, *The Go Programming Language Phrasebook*, Addison Wesley, 2012
- Alan A. A. Donovan, Brian W. Kernighan, *The Go Programming Language*, Addison Wesley, 2016
- Nathan Youngman, Roger Peppé, *Get Programming with Go*, Manning, 2018
- Naren Yellavula, *Building RESTful Web Services with Go*, Packt, 2017

Thank's for Your Attention!



Trayan Iliev

IPT – Intellectual Products & Technologies

<http://iproduct.org/>

<http://robolearn.org/>

<https://github.com/iproduct>

<https://twitter.com/trayaniliev>

<https://www.facebook.com/IPT.EACAD>