

# Other Python Libraries: Pandas, Requests, Beautiful Soup

#### About me



#### **Trayan Iliev**


- CEO of IPT Intellectual Products & Technologies
   <a href="http://www.iproduct.org">http://www.iproduct.org</a>
- Oracle® certified programmer 15+ Y
- end-to-end reactive fullstack apps with Java, ES6+,
   TypeScript, Angular, React and Vue.js
- 12+ years IT trainer: Spring, Java EE, Node.js, Express,
   GraphQL, SOA, REST, DDD & Reactive Microservices
- Voxxed Days, jPrime, Java2Days, jProfessionals, BGOUG, BGJUG, DEV.BG speaker
- Organizer RoboLearn hackathons and IoT enthusiast

#### Where to Find The Code and Materials?

https://github.com/iproduct/intro-python

## **Pandas**

Working with dataframes



#### Pandas [https://www.w3schools.com/python/pandas/default.asp]

- Pandas is a Python library used for working with data sets.
- Fast, flexible, and expressive data structures designed to make working with 'relationa' or 'labeled' data both easy and intuitive. It aims to be the fundamental high-level building block for real world data analysis.
- It has functions for cleaning, exploring, analyzing, and manipulating data.
- "Pandas" name has a reference to "Panel Data", and "Python Data Analysis" created by Wes McKinney in 2008.
- Pandas allows us to analyze big data and make conclusions based on statistical theories – allows us to answer questions like:
  - is there a correlation between two columns?
  - what is average / max /min value?
  - clean datasets
  - etc.

#### Pandas DataFrame Example


```
df = pd.DataFrame(
                                                        DataFrame
     "Name": [
       "Braund, Mr. Owen Harris",
       "Allen, Mr. William Henry",
       "Bonnell, Miss. Elizabeth",
                                                                           row
     "Age": [22, 35, 58],
     "Sex": ["male", "male", "female"],
                                                              column
```

Pandas official documentation: <a href="https://pandas.pydata.org/docs/index.html">https://pandas.pydata.org/docs/index.html</a>

Pandas Tutorial in W3Schools: <a href="https://www.w3schools.com/python/pandas/default.asp">https://www.w3schools.com/python/pandas/default.asp</a>

Pandas Exercises and problems: <a href="https://www.w3resource.com/python-exercises/pandas/index.php">https://www.w3resource.com/python-exercises/pandas/index.php</a>

## Pandas plot with Mathplotlib



https://matplotlib.org/stable/
https://www.w3schools.com/python/matplotlib\_intro.asp

# **Beautiful Soup**



#### **Beautiful Soup**

[https://www.crummy.com/software/BeautifulSoup/bs4/doc/]

Beautiful Soup is a Python library for pulling data out of HTML and XML files. It works with your favorite parser to provide idiomatic ways of navigating, searching, and modifying the parse tree. It commonly saves programmers hours or days of work.



#### Beautiful Soup 4 Basic Examples I

[https://www.crummy.com/software/BeautifulSoup/bs4/doc/]

```
from bs4 import BeautifulSoup
html_doc = """<html><head><title>The Dormouse's story</title></head>
<body>
<b>The Dormouse's story</b>
Once upon a time there were three little sisters; and their names were
<a href="http://example.com/elsie" class="sister" id="link1">Elsie</a>,
<a href="http://example.com/lacie" class="sister" id="link2">Lacie</a> and
<a href="http://example.com/tillie" class="sister" id="link3">Tillie</a>;
and they lived at the bottom of a well.
...
soup = BeautifulSoup(html_doc, 'html.parser')
print(soup.prettify())
```

## Beautiful Soup 4 Basic Examples II

```
soup.title
# <title>The Dormouse's story</title>
soup.title.name
# u'title'
soup.title.string
# u'The Dormouse's story'
soup.title.parent.name
# u'head'
soup.p
# <b>The Dormouse's story</b>
soup.p['class']
# u'title'
soup.a
```

# <a class="sister" href="http://example.com/elsie" id="link1">Elsie</a>

## Beautiful Soup 4 Basic Examples III

```
soup.find_all('a')
# [<a class="sister" href="http://example.com/elsie" id="link1">Elsie</a>,
# <a class="sister" href="http://example.com/lacie" id="link2">Lacie</a>,
# <a class="sister" href="http://example.com/tillie" id="link3">Tillie</a>]
soup.find(id="link3")
# <a class="sister" href="http://example.com/tillie" id="link3">Tillie</a>
for link in soup.find_all('a'):
  print(link.get('href'))
# http://example.com/elsie
# http://example.com/lacie
# http://example.com/tillie
print(soup.get_text())
# The Dormouse's story
# The Dormouse's story
# ...
```

# Requests for Humans



## Requests - Features: [https://docs.python-requests.org/en/latest/]

- Keep-Alive & Connection Pooling
- International Domains and URLs
- Sessions with Cookie Persistence
- Browser-style SSL Verification
- Automatic Content Decoding
- Basic/Digest Authentication
- Elegant Key/Value Cookies

- Automatic Decompression
- Unicode Response Bodies
- HTTP(S) Proxy Support
- Multipart File Uploads
- Streaming Downloads
- Connection Timeouts
- Chunked Requests
- .netrc Support

#### Requests [https://docs.python-requests.org/en/latest/]

```
>>> r = requests.get('https://api.github.com/user', auth=('user', 'pass'))
>>> r.status code
200
>>> r.headers['content-type']
'application/json; charset=utf8'
>>> r.encoding
'utf-8'
>>> r.text
'{"type":"User"...'
>>> r.json()
{'private_gists': 419, 'total_private_repos': 77, ...}
```

#### Requests Basic Example

```
import requests

if __name__ == '__main__':
    r = requests.get('https://api.github.com/events')
    # for event in r.json():
    # print(event)

r = requests.get('https://docs.python-requests.org/en/latest/user/quickstart/')
    print(r.text[:1000])
```

#### Requests + Beautiful Soup 4 Example

```
import requests
from bs4 import BeautifulSoup
if name == ' main ':
  r = requests.get('https://docs.python-requests.org/en/latest/user/quickstart/')
  # print(r.text[:1000])
  soup = BeautifulSoup(r.text, 'html.parser')
  # print(soup.prettify())
  print("soup.title = ", soup.title)
  print("soup.title.name = ", soup.title.name)
  print("soup.title.string = ", soup.title.string)
  print("soup.title.parent.name = ", soup.title.parent.name)
  print("soup.p = ", soup.p)
  print("soup.a = ", soup.a)
  for link in soup.find_all('a'):
     print(link, "->", link.get('href'))
  print("\nTEXT CONTENT:")
  lines = [line.strip() for line in soup.body.get_text().split("\n") if len(line.strip()) > 0]
  for I in lines:
     print(I)
```

# Problem: Fetch <a href="http://python.org">http://python.org</a> and print all widget texts

Write a program using Resquests and Beautiful Soup 4 (BS4) libraries, with following functionality:

- 1. Using GET method of HTTP protocol, fetch the <a href="http://python.org">http://python.org</a> web page document.
- 2. Parse the web page using BS4 and print the <title> tag content.
- 3. Print the text content of all menus in the <nav> tag of the page.
- 4. Print the alt attribute of the image in the <header> tag section of the page.
- 5. Print the text content of all divisions of class "small-widget" or "medium-widget" in the page



#### Thank's for Your Attention!



Trayan Iliev

IPT – Intellectual Products & Technologies

http://iproduct.org/

https://github.com/iproduct

https://twitter.com/trayaniliev

https://www.facebook.com/IPT.EACAD