



Dispersion Measure Variability in NANOGrav data

David Nice


IPTA 2012, Kiama, NSW

25 June 2012

- I. Overview of DM and dual-frequency measurements
(because I didn't give a student talk last week)
- II. NANOGrav observations & a few pretty plots
(depending on your definition of “pretty”)
- III. Impact on fitting DM at every epoch on timing
(a *very* qualitative discussion)
- IV. Wide-band timing analysis
(what happens next....)
- V. A scary plot
(a reminder that DM variations are just one aspect of our ISM troubles)

- I. Overview of DM and dual-frequency measurements
(because I didn't give a student talk last week)
- II. NANOGrav observations & a few pretty plots
(depending on your definition of “pretty”)
- III. Impact on fitting DM at every epoch on timing
(a *very* qualitative discussion)
- IV. Wide-band timing analysis
(what happens next....)
- V. A scary plot
(a reminder that DM variations are just one aspect of our ISM troubles)

Interstellar Dispersion




column density of electrons: $DM = \int n_e(l) dl$ usual units: pc cm^{-3}

excess delay (in seconds): $t_{\text{delay}}(\text{sec}) = t_f - t_\infty = DM / 2.41 \times 10^{-4} [f(\text{MHz})]^2$


typical delay: $t_{\text{delay}} = 43 \text{ ms}$ for a $DM = 20$ pulsar at 1400 MHz.

a change in DM by 1 part in 10^4 changes the delay by 200 ns at 1400 MHz


$$t_f = t_\infty + \text{DM} / 2.41 \times 10^{-4} [f(\text{MHz})]^2$$



$$t_f = t_\infty + \text{DM} / 2.41 \times 10^{-4} [f(\text{MHz})]^2$$




$$t_f = t_\infty + \text{DM} / 2.41 \times 10^{-4} [f(\text{MHz})]^2$$



- I. Overview of DM and dual-frequency measurements
(because I didn't give a student talk last week)
- II. NANOGrav observations & a few pretty plots
(depending on your definition of “pretty”)
- III. Impact on fitting DM at every epoch on timing
(a *very* qualitative discussion)
- IV. Wide-band timing analysis
(what happens next....)
- V. A scary plot
(a reminder that DM variations are just one aspect of our ISM troubles)

Pulsars We Observe



Under observation since 2005
using ASP/GASP

Millisecond pulsars added to NANOGrav
campaigns starting in ~2009

Millisecond pulsars added to NANOGrav
campaigns starting in ~2011

- ☆ Arecibo
- Green Bank
- ☆ Arecibo
- Green Bank
- ☆ Arecibo
- Green Bank


Demorest et al (2012) data set

arXiv:1201.6641




- 17 Pulsars (8 Arecibo, 10 GBT; 1 overlap)
- 5 years of observations, typically monthly (with some gaps)
- ASP (Arecibo) and GASP (Green Bank) backends
 - 64 MHz software coherent dedispersion, 4 MHz channels, full Stokes
- Dual frequency observations of all but three sources at every epoch
 - Green Bank
 - 800/1400 MHz
 - Arecibo: depends on pulsar spectrum, flux density, scintillation
 - 327/430 MHz
 - 430/1400 MHz
 - 1400/2350 MHz
- Timing analysis (tempo) fits for DM at every epoch in addition to fitting for all other usual parameters (spin, astrometry, binary).


DM for Pulsar 1600-3053




DM for Pulsar 1855+09




DM for Pulsar 1713+0747




DM for Pulsar 1909-3744





DM for Pulsar 2317+1439




Dispersion Measure Variation





Variations in dispersion on small scales are *inevitable* due to the solar wind. Multi-frequency observations at each epoch are *crucial* to removing imprint of these variations from the data.

Twelve-Hour running average solar wind proton speed, density, temperature, and alpha-to-proton ratio over the equivalent portions of two orbits of Ulysses. From McComsas et al. 2003, Geophysical Research Letters, 30: 1517.





Solar Image: SOHO/NASA
Ulysses Orbit Figure: ESA

0030+0451


red:aspfitsreader
blue:psrchive

△ 327 MHz
☆ 430 MHz
□ 800 MHz
○ 1410 MHz
△ 2350 MHz



- I. Overview of DM and dual-frequency measurements
(because I didn't give a student talk last week)
- II. NANOGrav observations & a few pretty plots
(depending on your definition of “pretty”)
- III. Impact on fitting DM at every epoch on timing
(a *very* qualitative discussion)
- IV. Wide-band timing analysis
(what happens next....)
- V. A scary plot
(a reminder that DM variations are just one aspect of our ISM troubles)


- We fit for DM at each epoch within tempo or tempo 2 (“DMX”).
The fit is *simultaneous* with the fit for all other parameters.
- This approach is good *if* the timing model being used by tempo or tempo2 *completely describes* the data (i.e., post-fit residuals truly should be Gaussian).
- If the timing model is incomplete then tempo/tempo2 may mis-adjust DMX offsets in its effort to minimize the weighted residual. Un-modeled (non-white) signals in the residuals can be reduced by this.
- Because low-frequency points are usually weighted more heavily than high-frequency points, the daily post-fit-residuals for low-frequency points tend to be artificially low (see PSR J0030+0451 residuals on previous slide.) Better to use “common mode” residuals.




- Our approach of fitting DM independently at every epoch is absolutely necessary. At our desired level of measurement, DM(t) is not necessarily a smooth function; we must treat it as a “random variable” which must be measured at every epoch.
- As with any measurement, DM(t) can only be measured to finite precision. Uncertainty in DM(t) leads to effectively reduced precision of absolute (infinite frequency) TOAs within timing codes.
- At any given epoch, the inferred DM(t) and the inferred “average infinite frequency TOA” are covariant with each other. This magnifies the effect of uncertainty of DM(t) values.
- To date, we have taken the conservative approach of *not* attempting to take this additional noise into account when placing an upper limit on the GWB. Crudely speaking, the observed pulsar measurements might have:
observed red noise = GWB signal + timing noise + DM-related-noise
Hence:
GWB signal = observed red noise - timing noise - DM-related-noise
In other words, accounting for DM-covariance-noise might (in principle) allow for a reduced upper limit on the GWB signal. (But how to do this??)

- I. Overview of DM and dual-frequency measurements
(because I didn't give a student talk last week)
- II. NANOGrav observations & a few pretty plots
(depending on your definition of “pretty”)
- III. Impact on fitting DM at every epoch on timing
(a *very* qualitative discussion)
- IV. Wide-band timing analysis
(what happens next....)
- V. A scary plot
(a reminder that DM variations are just one aspect of our ISM troubles)



$$t_f = t_\infty + \text{DM} / 2.41 \times 10^{-4} [f(\text{MHz})]^2$$




$$t_f = t_\infty + \text{DM} / 2.41 \times 10^{-4} [f(\text{MHz})]^2$$




GUPPI (GBT), PUPPI (Arecibo)
coherent dedispersion 800 MHz bandwidth



$$t_f = t_\infty + \text{DM} / 2.41 \times 10^{-4} [f(\text{MHz})]^2$$



$$t_f = t_\infty + \text{DM} / 2.41 \times 10^{-4} [f(\text{MHz})]^2$$






Figure: Tim Pennucci

In the works: Broadband timing code

- Profile variation over the band
 - A possible standard profile model: sum of Gaussian components with properties which vary over the band
- Cross correlate standard profile to data
 - Simultaneously fit for time shift *and DM shift*
 - Work in Fourier domain (similar to fftfit)

- I. Overview of DM and dual-frequency measurements
(because I didn't give a student talk last week)
- II. NANOGrav observations & a few pretty plots
(depending on your definition of “pretty”)
- III. Impact on fitting DM at every epoch on timing
(a *very* qualitative discussion)
- IV. Wide-band timing analysis
(what happens next....)
- V. A scary plot
(a reminder that DM variations are just one aspect of our ISM troubles)

DM variations are just one aspect of the corruption of pulsar signals by the ISM.

Hemberger & Stinebring 2008
(One of the scariest plots in the history
of pulsar timing!)




FIG. 2.—Scattering delay, τ_{ss} , as a function of time. The four frequencies were offset in average delay because of the frequency dependence of scattering. They have been aligned as shown here by performing a least-squares fit to a one-parameter function of the form $\tau_{ss} \propto \nu^{-\alpha}$. The best-fit value was $\alpha = 3.6 \pm 0.2$. The standard deviation for all the data is 100 ns. All delays have been referenced to 1380 MHz.

End of talk...

... beginning of discussion.

- I. Overview of DM and dual-frequency measurements
(because I didn't give a student talk last week)
- II. NANOGrav observations & a few pretty plots
(depending on your definition of "pretty")
- III. Impact on fitting DM at every epoch on timing
(a *very* qualitative discussion)
- IV. Wide-band timing analysis
(what happens next....)
- V. A scary plot
(a reminder that DM variations are just one aspect of our ISM troubles)