EXPERIMENT - 3

AIM: Create an Employee–Department–Project schema. Insert at least 30 employees across 5 departments and 8 projects. Write SQL queries demonstrating selection, projection, aggregates, GROUP BY, HAVING, CASE expressions, and ORDER BY.

SOURCE CODE:

```
CREATE TABLE Department (
    dept_id INT PRIMARY KEY,
    dept_name VARCHAR(50)
);

CREATE TABLE Project (
    project_id INT PRIMARY KEY,
    project_name VARCHAR(50),
    dept_id INT,
    FOREIGN KEY (dept_id) REFERENCES Department(dept_id)
);

CREATE TABLE Employee (
    emp_id INT PRIMARY KEY,
    emp_name VARCHAR(50),
    dept_id INT,
    project_id INT,
    salary DECIMAL(10,2), city
    VARCHAR(50),
    FOREIGN KEY (dept_id) REFERENCES Department(dept_id), FOREIGN
    KEY (project_id) REFERENCES Project(project_id)
);

INSERT INTO Department VALUES
(1, 'HR'), (2, 'Finance'), (3, 'IT'), (4, 'Marketing'), (5, 'Operations');

INSERT INTO Project VALUES
(101, 'Recruitment System', 1), (102, 'Payroll Automation', 2),
(103, 'Cybersecurity Upgrade', 3), (104, 'Website Revamp', 3),
(105, 'Ad Campaign', 4), (106, 'Market Research', 4),
(107, 'Logistics Optimization', 5), (108, 'Inventory System', 5);

INSERT INTO Employee VALUES
(1, 'Alice', 1, 101, 45000, 'Delhi'),
(2, 'Bob', 1, 101, 42000, 'Mumbai'),
(3, 'Charlie', 1, 101, 47000, 'Pune'),
(4, 'David', 2, 102, 55000, 'Delhi'),
(5, 'Eva', 2, 102, 60000, 'Lucknow'),
```

```
(6, 'Frank', 2, 102, 52000, 'Chennai'),
(7, 'Grace', 3, 103, 70000, 'Bangalore'),
(8, 'Hannah', 3, 103, 68000, 'Hyderabad'),
(9, 'Ian', 3, 104, 72000, 'Delhi'),
(10, 'Jack', 3, 104, 65000, 'Pune'),
(11, 'Karen', 3, 104, 64000, 'Mumbai'),
(12, 'Leo', 4, 105, 48000, 'Delhi'),
(13, 'Mia', 4, 105, 50000, 'Lucknow'),
(14, 'Nina', 4, 106, 51000, 'Chennai'),
(15, 'Oscar', 4, 106, 53000, 'Delhi'),
(16, 'Paul', 5, 107, 56000, 'Hyderabad'),
(17, 'Quinn', 5, 107, 57000, 'Bangalore'),
(18, 'Rita', 5, 107, 59000, 'Delhi'),
(19, 'Sam', 5, 108, 60000, 'Lucknow'),
(20, 'Tina', 5, 108, 61000, 'Mumbai'),
(21, 'Uma', 5, 108, 62000, 'Chennai'),
(22, 'Victor', 2, 102, 53000, 'Delhi'),
(23, 'Wendy', 2, 102, 54000, 'Hyderabad'),
(24, 'Xavier', 3, 103, 71000, 'Bangalore'),
(25, 'Yara', 3, 104, 66000, 'Lucknow'),
(26, 'Zane', 4, 105, 49000, 'Delhi'),
(27, 'Aditi', 4, 106, 52000, 'Mumbai'),
(28, 'Bhavya', 1, 101, 46000, 'Chennai'),
(29, 'Chetan', 1, 101, 43000, 'Lucknow'),
(30, 'Devika', 5, 107, 58000, 'Delhi');

SELECT *
FROM Employee WHERE
city = 'Delhi';

SELECT emp_name, salary
FROM Employee;

SELECT dept_id, AVG(salary) AS avg_salary FROM
Employee
GROUP BY dept_id;

SELECT dept_id, COUNT(*) AS num_employees
FROM Employee
GROUP BY dept_id HAVING
COUNT(*) > 5;
```

```
SELECT emp_name, salary,
CASE
        WHEN salary < 50000 THEN 'Low'
        WHEN salary BETWEEN 50000 AND 60000 THEN 'Medium' ELSE
        'High'
    END AS salary_category

FROM Employee;
SELECT emp_name, dept_id, salary
FROM Employee
ORDER BY salary DESC;
```

OUTPUT :

