

## Harcourt HSPIN-Standard Length, Standard Range

| Code           | A       | B        | E     | F     | G-Thread |
|----------------|---------|----------|-------|-------|----------|
| HSPIN-10-.115  | 0.115g6 | 10mm g6  | 0.65" | 1.10" | M3       |
| HSPIN-10-.147  | .147 g6 | 10mm g6  | 0.65" | 1.10" | M4       |
| HSPIN-10-.157  | .157 g6 | 10mm g6  | 0.65" | 1.10" | M4       |
| HSPIN-10-.181  | .181 g6 | 10mm g6  | 0.65" | 1.10" | M4       |
| HSPIN-10-.190  | .190 g6 | 10mm g6  | 0.65" | 1.10" | M4       |
| HSPIN-12-.125  | .125 g6 | 12mm g6  | 0.65" | 1.10" | M3       |
| HSPIN-12-.147  | .147 g6 | 12mm g6  | 0.65" | 1.10" | M4       |
| HSPIN-12-.157  | .157 g6 | 12mm g6  | 0.65" | 1.10" | M4       |
| HSPIN-12-.181  | .181 g6 | 12mm g6  | 0.65" | 1.10" | M4       |
| HSPIN-12-.250  | .250 g6 | 12mm g6  | 0.65" | 1.10" | M4       |
| HSPIN-12-.234  | .234 g6 | 12mm g6  | 0.65" | 1.10" | M5       |
| HSPIN-.5-.240  | .240 g6 | .500" g6 | 0.65" | 1.10" | M6       |
| HSPIN-.5-.250  | .250 g6 | .500" g6 | 0.65" | 1.10" | M6       |
| HSPIN-.5-.3125 | .3125g6 | .500" g6 | 0.65" | 1.10" | M8       |