

Computer Programming

Irwan Prasetya Gunawan, Ph.D

Sampoerna University
ipg@ieee.org

03: Branching: selection, if-else, while, switch

Version: July 9, 2019

Contents

00: Introduction: Overview, Code Building, IDE
01: Basic: Elements of C Program, Identifiers, Data Types
02: Branching: Conditional expressions, logical operators
03: Branching: selection, if-else, while, switch
04: Loops: repetition, for, do-while
05: Increment/decrement, nested loops, loop tracing
06: Functions: declaration, definitions, calls
07: Pointers and addresses: pass by reference, pointer arithmetic
08: File I/O
09: Arrays: declarations, initialization, search, sort
10: Strings
11: Recursion
12: Structures
13: Applications
14: Revisions

C Statements

- ◆ In the most general sense, a statement is a part of your program that can be executed.
- ◆ An expression is a statement.

```
a=a+1;
```

```
a--;
```

- ◆ A function call is also a statement.

```
printf("%d",a);
```

- ◆ Other statements
- ◆ C is a free form language, so you may type the statements in any style you feel comfortable:

```
a=
```

```
a+
```

```
1;a--;
```

line breaks can be anywhere

Compound Statements

- ◆ Sequences of statements can be combined into one with {...}

- ◆ Much like Java:

```
{  
    printf ("Hello, ");  
    printf ("world! \n");  
}
```

- ◆ The C compiler treats the collection of these statements like they are a single statement.

C Statements

Some Suggestions

- ◆ DO: stay consistent with how you use whitespace
- ◆ DO: put block braces on their own line.
 - This makes the code easier to read.
- ◆ DO: line up block braces so that it is easy to find the beginning and end of a block.
- ◆ AVOID: spreading a single statement across multiple lines if there is no need.
 - Try to keep it on one line.

The if Statement (1)

◆ Form 1:

```
if (expression)
    statement1;
next statement;
```

Execute statement1
if expression is non-zero
(i.e., it does not have to be exactly 1)

◆ Form 2:

```
if (expression)
    statement1;
else
    statement2;
next statement;
```

◆ Form 3:

```
if (expression)
    statement1;
else if (expression)
    statement2;
else
    statement3;
next statement;
```

The if Statement (2)

◆ For Example:

```
#include <stdio.h>
int x,y;
int main ()
{
    printf ("\nInput an integer value for x: ");
    scanf ("%d", &x);
    printf ("\nInput an integer value for y: ");
    scanf ("%d",&y);
    if (x==y)
        printf ("x is equal to y\n");
    else if (x > y)
        printf ("x is greater than y\n");
    else
        printf ("x is smaller than y\n");
    return 0;
}
```

The for Statement (1)

- ◆ The most important looping structure in C.
- ◆ Generic Form:

*for (initial ; condition ; increment)
statement*

- ◆ *initial*, *condition*, and *increment* are C expressions.
- ◆ For loops are executed as follows:
 1. *initial* is evaluated. Usually an assignment statement.
 2. *condition* is evaluated. Usually a relational expression.
 3. If *condition* is false (i.e. 0), fall out of the loop (go to step 6.)
 4. If *condition* is true (i.e. nonzero), execute *statement*
 5. Execute *increment* and go back to step 2.
 6. Next statement

The for Statement (2)

For statement examples

```
#include <stdio.h>
```

```
int main () {
```

```
    int count,x,y;
```

```
    int ctd;
```

```
    /* 1. simple counted for loop */
```

```
    for (count =1; count <=20; count++)
```

```
        printf ("%d\n", count);
```

```
    /* 2. for loop counting backwards */
```

```
    for (count = 100; count >0; count--) {
```

```
        x*=count;
```

```
        printf("count=%d x=%d\n", count,x);
```

```
    }
```

```
    /* 3. for loop counting by 5's */
```

```
    for (count=0; count<1000; count += 5)
```

```
        v=v+count;
```

```
    /* 4. initialization outside of loop */
```

```
    count = 1;
```

```
    for ( ; count < 1000; count++)
```

```
        printf("%d ", count);
```

```
    /* 5. very little need be in the for */
```

```
    count=1; ctd=1;
```

```
    for ( ; ctd; ) {
```

```
        printf("%d ", count);
```

```
        count++; ctd=count<1000;
```

```
    }
```

```
    /* 6. compound statements for  
    initialization and increment */
```

```
    for (x=0, y=100; x<y; x++, y--) {
```

```
        printf("%d %d\n", x,y);
```

```
    }
```

```
    return 0;
```

```
}
```

The for Statement (3)

◆ Nesting for Statements

- for statements (and any other C statement) can go inside the loop of a for statement.
- For example:

```
#include <stdio.h>
int main( ) {
    int rows=10, columns=20;
    int r, c;
    for ( r=rows ; r>0 ; r--)
    {
        for (c = columns; c>0; c--)
            printf ("X");
        printf ("\n");
    }
}
```

The while Statement

- ◆ Generic Form

while (condition)
statement

- ◆ Executes as expected:

1. condition is evaluated
2. If condition is false (i.e. 0), loop is exited (go to step 5)
3. If condition is true (i.e. nonzero), statement is executed
4. Go to step 1
5. Next statement

- ◆ Note:

- for (; condition ;) stmt; is equivalent to while (condition) stmt;
- for (exp1; exp2; exp3) stmt; is equivalent to exp1; while(exp2) { stmt; exp3; }

The do ... while Loop (1)

- ◆ Generic Form:

```
do  
    statement  
while (condition);
```

- ◆ Standard repeat until loop

- ❖ Like a **while** loop, but with **condition** test at bottom.
- ❖ Always executes at least once.

- ◆ The semantics of **do...while**:

1. Execute **statement**
2. Evaluate **condition**
3. If **condition** is true go to step 1
4. Next statement

The do ... while Loop (2)

```
#include <stdio.h>
int get_menu_choice (void);
main()
{
    int choice;
    do
    {
        choice = get_menu_choice ();
        printf ("You chose %d\n",choice);
    } while(choice!=4);
    return 0;
}
```

```
/* simple function get_menu_choice */

int get_menu_choice (void)
{
    int selection = 0;
    do {
        printf ("\n");
        printf ("\n1 - Add a Record ");
        printf ("\n2 - Change a Record ");
        printf ("\n3 - Delete a Record ");
        printf ("\n4 - Quit ");
        printf ("\n\nEnter a selection: ");
        scanf ("%d", &selection);
    } while ( selection<1 || selection>4);
    return selection;
}
```

break and continue

- ◆ The flow of control in any loop can be changed through the use of the **break** and **continue** commands.
- ◆ The **break** command exits the loop immediately.
 - Useful for stopping on conditions not controlled in the loop condition.
 - For example:

```
for (x=0; x<10000; x++) {  
    if ( x*x % 5==1) break;  
    ... do some more work ...  
}
```

- Loop terminates if $x*x \% 5 == 1$

- ◆ The **continue** command causes the next iteration of the loop to be started immediately.
 - For example:

```
for (x=0; x<10000; x++) {  
    if (x*x % 5 == 1) continue;  
    printf( "%d ", 1/ (x*x % 5 - 1) );  
}
```

- Don't execute loop when $x*x \% 5 == 1$ (and avoid division by 0)

Example: for and break Together

```
const int mycard=3;
int guess;
for(;;)
{
    printf("Guess my card:");
    scanf("%d",&guess);
    if(guess==mycard)
    {
        printf("Good guess!\n");
        break;
    }
    else
        printf("Try again.\n");
}
```

The notation for(;;) is used to create an infinite for loop. while(1) creates an infinite while loop instead.

To get out of an infinite loop like this one, we have to use the break statement.

switch Statement

- ◆ Switch statement is used to do “multiple choices”.
- ◆ Generic form:

```
switch(expression)
{
    case constant_expr1 : statements
    case constant_expr2 : statements
    ...
    case constant_exprk : statements
    default : statements
}
```

1. `expression` is evaluated.
2. The program jumps to the corresponding `constant_expr`.
3. All statements after the `constant_expr` are executed until a `break` (or `goto`, `return`) statement is encountered.

Example: switch Statement

```
int a;
printf("1. Open file..\n");
printf("2. Save file..\n");
printf("3. Save as..\n");
printf("4. Quit..\n");
printf("Your choice:");
scanf("%d", &a);
if(a==1)
    open_file();
else if(a==2)
    save_file();
else if(a==3)
    save_as();
else if(a==4) return 0;
else return 1;
```

```
int a;
printf("1. Open file..\n");
printf("2. Save file..\n");
printf("3. Save as..\n");
printf("4. Quit..\n");
printf("Your choice:");
scanf("%d", &a);
switch(a)
{
    case 1: open_file();break;
    case 2: save_file();break;
    case 3: save_as();break;
    case 4: return 0;
    default: return 1;
}
```

Jumping Out of Nested Loops -- goto

- ◆ The **goto** statement will jump to any point of your program.
- ◆ Use only if it is absolutely necessary (**never in this course**)

```
for(;;)
```

```
{
```

```
.....
```

```
while(...)
```

```
{
```

```
    switch(...)
```

```
    {
```

```
        .....
```

```
        case ... : goto finished;  /* finished is a label */
```

```
    }
```

```
}
```

```
}
```

```
finished:  /* Jumped out from the nested loops */
```

Never jump into a loop!

Never jump backward!

References I

- [1] MinGW Installation Notes Wiki Page, May 2007. URL http://www.mingw.org/wiki/Getting_Started. Accessed 18 June 2019.
- [2] MSYS Wiki Page, January 2008. URL <http://www.mingw.org/wiki/MSYS>. Accessed 18 June 2019.
- [3] Eclipse Foundation. Eclipse Project. URL <https://www.eclipse.org/>.
- [4] Chua Hock-Chuan. Yet another insignificant ... programming notes, March 2019. URL <https://www3.ntu.edu.sg/home/ehchua/programming/index.html>. Accessed 18 June 2019.
- [5] Marc Moreno Maza. Lecture notes: Software tools and systems programming. University of Western Ontario, 2011.
- [6] Daniel Weller and Sharat Chikkerur. 6.087 Practical Programming in C. Massachusetts Institute of Technology: MIT OpenCourseWare, January 2010. URL <https://ocw.mit.edu>. License: Creative Commons BY-NC-SA.